



JUL 14 2016

Mr. Zach Dransoff
California Resources Production Corporation
9600 Ming Ave.
Bakersfield, CA 93314

**Re: Notice of Final Action - Title V Permit Renewal
District Facility # S-1326
Project # 1153214**

Dear Mr. Dransoff:

The District has issued the Final Renewed Title V Permit for California Resources Production Corporation. The preliminary decision for this project was made on 5/17/16. No comments were received subsequent to the District preliminary decision.

The public notice for issuance of the Final Title V Permit will be published approximately three days from the date of this letter.

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Leonard Scandura, Permit Services Manager, at (661) 392-5500.

Sincerely,


for Arnaud Marjollet
Director of Permit Services

Enclosures

cc: Tung Le, CARB (w/enclosure) via email
cc: Gerardo C. Rios, EPA (w/enclosure) via email

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585



Facility # S-1326
CALIFORNIA RESOURCES PRODUCTION CORP
11109 RIVER RUN BLVD
BAKERSFIELD, CA 93311

Notice of Permit Issuance

The enclosed permit unit requirements authorize the operation of the equipment as described. These permit unit requirements supersede any and all previous permits for the specified equipment.* Please insert these documents into the Facility Permit to Operate, and post copies on or near the equipment as required by District Rule 2010.

Please contact any of our Small Business Assistance (SBA) staff at the numbers below if you have any questions:

Modesto:	(209) 557-6446
Fresno:	(559) 230-5888
Bakersfield:	(661) 392-5665

*Failure to comply with the permit unit requirements may result in enforcement action.

Seyed Sadredin

Executive Director/Air Pollution Control Officer

Northern Region

4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)

1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region

34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585



Permit to Operate

FACILITY: S-1326

EXPIRATION DATE: 03/31/2021

LEGAL OWNER OR OPERATOR:
MAILING ADDRESS:

CALIFORNIA RESOURCES PRODUCTION CORP
11109 RIVER RUN BLVD
BAKERSFIELD, CA 93311

FACILITY LOCATION:

HEAVY OIL CENTRAL STATIONARY SOURCE
KERN COUNTY, CA

FACILITY DESCRIPTION:

OIL AND NATURAL GAS PRODUCTION

The Facility's Permit to Operate may include Facility-wide Requirements as well as requirements that apply to specific permit units.

This Permit to Operate remains valid through the permit expiration date listed above, subject to payment of annual permit fees and compliance with permit conditions and all applicable local, state, and federal regulations. This permit is valid only at the location specified above, and becomes void upon any transfer of ownership or location. Any modification of the equipment or operation, as defined in District Rule 2201, will require prior District approval. This permit shall be posted as prescribed in District Rule 2010.

Seyed Sadredin
Executive Director / APCO

Arnaud Marjollet
Director of Permit Services

San Joaquin Valley Air Pollution Control District

FACILITY: S-1326-0-3

EXPIRATION DATE: 03/31/2021

FACILITY-WIDE REQUIREMENTS

1. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
2. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
3. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.9.1 and 9.13.1] Federally Enforceable Through Title V Permit
6. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: CALIFORNIA RESOURCES PRODUCTION CORP
Location: HEAVY OIL CENTRAL STATIONARY SOURCE, KERN COUNTY, CA
S-1326-0-3 : Jul 13 2016 8:19AM - VELASCOA

10. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit
11. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
12. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
13. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
14. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
15. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
16. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
17. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
18. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
19. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
20. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
21. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit
22. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

23. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in Table of Standards 1 effective until 12/30/10 or Table of Standards 2 effective on and after 1/1/11 of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
24. All VOC-containing materials subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
25. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
26. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
27. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
28. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit
29. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8021 and 8011] Federally Enforceable Through Title V Permit
30. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8031 and 8011] Federally Enforceable Through Title V Permit
31. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8041 and 8011] Federally Enforceable Through Title V Permit
32. Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8051 and 8011] Federally Enforceable Through Title V Permit
33. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8061 and 8011] Federally Enforceable Through Title V Permit
34. Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rules 8071 and 8011] Federally Enforceable Through Title V Permit
35. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

36. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
37. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
38. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
39. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), Rule 111 (Kern, Tulare, Kings), and Rule 202 (Fresno, Kern, Tulare, Kings, Madera, Stanislaus, Merced, San Joaquin). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601 (12/17/09); 8021 (8/19/2004); 8031 (8/19/2004); 8041 (8/19/2004); 8051 (8/19/2004); 8061 (8/19/2004); and 8071 (9/16/2004). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
42. Should the facility, as defined in 40 CFR 68.3, become subject to Part 68, then the owner or operator shall submit a risk management plan (RMP) by the date specified in 40 CFR 68.10. The facility shall certify compliance as part of the annual certification as required by 40 CFR part 70. [40 CFR 68] Federally Enforceable Through Title V Permit
43. On August 31, 2001, the initial Title V permit was issued, the reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. This reports are due within 30 days of the end of reporting period. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-9-24

EXPIRATION DATE: 03/31/2021

SECTION: SE23 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

62.5 MMBTU/HR NATURAL GAS-FIRED STRUTHERS STEAM GENERATOR WITH A NORTH AMERICAN MAGNA-FLAME G-LE ULTRA LOW NOX BURNER AND A FLUE GAS RECIRCULATION (FGR) SYSTEM - DIS# 21928-82

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. The unit shall only be fired on PUC-quality natural gas and scrubbed TEOR and TVR gas from S-1326-26, '-27, '-28, '-35 and '-263 with a sulfur content no greater than 1 gr S/100 scf. [District Rules 2201, 4301, 4320, 4406, and 4801] Federally Enforceable Through Title V Permit
4. Emission rates shall not exceed: PM10: 0.003 lb/MMBtu, VOC: 0.0055 lb/MMBtu, NOx (as NO2): 7 ppmvd NOx @ 3% O2, or CO: 75 ppmv @ 3% O2. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
5. Permittee shall test annually the sulfur content of the fuel gas combusted in steam generator and make test results readily available for District inspection. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit
6. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. Unless otherwise specified in the Permit to Operate, no determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
8. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
9. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
10. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The following test methods shall be used: NO_x (ppmv) - EPA Method 7E or ARB Method 100, NO_x (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, stack gas moisture content - EPA Method 4, stack gas velocities - EPA Method 2, fuel gas sulfur content - ASTM D1072, ASTM 3031, ASTM 4084, ASTM D3246, ASTM D6228 (GC-FPD) or double GC for H₂S and mercaptans. [District Rules 1081, 4305, 4306, 6.2, 4320, and 4351] Federally Enforceable Through Title V Permit
12. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. The permittee shall monitor and record the stack concentration of NO_x, CO, and O₂ at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
14. If either the NO_x or CO concentrations corrected to 3% O₂, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
15. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
16. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
17. Permittee shall maintain daily records of the type and quantity of fuel combusted by the steam generator. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
18. The permittee shall maintain records of: (1) the date and time of NO_x, CO, and O₂ measurements, (2) the O₂ concentration in percent and the measured NO_x and CO concentrations corrected to 3% O₂, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
19. Permittee shall maintain records of fuel gas sulfur compound measurements. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
20. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 1070, 4305, 4306, 4320, and 40 CFR 60.48c (i)] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-26-25

EXPIRATION DATE: 03/31/2021

SECTION: NE23 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

THERMALLY ENHANCED OIL RECOVERY OPERATION WITH WELL VENT VAPOR CONTROL SYSTEM SERVING 120 STEAM ENHANCED WELLS, INCLUDING SULFA-TREAT SYSTEM, GAS TRAPS, COLLECTION PIPING, VAPOR COMPRESSOR WITH ELECTRIC MOTOR, AND PIPING TO FIELD FUEL GAS SYSTEM, DOGGR DISPOSAL WELL, AND FLARE (FANO)

PERMIT UNIT REQUIREMENTS

1. TEOR operation shall include sulfatreat system, gas traps, collection piping, vapor compressor with electric motor, piping to field fuel gas system, piping to steam generators S-1326-9, '-294, '-314, '-337, '-338, '-385, '-390, '-391, '-392, '-400, '-401, and '-419 through '-425, DOGGR disposal well and flare (Fano). [District Rule 2201] Federally Enforceable Through Title V Permit
2. Wells may be operated with closed casing vents or be vented to vapor control system. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Fluids produced from wells with closed vents shall be introduced only to production equipment served by vapor control system listed on tank S-1326-46 which is 99% efficient. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The crude oil production from wells associated with this permit unit shall not lie within 1000 feet of an air injection well used for in-situ combustion. [District Rule 4407, 2.0, 3.4, and 3.5] Federally Enforceable Through Title V Permit
5. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401, 5.0 (as amended January 15, 1998). [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
6. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(as amended December 16, 1993). [District Rule 1081] Federally Enforceable Through Title V Permit
7. The operator shall maintain monitoring records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit
8. The uncontrolled VOC emissions from any well vent shall be reduced by at least 99 percent by weight or, if several steam-enhanced crude oil production well vents are connected to a vapor collection and control system, total uncontrolled VOC emissions shall be reduced by at least 99 percent. This requirement does not apply to cyclic wells located on contiguous and adjacent oil production properties with less than 10 cyclic wells owned by or under the control of a company. [District Rule 4401, 5.1 and 5.2] Federally Enforceable Through Title V Permit
9. For cyclic wells located on properties with less than 10 cyclic wells and owned by a company, the uncontrolled VOC emissions from any well vent or system of well vents connected to a single control device shall be reduced by at least 50 percent. Properties shall include contiguous and adjacent oil production properties owned by or under control of the company. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit
10. Total number of leaks from the vapor collection and control system, including condensate handling, shall not exceed the number as allowed by Rule 4401 (as amended January 15, 1998) at any one time. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Operator shall affix a readily visible tag bearing the date on which a leak is detected. The tag shall remain in place until the leaking component is repaired. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit
12. Operator shall repair each leak within 15 days of detection. The APCO may grant a 10 day extension if the operator demonstrates that the necessary and sufficient actions have and are being taken to correct the leak. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit
13. Operator shall maintain all components of a well vent vapor collection and control system in good repair. Components of the well vent vapor collection and control system shall include all piping, valves, fittings, pumps, compressors, tanks, etc. used to collect, control, store, or dispose of VOC condensate or non-condensable VOCs and which is prior to any blending of VOC condensate with crude oil or blending of non-condensable VOCs with gases to be used as a fuel. [District Rule 4401, 5.3 and 5.3.2] Federally Enforceable Through Title V Permit
14. Annual control efficiency compliance tests shall be performed on all vapor collection and control systems used to control emissions from steam-enhanced crude oil production wells. Testing shall be performed by source tester certified by the California Air Resource Board (CARB) certified contractors during June, July, August or September of each year if the system's control efficiency is dependent upon ambient air temperature. The APCO may waive the requirements of this condition if the vapor control system does not exhaust to atmosphere or if all uncondensed VOC emissions collected by a vapor collection and control system are burned in fuel burning equipment or in a smokeless open flare and the source's Operating Permit contains adequate periodic monitoring to ensure the source meets 99% control efficiency. [District Rule 4401, 5.1, 5.2 and 6.2.1] Federally Enforceable Through Title V Permit
15. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit
16. The permittee shall perform leak inspections at least annually, using a portable hydrocarbon detection instrument in accordance with USEPA Method 21. [District Rules 2520, 9.3.2 and 4401, 6.3.3] Federally Enforceable Through Title V Permit
17. Compliance with permit conditions in the Title V permit shall be deemed compliance with Kern County Rule 108.1. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
18. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4401 (Amended January 15, 1998), excluding sections 5.1 and 5.2 for control systems which have been waived from complying with the requirement of section 6.2.1. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
19. The requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
20. Permittee shall maintain with the permit a current listing of all steam enhanced wells connected to the casing vent control system and shall make such listing readily available for District inspection upon request. [District Rule 4401] Federally Enforceable Through Title V Permit
21. Sulfur content of scrubbed TEOR gas and flare pilot gas shall not exceed 1 gr/100scf. [District Rule 2201] Federally Enforceable Through Title V Permit
22. The well vent vapors and tank vapors from vapor collection systems #S-1326-46 shall vent only to existing otherwise permit exempt combustion equipment, DOGGR approved injection wells, 2.9 MMBtu/hr waste gas flare, or steam generators S-1326-9, '-294, '-314, '-337, '-338, '-385, '-390, '-391, '-392, '-400, '-401, and '-419 through '-425. [District Rule 2201] Federally Enforceable Through Title V Permit
23. Flare shall be used exclusively for incineration of vapors from this TEOR control system and tank vapor control systems #S-1326-46. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

24. Collected liquids shall be piped only to vapor controlled tanks. [District Rule 2201] Federally Enforceable Through Title V Permit
25. VOC content of well vent vapor gas shall not exceed 10% by weight. If the VOC content of the well vent vapor gas is less than 10% by weight for 8 consecutive quarterly samplings per District approved plan, sampling frequency shall only be required annually. Representative samples shall be collected during periods of normal operation and not be within 48 hours after routine maintenance or repair. Records of test shall be maintained for a period of five years and be made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
26. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.5] Federally Enforceable Through Title V Permit
27. Emissions rates shall not exceed any of the following: VOC: 0.063 lb/MMBtu; NOx: 0.068 lb/MMBtu; PM10: 0.008 lb/MMBtu; and CO: 0.37 lb/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
28. The higher heating value of the flared gas shall be monitored at least quarterly. Measured higher heating value and quantity of gas flared shall be used to determine compliance with heat input limits. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
29. Permittee shall test annually the sulfur content of casing gas combusted in permit exempt equipment using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
30. The flare shall be operated according to the manufacturer's specifications, a copy of which shall be maintained on site. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
31. If this flare requires a pilot flame, then the flare shall be operated with a flame present at all times, and kept in operation when emissions may be vented to it. The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
32. Permittee shall maintain daily records of pilot gas and TEOR gas flared and shall make such records readily available for District inspection for a period of five years. [District Rule 2520, 9.4.2 and District Rule 1070] Federally Enforceable Through Title V Permit
33. This flare shall be inspected every two weeks while in operation for visible emissions. If visible emissions are observed, corrective action shall be taken. If visible emissions continue, an EPA Method 9 test shall be conducted within 72 hours. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
34. This flare shall not be used as a leak control device as described in Rule 4403, 5.3.1, nor as a control device for any permit unit subject to NSPS, without modification of permit requirements to address 40 CFR 60.18. [District Rule 2520, 9.3.3] Federally Enforceable Through Title V Permit
35. Sulfa Treat equipment shall be purged with natural gas, inert gas, or air prior to opening any vessel, filter, pipeline or connection to prevent sulfur compound emissions. [District Rule 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-27-22

EXPIRATION DATE: 03/31/2021

SECTION: 02 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

THERMALLY ENHANCED OIL RECOVERY (TEOR) OPERATION WITH WELL VENT VAPOR CONTROL SYSTEM SERVING UP TO 100 STEAM ENHANCED WELLS INCLUDING: GAS LIQUID SEPARATORS, COMPRESSOR, CONDENSATE HANDLING AND 2.9 MMBTU/HR AIR ASSISTED FLARE (SECTION 2 EAST CVR)

PERMIT UNIT REQUIREMENTS

1. Wells may be operated with closed casing vents or be vented to vapor control system. [District Rule 2201] Federally Enforceable Through Title V Permit
2. TEOR operation (Section 2 East CVR) shall include gas liquid separator, compressor, condensate handling equipment, 2.9 MMBtu/hr McGill, #1011-2, flare equipped with 2 in. dia. burner tip, 1/2 hp air assist blower, and K/O drum at flare base and vapor piping from TEOR system S-1326-28 . [District Rule 2201] Federally Enforceable Through Title V Permit
3. The well vent vapors shall vent only to 2.9 MMBtu/hr waste gas flare or steam generators S-1326-9, '-294, '-314, '-337, '-338, '-385, '-390, '-391, '-392, '-400, '-401, and '-419 through '-425. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Fluids produced from wells with closed vents shall be introduced only to production equipment served by vapor control system listed on tank S-1326-201 which is 99% efficient. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The crude oil production from wells associated with this permit unit shall not lie within 1000 feet of an air injection well used for in-situ combustion. [District Rule 4407, 2.0, 3.4, and 3.5] Federally Enforceable Through Title V Permit
6. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401, 5.0 (as amended January 15, 1998). [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
7. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(as amended December 16, 1993). [District Rule 1081] Federally Enforceable Through Title V Permit
8. The operator shall maintain monitoring records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit
9. The uncontrolled VOC emissions from any well vent shall be reduced by at least 99 percent by weight or, if several steam-enhanced crude oil production well vents are connected to a vapor collection and control system, total uncontrolled VOC emissions shall be reduced by at least 99 percent. This requirement does not apply to cyclic wells located on contiguous and adjacent oil production properties with less than 10 cyclic wells owned by or under the control of a company. [District Rule 4401, 5.1 and 5.2] Federally Enforceable Through Title V Permit
10. For cyclic wells located on properties with less than 10 cyclic wells and owned by a company, the uncontrolled VOC emissions from any well vent or system of well vents connected to a single control device shall be reduced by at least 50 percent. Properties shall include contiguous and adjacent oil production properties owned by or under control of the company. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Total number of leaks from the vapor collection and control system, including condensate handling, shall not exceed the number as allowed by Rule 4401 (as amended January 15, 1998) at any one time. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit
12. Operator shall affix a readily visible tag bearing the date on which a leak is detected. The tag shall remain in place until the leaking component is repaired. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit
13. Operator shall repair each leak within 15 days of detection. The APCO may grant a 10 day extension if the operator demonstrates that the necessary and sufficient actions have and are being taken to correct the leak. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit
14. Operator shall maintain all components of a well vent vapor collection and control system in good repair. Components of the well vent vapor collection and control system shall include all piping, valves, fittings, pumps, compressors, tanks, etc. used to collect, control, store, or dispose of VOC condensate or non-condensable VOCs and which is prior to any blending of VOC condensate with crude oil or blending of non-condensable VOCs with gases to be used as a fuel. [District Rule 4401, 5.3 and 5.3.2] Federally Enforceable Through Title V Permit
15. Annual control efficiency compliance tests shall be performed on all vapor collection and control systems used to control emissions from steam-enhanced crude oil production wells. Testing shall be performed by source tester certified by the California Air Resource Board (CARB) certified contractors during June, July, August or September of each year if the system's control efficiency is dependent upon ambient air temperature. The APCO may waive the requirements of this condition if the vapor control system does not exhaust to atmosphere or if all uncondensed VOC emissions collected by a vapor collection and control system are burned in fuel burning equipment or in a smokeless open flare and the source's Operating Permit contains adequate periodic monitoring to ensure the source meets 99% control efficiency. [District Rule 4401, 5.1, 5.2 and 6.2.1] Federally Enforceable Through Title V Permit
16. The control efficiency, measured and calculated as carbon, of the vapor collection and control system used to control VOC emissions from steam enhanced crude oil production well shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit
17. The source shall perform leak inspections at least annually, using a portable hydrocarbon detection instrument in accordance with USEPA Method 21. [District Rules 2520, 9.3.2 and 4401, 6.3.3] Federally Enforceable Through Title V Permit
18. Permittee shall maintain with the permit a current listing of all steam enhanced wells connected to the casing vent control system and shall make such listing readily available for District inspection upon request. [District Rule 4401, 6.6] Federally Enforceable Through Title V Permit
19. Compliance with permit conditions in the Title V permit shall be deemed compliance with Kern County Rule 108.1. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
20. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4401 (Amended January 15, 1998), excluding sections 5.1 and 5.2 for control systems which have been waived from complying with the requirement of section 6.2.1. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
21. The requirements of District Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit because it is not an in situ combustion well vent. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
22. Flare Visible emissions shall not exceed 1/4 Ringelmann. [District Rule 2201] Federally Enforceable Through Title V Permit
23. Sulfur content of scrubbed TEOR gas and flare pilot gas shall not exceed 1 gr/100scf. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

24. All well vent gas shall be scrubbed prior to incineration in 2.9 MMBtu/hr waste gas flare or steam generators S-1326-9, '-294, '-314, '-337, '-338, '-385, '-390, '-391, '-392, '-400, '-401, and '-419 through '-425. [District Rule 2201] Federally Enforceable Through Title V Permit
25. Emission rates for flare shall not exceed any of the following limits: 0.008 lb-PM10/MMBtu, 0.068 lb-NOx/MMBtu (as NO2), 0.063 lb-VOC/MMBtu, or 0.37 lb-CO/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
26. The higher heating value of the flared gas shall be monitored at least quarterly. Measured higher heating value and quantity of gas flared shall be used to determine compliance with heat input limits. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
27. VOC content of well vent vapor gas shall not exceed 10% by weight. If the VOC content of the well vent vapor gas is less than 10% by weight for 8 consecutive quarterly samplings per District approved plan, sampling frequency shall only be required annually. Representative samples shall be collected during periods of normal operation and not be within 48 hours after routine maintenance or repair. Records of test shall be maintained for a period of five years and be made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
28. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.5] Federally Enforceable Through Title V Permit
29. Permittee shall test annually the sulfur content of scrubbed casing gas using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
30. Permittee shall maintain a current well roster and shall make such roster, component count and resulting emissions readily available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
31. Condensed liquids from condensate handling system shall be piped in closed systems to the WASP disposal well. [District Rule 2201] Federally Enforceable Through Title V Permit
32. Emergency condensate overflow pit shall be empty except during breakdown conditions pursuant to Rule 1100. [District Rule 2201] Federally Enforceable Through Title V Permit
33. All wells served by this vapor control system shall be shut-in and shall not vent to the atmosphere in the event of failure of the non-condensable VOC disposal system. [District Rule 2201] Federally Enforceable Through Title V Permit
34. Permittee shall at least monthly, measure and record sulfur content and BTU content of TEOR gas exiting the desulfurizer using ASTM method D1072, D3031, D4084, D3246 or a gas detector tube, and shall make all records and analyses readily available for District inspection. [District Rule 2201 and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
35. Permittee shall maintain daily records of pilot gas and TEOR gas flared and shall make such records readily available for District inspection for a period of five years. [District Rule 2520, 9.4.2 and District Rule 1070] Federally Enforceable Through Title V Permit
36. The flare shall be operated according to the manufacturer's specifications, a copy of which shall be maintained on site. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
37. If this flare requires a pilot flame, then the flare shall be operated with a flame present at all times, and kept in operation when emissions may be vented to it. The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

38. This flare shall be inspected every two weeks while in operation for visible emissions. If visible emissions are observed, corrective action shall be taken. If visible emissions continue, an EPA Method 9 test shall be conducted within 72 hours. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
39. This flare shall not be used as a leak control device as described in Rule 4403, 5.3.1, nor as a control device for any permit unit subject to NSPS, without modification of permit requirements to address 40 CFR 60.18. [District Rule 2520, 9.3.3] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-28-21

EXPIRATION DATE: 03/31/2021

SECTION: 2 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

THERMALLY ENHANCED OIL RECOVERY OPERATION INCLUDING DEEP EMERGENCY OVERFLOW PIT WITH MESH COVER, HORIZONTAL GAS-LIQUID SEPARATOR, AIR-COOLED HEAT EXCHANGER, HORIZONTAL CONDENSATE COLLECTION VESSEL WITH LIQUID TRANSFER PUMPS, 30 HP COMPRESSOR (K-101), 2.9 MMBTU/HR MCGILL STANDBY FLARE (#1011-2) EQUIPPED WITH 2 IN DIA BURNER TIP, AIR ASSIST BLOWER, KO DRUM SHARED WITH PERMIT UNIT S-1326-27, AND WELL VENT VAPOR CONTROL SYSTEM SERVING 150 STEAM DRIVE WELLS

PERMIT UNIT REQUIREMENTS

1. TEOR operation shall include deep emergency overflow pit with mesh cover, horizontal gas-liquid separator, air-cooled heat exchanger, horizontal condensate collection vessel with liquid transfer pumps for the pumping of condensate to heavy oil tank battery, 30 hp compressor (K-101) with compressed vapors sent to common field fuel gas line, and production well vent casing line to TEOR system S-1326-27 and steam generators S-1326-9, '-294, '-314, '-337, '-338, '-385, '-390, '-391, '-392, '-400, '-401, and '-419 through '-425. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Wells may be operated with closed casing vents or be vented to vapor control system. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Fluids produced from wells with closed vents shall be introduced only to production equipment served by vapor control system listed on tank S-1326-201 which is 99% efficient. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The crude oil production from wells associated with this permit unit shall not lie within 1000 feet of an air injection well used for in-situ combustion. [District Rule 4407, 2.0, 3.4, and 3.5] Federally Enforceable Through Title V Permit
5. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401, 5.0 (as amended January 15, 1998). [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
6. All required source testing shall conform to the compliance testing procedures described in District Rule 1081 (as amended December 16, 1993). [District Rule 1081] Federally Enforceable Through Title V Permit
7. The operator shall maintain monitoring records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit
8. The uncontrolled VOC emissions from any well vent shall be reduced by at least 99 percent by weight or, if several steam-enhanced crude oil production well vents are connected to a vapor collection and control system, total uncontrolled VOC emissions shall be reduced by at least 99 percent. This requirement does not apply to cyclic wells located on contiguous and adjacent oil production properties with less than 10 cyclic wells owned by or under the control of a company. [District Rule 4401, 5.1 and 5.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. For cyclic wells located on properties with less than 10 cyclic wells and owned by a company, the uncontrolled VOC emissions from any well vent or system of well vents connected to a single control device shall be reduced by at least 50 percent. Properties shall include contiguous and adjacent oil production properties owned by or under control of the company. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit
10. Total number of leaks from the vapor collection and control system, including condensate handling, shall not exceed the number as allowed by Rule 4401 (as amended January 15, 1998) at any one time. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit
11. Operator shall affix a readily visible tag bearing the date on which a leak is detected. The tag shall remain in place until the leaking component is repaired. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit
12. Operator shall repair each leak within 15 days of detection. The APCO may grant a 10 day extension if the operator demonstrates that the necessary and sufficient actions have and are being taken to correct the leak. [District Rule 4401, 5.3.1] Federally Enforceable Through Title V Permit
13. Operator shall maintain all components of a well vent vapor collection and control system in good repair. Components of the well vent vapor collection and control system shall include all piping, valves, fittings, pumps, compressors, tanks, etc. used to collect, control, store, or dispose of VOC condensate or non-condensable VOCs and which is prior to any blending of VOC condensate with crude oil or blending of non-condensable VOCs with gases to be used as a fuel. [District Rule 4401, 5.3 and 5.3.2] Federally Enforceable Through Title V Permit
14. Annual control efficiency compliance tests shall be performed on all vapor collection and control systems used to control emissions from steam-enhanced crude oil production wells. Testing shall be performed by source tester certified by the California Air Resource Board (CARB) certified contractors during June, July, August or September of each year if the system's control efficiency is dependent upon ambient air temperature. The APCO may waive the requirements of this condition if the vapor control system does not exhaust to atmosphere or if all uncondensed VOC emissions collected by a vapor collection and control system are burned in fuel burning equipment or in a smokeless open flare and the source's Operating Permit contains adequate periodic monitoring to ensure the source meets 99% control efficiency. [District Rule 4401, 5.1, 5.2 and 6.2.1] Federally Enforceable Through Title V Permit
15. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit
16. The permittee shall perform leak inspections at least annually, using a portable hydrocarbon detection instrument in accordance with USEPA Method 21. [District Rules 2520, 9.3.2 and 4401, 6.3.3] Federally Enforceable Through Title V Permit
17. Compliance with permit conditions in the Title V permit shall be deemed compliance with Kern County Rule 108.1. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
18. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4401 (Amended January 15, 1998), excluding sections 5.1 and 5.2 for control systems which have been waived from complying with the requirement of section 6.2.1. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
19. The requirements of District Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit because it is not an in situ combustion well vent. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
20. Components shall be maintained and leaks shall be repaired as specified in Rule 4401. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401, 6.3.5] Federally Enforceable Through Title V Permit
22. Permittee shall maintain with the permit a current listing of all steam enhanced wells connected to the casing vent control system and shall make such listing readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
23. Well vent vapor control system shall include vapor piping connected to tank vapor control system listed on permit #S-1326-201. [District Rule 2201] Federally Enforceable Through Title V Permit
24. Sulfur content of scrubbed TEOR gas shall not exceed 1 gr/100scf. [District Rule 2201] Federally Enforceable Through Title V Permit
25. Sulfur scrubber shall be operated to maintain continued compliance with fuel gas sulfur content limit of 1 grain-S/100 scf of fuel gas. [District Rule 2201] Federally Enforceable Through Title V Permit
26. Only PUC quality natural gas or comparable quality lease gas with sulfur content of 1 grain-S/100 scf or less shall be utilized as make-up gas for the horizontal condensate collection vessel and utilized as pilot fuel for standby flare. [District Rule 2201] Federally Enforceable Through Title V Permit
27. Sulfur scrubber shall be monitored monthly for H₂S content of gas after treatment to determine when recharging is required. [District Rule 2201] Federally Enforceable Through Title V Permit
28. Permittee shall maintain a written record of H₂S content and recharging dates and such records shall be made readily available for District inspection upon request. [District NSR Rule and District Rule 1070] Federally Enforceable Through Title V Permit
29. Permittee shall test annually the sulfur content of scrubbed casing gas using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
30. VOC content of well vent vapor gas shall not exceed 10% by weight. If the VOC content of the well vent vapor gas is less than 10% by weight for 8 consecutive quarterly samplings per District approved plan, sampling frequency shall only be required annually. Representative samples shall be collected during periods of normal operation and not be within 48 hours after routine maintenance or repair. Records of test shall be maintained for a period of five years and be made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
31. The emergency condensate overflow pit shall be empty except during breakdown conditions pursuant to Rule 1100. [District Rule 2201] Federally Enforceable Through Title V Permit
32. Well head casing vent gas collection system shall be shut-in and shall not vent to the atmosphere in the event of failure of the non-condensable VOC disposal system. [District Rule 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-35-19

EXPIRATION DATE: 03/31/2021

SECTION: 14 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

THERMALLY ENHANCED OIL RECOVERY OPERATION WITH WELL VENT VAPOR CONTROL SYSTEM SERVING 250 STEAM ENHANCED WELLS, INCLUDING 50 HP COMPRESSOR, ONE AIR-COOLED VAPOR CONDENSER, AND PIPING TO FIELD FUEL GAS SYSTEM, DOGGR DISPOSAL WELL, AND/OR 3.6 MMBTU/HR KALDAIR FLARE INCLUDING TWO 8000 LB SULFATREAT CANISTERS (ONE AS BACKUP) (SECTION 14 YOUNG)

PERMIT UNIT REQUIREMENTS

1. Fluids produced from wells with closed vents shall be introduced only to production equipment served by vapor control system listed on tank S-1326-201 which is 99% efficient. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Well vent vapors shall vent to the field fuel gas system, DOGGR approved injection wells, flare listed on this permit, or steam generators S-1326-9, '-294, '-314, '-337, '-338, '-385, '-390, '-391, '-392, '-400, '-401, and '-419 through '-425. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Well head casing vent collection piping network shall be limited to 250 steam enhanced wells. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Sulfur scrubber shall be monitored monthly for H₂S content of gas after treatment to determine when recharging is required. [District NSR Rule and District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
5. Sulfur content of gas combusted in flare shall not exceed 1 gr/100 scf. [District NSR Rule, District Rule 4801, and Kern County Rule 407] Federally Enforceable Through Title V Permit
6. Permittee shall test annually the sulfur content of gas combusted in flare using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
7. Flare shall operate with no visible emission in excess of 5% opacity. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Maximum amount of gas (pilot and waste gas) combusted by flare shall not exceed 150.0 MMBtu/day. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Emissions from the flare shall not exceed any of the following limits (based on total gas combusted): NO_x (as NO₂): 0.068 lb/MMBtu; PM₁₀: 0.008 lb/MMBtu; CO: 0.37 lb/MMBtu; or VOC: 0.063 lb/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The higher heating value of the flared gas shall be monitored at least quarterly. Measured higher heating value and quantity of gas flared shall be used to determine compliance with heat input limit. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
11. The flare shall be operated according to the manufacturer's specifications, a copy of which shall be maintained on site. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. If this flare requires a pilot flame, then the flare shall be operated with a flame present at all times, and kept in operation when emissions may be vented to it. The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
13. This flare shall be inspected every two weeks while in operation for visible emissions. If visible emissions are observed, corrective action shall be taken. If visible emissions continue, an EPA Method 9 test shall be conducted within 72 hours. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
14. This flare shall not be used as a leak control device as described in Rule 4403, 5.3.1, nor as a control device for any permit unit subject to NSPS, without modification of permit requirements to address 40 CFR 60.18. [District Rule 2520, 9.3.3] Federally Enforceable Through Title V Permit
15. A gas leak is defined as the detection of a concentration of total organic compounds, above background (measured in accordance with EPA Method 21) that exceeds the following values: 1) A major gas leak is a detection of greater than 10,000 ppmv as methane; and 2) A minor gas leak is a detection of 400 to 10,000 ppmv as methane for pressure relief devices (PRDs) and 2,000 to 10,000 for components other than PRDs. [District Rule 4401] Federally Enforceable Through Title V Permit
16. A liquid leak is defined as the dripping of VOC-containing liquid. A major liquid leak is a visible mist or a continuous flow of liquid that is not seal lubricant. A minor liquid leak is a liquid leak that is not a major liquid leak and drips liquid at a rate of more than three drops per minute, except for seal lubricant. [District Rule 4401] Federally Enforceable Through Title V Permit
17. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401, 5.0 (as amended December 14, 2006). [District Rule 4401] Federally Enforceable Through Title V Permit
18. The following conditions shall be used to determination of a violation: 1) Existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended lines. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere; 2) Existence of a component with a major liquid leak; 3) Existence of a component with a gas leak greater than 50,000 ppmv; or 4) Existence of a component leak consisting of a minor liquid or gas leak, or a gas leak greater than 10,000 ppmv up to 50,000 ppmv, in excess of the allowable number of leaks specified in Table 3 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit
19. Total number of leaks from the vapor collection and control system, including condensate handling, shall not exceed the number as allowed by Rule 4401 (as amended December 14, 2006) at any one time. [District Rule 4401] Federally Enforceable Through Title V Permit
20. Operator shall affix a readily visible tag bearing the date and time of leak detection, the date and time of leak measurement, the leak concentration of gaseous leaks (in ppmv), for liquid leaks whether it is a major liquid leak or a minor liquid leak, and whether the component is an essential component, an unsafe-to monitor component, or a critical component leak. [District Rule 4401] Federally Enforceable Through Title V Permit
21. The tag shall remain in place until the leaking component is repaired, re-inspected, using the test method in Section 6.3.3, and the component is found to be in compliance with the requirements of this rule. [District Rule 4401] Federally Enforceable Through Title V Permit
22. An operator shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401] Federally Enforceable Through Title V Permit
23. Except for leaking critical components or leaking essential components, the operator shall repair each leak within time specified in Table 3, of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

24. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401] Federally Enforceable Through Title V Permit
25. The operator shall not use any components that leak in excess of the applicable leak standards as specified in this permit. Components that have been found leaking in excess of the applicable leak standards of this rule may be used provided such leaking components have been identified with a tag for repair, are repaired, or are awaiting re-inspection after being repaired, within the applicable time period specified in this permit. [District Rule 4401] Federally Enforceable Through Title V Permit
26. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401] Federally Enforceable Through Title V Permit
27. Except for pipes and unsafe-to-monitor components, an operator shall inspect all other components pursuant to the requirements of Section 6.3.3 at least once every year [District Rule 4401] Federally Enforceable Through Title V Permit
28. An operator shall visually inspect all pipes at least once every year. Any visual inspection of pipes that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected within 24 hours after detecting the leak. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of this rule. [District Rule 4401] Federally Enforceable Through Title V Permit
29. An operator shall audio-visually (by hearing and by sight) inspect for leaks all accessible operating pumps, compressors, and PRDs in service at least once each calendar week. [District Rule 4401] Federally Enforceable Through Title V Permit
30. Any audio-visual inspection of an accessible operating pump, compressor, and PRD performed by an operator that indicates a leak that cannot be immediately repaired to meet the leak standards of this rule shall be inspected not later than 24 hours after conducting the audio-visual inspection. If a leak is found, the leak shall be repaired as soon as practicable but not later than the time frame specified in Table 3 of this rule. [District Rule 4401] Federally Enforceable Through Title V Permit
31. An operator shall initially inspect a PRD that releases to the atmosphere as soon as practicable but not later than 24 hours after the discovery of the release. An operator shall re-inspect the PRD not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the initial inspection. [District Rule 4401] Federally Enforceable Through Title V Permit
32. An operator shall inspect all new, replaced, or repaired fittings, flanges, and threaded connections within 72 hours of placing the component in service. [District Rule 4401] Federally Enforceable Through Title V Permit
33. An operator shall inspect a component, except for a PRD that releases to the atmosphere, that has been repaired or replaced not later than 15 calendar days after the component was repaired or replaced. [District Rule 4401] Federally Enforceable Through Title V Permit
34. An operator shall inspect all unsafe-to-monitor components during each turnaround. [District Rule 4401] Federally Enforceable Through Title V Permit
35. The operator shall perform leak inspections at least annually, using a portable hydrocarbon detection instrument in accordance with USEPA Method 21. Where safety is a concern, such as measuring leaks from compressor seals or pump seals when the shaft is rotating, a person shall measure leaks by placing the instrument probe inlet at a distance of one centimeter or less from the surface of the component interface. [District Rule 4401] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

36. VOC content of well vent vapor gas shall not exceed 10% by weight. If the VOC content of the well vent vapor gas is less than 10% by weight for 8 consecutive quarterly samplings per District approved plan, sampling frequency shall only be required annually. Representative samples shall be collected during periods of normal operation and not be within 48 hours after routine maintenance or repair. Records of test shall be maintained for a period of five years and be made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
37. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. [District Rule 4401] Federally Enforceable Through Title V Permit
38. Annual control efficiency compliance tests shall be performed on all vapor collection and control systems used to control emissions from steam-enhanced crude oil production wells. Testing shall be performed by source tester certified by the California Air Resource Board (CARB) certified contractors during June, July, August or September of each year if the system's control efficiency is dependent upon ambient air temperature. The APCO may waive the requirements of this condition if the vapor control system does not exhaust to atmosphere or if all uncondensed VOC emissions collected by a vapor collection and control system are burned in fuel burning equipment or in a smokeless open flare and the source's Operating Permit contains adequate periodic monitoring to ensure the source meets 99% control efficiency. [District Rule 4401] Federally Enforceable Through Title V Permit
39. The control efficiency of the vapor collection and control system used to control VOC emissions from steam enhanced crude oil production well shall be determined by mass balance based on most stringent of a source test, USEPA approved emission factors, or Air Pollution (AP)-42 emission factors for components; and the efficiency of destruction devices determined by USEPA Method 25, 25a, or 25b as applicable. [District Rule 4401] Federally Enforceable Through Title V Permit
40. Permittee shall maintain an inspection log which includes the following information: 1) the total number of components inspected and the total number and percentage of leaking components found by component type, 2) the location, type, and name or description of each leaking component and description of any unit where the leaking component is found, 3) the date and method of leak detection, 4) the size of the leak (in ppmv for gaseous leaks, and major or minor for liquid leaks), 5) the date the leaking component is repaired, replaced, or removed from service, 6) the identity and location of essential or critical components found leaking that cannot be repaired until the next regular process unit turnaround or not later than one year after leak detection, whichever comes later, 7) the methods used to minimize the leak from essential or critical components, 8) the date of re-inspection and the leak concentration (in ppmv) after the component is repaired or replaced, 9) the inspector's name, mailing address, and business telephone number, and 10) the date and signature of the facility operator responsible for the inspection and repair program certifying the accuracy of the information recorded in the log. [District Rule 4401] Federally Enforceable Through Title V Permit
41. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components. The records shall include a copy of the current calibration gas certification from the vendor of the calibration gas cylinder, the date of calibration, the concentration of calibration gas, the instrument reading of calibration gas before adjustment, the instrument reading of calibration gas after adjustment, the calibration gas expiration date, and the calibration gas cylinder pressure at the time of calibration. [District Rule 4401] Federally Enforceable Through Title V Permit
42. The operator shall keep source test records which demonstrate compliance with the control efficiency requirements of the VOC collection and control system. [District Rule 4401] Federally Enforceable Through Title V Permit
43. Permittee shall establish and implement an employee training program for inspecting and repairing components and recordkeeping procedures, as necessary. Permittee shall maintain at the facility the copies of the training records of the training program. [District Rule 4401] Federally Enforceable Through Title V Permit
44. By January 30 of each year, permittee shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing, approved OMP. [District Rule 4401] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

45. Permittee shall maintain a copy of the latest APCO-approved Operator Management Plan (OMP) at the facility and make it available to the APCO, ARB, and US EPA upon request. [District Rule 4401] Federally Enforceable Through Title V Permit
46. The operator shall maintain monitoring records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit
47. The permittee shall keep accurate records of the amount of gas (pilot and waste gas) flared, H₂S content and recharging dates, for a period of five years, and shall make such records available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
48. Permittee shall maintain a current well roster of all wells served by collection system, and such roster shall be made readily available for District inspection upon request. [District Rule 2520, 9.3.2 and District Rule 1070] Federally Enforceable Through Title V Permit
49. All records required by this permit shall be maintained and retained on-site for a minimum of five (5) years and made available for District, ARB, and EPA inspection upon request. [District Rules 2201 and 4401] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-36-3

EXPIRATION DATE: 03/31/2021

EQUIPMENT DESCRIPTION:

UP TO 5 UNCONTROLLED CYCLICLY STEAMED OIL WELLS HEAVY OIL CENTRAL STATIONARY SOURCE

PERMIT UNIT REQUIREMENTS

1. Sulfur compounds emission concentration shall not exceed 0.2 percent by volume calculated as sulfur dioxide (SO₂), on a dry basis averaged over 15 consecutive minutes. [District Rule 4801] Federally Enforceable Through Title V Permit
2. An increase in the number of wells listed on this Permit to Operate shall require an Authority to Construct. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The well contained in this permit unit shall be located more than 1000 feet from an existing well vent vapor control system. [District Rule 4401, 4.4] Federally Enforceable Through Title V Permit
4. Permittee shall maintain a current well roster of all open well vents and, upon request, shall make such roster available for District inspection. [District 1070] Federally Enforceable Through Title V Permit
5. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-46-10

EXPIRATION DATE: 03/31/2021

SECTION: NE 23 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

1000 BBL FIXED-ROOF STOCK TANK WITH VAPOR CONTROL SYSTEM INCLUDING GAS/LIQUID SEPARATOR
SHARED WITH PERMIT UNITS S-1326-47, -48, -214, AND -215 (FANO LEASE)

PERMIT UNIT REQUIREMENTS

1. The true vapor pressure of the liquids stored in this tank shall not exceed 0.5 psia. [District Rules 4623, 4.4 and 2201] Federally Enforceable Through Title V Permit
2. Tank vapors shall be compressed and routed to approved control equipment listed on permit S-1326-26. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Vapor control efficiency shall be maintained at no less than 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The vapor control system compressor shall activate when the tank internal pressure exceeds 1.5 in. w.c. and deactivate when the tank internal pressure falls to 0.5 in. w.c. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Fuel gas system gas shall consist primarily of methane containing no more than 5% by weight hydrocarbons heavier than butane and shall have a sulfur content of no more than 0.75 gr/100 scf. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The tank pressure relief valves shall not open unless the tank internal pressure exceeds 2.0 oz. or falls below 0.5 oz. vacuum. [District Rule 2201] Federally Enforceable Through Title V Permit
7. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor recovery system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed. Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor recovery system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3 V / Q$, where t = time, V = tank volume (cubic feet), and Q = flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the procedure used to vent tank vapors prior to opening, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
12. To qualify for quantification of no fugitive emissions, operator shall conduct quarterly gas sampling after TVR compressor (prior to connection to any other vapor control system) and at either the first line tank or at any secondary tank which is heated above ambient temperature. If gas samples are less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually and whenever there is a change in source or type of petroleum processed. Samples shall be collected during periods of normal operation, and not be within 48 hours after routine maintenance or repair. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Permittee shall provide the District with written notification at least 30 days prior to installation of components handling fluid streams with a VOC content of 10% or less by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. Gas-tight shall be defined as emitting no more than 10,000 ppm of methane with an instrument calibrated with methane in accordance with USEPA Method 21. Emissions in excess of this limit shall be considered a leak. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
15. All tank seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a gas-tight condition. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. Compressor knockout drum liquids shall be piped only to vapor-controlled tanks or WASP disposal well. [District Rule 2201] Federally Enforceable Through Title V Permit
17. The permittee shall keep accurate records of liquids stored and true vapor pressure of such liquids. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
18. The operator shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
19. The API gravity of organic liquid stored in this tank shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method)". Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products". [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
20. Control efficiency shall be determined by a comparison of controlled emissions to those emissions which would occur from a fixed or cone roof tank in the same product service without a vapor recovery system. Emissions shall be determined based on tank emission factors in USEPA Publication AP-42, component counts for fugitive emissions sources, recognized emission factors for fugitive emission sources and the efficiency of any VOC destruction device. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
21. Operator shall ensure the vapor control system is functional and operating as designed at all times, except during periods of routine maintenance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
22. Operator shall determine the true vapor pressure of the petroleum liquid stored in the tank located at the beginning of the process flow after the production header at least once per year. The latest version of the Lawrence Berkeley National Laboratory "Test Method for Vapor Pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA, shall be used to determine the TVP of crude oil with an API gravity of 26 or less, or for any API gravity that is specified in this test method. Determinations shall be made annually during summer and whenever there is a change in the source or type of petroleum entering the tank. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

23. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
24. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
25. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids store in this unit to determine which oil are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-47-6

EXPIRATION DATE: 03/31/2021

SECTION: NE 23 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

1000 BBL FIXED-ROOF STOCK TANK SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1326-46 (FANO LEASE)

PERMIT UNIT REQUIREMENTS

1. The true vapor pressure of the liquids stored in this tank shall not exceed 0.5 psia. [District Rules 4623, 4.4 and 2201] Federally Enforceable Through Title V Permit
2. Vapor control efficiency shall be maintained at no less than 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Fuel gas system gas shall consist primarily of methane containing no more than 5% by weight hydrocarbons heavier than butane and shall have a sulfur content of no more than 0.75 gr/100 scf. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The tank pressure relief valves shall not open unless the tank internal pressure exceeds 2.0 oz. or falls below 0.5 oz. vacuum. [District Rule 2201] Federally Enforceable Through Title V Permit
5. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor recovery system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed. Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor recovery system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3 V / Q$, where t = time, V = tank volume (cubic feet), and Q = flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the procedure used to vent tank vapors prior to opening, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. To qualify for quantification of no fugitive emissions, operator shall conduct quarterly gas sampling after TVR compressor (prior to connection to any other vapor control system) and at either the first line tank or at any secondary tank which is heated above ambient temperature. If gas samples are less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually and whenever there is a change in source or type of petroleum processed. Samples shall be collected during periods of normal operation, and not be within 48 hours after routine maintenance or repair. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Permittee shall provide the District with written notification at least 30 days prior to installation of components handling fluid streams with a VOC content of 10% or less by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. Gas-tight shall be defined as emitting no more than 10,000 ppm of methane with an instrument calibrated with methane in accordance with USEPA Method 21. Emissions in excess of this limit shall be considered a leak. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
13. All tank seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a leak-free condition. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
14. The permittee shall keep accurate records of liquids stored and true vapor pressure of such liquids. [District Rule 4623.6.3] Federally Enforceable Through Title V Permit
15. The operator shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
16. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
17. The API gravity of organic liquid stored in this tank shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method)". Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products". [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
18. Control efficiency shall be determined by a comparison of controlled emissions to those emissions which would occur from a fixed or cone roof tank in the same product service without a vapor recovery system. Emissions shall be determined based on tank emission factors in USEPA Publication AP-42, component counts for fugitive emissions sources, recognized emission factors for fugitive emission sources and the efficiency of any VOC destruction device. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
19. Operator shall ensure the vapor control system is functional and operating as designed at all times, except during periods of routine maintenance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
20. Operator shall determine the true vapor pressure of the petroleum liquid stored in the tank located at the beginning of the process flow after the production header at least once per year. The latest version of the Lawrence Berkeley National Laboratory "Test Method for Vapor Pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA, shall be used to determine the TVP of crude oil with an API gravity of 26 or less, or for any API gravity that is specified in this test method. Determinations shall be made annually during summer and whenever there is a change in the source or type of petroleum entering the tank. [District Rules 2520, 9.3.2 and 4623, 4.4] Federally Enforceable Through Title V Permit
21. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
22. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

23. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids store in this unit to determine which oil are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-48-6

EXPIRATION DATE: 03/31/2021

SECTION: NE 23 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

5000 BBL FIXED-ROOF WASTE WATER TANK SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1326-46
(FANO LEASE)

PERMIT UNIT REQUIREMENTS

1. The true vapor pressure of the liquids stored in this tank shall not exceed 0.5 psia. [District Rules 4623, 2.0 and 2201] Federally Enforceable Through Title V Permit
2. Vapor control efficiency shall be maintained at no less than 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Fuel gas system gas shall consist primarily of methane containing no more than 5% by weight hydrocarbons heavier than butane and shall have a sulfur content of no more than 0.75 gr/100 scf. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The tank pressure relief valves shall not open unless the tank internal pressure exceeds 2.0 oz. or falls below 0.5 oz. vacuum. [District Rule 2201] Federally Enforceable Through Title V Permit
5. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor recovery system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed. Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor recovery system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3 V / Q$, where t = time, V = tank volume (cubic feet), and Q = flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the procedure used to vent tank vapors prior to opening, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. To qualify for quantification of no fugitive emissions, operator shall conduct quarterly gas sampling after TVR compressor (prior to connection to any other vapor control system) and at either the first line tank or at any secondary tank which is heated above ambient temperature. If gas samples are less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually and whenever there is a change in source or type of petroleum processed. Samples shall be collected during periods of normal operation, and not be within 48 hours after routine maintenance or repair. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Permittee shall provide the District with written notification at least 30 days prior to installation of components handling fluid streams with a VOC content of 10% or less by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. Leak-free shall be defined as emitting no more than 10,000 ppm of methane measured at a distance of one centimeter from the potential source with an instrument calibrated with methane in accordance with USEPA Method 21. Emissions in excess of this limit shall be considered a leak. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
13. All tank seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a leak-free condition. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
14. The permittee shall keep accurate records of liquids stored and true vapor pressure of such liquids. [District Rule 4623, 6.3] Federally Enforceable Through Title V Permit
15. The operator shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
16. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
17. The API gravity of organic liquid stored in this tank shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method)". Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products". [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
18. Control efficiency shall be determined by a comparison of controlled emissions to those emissions which would occur from a fixed or cone roof tank in the same product service without a vapor recovery system. Emissions shall be determined based on tank emission factors in USEPA Publication AP-42, component counts for fugitive emissions sources, recognized emission factors for fugitive emission sources and the efficiency of any VOC destruction device. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
19. The operator shall ensure that the vapor control system is functional and is operating as designed at all times, except during periods of routine maintenance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
20. Operator shall determine the true vapor pressure of the petroleum liquid stored in the tank located at the beginning of the process flow after the production header at least once per year. The latest version of the Lawrence Berkeley National Laboratory "Test Method for Vapor Pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA, shall be used to determine the TVP of crude oil with an API gravity of 26 or less, or for any API gravity that is specified in this test method. Determinations shall be made annually during summer and whenever there is a change in the source or type of petroleum entering the tank. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit
21. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
22. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

23. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids store in this unit to determine which oil are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-119-4

EXPIRATION DATE: 03/31/2021

SECTION: 14 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

2000 BBL FIXED-ROOF PETROLEUM STORAGE TANK #2GK-255 (LENHARDT USL).

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. Operator shall determine the true vapor pressure of the petroleum liquid stored in the tank located at the beginning of the process flow after the production header at least once per year. The latest version of the Lawrence Berkeley National Laboratory "Test Method for Vapor Pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA, shall be used to determine the TVP of crude oil with an API gravity of 26 or less, or for any API gravity that is specified in this test method. Determinations shall be made annually during summer and whenever there is a change in the source or type of petroleum entering the tank. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-120-4

EXPIRATION DATE: 03/31/2021

SECTION: 14 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

2000 BBL FIXED-ROOF PETROLEUM STORAGE TANK #2L100 (LENHARDT USL).

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. Operator shall determine the true vapor pressure of the petroleum liquid stored in the tank located at the beginning of the process flow after the production header at least once per year. The latest version of the Lawrence Berkeley National Laboratory "Test Method for Vapor Pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA, shall be used to determine the TVP of crude oil with an API gravity of 26ø or less, or for any API gravity that is specified in this test method. Determinations shall be made annually during summer and whenever there is a change in the source or type of petroleum entering the tank. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-121-4

EXPIRATION DATE: 03/31/2021

SECTION: 14 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

5000 BBL FIXED-ROOF PETROLEUM STORAGE TANK #5L101 (LENHARDT USL).

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. Operator shall determine the true vapor pressure of the petroleum liquid stored in the tank located at the beginning of the process flow after the production header at least once per year. The latest version of the Lawrence Berkeley National Laboratory "Test Method for Vapor Pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA, shall be used to determine the TVP of crude oil with an API gravity of 26 or less, or for any API gravity that is specified in this test method. Determinations shall be made annually during summer and whenever there is a change in the source or type of petroleum entering the tank. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-126-4

EXPIRATION DATE: 03/31/2021

SECTION: 14 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

2000 BBL FIXED-ROOF PETROLEUM STORAGE TANK #20WSTWTR (SEC. 14 USL).

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. Operator shall determine the true vapor pressure of the petroleum liquid stored in the tank located at the beginning of the process flow after the production header at least once per year. The latest version of the Lawrence Berkeley National Laboratory "Test Method for Vapor Pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA, shall be used to determine the TVP of crude oil with an API gravity of 26.0 or less, or for any API gravity that is specified in this test method. Determinations shall be made annually during summer and whenever there is a change in the source or type of petroleum entering the tank. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-127-4

EXPIRATION DATE: 03/31/2021

SECTION: 14 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

2000 BBL FIXED-ROOF PETROLEUM STORAGE TANK #20X1504 (SEC. 14 USL).

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-128-4

EXPIRATION DATE: 03/31/2021

SECTION: 14 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

2000 BBL FIXED-ROOF PETROLEUM STORAGE TANK #2GK37 (SEC. 14 USL)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-129-3

EXPIRATION DATE: 03/31/2021

SECTION: 22 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

5000 BBL FIXED-ROOF PETROLEUM STORAGE TANK #5GK43 (ROBINSON A/USL)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-130-3

EXPIRATION DATE: 03/31/2021

SECTION: 22 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

5000 BBL FIXED-ROOF PETROLEUM STORAGE TANK #5GK-34 (ROBINSON A/USL)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-131-3

EXPIRATION DATE: 03/31/2021

SECTION: 22 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

2000 BBL FIXED-ROOF PETROLEUM STORAGE TANK #2RA100 (ROBINSON A/USL)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-132-3

EXPIRATION DATE: 03/31/2021

SECTION: 22 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

2000 BBL FIXED-ROOF PETROLEUM STORAGE TANK #SPLCONTTNK (STAR USL/STAR ROBINSON)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-133-3

EXPIRATION DATE: 03/31/2021

SECTION: 22 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

1000 BBL FIXED-ROOF PETROLEUM STORAGE TANK #152323 (STAR USL)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-134-3

EXPIRATION DATE: 03/31/2021

SECTION: 22 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

1000 BBL FIXED-ROOF PETROLEUM STORAGE TANK #15322 (STAR USL)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-135-3

EXPIRATION DATE: 03/31/2021

SECTION: 22 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

1000 BBL FIXED-ROOF PETROLEUM STORAGE TANK #15321 (STAR USL)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-136-3

EXPIRATION DATE: 03/31/2021

SECTION: 22 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

1000 BBL FIXED-ROOF PETROLEUM STORAGE TANK #WSTWTR1 (STAR USL)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-137-4

EXPIRATION DATE: 03/31/2021

SECTION: 22 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

1000 BBL FIXED-ROOF PETROLEUM STORAGE TANK #15324 (STAR ROBINSON).

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-138-4

EXPIRATION DATE: 03/31/2021

SECTION: 22 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

1000 BBL FIXED-ROOF PETROLEUM STORAGE TANK #15325 (STAR ROBINSON).

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-139-4

EXPIRATION DATE: 03/31/2021

SECTION: 22 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

1000 BBL FIXED-ROOF PETROLEUM STORAGE TANK #15326 (STAR ROBINSON).

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-140-4

EXPIRATION DATE: 03/31/2021

SECTION: 22 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

1000 BBL FIXED-ROOF PETROLEUM STORAGE TANK #WSTWTR1 (STAR ROBINSON).

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-147-3

EXPIRATION DATE: 03/31/2021

SECTION: 22 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

2000 BBL FIXED-ROOF PETROLEUM STORAGE TANK #2GK-18 (ROBINSON B/USL)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-148-3

EXPIRATION DATE: 03/31/2021

SECTION: 22 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

2000 BBL FIXED-ROOF PETROLEUM STORAGE TANK #2GK-23 (ROBINSON B/USL)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-149-3

EXPIRATION DATE: 03/31/2021

SECTION: 22 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

1000 BBL FIXED-ROOF PETROLEUM STORAGE TANK #1RB101 (ROBINSON B/USL)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-150-4

EXPIRATION DATE: 03/31/2021

SECTION: 22 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

1000 BBL FIXED-ROOF PETROLEUM STORAGE TANK #1DRNTK3 (ROBINSON B DEHY).

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-151-4

EXPIRATION DATE: 03/31/2021

SECTION: 22 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

5000 BBL FIXED-ROOF PETROLEUM STORAGE TANK #5RB1035RG (ROBINSON B DEHY).

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-152-4

EXPIRATION DATE: 03/31/2021

SECTION: 22 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

1000 BBL FIXED-ROOF PETROLEUM STORAGE TANK #10WSTWTR (ROBINSON B DEHY).

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-153-4

EXPIRATION DATE: 03/31/2021

SECTION: 22 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

3000 BBL FIXED-ROOF PETROLEUM STORAGE TANK #3GK309SHP (ROBINSON B DEHY).

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-154-4

EXPIRATION DATE: 03/31/2021

SECTION: 22 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

3000 BBL FIXED-ROOF PETROLEUM STORAGE TANK #3GK310SHP (ROBINSON B DEHY).

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-158-3

EXPIRATION DATE: 03/31/2021

SECTION: 22 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

5000 BBL FIXED-ROOF PETROLEUM STORAGE TANK #5T100 (TEGELER/USL)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-159-3

EXPIRATION DATE: 03/31/2021

SECTION: 22 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

2000 BBL FIXED-ROOF PETROLEUM STORAGE TANK #3GK24 (TEGELER/USL)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-160-3

EXPIRATION DATE: 03/31/2021

SECTION: 22 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

2000 BBL FIXED-ROOF PETROLEUM STORAGE TANK #2GK13 (TEGELER/USL)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-201-11

EXPIRATION DATE: 03/31/2021

SECTION: SW11 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

3,000 BBL FIXED ROOF WASH TANK (#T-1) WITH SHARED VAPOR CONTROL SYSTEM SERVING TEOR SYSTEM TEOR SYSTEM S-1326-28 AND TANKS S-1326-201, '-202, '-203, '-204, '-205, '-206, '-212, '-261, '-262, '-268, '-269, '-270, '-271, '-272, AND '-274. (NORTH TREATING FACILITY).

PERMIT UNIT REQUIREMENTS

1. Tank vapor control system consists of three 15 hp vapor compressors and compressed vapor piping to TEOR well vent vapor control system S-1326-28. [District 2201 Rule] Federally Enforceable Through Title V Permit
2. Tank stored liquid temperature shall not exceed 220 degrees F. [District 2201 Rule] Federally Enforceable Through Title V Permit
3. Tank shall be equipped with an operational stored liquid temperature indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Tank shall operate at a constant level. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The Reid Vapor Pressure (RVP) of the liquid stored in this tank shall not exceed 0.75 psia. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device the reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. All piping, valves, and fittings shall be constructed and maintained in a gas-tight condition. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
9. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with USEPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
11. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
12. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
13. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
14. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by USEPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by USEPA Method 25 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
15. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. True Vapor Pressure (TVP) shall be measured using Reid vapor pressure ASTM Method D323 modified by maintaining the hot water bath at storage temperature. Where storage temperature is above 100 degrees F true vapor pressure shall be determined by Reid vapor pressure at 100 degrees F and CARB approved calculations. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
18. True vapor pressure of crude oil with an API (American Petroleum Institute) gravity less than 30 deg, as determined by API 2547, may be determined by Headspace Gas Chromatography using the procedures from CARB Evaluation of a Method for Determining Vapor Pressures of Petroleum Mixtures by Headspace Gas Chromatography, October 1990. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

19. Control efficiency shall be determined by a comparison of controlled emissions to those emissions which would occur from a fixed or cone roof tank in the same product service without a vapor recovery system. Emissions shall be determined based on tank emission factors in USEPA Publication AP-42, component counts for fugitive emissions sources, recognized emission factors for fugitive emission sources and the efficiency of any VOC destruction device. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
20. The efficiency of any VOC destruction device shall be measured by USEPA Method 25, 25a, or 25b. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
21. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
22. Operator shall determine the True Vapor Pressure and the Reid Vapor Pressure of the petroleum liquid received at the North Treating Facility (SW/4 Sec. 11, T28S, R27E) at least once per year in accordance with methods described in Section 6.2 of District Rule 4623 (amended 12/17/92). Determinations shall be made annually during summer and whenever there is a change in the source or type of petroleum entering the tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
23. The permittee shall keep accurate records of Reid Vapor Pressure, and storage temperature of liquids stored, and shall make such records available for District inspection upon request. [District Rule 1070; District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
24. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-202-7

EXPIRATION DATE: 03/31/2021

SECTION: 11 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

1,000 BBL FIXED ROOF REJECT OIL TANK (#T-2) CONNECTED TO THE VAPOR CONTROL SYSTEM LISTED ON PERMIT S-1326-201 (NORTH TREATING FACILITY).

PERMIT UNIT REQUIREMENTS

1. The Reid vapor pressure of the liquid stored in this tank shall not exceed 0.75 psia. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Tank stored liquid temperature shall not exceed 220 degrees F. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Tank shall be equipped with a stored liquid temperature indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The average daily throughput for this tank (on an annual basis) shall not exceed 12,000 bbl/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. VOC emission rate shall not exceed 5.3 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. Gas-tight shall be defined as emitting no more than 10,000 ppm of methane measured at a distance of one centimeter from the potential source with an instrument calibrated with methane in accordance with USEPA Method 21. Emissions in excess of this limit shall be considered a leak. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. Tank seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a gas-tight condition. [District Rule 2520, 9.34.2] Federally Enforceable Through Title V Permit
8. The permittee shall keep accurate records of Reid vapor pressure, storage temperature, and tank throughput and shall make such records available for District inspection upon request. [District Rules 1070 and District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
9. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with USEPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
10. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
12. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
13. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by USEPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by USEPA Method 25 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
14. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. True vapor pressure shall be measured using Reid vapor pressure ASTM Method D323 modified by maintaining the hot water bath at storage temperature. Where storage temperature is above 100 degrees F true vapor pressure shall be determined by Reid vapor pressure at 100 degrees F and CARB approved calculations. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. True vapor pressure of crude oil with an API (American Petroleum Institute) gravity less than 30 deg, as determined by API 2547, may be determined by Headspace Gas Chromatography using the procedures from CARB Evaluation of a Method for Determining Vapor Pressures of Petroleum Mixtures by Headspace Gas Chromatography, October 1990. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
18. Control efficiency shall be determined by a comparison of controlled emissions to those emissions which would occur from a fixed or cone roof tank in the same product service without a vapor recovery system. Emissions shall be determined based on tank emission factors in USEPA Publication AP-42, component counts for fugitive emissions sources, recognized emission factors for fugitive emission sources and the efficiency of any VOC destruction device. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
19. The efficiency of any VOC destruction device shall be measured by USEPA Method 25, 25a, or 25b. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
20. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
21. Operator shall determine the true vapor pressure of the petroleum liquid stored in the tank located at the beginning of the process flow after the production header at least once per year in accordance with methods described in Section 6.2 of District Rule 4623 (Amended 12/17/92). Determinations shall be made annually during summer and whenever there is a change in the source or type of petroleum entering the tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

22. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-203-8

EXPIRATION DATE: 03/31/2021

SECTION: 11 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

2,000 BBL FIXED ROOF STOCK TANK (#T-3) WITH VAPOR CONTROL LISTED ON PERMIT S-1326-201 (NORTH TREATING FACILITY)

PERMIT UNIT REQUIREMENTS

1. The Reid vapor pressure of the liquid stored in this tank shall not exceed 0.75 psia. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Tank stored liquid temperature shall not exceed 220 degrees F. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Tank shall be equipped with a stored liquid temperature indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The average daily throughput for this tank (on an annual basis) shall not exceed 7500 bbl/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. VOC emission rate shall not exceed 3.6 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. Gas-tight shall be defined as emitting no more than 10,000 ppm of methane measured at a distance of one centimeter from the potential source with an instrument calibrated with methane in accordance with USEPA Method 21. Emissions in excess of this limit shall be considered a leak. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. Tank seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a gas-tight condition. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. The permittee shall keep accurate records of Reid vapor pressure, storage temperature, and tank throughput and shall make such records available for District inspection upon request. [District Rule 1070; District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
9. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with USEPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
10. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
12. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
13. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by USEPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by USEPA Method 25 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
14. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. True vapor pressure shall be measured using Reid vapor pressure ASTM Method D323 modified by maintaining the hot water bath at storage temperature. Where storage temperature is above 100 degrees F true vapor pressure shall be determined by Reid vapor pressure at 100 degrees F and CARB approved calculations. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. True vapor pressure of crude oil with an API (American Petroleum Institute) gravity less than 30 deg, as determined by API 2547, may be determined by Headspace Gas Chromatography using the procedures from CARB Evaluation of a Method for Determining Vapor Pressures of Petroleum Mixtures by Headspace Gas Chromatography, October 1990. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
18. Control efficiency shall be determined by a comparison of controlled emissions to those emissions which would occur from a fixed or cone roof tank in the same product service without a vapor recovery system. Emissions shall be determined based on tank emission factors in USEPA Publication AP-42, component counts for fugitive emissions sources, recognized emission factors for fugitive emission sources and the efficiency of any VOC destruction device. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
19. The efficiency of any VOC destruction device shall be measured by USEPA Method 25, 25a, or 25b. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
20. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
21. Operator shall determine the true vapor pressure of the petroleum liquid stored in the tank located at the beginning of the process flow after the production header at least once per year in accordance with methods described in Section 6.2 of District Rule 4623 (Amended 12/17/92). Determinations shall be made annually during summer and whenever there is a change in the source or type of petroleum entering the tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

22. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-204-8

EXPIRATION DATE: 03/31/2021

SECTION: 11 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

2,000 BBL FIXED ROOF STOCK TANK (#T-4) WITH VAPOR CONTROL LISTED ON PERMIT S-1326-201 (NORTH TREATING FACILITY)

PERMIT UNIT REQUIREMENTS

1. The Reid vapor pressure of the liquid stored in this tank shall not exceed 0.75 psia. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Tank stored liquid temperature shall not exceed 220 degrees F. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Tank shall be equipped with a stored liquid temperature indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The average daily throughput for this tank (on an annual basis) shall not exceed 7,500 bbl/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. VOC emission rate shall not exceed 3.6 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. Gas-tight shall be defined as emitting no more than 10,000 ppm of methane measured at a distance of one centimeter from the potential source with an instrument calibrated with methane in accordance with USEPA Method 21. Emissions in excess of this limit shall be considered a leak. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. Tank seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a gas-tight condition. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. The permittee shall keep accurate records of Reid vapor pressure, storage temperature, and tank throughput and shall make such records available for District inspection upon request. [District Rule 1070; District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
9. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with USEPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
10. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
12. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
13. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by USEPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by USEPA Method 25 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
14. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. Operator shall determine the true vapor pressure of the petroleum liquid stored in the tank located at the beginning of the process flow after the production header at least once per year in accordance with methods described in Section 6.2 of District Rule 4623 (Amended 12/17/92). Determinations shall be made annually during summer and whenever there is a change in the source or type of petroleum entering the tank. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
17. True vapor pressure shall be measured using Reid vapor pressure ASTM Method D323 modified by maintaining the hot water bath at storage temperature. Where storage temperature is above 100 degrees F true vapor pressure shall be determined by Reid vapor pressure at 100 degrees F and CARB approved calculations. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
18. True vapor pressure of crude oil with an API (American Petroleum Institute) gravity less than 30 deg, as determined by API 2547, may be determined by Headspace Gas Chromatography using the procedures from CARB Evaluation of a Method for Determining Vapor Pressures of Petroleum Mixtures by Headspace Gas Chromatography, October 1990. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
19. Control efficiency shall be determined by a comparison of controlled emissions to those emissions which would occur from a fixed or cone roof tank in the same product service without a vapor recovery system. Emissions shall be determined based on tank emission factors in USEPA Publication AP-42, component counts for fugitive emissions sources, recognized emission factors for fugitive emission sources and the efficiency of any VOC destruction device. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
20. The efficiency of any VOC destruction device shall be measured by USEPA Method 25, 25a, or 25b. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
21. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-205-7

EXPIRATION DATE: 03/31/2021

SECTION: 11 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

5,000 BBL FIXED ROOF WATER TANK #T-5 WITH VAPOR CONTROL LISTED ON PERMIT S-1326-201 (NORTH TREATING FACILITY).

PERMIT UNIT REQUIREMENTS

1. The Reid vapor pressure of the liquid stored in this tank shall not exceed 0.75 psia. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Tank stored liquid temperature shall not exceed 220 degrees F. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Tank shall be equipped with a stored liquid temperature indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. Gas-tight shall be defined as emitting no more than 10,000 ppm of methane measured at a distance of one centimeter from the potential source with an instrument calibrated with methane in accordance with USEPA Method 21. Emissions in excess of this limit shall be considered a leak. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. Tank seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a gas-tight condition. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. The permittee shall keep accurate records of Reid vapor pressure, storage temperature, and tank throughput and shall make such records available for District inspection upon request. [District Rule 1070; District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with USEPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
9. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
11. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by USEPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by USEPA Method 25 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
12. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
13. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
14. True vapor pressure shall be measured using Reid vapor pressure ASTM Method D323 modified by maintaining the hot water bath at storage temperature. Where storage temperature is above 100 degrees F true vapor pressure shall be determined by Reid vapor pressure at 100 degrees F and CARB approved calculations. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
15. True vapor pressure of crude oil with an API (American Petroleum Institute) gravity less than 30 deg, as determined by API 2547, may be determined by Headspace Gas Chromatography using the procedures from CARB Evaluation of a Method for Determining Vapor Pressures of Petroleum Mixtures by Headspace Gas Chromatography, October 1990. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. Control efficiency shall be determined by a comparison of controlled emissions to those emissions which would occur from a fixed or cone roof tank in the same product service without a vapor recovery system. Emissions shall be determined based on tank emission factors in USEPA Publication AP-42, component counts for fugitive emissions sources, recognized emission factors for fugitive emission sources and the efficiency of any VOC destruction device. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. The efficiency of any VOC destruction device shall be measured by USEPA Method 25, 25a, or 25b. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
18. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
19. Operator shall determine the true vapor pressure of the petroleum liquid stored in the tank located at the beginning of the process flow after the production header at least once per year in accordance with methods described in Section 6.2 of District Rule 4623 (Amended 12/17/92). Determinations shall be made annually during summer and whenever there is a change in the source or type of petroleum entering the tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
20. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-206-8

EXPIRATION DATE: 03/31/2021

SECTION: 11 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

1,000 BBL FIXED ROOF WATER TANK (#T-6) WITH VAPOR CONTROL LISTED ON PERMIT S-1326-201 (NORTH TREATING FACILITY)

PERMIT UNIT REQUIREMENTS

1. The Reid vapor pressure of the liquid stored in this tank shall not exceed 0.75 psia. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Tank stored liquid temperature shall not exceed 220 degrees F. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Tank shall be equipped with a stored liquid temperature indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The average daily throughput for this tank (on an annual basis) shall not exceed 4000 bbl/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. VOC emission rate shall not exceed 1.9 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. Gas-tight shall be defined as emitting no more than 10,000 ppm of methane measured at a distance of one centimeter from the potential source with an instrument calibrated with methane in accordance with USEPA Method 21. Emissions in excess of this limit shall be considered a leak. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. Tank seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a gas-tight condition. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. The permittee shall keep accurate records of Reid vapor pressure, storage temperature, and tank throughput and shall make such records available for District inspection upon request. [District Rule 1070; District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
9. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with USEPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
10. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
12. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
13. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by USEPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by USEPA Method 25 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
14. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
15. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.4/3.2] Federally Enforceable Through Title V Permit
16. True vapor pressure shall be measured using Reid vapor pressure ASTM Method D323 modified by maintaining the hot water bath at storage temperature. Where storage temperature is above 100 degrees F true vapor pressure shall be determined by Reid vapor pressure at 100 degrees F and CARB approved calculations. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. True vapor pressure of crude oil with an API (American Petroleum Institute) gravity less than 30 deg, as determined by API 2547, may be determined by Headspace Gas Chromatography using the procedures from CARB Evaluation of a Method for Determining Vapor Pressures of Petroleum Mixtures by Headspace Gas Chromatography, October 1990. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
18. Control efficiency shall be determined by a comparison of controlled emissions to those emissions which would occur from a fixed or cone roof tank in the same product service without a vapor recovery system. Emissions shall be determined based on tank emission factors in USEPA Publication AP-42, component counts for fugitive emissions sources, recognized emission factors for fugitive emission sources and the efficiency of any VOC destruction device. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
19. The efficiency of any VOC destruction device shall be measured by USEPA Method 25, 25a, or 25b. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
20. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
21. Operator shall determine the true vapor pressure of the petroleum liquid stored in the tank located at the beginning of the process flow after the production header at least once per year in accordance with methods described in Section 6.2 of District Rule 4623 (Amended 12/17/92). Determinations shall be made annually during summer and whenever there is a change in the source or type of petroleum entering the tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

22. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-212-8

EXPIRATION DATE: 03/31/2021

SECTION: 11 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

2,000 BBL FIXED ROOF SURGE TANK #ST-1 WITH VAPOR CONTROL LISTED ON PERMIT S-1326-201 (NORTH TREATING FACILITY).

PERMIT UNIT REQUIREMENTS

1. The Reid vapor pressure of the liquid stored in this tank shall not exceed 0.75 psia. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Tank stored liquid temperature shall not exceed 220 degrees F. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Tank shall be equipped with a stored liquid temperature indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Tank shall operate at a constant level. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. Gas-tight shall be defined as emitting no more than 10,000 ppm of methane measured at a distance of one centimeter from the potential source with an instrument calibrated with methane in accordance with USEPA Method 21. Emissions in excess of this limit shall be considered a leak. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. Tank seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a gas-tight condition. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of Reid vapor pressure, and storage temperature of liquids stored and shall make such records available for District inspection upon request. [District Rule 1070; District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with USEPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
9. A facility operator, upon detection of a leaking component, shall affix to that component a weatherproof readily visible tag bearing the date on which the leak is detected. The tag shall remain in place until the leaking component is repaired, reinspected and found to be in compliance with the requirements of this rule. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
10. An operator shall reinspect a component for leaks within thirty working days after the date on which the component is repaired. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Emissions from components which have been tagged by the facility operator for repair within 15 calendar days or which have been repaired and are awaiting re-inspection shall not be in violation of this permit. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
12. Any component leak shall be repaired to a leak-free condition or vented to a flare satisfying the requirements of 40 CFR 60.18 or to a vapor control device that is at least 99 percent efficient as measured by USEPA Method 25 within fifteen (15) calendar days of detection. The APCO may grant a ten (10) calendar day extension provided the operator demonstrates that necessary and sufficient actions are being taken to correct the leak within this time period. Any vapor control device, other than a flare, used to comply with this condition shall demonstrate at least 99% control efficiency as measured by USEPA Method 25 at least annually. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
13. If the leaking component is an essential part of a critical process unit which cannot be immediately shut down for repairs, the operator shall 1) Minimize the leak within 15 calendar days; and 2) If the leak which has been minimized still exceeds the concentration allowed by this permit, the essential component shall be repaired to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection. A critical process unit is any process unit which would result in the automatic shutdown of other process units if it were shut down. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
14. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
15. True vapor pressure shall be measured using Reid vapor pressure ASTM Method D323 modified by maintaining the hot water bath at storage temperature. Where storage temperature is above 100 degrees F true vapor pressure shall be determined by Reid vapor pressure at 100 degrees F and CARB approved calculations. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. True vapor pressure of crude oil with an API (American Petroleum Institute) gravity less than 30 deg, as determined by API 2547, may be determined by Headspace Gas Chromatography using the procedures from CARB Evaluation of a Method for Determining Vapor Pressures of Petroleum Mixtures by Headspace Gas Chromatography, October 1990. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. Control efficiency shall be determined by a comparison of controlled emissions to those emissions which would occur from a fixed or cone roof tank in the same product service without a vapor recovery system. Emissions shall be determined based on tank emission factors in USEPA Publication AP-42, component counts for fugitive emissions sources, recognized emission factors for fugitive emission sources and the efficiency of any VOC destruction device. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
18. The efficiency of any VOC destruction device shall be measured by USEPA Method 25, 25a, or 25b. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
19. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
20. Operator shall determine the true vapor pressure of the petroleum liquid stored in the tank located at the beginning of the process flow after the production header at least once per year in accordance with methods described in 40 CFR 60.113 and Section 6.2 of District Rule 4623 (Amended 12/17/92). Determinations shall be made annually during summer and whenever there is a change in the source or type of petroleum entering the tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
21. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-214-8

EXPIRATION DATE: 03/31/2021

SECTION: NE 23 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

2000 BBL FIXED-ROOF STOCK TANK SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1326-46 (FANO LEASE)

PERMIT UNIT REQUIREMENTS

1. Tank vapors shall be vented only to vapor control system listed on tank permit S-1326-46. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The true vapor pressure of the liquids stored in this tank shall not exceed 0.5 psia. [District Rules 4623, 4.4 and 2201] Federally Enforceable Through Title V Permit
3. Vapor control efficiency shall be maintained at no less than 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Fuel gas system gas shall consist primarily of methane containing no more than 5% by weight hydrocarbons heavier than butane and shall have a sulfur content of no more than 0.75 gr/100 scf. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The tank pressure relief valves shall not open unless the tank internal pressure exceeds 2.0 oz. or falls below 0.5 oz. vacuum. [District Rule 2201] Federally Enforceable Through Title V Permit
6. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor recovery system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed. Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor recovery system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3 V / Q$, where t = time, V = tank volume (cubic feet), and Q = flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the procedure used to vent tank vapors prior to opening, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
11. To qualify for quantification of no fugitive emissions, operator shall conduct quarterly gas sampling after TVR compressor (prior to connection to any other vapor control system) and at either the first line tank or at any secondary tank which is heated above ambient temperature. If gas samples are less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually and whenever there is a change in source or type of petroleum processed. Samples shall be collected during periods of normal operation, and not be within 48 hours after routine maintenance or repair. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Permittee shall provide the District with written notification at least 30 days prior to installation of components handling fluid streams with a VOC content of 10% or less by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. Gas-tight shall be defined as emitting no more than 10,000 ppm of methane measured at a distance of one centimeter from the potential source with an instrument calibrated with methane in accordance with USEPA Method 21. Emissions in excess of this limit shall be considered a leak. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
14. All tank seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a gas-tight condition. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
15. The permittee shall keep accurate records of liquids stored and true vapor pressure of such liquids. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
17. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
18. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
19. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
20. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
21. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

22. Control efficiency shall be determined by a comparison of controlled emissions to those emissions which would occur from a fixed or cone roof tank in the same product service without a vapor recovery system. Emissions shall be determined based on tank emission factors in USEPA Publication AP-42, component counts for fugitive emissions sources, recognized emission factors for fugitive emission sources and the efficiency of any VOC destruction device. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
23. The operator shall ensure that the vapor control system is functional and is operating as designed at all times, except during periods of routine maintenance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
24. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids store in this unit to determine which oil are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
25. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-215-8

EXPIRATION DATE: 03/31/2021

SECTION: NE 23 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

3000 BBL FIXED-ROOF WASH TANK SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1326-46 (FANO LEASE)

PERMIT UNIT REQUIREMENTS

1. The true vapor pressure of the liquids stored in this tank shall not exceed 0.5 psia. [District Rule 2201 and District Rule 4623, 4.4] Federally Enforceable Through Title V Permit
2. Vapor control efficiency shall be maintained at no less than 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Fuel gas system gas shall consist primarily of methane containing no more than 5% by weight hydrocarbons heavier than butane and shall have a sulfur content of no more than 0.75 gr/100 scf. [District Rule 2201] Federally Enforceable Through Title V Permit
4. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor recovery system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed. Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor recovery system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3 V / Q$, where t = time, V = tank volume (cubic feet), and Q = flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the procedure used to vent tank vapors prior to opening, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. To qualify for quantification of no fugitive emissions, operator shall conduct quarterly gas sampling after TVR compressor (prior to connection to any other vapor control system) and at either the first line tank or at any secondary tank which is heated above ambient temperature. If gas samples are less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually and whenever there is a change in source or type of petroleum processed. Samples shall be collected during periods of normal operation, and not be within 48 hours after routine maintenance or repair. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Permittee shall provide the District with written notification at least 30 days prior to installation of components handling fluid streams with a VOC content of 10% or less by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. Gas-tight shall be defined as emitting no more than 10,000 ppm of methane measured at a distance of one centimeter from the potential source with an instrument calibrated with methane in accordance with USEPA Method 21. Emissions in excess of this limit shall be considered a leak. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
12. All tank seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a gas-tight condition. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
13. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
14. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
15. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
16. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
17. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
18. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
19. Control efficiency shall be determined by a comparison of controlled emissions to those emissions which would occur from a fixed or cone roof tank in the same product service without a vapor recovery system. Emissions shall be determined based on tank emission factors in USEPA Publication AP-42, component counts for fugitive emissions sources, recognized emission factors for fugitive emission sources and the efficiency of any VOC destruction device. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
20. The operator shall ensure that the vapor control system is functional and is operating as designed at all times, except during periods of routine maintenance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
21. All records required to be maintained by this permit shall be maintained for a period of at least 5 years and shall be made readily available for District inspection upon request. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-263-26

EXPIRATION DATE: 03/31/2021

SECTION: SW23 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

3,000 BBL FIXED ROOF WASH TANK SERVED BY TANK VAPOR CONTROL SYSTEM SHARED WITH CASING VENT RECOVERY (CVR) SYSTEM LISTED ON S-1326-287 AND CRUDE OIL STORAGE TANKS S-1326-263, -279, -280, -281, -283, -285, AND '-315 (SECTION 23 FACILITY)

PERMIT UNIT REQUIREMENTS

1. Collected TVR vapors shall be disposed of in a Department of Oil, Gas and Geothermal Resources (DOGGR) approved vapor disposal well, injected into the field fuel gas system and used in permit exempt equipment, or combusted in steam generators S-1326-9, '-294, '-314, '-337, '-338, '385, '-390, '-391, '-392, '-400, '-401, and '-419 through '-425. [District Rules 2020 and 2201] Federally Enforceable Through Title V Permit
2. VOC content of tank vapor space and vapor control system piping and components shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Prior to injecting collected TVR (and S-1326-287 CVR) vapors into field fuel gas system, the collected vapors shall be treated by a hydrogen sulfide removal system which reduces the hydrogen sulfide concentration in the collected vapors by at least 95%. The sulfur content of the treated vapors may not exceed 1.0 grains S/ 100 scf gas. The treated TVR (and CVR) vapors injected into the field fuel gas line shall not be greater than five percent by weight hydrocarbons heavier than butane as determined by test method ASTM D-1945 or equivalent test method with prior District approval. [District Rules 2020 and 2201] Federally Enforceable Through Title V Permit
4. Operator shall ensure the vapor control system is functional and operating as designed at all times, except during periods of routine maintenance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. The tank shall be equipped with a vapor loss prevention system capable of collecting all VOC emissions and preventing their emissions to the atmosphere at an efficiency of at least 99% by weight. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. The true vapor pressure of the liquids stored in this tank shall not exceed 0.5 psia. [District Rules 4623, 4.4 and 2201] Federally Enforceable Through Title V Permit
7. Connections between this TVR system and the wellhead casing vent recovery (CVR) system listed on S-1326-287 shall be made upstream of the hydrogen sulfide removal system included in this permit. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit
9. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Prior to opening the tank to allow tank cleaning, one of the following procedures must be followed: 1) Prior to venting the tank to the atmosphere, operate the tank vapor recovery system/vapor control device for at least 24 hours such that it collects the tank vapors; or 2) use liquid displacement, conducted using a liquid with a TVP less than 0.5 psia, or conducted by floating the oil pad off a crude oil tank by restricting the outflow of water, such that 90% of the tank volume is displaced; or 3) Vent the tank to a vapor control device/vapor recovery system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3 V/Q$, where t = time, V = tank volume (cubic feet), and Q = flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit
11. The tank shall be cleaned using one of the following methods: water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment may be used for road mix as allowed by Section 6.17 of District Rule 2020. [District Rule 2080] Federally Enforceable Through Title V Permit
12. Steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit
13. Prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2080] Federally Enforceable Through Title V Permit
14. Within 48 hours after refilling the tank with crude oil/water, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
15. Permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the procedure used to vent tank vapors prior to opening, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit
16. Operator shall conduct quarterly gas sampling after TVR compressor (prior to connection to any other vapor control system) and at either the first line tank or at any secondary tank which is heated above ambient temperature. If gas samples are less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually and whenever there is a change in source or type of petroleum processed. Samples shall be collected during periods of normal operation, and not be within 48 hours after routine maintenance or repair. [District Rule 2201] Federally Enforceable Through Title V Permit
17. VOC content of gas shall be measured using ASTM D-1945, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rule 2201] Federally Enforceable Through Title V Permit
18. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
19. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
20. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
22. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
23. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
24. The permittee shall keep accurate records of VOC content of vapors, liquids stored and true vapor pressure of such liquids for a period of 5 years and shall make such records available for District inspection upon request. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
25. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-268-7

EXPIRATION DATE: 03/31/2021

SECTION: SW11 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

5,000 BBL FIXED ROOF SURGE/FWKO TANK #T-12 WITH VAPOR CONTROL LISTED ON PERMIT S-1326-201 (NORTH TREATING FACILITY).

PERMIT UNIT REQUIREMENTS

1. The Reid vapor pressure of liquids stored shall not exceed 1.84 psia. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Tank stored liquid temperature shall not exceed 220 degrees F. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Tank shall be equipped with a stored liquid temperature indicator. [District Rule 2080] Federally Enforceable Through Title V Permit
4. VOC emissions shall not exceed 2.6 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Tank shall be operated at a constant level. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device that reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623] Federally Enforceable Through Title V Permit
7. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
8. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623] Federally Enforceable Through Title V Permit
9. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
10. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
16. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
17. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 4623,] Federally Enforceable Through Title V Permit
18. The permittee shall keep accurate records of Reid vapor pressure, and storage temperature of liquids stored, and shall make such records readily available for District inspection upon request. [District Rule 1070; District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
19. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623 and District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-270-6

EXPIRATION DATE: 03/31/2021

SECTION: SW11 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

1,000 BBL FIXED ROOF OIL TREATING TANK #TS-1 WITH VAPOR CONTROL LISTED ON PERMIT S-1326-201 (NORTH TREATING FACILITY).

PERMIT UNIT REQUIREMENTS

1. The Reid vapor pressure of the liquid stored in this tank shall not exceed 0.75 psia. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Tank stored liquid temperature shall not exceed 220 degrees F. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Tank shall be equipped with a stored liquid temperature indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The average daily throughput for this tank (on an annual basis) shall not exceed 2500 bbl/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. VOC emission rate shall not exceed 1.3 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device that reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623] Federally Enforceable Through Title V Permit
7. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
8. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623] Federally Enforceable Through Title V Permit
9. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
10. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
16. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
17. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 4623,] Federally Enforceable Through Title V Permit
18. The permittee shall keep accurate records of Reid vapor pressure, storage temperature, and tank throughput, and shall make such records available for District inspection upon request. [District Rules 1070; District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
19. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rules 4623 and 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-271-6

EXPIRATION DATE: 03/31/2021

SECTION: SW11 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

500 BBL FIXED ROOF DEHYDRATION TANK #TS-2 WITH VAPOR CONTROL LISTED ON PERMIT S-1326-201 (NORTH TREATING FACILITY).

PERMIT UNIT REQUIREMENTS

1. The Reid vapor pressure of the liquid stored in this tank shall not exceed 0.75 psia. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Tank stored liquid temperature shall not exceed 220 degrees F. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Tank shall be equipped with a stored liquid temperature indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The average daily throughput for this tank (on an annual basis) shall not exceed 1,000 bbl/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device that reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623] Federally Enforceable Through Title V Permit
6. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
7. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623] Federally Enforceable Through Title V Permit
8. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
9. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
10. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
16. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 4623,] Federally Enforceable Through Title V Permit
17. The permittee shall keep accurate records of Reid vapor pressure, and storage temperature of liquids stored, and shall make such records available for District inspection upon request. [District Rules 1070 and District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
18. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rules 4623 and 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-272-6

EXPIRATION DATE: 03/31/2021

SECTION: SW11 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

1,000 BBL FIXED ROOF WATER TANK #TS-3 WITH VAPOR CONTROL LISTED ON PERMIT S-1326-201 (NORTH TREATING FACILITY).

PERMIT UNIT REQUIREMENTS

1. The Reid vapor pressure of the liquid stored in this tank shall not exceed 0.75 psia. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Tank stored liquid temperature shall not exceed 220 degrees F. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Tank shall be equipped with a stored liquid temperature indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The average daily throughput for this tank (on an annual basis) shall not exceed 5000 bbl/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. VOC emission rate shall not exceed 2.3 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device that reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623] Federally Enforceable Through Title V Permit
7. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
8. A gas-tight condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623] Federally Enforceable Through Title V Permit
9. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
10. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
16. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
17. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 4623,] Federally Enforceable Through Title V Permit
18. The permittee shall keep accurate records of Reid vapor pressure, storage temperature, and tank throughput, and shall make such records available for District inspection upon request. [District Rule 1070; District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
19. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rules 4623 and 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-273-3

EXPIRATION DATE: 03/31/2021

SECTION: SW22 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

110 BBL FIXED ROOF CRUDE OIL SKIM TANK (ROBINSON B LEASE, KERN FRONT OIL FIELD)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
6. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
7. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
8. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-274-5

EXPIRATION DATE: 03/31/2021

SECTION: SW11 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

1000 BBL FIXED ROOF SLOP OIL TANK (# TS-8) WITH VAPOR CONTROL LISTED ON PERMIT S-1326-201.

PERMIT UNIT REQUIREMENTS

1. The Reid vapor pressure of the liquid stored in this tank shall not exceed 0.75 psia. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Tank stored liquid temperature shall not exceed 220 degrees F. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Tank shall be equipped with a stored liquid temperature indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The average daily throughput for this tank (on an annual basis) shall not exceed 970 bbl/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device that reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.7. [District Rule 4623] Federally Enforceable Through Title V Permit
6. All piping, valves, and fittings shall be constructed and maintained in a Leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
7. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623] Federally Enforceable Through Title V Permit
8. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
9. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
10. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
14. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
15. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
16. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 4623,] Federally Enforceable Through Title V Permit
17. The permittee shall maintain accurate records of Reid vapor pressure, and storage temperature of liquids stored, and shall make such records available for District inspection upon request. [District Rules 1070, 2520, 9.5.2, and 4623] Federally Enforceable Through Title V Permit
18. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rules 4623 and 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-279-7

EXPIRATION DATE: 03/31/2021

SECTION: SW23 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

5000 BBL FREE WATER KNOCKOUT STORAGE TANK SERVED BY VAPOR CONTROL SYSTEM LISTED ON S-1326-263

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The true vapor pressure of the liquids stored in this tank shall not exceed 0.5 psia. [District Rules 4623,4.4] Federally Enforceable Through Title V Permit
3. Vapor control efficiency shall be maintained at no less than 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The permittee shall keep accurate records of liquids stored and true vapor pressure of such liquids. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor recovery system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed. Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor recovery system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3 V / Q$, where t = time, V = tank volume (cubic feet), and Q = flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the procedure used to vent tank vapors prior to opening, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. To qualify for quantification of no fugitive emissions, operator shall conduct quarterly gas sampling after TVR compressor (prior to connection to any other vapor control system) and at either the first line tank or at any secondary tank which is heated above ambient temperature. If gas samples are less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually and whenever there is a change in source or type of petroleum processed. Samples shall be collected during periods of normal operation, and not be within 48 hours after routine maintenance or repair. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Permittee shall provide the District with written notification at least 30 days prior to installation of components handling fluid streams with a VOC content of 10% or less by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. Gas-tight shall be defined as emitting no more than 10,000 ppm of methane measured at a distance of one centimeter from the potential source with an instrument calibrated with methane in accordance with USEPA Method 21. Emissions in excess of this limit shall be considered a leak. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
13. All tank seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a gas-tight condition. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
14. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
15. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
16. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
17. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4] Federally Enforceable Through Title V Permit
18. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
19. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623, 6.3.6] Federally Enforceable Through Title V Permit
20. Control efficiency shall be determined by a comparison of controlled emissions to those emissions which would occur from a fixed or cone roof tank in the same product service without a vapor recovery system. Emissions shall be determined based on tank emission factors in USEPA Publication AP-42, component counts for fugitive emissions sources, recognized emission factors for fugitive emission sources and the efficiency of any VOC destruction device. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
21. The operator shall ensure that the vapor control system is functional and is operating as designed at all times, except during periods of routine maintenance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
22. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rules 2520, 9.4.2 and 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-287-17

EXPIRATION DATE: 03/31/2021

SECTION: SW23 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

THERMALLY ENHANCED OIL RECOVERY OPERATION WITH 1085 STEAM ENHANCED PRODUCTION WELLS CONNECTED TO WELL HEAD CASING VENT VAPOR RECOVERY SYSTEM (CVR) VENTING VAPORS TO SECTION 23 TANK VAPOR RECOVERY SYSTEM (S-1326-263)

PERMIT UNIT REQUIREMENTS

1. The TEOR operation shall be located within Sections: 22, 23, 24, 25 and 26, Township: 28S, Range: 27E [District Rule 2201] Federally Enforceable Through Title V Permit
2. Well casing vents shall remain closed, connected to well produced fluids lines, or connected to a well vent VOC collection and control system at all times except during periods of actual service or repair when wells are not producing. [District Rules 2201 and 4401] Federally Enforceable Through Title V Permit
3. Collected CVR vapor shall be piped to tank vapor recovery system (TVR) serving S-1326-263. [District Rule 2201] Federally Enforceable Through Title V Permit
4. VOC content of gas collected by the CVR system shall not exceed 10% by weight. Permittee shall maintain a written record of VOC content (sampled not less than annually) and shall make such records available for District inspection upon request for a period of five years. Permittee may use test results obtained from S-1326-263 to demonstrate compliance. [District Rule 2201 and District Rule 4401] Federally Enforceable Through Title V Permit
5. Operator shall conduct quarterly gas sampling for gas exiting the separator pressure vessel to qualify for exemption from fugitive component counts for components handling fluids with VOC content equal to or less than 10% by weight. If gas samples are equal to or less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually. [District Rule 2201 and 4401] Federally Enforceable Through Title V Permit
6. Fluids produced from these steam enhanced wells shall be introduced only to tanks listed on permit S-1326-263 that are vented to an approved vapor collection and control system achieving 99% control. [District Rule 2201] Federally Enforceable Through Title V Permit
7. An operator shall not operate a steam-enhanced crude oil production well unless the operator complies with the following requirements: The steam-enhanced crude oil production well vent is closed and the front line production equipment downstream of the wells that carry produced fluids (crude oil or mixture of crude oil and water) is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401, the well vent may be temporarily opened during periods of attended service or repair of the well provided such activity is done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere, the steam-enhanced crude oil production well vent is open and the well vent is connected to a VOC collection and control system as defined in Section 3.0 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit
8. Steam enhanced production wells covered by this permit shall each have a visible identification number. Field personnel shall be provided with written instructions concerning proper operation and maintenance of these wells. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. The crude oil production from wells associated with this permit unit shall not lie within 1000 feet of an air injection well used for in-situ combustion. [District Rule 4407] Federally Enforceable Through Title V Permit
10. Total combined fugitive emissions from all components associated with this TEOR operation shall not exceed 0.0 lb VOC/ day. [District Rule 2201] Federally Enforceable Through Title V Permit
11. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401, 5.0 (as amended June 16, 2011). [District Rule 4401] Federally Enforceable Through Title V Permit
12. The operator shall maintain monitoring records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401] Federally Enforceable Through Title V Permit
13. Gas and liquid leaks are as defined in Section 3.20 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit
14. A gas leak is defined as the detection of a concentration of total organic compounds, above background (measured in accordance with EPA Method 21) that exceeds the following values: 1) A major gas leak is a detection of greater than 10,000 ppmv as methane; and 2) A minor gas leak is a detection of 400 to 10,000 ppmv as methane for pressure relief devices (PRDs) and 2,000 to 10,000 for components other than PRDs. [District Rule 4401] Federally Enforceable Through Title V Permit
15. A liquid leak is defined as the dripping of VOC-containing liquid. A major liquid leak is a visible mist or a continuous flow of liquid that is not seal lubricant. A minor liquid leak is a liquid leak that is not a major liquid leak and drips liquid at a rate of more than three drops per minute, except for seal lubricant. [District Rule 4401] Federally Enforceable Through Title V Permit
16. Operator shall affix a readily visible tag bearing the date on which a leak is detected. The tag shall remain in place until the leaking component is repaired. [District Rule 4401] Federally Enforceable Through Title V Permit
17. An operator shall not use any component with a leak as defined in Section 3.0 of Rule 4401, or that is found to be in violation of the provisions of Section 5.2.2 of Rule 4401. However, components that were found leaking may be used provided such leaking components have been identified with a tag for repair, are repaired, or awaiting re-inspection after being repaired within the applicable time frame specified in Section 5.5 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit
18. An operator shall comply with the requirements of Section 6.7 of Rule 4401 if there is any change in the description of major components or critical components. [District Rule 4401] Federally Enforceable Through Title V Permit
19. An operator shall be in violation of this rule if any District inspection demonstrates that the following conditions in Section 5.2.2 exist at the facility: Existence of an open-ended line or a valve located at the end of the line that is not sealed with a blind flange, plug, cap, or a second closed valve that is not closed at all times, except during attended operations as defined by Section 5.2.2.1 of Rule 4401 requiring process fluid flow through the open-ended lines. [District Rule 4401] Federally Enforceable Through Title V Permit
20. An operator shall be in violation of this rule if any District inspection demonstrates that one or more of the following conditions exist at the facility: existence of a component with any of the following: a major liquid leak, a gas leak greater than 50,000 ppmv, a minor liquid leak or a minor gas leak in excess of the allowable number of leaks allowed by Table 3 of Rule 4401, or a gas leak greater than 10,000 ppmv up to 50,000 ppmv in excess of the allowable number of leaks allowed by Table 3 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit
21. Permittee shall keep all hatches closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4401]
22. Permittee shall affix a readily visible weatherproof tag to a leaking component upon detection of the leak. The following information shall be included on the tag: 1) the date and time of leak detection; 2) the date and time of leak measurement; 3) leak concentration in ppmv for a gaseous leak; 4) description of whether it is a major liquid leak or a minor liquid leak; and 5) whether the component is an essential component, an unsafe-to-monitor component, or a critical component. [District Rule 4401] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

23. Permittee shall keep the tag affixed to the component until all of the following conditions have been met: 1) the leaking component has been repaired or replaced, and 2) the component has been re-inspected using the test methods described in this permit; and 3) the component is found to be in compliance with the requirements of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit
24. Permittee shall minimize a component leak in order to stop or reduce leakage to the atmosphere immediately to the extent possible, but not later than one (1) hour after detection of the leak. [District Rule 4401] Federally Enforceable Through Title V Permit
25. Except for leaking critical components or leaking essential components, if the operator has minimized a leak but the leak still exceeds the applicable leak limits, the operator shall comply with at least one of the following requirements as soon as practicable but not later than the time period specified in Table 4 of Rule 4401: 1) repair or replace the leaking component; 2) vent the leaking component to a VOC collection and control system; or 3) remove the leaking component from operation. [District Rule 4401] Federally Enforceable Through Title V Permit
26. The leak rate, measured after leak minimization has been performed, shall be used to determine the applicable repair period specified in Table 4 of Rule 4401 and the time of initial leak detection shall be the start of the repair period specified in Table 4 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit
27. If the leaking component is an essential component or a critical component that cannot be immediately shut down for repairs, and if the leak has been minimized but the leak still exceeds the applicable leak standard of this rule, the operator shall repair or replace the essential component or critical component to eliminate the leak during the next process unit turnaround, but in no case later than one year from the date of the original leak detection, whichever comes earlier. [District Rule 4401] Federally Enforceable Through Title V Permit
28. Flanges shall be monitored with a portable hydrocarbon detection instrument along the entire circumference of the flange-gasket interface. Threaded connections, tubing fittings, and other types of non-permanent joints shall be monitored along the entire circumference of joint interface. [District Rule 2201] Federally Enforceable Through Title V Permit
29. Valves shall be monitored with a portable hydrocarbon detection instrument where the stem comes through the packing gland, and at any attached or connected body flange(s), bonnet flange(s), or plug(s). [District Rule 2201] Federally Enforceable Through Title V Permit
30. All other components such as diaphragms, dump arms, instruments, meters shall be monitored at all points of possible emissions. [District Rule 2201] Federally Enforceable Through Title V Permit
31. In lieu of conducting annual source tests of all vapor collection and control systems used to control emissions from steam-enhanced crude oil production well vents to determine the control efficiency of the device(s) used for destruction or removal of VOC, all uncondensed VOC emissions collected by a vapor collection and control system shall be incinerated in fuel burning equipment, an internal combustion engine or in a smokeless flare. [District Rule 4401] Federally Enforceable Through Title V Permit
32. An operator shall comply with the following requirements for each gauge tank, as defined in Section 3.0 of Rule 4401: Conduct periodic TVP testing of each gauge tank at least once every 24 months during summer (July - September), and whenever there is a change in the source or type of produced fluid in the gauge tank, the TVP testing shall be conducted at the actual storage temperature of the produced fluid in the gauge tank using the applicable TVP test method specified in Section 6.4 of Rule 4623 (Storage of Organic Liquids). The operator shall submit the TVP testing results to the APCO as specified in Section 6.1.9 of Rule 4401. [District Rule 4401] Federally Enforceable Through Title V Permit
33. The control efficiency of the vapor collection and control system used to control VOC emissions from steam enhanced crude oil production well shall be determined by mass balance based on most stringent of a source test, USEPA approved emission factors, or Air Pollution (AP)-42 emission factors for components and number of components; and the efficiency of destruction devices determined by USEPA Method 25, 25a, or 25b as applicable. [District Rule 4401] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

34. The VOC content by weight percent (wt.%) shall be determined using American Society of Testing and Materials (ASTM) D1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 or the latest revision of ASTM Method E168, E169 or E260 for liquids. Halogenated exempt compounds shall be determined by CARB Method 432. [District Rule 4401] Federally Enforceable Through Title V Permit
35. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: County Rules 108 (Kings), 108.1 (Fresno, Merced, San Joaquin, Tulare, Kern, and Stanislaus), and 110 (Madera). A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit
36. Compliance with permit conditions in the Title V permit shall be deemed compliance with SJVUAPCD Rule 4401 (Amended January 15, 1998), excluding sections 5.1 and 5.2 for control systems which have been waived from complying with the requirement of section 6.2.1. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit
37. The requirements of SJVUAPCD Rule 4407 (Adopted May 19, 1994) do not apply to this permit unit. A permit shield is granted from this requirement. [District Rule 2520] Federally Enforceable Through Title V Permit
38. Permittee shall maintain a copy of the latest APCO-approved Operator Management Plan (OMP) at the facility and make it available to the APCO, ARB, and US EPA upon request. [District Rule 4401] Federally Enforceable Through Title V Permit
39. By January 30 of each year, permittee shall submit to the APCO for approval, in writing, an annual report indicating any changes to the existing, approved OMP. [District Rule 4401] Federally Enforceable Through Title V Permit
40. Permittee shall maintain a current list of all steam enhanced wells authorized by this permit and shall update the list whenever a well is added, replaced, or deleted. [District Rule 2201] Federally Enforceable Through Title V Permit
41. Permittee shall maintain an accurate component count for the well vent collection and control system serving this operation, in accordance with CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors. Permittee shall update such records when new components are installed. [District Rule 2201] Federally Enforceable Through Title V Permit
42. All records required by this permit shall be maintained and retained on-site for a minimum of five (5) years and made available for District, ARB, and EPA inspection upon request. [District Rule 4401] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-294-9

EXPIRATION DATE: 03/31/2021

SECTION: SE23 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

62.5 MMBTU/HR NATURAL GAS-FIRED STRUTHERS STEAM GENERATOR WITH A NORTH AMERICAN MAGNA-FLAME G-LE ULTRA LOW NOX BURNER AND A FLUE GAS RECIRCULATION (FGR) SYSTEM

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. The unit shall only be fired on PUC-quality natural gas and scrubbed TEOR and TVR gas from S-1326-26, '-27, '-28, '-35 and '-263 with a sulfur content no greater than 1 gr S/100 scf. [District Rules 2201, 4301, 4320, 4406, and 4801] Federally Enforceable Through Title V Permit
4. Emission rates shall not exceed: PM10: 0.003 lb/MMBtu, VOC: 0.0055 lb/MMBtu, NOx (as NO2): 7 ppmvd NOx @ 3% O2, or CO: 75 ppmv @ 3% O2. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
5. Permittee shall test annually the sulfur content of the fuel gas combusted in steam generator and make test results readily available for District inspection. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit
6. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. Unless otherwise specified in the Permit to Operate, no determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
8. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
9. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
10. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The following test methods shall be used: NO_x (ppmv) - EPA Method 7E or ARB Method 100, NO_x (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, stack gas moisture content - EPA Method 4, stack gas velocities - EPA Method 2, fuel gas sulfur content - ASTM D1072, ASTM 3031, ASTM 4084, ASTM D3246, ASTM D6228 (GC-FPD) or double GC for H₂S and mercaptans. [District Rules 1081, 4305, 4306, 6.2, 4320, and 4351] Federally Enforceable Through Title V Permit
12. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. The permittee shall monitor and record the stack concentration of NO_x, CO, and O₂ at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
14. If either the NO_x or CO concentrations corrected to 3% O₂, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
15. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
16. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
17. Permittee shall maintain daily records of the type and quantity of fuel combusted by the steam generator. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
18. The permittee shall maintain records of: (1) the date and time of NO_x, CO, and O₂ measurements, (2) the O₂ concentration in percent and the measured NO_x and CO concentrations corrected to 3% O₂, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
19. Permittee shall maintain records of fuel gas sulfur compound measurements. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
20. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 1070, 4305, 4306, 4320, and 40 CFR 60.48c (i)] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-314-6

EXPIRATION DATE: 03/31/2021

SECTION: 23 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

85.0 MMBTU/HR STRUTHERS NATURAL GAS-FIRED STEAM GENERATOR WITH A NORTH AMERICAN MODEL MAGNA-FLAME G-LE ULTRA ULTRA-LOW NOX BURNER WITH FLUE GAS RECIRCULATION (FGR) AND AN O2 CONTROLLER

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The unit shall only be fired on PUC-quality natural gas and scrubbed TEOR and TVR gas from S-1326-26, '-27, '-28, '-35 and '-263 with a sulfur content no greater than 1 gr S/100 scf. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
3. Permittee shall test annually the sulfur content of the fuel gas combusted in steam generator using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit
4. Emissions rates from unit shall not exceed any of the following limits: 7 ppmv NOx @ 3% O2 or 0.008 lb-NOx/MMBtu, 0.00300 lb-PM10/MMBtu, 35 ppmv CO @ 3% O2 or 0.026 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4301, 5.2, 4305, 5.1, and 4306, 5.1, 4320, and 40 CFR 60.43c(e)(1)] Federally Enforceable Through Title V Permit
5. Source testing to measure NOx, and CO emissions from this unit while fired on natural gas shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3.1, 4306, 6.3.1, and 4320] Federally Enforceable Through Title V Permit
6. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. Unless otherwise specified in the Permit to Operate, no determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 5.5.2, 4306, 5.5.2, and 4320] Federally Enforceable Through Title V Permit
7. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
8. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
9. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5.1, 4306, 5.5.1, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5, 4306, 5.5.5, and 4320] Federally Enforceable Through Title V Permit
11. The following test methods shall be used: NO_x (ppmv) - EPA Method 7E or ARB Method 100, NO_x (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, stack gas moisture content - EPA Method 4, stack gas velocities - EPA Method 2, and fuel gas sulfur content - ASTM D1072, ASTM D3246, ASTM D6228 (GC-FPD) or double GC for H₂S and mercaptans. [District Rule 1081, 4305, 4306, 6.2, 4320, and 4351] Federally Enforceable Through Title V Permit
12. The permittee shall monitor and record the stack concentration of NO_x, CO, and O₂ at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4, 4306, 5.4, and 4320] Federally Enforceable Through Title V Permit
13. If either the NO_x or CO concentrations corrected to 3% O₂, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4, 4306, 5.4, and 4320] Federally Enforceable Through Title V Permit
14. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4, 4306, 5.4, and 4320] Federally Enforceable Through Title V Permit
15. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
16. Permittee shall maintain daily records of the type and quantity of fuel combusted by the steam generator. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
17. The permittee shall maintain records of: (1) the date and time of NO_x, CO, and O₂ measurements, (2) the O₂ concentration in percent and the measured NO_x and CO concentrations corrected to 3% O₂, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1, 4306, 6.1, and 4320] Federally Enforceable Through Title V Permit
18. Permittee shall maintain records of fuel gas sulfur compound measurements. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
19. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 1070, 4305, 4306, 4320, and 40 CFR 60.48c (i)] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-315-2

EXPIRATION DATE: 03/31/2021

EQUIPMENT DESCRIPTION:

20,000 BBL FWKO VENTED TO VAPOR CONTROL SYSTEM LISTED ON S-1326-263

PERMIT UNIT REQUIREMENTS

1. Vapor control efficiency shall be maintained at no less than 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
2. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
3. Permittee shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623] Federally Enforceable Through Title V Permit
4. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623] Federally Enforceable Through Title V Permit
5. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623] Federally Enforceable Through Title V Permit
6. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. The permittee shall also conduct an API gravity testing. [District Rule 4623] Federally Enforceable Through Title V Permit
7. This permit authorizes FWKO cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2080] Federally Enforceable Through Title V Permit
8. Permittee shall conduct FWKO cleaning and maintenance operations in accordance with District approved procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit
9. FWKO may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit
10. Permittee shall notify the District Compliance Division at least 24 hours before FWKO cleaning and vapor control system disconnection and within 72 hours after restoring crude oil flow to the FWKO. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Prior to opening the FWKO to allow FWKO cleaning, one of the following procedures must be followed: 1) Prior to venting the FWKO to the atmosphere, operate the FWKO vapor recovery system/vapor control device for at least 24 hours such that it collects the FWKO vapors; or 2) use liquid displacement, conducted using a liquid with a TVP less than 0.5 psia, or conducted by floating the oil pad off a crude oil FWKO by restricting the outflow of water, such that 90% of the FWKO volume is displaced; or 3) Vent the FWKO to a vapor control device/vapor recovery system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the FWKO to the vapor control system for a length of time determined by the following relationship: $t = 2.3 V/Q$, where t = time, V = tank volume (cubic feet), and Q = flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit
12. The FWKO shall be cleaned using one of the following methods: water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The FWKO sediment may be used for road mix as allowed by Section 6.17 of District Rule 2020. [District Rule 2080] Federally Enforceable Through Title V Permit
13. Steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit
14. Prior to reintroducing crude oil/water to the FWKO, the FWKO shall be filled to the maximum possible level with water, the FWKO vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2080] Federally Enforceable Through Title V Permit
15. Within 48 hours after refilling the FWKO with crude oil/water, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA method 21 and the regular FWKO maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
16. Permittee shall maintain records of each period of cleaning and maintenance when the FWKO is disconnected or isolated from the vapor control system. Records shall include the date that FWKO cleaning was initiated, the date FWKO cleaning was completed, the procedure used to vent FWKO vapors prior to opening, the method of FWKO cleaning used, and a description of internal and external FWKO repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit
17. Operator shall conduct quarterly gas sampling after TVR compressor (prior to connection to any other vapor control system) and at either the first line tank or at any secondary tank which is heated above ambient temperature. If gas samples are less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually and whenever there is a change in source or type of petroleum processed. Samples shall be collected during periods of normal operation, and not be within 48 hours after routine maintenance or repair. [District Rule 2201] Federally Enforceable Through Title V Permit
18. VOC content of tank vapor space and vapor control system piping and components shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
19. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
20. Permittee shall maintain daily records of the type and quantity of fuel combusted by the steam generator. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
21. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
22. The permittee shall keep accurate records of each organic liquid stored in the tank, including its storage temperature, TVP, and API gravity. [District Rule 4623] Federally Enforceable Through Title V Permit
23. VOC content of gas shall be measured using ASTM D-1945, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

24. The permittee shall keep accurate records of VOC content of vapors for a period of 5 years and shall make such records available for District inspection upon request. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-337-7

EXPIRATION DATE: 03/31/2021

EQUIPMENT DESCRIPTION:

85.0 MMBTU/HR STRUTHERS NATURAL GAS-FIRED STEAM GENERATOR WITH A NORTH AMERICAN MODEL MAGNA-FLAME G-LE ULTRA ULTRA-LOW NOX BURNER WITH FLUE GAS RECIRCULATION (FGR) AND AN O2 CONTROLLER

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. The unit shall only be fired on regulated natural gas and scrubbed TEOR and TVR gas from S-1326-26, '-27, '-28, '-35 and '-263 with a sulfur content no greater than 1 gr S/100 scf. [District Rule 2201 and 4320, 5.4.1.2] Federally Enforceable Through Title V Permit
4. Permittee shall test annually the sulfur content of TEOR/TVR gas combusted in steam generator using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rule 2520, 9.4.1 and 4320, 5.7.6.1] Federally Enforceable Through Title V Permit
5. Emissions from the steam generator shall not exceed any of the following limits: 0.003 lb-PM10/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 16.3 lb-NOx/day, 5,957 lb-NOx/yr, 18.4 lb-CO/day, and 6,701 lb-CO/yr. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 7 ppmvd NOx @ 3% O2 or 0.008 lb-NOx/MMBtu or 10 ppmvd CO @ 3% O2 or 0.009 lb-CO/MMBtu. [District Rules 2201, 4301, 5.2, 4305, 5.1, 4306, 5.1, and 4320, 5.2] Federally Enforceable Through Title V Permit
8. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 4305, 5.5.6, 4306, 5.3, and 4320, 5.6] Federally Enforceable Through Title V Permit
9. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rule 4306, 3.25, 3.22, and 4320, 5.6] Federally Enforceable Through Title V Permit
10. Source testing to measure NOx and CO emissions from this unit while fired on natural gas shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3.1, 4306, 6.3.1, and 4320, 6.3.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 5.5.2, 4306, 5.5.2, and 4320, 5.8.2] Federally Enforceable Through Title V Permit
12. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5.1, 4306, 5.5.1 and 4320, 5.8.2] Federally Enforceable Through Title V Permit
13. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
14. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
15. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5, 4306, 5.5.5, and 4320, 5.8.1] Federally Enforceable Through Title V Permit
16. The following test methods shall be used: PM10 (lb/MMBtu) - EPA 201A - 202 or Method 5, NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, stack gas moisture content - EPA Method 4, stack gas velocities - EPA Method 2, and fuel gas sulfur content -EPA method 11 or method 15. [District Rule 1081, 4305, 4306, 6.2, 4320, 6.2 and 4351] Federally Enforceable Through Title V Permit
17. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4, 4306, 5.4, and 4320 2.7] Federally Enforceable Through Title V Permit
18. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4, 4306, 5.4, and 4320 5.7] Federally Enforceable Through Title V Permit
19. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4, 4306, 5.4, and 4320 6.1] Federally Enforceable Through Title V Permit
20. Permittee shall comply with all notification and recordkeeping requirements of 40 CFR 60.7 a (1)(3) and (b). [District Rule 4001] Federally Enforceable Through Title V Permit
21. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

22. Permittee shall maintain daily records of the type and quantity of fuel combusted by the steam generator. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
23. The permittee shall maintain records of: (1) the date and time of NO_x, CO, and O₂ measurements, (2) the O₂ concentration in percent and the measured NO_x and CO concentrations corrected to 3% O₂, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1, 4306, 6.1, and 4320, 6.1] Federally Enforceable Through Title V Permit
24. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 1070, 4305, 4306, 4320, and 40 CFR 60.48c (i)] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-338-7

EXPIRATION DATE: 03/31/2021

SECTION: NE23 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

85.0 MMBTU/HR STRUTHERS NATURAL GAS-FIRED STEAM GENERATOR WITH A NORTH AMERICAN MODEL MAGNA-FLAME G-LE ULTRA ULTRA-LOW NOX BURNER (OR EQUIVALENT) WITH FLUE GAS RECIRCULATION (FGR) AND AN O2 CONTROLLER

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. The unit shall only be fired on regulated natural gas and scrubbed TEOR and TVR gas from S-1326-26, '-27, '-28, '-35 and '-263 with a sulfur content no greater than 1 gr S/100 scf. [District Rule 2201 and 4320, 5.4.1.2] Federally Enforceable Through Title V Permit
4. Permittee shall test annually the sulfur content of TEOR/TVR gas combusted in steam generator using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rule 2520, 9.4.1 and 4320, 5.7.6.1] Federally Enforceable Through Title V Permit
5. Emissions from the steam generator shall not exceed any of the following limits: 0.003 lb-PM10/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 16.3 lb-NOx/day, 5,957 lb-NOx/yr, 18.4 lb-CO/day, and 6,701 lb-CO/yr. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 7 ppmvd NOx @ 3% O2 or 0.008 lb-NOx/MMBtu or 10 ppmvd CO @ 3% O2 or 0.009 lb-CO/MMBtu. [District Rules 2201, 4301, 5.2, 4305, 5.1, 4306, 5.1, and 4320, 5.2] Federally Enforceable Through Title V Permit
8. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 4305, 5.5.6, 4306, 5.3, and 4320, 5.6] Federally Enforceable Through Title V Permit
9. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rule 4306, 3.25, 3.22, and 4320, 5.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Source testing to measure NO_x and CO emissions from this unit while fired on natural gas shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3.1, 4306, 6.3.1, and 4320, 6.3.1] Federally Enforceable Through Title V Permit
11. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 5.5.2, 4306, 5.5.2, and 4320, 5.8.2] Federally Enforceable Through Title V Permit
12. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5.1, 4306, 5.5.1 and 4320, 5.8.2] Federally Enforceable Through Title V Permit
13. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
14. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
15. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5, 4306, 5.5.5, and 4320, 5.8.1] Federally Enforceable Through Title V Permit
16. The following test methods shall be used: PM₁₀ (lb/MMBtu) - EPA 201A - 202 or Method 5, NO_x (ppmv) - EPA Method 7E or ARB Method 100, NO_x (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, stack gas moisture content - EPA Method 4, stack gas velocities - EPA Method 2, and fuel gas sulfur content -EPA method 11 or method 15. [District Rule 1081, 4305, 4306, 6.2, 4320, 6.2 and 4351] Federally Enforceable Through Title V Permit
17. The permittee shall monitor and record the stack concentration of NO_x, CO, and O₂ at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4, 4306, 5.4, and 4320 2.7] Federally Enforceable Through Title V Permit
18. If either the NO_x or CO concentrations corrected to 3% O₂, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4, 4306, 5.4, and 4320 5.7] Federally Enforceable Through Title V Permit
19. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4, 4306, 5.4, and 4320 6.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

20. Permittee shall comply with all notification and recordkeeping requirements of 40 CFR 60.7 a (1)(3) and (b). [District Rule 4001] Federally Enforceable Through Title V Permit
21. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
22. Permittee shall maintain daily records of the type and quantity of fuel combusted by the steam generator. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
23. The permittee shall maintain records of: (1) the date and time of NO_x, CO, and O₂ measurements, (2) the O₂ concentration in percent and the measured NO_x and CO concentrations corrected to 3% O₂, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1, 4306, 6.1, and 4320, 6.1] Federally Enforceable Through Title V Permit
24. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 1070, 4305, 4306, 4320, and 40 CFR 60.48c (i)] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-341-2

EXPIRATION DATE: 03/31/2021

SECTION: 11 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

THERMALLY ENHANCED OIL RECOVERY OPERATION WELL VENT VAPOR CONTROL SYSTEM SERVING UP TO 50 STEAM DRIVE WELLS AND 40 CYCLIC WELLS (MOVIUS FEE LEASE)

PERMIT UNIT REQUIREMENTS

1. Permittee shall maintain a current roster of all wells connected to this system and shall make such roster available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Non condensed well vent vapors shall only be disposed of in approved incineration/disposal devices, including one 3.0 MMBtu/hr gas-fired heater and reinjection wells. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Gas being incinerated in the 3.0 MMBtu/hr heater shall not exceed 0.75 grains of total sulfur per 100 dscf and 5% by weight hydrocarbons heavier than butane. [District Rule 2020] Federally Enforceable Through Title V Permit
4. Permittee shall keep accurate records of sulfur and VOC content of gas being incinerated and shall make records readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Fugitive Volatile Organic Compound (VOC) emission limit shall not exceed 114.8 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Gas being incinerated in the 3.0 MMBtu/hr heater shall be tested annually for sulfur content value by using ASTM methods D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2020] Federally Enforceable Through Title V Permit
7. During the time any steam-enhanced crude oil production well is undergoing service or repair while the well is not producing, it shall be exempt from the emission control requirements of District Rule 4401, 5.0 (as amended January 15, 1998). [District Rule 4401, 4.1] Federally Enforceable Through Title V Permit
8. All required source testing shall conform to the compliance testing procedures described in District Rule 1081(as amended December 16, 1993). [District Rule 1081] Federally Enforceable Through Title V Permit
9. The operator shall maintain monitoring records of the date and well identification where steam injection or well stimulation occurs. [District Rule 4401, 6.1] Federally Enforceable Through Title V Permit
10. The uncontrolled VOC emissions from any well vent shall be reduced by at least 99 percent by weight or, if several steam-enhanced crude oil production well vents are connected to a vapor collection and control system, total uncontrolled VOC emissions shall be reduced by at least 99 percent. This requirement does not apply to cyclic wells located on contiguous and adjacent oil production properties with less than 10 cyclic wells owned by or under the control of a company. [District Rule 4401, 5.1 and 5.2] Federally Enforceable Through Title V Permit
11. For cyclic wells located on properties with less than 10 cyclic wells and owned by a company, the uncontrolled VOC emissions from any well vent or system of well vents connected to a single vapor collection and control device shall be reduced by at least 50 percent. Properties shall include contiguous and adjacent oil production properties owned by or under control of the company. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. Total number of leaks from the vapor collection and control system, including condensate handling, shall not exceed 8 as allowed by Rule 4401 (as amended January 15, 1998) at any one time. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit
13. Units consisting of more than 500 wells shall not exceed one leak detected for each 20 wells tested with a minimum of 50 wells tested. [District Rule 4401, 5.2] Federally Enforceable Through Title V Permit
14. Operator shall affix a readily visible tag bearing the date on which a leak is detected. The tag shall remain in place until the leaking component is repaired. [District Rule 4401, 5.4] Federally Enforceable Through Title V Permit
15. Operator shall repair each leak within 15 calendar days of detection. The APCO may grant a 10 calendar day extension if the operator demonstrates that the necessary and sufficient actions have and are being taken to correct the leak. [District Rule 4401, 5.5] Federally Enforceable Through Title V Permit
16. Operator shall maintain all components of a well vent vapor collection and control system in good repair. Components of the well vent vapor collection and control system shall include all piping, valves, fittings, pumps, compressors, tanks, etc. used to collect, control, store, or dispose of VOC condensate or non-condensable VOCs and which is prior to any blending of VOC condensate with crude oil or blending of non-condensable VOCs with gases to be used as a fuel. [District Rule 4401, 5.3] Federally Enforceable Through Title V Permit
17. Annual control efficiency compliance tests shall be performed on all vapor collection and control systems used to control emissions from steam-enhanced crude oil production wells. Testing shall be performed by source testers certified by the California Air Resources Board (CARB) during June, July, August or September of each year if the system's control efficiency is dependent upon ambient air temperature. The APCO may waive the annual testing requirements of this condition if the vapor control system does not exhaust to atmosphere or if all uncondensed VOC emissions collected by a vapor collection and control system are incinerated in fuel burning equipment, an internal combustion engine or in a smokeless open flare, and the source's Operating Permit contains adequate periodic monitoring to ensure the source meets 99% control efficiency. [District Rule 4401, 5.1, 5.2 and 6.2.1] Federally Enforceable Through Title V Permit
18. The control efficiency of the vapor collection and control system used to control VOC emissions from steam enhanced crude oil production well shall be determined by mass balance based on most stringent of a source test, USEPA approved emission factors, or Air Pollution (AP)-42 emission factors for components and number of components; and the efficiency of destruction devices determined by USEPA Method 25, 25a, or 18 as applicable. [District Rule 4401, 6.3.1] Federally Enforceable Through Title V Permit
19. VOC content shall be determined using the latest revision of ASTM Method E168, E169, or E260 as applicable. Halogenated exempt compounds shall be determined by CARB Method 432. [District Rule 4401, 6.3.2] Federally Enforceable Through Title V Permit
20. The source shall perform leak inspections at least annually, using a portable hydrocarbon detection instrument in accordance with USEPA Method 21. [District Rule 4401, 6.3.3] Federally Enforceable Through Title V Permit
21. Formerly permit number S-1342-7.

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-360-2

EXPIRATION DATE: 03/31/2021

SECTION: SW15 **TOWNSHIP:** 29S **RANGE:** 29E

EQUIPMENT DESCRIPTION:

3000 BBL FIXED ROOF WASH TANK WITH VAPOR CONTROL SYSTEM SHARED WITH S-1326-361, '-362, AND '-370 (ANTHILL LEASE)

PERMIT UNIT REQUIREMENTS

1. Existing oil production sumps shall be used for intermittent or emergency collection of crude oil and water pursuant to Rule 1100 and 4402, or used exclusively for storage of fresh or clean produced water. [District Rules 1100 and 2201] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. The VOC control device shall be either of the following: boiler #S-1326-339, steam generator #S-1326-369, or flare #S-1326-382. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
3. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
5. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
6. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
7. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
8. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
10. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 2201 and 4623,] Federally Enforceable Through Title V Permit
14. The operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rules 1070 and 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-361-4

EXPIRATION DATE: 03/31/2021

SECTION: SW15 **TOWNSHIP:** 29S **RANGE:** 29E

EQUIPMENT DESCRIPTION:

2000 BBL FIXED ROOF STORAGE TANK WITH VAPOR CONTROL LISTED ON PERMIT S-1326-360 (ANTHILL LEASE)

PERMIT UNIT REQUIREMENTS

1. Tank shall vent only to tank vapor control system shared with permit unit #S-1326-360. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. The VOC control device shall be either of the following: boiler #S-1326-339, steam generator #S-1326-369, or flare #S-1326-382 . [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
3. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
5. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
6. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
7. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
8. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
9. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule Rules 2201 and 4623,] Federally Enforceable Through Title V Permit
14. The operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rules 1070 and 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-362-4

EXPIRATION DATE: 03/31/2021

SECTION: SW15 **TOWNSHIP:** 29S **RANGE:** 29E

EQUIPMENT DESCRIPTION:

2000 BBL FIXED ROOF STORAGE TANK WITH VAPOR CONTROL LISTED ON S-1326-360 (ANTHILL LEASE)

PERMIT UNIT REQUIREMENTS

1. Existing oil production sumps shall be used for intermittent or emergency collection of crude oil and water pursuant to Rule 1100 and 4402, or used exclusively for storage of fresh or clean produced water. [District Rules 1100 and 4623] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. The VOC control device shall be either of the following: boiler #S-1326-339, steam generator #S-1326-369, or flare #S-1326-382. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
3. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
5. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
6. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
7. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
8. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
9. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
11. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
12. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rule 4623, Table 3] Federally Enforceable Through Title V Permit
13. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 2201 and 4623,] Federally Enforceable Through Title V Permit
14. The operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rules 1070 and 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-382-3

EXPIRATION DATE: 03/31/2021

SECTION: SW15 **TOWNSHIP:** 29S **RANGE:** 29E

EQUIPMENT DESCRIPTION:

25 FOOT TALL MACTRONIC AIR-ASSISTED PROCESS FLARE WITH 6 INCH DIAMETER FLARE STACK AND AUTOMATIC RE-IGNITION

PERMIT UNIT REQUIREMENTS

1. The "effective" stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction and stack shall vent vertically upward. [District Rule 4102]
2. The flare is to be used only if disposal wells, a sales gas line, combustion sources creating useful work or permit exempt heater are not available. The flare shall have a destruction efficiency > 98% and be air assist and equipped with non automatic or electronic or ballistic ignition. [Public Resources Code 21000-21177: California Environmental Quality Act, District Rule 4102, and CH&SC 41700]
3. Flare shall be equipped with total waste gas volume flow meter. [District Rule 2201] Federally Enforceable Through Title V Permit
4. This permit does not authorize the utilization of any IC engine, or other combustion device requiring a separate permit, for powering the air assist to the flare. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Flare shall operate in a smokeless manner (no greater than 5% opacity) except for three minutes in any one hour. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Total sulfur (as H₂S) concentration of gas incinerated in flare shall not exceed 19 ppmv. [District Rule 2201 and District Rule 4801] Federally Enforceable Through Title V Permit
7. Maximum amount of gas combusted shall not exceed 150,000 scf/day. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Maximum amount of gas combusted shall not exceed 20.0 MMscf/year. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Emissions from the flare shall not exceed any of the following (based on total gas combusted): NO_x (as NO₂): 0.068 lb/MMBtu; PM₁₀: 0.008 lb/MMBtu; CO: 0.37 lb/MMBtu; or VOC: 0.063 lb/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Flare shall comply with all of the applicable requirements of Rule 4311. [District Rule 4311] Federally Enforceable Through Title V Permit
11. The flame shall be present at all times when combustible gases are vented through the flare. [District Rule 4311, 5.2] Federally Enforceable Through Title V Permit
12. The flare outlet shall be equipped with an automatic ignition system, or, shall operate with a pilot flame present at all times when combustible gases are vented through the flare, except during purge periods for automatic-ignition equipped flares. [District Rule 4311, 5.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

13. Except for flares equipped with a flow-sensing ignition system, a heat sensing device such as a thermocouple, ultraviolet beam sensor, infrared sensor, or an equivalent device, capable of continuously detecting at least one pilot flame or the flare flame is present shall be installed and operated. [District Rule 4311, 5.4] Federally Enforceable Through Title V Permit
14. Flares using flow-sensing automatic ignition systems and not using a continuous flame pilot shall use purge gas for purging. [District Rule 4311, 5.5] Federally Enforceable Through Title V Permit
15. Open flares (air-assisted, steam-assisted, or non-assisted) in which the flare gas pressure is less than 5 psig shall be operated in such a manner that meets the provisions of 40 CFR 60.18. [District Rule 4311, 5.6] Federally Enforceable Through Title V Permit
16. Flaring is prohibited unless it is consistent with an approved flare minimization plan (FMP), pursuant to Rule 4311, Section 6.5, and all commitments listed in that plan have been met. This standard shall not apply if the APCO determines that the flaring is caused by an emergency as defined by Section 3.7 and is necessary to prevent an accident, hazard or release of vent gas directly to the atmosphere [District Rule 4311, 5.8] Federally Enforceable Through Title V Permit
17. Permittee shall measure sulfur content of gas incinerated in flare at least once every year. Such data shall be submitted to the District upon request. [District Rule 2201 and District Rule 4801] Federally Enforceable Through Title V Permit
18. Permittee shall determine sulfur content of gas flared using ASTM method D3246 or double GC for H₂S and mercaptans. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Hydrogen sulfide content of vent gas shall be determined using ASTM Method D 1945-96, ASTM Method UOP 539-97, ASTM Method D 4084-94, or ASTM Method D 4810-88. [District Rule 4311, 6.3.4] Federally Enforceable Through Title V Permit
20. The operator of a flare subject to flare minimization requirements pursuant to Section 5.8 shall monitor the vent gas flow to the flare with a flow measuring device or other parameters as specified in the Permit to Operate. The operator shall maintain records pursuant to Section 6.1.7. Flares that the operator can verify, based on permit conditions, are not capable of producing reportable flare events pursuant to Section 6.2.2 shall not be required to monitor vent gas flow to the flare. [District Rule 4311, 5.10] Federally Enforceable Through Title V Permit
21. Permittee shall keep accurate records of daily, quarterly, and annual quantity of gas combusted, and such records shall be retained for a period of five years and made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
22. Flare shall only be used with the net heating value of the gas being combusted being 300 Btu/scf or greater. [40 CFR 60.18 (c)(3) and District Rule 4311, 5.6] Federally Enforceable Through Title V Permit
23. The net heating value of the gas being combusted in a flare shall be determined annually, pursuant to 40 CFR 60.18(f)(3) using EPA Method 18, ASTM D1946, and ASTM D2382. [40 CFR 60.18 (f)(3) and District Rule 4311, 5.6] Federally Enforceable Through Title V Permit
24. The operator of a flare subject to flare minimization plans pursuant to Section 5.8 of Rule 4311 shall notify the APCO of an unplanned flaring event within 24 hours after the start of the next business day or within 24 hours of their discovery, whichever occurs first. The notification shall include the flare source identification, the start date and time, and the end date and time. [District Rule 4311, 6.2.1] Federally Enforceable Through Title V Permit
25. Permittee shall comply with all notification and recordkeeping requirements of 40 CFR 60.7 a (1)(3) and (b). [District Rule 4001] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

26. Effective on and after July 1, 2012, and annually thereafter, the operator of a flare subject to flare minimization plans pursuant to Section 5.8 shall submit an annual report to the APCO that summarizes all Reportable Flaring Events as defined in Section 3.0 that occurred during the previous 12 month period. The report shall be submitted within 30 days following the end of the twelve month period of the previous year. The report shall include, but is not limited to all of the following: 1) The results of an investigation to determine the primary cause and contributing factors of the flaring event; 2) Any prevention measures considered or implemented to prevent recurrence together with a justification for rejecting any measures that were considered but not implemented; 3) If appropriate, an explanation of why the flaring was an emergency and necessary to prevent accident, hazard or release of vent gas to the atmosphere, or where, due to a regulatory mandate to vent a flare, it cannot be recovered, treated and used as a fuel gas at the facility; and 4) The date, time, and duration of the flaring event. [District Rule 4311, 6.2.2] Federally Enforceable Through Title V Permit
27. Effective on and after July 1, 2012, and annually thereafter, the operator of a flare subject to flare monitoring requirements pursuant to Rule 4311, Sections 5.10, 6.6, 6.7, 6.8, 6.9, and 6.10, as appropriate, shall submit an annual report to the APCO within 30 days following the end of each 12 month period. The report shall include the following: 1) The total volumetric flow of vent gas in standard cubic feet for each day, 2) Hydrogen sulfide content, methane content, and hydrocarbon content of vent gas composition pursuant to Section 6.6, 3) If vent gas composition is monitored by a continuous analyzer or analyzers pursuant to Section 5.11, average total hydrocarbon content by volume, average methane content by volume, and depending upon the analytical method used pursuant to Section 6.3.4, total reduced sulfur content by volume or hydrogen sulfide content by volume of vent gas flared for each hour of the month, 4) If the flow monitor used pursuant to Section 5.10 measures molecular weight, the average molecular weight for each hour of each month, 5) For any pilot and purge gas used, the type of gas used, the volumetric flow for each day and for each month, and the means used to determine flow, 6) Flare monitoring system downtime periods, including dates and times, 7) For each day and for each month provide calculated sulfur dioxide emissions, and 8) A flow verification report for each flare subject to this rule. The flow verification report shall include flow verification testing pursuant to Section 6.3.5. [District Rule 4311, 6.2.3] Federally Enforceable Through Title V Permit
28. Upon request, the operator of flares that are subject to Section 5.6 shall make available to the APCO the compliance determination records that demonstrate compliance with the provisions of 40 CFR 60.18, (c)(3) through (c)(5). [District Rule 4311, 6.4.1] Federally Enforceable Through Title V Permit
29. The following records shall be maintained, retained on-site for a minimum of five years, and made available to the APCO, ARB, and EPA upon request: 1) A copy of the compliance determination conducted pursuant to Section 6.4.1, 2) For flares used during an emergency, record of the duration of flare operation, amount of gas burned, and the nature of the emergency situation, 3) A copy of the approved flare minimization plan pursuant to Section 6.5, 4) On and after July 1, 2012, where applicable, a copy of annual reports submitted to the APCO pursuant to Section 6.2, and 5) Where applicable, monitoring data collected pursuant to Sections 5.10. [District Rule 4311, 6.1] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-385-5

EXPIRATION DATE: 03/31/2021

SECTION: NE23 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

85 MMBTU/HR NATURAL/TEOR/TVR GAS-FIRED STEAM GENERATOR WITH A NORTH AMERICAN 4231-85 GLE BURNER, AND FLUE GAS RECIRCULATION (FGR)

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. The unit shall only be fired on PUC-quality natural/TEOR/TVR gas. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
4. Emissions rates from the unit shall not exceed any of the following emission limits: 7 ppmv NO_x @ 3% O₂ or 0.008 lb NO_x/MMBtu, 0.00285 lb-SO_x/MMBtu, 0.003 lb-PM₁₀/MMBtu, 25 ppmv CO @ 3% O₂ or 0.0185 lb CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
5. Permittee shall test annually the sulfur content of the fuel gas combusted in steam generator using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rule 4320] Federally Enforceable Through Title V Permit
6. Source testing to measure NO_x and CO emissions from this unit while fired on natural gas shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3.1, 4306, 6.3.1, and 4320] Federally Enforceable Through Title V Permit
7. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. Unless otherwise specified in the Permit to Operate, no determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 5.5.2, 4306, 5.5.2, and 4320] Federally Enforceable Through Title V Permit
8. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
9. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
10. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5.1, 4306, 5.5.1, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. For NO_x and CO emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5, 4306, 5.5.5, and 4320] Federally Enforceable Through Title V Permit
12. NO_x emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305, 6.2, 4306, 6.2, and 4320] Federally Enforceable Through Title V Permit
13. PM₁₀ emissions for source test purposes shall be determined using EPA Methods 201A and 202, or other District approved methods. [District Rule 2201] Federally Enforceable Through Title V Permit
14. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305, 6.2, 4306, 6.2, and 4320] Federally Enforceable Through Title V Permit
15. Stack gas oxygen (O₂) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 6.2, 4306, 6.2, and 4320] Federally Enforceable Through Title V Permit
16. The permittee shall monitor and record the stack concentration of NO_x, CO, and O₂ at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4, 4306, 5.4, and 4320] Federally Enforceable Through Title V Permit
17. If either the NO_x or CO concentrations corrected to 3% O₂, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4, 4306, 5.4, and 4320] Federally Enforceable Through Title V Permit
18. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4, 4306, 5.4, and 4320] Federally Enforceable Through Title V Permit
19. Permittee shall comply with all notification and recordkeeping requirements of 40 CFR 60.7 a (1)(3) and (b). [District Rule 4001] Federally Enforceable Through Title V Permit
20. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
21. Permittee shall maintain daily records of the type and quantity of fuel combusted by the steam generator. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
22. The permittee shall maintain records of: (1) the date and time of NO_x, CO, and O₂ measurements, (2) the O₂ concentration in percent and the measured NO_x and CO concentrations corrected to 3% O₂, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1, 4306, 6.1, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

23. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 1070, 4305, 4306, 4320, and 40 CFR 60.48c (i)] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-390-3

EXPIRATION DATE: 03/31/2021

EQUIPMENT DESCRIPTION:

85.0 MMBTU/HR STRUTHERS NATURAL GAS-FIRED STEAM GENERATOR WITH A NORTH AMERICAN MODEL MAGNA-FLAME G-LE ULTRA ULTRA-LOW NOX BURNER WITH FLUE GAS RECIRCULATION (FGR) AND AN O2 CONTROLLER

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
3. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
4. The unit shall only be fired on regulated natural gas and scrubbed TEOR and TVR gas from S-1326-26, '-27, '-28, '-35 and '-263 with a sulfur content no greater than 1 gr S/100 scf. [District Rules 2201 and 4320, 5.4] Federally Enforceable Through Title V Permit
5. Permittee shall test annually the sulfur content of TEOR/TVR gas combusted in steam generator using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rule 4320, 5.7] Federally Enforceable Through Title V Permit
6. Emissions from the steam generator shall not exceed any of the following limits: 0.003 lb-PM10/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 16.3 lb-NOx/day, 5,957 lb-NOx/yr, 18.4 lb-CO/day, and 6,701 lb-CO/yr. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 7 ppmvd NOx @ 3% O2 or 0.008 lb-NOx/MMBtu or 10 ppmvd CO @ 3% O2 or 0.009 lb-CO/MMBtu. [District Rules 2201, 4301, 5.2, 4305, 5.1, 4306, 5.1 and 4320, 5.2] Federally Enforceable Through Title V Permit
9. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 4305, 5.5.6, 4306, 5.3 and 4320, 5.6]
10. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rule 4306, 3.25 and 3.22 and 4320, 5.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Source testing to measure NOx and CO emissions from this unit while fired on natural gas shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3.1, 4306, 6.3.1 and 4320, 5.6] Federally Enforceable Through Title V Permit
12. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 5.5.2, 4306, 5.5.2 and 4320, 5.6] Federally Enforceable Through Title V Permit
13. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5.1, 4306, 5.5.1 and 4320, 6.3] Federally Enforceable Through Title V Permit
14. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
15. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
16. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5, 4306, 5.5.5 and 4320, 6.3] Federally Enforceable Through Title V Permit
17. The following test methods shall be used: PM10 (lb/MMBtu) - EPA 201A - 202 or Method 5, NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, stack gas moisture content - EPA Method 4, stack gas velocities - EPA Method 2, and fuel gas sulfur content - ASTM D1072, ASTM D3246, ASTM D6228 (GC-FPD) or double GC for H2S and mercaptans. [District Rule 1081, 4305, 4306, 6.2, 4320, 6.2 and 4351] Federally Enforceable Through Title V Permit
18. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4, 4306, 5.4, 4320, 5.7] Federally Enforceable Through Title V Permit
19. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4, 4306, 5.4 and 4320, 5.7] Federally Enforceable Through Title V Permit
20. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4, 4306, 5.4 and 4320, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
22. Permittee shall maintain daily records of the type and quantity of fuel combusted by the steam generator. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
23. The permittee shall maintain records of: (1) the date and time of NO_x, CO, and O₂ measurements, (2) the O₂ concentration in percent and the measured NO_x and CO concentrations corrected to 3% O₂, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1, 4306, 6.1 and 4320, 6.1] Federally Enforceable Through Title V Permit
24. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 1070, 4305, 4306, 4320, and 40 CFR 60.48c (i)] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-391-3

EXPIRATION DATE: 03/31/2021

EQUIPMENT DESCRIPTION:

85.0 MMBTU/HR STRUTHERS NATURAL GAS-FIRED STEAM GENERATOR WITH A NORTH AMERICAN MODEL MAGNA-FLAME G-LE ULTRA ULTRA-LOW NOX BURNER WITH FLUE GAS RECIRCULATION (FGR) AND AN O2 CONTROLLER

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
3. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
4. The unit shall only be fired on regulated natural gas and scrubbed TEOR and TVR gas from S-1326-26, '-27, '-28, '-35 and '-263 with a sulfur content no greater than 1 gr S/100 scf. [District Rule 2201 and 4320, 5.4] Federally Enforceable Through Title V Permit
5. Permittee shall test annually the sulfur content of TEOR/TVR gas combusted in steam generator using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rule 4320, 5.7] Federally Enforceable Through Title V Permit
6. Emissions from the steam generator shall not exceed any of the following limits: 0.003 lb-PM10/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 16.3 lb-NOx/day, 5,957 lb-NOx/yr, 18.4 lb-CO/day, and 6,701 lb-CO/yr. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 7 ppmvd NOx @ 3% O2 or 0.008 lb-NOx/MMBtu or 10 ppmvd CO @ 3% O2 or 0.009 lb-CO/MMBtu. [District Rules 2201, 4301, 5.2, 4305, 5.1, 4306, 5.1 and 4320, 5.2] Federally Enforceable Through Title V Permit
9. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 4305, 5.5.6, 4306, 5.3 and 4320, 5.6]
10. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rule 4306, 3.25, 3.22 and 4320, 5.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Source testing to measure NOx and CO emissions from this unit while fired on natural gas shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3.1, 4306, 6.3.1 and 4320, 6.3] Federally Enforceable Through Title V Permit
12. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 5.5.2, 4306, 5.5.2 and 4320, 6.3] Federally Enforceable Through Title V Permit
13. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5.1, 4306, 5.5.1 and 4320, 6.3] Federally Enforceable Through Title V Permit
14. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
15. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
16. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5, 4306, 5.5.5 and 4320, 6.3] Federally Enforceable Through Title V Permit
17. The following test methods shall be used: PM10 (lb/MMBtu) - EPA 201A - 202 or Method 5, NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, stack gas moisture content - EPA Method 4, stack gas velocities - EPA Method 2, and fuel gas sulfur content - ASTM D1072, ASTM D3246, ASTM D6228 (GC-FPD) or double GC for H2S and mercaptans. [District Rule 1081, 4305, 4306, 6.2, 4320, 6.2 and 4351] Federally Enforceable Through Title V Permit
18. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4, 4306, 5.4 and 4320, 5.7] Federally Enforceable Through Title V Permit
19. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4, 4306, 5.4 and 4320, 5.7] Federally Enforceable Through Title V Permit
20. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4, 4306, 5.4 and 4320, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
22. Permittee shall maintain daily records of the type and quantity of fuel combusted by the steam generator. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
23. The permittee shall maintain records of: (1) the date and time of NO_x, CO, and O₂ measurements, (2) the O₂ concentration in percent and the measured NO_x and CO concentrations corrected to 3% O₂, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1, 4306, 6.1 and 4320, 6.1] Federally Enforceable Through Title V Permit
24. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 1070, 4305, 4306, 4320, and 40 CFR 60.48c (i)] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-392-2

EXPIRATION DATE: 03/31/2021

EQUIPMENT DESCRIPTION:

85.0 MMBTU/HR STRUTHERS NATURAL GAS-FIRED STEAM GENERATOR WITH A NORTH AMERICAN MODEL MAGNA-FLAME G-LE ULTRA ULTRA-LOW NOX BURNER WITH FLUE GAS RECIRCULATION (FGR) AND AN O2 CONTROLLER

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
3. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
4. The unit shall only be fired on regulated natural gas and scrubbed TEOR and TVR gas from S-1326-26, '-27, '-28, '-35 and '-263 with a sulfur content no greater than 1 gr S/100 scf . [District Rule 2201 and 4320, 5.4] Federally Enforceable Through Title V Permit
5. Permittee shall test annually the sulfur content of TEOR/TVR gas combusted in steam generator using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rule 4320, 5.7] Federally Enforceable Through Title V Permit
6. Emissions from the steam generator shall not exceed any of the following limits: 0.003 lb-PM10/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Maximum emissions from the steam generator, including start-up and shutdown, shall not exceed any of the following limits: 16.3 lb-NOx/day, 5,957 lb-NOx/yr, 18.4 lb-CO/day, and 6,701 lb-CO/yr. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Except during start-up and shutdown periods emissions from the steam generator shall not exceed any of the following limits: 7 ppmvd NOx @ 3% O2 or 0.008 lb-NOx/MMBtu or 10 ppmvd CO @ 3% O2 or 0.009 lb-CO/MMBtu. [District Rules 2201, 4301, 5.2, 4305, 5.1, 4306, 5.1 and 4320, 5.2] Federally Enforceable Through Title V Permit
9. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 4305, 5.5.6, 4306, 5.3 and 4320, 5.6]
10. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rule 4306, 3.25 and 3.22 and 4320, 5.6] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Source testing to measure NOx and CO emissions from this unit while fired on natural gas shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3.1, 4306, 6.3.1 and 4320, 6.3] Federally Enforceable Through Title V Permit
12. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 5.5.2, 4306, 5.5.2 and 4320, 6.3] Federally Enforceable Through Title V Permit
13. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5.1, 4306, 5.5.1 and 4320, 6.3] Federally Enforceable Through Title V Permit
14. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
15. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
16. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5, 4306, 5.5.5 and 4320, 6.3] Federally Enforceable Through Title V Permit
17. The following test methods shall be used: PM10 (lb/MMBtu) - EPA 201A - 202 or Method 5, NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, stack gas moisture content - EPA Method 4, stack gas velocities - EPA Method 2, and fuel gas sulfur content - ASTM D1072, ASTM D3246, ASTM D6228 (GC-FPD) or double GC for H2S and mercaptans. [District Rule 1081, 4305, 4306, 6.2, 4320, 6.2 and 4351] Federally Enforceable Through Title V Permit
18. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4, 4306, 5.4 and 4320, 5.7] Federally Enforceable Through Title V Permit
19. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4, 4306, 5.4 and 4320, 5.7] Federally Enforceable Through Title V Permit
20. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4, 4306, 5.4 and 4320, 5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
22. Permittee shall maintain daily records of the type and quantity of fuel combusted by the steam generator. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
23. The permittee shall maintain records of: (1) the date and time of NO_x, CO, and O₂ measurements, (2) the O₂ concentration in percent and the measured NO_x and CO concentrations corrected to 3% O₂, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1, 4306, 6.1 and 4320, 6.1] Federally Enforceable Through Title V Permit
24. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 1070, 4305, 4306, 4320, and 40 CFR 60.48c (i)] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-394-1

EXPIRATION DATE: 03/31/2021

SECTION: 23 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

20,000 BBL FWKO TANK CONNECTED TO SECTION 23 TVR SYSTEM LISTED ON PERMIT S-1326-263 (SECTION 23 FACILITY)

PERMIT UNIT REQUIREMENTS

1. Tank shall vent only to vapor control system listed on permit S-1326-263. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Vapor control efficiency shall be maintained at no less than 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The true vapor pressure of the liquids handled by tank shall not exceed 0.5 psia. [District Rules 4623] Federally Enforceable Through Title V Permit
4. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2080] Federally Enforceable Through Title V Permit
5. Permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit
6. Tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit
7. Permittee shall notify the District Compliance Division at least 24 hours before tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit
8. Prior to opening the tank to allow tank cleaning, one of the following procedures must be followed: 1) Prior to venting the tank to the atmosphere, operate the tank vapor recovery system/vapor control device for at least 24 hours such that it collects the tank vapors; or 2) use liquid displacement, conducted using a liquid with a TVP less than 0.5 psia, or conducted by floating the oil pad off a crude oil FWKO by restricting the outflow of water, such that 90% of the tank volume is displaced; or 3) Vent the tank to a vapor control device/vapor recovery system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3 V/Q$, where t = time, V = tank volume (cubic feet), and Q = flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit
9. The tank shall be cleaned using one of the following methods: water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment may be used for road mix as allowed by Section 6.17 of District Rule 2020. [District Rule 2080] Federally Enforceable Through Title V Permit
10. Steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2080] Federally Enforceable Through Title V Permit
12. Within 48 hours after refilling the tank with crude oil/water, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
13. Permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the procedure used to vent tank vapors prior to opening, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit
14. VOC content of tank vapor space and vapor control system piping and components shall not exceed 10% by weight. [District Rule 2201]
15. VOC content of gas shall be measured using ASTM D-1945, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rule 2201] Federally Enforceable Through Title V Permit
16. The permittee shall keep accurate records of VOC content of vapors for a period of 5 years and shall make such records available for District inspection upon request. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-395-1

EXPIRATION DATE: 03/31/2021

SECTION: 23 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

5,000 BBL CRUDE OIL TANK CONNECTED TO SECTION 23 TVR SYSTEM LISTED ON PERMIT S-1326-263 (SECTION 23 FACILITY)

PERMIT UNIT REQUIREMENTS

1. Tank shall vent only to vapor control system listed on permit S-1326-263. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The true vapor pressure of the liquids stored in this tank shall not exceed 0.5 psia. [District Rules 4623, 2.0 and 2201] Federally Enforceable Through Title V Permit
4. Vapor control efficiency shall be maintained at no less than 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The permittee shall keep accurate records of liquids stored and true vapor pressure of such liquids. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit
8. Permittee shall notify the District Compliance Division at least 24 hours before tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit
9. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor recovery system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed. Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor recovery system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3 V / Q$, where t = time, V = tank volume (cubic feet), and Q = flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. Permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the procedure used to vent tank vapors prior to opening, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Permittee shall provide the District with written notification at least 30 days prior to installation of components handling fluid streams with a VOC content of 10% or less by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. Gas-tight shall be defined as emitting no more than 10,000 ppm of methane measured at a distance of one centimeter from the potential source with an instrument calibrated with methane in accordance with USEPA Method 21. Emissions in excess of this limit shall be considered a leak. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
15. All tank seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a gas-tight condition. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. The operator shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. The API gravity of organic liquid stored in this tank shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method)". Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products". [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
18. Control efficiency shall be determined by a comparison of controlled emissions to those emissions which would occur from a fixed or cone roof tank in the same product service without a vapor recovery system. Emissions shall be determined based on tank emission factors in USEPA Publication AP-42, component counts for fugitive emissions sources, recognized emission factors for fugitive emission sources and the efficiency of any VOC destruction device. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
19. The operator shall ensure that the vapor control system is functional and is operating as designed at all times, except during periods of routine maintenance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
20. Operator shall determine the true vapor pressure of the petroleum liquid stored in the tank located at the beginning of the process flow after the production header at least once per year. The latest version of the Lawrence Berkeley National Laboratory "Test Method for Vapor Pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA, shall be used to determine the TVP of crude oil with an API gravity of 26 or less, or for any API gravity that is specified in this test method. Determinations shall be made annually during summer and whenever there is a change in the source or type of petroleum entering the tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
21. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids store in this unit to determine which oil are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-396-1

EXPIRATION DATE: 03/31/2021

SECTION: 23 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

5,000 BBL CRUDE OIL TANK CONNECTED TO SECTION 23 TVR SYSTEM LISTED ON PERMIT S-1326-263 (SECTION 23 FACILITY)

PERMIT UNIT REQUIREMENTS

1. Tank shall vent only to vapor control system listed on permit S-1326-263. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The tank shall be equipped with a fixed roof with no holes or openings. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The true vapor pressure of the liquids stored in this tank shall not exceed 0.5 psia. [District Rules 4623, 2.0 and 2201] Federally Enforceable Through Title V Permit
4. Vapor control efficiency shall be maintained at no less than 99%. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The permittee shall keep accurate records of liquids stored and true vapor pressure of such liquids. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit
8. Permittee shall notify the District Compliance Division at least 24 hours before tank cleaning and vapor control system disconnection. [District Rule 2080] Federally Enforceable Through Title V Permit
9. Prior to opening the tank to allow tank cleaning the following procedure must be followed. Operate PV valve and vapor recovery system (if equipped) during emptying, filling, and flushing. During filling and purging, no vapor leakage is allowed. Drain all liquid from the tank to the maximum extent feasible prior to opening the tank. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Prior to opening the tank to allow tank cleaning one of the following options must be followed: 1) operate the vapor recovery system for at least 2 hours after all the liquid in the tank has been drained, 2) displace vapors floating the oil pad off with water such that 90% of the tank volume is displaced, 3) vent the tank to the vapor control system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3 V / Q$, where t = time, V = tank volume (cubic feet), and Q = flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Allowable methods of cleaning include using steam, diesel, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams/liter VOC content or less. Steam cleaning shall be allowed at locations where wastewater treatment facilities are limited or during December through March. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. Permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the procedure used to vent tank vapors prior to opening, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Permittee shall provide the District with written notification at least 30 days prior to installation of components handling fluid streams with a VOC content of 10% or less by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a gas-tight cover which shall be closed at all times except during gauging or sampling. Gas-tight shall be defined as emitting no more than 10,000 ppm of methane measured at a distance of one centimeter from the potential source with an instrument calibrated with methane in accordance with USEPA Method 21. Emissions in excess of this limit shall be considered a leak. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
15. All tank seams, welds, joints, piping, valves, and fittings shall be inspected and maintained in a gas-tight condition. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
16. The operator shall conduct true vapor pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. The API gravity of organic liquid stored in this tank shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method)". Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products". [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
18. Control efficiency shall be determined by a comparison of controlled emissions to those emissions which would occur from a fixed or cone roof tank in the same product service without a vapor recovery system. Emissions shall be determined based on tank emission factors in USEPA Publication AP-42, component counts for fugitive emissions sources, recognized emission factors for fugitive emission sources and the efficiency of any VOC destruction device. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
19. The operator shall ensure that the vapor control system is functional and is operating as designed at all times, except during periods of routine maintenance. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
20. Operator shall determine the true vapor pressure of the petroleum liquid stored in the tank located at the beginning of the process flow after the production header at least once per year. The latest version of the Lawrence Berkeley National Laboratory "Test Method for Vapor Pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA, shall be used to determine the TVP of crude oil with an API gravity of 26 or less, or for any API gravity that is specified in this test method. Determinations shall be made annually during summer and whenever there is a change in the source or type of petroleum entering the tank. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
21. As used in this permit, the term "source or type of petroleum" shall mean petroleum liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids store in this unit to determine which oil are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-400-1

EXPIRATION DATE: 03/31/2021

SECTION: 23 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

85 MMBTU/HR STRUTHERS NATURAL GAS/TEOR/TVR-FIRED STEAM GENERATOR WITH NORTH AMERICAN MODEL MAGNA-FLAME 4231-85 GLE BURNER AND A FLUE GAS RECIRCULATION (FGR) SYSTEM

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
3. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
4. Natural gas and or TEOR and TVR gas combusted in this unit shall have a sulfur content no greater than 1 gr S/100 scf. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
5. Permittee shall test annually the sulfur content of the fuel gas combusted in steam generator using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit
6. Emissions rates from unit shall not exceed any of the following limits: 7 ppmv NO_x @ 3% O₂ or 0.008 lb-NO_x/MMBtu, 0.003 lb-PM₁₀/MMBtu, 25 ppmv CO @ 3% O₂ or 0.0185 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4301, 5.2, 4305, 5.1, 4306, 5.1, 4320, and 40 CFR 60.43c(e)(1)] Federally Enforceable Through Title V Permit
7. Source testing to measure NO_x and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 6.3.1, 4306, 6.3.1, and 4320] Federally Enforceable Through Title V Permit
8. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. Unless otherwise specified in the Permit to Operate, no determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 5.5.2, 4306, 5.5.2, and 4320] Federally Enforceable Through Title V Permit
9. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
10. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 5.5.1, 4306, 5.5.1, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
12. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5, 4306, 5.5.5, and 4320] Federally Enforceable Through Title V Permit
13. The following test methods shall be used: NO_x (ppmv) - EPA Method 7E or ARB Method 100, NO_x (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100, stack gas moisture content - EPA Method 4, stack gas velocities - EPA Method 2, and fuel gas sulfur content - ASTM D1072, ASTM D3246, ASTM D6228 (GC-FPD) or double GC for H₂S and mercaptans. [District Rule 1081, 4305, 4306, 6.2, 4320, and 4351] Federally Enforceable Through Title V Permit
14. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305 and 4306] Federally Enforceable Through Title V Permit
15. The permittee shall monitor and record the stack concentration of NO_x, CO, and O₂ at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 5.4, 4306, 5.4, and 4320] Federally Enforceable Through Title V Permit
16. If either the NO_x or CO concentrations corrected to 3% O₂, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 5.4, 4306, 5.4, and 4320] Federally Enforceable Through Title V Permit
17. All NO_x, CO, and O₂ emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 5.4, 4306, 5.4, and 4320] Federally Enforceable Through Title V Permit
18. The permittee shall maintain records of: (1) the date and time of NO_x, CO, and O₂ measurements, (2) the O₂ concentration in percent and the measured NO_x and CO concentrations corrected to 3% O₂, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 6.1, 4306, 6.1, and 4320] Federally Enforceable Through Title V Permit
19. PUC quality natural gas is any gaseous fuel where the sulfur content is no more than one-fourth (0.25) grain of hydrogen sulfide per one hundred (100) standard cubic feet, no more than five (5) grains of total sulfur per one hundred (100) standard cubic feet, and at least 80% methane by volume. [District Rule 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

20. If the steam generator is not fired on PUC-regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. The sulfur content of the fuel shall be determined using the test methods referenced in this permit. [District Rule 4320] Federally Enforceable Through Title V Permit
21. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
22. Permittee shall maintain daily records of the type and quantity of fuel combusted by the steam generator. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
23. Permittee shall maintain records of fuel gas sulfur compound measurements. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
24. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320] Federally Enforceable Through Title V Permit
25. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 1070, 4305, 4306, 4320, and 40 CFR 60.48c (i)] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-401-1

EXPIRATION DATE: 03/31/2021

SECTION: 23 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

85 MMBTU/HR NATURAL AND/OR TVR GAS-FIRED STEAM GENERATOR WITH NORTH AMERICAN MODEL MAGNA-FLAME 4231-85 GLE BURNER AND A FLUE GAS RECIRCULATION (FGR) SYSTEM

PERMIT UNIT REQUIREMENTS

1. This unit is approved for operation at the SE/4 and NW/4 of Section 23, T28S, R27E. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Permittee shall notify the District Compliance Division of each location at which the unit is located in excess of 24 hours. Such notification shall be made no later than 48 hours after starting operation at the location. [District Rule 2201] Federally Enforceable Through Title V Permit
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
5. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
6. Natural gas and/or TEOR and TVR gas combusted in this unit shall have a sulfur content no greater than 1 gr S/100 scf. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
7. Permittee shall test annually the sulfur content of the fuel gas combusted in steam generator using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit
8. Emissions rates from unit shall not exceed any of the following limits: 7 ppmv NO_x @ 3% O₂ or 0.008 lb-NO_x/MMBtu, 0.003 lb-PM₁₀/MMBtu, 25 ppmv CO @ 3% O₂ or 0.0185 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4301, 4305, 4306, 4320, and 40 CFR 60.43c(e)(1)] Federally Enforceable Through Title V Permit
9. Source testing to measure NO_x and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
10. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. Unless otherwise specified in the Permit to Operate, no determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
12. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
13. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
14. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5, 4306, 5.5.5, and 4320] Federally Enforceable Through Title V Permit
15. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; Stack gas oxygen (O2) - EPA Method 3 or 3A or ARB Method 100; stack gas velocities - EPA Method 2; Stack gas moisture content - EPA Method 4; SOx - EPA Method 6C or 8 or ARB Method 100; fuel gas sulfur as H2S content - EPA Method 11 or 15; and fuel hhv (MMBtu) - ASTM D 1826 or D 1945 in conjunction with ASTM D 3588. [District Rule 1081, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit
16. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
17. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
18. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
19. All NOx, CO, and O2 emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
20. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. PUC quality natural gas is any gaseous fuel where the sulfur content is no more than one-fourth (0.25) grain of hydrogen sulfide per one hundred (100) standard cubic feet, no more than five (5) grains of total sulfur per one hundred (100) standard cubic feet, and at least 80% methane by volume. [District Rule 4320] Federally Enforceable Through Title V Permit
22. If the steam generator is not fired on PUC-regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. The sulfur content of the fuel shall be determined using the test methods referenced in this permit. [District Rule 4320] Federally Enforceable Through Title V Permit
23. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
24. Permittee shall maintain daily records of the type and quantity of fuel combusted by the steam generator. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
25. Permittee shall maintain records of fuel gas sulfur compound measurements. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
26. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320] Federally Enforceable Through Title V Permit
27. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 1070, 4305, 4306, 4320, and 40 CFR 60.48c (i)] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-405-3

EXPIRATION DATE: 03/31/2021

SECTION: NE 23 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

85.0 MMBTU/HR NATURAL GAS -FIRED STEAM GENERATOR WITH NORTH AMERICAN 4231-85-GLE/X8701 GLE BURNER S/N SD857413-01 AND A FLUE GAS RECIRCULATION SYSTEM

PERMIT UNIT REQUIREMENTS

1. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
2. Steam generator shall be equipped with variable frequency drive electrical motors driving the blower and water pump and a convection section with at least 235 square feet of heat transfer surface area per MMBtu/hr of maximum rated heat input (verified by manufacturer) or a manufacturer's overall thermal efficiency rating of 88%. [Public Resources Code 21000-21177: California Environmental Quality Act]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
5. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
6. The unit shall only be fired on PUC-quality natural gas with a maximum sulfur content of 1.0 gr S/100scf. [District Rules 2201 4801, and 4320] Federally Enforceable Through Title V Permit
7. Permittee shall test annually the sulfur content of the fuel gas combusted in steam generator using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit
8. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
9. Emission rates shall not exceed: PM10: 0.003 lb/MMBtu, VOC: 0.0055 lb/MMBtu, NOx (as NO2): 7 ppmvd NOx @ 3% O2, or CO: 10 ppmv @ 3% O2. [District Rules 2201, 4201, 4301, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit
10. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. Unless otherwise specified in the Permit to Operate, no determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
12. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
13. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
14. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
15. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5, 4306, 5.5.5, and 4320] Federally Enforceable Through Title V Permit
16. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; Stack gas oxygen (O2) - EPA Method 3 or 3A or ARB Method 100; stack gas velocities - EPA Method 2; Stack gas moisture content - EPA Method 4; SOx - EPA Method 6C or 8 or ARB Method 100; fuel gas sulfur as H2S content - EPA Method 11 or 15; and fuel hhv (MMBtu) - ASTM D 1826 or D 1945 in conjunction with ASTM D 3588. [District Rule 1081, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit
17. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
18. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
19. All NOx, CO, and O2 emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
20. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. PUC quality natural gas is any gaseous fuel where the sulfur content is no more than one-fourth (0.25) grain of hydrogen sulfide per one hundred (100) standard cubic feet, no more than five (5) grains of total sulfur per one hundred (100) standard cubic feet, and at least 80% methane by volume. [District Rule 4320] Federally Enforceable Through Title V Permit
22. If the steam generator is not fired on PUC-regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. The sulfur content of the fuel shall be determined using the test methods referenced in this permit. [District Rule 4320] Federally Enforceable Through Title V Permit
23. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
24. Permittee shall maintain daily records of the type and quantity of fuel combusted by the steam generator. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
25. Permittee shall maintain records of fuel gas sulfur compound measurements. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
26. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320] Federally Enforceable Through Title V Permit
27. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 1070, 4305, 4306, 4320, and 40 CFR 60.48c (i)] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-406-3

EXPIRATION DATE: 03/31/2021

SECTION: NE 23 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

85.0 MMBTU/HR NATURAL GAS -FIRED STEAM GENERATOR WITH NORTH AMERICAN 4231-85-GLE/X8701 GLE BURNER AND A FLUE GAS RECIRCULATION SYSTEM

PERMIT UNIT REQUIREMENTS

1. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
2. Steam generator shall be equipped with variable frequency drive electrical motors driving the blower and water pump and a convection section with at least 235 square feet of heat transfer surface area per MMBtu/hr of maximum rated heat input (verified by manufacturer) or a manufacturer's overall thermal efficiency rating of 88%. [Public Resources Code 21000-21177: California Environmental Quality Act]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
5. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
6. The unit shall only be fired on PUC-quality natural gas with a maximum sulfur content of 1.0 gr S/100scf. [District Rules 2201 4801, and 4320] Federally Enforceable Through Title V Permit
7. Permittee shall test annually the sulfur content of the fuel gas combusted in steam generator using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit
8. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
9. Emission rates shall not exceed: PM10: 0.003 lb/MMBtu, VOC: 0.0055 lb/MMBtu, NOx (as NO2): 7 ppmvd NOx @ 3% O2, or CO: 10 ppmv @ 3% O2. [District Rules 2201, 4201, 4301, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit
10. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. Unless otherwise specified in the Permit to Operate, no determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
12. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
13. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
14. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
15. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5, 4306, 5.5.5, and 4320] Federally Enforceable Through Title V Permit
16. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; Stack gas oxygen (O2) - EPA Method 3 or 3A or ARB Method 100; stack gas velocities - EPA Method 2; Stack gas moisture content - EPA Method 4; SOx - EPA Method 6C or 8 or ARB Method 100; fuel gas sulfur as H2S content - EPA Method 11 or 15; and fuel hhv (MMBtu) - ASTM D 1826 or D 1945 in conjunction with ASTM D 3588. [District Rule 1081, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit
17. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
18. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
19. All NOx, CO, and O2 emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
20. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. PUC quality natural gas is any gaseous fuel where the sulfur content is no more than one-fourth (0.25) grain of hydrogen sulfide per one hundred (100) standard cubic feet, no more than five (5) grains of total sulfur per one hundred (100) standard cubic feet, and at least 80% methane by volume. [District Rule 4320] Federally Enforceable Through Title V Permit
22. If the steam generator is not fired on PUC-regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. The sulfur content of the fuel shall be determined using the test methods referenced in this permit. [District Rule 4320] Federally Enforceable Through Title V Permit
23. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
24. Permittee shall maintain daily records of the type and quantity of fuel combusted by the steam generator. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
25. Permittee shall maintain records of fuel gas sulfur compound measurements. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
26. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320] Federally Enforceable Through Title V Permit
27. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 1070, 4305, 4306, 4320, and 40 CFR 60.48c (i)] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-407-3

EXPIRATION DATE: 03/31/2021

SECTION: NE 23 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

85.0 MMBTU/HR NATURAL GAS -FIRED STEAM GENERATOR WITH NORTH AMERICAN 4231-85-GLE/X8701 GLE BURNER S/N SD89244-04 AND A FLUE GAS RECIRCULATION SYSTEM

PERMIT UNIT REQUIREMENTS

1. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
2. Steam generator shall be equipped with variable frequency drive electrical motors driving the blower and water pump and a convection section with at least 235 square feet of heat transfer surface area per MMBtu/hr of maximum rated heat input (verified by manufacturer) or a manufacturer's overall thermal efficiency rating of 88%. [Public Resources Code 21000-21177: California Environmental Quality Act]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
5. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
6. The unit shall only be fired on PUC-quality natural gas with a maximum sulfur content of 1.0 gr S/100scf. [District Rules 2201 4801, and 4320] Federally Enforceable Through Title V Permit
7. Permittee shall test annually the sulfur content of the fuel gas combusted in steam generator using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit
8. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
9. Emission rates shall not exceed: PM10: 0.003 lb/MMBtu, VOC: 0.0055 lb/MMBtu, NOx (as NO2): 7 ppmvd NOx @ 3% O2, or CO: 10 ppmv @ 3% O2. [District Rules 2201, 4201, 4301, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit
10. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. Unless otherwise specified in the Permit to Operate, no determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
12. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
13. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
14. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
15. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5, 4306, 5.5.5, and 4320] Federally Enforceable Through Title V Permit
16. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; Stack gas oxygen (O2) - EPA Method 3 or 3A or ARB Method 100; stack gas velocities - EPA Method 2; Stack gas moisture content - EPA Method 4; SOx - EPA Method 6C or 8 or ARB Method 100; fuel gas sulfur as H2S content - EPA Method 11 or 15; and fuel hhv (MMBtu) - ASTM D 1826 or D 1945 in conjunction with ASTM D 3588. [District Rule 1081, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit
17. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
18. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
19. All NOx, CO, and O2 emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
20. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. PUC quality natural gas is any gaseous fuel where the sulfur content is no more than one-fourth (0.25) grain of hydrogen sulfide per one hundred (100) standard cubic feet, no more than five (5) grains of total sulfur per one hundred (100) standard cubic feet, and at least 80% methane by volume. [District Rule 4320] Federally Enforceable Through Title V Permit
22. If the steam generator is not fired on PUC-regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. The sulfur content of the fuel shall be determined using the test methods referenced in this permit. [District Rule 4320] Federally Enforceable Through Title V Permit
23. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
24. Permittee shall maintain daily records of the type and quantity of fuel combusted by the steam generator. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
25. Permittee shall maintain records of fuel gas sulfur compound measurements. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
26. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320] Federally Enforceable Through Title V Permit
27. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 1070, 4305, 4306, 4320, and 40 CFR 60.48c (i)] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-409-3

EXPIRATION DATE: 03/31/2021

SECTION: SW 23 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

20,000 BBL FWKO VESSEL SERVED BY VAPOR RECOVERY SYSTEM LISTED IN S-1326-263

PERMIT UNIT REQUIREMENTS

1. This FWKO shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. The true vapor pressure of the liquids handled by FWKO shall not exceed 0.5 psia. [40 CFR 60 Subpart Kb and District Rule 4623] Federally Enforceable Through Title V Permit
3. VOC content of tank vapor space and vapor control system piping and components shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
4. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
5. A leak-free condition is defined as a condition without a gas leak or liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623, 3.11, 3.17, and 3.18] Federally Enforceable Through Title V Permit
6. Any tank gauging or sampling device on a vessel vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Operator shall visually inspect vessel shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shell and roof of the uninsulated vessel for structural integrity annually. [District Rule 2210] Federally Enforceable Through Title V Permit
8. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 2210] Federally Enforceable Through Title V Permit
9. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 2201] Federally Enforceable Through Title V Permit
12. If a component type for the vessel is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
15. This permit authorizes FWKO cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rule 2080] Federally Enforceable Through Title V Permit
16. Permittee shall conduct FWKO cleaning and maintenance operations in accordance with District approved procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit
17. FWKO may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit
18. Permittee shall notify the APCO in writing at least three (3) days prior to performing FWKO degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the FWKO being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the FWKO, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 2080] Federally Enforceable Through Title V Permit
19. Prior to opening the FWKO to allow FWKO cleaning, one of the following procedures must be followed: 1) Prior to venting the FWKO to the atmosphere, operate the FWKO vapor recovery system/vapor control device for at least 24 hours such that it collects the FWKO vapors; or 2) use liquid displacement, conducted using a liquid with a TVP less than 0.5 psia, or conducted by floating the oil pad off a crude oil FWKO by restricting the outflow of water, such that 90% of the FWKO volume is displaced; or 3) Vent the FWKO to a vapor control device/vapor recovery system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the FWKO to the vapor control system for a length of time determined by the following relationship: $t = 2.3 V/Q$, where t = time, V = tank volume (cubic feet), and Q = flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit
20. The FWKO shall be cleaned using one of the following methods: water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The FWKO sediment may be used for road mix as allowed by Section 6.17 of District Rule 2020. [District Rule 2080] Federally Enforceable Through Title V Permit
21. Steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

22. Prior to reintroducing crude oil/water to the FWKO, the FWKO shall be filled to the maximum possible level with water, the FWKO vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2080] Federally Enforceable Through Title V Permit
23. Within 48 hours after refilling the FWKO with crude oil/water, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA method 21 and the regular FWKO maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
24. Permittee shall maintain records of each period of cleaning and maintenance when the FWKO is disconnected or isolated from the vapor control system. Records shall include the date that FWKO cleaning was initiated, the date FWKO cleaning was completed, the procedure used to vent FWKO vapors prior to opening, the method of FWKO cleaning used, and a description of internal and external FWKO repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit
25. Operator shall conduct quarterly gas sampling after TVR compressor (prior to connection to any other vapor control system) and at either the first line tank or at any secondary tank which is heated above ambient temperature. If gas samples are less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually and whenever there is a change in source or type of petroleum processed. Samples shall be collected during periods of normal operation, and not be within 48 hours after routine maintenance or repair. [District Rule 2201] Federally Enforceable Through Title V Permit
26. VOC content of gas shall be measured using ASTM D-1945, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rule 2201] Federally Enforceable Through Title V Permit
27. The permittee shall keep accurate records of VOC content of vapors for a period of 5 years and shall make such records available for District inspection upon request. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-410-3

EXPIRATION DATE: 03/31/2021

SECTION: SW 23 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

5,000 BBL FIXED ROOF CRUDE OIL WASH TANK SERVED BY VAPOR RECOVERY SYSTEM LISTED IN S-1326-263

PERMIT UNIT REQUIREMENTS

1. Tank shall vent only to vapor control system listed on S-1326-263. [District Rule 2201] Federally Enforceable Through Title V Permit
2. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
3. VOC content of tank vapor space and vapor control system piping and components shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
4. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
5. A leak-free condition is defined as a condition without a gas leak or liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shell and roof of the uninsulated tank for structural integrity annually. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 2201] Federally Enforceable Through Title V Permit
12. If a component type for the tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
15. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rules 2020 and 2080] Federally Enforceable Through Title V Permit
16. Permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit
17. Tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit
18. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 2080] Federally Enforceable Through Title V Permit
19. Prior to opening the tank to allow tank cleaning, one of the following procedures must be followed: 1) Prior to venting the tank to the atmosphere, operate the tank vapor recovery system/vapor control device for at least 24 hours such that it collects the tank vapors; or 2) use liquid displacement, conducted using a liquid with a TVP less than 0.5 psia, or conducted by floating the oil pad off a crude oil tank by restricting the outflow of water, such that 90% of the tank volume is displaced; or 3) Vent the tank to a vapor control device/vapor recovery system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3 V/Q$, where t = time, V = tank volume (cubic feet), and Q = flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit
20. The tank shall be cleaned using one of the following methods: water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment may be used for road mix as allowed by Section 6.17 of District Rule 2020. [District Rule 2080] Federally Enforceable Through Title V Permit
21. Steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

22. Prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2080] Federally Enforceable Through Title V Permit
23. Within 48 hours after refilling the tank with crude oil/water, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
24. Operator shall conduct quarterly gas sampling after TVR compressor (prior to connection to any other vapor control system) and at either the first line tank or at any secondary tank which is heated above ambient temperature. If gas samples are less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually and whenever there is a change in source or type of petroleum processed. Samples shall be collected during periods of normal operation, and not be within 48 hours after routine maintenance or repair. [District Rule 2201] Federally Enforceable Through Title V Permit
25. VOC content of gas shall be measured using ASTM D-1945, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rule 2201] Federally Enforceable Through Title V Permit
26. Permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the procedure used to vent tank vapors prior to opening, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit
27. The permittee shall keep accurate records of VOC content of vapors for a period of 5 years and shall make such records available for District inspection upon request. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-411-3

EXPIRATION DATE: 03/31/2021

SECTION: SW 23 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

5,000 BBL FIXED ROOF CRUDE OIL LACT TANK SERVED BY VAPOR RECOVERY SYSTEM LISTED IN S-1326-263

PERMIT UNIT REQUIREMENTS

1. Tank shall vent only to vapor control system listed on S-1326-263. [District Rule 2201] Federally Enforceable Through Title V Permit
2. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
3. VOC content of tank vapor space and vapor control system piping and components shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
4. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
5. A leak-free condition is defined as a condition without a gas leak or liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shell and roof of the uninsulated tank for structural integrity annually. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 2201] Federally Enforceable Through Title V Permit
12. If a component type for the tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
15. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rules 2020 and 2080] Federally Enforceable Through Title V Permit
16. Permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit
17. Tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit
18. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 2080] Federally Enforceable Through Title V Permit
19. Prior to opening the tank to allow tank cleaning, one of the following procedures must be followed: 1) Prior to venting the tank to the atmosphere, operate the tank vapor recovery system/vapor control device for at least 24 hours such that it collects the tank vapors; or 2) use liquid displacement, conducted using a liquid with a TVP less than 0.5 psia, or conducted by floating the oil pad off a crude oil tank by restricting the outflow of water, such that 90% of the tank volume is displaced; or 3) Vent the tank to a vapor control device/vapor recovery system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3 V/Q$, where t = time, V = tank volume (cubic feet), and Q = flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit
20. The tank shall be cleaned using one of the following methods: water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment may be used for road mix as allowed by Section 6.17 of District Rule 2020. [District Rule 2080] Federally Enforceable Through Title V Permit
21. Steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

22. Prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2080] Federally Enforceable Through Title V Permit
23. Within 48 hours after refilling the tank with crude oil/water, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
24. Operator shall conduct quarterly gas sampling after TVR compressor (prior to connection to any other vapor control system) and at either the first line tank or at any secondary tank which is heated above ambient temperature. If gas samples are less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually and whenever there is a change in source or type of petroleum processed. Samples shall be collected during periods of normal operation, and not be within 48 hours after routine maintenance or repair. [District Rule 2201] Federally Enforceable Through Title V Permit
25. VOC content of gas shall be measured using ASTM D-1945, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rule 2201] Federally Enforceable Through Title V Permit
26. Permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the procedure used to vent tank vapors prior to opening, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit
27. The permittee shall keep accurate records of VOC content of vapors for a period of 5 years and shall make such records available for District inspection upon request. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-412-3

EXPIRATION DATE: 03/31/2021

SECTION: SW 23 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

3,400 BBL FIXED ROOF CRUDE OIL DRAIN TANK SERVED BY VAPOR RECOVERY SYSTEM LISTED IN S-1326-263

PERMIT UNIT REQUIREMENTS

1. Tank shall vent only to vapor control system listed on S-1326-263. [District Rule 2201] Federally Enforceable Through Title V Permit
2. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
3. VOC content of tank vapor space and vapor control system piping and components shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
4. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
5. A leak-free condition is defined as a condition without a gas leak or liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shell and roof of the uninsulated tank for structural integrity annually. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 2201] Federally Enforceable Through Title V Permit
12. If a component type for the tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
15. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rules 2020 and 2080] Federally Enforceable Through Title V Permit
16. Permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit
17. Tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit
18. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 2080] Federally Enforceable Through Title V Permit
19. Prior to opening the tank to allow tank cleaning, one of the following procedures must be followed: 1) Prior to venting the tank to the atmosphere, operate the tank vapor recovery system/vapor control device for at least 24 hours such that it collects the tank vapors; or 2) use liquid displacement, conducted using a liquid with a TVP less than 0.5 psia, or conducted by floating the oil pad off a crude oil tank by restricting the outflow of water, such that 90% of the tank volume is displaced; or 3) Vent the tank to a vapor control device/vapor recovery system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3 V/Q$, where t = time, V = tank volume (cubic feet), and Q = flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit
20. The tank shall be cleaned using one of the following methods: water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment may be used for road mix as allowed by Section 6.17 of District Rule 2020. [District Rule 2080] Federally Enforceable Through Title V Permit
21. Steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

22. Prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2080] Federally Enforceable Through Title V Permit
23. Within 48 hours after refilling the tank with crude oil/water, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
24. Operator shall conduct quarterly gas sampling after TVR compressor (prior to connection to any other vapor control system) and at either the first line tank or at any secondary tank which is heated above ambient temperature. If gas samples are less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually and whenever there is a change in source or type of petroleum processed. Samples shall be collected during periods of normal operation, and not be within 48 hours after routine maintenance or repair. [District Rule 2201] Federally Enforceable Through Title V Permit
25. VOC content of gas shall be measured using ASTM D-1945, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rule 2201] Federally Enforceable Through Title V Permit
26. Permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the procedure used to vent tank vapors prior to opening, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit
27. The permittee shall keep accurate records of VOC content of vapors for a period of 5 years and shall make such records available for District inspection upon request. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-413-3

EXPIRATION DATE: 03/31/2021

SECTION: SW 23 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

5,000 BBL FIXED ROOF CRUDE OIL REJECT TANK SERVED BY VAPOR RECOVERY SYSTEM LISTED IN S-1326-263

PERMIT UNIT REQUIREMENTS

1. Tank shall vent only to vapor control system listed on S-1326-263. [District Rule 2201] Federally Enforceable Through Title V Permit
2. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
3. VOC content of tank vapor space and vapor control system piping and components shall not exceed 10% by weight. [District Rule 2201] Federally Enforceable Through Title V Permit
4. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
5. A leak-free condition is defined as a condition without a gas leak or liquid leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shell and roof of the uninsulated tank for structural integrity annually. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take on of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rule 2201] Federally Enforceable Through Title V Permit
12. If a component type for the tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rule 2201] Federally Enforceable Through Title V Permit
15. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rules 2020 and 2080] Federally Enforceable Through Title V Permit
16. Permittee shall conduct tank cleaning and maintenance operations in accordance with District approved procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit
17. Tank may be disconnected from vapor control system during District approved cleaning and maintenance procedures as described in this permit. [District Rule 2080] Federally Enforceable Through Title V Permit
18. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 2080] Federally Enforceable Through Title V Permit
19. Prior to opening the tank to allow tank cleaning, one of the following procedures must be followed: 1) Prior to venting the tank to the atmosphere, operate the tank vapor recovery system/vapor control device for at least 24 hours such that it collects the tank vapors; or 2) use liquid displacement, conducted using a liquid with a TVP less than 0.5 psia, or conducted by floating the oil pad off a crude oil tank by restricting the outflow of water, such that 90% of the tank volume is displaced; or 3) Vent the tank to a vapor control device/vapor recovery system until the vapor concentration is less than 10% of the lower explosive limit (LEL) or 5,000 ppmv whichever is less; or 4) vent the tank to the vapor control system for a length of time determined by the following relationship: $t = 2.3 V/Q$, where t = time, V = tank volume (cubic feet), and Q = flow rate to the vapor control system as determined using appropriate engineering calculations. [District Rule 2080] Federally Enforceable Through Title V Permit
20. The tank shall be cleaned using one of the following methods: water, hot water, solvents with an initial boiling point of greater than 302 F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams VOC per liter or less. The tank sediment may be used for road mix as allowed by Section 6.17 of District Rule 2020. [District Rule 2080] Federally Enforceable Through Title V Permit
21. Steam cleaning shall be allowed only during December through March, or at locations where wastewater treatment facilities are limited. [District Rule 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

22. Prior to reintroducing crude oil/water to the tank, the tank shall be filled to the maximum possible level with water, the tank vapor control system shall be reactivated and pressure/relief valves closed, and the liquid level shall be adjusted as necessary. [District Rule 2080] Federally Enforceable Through Title V Permit
23. Within 48 hours after refilling the tank with crude oil/water, the pressure relief valve seats and hatch seals shall be inspected for leaks using EPA method 21 and the regular tank maintenance and inspection program shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
24. Operator shall conduct quarterly gas sampling after TVR compressor (prior to connection to any other vapor control system) and at either the first line tank or at any secondary tank which is heated above ambient temperature. If gas samples are less than 10% VOC by weight for 8 consecutive quarterly samplings, sampling frequency shall only be required annually and whenever there is a change in source or type of petroleum processed. Samples shall be collected during periods of normal operation, and not be within 48 hours after routine maintenance or repair. [District Rule 2201] Federally Enforceable Through Title V Permit
25. VOC content of gas shall be measured using ASTM D-1945, EPA Method 18 referenced as methane, or equivalent test method with prior District approval. [District Rule 2201] Federally Enforceable Through Title V Permit
26. Permittee shall maintain records of each period of cleaning and maintenance when the tank is disconnected or isolated from the vapor control system. Records shall include the date that tank cleaning was initiated, the date tank cleaning was completed, the procedure used to vent tank vapors prior to opening, the method of tank cleaning used, and a description of internal and external tank repairs and maintenance performed. Such records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 2080] Federally Enforceable Through Title V Permit
27. The permittee shall keep accurate records of VOC content of vapors for a period of 5 years and shall make such records available for District inspection upon request. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-417-3

EXPIRATION DATE: 03/31/2021

EQUIPMENT DESCRIPTION:

85 MMBTU/HR NATURAL GAS-FIRED STEAM GENERATOR WITH NORTH AMERICAN 4231-85 GLE BURNER AND A FLUE GAS RECIRCULATION SYSTEM

PERMIT UNIT REQUIREMENTS

1. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
4. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
5. The unit shall only be fired on PUC-quality natural gas with a maximum sulfur content of 1.0 gr S/100scf. [District Rules 2201 4801, and 4320] Federally Enforceable Through Title V Permit
6. Permittee shall test annually the sulfur content of the fuel gas combusted in steam generator using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit
7. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
8. Emission rates shall not exceed: PM10: 0.003 lb/MMBtu, VOC: 0.0055 lb/MMBtu, NOx (as NO2): 7 ppmvd NOx @ 3% O2, or CO: 25 ppmv @ 3% O2. [District Rules 2201, 4201, 4301, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit
9. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
10. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. Unless otherwise specified in the Permit to Operate, no determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
11. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
13. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
14. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5, 4306, 5.5.5, and 4320] Federally Enforceable Through Title V Permit
15. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; Stack gas oxygen (O₂) - EPA Method 3 or 3A or ARB Method 100; stack gas velocities - EPA Method 2; Stack gas moisture content - EPA Method 4; SOx - EPA Method 6C or 8 or ARB Method 100; fuel gas sulfur as H₂S content - EPA Method 11 or 15; and fuel hhv (MMBtu) - ASTM D 1826 or D 1945 in conjunction with ASTM D 3588. [District Rule 1081, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit
16. The permittee shall monitor and record the stack concentration of NOx, CO, and O₂ at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
17. If either the NOx or CO concentrations corrected to 3% O₂, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
18. All NOx, CO, and O₂ emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
19. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O₂ measurements, (2) the O₂ concentration in percent and the measured NOx and CO concentrations corrected to 3% O₂, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
20. PUC quality natural gas is any gaseous fuel where the sulfur content is no more than one-fourth (0.25) grain of hydrogen sulfide per one hundred (100) standard cubic feet, no more than five (5) grains of total sulfur per one hundred (100) standard cubic feet, and at least 80% methane by volume. [District Rule 4320] Federally Enforceable Through Title V Permit
21. If the steam generator is not fired on PUC-regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. The sulfur content of the fuel shall be determined using the test methods referenced in this permit. [District Rule 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

22. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
23. Permittee shall maintain daily records of the type and quantity of fuel combusted by the steam generator. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
24. Permittee shall maintain records of fuel gas sulfur compound measurements. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
25. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320] Federally Enforceable Through Title V Permit
26. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 1070, 4305, 4306, 4320, and 40 CFR 60.48c (i)] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-418-3

EXPIRATION DATE: 03/31/2021

EQUIPMENT DESCRIPTION:

85 MMBTU/HR NATURAL GAS-FIRED STEAM GENERATOR WITH COEN QLN-II ULTRA LOW NOX BURNER AND A FLUE GAS RECIRCULATION SYSTEM

PERMIT UNIT REQUIREMENTS

1. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
2. Steam generator shall be equipped with variable frequency drive electrical motors driving the blower and water pump and a convection section with at least 235 square feet of heat transfer surface area per MMBtu/hr of maximum rated heat input (verified by manufacturer) or a manufacturer's overall thermal efficiency rating of 88%. [Public Resources Code 21000-21177: California Environmental Quality Act]
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
5. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
6. The unit shall only be fired on PUC-quality natural gas with a maximum sulfur content of 1.0 gr S/100scf. [District Rules 2201 4801, and 4320] Federally Enforceable Through Title V Permit
7. Permittee shall test annually the sulfur content of the fuel gas combusted in steam generator using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit
8. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
9. Emission rates shall not exceed: PM10: 0.003 lb/MMBtu, VOC: 0.0055 lb/MMBtu, NOx (as NO2): 7 ppmvd NOx @ 3% O2, or CO: 25 ppmv @ 3% O2. [District Rules 2201, 4201, 4301, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit
10. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. Unless otherwise specified in the Permit to Operate, no determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
12. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
13. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
14. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
15. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5, 4306, 5.5.5, and 4320] Federally Enforceable Through Title V Permit
16. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; Stack gas oxygen (O2) - EPA Method 3 or 3A or ARB Method 100; stack gas velocities - EPA Method 2; Stack gas moisture content - EPA Method 4; SOx - EPA Method 6C or 8 or ARB Method 100; fuel gas sulfur as H2S content - EPA Method 11 or 15; and fuel hhv (MMBtu) - ASTM D 1826 or D 1945 in conjunction with ASTM D 3588. [District Rule 1081, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit
17. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
18. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
19. All NOx, CO, and O2 emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
20. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. PUC quality natural gas is any gaseous fuel where the sulfur content is no more than one-fourth (0.25) grain of hydrogen sulfide per one hundred (100) standard cubic feet, no more than five (5) grains of total sulfur per one hundred (100) standard cubic feet, and at least 80% methane by volume. [District Rule 4320] Federally Enforceable Through Title V Permit
22. If the steam generator is not fired on PUC-regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. The sulfur content of the fuel shall be determined using the test methods referenced in this permit. [District Rule 4320] Federally Enforceable Through Title V Permit
23. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
24. Permittee shall maintain daily records of the type and quantity of fuel combusted by the steam generator. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
25. Permittee shall maintain records of fuel gas sulfur compound measurements. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
26. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320] Federally Enforceable Through Title V Permit
27. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 1070, 4305, 4306, 4320, and 40 CFR 60.48c (i)] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-419-4

EXPIRATION DATE: 03/31/2021

SECTION: NW 26 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

85 MMBTU/HR TEOR/TVR/NATURAL GAS-FIRED STEAM GENERATOR WITH A COEN QLN-II BURNER AND A FLUE GAS RECIRCULATION SYSTEM

PERMIT UNIT REQUIREMENTS

1. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
4. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
5. The unit shall only be fired on gas with a maximum sulfur content of 1.0 gr S/100scf. [District Rules 2201, 4301, 4320, and 4801] Federally Enforceable Through Title V Permit
6. Permittee shall test annually the sulfur content of the fuel gas combusted in steam generator using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rules 2520, 9.3.2 and 4320] Federally Enforceable Through Title V Permit
7. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
8. Emission rates shall not exceed: PM10: 0.003 lb/MMBtu, VOC: 0.0055 lb/MMBtu, NOx (as NO2): 7 ppmvd NOx @ 3% O2, or CO: 25 ppmv @ 3% O2. [District Rules 2201, 4201, 4301, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit
9. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
10. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. Unless otherwise specified in the Permit to Operate, no determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
12. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
13. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
14. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 5.5.5, 4306, 5.5.5, and 4320] Federally Enforceable Through Title V Permit
15. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; Stack gas oxygen (O2) - EPA Method 3 or 3A or ARB Method 100; stack gas velocities - EPA Method 2; Stack gas moisture content - EPA Method 4; SOx - EPA Method 6C or 8 or ARB Method 100; fuel gas sulfur as H2S content - EPA Method 11 or 15; and fuel hhv (MMBtu) - ASTM D 1826 or D 1945 in conjunction with ASTM D 3588. [District Rule 1081, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit
16. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
17. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
18. All NOx, CO, and O2 emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
19. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
20. PUC quality natural gas is any gaseous fuel where the sulfur content is no more than one-fourth (0.25) grain of hydrogen sulfide per one hundred (100) standard cubic feet, no more than five (5) grains of total sulfur per one hundred (100) standard cubic feet, and at least 80% methane by volume. [District Rule 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. If the steam generator is not fired on PUC-regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. The sulfur content of the fuel shall be determined using the test methods referenced in this permit. [District Rule 4320] Federally Enforceable Through Title V Permit
22. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
23. Permittee shall maintain daily records of the type and quantity of fuel combusted by the steam generator. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
24. Permittee shall maintain records of fuel gas sulfur compound measurements. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
25. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320] Federally Enforceable Through Title V Permit
26. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 1070, 4305, 4306, 4320, and 40 CFR 60.48c (i)] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-420-3

EXPIRATION DATE: 03/31/2021

SECTION: NW 26 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

85 MMBTU/HR TEOR/TVR/NATURAL GAS-FIRED STEAM GENERATOR WITH A COEN QLN-II BURNER AND A FLUE GAS RECIRCULATION SYSTEM

PERMIT UNIT REQUIREMENTS

1. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
4. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
5. The unit shall only be fired on gas with a maximum sulfur content of 1.0 gr S/100scf. [District Rules 2201, 4301, 4320, and 4801] Federally Enforceable Through Title V Permit
6. Permittee shall test annually the sulfur content of the fuel gas combusted in steam generator using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rule 4320] Federally Enforceable Through Title V Permit
7. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
8. Emission rates shall not exceed: PM10: 0.003 lb/MMBtu, VOC: 0.0055 lb/MMBtu, NOx (as NO2): 7 ppmvd NOx @ 3% O2, or CO: 25 ppmv @ 3% O2. [District Rules 2201, 4201, 4301, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit
9. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. Unless otherwise specified in the Permit to Operate, no determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
12. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
14. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
15. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; Stack gas oxygen (O2) - EPA Method 3 or 3A or ARB Method 100; stack gas velocities - EPA Method 2; Stack gas moisture content - EPA Method 4; SOx - EPA Method 6C or 8 or ARB Method 100; fuel gas sulfur as H2S content - EPA Method 11 or 15; and fuel hhv (MMBtu) - ASTM D 1826 or D 1945 in conjunction with ASTM D 3588. [District Rule 1081, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit
16. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
17. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
18. All NOx, CO, and O2 emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
19. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
20. PUC quality natural gas is any gaseous fuel where the sulfur content is no more than one-fourth (0.25) grain of hydrogen sulfide per one hundred (100) standard cubic feet, no more than five (5) grains of total sulfur per one hundred (100) standard cubic feet, and at least 80% methane by volume. [District Rule 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. If the steam generator is not fired on PUC-regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. The sulfur content of the fuel shall be determined using the test methods referenced in this permit. [District Rule 4320] Federally Enforceable Through Title V Permit
22. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
23. Permittee shall maintain daily records of the type and quantity of fuel combusted by the steam generator. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
24. Permittee shall maintain records of fuel gas sulfur compound measurements. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
25. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320] Federally Enforceable Through Title V Permit
26. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 1070, 4305, 4306, 4320, and 40 CFR 60.48c (i)] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-421-3

EXPIRATION DATE: 03/31/2021

SECTION: NW 26 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

85 MMBTU/HR TEOR/TVR/NATURAL GAS-FIRED STEAM GENERATOR WITH A COEN QLN-II BURNER AND A FLUE GAS RECIRCULATION SYSTEM

PERMIT UNIT REQUIREMENTS

1. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
4. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
5. The unit shall only be fired on gas with a maximum sulfur content of 1.0 gr S/100scf. [District Rules 2201, 4301, 4320, and 4801] Federally Enforceable Through Title V Permit
6. Permittee shall test annually the sulfur content of the fuel gas combusted in steam generator using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rule 4320] Federally Enforceable Through Title V Permit
7. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
8. Emission rates shall not exceed: PM10: 0.003 lb/MMBtu, VOC: 0.0055 lb/MMBtu, NOx (as NO2): 7 ppmvd NOx @ 3% O2, or CO: 25 ppmv @ 3% O2. [District Rules 2201, 4201, 4301, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit
9. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. Unless otherwise specified in the Permit to Operate, no determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
12. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
14. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
15. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; Stack gas oxygen (O2) - EPA Method 3 or 3A or ARB Method 100; stack gas velocities - EPA Method 2; Stack gas moisture content - EPA Method 4; SOx - EPA Method 6C or 8 or ARB Method 100; fuel gas sulfur as H2S content - EPA Method 11 or 15; and fuel hhv (MMBtu) - ASTM D 1826 or D 1945 in conjunction with ASTM D 3588. [District Rule 1081, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit
16. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
17. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
18. All NOx, CO, and O2 emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
19. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
20. PUC quality natural gas is any gaseous fuel where the sulfur content is no more than one-fourth (0.25) grain of hydrogen sulfide per one hundred (100) standard cubic feet, no more than five (5) grains of total sulfur per one hundred (100) standard cubic feet, and at least 80% methane by volume. [District Rule 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. If the steam generator is not fired on PUC-regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. The sulfur content of the fuel shall be determined using the test methods referenced in this permit. [District Rule 4320] Federally Enforceable Through Title V Permit
22. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
23. Permittee shall maintain daily records of the type and quantity of fuel combusted by the steam generator. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
24. Permittee shall maintain records of fuel gas sulfur compound measurements. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
25. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320] Federally Enforceable Through Title V Permit
26. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 1070, 4305, 4306, 4320, and 40 CFR 60.48c (i)] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-422-3

EXPIRATION DATE: 03/31/2021

SECTION: NW 26 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

85 MMBTU/HR TEOR/TVR/NATURAL GAS-FIRED STEAM GENERATOR WITH A COEN QLN-II BURNER AND A FLUE GAS RECIRCULATION SYSTEM

PERMIT UNIT REQUIREMENTS

1. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101]
Federally Enforceable Through Title V Permit
4. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
5. The unit shall only be fired on gas with a maximum sulfur content of 1.0 gr S/100scf. [District Rules 2201, 4301, 4320, and 4801] Federally Enforceable Through Title V Permit
6. Permittee shall test annually the sulfur content of the fuel gas combusted in steam generator using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rule 4320]
Federally Enforceable Through Title V Permit
7. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
8. Emission rates shall not exceed: PM10: 0.003 lb/MMBtu, VOC: 0.0055 lb/MMBtu, NOx (as NO2): 7 ppmvd NOx @ 3% O2, or CO: 25 ppmv @ 3% O2. [District Rules 2201, 4201, 4301, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit
9. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. Unless otherwise specified in the Permit to Operate, no determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
12. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
14. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
15. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; Stack gas oxygen (O2) - EPA Method 3 or 3A or ARB Method 100; stack gas velocities - EPA Method 2; Stack gas moisture content - EPA Method 4; SOx - EPA Method 6C or 8 or ARB Method 100; fuel gas sulfur as H2S content - EPA Method 11 or 15; and fuel hhv (MMBtu) - ASTM D 1826 or D 1945 in conjunction with ASTM D 3588. [District Rule 1081, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit
16. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
17. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
18. All NOx, CO, and O2 emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
19. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
20. PUC quality natural gas is any gaseous fuel where the sulfur content is no more than one-fourth (0.25) grain of hydrogen sulfide per one hundred (100) standard cubic feet, no more than five (5) grains of total sulfur per one hundred (100) standard cubic feet, and at least 80% methane by volume. [District Rule 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. If the steam generator is not fired on PUC-regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. The sulfur content of the fuel shall be determined using the test methods referenced in this permit. [District Rule 4320] Federally Enforceable Through Title V Permit
22. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
23. Permittee shall maintain daily records of the type and quantity of fuel combusted by the steam generator. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
24. Permittee shall maintain records of fuel gas sulfur compound measurements. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
25. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320] Federally Enforceable Through Title V Permit
26. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 1070, 4305, 4306, 4320, and 40 CFR 60.48c (i)] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-423-3

EXPIRATION DATE: 03/31/2021

SECTION: NW 26 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

85 MMBTU/HR TEOR/TVR/NATURAL GAS-FIRED STEAM GENERATOR WITH A COEN QLN-II BURNER AND A FLUE GAS RECIRCULATION SYSTEM

PERMIT UNIT REQUIREMENTS

1. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
4. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
5. The unit shall only be fired on gas with a maximum sulfur content of 1.0 gr S/100scf. [District Rules 2201, 4301, 4320, and 4801] Federally Enforceable Through Title V Permit
6. Permittee shall test annually the sulfur content of the fuel gas combusted in steam generator using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rule 4320] Federally Enforceable Through Title V Permit
7. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
8. Emission rates shall not exceed: PM10: 0.003 lb/MMBtu, VOC: 0.0055 lb/MMBtu, NOx (as NO2): 7 ppmvd NOx @ 3% O2, or CO: 25 ppmv @ 3% O2. [District Rules 2201, 4201, 4301, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit
9. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. Unless otherwise specified in the Permit to Operate, no determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
12. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
14. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
15. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; Stack gas oxygen (O2) - EPA Method 3 or 3A or ARB Method 100; stack gas velocities - EPA Method 2; Stack gas moisture content - EPA Method 4; SOx - EPA Method 6C or 8 or ARB Method 100; fuel gas sulfur as H2S content - EPA Method 11 or 15; and fuel hhv (MMBtu) - ASTM D 1826 or D 1945 in conjunction with ASTM D 3588. [District Rule 1081, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit
16. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
17. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
18. All NOx, CO, and O2 emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
19. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
20. PUC quality natural gas is any gaseous fuel where the sulfur content is no more than one-fourth (0.25) grain of hydrogen sulfide per one hundred (100) standard cubic feet, no more than five (5) grains of total sulfur per one hundred (100) standard cubic feet, and at least 80% methane by volume. [District Rule 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. If the steam generator is not fired on PUC-regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. The sulfur content of the fuel shall be determined using the test methods referenced in this permit. [District Rule 4320] Federally Enforceable Through Title V Permit
22. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
23. Permittee shall maintain daily records of the type and quantity of fuel combusted by the steam generator. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
24. Permittee shall maintain records of fuel gas sulfur compound measurements. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
25. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320] Federally Enforceable Through Title V Permit
26. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 1070, 4305, 4306, 4320, and 40 CFR 60.48c (i)] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-424-3

EXPIRATION DATE: 03/31/2021

SECTION: NW 26 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

85 MMBTU/HR TEOR/TVR/NATURAL GAS-FIRED STEAM GENERATOR WITH A COEN QLN-II BURNER AND A FLUE GAS RECIRCULATION SYSTEM

PERMIT UNIT REQUIREMENTS

1. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
4. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
5. The unit shall only be fired on gas with a maximum sulfur content of 1.0 gr S/100scf. [District Rules 2201, 4301, 4320, and 4801] Federally Enforceable Through Title V Permit
6. Permittee shall test annually the sulfur content of the fuel gas combusted in steam generator using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rule 4320] Federally Enforceable Through Title V Permit
7. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
8. Emission rates shall not exceed: PM10: 0.003 lb/MMBtu, VOC: 0.0055 lb/MMBtu, NOx (as NO2): 7 ppmvd NOx @ 3% O2, or CO: 25 ppmv @ 3% O2. [District Rules 2201, 4201, 4301, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit
9. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. Unless otherwise specified in the Permit to Operate, no determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
12. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
14. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
15. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; Stack gas oxygen (O2) - EPA Method 3 or 3A or ARB Method 100; stack gas velocities - EPA Method 2; Stack gas moisture content - EPA Method 4; SOx - EPA Method 6C or 8 or ARB Method 100; fuel gas sulfur as H2S content - EPA Method 11 or 15; and fuel hhv (MMBtu) - ASTM D 1826 or D 1945 in conjunction with ASTM D 3588. [District Rule 1081, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit
16. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
17. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
18. All NOx, CO, and O2 emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
19. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
20. PUC quality natural gas is any gaseous fuel where the sulfur content is no more than one-fourth (0.25) grain of hydrogen sulfide per one hundred (100) standard cubic feet, no more than five (5) grains of total sulfur per one hundred (100) standard cubic feet, and at least 80% methane by volume. [District Rule 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. If the steam generator is not fired on PUC-regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. The sulfur content of the fuel shall be determined using the test methods referenced in this permit. [District Rule 4320] Federally Enforceable Through Title V Permit
22. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
23. Permittee shall maintain daily records of the type and quantity of fuel combusted by the steam generator. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
24. Permittee shall maintain records of fuel gas sulfur compound measurements. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
25. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320] Federally Enforceable Through Title V Permit
26. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 1070, 4305, 4306, 4320, and 40 CFR 60.48c (i)] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-425-3

EXPIRATION DATE: 03/31/2021

SECTION: NW 26 **TOWNSHIP:** 28S **RANGE:** 27E

EQUIPMENT DESCRIPTION:

85 MMBTU/HR TEOR/TVR/NATURAL GAS-FIRED STEAM GENERATOR WITH A COEN QLN-II BURNER AND A FLUE GAS RECIRCULATION SYSTEM

PERMIT UNIT REQUIREMENTS

1. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101]
Federally Enforceable Through Title V Permit
4. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
5. The unit shall only be fired on gas with a maximum sulfur content of 1.0 gr S/100scf. [District Rules 2201, 4301, 4320, and 4801] Federally Enforceable Through Title V Permit
6. Permittee shall test annually the sulfur content of the fuel gas combusted in steam generator using ASTM method D1072, D3031, D4084, or D3246 and make test results readily available for District inspection. [District Rule 4320]
Federally Enforceable Through Title V Permit
7. If fuel analysis is used to demonstrate compliance with the conditions of this permit, the fuel higher heating value for each fuel shall be certified by third party fuel supplier or determined by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
8. Emission rates shall not exceed: PM10: 0.003 lb/MMBtu, VOC: 0.0055 lb/MMBtu, NOx (as NO2): 7 ppmvd NOx @ 3% O2, or CO: 25 ppmv @ 3% O2. [District Rules 2201, 4201, 4301, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit
9. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. Unless otherwise specified in the Permit to Operate, no determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
12. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
14. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
15. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19; CO (ppmv) - EPA Method 10 or ARB Method 100; Stack gas oxygen (O2) - EPA Method 3 or 3A or ARB Method 100; stack gas velocities - EPA Method 2; Stack gas moisture content - EPA Method 4; SOx - EPA Method 6C or 8 or ARB Method 100; fuel gas sulfur as H2S content - EPA Method 11 or 15; and fuel hhv (MMBtu) - ASTM D 1826 or D 1945 in conjunction with ASTM D 3588. [District Rule 1081, 4305, 4306, 4320, and 4351] Federally Enforceable Through Title V Permit
16. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
17. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
18. All NOx, CO, and O2 emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
19. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
20. PUC quality natural gas is any gaseous fuel where the sulfur content is no more than one-fourth (0.25) grain of hydrogen sulfide per one hundred (100) standard cubic feet, no more than five (5) grains of total sulfur per one hundred (100) standard cubic feet, and at least 80% methane by volume. [District Rule 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

21. If the steam generator is not fired on PUC-regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. The sulfur content of the fuel shall be determined using the test methods referenced in this permit. [District Rule 4320] Federally Enforceable Through Title V Permit
22. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
23. Permittee shall maintain daily records of the type and quantity of fuel combusted by the steam generator. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
24. Permittee shall maintain records of fuel gas sulfur compound measurements. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
25. If the unit is fired on PUC-regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320] Federally Enforceable Through Title V Permit
26. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 1070, 4305, 4306, 4320, and 40 CFR 60.48c (i)] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-435-2

EXPIRATION DATE: 03/31/2021

EQUIPMENT DESCRIPTION:

25 MMBTU/HR NATURAL GAS/TEOR GAS/FIELD GAS/PROPANE FIRED PORTABLE STEAM GENERATOR WITH NORTH AMERICAN LE, COEN QLN-11, OR EQUIVALENT BURNER AND FLUE GAS RECIRCULATION (VARIOUS UNSPECIFIED LOCATIONS WITHIN HEAVY OIL CENTRAL STATIONARY SOURCE)

PERMIT UNIT REQUIREMENTS

1. This unit is permitted as S-1326-435, S-1327-208, S-1737-194 and S-1738-466 and is approved to operate in Vintage Production's and Occidental's, or its subsidiary's, Light and Heavy Oil Western and Central stationary sources. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The permittee shall obtain written District approval for the use of any equivalent equipment not specifically approved by this Authority to Construct. Approval of the equivalent equipment shall be made only after the District's determination that the submitted design and performance of the proposed alternate equipment is equivalent to the specifically authorized equipment. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The permittee's request for approval of equivalent equipment shall include the make, model, manufacturer's maximum rating, manufacturer's guaranteed emission rates, equipment drawing(s), and operational characteristics/parameters. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Alternate equipment shall be of the same class and category of source as the equipment authorized by the Authority to Construct. [District Rule 2201] Federally Enforceable Through Title V Permit
5. No emission factor and no emission shall be greater for the alternate equipment than for the proposed equipment. No changes in the hours of operation, operating rate, throughput, or firing rate may be authorized for any alternate equipment. [District Rule 2201] Federally Enforceable Through Title V Permit
6. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
7. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
8. This unit shall only use public utility supplied power for its electrical needs and shall not utilize IC engine powered electrical generators. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The unit shall not operate within 100 meters of the facility boundary. [District Rule 4102]
10. Unit shall not be located within 1000 feet of any K-12 school. [CH&SC 42301.6]
11. Permittee shall notify the District Compliance Division to arrange a start-up inspection at the initial location of the unit. [District Rule 1070]
12. Permittee shall notify the District Compliance Division of each location at which the unit is located in excess of 24 hours. Such notification shall be made no later than 48 hours after starting operation at the location. [District Rule 1070]
13. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

14. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
15. Unit shall be fired only on LPG or propane, regulated natural gas, TEOR gas or waste/field gas, or a mixture of any of these fuels, with no more than 1.0 gr-S/100 scf, or waste/field gas treated to remove at least 95% by weight of sulfur compounds. [District Rule 2201]
16. Except for periods of startup and shutdown, emissions shall not exceed any of the following limits: 7 ppmvd NOx @ 3% O2 or 0.008 lb-NOx/MMBtu, 0.016 lb-SOx/MMBtu, 0.0076 lb-PM10/MMBtu, 25 ppmvd CO @ 3% O2 or 0.0185 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
17. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
18. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
19. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months thereafter. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
20. Source testing and/or stack monitoring prescribed in this permit shall not be required while this equipment is in storage or is located outside of the jurisdiction of the San Joaquin Valley Air Pollution Control District. Upon reactivation from storage or relocation of this equipment within the jurisdiction of the SJVUAPCD, normal source testing and/or stack monitoring shall recommence. If a source test is postponed due to the equipment being in storage or located outside of SJVAPCD jurisdiction, a source test shall be conducted within 60 days of recommencing operation within the jurisdiction of the SJVUAPCD. [District Rules 201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
21. If and when this unit is fired on LPG/propane, source testing to measure NOx and CO emissions from this unit shall be conducted within 60 days of first firing on the LPG/propane fuel. Additional source testing when firing on LPG/propane fuel is not required, but may be conducted and used by the operator to satisfy the applicable twelve (12) month or thirty-six (36) month periodic testing required by this permit. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
22. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
23. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
24. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
25. NOx emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
26. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

27. Stack gas oxygen (O₂) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
28. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
29. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
30. The operator shall determine within 60 days of first use and annually thereafter the fuel sulfur content of each source of unregulated natural gas fuel combusted in this unit using EPA Method 11 or 15, or ASTM Method D1072, D3246 or D6228 or double GC with mercaptans. In lieu of fuel sulfur content testing, the operator may conduct a source test for combustion SO_x emissions within 60 days of startup and at least once every 12 months thereafter. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
31. If the unit is fired on regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320] Federally Enforceable Through Title V Permit
32. If the unit is not fired solely on regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. The sulfur content of the fuel shall be determined using the test methods referenced in this permit. [District Rule 4320] Federally Enforceable Through Title V Permit
33. The permittee shall monitor and record the stack concentration of NO_x, CO, and O₂ at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
34. If either the NO_x or CO concentrations corrected to 3% O₂, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
35. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
36. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

37. Permittee shall maintain daily records of the type and quantity of fuel combusted by the steam generator. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
38. The permittee shall maintain records of: (1) the date and time of NO_x, CO, and O₂ measurements, (2) the O₂ concentration in percent and the measured NO_x and CO concentrations corrected to 3% O₂, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
39. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 1070, 4305, 4306, 4320, and 40 CFR 60.48c (i)] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1326-443-2

EXPIRATION DATE: 03/31/2021

EQUIPMENT DESCRIPTION:

25 MMBTU/HR NATURAL GAS/TEOR GAS/FIELD GAS/PROPANE FIRED PORTABLE STEAM GENERATOR WITH NORTH AMERICAN LE, COEN QLN-11, OR EQUIVALENT BURNER AND FLUE GAS RECIRCULATION (VARIOUS UNSPECIFIED LOCATIONS WITHIN HEAVY OIL CENTRAL STATIONARY SOURCE)

PERMIT UNIT REQUIREMENTS

1. This unit is permitted as S-1326-443, S-1327-195, S-1737-195 and S-1738-493 and is approved to operate in Vintage Production's and Occidental's, or its subsidiary's, Light and Heavy Oil Western and Central stationary sources. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The permittee shall obtain written District approval for the use of any equivalent equipment not specifically approved by this Authority to Construct. Approval of the equivalent equipment shall be made only after the District's determination that the submitted design and performance of the proposed alternate equipment is equivalent to the specifically authorized equipment. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The permittee's request for approval of equivalent equipment shall include the make, model, manufacturer's maximum rating, manufacturer's guaranteed emission rates, equipment drawing(s), and operational characteristics/parameters. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Alternate equipment shall be of the same class and category of source as the equipment authorized by the Authority to Construct. [District Rule 2201] Federally Enforceable Through Title V Permit
5. No emission factor and no emission shall be greater for the alternate equipment than for the proposed equipment. No changes in the hours of operation, operating rate, throughput, or firing rate may be authorized for any alternate equipment. [District Rule 2201] Federally Enforceable Through Title V Permit
6. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
7. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
8. This unit shall only use public utility supplied power for its electrical needs and shall not utilize IC engine powered electrical generators. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The unit shall not operate within 100 meters of the facility boundary. [District Rule 4102]
10. Unit shall not be located within 1000 feet of any K-12 school. [CH&SC 42301.6]
11. Permittee shall notify the District Compliance Division to arrange a start-up inspection at the initial location of the unit. [District Rule 1070]
12. Permittee shall notify the District Compliance Division of each location at which the unit is located in excess of 24 hours. Such notification shall be made no later than 48 hours after starting operation at the location. [District Rule 1070]
13. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

14. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
15. Unit shall be fired only on LPG or propane, regulated natural gas, TEOR gas or waste/field gas, or a mixture of any of these fuels, with no more than 1.0 gr-S/100 scf, or waste/field gas treated to remove at least 95% by weight of sulfur compounds. [District Rule 2201]
16. Except for periods of startup and shutdown, emissions shall not exceed any of the following limits: 7 ppmvd NOx @ 3% O2 or 0.008 lb-NOx/MMBtu, 0.016 lb-SOx/MMBtu, 0.0076 lb-PM10/MMBtu, 25 ppmvd CO @ 3% O2 or 0.0185 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
17. Duration of start-up or shutdown shall not exceed two hours each per occurrence. During start-up or shutdown, the emissions control system shall be in operation, and emissions shall be minimized insofar as technologically possible. The operator shall maintain daily records of the duration of start-up and shutdown periods. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
18. Start-up is defined as the period of time during which a unit is brought from a shutdown status to its operating temperature and pressure, including the time required by the unit's emission control system to reach full operation. Shutdown is defined as the period of time during which a unit is taken from an operational to a non-operational status by allowing it to cool down from its operating temperature to ambient temperature as the fuel supply to the unit is completely turned off. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
19. Source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months thereafter. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
20. Source testing and/or stack monitoring prescribed in this permit shall not be required while this equipment is in storage or is located outside of the jurisdiction of the San Joaquin Valley Air Pollution Control District. Upon reactivation from storage or relocation of this equipment within the jurisdiction of the SJVUAPCD, normal source testing and/or stack monitoring shall recommence. If a source test is postponed due to the equipment being in storage or located outside of SJVAPCD jurisdiction, a source test shall be conducted within 60 days of recommencing operation within the jurisdiction of the SJVUAPCD. [District Rules 201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
21. If and when this unit is fired on LPG/propane, source testing to measure NOx and CO emissions from this unit shall be conducted within 60 days of first firing on the LPG/propane fuel. Additional source testing when firing on LPG/propane fuel is not required, but may be conducted and used by the operator to satisfy the applicable twelve (12) month or thirty-six (36) month periodic testing required by this permit. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
22. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
23. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
24. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
25. NOx emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
26. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

27. Stack gas oxygen (O₂) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
28. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
29. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
30. The operator shall determine within 60 days of first use and annually thereafter the fuel sulfur content of each source of unregulated natural gas fuel combusted in this unit using EPA Method 11 or 15, or ASTM Method D1072, D3246 or D6228 or double GC with mercaptans. In lieu of fuel sulfur content testing, the operator may conduct a source test for combustion SO_x emissions within 60 days of startup and at least once every 12 months thereafter. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
31. If the unit is fired on regulated natural gas, valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy the fuel sulfur content analysis, provided they establish the fuel sulfur concentration and higher heating value. [District Rule 4320] Federally Enforceable Through Title V Permit
32. If the unit is not fired solely on regulated natural gas and compliance is achieved through fuel sulfur content limitations, then the sulfur content of the fuel shall be determined by testing sulfur content at a location after all fuel sources are combined prior to incineration, or by performing mass balance calculations based on monitoring the sulfur content and volume of each fuel source. The sulfur content of the fuel shall be determined using the test methods referenced in this permit. [District Rule 4320] Federally Enforceable Through Title V Permit
33. The permittee shall monitor and record the stack concentration of NO_x, CO, and O₂ at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
34. If either the NO_x or CO concentrations corrected to 3% O₂, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
35. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
36. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

37. Permittee shall maintain daily records of the type and quantity of fuel combusted by the steam generator. [District Rule 2201 and 40 CFR 60.48c (g)] Federally Enforceable Through Title V Permit
38. The permittee shall maintain records of: (1) the date and time of NO_x, CO, and O₂ measurements, (2) the O₂ concentration in percent and the measured NO_x and CO concentrations corrected to 3% O₂, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
39. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 1070, 4305, 4306, 4320, and 40 CFR 60.48c (i)] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

PERMIT-EXEMPT EQUIPMENT REGISTRATION (PEER)

PEER NO: S-1326-2-0

EXPIRATION DATE: 03/27/2013

LEGAL OWNER OR OPERATOR: CALIFORNIA RESOURCES PRODUCTION CORP

MAILING ADDRESS: 11109 RIVER RUN BLVD
BAKERSFIELD, CA 93311

FACILITY LOCATION: HEAVY OIL CENTRAL STATIONARY SOURCE
KERN COUNTY, CA

SECTION: 9 **TOWNSHIP:** 27S **RANGE:** 28E

LOCATION DESCRIPTION: VPC 2

EQUIPMENT DESCRIPTION:

4.2 MMBTU/HR NATURAL GAS-FIRED BOILER (DORMANT - NOT OPERATIONAL)

CONDITIONS

1. The fuel supply line shall be physically disconnected from the unit. [District Rules 4307]
2. The unit shall not be operated for any reason until the necessary retrofit/replacement is made to comply with District Rule 4307. [District Rule 4307]
3. Prior to operating a 4307-compliant replacement or retrofitted unit, the owner/operator shall submit a Permit-Exempt Equipment Registration (PEER) application to the District. [District Rules 4307 and 2250]

This PEER remains valid through the expiration date listed above, subject to payment of the annual registration fees and compliance with the PEER conditions and all applicable local, state, and federal regulations. This PEER is valid only within the San Joaquin Valley Air Pollution Control District. Any equipment or operation change may require a PEER application be filed with the District.

Seyed Sadredin

Executive Director / APCO

S-1326-2-0 : 07/13/2016 – VELASCOA : Joint Inspection NOT Required

Arnaud Marjollet

Director of Permit Services

Southern Regional Office • 34946 Flyover Court • Bakersfield, CA 93308 • (661) 392-5500 • Fax (661) 392-5585