



NOV 09 2016

Mr. Bob Bennett
Silgan Containers Manufacturing Corporation
567 South Riverside Drive
Modesto, CA 95354

**Re: Notice of Preliminary Decision – Title V Permit Renewal
District Facility # N-1719
Project # N-1152650**

Dear Mr. Bennett:

Enclosed for your review and comment is the District's analysis of the application to renew the Federally Mandated Operating Permit for Silgan Containers Manufacturing Corporation at 567 South Riverside Drive, Modesto, California.

The notice of preliminary decision for this project will be published approximately three days from the date of this letter. After addressing all comments made during the 30-day public notice and the 45-day EPA comment periods, the District intends to issue the renewed Federally Mandated Operating Permit. Please submit your written comments on this project within the 30-day public comment period, as specified in the enclosed public notice.

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Nick Peirce, Permit Services Manager, at (209) 557-6400.

Sincerely,



Arnaud Marjollet
Director of Permit Services

Enclosures

cc: Tung Le, CARB (w/enclosure) via email
cc: Gerardo C. Rios, EPA (w/enclosure) via email

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

SAN JOAQUIN VALLEY AIR POLLUTION CONTROL DISTRICT

**Proposed Title V Permit Renewal Evaluation
Silgan Containers Manufacturing Corporation
N-1719**

TABLE OF CONTENTS

I.	PROPOSAL	2
II.	FACILITY LOCATION	3
III.	EQUIPMENT LISTING.....	3
IV.	GENERAL PERMIT TEMPLATE USAGE.....	3
V.	SCOPE OF EPA AND PUBLIC REVIEW.....	5
VI.	FEDERALLY ENFORCEABLE REQUIREMENTS.....	5
VII.	REQUIREMENTS NOT FEDERALLY ENFORCEABLE	6
VIII.	PERMIT REQUIREMENTS.....	7
IX.	PERMIT SHIELD	10
X.	PERMIT CONDITIONS	10
XI.	ATTACHMENTS	11
A.	DRAFT RENEWED TITLE V OPERATING PERMIT	
B.	PREVIOUS TITLE V OPERATING PERMIT	
C.	DETAILED FACILITY LIST	

TITLE V PERMIT RENEWAL EVALUATION

Metal Can and Container Manufacturing Facility

Engineer: Kai Chan

Date: November 7, 2016

Facility Number: N-1719

Facility Name: Silgan Containers Mfg. Corp.

Mailing Address: 567 South Riverside Drive
Modesto, CA 95354

Contact Name: Bob Bennett

Phone: (209) 491-7334

Email: bbennett@silgancontainers.com

Responsible Official: Arnold Naimark

Title: Plant Manager

Project # : N-1152650

Deemed Complete: July 22, 2015

I. PROPOSAL

Silgan Containers Mfg. Corp. was issued a Title V permit on November 30, 2011. As required by District Rule 2520, the applicant is requesting a permit renewal. The existing Title V permit shall be reviewed and modified to reflect all applicable District and federal rules updated, removed, or added since the issuance of the initial Title V permit.

Silgan Containers Mfg. Corp. received Authority to Construct (ATC) permits N-1719-1-6, '-2-4, '-3-4, and '-8-0 to modify three existing side seam stripe coating lines to control VOC emissions with a shared regenerative thermal oxidizer (RTO) and install a new side seam stripe coating line, which will also be served by the shared RTO. These ATC permits have not been fully implemented at this time and are being processed separately under project #N-1123615; therefore, these ATC permits will NOT be incorporated into their Title V permit within this Title V renewal project.

The purpose of this evaluation is to provide the legal and factual basis for all updated applicable requirements and to determine if the facility will comply with these updated requirements. It also specifically identifies all additions, deletions, and/or changes made to permit conditions or equipment descriptions.

II. FACILITY LOCATION

Silgan Containers Mfg. Corp. is located at 567 S. Riverside Drive in Modesto, CA.

III. EQUIPMENT LISTING

A detailed facility printout listing all permitted equipment at the facility is included as Attachment C.

IV. GENERAL PERMIT TEMPLATE USAGE

The applicant is requesting to use the following model general permit Template:

Template SJV-UM-0-3 Facility Wide Umbrella

The applicant has requested to utilize template No. SJV-UM-0-3, Facility Wide Umbrella. Based on the information submitted in the Template Qualification Form, the applicant qualifies for the use of this template.

The following applicable requirements have been addressed by the general permit facility wide umbrella Template SJV-UM-03, which have not been updated since the previous Title V renewal, and will not be discussed in this document:

- District Rule 1100, Equipment Breakdown
(amended December 17, 1992)
- District Rule 1160, Emission Statements
(adopted November 18, 1992)
- District Rule 2010, Permits Required
(amended December 17, 1992)
- District Rule 2031, Transfer of Permits
(amended December 17, 1992)
- District Rule 2040, Applications
(amended December 17, 1992)

- District Rule 2070, Standards for Granting Applications
(amended December 17, 1992)
- District Rule 2080, Conditional Approval
(amended December 17, 1992)
- District Rule 2520, Federally Mandated Operating Permits
(amended June 21, 2001)
- District Rule 4101, Visible Emissions
(amended February 17, 2005)
- District Rule 4601, Architectural Coatings
(amended October 31, 2001 ⇒ amended December 17, 2009)
- District Rule 8021, Construction, Demolition, Excavation, Extraction, and Other Earthmoving Activities
(adopted November 15, 2001 ⇒ amended August 19, 2004)
- District Rule 8031, Bulk Materials
(adopted November 15, 2001 ⇒ amended August 19, 2004)
- District Rule 8041, Carryout and Trackout
(adopted November 15, 2001 ⇒ amended August 19, 2004)
- District Rule 8051, Open Areas
(adopted November 15, 2001 ⇒ amended August 19, 2004)
- District Rule 8061, Paved and Unpaved Roads
(adopted November 15, 2001 ⇒ amended August 19, 2004)
- District Rule 8071, Unpaved Vehicle/Equipment Traffic Areas
(adopted November 15, 2001 ⇒ amended September 16, 2004)
- 40 CFR Part 61, Subpart M, National Emission Standard for Asbestos
(amended July 20, 2004)

V. SCOPE OF EPA AND PUBLIC REVIEW

Certain segments of the proposed Renewed Operating Permit are based on model general permit templates that have been previously subject to EPA and public review. The terms and conditions from the model general permit templates are included in the proposed permit and are not subject to further EPA and public review.

For permit applications utilizing model general permit templates, public and agency comments on the District's proposed actions are limited to the applicant's eligibility for model general permit template, applicable requirements not covered by the model general permit template, and the applicable procedural requirements for issuance of Title V Operating Permits.

The following permit conditions, including their underlying applicable requirements, originate from model general permit templates and are not subject to further EPA or public review.

Conditions 1-42 of the facility-wide requirements N-1719-0-1 have been subsumed by conditions 1-42 of the facility-wide requirements N-1719-0-2.

VI. FEDERALLY ENFORCEABLE REQUIREMENTS

A. Rules Updated

- District Rule 2020, Exemptions
(amended December 20, 2007 ⇒ amended December 18, 2014)
- District Rule 2201, New and Modified Stationary Source Review Rule
(amended April 21, 2011 ⇒ amended February 18, 2016)
- 40 CFR Part 82, Subpart B, Servicing of Motor Vehicle Air Conditioners
(amended June 25, 2013)
- 40 CFR Part 82, Subpart F, Recycling and Emissions Reduction
(amended April 10, 2015)

B. Rules Removed

There are no applicable rules that were removed since the previous Title V renewal.

C. Rules Added

- District Rule 2410, Prevention of Significant Deterioration
(adopted June 16, 2011, effective November 26, 2012)

D. Rules Not Updated

- District Rule 2520, Federally Mandated Operating Permits
(amended June 21, 2001)
- District Rule 4201, Particulate Matter Concentration
(amended December 17, 1992)
- District Rule 4202, Particulate Matter - Emission Rate
(amended December 17, 1992)
- District Rule 4604, Can and Coil Coating Operations
(amended January 15, 2004 ⇒ amended September 20, 2007)
- 40 CFR Part 63, Subpart KKKK, National Emission Standards for Hazardous Air Pollutants: Surface Coating of Metal Cans
(amended April 20, 2006)
- 40 CFR Part 64, Compliance Assurance Monitoring (CAM)
(amended October 22, 1997)

VII. REQUIREMENTS NOT FEDERALLY ENFORCEABLE

For each Title V source, the District issues a single permit that contains the Federally Enforceable requirements, as well as the District-only requirements. The District-only requirements are not a part of the Title V Operating Permits. The terms and conditions that are part of the facility's Title V permit are designated as "Federally Enforceable Through Title V Permit".

For this facility, the following are not federally enforceable and will not be discussed in further detail:

A. Rules Updated

There are no applicable rules that have been updated since the previous Title V renewal.

B. Rules Added

There are no applicable rules added since the previous Title V renewal.

C. Rules Not Updated

- District Rule 1070, Inspections
(amended December 17, 1992)
- District Rule 4102, Nuisance
(amended December 17, 1992)

VIII. PERMIT REQUIREMENTS

The purpose of this evaluation is to review changes to federally enforceable requirements; therefore, this compliance section will only address rules that have been amended or added since the previous Title V renewal.

A. District Rule 2020 - Exemptions

District Rule 2020 lists source categories that may be exempt from obtaining permits, and specifies recordkeeping requirements to verify such exemptions. The amendments to this rule do not have any effect on current permit requirements and will therefore not be addressed in this evaluation.

B. District Rule 2201 - New and Modified Stationary Source Review Rule

This rule applies to all new stationary sources and all modifications to existing stationary sources which are subject to the District permit requirements and after construction emit or may emit one or more affected pollutant. The requirements of this rule in effect on the date the application is determined to be complete by the Air Pollution Control Officer (APCO) shall apply to such application.

District Rule 2201 has been amended since this facility's previous Title V permit was issued. However, the requirements of this rule are only triggered at the time the source undergoes a modification. All applicable requirements from any NSR permit actions have already been incorporated into the current Title V permit. Therefore, the requirements for new and modified units to which this version of the rule applies are up-to-date, and no additional conditions are required.

C. District Rule 2410 – Prevention of Significant Deterioration

The provisions of this rule shall apply to any source and the owner or operator of any source subject to any requirement under Title 40 Code of Federal Regulations (40 CFR) Part 52.21 as incorporated into this rule.

Section 4.1 of the rule states that an owner or operator must obtain a PSD permit pursuant to this Rule before beginning actual construction of a new major stationary source, a major modification, or a plant wide applicability limitation (PAL) major modification, as defined in 40 CFR 52.21(b).

District Rule 2410 has been newly adopted since this Title V permit was last renewed. However the requirements of this rule are only triggered at the time the source undergoes a modification. All applicable requirements from any PSD permit actions have already been incorporated into the current Title V permit. Therefore, the current permits are up-to-date, and no additional permit conditions are required.

D. 40 CFR Part 82, Subpart B (Servicing of Motor Vehicle Air Conditioners) and Subpart F (Recycling and Emissions Reduction)

There are applicable requirements from Title VI of the CAA (Stratospheric Ozone) that apply to all sources. These requirements pertain to air conditioners, chillers and refrigerators located at a Title V source and to disposal of air conditioners or maintenance/recharging/disposal of motor vehicle air conditioners (MVAC). These requirements are addressed in conditions 27. and 28. of the draft Title V permit N-1719-0-2.

E. 40 CFR Part 63, Subpart KKKK, National Emission Standards for Hazardous Air Pollutants: Surface Coating of Metal Cans

Per §63.3481(b) of 40 CFR Part 60 Subpart KKKK, this subpart applies to facilities that use 1,500 gallons per year, or more, of coatings in the source category defined in §63.3481(a) of this regulation and that is a Major HAP source (as defined in 40 CFR 63.2 – Definitions).

Pursuant to the HAP emission calculations under project #N-1122502, this facility's total HAP emissions is 2.384 tons/year, which is below the Major HAP source thresholds of 10 tons/year for a single-HAP and 25 tons/year for combined-HAPs. Therefore, the requirements of this subpart continue to not apply and no further discussion is required.

F. 40 CFR Part 64, Compliance Assurance Monitoring (CAM)

40 CFR Part 64 requires Compliance Assurance Monitoring (CAM) for units that meet the following three criteria:

1. The unit must have an emission limit for the pollutant;
2. The unit must have add-on controls for the pollutant (these are devices such as flue gas recirculation (FGR), baghouses, and catalytic oxidizers); and
3. The unit must have a pre-control potential to emit of greater than the major source thresholds.

Major Source Thresholds		
Pollutant	lb/year	ton/year
NOx	20,000	10
SOx	140,000	70
PM ₁₀	140,000	70
CO	200,000	100
VOC	20,000	10

Permit Number N-1719-1-8 (One Soudronic Resistance Welding Bodymaker Served by One 0.4 MMBtu/hr Natural Gas Fired Sardee Model SU-SL-130 Straight Line Curing Tunnel (Line #2)):

This permit unit contains VOC emission limits for the coating operation along with NOx, SOx, PM₁₀, CO, and VOC from the combustion of natural gas for the associated curing tunnel. However, this unit does not utilize an add-on control device for these pollutants. Therefore, this permit unit is not subject to CAM requirements for any pollutant.

Permit Number N-1719-2-6 (One 787-BW-5 Can Bodywelder (FAEL S.A.) and 4+2 Side-Stripe Curing System (Line #1)):

Permit Number N-1719-3-6 (One Soudronic Resistance Welding Bodymaker Sardee/Carnoud Curing Tunnel (Line #3)):

These permit units only contain VOC emission limits for the coating operation. However, these units do not utilize an add-on control device for VOC emissions. Therefore, these permit units are not subject to CAM requirements for VOC emissions.

Permit Number N-1719-7-2 (Alfons Haar-Manster P2H Can End Manufacturing Line with a 650 Gallons Compound Liner Tank and Two Permit Exempt Electric Induction Ovens):

This permit unit does not contain emission limitations for any pollutant. Therefore, this permit unit is not subject to CAM requirements for any pollutant.

IX. PERMIT SHIELD

A permit shield legally protects a facility from enforcement of the shielded regulations when a source is in compliance with the terms and conditions of the Title V permit. Compliance with the terms and conditions of the Operating Permit is considered compliance with all applicable requirements upon which those conditions are based, including those that have been subsumed.

A. Requirements Addressed by Model General Permit Templates

Model General Permit Template SJV-UM-0-3

By submitting Model General Permit Template SJV-UM-0-3 qualification form, the applicant has requested that a permit shield be granted for all the applicable requirements identified by the template. Therefore, the permit shields as granted in Model General Permit Template are included as conditions 39. and 40. of the facility-wide requirements (N-1719-0-2).

B. Requirements not Addressed by Model General Permit Templates

The applicant is not requesting any new permit shields under this Title V renewal application.

X. PERMIT CONDITIONS

See Attachment A - Draft Renewed Title V Operating Permit

XI. ATTACHMENTS

- A. Draft Renewed Title V Operating Permit
- B. Previous Title V Operating Permit
- C. Detailed Facility List

Draft Renewed Title V Operating Permit

ATTACHMENT A

San Joaquin Valley Air Pollution Control District

FACILITY: N-1719-0-2

EXPIRATION DATE: 10/31/2016

FACILITY-WIDE REQUIREMENTS

1. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rule 110 (Stanislaus)] Federally Enforceable Through Title V Permit
2. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rule 110 (Stanislaus)] Federally Enforceable Through Title V Permit
3. {4364} The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. {4365} Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. {4366} The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.9.1 and 9.13.1] Federally Enforceable Through Title V Permit
6. {4367} A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. {4368} Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. {4369} The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. {4370} The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: SILGAN CONTAINERS MFR. CORP.
Location: 567 S RIVERSIDE DR, MODESTO, CA 95354
N-1719-0-2 Nov 7 2015 2:08PM - CHANK

10. {4371} The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit
11. {4372} Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
12. {4373} If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
13. {4374} It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
14. {4375} The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
15. {4376} The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
16. {4377} The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
17. {4378} The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
18. {4379} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
19. {4380} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
20. {4381} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
21. {4382} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

22. {4383} No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit
23. {4384} No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in Table of Standards 1 effective until 12/30/10 or Table of Standards 2 effective on and after 1/1/11 of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
24. {4385} All VOC-containing materials subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
25. {4386} The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
26. {4387} With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
27. {4388} If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
28. {4389} If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit
29. {4390} Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8021 and 8011] Federally Enforceable Through Title V Permit
30. {4391} Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8031 and 8011] Federally Enforceable Through Title V Permit
31. {4392} An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8041 and 8011] Federally Enforceable Through Title V Permit
32. {4393} Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8051 and 8011] Federally Enforceable Through Title V Permit
33. {4394} Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8061 and 8011] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

34. {4395} Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rules 8071 and 8011] Federally Enforceable Through Title V Permit
35. {4396} Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit
36. {4397} The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
37. {4398} The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
38. {4399} When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
39. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Stanislaus), Rule 110 (Stanislaus), and Rule 202 (Stanislaus). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. {4401} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601 (12/17/09); 8021 (8/19/2004); 8031 (8/19/2004); 8041 (8/19/2004); 8051 (8/19/2004); 8061 (8/19/2004); and 8071 (9/16/2004). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
42. On November 30, 2011, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1719-1-8

EXPIRATION DATE: 10/31/2016

EQUIPMENT DESCRIPTION:

ONE (1) SOUDRONIC RESISTANCE WELDING BODYMAKER SERVED BY ONE (1) 0.4 MMBTU/HR NATURAL GAS FIRED SARDEE MODEL SU-SL-130 STRAIGHT LINE CURING TUNNEL (LINE #2)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Both powder coatings and liquid coatings may be used for the side seam coating operation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The VOC emissions from the coating operation shall not exceed 89.3 pounds in any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The NOx emissions from natural gas combustion shall not exceed 0.1 pounds per MMBtu of heat input. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The VOC emissions from natural gas combustion shall not exceed 0.0053 pounds per MMBtu of heat input. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The SOx emissions from natural gas combustion shall not exceed 0.0006 pounds per MMBtu of heat input. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The CO emissions from natural gas combustion shall not exceed 0.021 pounds per MMBtu of heat input. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The PM10 emissions from natural gas combustion shall not exceed 0.012 pounds per MMBtu of heat input. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Records of the cumulative facility-wide VOC emissions shall be kept to demonstrate compliance with the 12 month period. [District Rule 2201] Federally Enforceable Through Title V Permit
10. VOC content of any coatings as applied, excluding water and exempt compounds, used for two-piece can coating operations shall not exceed any of the following limits: interior sheet basecoat and interior overvarnish: 225 g/l; exterior sheet basecoat and exterior overvarnish: 250 g/l; body spray and end coating (interior or exterior): 420 g/l; repair coating: 750 g/l; and end sealing compound: 20 g/l. [District Rule 4604, 5.1] Federally Enforceable Through Title V Permit
11. VOC content of any coatings as applied, excluding water and exempt compounds, used for three-piece can coating operations shall not exceed any of the following limits: sheet basecoat, overvarnish and end coating (interior or exterior) : 225 g/l; interior body spray: 360 g/l; exterior body spray: 420 g/l, side seam coating: 660 g/l; repair coating: 750 g/l; and end sealing compound: 20 g/l. [District Rule 4604, 5.1] Federally Enforceable Through Title V Permit
12. Solvents used for product cleaning, surface preparation or repair and maintenance cleaning shall have a VOC content not exceeding 25 g/l. [District Rule 4604, 5.4.1] Federally Enforceable Through Title V Permit
13. Solvents used for cleaning of any coating application equipment not used for sheet coating of three-piece cans shall have a VOC content not exceeding 25 g/l. [District Rule 4604, 5.4.2.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

14. Solvents used for cleaning coating application equipment used for sheet coating of three-piece cans shall not exceed 250 g/l. [District Rule 4604, 5.4.1] Federally Enforceable Through Title V Permit
15. Cleaning of coating application equipment used for sheet coating of three-piece cans using solvents with a VOC content greater than 25 g/l shall be performed by one or more of the following methods: wipe cleaning; application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rule 4604, 5.4.3.2] Federally Enforceable Through Title V Permit
16. All fresh or spent coatings, adhesives, catalysts, thinners and solvents shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rule 4604, 5.5] Federally Enforceable Through Title V Permit
17. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios (by volume) of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent. [District Rule 4604, 6.0] Federally Enforceable Through Title V Permit
18. A list of the specific coatings, catalysts, and reducers used; the VOC content of each coating, as applied; the mix ratio of components used; and the VOC content of all cleanup and surface preparation solvents shall be maintained on the premises at all times. [District Rule 4604, 6.0] Federally Enforceable Through Title V Permit
19. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rule 4604, 6.0] Federally Enforceable Through Title V Permit
20. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rule 4604, 6.0] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1719-2-6

EXPIRATION DATE: 10/31/2016

EQUIPMENT DESCRIPTION:

ONE (1) 787-BW-5 CAN BODYWELDER (FAEL S.A.) AND 4+2 SIDE-STRIPE CURING SYSTEM (LINE #1)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The facility-wide VOC emissions shall not exceed 49,999 pounds per year. A year, for this condition, is any 12 month period based on a monthly rolling average. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Both powder coatings and liquid coatings may be used for the side seam coating operation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The VOC emissions from the coating operation shall not exceed 89.3 pounds in any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Records of the cumulative facility-wide VOC emissions shall be kept to demonstrate compliance with the 12 month period. [District Rule 2201] Federally Enforceable Through Title V Permit
6. VOC content of any coatings as applied, excluding water and exempt compounds, used for two-piece can coating operations shall not exceed any of the following limits: interior sheet basecoat and interior overvarnish: 225 g/l; exterior sheet basecoat and exterior overvarnish: 250 g/l; body spray and end coating (interior or exterior): 420 g/l; repair coating: 750 g/l; and end sealing compound: 20 g/l. [District Rule 4604, 5.1] Federally Enforceable Through Title V Permit
7. VOC content of any coatings as applied, excluding water and exempt compounds, used for three-piece can coating operations shall not exceed any of the following limits: sheet basecoat, overvarnish and end coating (interior or exterior) : 225 g/l; interior body spray: 360 g/l; exterior body spray: 420 g/l; side seam coating: 660 g/l; repair coating: 750 g/l; and end sealing compound: 20 g/l. [District Rule 4604, 5.1] Federally Enforceable Through Title V Permit
8. Solvents used for product cleaning, surface preparation or repair and maintenance cleaning shall have a VOC content not exceeding 25 g/l. [District Rule 4604, 5.4.1] Federally Enforceable Through Title V Permit
9. Solvents used for cleaning of any coating application equipment not used for sheet coating of three-piece cans shall have a VOC content not exceeding 25 g/l. [District Rule 4604, 5.4.2.2] Federally Enforceable Through Title V Permit
10. Solvents used for cleaning coating application equipment used for sheet coating of three-piece cans shall not exceed 250 g/l. [District Rule 4604, 5.4.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Cleaning of coating application equipment used for sheet coating of three-piece cans using solvents with a VOC content greater than 25 g/l shall be performed by one or more of the following methods: wipe cleaning; application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rule 4604, 5.4.3.2] Federally Enforceable Through Title V Permit
12. All fresh or spent coatings, adhesives, catalysts, thinners and solvents shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rule 4604, 5.5] Federally Enforceable Through Title V Permit
13. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios (by volume) of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent. [District Rule 4604, 6.0] Federally Enforceable Through Title V Permit
14. A list of the specific coatings, catalysts, and reducers used; the VOC content of each coating, as applied; the mix ratio of components used; and the VOC content of all cleanup and surface preparation solvents shall be maintained on the premises at all times. [District Rule 4604, 6.0] Federally Enforceable Through Title V Permit
15. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rule 4604, 6.0] Federally Enforceable Through Title V Permit
16. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rule 4604, 6.0] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1719-3-6

EXPIRATION DATE: 10/31/2016

EQUIPMENT DESCRIPTION:

ONE (1) SOUDRONIC RESISTANCE WELDING BODYMAKER SARDEE/CARNOUD CURING TUNNEL (LINE #3)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The VOC emissions from the coating operation shall not exceed 89.3 pounds in any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Both powder coatings and liquid coatings may be used for the side seam coating operation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The facility-wide VOC emissions shall not exceed 49,999 pounds per year. A year, for this condition, is any 12 month period based on a monthly rolling average. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Records of the cumulative facility-wide VOC emissions shall be kept to demonstrate compliance with the 12 month period. [District Rule 2201] Federally Enforceable Through Title V Permit
6. VOC content of any coatings as applied, excluding water and exempt compounds, used for two-piece can coating operations shall not exceed any of the following limits: interior sheet basecoat and interior overvarnish: 225 g/l; exterior sheet basecoat and exterior overvarnish: 250 g/l; body spray and end coating (interior or exterior): 420 g/l; repair coating: 750 g/l; and end sealing compound: 20 g/l. [District Rule 4604, 5.1] Federally Enforceable Through Title V Permit
7. VOC content of any coatings as applied, excluding water and exempt compounds, used for three-piece can coating operations shall not exceed any of the following limits: sheet basecoat, overvarnish and end coating (interior or exterior) : 225 g/l; interior body spray: 360 g/l; exterior body spray: 420 g/l; side seam coating: 660 g/l; repair coating: 750 g/l; and end sealing compound: 20 g/l. [District Rule 4604, 5.1] Federally Enforceable Through Title V Permit
8. Solvents used for product cleaning, surface preparation or repair and maintenance cleaning shall have a VOC content not exceeding 25 g/l. [District Rule 4604, 5.4.1] Federally Enforceable Through Title V Permit
9. Solvents used for cleaning of any coating application equipment not used for sheet coating of three-piece cans shall have a VOC content not exceeding 25 g/l. [District Rule 4604, 5.4.2.2] Federally Enforceable Through Title V Permit
10. Solvents used for cleaning coating application equipment used for sheet coating of three-piece cans shall not exceed 250 g/l. [District Rule 4604, 5.4.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Cleaning of coating application equipment used for sheet coating of three-piece cans using solvents with a VOC content greater than 25 g/l shall be performed by one or more of the following methods: wipe cleaning; application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rule 4604, 5.4.3.2] Federally Enforceable Through Title V Permit
12. All fresh or spent coatings, adhesives, catalysts, thinners and solvents shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rule 4604, 5.5] Federally Enforceable Through Title V Permit
13. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios (by volume) of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent. [District Rule 4604, 6.0] Federally Enforceable Through Title V Permit
14. A list of the specific coatings, catalysts, and reducers used; the VOC content of each coating, as applied; the mix ratio of components used; and the VOC content of all cleanup and surface preparation solvents shall be maintained on the premises at all times. [District Rule 4604, 6.0] Federally Enforceable Through Title V Permit
15. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rule 4604, 6.0] Federally Enforceable Through Title V Permit
16. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rule 4604, 6.0] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1719-7-2

EXPIRATION DATE: 10/31/2016

EQUIPMENT DESCRIPTION:

ALFONS HAAR-MANSTER P2H CAN END MANUFACTURING LINE WITH A 650 GALLONS COMPOUND LINER TANK AND TWO PERMIT EXEMPT ELECTRIC INDUCTION OVENS

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The end seal compound applied shall contain zero VOC's. [District Rule 2201 and 4604] Federally Enforceable Through Title V Permit
3. The end seal compound throughput shall not exceed 819.6 pounds in any one day. [District Rules 2201] Federally Enforceable Through Title V Permit
4. Ammonia emissions shall not exceed 0.5% by weight of end seal compound use. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Daily records of the amount of end seal compound used, shall be kept and maintained on the premises at all times. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Solvents used for product cleaning, surface preparation or repair and maintenance cleaning shall have a VOC content not exceeding 25 g/l. [District Rule 4604, 5.4.1] Federally Enforceable Through Title V Permit
7. Solvents used for cleaning of any coating application equipment not used for sheet coating of three-piece cans shall have a VOC content not exceeding 25 g/l. [District Rule 4604, 5.4.2.2] Federally Enforceable Through Title V Permit
8. Solvents used for cleaning coating application equipment used for sheet coating of three-piece cans shall not exceed 250 g/l. [District Rule 4604, 5.4.1] Federally Enforceable Through Title V Permit
9. Cleaning of coating application equipment used for sheet coating of three-piece cans using solvents with a VOC content greater than 25 g/l shall be performed by one or more of the following methods: wipe cleaning; application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rule 4604, 5.4.3.2] Federally Enforceable Through Title V Permit
10. All fresh or spent coatings, adhesives, catalysts, thinners and solvents shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rule 4604, 5.5] Federally Enforceable Through Title V Permit
11. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios (by volume) of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent. [District Rule 4604, 6.0] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rule 4604, 6.0] Federally Enforceable Through Title V Permit
13. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rule 4604, 6.0] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

Previous Title V Operating Permit

ATTACHMENT B



San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT



HEALTHY AIR LIVING™

Permit to Operate

FACILITY: N-1719

EXPIRATION DATE: 10/31/2016

LEGAL OWNER OR OPERATOR:
MAILING ADDRESS:

SILGAN CONTAINERS MFR. CORP.
430 DOHERTY AVE
MODESTO, CA 95354

FACILITY LOCATION:

567 RIVERSIDE DR
MODESTO, CA 95354

FACILITY DESCRIPTION:

METAL CANS

The Facility's Permit to Operate may include Facility-wide Requirements as well as requirements that apply to specific permit units.

This Permit to Operate remains valid through the permit expiration date listed above, subject to payment of annual permit fees and compliance with permit conditions and all applicable local, state, and federal regulations. This permit is valid only at the location specified above, and becomes void upon any transfer of ownership or location. Any modification of the equipment or operation, as defined in District Rule 2201, will require prior District approval. This permit shall be posted as prescribed in District Rule 2010.

Seyed Sadredin
Executive Director / APCO

David Warner
Director of Permit Services

San Joaquin Valley Air Pollution Control District

FACILITY: N-1719-0-1

EXPIRATION DATE: 10/31/2016

FACILITY-WIDE REQUIREMENTS

1. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
2. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
3. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.9.1 and 9.13.1] Federally Enforceable Through Title V Permit
6. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: SILGAN CONTAINERS MFR. CORP.
Location: 567 RIVERSIDE DR. MODESTO, CA 95354
N-1719-0-1: Nov 3 2011 4:22PM - ROBERTSD

10. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit
11. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
12. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
13. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
14. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
15. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
16. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
17. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
18. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
19. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
20. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
21. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit
22. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

23. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in Table of Standards 1 effective until 12/30/10 or Table of Standards 2 effective on and after 1/1/11 of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
24. All VOC-containing materials subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
25. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
26. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
27. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
28. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit
29. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8021 and 8011] Federally Enforceable Through Title V Permit
30. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8031 and 8011] Federally Enforceable Through Title V Permit
31. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8041 and 8011] Federally Enforceable Through Title V Permit
32. Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8051 and 8011] Federally Enforceable Through Title V Permit
33. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rule 8061 and Rule 8011] Federally Enforceable Through Title V Permit
34. Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rule 8071 and Rule 8011] Federally Enforceable Through Title V Permit
35. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

36. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
37. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
38. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
39. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), Rule 111 (Kern, Tulare, Kings), and Rule 202 (Fresno, Kern, Tulare, Kings, Madera, Stanislaus, Merced, San Joaquin). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601 (12/17/09); 8021 (8/19/2004); 8031 (8/19/2004); 8041 (8/19/2004); 8051 (8/19/2004); 8061 (8/19/2004); and 8071 (9/16/2004). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
42. On November 30, 2011, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1719-1-5

EXPIRATION DATE: 10/31/2016

EQUIPMENT DESCRIPTION:

ONE (1) SOUDRONIC RESISTANCE WELDING BODYMAKER SERVED BY ONE (1) 0.4 MMBTU/HR NATURAL GAS FIRED SARDEE MODEL SU-SL-130 STRAIGHT LINE CURING TUNNEL (LINE #2)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Both powder coatings and liquid coatings may be used for the side seam coating operation. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The VOC emissions from the coating operation shall not exceed 89.3 pounds in any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The NOx emissions from natural gas combustion shall not exceed 0.1 pounds per MMBtu of heat input. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The VOC emissions from natural gas combustion shall not exceed 0.0053 pounds per MMBtu of heat input. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The SOx emissions from natural gas combustion shall not exceed 0.0006 pounds per MMBtu of heat input. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The CO emissions from natural gas combustion shall not exceed 0.021 pounds per MMBtu of heat input. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The PM10 emissions from natural gas combustion shall not exceed 0.012 pounds per MMBtu of heat input. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Records of the cumulative facility-wide VOC emissions shall be kept to demonstrate compliance with the 12 month period. [District Rule 2201] Federally Enforceable Through Title V Permit
10. VOC content of any coatings as applied, excluding water and exempt compounds, used for two-piece can coating operations shall not exceed any of the following limits: interior sheet basecoat and interior overvarnish: 225 g/l; exterior sheet basecoat and exterior overvarnish: 250 g/l; body spray and end coating (interior or exterior): 420 g/l; repair coating: 750 g/l; and end sealing compound: 20 g/l. [District Rule 4604, 5.1] Federally Enforceable Through Title V Permit
11. VOC content of any coatings as applied, excluding water and exempt compounds, used for three-piece can coating operations shall not exceed any of the following limits: sheet basecoat, overvarnish and end coating (interior or exterior): 225 g/l; interior body spray: 360 g/l; exterior body spray: 420 g/l; side seam coating: 660 g/l; repair coating: 750 g/l; and end sealing compound: 20 g/l. [District Rule 4604, 5.1] Federally Enforceable Through Title V Permit
12. Solvents used for product cleaning, surface preparation or repair and maintenance cleaning shall have a VOC content not exceeding 25 g/l. [District Rule 4604, 5.4.1] Federally Enforceable Through Title V Permit
13. Solvents used for cleaning of any coating application equipment not used for sheet coating of three-piece cans shall have a VOC content not exceeding 25 g/l. [District Rule 4604, 5.4.2.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: SILGAN CONTAINERS MFR. CORP.
Location: 567 RIVERSIDE DR, MODESTO, CA 95354
N-1719-1-5 - Nov 2 2011 4:22PM - ROBERTSD

14. Until September 30, 2011, solvents used for cleaning coating application equipment used for sheet coating of three-piece cans shall not exceed 550 g/l. Effective on and after October 1, 2011, solvents used for cleaning coating application equipment used for sheet coating of three-piece cans shall not exceed 250 g/l. [District Rule 4604, 5.4.1] Federally Enforceable Through Title V Permit
15. Cleaning of coating application equipment used for sheet coating of three-piece cans using solvents with a VOC content greater than 25 g/l shall be performed by one or more of the following methods: wipe cleaning; application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rule 4604, 5.4.3.2] Federally Enforceable Through Title V Permit
16. All fresh or spent coatings, adhesives, catalysts, thinners and solvents shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rule 4604, 5.5] Federally Enforceable Through Title V Permit
17. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios (by volume) of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent. [District Rule 4604, 6.0] Federally Enforceable Through Title V Permit
18. A list of the specific coatings, catalysts, and reducers used; the VOC content of each coating, as applied; the mix ratio of components used; and the VOC content of all cleanup and surface preparation solvents shall be maintained on the premises at all times. [District Rule 4604, 6.0] Federally Enforceable Through Title V Permit
19. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rule 4604, 6.0] Federally Enforceable Through Title V Permit
20. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rule 4604, 6.0] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1719-2-3

EXPIRATION DATE: 10/31/2016

EQUIPMENT DESCRIPTION:

ONE (1) 787-BW-5 CAN BODYWELDER (FAEL S.A.) AND 4+2 SIDE-STRIPE CURING SYSTEM (LINE #1)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The facility-wide VOC emissions shall not exceed 49,999 pounds per year. A year, for this condition, is any 12 month period based on a monthly rolling average. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Both powder coatings and liquid coatings may be used for the side seam coating operation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The VOC emissions from the coating operation shall not exceed 89.3 pounds in any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Records of the cumulative facility-wide VOC emissions shall be kept to demonstrate compliance with the 12 month period. [District Rule 2201] Federally Enforceable Through Title V Permit
6. VOC content of any coatings as applied, excluding water and exempt compounds, used for two-piece can coating operations shall not exceed any of the following limits: interior sheet basecoat and interior overvarnish: 225 g/l; exterior sheet basecoat and exterior overvarnish: 250 g/l; body spray and end coating (interior or exterior): 420 g/l; repair coating: 750 g/l; and end sealing compound: 20 g/l. [District Rule 4604, 5.1] Federally Enforceable Through Title V Permit
7. VOC content of any coatings as applied, excluding water and exempt compounds, used for three-piece can coating operations shall not exceed any of the following limits: sheet basecoat, overvarnish and end coating (interior or exterior): 225 g/l; interior body spray: 360 g/l; exterior body spray: 420 g/l; side seam coating: 660 g/l; repair coating: 750 g/l; and end sealing compound: 20 g/l. [District Rule 4604, 5.1] Federally Enforceable Through Title V Permit
8. Solvents used for product cleaning, surface preparation or repair and maintenance cleaning shall have a VOC content not exceeding 25 g/l. [District Rule 4604, 5.4.1] Federally Enforceable Through Title V Permit
9. Solvents used for cleaning of any coating application equipment not used for sheet coating of three-piece cans shall have a VOC content not exceeding 25 g/l. [District Rule 4604, 5.4.2.2] Federally Enforceable Through Title V Permit
10. Until September 30, 2011, solvents used for cleaning coating application equipment used for sheet coating of three-piece cans shall not exceed 550 g/l. Effective on and after October 1, 2011, solvents used for cleaning coating application equipment used for sheet coating of three-piece cans shall not exceed 250 g/l. [District Rule 4604, 5.4.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Cleaning of coating application equipment used for sheet coating of three-piece cans using solvents with a VOC content greater than 25 g/l shall be performed by one or more of the following methods: wipe cleaning; application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rule 4604, 5.4.3.2] Federally Enforceable Through Title V Permit
12. All fresh or spent coatings, adhesives, catalysts, thinners and solvents shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rule 4604, 5.5] Federally Enforceable Through Title V Permit
13. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios (by volume) of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent. [District Rule 4604, 6.0] Federally Enforceable Through Title V Permit
14. A list of the specific coatings, catalysts, and reducers used; the VOC content of each coating, as applied; the mix ratio of components used; and the VOC content of all cleanup and surface preparation solvents shall be maintained on the premises at all times. [District Rule 4604, 6.0] Federally Enforceable Through Title V Permit
15. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rule 4604, 6.0] Federally Enforceable Through Title V Permit
16. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rule 4604, 6.0] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1719-3-3

EXPIRATION DATE: 10/31/2016

EQUIPMENT DESCRIPTION:

ONE (1) SOUDRONIC RESISTANCE WELDING BODYMAKER SARDEE/CARNOUD CURING TUNNEL (LINE #3)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The VOC emissions from the coating operation shall not exceed 89.3 pounds in any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Both powder coatings and liquid coatings may be used for the side seam coating operation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The facility-wide VOC emissions shall not exceed 49,999 pounds per year. A year, for this condition, is any 12 month period based on a monthly rolling average. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Records of the cumulative facility-wide VOC emissions shall be kept to demonstrate compliance with the 12 month period. [District Rule 2201] Federally Enforceable Through Title V Permit
6. VOC content of any coatings as applied, excluding water and exempt compounds, used for two-piece can coating operations shall not exceed any of the following limits: interior sheet basecoat and interior overvarnish: 225 g/l; exterior sheet basecoat and exterior overvarnish: 250 g/l; body spray and end coating (interior or exterior): 420 g/l; repair coating: 750 g/l; and end sealing compound: 20 g/l. [District Rule 4604, 5.1] Federally Enforceable Through Title V Permit
7. VOC content of any coatings as applied, excluding water and exempt compounds, used for three-piece can coating operations shall not exceed any of the following limits: sheet basecoat, overvarnish and end coating (interior or exterior): 225 g/l; interior body spray: 360 g/l; exterior body spray: 420 g/l; side seam coating: 660 g/l; repair coating: 750 g/l; and end sealing compound: 20 g/l. [District Rule 4604, 5.1] Federally Enforceable Through Title V Permit
8. Solvents used for product cleaning, surface preparation or repair and maintenance cleaning shall have a VOC content not exceeding 25 g/l. [District Rule 4604, 5.4.1] Federally Enforceable Through Title V Permit
9. Solvents used for cleaning of any coating application equipment not used for sheet coating of three-piece cans shall have a VOC content not exceeding 25 g/l. [District Rule 4604, 5.4.2.2] Federally Enforceable Through Title V Permit
10. Until September 30, 2011, solvents used for cleaning coating application equipment used for sheet coating of three-piece cans shall not exceed 550 g/l. Effective on and after October 1, 2011, solvents used for cleaning coating application equipment used for sheet coating of three-piece cans shall not exceed 250 g/l. [District Rule 4604, 5.4.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Cleaning of coating application equipment used for sheet coating of three-piece cans using solvents with a VOC content greater than 25 g/l shall be performed by one or more of the following methods: wipe cleaning; application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rule 4604, 5.4.3.2] Federally Enforceable Through Title V Permit
12. All fresh or spent coatings, adhesives, catalysts, thinners and solvents shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rule 4604, 5.5] Federally Enforceable Through Title V Permit
13. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios (by volume) of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent. [District Rule 4604, 6.0] Federally Enforceable Through Title V Permit
14. A list of the specific coatings, catalysts, and reducers used; the VOC content of each coating, as applied; the mix ratio of components used; and the VOC content of all cleanup and surface preparation solvents shall be maintained on the premises at all times. [District Rule 4604, 6.0] Federally Enforceable Through Title V Permit
15. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rule 4604, 6.0] Federally Enforceable Through Title V Permit
16. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rule 4604, 6.0] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: N-1719-7-1

EXPIRATION DATE: 10/31/2016

EQUIPMENT DESCRIPTION:

ALFONS HAAR-MANSTER P2H CAN END MANUFACTURING LINE WITH A 650 GALLONS COMPOUND LINER TANK AND TWO PERMIT EXEMPT ELECTRIC INDUCTION OVENS

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The end seal compound applied shall contain zero VOC's. [District Rule 2201 and 4604] Federally Enforceable Through Title V Permit
3. The end seal compound throughput shall not exceed 819.6 pounds in any one day. [District Rules 2201] Federally Enforceable Through Title V Permit
4. Ammonia emissions shall not exceed 0.5% by weight of end seal compound use. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Daily records of the amount of end seal compound used, shall be kept and maintained on the premises at all times. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Solvents used for product cleaning, surface preparation or repair and maintenance cleaning shall have a VOC content not exceeding 25 g/l. [District Rule 4604, 5.4.1] Federally Enforceable Through Title V Permit
7. Solvents used for cleaning of any coating application equipment not used for sheet coating of three-piece cans shall have a VOC content not exceeding 25 g/l. [District Rule 4604, 5.4.2.2] Federally Enforceable Through Title V Permit
8. Until September 30, 2011, solvents used for cleaning coating application equipment used for sheet coating of three-piece cans shall not exceed 550 g/l. Effective on and after October 1, 2011, solvents used for cleaning coating application equipment used for sheet coating of three-piece cans shall not exceed 250 g/l. [District Rule 4604, 5.4.1] Federally Enforceable Through Title V Permit
9. Cleaning of coating application equipment used for sheet coating of three-piece cans using solvents with a VOC content greater than 25 g/l shall be performed by one or more of the following methods: wipe cleaning; application of solvent from hand-held spray bottles from which solvents are dispensed without a propellant-induced force; non-atomized solvent flow method in which the cleaning solvent is collected in a container or a collection system which is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container; or solvent flushing method in which the cleaning solvent is discharged into a container that is closed except for solvent collection openings and, if necessary, openings to avoid excessive pressure build-up inside the container. The discharged solvent from the equipment must be collected into containers without atomizing into the open air. The solvent may be flushed through the system by air or hydraulic pressure, or by pumping. [District Rule 4604, 5.4.3.2] Federally Enforceable Through Title V Permit
10. All fresh or spent coatings, adhesives, catalysts, thinners and solvents shall be stored in closed containers. Solvent laden cloth or paper shall be stored and disposed in closed non-absorbent containers. [District Rule 4604, 5.5] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: SILGAN CONTAINERS MFR. CORP.
Location: 667 RIVERSIDE DR, MODESTO, CA 95354
N-1719-7-1: Nov 3 2011 4:22PM - ROBERTSD

11. Permittee shall maintain daily records of the following: quantity and type of coatings and solvents used, mix ratios (by volume) of components added to each coating, volume of coatings applied, VOC content of each coating as applied, and VOC content of each solvent. [District Rule 4604, 6.0] Federally Enforceable Through Title V Permit
12. Permittee shall keep the following records for solvent cleaning activities: manufacturers product data sheet or MSDS of solvents used, VOC content of solvents in g/l or lb/gal, and the type of cleaning activity for which each solvent is used. [District Rule 4604, 6.0] Federally Enforceable Through Title V Permit
13. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rule 4604, 6.0] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

ATTACHMENT C

Detailed Facility List

SJVUAPCD
NORTHERN

Detailed Facility Report
For Facility=1719 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

11/7/16
2:13 pm

SILGAN CONTAINERS MFR. CORP. 567 S RIVERSIDE DR MODESTO, CA 95354	FAC # STATUS: TELEPHONE:	N 1719 A 2095237761	TYPE: TOXIC ID:	TitleV 70159	EXPIRE ON: AREA: INSP. DATE:	10/31/2016 10 / 03/17
---	--------------------------------	---------------------------	--------------------	-----------------	------------------------------------	-----------------------------

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
N-1719-1-5	400 KBTU/HR	3020-02 C	1	217.00	217.00	A	ONE (1) SOUDRONIC RESISTANCE WELDING BODYMAKER SERVED BY ONE (1) 0.4 MMBTU/HR NATURAL GAS FIRED SARDEE MODEL SU-SL-130 STRAIGHT LINE CURING TUNNEL (LINE #2)
N-1719-2-3	400 KBTU/HR	3020-02 C	1	217.00	217.00	A	ONE (1) 787-BW-5 CAN BODYWELDER (FAEL S.A.) AND 4+2 SIDE-STRIPE CURING SYSTEM (LINE #1)
N-1719-3-3	400 KBTU/HR	3020-02 C	1	217.00	217.00	A	ONE (1) SOUDRONIC RESISTANCE WELDING BODYMAKER SARDEE/CARNOUD CURING TUNNEL (LINE #3)
N-1719-7-1	100 hp can mfg line	3020-01 D	1	345.00	345.00	A	ALFONS HAAR-MANSTER P2H CAN END MANUFACTURING LINE WITH A 650 GALLONS COMPOUND LINER TANK AND TWO PERMIT EXEMPT ELECTRIC INDUCTION OVENS

Number of Facilities Reported: 1