San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

DEC 16 2016

Christine Campbell
Delicato Vineyards
12001 S Highway 99
Manteca, CA 95336

RE: Notice of Final Action - Authority to Construct
Facility Number: N-266
Project Number: N-1152244

Dear Ms. Campbell:

The Air Pollution Control Officer has issued the Authority to Construct permits to Delicato Vineyards for the installation of 128 new wine fermentation and storage tanks, at 12001 S Highway 99, Manteca. Enclosed are the Authority to Construct permits and a copy of the notice of final action to be published approximately three days from the date of this letter. As discussed below, Delicato Vineyards must not begin construction until applying for, and receiving, a final Part 70 (Title V) permit amendment.

Please be aware that EPA has expressed concern about your project with respect to federal Lowest Achievable Emission Rate (LAER) requirements for new and modified fermentation tanks. While the District believes it has fully demonstrated that your proposal complies with all federal, state, and local permitting requirements, it is evident that additional time would be beneficial to allow further discussions on this issue. Therefore, the District has issued these Authority to Construct permits without Certificates of Conformity with Part 70 (Title V) permitting requirements, with the intent that EPA, the District, and other interested parties work together to resolve these LAER concerns so that the District may issue at a later date your facility's Title V permit without EPA objection.

Also, please be aware that your project triggers a significant permit modification to the Title V permit and a final Part 70 permit amendment has not been issued for this proposal. Pursuant to Section 6.3 of District Rule 2520, a source may implement the changes addressed in the request for a significant permit modification only after a final Part 70 permit amendment is issued by the District. Therefore, you may not begin construction of the proposed tanks until the Part 70 permit amendment is issued.

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

www.valleyair.org www.healthyairliving.com

Printed on recycled paper.

Notice of the District's preliminary decision to issue the Authority to Construct permits was published on June 6, 2016. The District's analysis of the proposal was also sent to the California Air Resources Board (CARB) and US EPA Region IX on June 1, 2016. All comments received following the District's preliminary decision on this project were considered.

Comments received by the District during the public notice period resulted in revisions to the conditions relating to the Title V application requirements. These changes were minor and did not trigger additional public notification requirements, nor did they have any impact upon the Best Available Control Technology determination or on the amount of offsets required for project approval.

Also enclosed is an invoice for the engineering evaluation fees pursuant to District Rule 3010. Please remit the amount owed, along with a copy of the attached invoice, within 60 days.

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Errol Villegas at (559) 230-6000.

Sincerely,

Arnaud Marjollet
Director of Permit Services

AM:jag

Enclosures

cc: Tung Le, CARB (w/enclosure) via email
cc: Gerardo C. Rios, EPA (w/enclosure) via email

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

Facility # N-266
DELICATO VINEYARDS
12001 S HIGHWAY 99
MANTECA, CA 95336

AUTHORITY TO CONSTRUCT (ATC)

QUICK START GUIDE

1. **Pay Invoice**: Please pay enclosed invoice before due date.
2. **Modify Your Title V Permit.** Prior to operating the equipment authorized under this ATC, submit an application to modify your Title V permit. See application forms at http://www.valleyair.org/busind/pto/ptoforms/1ptoformidx.htm.
3. **Fully Understand ATC**: Make sure you understand ALL conditions in the ATC prior to construction, modification and/or operation.
4. **Follow ATC**: You must construct, modify and/or operate your equipment as specified on the ATC. Any unspecified changes may require a new ATC.
5. **Notify District**: You must notify the District's Compliance Department, at the telephone numbers below, upon start-up and/or operation under the ATC. Please record the date construction or modification commenced and the date the equipment began operation under the ATC. You may NOT operate your equipment until you have notified the District's Compliance Department. A startup inspection may be required prior to receiving your Permit to Operate.
6. **Source Test**: Schedule and perform any required source testing. See http://www.valleyair.org/busind/comply/source_testing.htm for source testing resources.
7. **Maintain Records**: Maintain all records required by ATC. Records are reviewed during every inspection (or upon request) and must be retained for at least 5 years. Sample record keeping forms can be found at http://www.valleyair.org/busind/comply/compliance_forms.htm.

By operating in compliance, you are doing your part to improve air quality for all Valley residents.

For assistance, please contact District Compliance staff at any of the telephone numbers listed below.

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

www.valleyair.org www.healthyairliving.com

Printed on recycled paper.

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-822-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
154,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-1) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for Arnaud Marjollet, Director of Permit Services
N-266-822-0 Dec 14 2016 4:09PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-823-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
154,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-2) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-823-0 Dec 14 2016 4:09PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-824-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
154,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-3) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-824-0 Dec 14 2016 4:09PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-825-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
154,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-4) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-825-0 Dec 14 2016 4:09PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-826-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
154,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-5) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for Arnaud Marjollet, Director of Permit Services

N-266-826-0 Dec 14 2016 4:09PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-827-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
154,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-6) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

For
Arnaud Marjollet, Director of Permit Services
N-266-827-0 Dec 14 2016 4:09PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-828-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
154,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-7) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-828-0 : Dec 14 2016 4:08PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-829-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
154,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-8) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-829-0 Dec 14 2016 4:08PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-830-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
154,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-9) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-830-0 : Dec 14 2016 4:09PM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-831-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
154,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-10) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-831-0 : Dec 14 2016 4:09PM -- GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-832-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
154,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-11) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-832-0 Dec 14 2016 4:09PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-833-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
154,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-12) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-833-0 Dec 14 2016 4:09PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-834-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
154,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-13) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-834-0 : Dec 14 2016 4:09PM -- GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-835-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
154,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-14) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-835-0 Dec 14 2016 4:08PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-836-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
154,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-15) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for Arnaud Marjollet, Director of Permit Services

N-266-836-0 : Dec 14 2016 4:09PM -- GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-837-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
154,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-16) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for Arnaud Marjollet, Director of Permit Services
N-266-837-0 Dec 14 2016 4:09PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-838-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-17) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for Arnaud Marjollet, Director of Permit Services
N-266-838-0 : Dec 14 2016 4:09PM -- GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-839-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-18) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services

N-266-839-0 Dec 14 2016 4:09PM -- GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-840-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-19) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-840-0 Dec 14 2016 4:09PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-841-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-20) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-841-0 Dec 14 2016 4:09PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-842-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-21) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for Elvis

Arnaud Marjollet, Director of Permit Services
N-266-842-0 Dec 14 2016 4:09PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-843-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-22) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for _____
Arnaud Marjollet, Director of Permit Services

N-266-843-0 Dec 14 2016 4:10PM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-844-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-23) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for Arnaud Marjollet, Director of Permit Services
N-266-844-0 Dec 14 2016 4:10PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-845-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-24) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-845-0 Dec 14 2016 4:10PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-846-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-25) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-846-0 Dec 14 2016 4:10PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-847-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-26) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services

N-266-847-0 · Dec 14 2016 4:10PM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-848-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-27) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

Arnaud Marjollet, Director of Permit Services
N-266-848-0 Dec 14 2016 4:10PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-849-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-28) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services

N-266-849-0 Dec 14 2016 4:10PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-850-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-29) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-850-0 Dec 14 2016 4:10PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-851-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-30) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for Arnaud Marjollet, Director of Permit Services
N-266-851-0 Dec 14 2016 4:10PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-852-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-31) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-852-0 : Dec 14 2016 4:10PM -- GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-853-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-32) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-853-0 Dec 14 2016 4:10PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-854-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-33) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for Arnaud Marjollet, Director of Permit Services

N-266-854-0 Dec 14 2016 4:10PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-855-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-34) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services

Northern Regional Office • 4800 Enterprise Way • Modesto, CA 95356-8718 • (209) 557-6400 • Fax (209) 557-6475

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-856-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-35) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-856-0 Dec 14 2016 4 10PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-857-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-36) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-857-0 Dec 14 2016 4:10PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-858-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-37) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services

N-266-858-0 Dec 14 2016 4:10PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-859-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-38) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-859-0 : Dec 14 2016 4:10PM -- GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-860-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-39) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-860-0 Dec 14 2016 4:10PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-861-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-40) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-861-0 Dec 14 2016 4:10PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-862-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-41) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-862-0 Dec 14 2016 4:10PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-863-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-42) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services

N-266-863-0 Dec 14 2016 4:10PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-864-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-43) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-864-0 Dec 14 2016 4:10PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit
21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit
22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-865-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-44) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services

N-266-865-0 Dec 14 2016 4:10PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-866-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-45) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services

N-266-866-0 : Dec 14 2016 4:10PM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-867-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-46) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for Arnaud Marjollet, Director of Permit Services

N-266-867-0 Dec 14 2016 4:10PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-868-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-47) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-868-0 : Dec 14 2016 4:10PM -- GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-869-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-48) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services

N-266-869-0 Dec 14 2016 4:10PM -- GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-870-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-49) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-870-0 Dec 14 2016 4:10PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-871-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-50) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for Arnaud Marjollet, Director of Permit Services

N-266-871-0 Dec 14 2016 4:10PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-872-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-51) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-872-0 : Dec 14 2016 4:10PM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-873-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-52) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-873-0 Dec 14 2016 4:11PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-874-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-53) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services

N-266-874-0 Dec 14 2016 4:11PM -- GARCIAJ · Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-875-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-54) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for Arnaud Marjollet, Director of Permit Services

N-266-875-0 Dec 14 2016 4:11PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-876-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-55) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-876-0 Dec 14 2016 4:11PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-877-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-56) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-877-0 Dec 14 2016 4:11PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-878-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-57) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for Arnaud Marjollet, Director of Permit Services

N-266-878-0 Dec 14 2016 4:11PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-879-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-58) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

For

Arnaud Marjollet, Director of Permit Services

N-266-879-0 ' Dec 14 2016 4:11PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-880-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-59) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services

N-266-880-0 : Dec 14 2016 4:11PM - GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-881-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-60) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

For Arnaud Marjollet, Director of Permit Services

N-266-881-0 Dec 14 2016 4:11PM -- GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-882-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-61) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-882-0 Dec 14 2016 4:11PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-883-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-45) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-883-0 Dec 14 2016 4:11PM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-884-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-63) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-884-0 : Dec 14 2016 4:11PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-885-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-64) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for Arnaud Marjollet, Director of Permit Services
N-266-885-0 Dec 14 2016 4:11PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-886-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-65) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-886-0 Dec 14 2016 4:11PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-887-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-66) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-887-0 Dec 14 2016 4:11PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-888-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-67) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-888-0 : Dec 14 2016 4:11PM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-889-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-68) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-889-0 Dec 14 2016 4:11PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-890-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-69) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services

N-266-890-0 Dec 14 2016 4:11PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-891-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-70) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

For Arnaud Marjollet, Director of Permit Services

N-266-891-0 Dec 14 2016 4:11PM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit
21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit
22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-892-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-71) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-892-0 : Dec 14 2016 4:11PM -- GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-893-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-72) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services

N-266-893-0 Dec 14 2016 4:11PM -- GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-894-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-73) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-894-0 Dec 14 2016 4:11PM -- GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit
21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit
22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-895-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-74) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for Arnaud Marjollet, Director of Permit Services

N-266-895-0 Dec 14 2016 4:11PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-896-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-75) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-896-0 : Dec 14 2016 4:11PM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-897-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-76) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for Arnaud Marjollet, Director of Permit Services

N-266-897-0 Dec 14 2016 4:11PM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-898-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-77) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

For Arnaud Marjollet, Director of Permit Services
N-266-898-0 Dec 14 2016 4:11PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-899-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-78) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for Arnaud Marjollet, Director of Permit Services

N-266-899-0 Dec 14 2016 4:11PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-900-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-79) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

For Arnaud Marjollet, Director of Permit Services
N-266-900-0 Dec 14 2016 4:11PM -- GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-901-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-80) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-901-0 Dec 14 2016 4:11PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-902-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-81) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

Arnaud Marjollet, Director of Permit Services
N-266-902-0 Dec 14 2016 4:12PM -- GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-903-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-82) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

Arnaud Marjollet, Director of Permit Services
N-266-903-0 : Dec 14 2016 4 12PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-904-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-83) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services

N-266-904-0 : Dec 14 2016 4:12PM -- GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-905-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-84) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-905-0 Dec 14 2016 4:12PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-906-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-85) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for Arnaud Marjollet, Director of Permit Services

N-266-906-0 Dec 14 2016 4:12PM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-907-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-86) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services

N-266-907-0 Dec 14 2016 4:12PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-908-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-87) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for Arnaud Marjollet, Director of Permit Services

N-266-908-0 Dec 14 2016 4:12PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-909-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-88) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-909-0 : Dec 14 2016 4:12PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit
21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit
22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-910-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-89) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-910-0 Dec 14 2016 4:12PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-911-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-90) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for Arnaud Marjollet, Director of Permit Services

N-266-911-0 Dec 14 2016 4:12PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-912-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-91) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services

N-266-912-0 : Dec 14 2016 4:12PM -- GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-913-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-92) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-913-0 Dec 14 2016 4:12PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-914-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-93) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-914-0 Dec 14 2016 4:12PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-915-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-94) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for Arnaud Marjollet, Director of Permit Services
N-266-915-0 Dec 14 2016 4:12PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-916-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
74,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-95) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 28 feet in height with a proposed volume of 74,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for Arnaud Marjollet, Director of Permit Services

N-266-916-0 Dec 14 2016 4:12PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-917-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
74,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-96) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 28 feet in height with a proposed volume of 74,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services

N-266-917-0 Dec 14 2016 4:12PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-918-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
74,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-97) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 28 feet in height with a proposed volume of 74,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-918-0 Dec 14 2016 4:12PM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-919-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
74,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-98) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 28 feet in height with a proposed volume of 74,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-919-0 Dec 14 2016 4:12PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-920-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
74,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-99) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 28 feet in height with a proposed volume of 74,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-920-0 Dec 14 2016 4:12PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-921-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
74,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-100) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 28 feet in height with a proposed volume of 74,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-921-0 Dec 14 2016 4:12PM - GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-922-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
74,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-101) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 28 feet in height with a proposed volume of 74,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services

N-266-922-0 Dec 14 2016 4:12PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit.
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-923-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
74,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-102) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 28 feet in height with a proposed volume of 74,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-923-0 : Dec 14 2016 4:12PM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-924-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
74,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-103) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 28 feet in height with a proposed volume of 74,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-924-0 Dec 14 2016 4:12PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-925-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
74,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-104) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 28 feet in height with a proposed volume of 74,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-925-0 Dec 14 2016 4:12PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-926-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
74,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-105) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 28 feet in height with a proposed volume of 74,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-926-0 : Dec 14 2016 4:12PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit
21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit
22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-927-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
74,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-106) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 28 feet in height with a proposed volume of 74,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-927-0 Dec 14 2016 4:12PM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-928-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
74,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-107) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 28 feet in height with a proposed volume of 74,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for Arnaud Marjollet, Director of Permit Services

N-266-928-0 Dec 14 2016 4:12PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-929-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
74,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-108) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 28 feet in height with a proposed volume of 74,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for Arnaud Marjollet, Director of Permit Services
N-266-929-0 Dec 14 2016 4:12PM -- GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-930-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-109) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for Arnaud Marjollet, Director of Permit Services

N-266-930-0 Dec 14 2016 4:12PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-931-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-110) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-931-0 : Dec 14 2016 4:13PM -- GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-932-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-111) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-932-0 Dec 14 2016 4:13PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5,2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-933-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-112) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-933-0 : Dec 14 2016 4:13PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-934-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-113) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

For

Arnaud Marjollet, Director of Permit Services
N-266-934-0 Dec 14 2016 4:13PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-935-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-114) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

For Arnaud Marjollet, Director of Permit Services

N-266-935-0 : Dec 14 2016 4:13PM -- GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-936-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-115) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-936-0 Dec 14 2016 4:13PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit
21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit
22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-937-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-116) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services

N-266-937-0 Dec 14 2016 4:13PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-938-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-117) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-938-0 Dec 14 2016 4:13PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-939-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-118) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-939-0 Dec 14 2016 4:13PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-940-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-119) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-940-0 : Dec 14 2016 4:13PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-941-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-120) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-941-0 : Dec 14 2016 4:13PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-942-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-121) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

Arnaud Marjollet, Director of Permit Services
N-266-942-0 : Dec 14 2016 4:13PM - GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-943-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-122) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-943-0 Dec 14 2016 4:13PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-944-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-123) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-944-0 : Dec 14 2016 4:13PM -- GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-945-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-124) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for _____
Arnaud Marjollet, Director of Permit Services

N-266-945-0 Dec 14 2016 4:13PM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-946-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-125) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-946-0 Dec 14 2016 4:13PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-947-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-126) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for Arnaud Marjollet, Director of Permit Services

N-266-947-0 Dec 14 2016 4:13PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-948-0 **ISSUANCE DATE:** 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-127) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for

Arnaud Marjollet, Director of Permit Services
N-266-948-0 · Dec 14 2016 4:13PM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

AUTHORITY TO CONSTRUCT

PERMIT NO: N-266-949-0

ISSUANCE DATE: 12/14/2016

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-128) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

for Arnaud Marjollet, Director of Permit Services

N-266-949-0 Dec 14 2016 4:13PM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley Air Pollution Control District

Authority to Construct Application Review with Comments and District Responses

128 New Wine Fermentation and Storage Tanks

Facility Name:	Delicato Vineyards	Date:	December 14, 2016
Mailing Address:	12001 S Highway 99 Manteca, CA 95336	Engineer:	Jesse A. Garcia
		Lead Engineer:	Joven Refuerzo
Contact Person:	Christine Campbell		
Telephone:	(209) 824-3675		
Email:	Christine.campbell@delicato.com		
Application #(s):	N-266-822-0 through -949-0		
Project #:	N-1152244		
Deemed Complete:	June 1, 2014		

I. Proposal

Delicato Vineyards (Delicato) has requested Authority to Construct (ATC) permits for the installation of 128 new wine fermentation and storage tanks:

Quantity	ATC	Tank
16	N-266-822-0 thru -837-0	154,000 gallon insulated and jacketed stainless steel tanks
28	N-266-838-0 thru -865-0	103,000 gallon insulated and jacketed stainless steel tanks
50	N-266-866-0 thru -915-0	60,000 gallon insulated and jacketed stainless steel tanks
14	N-266-916-0 thru -929-0	74,000 gallon insulated and jacketed stainless steel tanks
20	N-266-930-0 thru -949-0	50,000 gallon insulated and jacketed stainless steel tanks

Delicato proposes to permit these tanks under the facility's existing Specific Limiting Condition (SLC) which limits the combined annual VOC emissions from all wine fermentation and storage operations at their facility.

Delicato Vineyards received their Title V Permit. This modification can be classified as a Title V significant modification pursuant to Rule 2520, and can be processed with a Certificate of Conformity (COC) however; the District does not intend to issue the ATC's with a COC. The "Enhanced Administrative Requirements" of Section 5.9 of District Rule 2201 allow the issuance of an Authority to Construct with or without Certificates of Conformity with Title V permitting requirements, provided specific administrative steps are taken prior to issuance. Therefore, a Title V Significant Modification must be performed prior to implementing the Authority to Construct permits issued with this project.

II. Applicable Rules

Rule 2201	New and Modified Stationary Source Review Rule (4/21/11) [1]
Rule 2410	Prevention of Significant Deterioration (6/16/11)
Rule 2520	Federally Mandated Operating Permits (6/21/01)
Rule 4001	New Source Performance Standards (4/14/99)
Rule 4002	National Emissions Standards for Hazardous Air Pollutants (5/20/04)
Rule 4102	Nuisance (12/17/92)
Rule 4694	Wine Fermentation and Storage Tanks (12/15/05)
CH&SC 41700	Health Risk Assessment
CH&SC 42301.6	School Notice

Public Resources Code 21000-21177: California Environmental Quality Act (CEQA)
California Code of Regulations, Title 14, Division 6, Chapter 3, Sections 15000-15387: CEQA Guidelines

III. Project Location

The facility is located at 12001 S Highway 99 in Manteca, CA. The equipment is not located within 1,000 feet of the outer boundary of a K-12 school. Therefore, the public notification requirement of California Health and Safety Code 42301.6 is not applicable to this project.

IV. Process Description

Delicato Vineyards produces both red and white table wines, as well as other specialty wine products, from the fermentation of grapes. During the "crush season," typically from late August to late November, both red and white grapes are received by truck and delivered to a crusher-stemmer which serves to crush the grapes and remove the stems. In the case of red wines, the resultant juice (termed "must" and containing the grape skins, pulp and seeds) is pumped to red wine fermentation tanks for fermentation, a batch process. The red wine fermentation tanks are specifically designed to ferment the must in contact with the skins and to allow the separation of the skins and seeds from the wine after fermentation. For white wines, the must is sent to screens and presses for separation of grape skins and seeds prior to entering the fermentation tank. Since the skins and seed have been separated, white wine fermentation is carried out in a tank that doesn't include design provisions for solids separation.

After transfer of the must (red or white) to the fermentation tank, the must is inoculated with yeast. This initiates the fermentation reactions. The yeast metabolizes the sugars in the must, converting the sugars to ethanol and carbon dioxide (CO_2). This process is an exothermic process, thus temperature must be controlled throughout the process. Refrigeration is used to maintain a temperature of 45-65°F for white wine fermentation and 70-95°F for red wine fermentation. The sugar content of the fermenting wine is measured in °Brix (weight %) and is typically 22-26° for unfermented wine, dropping to 4° or less by the end of fermentation process. For the wines produced in the proposed tanks, the final ethanol concentration will be no greater than 20.0%. Batch fermentation requires 5 days per batch of red wine and 1-2

[1] This project was deemed complete prior to the 2/18/2016 amendment to Rule 2201. Therefore, the project is subject to the previous 4/21/11 version of Rule 2201.

weeks per batch of white wine. VOCs are emitted during the fermentation process, along with CO_2. The VOCs are comprised primarily of ethanol along with some trace fermentation byproducts.

Following the completion of fermentation, white wine is transferred directly to storage tanks. Red wine is first directed to the presses for separation of solids and then routed to the storage tanks. Tanks can potentially operate in either: (1) a fermentation operation during which the tank is vented directly to the atmosphere to release the evolved CO_2 byproduct from the fermentation reaction; (2) a storage operation during which the tank is closed to minimize contact with air and refrigerated to preserve the wine; (3) or both fermentation and storage operations. Post-fermentation operations such as cold stabilization, racking, and filtration are conducted in the tanks, resulting in a number of inter-tank transfers during the period between the end of fermentation and bottling or bulk shipment. Storage operations are conducted year-round. VOC emissions occur primarily as a result of the inter-tank transfers which are necessitated by the post fermentation operations.

V. Equipment Listing

The applicant is proposing to install 128 new wine storage and fermentation tanks. All of the proposed tanks are equipped with pressure/vacuum valves and tank insulation. The typical equipment descriptions are as follows:

Tank I.D.	ATC #	Equipment Description
T-1 thru T-16	N-266-822-0 thru -837-0	154,000 GALLON INSULATED STAINLESS STEEL WINE FERMENTATION AND STORAGE TANK (TANK T-XXX*) WITH PRESSURE/VACUUM VALVE
T-17 thru T-44	N-266-838-0 thru -865-0	103,000 GALLON INSULATED STAINLESS STEEL WINE FERMENTATION AND STORAGE TANK (TANK T-XXX*) WITH PRESSURE/VACUUM VALVE
T-45 thru T-94	N-266-866-0 thru -915-0	60,000 GALLON INSULATED STAINLESS STEEL WINE FERMENTATION AND STORAGE TANK (TANK T-XXX*) WITH PRESSURE/VACUUM VALVE
T-95 thru T-108	N-266-916-0 thru -929-0	74,000 GALLON INSULATED STAINLESS STEEL WINE FERMENTATION AND STORAGE TANK (TANK T-XXX*) WITH PRESSURE/VACUUM VALVE
T-109 thru T-128	N-266-930-0 thru -949-0	50,000 GALLON INSULATED STAINLESS STEEL WINE FERMENTATION AND STORAGE TANK (TANK T-XXX*) WITH PRESSURE/VACUUM VALVE

* Typical tank number

As per District policy APR 1035 Flexibility in Equipment Descriptions in ATCs, some flexibility in the final specifications of the equipment is requested. The proposed tanks in this project will be built on-site and most likely will contain slight variations in the tank dimensions which lead to slightly different tank capacities than proposed. These slight tank variations should not have a significant effect on the tank emissions or tank operation. Therefore, the permit will specify the nominal tank dimensions and the source will submit to the District the measured tank

capacity (known as the gauge volume) once the tank is constructed. The following sample condition will be listed on the permits to ensure compliance:

- The nominal tank dimensions are XX feet in diameter and XX feet in height with a proposed volume of XXX,XXX gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201]

VI. Emission Control Technology Evaluation

VOCs, primarily ethanol, are emitted from wine fermentation and storage tanks as a result of both working losses (which occur when the liquid level in the tank changes) and breathing losses (expansion and contraction effects due to temperature variations). The proposed pressure/vacuum relief valve limits emissions of VOC's. Additionally, when wine storage tanks are insulated or located in a climate controlled building, breathing losses are considered to be negligible.

The tanks are equipped with temperature controls to maintain tank temperatures below levels that might be damaging to the yeast cells and reduces the potential for an out-of-control fermentation reaction in the tank. Since potential VOC emissions from the tanks increase with fermentation temperature, the use of temperature controls minimizes emissions.

VII. General Calculations

A. Assumptions

- VOC is the only pollutant emitted by the tanks.
- The proposed tanks will be used for red and white wine fermentation and storage.

Storage

- Typically, for enclosed tanks with refrigeration and/or insulation (or equivalent) and P/V valves, breathing losses from storage of wine are assumed to be negligible.
- Maximum daily liquid storage temperature = 81.0 °F (per FYI-114, See Appendix G)
- Maximum annual liquid storage temperature = 63.3 °F (per FYI-114, See Appendix G)
- Ethanol content of stored wine is 20% (per applicant)
- The applicant has proposed to the following storage throughputs:

ATC #	Daily Throughput (gallons/day)	Annual Throughput (gallons/year)*
N-266-822-0 thru -837-0	616,000	1,540,000
N-266-838-0 thru -865-0	412,000	1,030,000
N-266-866-0 thru -915-0	240,000	600,000
N-266-916-0 thru -929-0	296,000	740,000
N-266-930-0 thru -949-0	200,000	500,000

* Although the applicant proposed an annual throughput for each tank, the applicant has clarified that it only wishes to have the permits limited by a combined limit or SLC.

Fermentation

- For either red or white wine, the fermentation process takes longer than a day (3 to 5 days for red wine and 10 to 14 days for white wine). Therefore, a maximum of one turnover per day will be used to determine the potential daily emissions.
- The applicant has proposed to limit the annual throughput as follows:

ATC #	Annual Throughput (gallons/year)*	
	Red Wine	White Wine
N-266-822-0 thru -837-0	616,000	1,609,300
N-266-838-0 thru -865-0	412,000	1,076,350
N-266-866-0 thru -915-0	240,000	627,000
N-266-916-0 thru -929-0	280,000	731,500
N-266-930-0 thru -949-0	200,000	522,500

* As stated above, although annual throughput amounts are shown in the table, the applicant proposes to limit the annual fermentation emissions from the proposed tank to an equivalent combined limit or SLC as calculated in Section VII.C.2 below.

B. Emission Factors

Storage

Tanks 4.0 will be used to calculate the emissions from the storage tanks.

Fermentation

Uncontrolled emissions factors are taken from District FYI-114, *VOC Emission Factors for Wine Fermentation and Storage Tanks* (See Appendix G).

Wine Type	**Emission Factor**	
	Daily (lb-VOC/1000 gallons tank capacity per day)	Annual (lb-VOC/1,000 gallon of wine)
White	1.62	2.5
Red	3.46	6.2

C. Calculations

1. Pre-Project Potential to Emit (PE1)

Since these are new emissions units, PE1 = 0 all pollutants.

2. Post Project Potential to Emit (PE2)

Storage

Two Tanks 4.0 runs have been performed using each the daily and annual throughputs stated above. The daily post-project potential to emit is calculated by dividing the month of February emissions by the number of days in the month and the annual potential to emit is calculated using the Tanks 4.0 program for each tank.

Post-Project Potential to Emit (Storage)				
Permit Unit	**Daily PE2, each (lb-VOC/day)**	**Daily PE2, each group (lb-VOC/day)**	**Annual PE2, each tank (lb-VOC/year)**	**Annual PE2, each group (lb-VOC/year)**
N-266-822-0 thru -837-0	75.5	1,208.4	467	7,472
N-266-838-0 thru -865-0	55.9	1,565.9	312	8,736
N-266-866-0 thru -915-0	32.6	1,628.9	182	9,100
N-266-916-0 thru -929-0	40.2	562.5	224	3,136
N-266-930-0 thru -949-0	33.1	661.5	185	3,700
Total for all Tanks	- -	5,627.1	- -	32,144

Fermentation

The daily emissions are calculated using the following equation and summarized in the table below:

Daily PE_{VOC} = Tank Capacity (gal) x $EF_{Red/White}$ (lb-VOC/1000 gal of tanks capacity)

Daily Post-Project Potential to Emit (Wine Fermentation)						
Permit Unit	**Daily EF**		**Tank Capacity**	**PE2 Daily, each tank**		**PE2 Daily, each group**
	(lb-VOC/1,000 gal)		(gallons/day)	(lb/day)		(lb/day)
	Red	White	- -	Red	White	Red
N-266-822-0 thru -837-0	3.46	1.62	154,000	**532.8**	249.5	**8524.8**
N-266-838-0 thru -865-0			103,000	**356.4**	166.9	**9979.2**
N-266-866-0 thru -915-0			60,000	**207.6**	97.2	**10380.0**
N-266-916-0 thru -929-0			74,000	**256.0**	119.9	**3584.0**
N-266-930-0 thru -949-0			50,000	**173.0**	81.0	**3460.0**
					Total	**35,928.0**

* Since the emissions from red wine fermentation are greater than white wine fermentation, the red wine emissions will be taken as Daily PE2.

Since the proposed red and white wine fermentation operations have different throughput amounts and emission factors, the emissions for both will be calculated and the highest annual emissions will be used for the remainder of the evaluation. The annual emissions are calculated using the following equation and summarized in the table below:

Annual PE_{VOC} = $Throughput_{red/white}$ (gal/year) x $EF_{Red/White}$ (lb-VOC/1000 gal)

Annual Post-Project Potential to Emit (Wine Fermentation)							
Permit Unit	**Annual EF**		**Equivalent Annual Throughput**		**PE2 Annual, each tank**		**PE2 Annual, each group**
	(lb-VOC/1,000 gal)		(gallons/year)		(lb/year)		(lb/year)
	Red	White	Red	White	Red	White	White*
N-266-822-0 thru -837-0	6.2	2.5	616,000	1,609,300	3,819	**4,023**	**64,368**
N-266-838-0 thru -865-0			412,000	1,076,350	2,554	**2,691**	**75,348**
N-266-866-0 thru -915-0			240,000	627,000	1,488	**1,568**	**78,400**
N-266-916-0 thru -929-0			280,000	731,500	1,736	**1,829**	**25,606**
N-266-930-0 thru -949-0			200,000	522,500	1,240	**1,306**	**26,120**
						Total	**269,842**

* Since the emissions from white wine fermentation are greater than red wine fermentation, the white wine emissions will be taken as Annual PE2.

The PE2 for each tank is calculated above; however, the facility proposes to limit the annual emissions from the tanks in this project to the worst case annual emissions, which is from white wine fermentation of 269,842 lb-VOC/year, for all storage and fermentation operations in this project.

Additionally, the facility has an existing SLC of 394,298 lb-VOC/year for all wine storage and fermentation operations at the facility and the applicant is not proposing any changes to this limit.

These limits will be included on the draft ATCs and are listed under the Daily Emissions Limit of Rule 2201 under Section VIII below.

3. Pre-Project Stationary Source Potential to Emit (SSPE1)

Pursuant to District Rule 2201, the SSPE1 is the Potential to Emit (PE) from all units with valid Authorities to Construct (ATC) or Permits to Operate (PTO) at the Stationary Source and the quantity of Emission Reduction Credits (ERC) which have been banked since September 19, 1991 for Actual Emissions Reductions (AER) that have occurred at the source, and which have not been used on-site.

This project only concerns VOC emissions. This facility acknowledges that its VOC emissions are already above the Offset and Major Source Thresholds for VOC emissions; therefore, SSPE1 calculations are not necessary.

4. Post Project Stationary Source Potential to Emit (SSPE2)

Pursuant to District Rule 2201, the SSPE2 is the PE from all units with valid ATCs or PTOs at the Stationary Source and the quantity of ERCs which have been banked since September 19, 1991 for AER that have occurred at the source, and which have not been used on-site.

This project only concerns VOC emissions. This facility acknowledges that its VOC emissions are already above the Offset and Major Source Thresholds for VOC emissions; therefore, SSPE2 calculations are not necessary.

5. Major Source Determination

Rule 2201 Major Source Determination:

This source is an existing Major Source for VOC emissions and will remain a Major Source for VOC. No change in other pollutants are proposed or expected as a result of this project.

Rule 2410 Major Source Determination:

As indicated above, the SSPE VOC emission before the proposal project is limited by permit condition to 394,298 pounds of VOC per year, equivalent to 197.7 tons of VOC per year. The other pollutants were taken from Project N-1132478 and are summarized in the table below:

PSD Major Source Determination (tons/year)						
	NO2	VOC	SO2	CO	PM	PM10
Estimated Facility PE before Project Increase	0.3	197.7	0.1	0.8	0.3	0.3
PSD Major Source Thresholds	250	250	250	250	250	250
PSD Major Source ? (Y/N)	N	N	N	N	N	N

As shown above, the facility is not an existing Major Source for PSD for any pollutant. Therefore, the facility is not an existing Major Source for PSD.

6. Baseline Emissions (BE)

The BE calculation (in lbs/year) is performed pollutant-by-pollutant for each unit within the project, to calculate the QNEC and if applicable, to determine the amount of offsets required.

Pursuant to Section 3.7 of District Rule 2201, BE = Pre-project Potential to Emit for:

- Any unit located at a non-Major Source,
- Any Highly-Utilized Emissions Unit, located at a Major Source,
- Any Fully-Offset Emissions Unit, located at a Major Source, or
- Any Clean Emissions Unit, located at a Major Source.

Otherwise,

BE = Historic Actual Emissions (HAE), calculated pursuant to Section 3.22 of District Rule 2201.

Since these are new emissions units, BE = PE1 = 0 for all pollutants for each unit.

7. SB 288 Major Modification

SB 288 Major Modification is defined in 40 CFR Part 51.165 as "*any physical change in or change in the method of operation of a major stationary source that would result in a significant net emissions increase of any pollutant subject to regulation under the Act.*"

As discussed in Section VII.C.5 above, the facility is an existing Major Source for VOC; however, the project by itself would need to be a significant increase in order to trigger a Major Modification. The emissions units within this project have a total potential to emit which is greater than Major Modification thresholds (see table below). Therefore, the project is a significant increase and the project does constitute a Major Modification.

SB 288 Major Modification Thresholds (Existing Major Source)			
Pollutant	Project PE (lb/year)	Threshold (lb/year)	Major Modification?
VOC	269,842	50,000	Yes

8. Federal Major Modification

District Rule 2201, Section 3.17 states that Federal Major Modifications are the same as "Major Modification" as defined in 40 CFR 51.165 and part D of Title I of the CAA. SB 288 Major Modifications are not federal major modifications if they meet the criteria of the "Less-Than-Significant Emissions Increase" exclusion.

A Less-Than-Significant Emissions Increase exclusion is for an emissions increase for the

project, or a Net Emissions Increase for the project (as defined in 40 CFR 51.165 (a)(2)(ii)(B) through (D), and (F)), that is not significant for a given regulated NSR pollutant, and therefore is not a federal major modification for that pollutant.

- To determine the post-project projected actual emissions from existing units, the provisions of 40 CFR 51.165 (a)(1)(xxviii) shall be used.
- To determine the pre-project baseline actual emissions, the provisions of 40 CFR 51.165 (a)(1)(xxxv)(A) through (D) shall be used.
- If the project is determined not to be a federal major modification pursuant to the provisions of 40 CFR 51.165 (a)(2)(ii)(B), but there is a reasonable possibility that the project may result in a significant emissions increase, the owner or operator shall comply with all of the provisions of 40 CFR 51.165 (a)(6) and (a)(7).
- Emissions increases calculated pursuant to this section are significant if they exceed the significance thresholds specified in the table below.

Significant Threshold (lb/year)	
Pollutant	Threshold (lb/year)
VOC	0

The Net Emissions Increases (NEI) for purposes of determination of a "Less-Than-Significant Emissions Increase" exclusion will be calculated below to determine if this project qualifies for such an exclusion.

Net Emission Increase for New Units (NEI_N)

NEI can be calculated as the sum of the difference of the project actual emissions (PAE) and baseline actual emissions (BAE) for the emissions units involved in this project. Thus,

$NEI = \sum(PAE - BAE)$

Since this project involves only new emissions units, and no change to the existing emissions units. The baseline actual emissions for the new units are each equal to zero. Thus,

$NEI = \sum(PAE - BAE)_{New}$

Where:

$BAE_{New} = 0$

$NEI = \sum(PAE)_{New} = 269{,}842$ lb-VOC/year

Since there is an increase in VOC emissions, this project constitutes a Federal Major Modification. Federal Offset quantities are calculated below.

Federal Offset Quantities:

The Federal offset quantity is only calculated only for the pollutants for which the project is a Federal Major Modification. The Federal offset quantity is the sum of the annual emission changes for all new and modified emission units in a project calculated as the potential to emit after the modification (PE2) minus the actual emissions (AE) during the baseline period for each emission unit times the applicable federal offset ratio. There are no special calculations performed for units covered by an SLC.

VOC **Federal Offset Ratio** **1.5**

Permit No.	Actual Emissions (lb/year)	Potential Emissions (lb/year)	Emissions Change (lb/yr)
N-266-822-0 through -949-0	0	269,842	269,842
		Net Emission Change (lb/year):	269,842
		Federal Offset Quantity: (NEC * 1.5)	**404,763**

9. Rule 2410 – Prevention of Significant Deterioration (PSD) Applicability Determination

Rule 2410 applies to any pollutant regulated under the Clean Air Act, except those for which the District has been classified nonattainment. The pollutants which must be addressed in the PSD applicability determination for sources located in the SJV and which are emitted in this project are: (See 52.21 (b) (23) definition of significant)

- NO2 (as a primary pollutant)
- SO2 (as a primary pollutant)
- CO
- PM
- PM10
- Greenhouses gases (GHG): CO2, N2O, CH4, HFCs, PFCs, and SF6

I. Project Emissions Increase - New Major Source Determination

The post-project potentials to emit from all new and modified units are compared to the PSD major source thresholds to determine if the project constitutes a new major source subject to PSD requirements.

The facility or the equipment evaluated under this project is not listed as one of the categories specified in 40 CFR 52.21 (b)(1)(i). The PSD Major Source threshold is 250 tpy for any regulated NSR pollutant.

PSD Major Source Determination: Potential to Emit (tons/year)						
	NO2	VOC	SO2	CO	PM	PM10
Total PE from New and Modified Units	0	135	0	0	0	0
PSD Major Source threshold	250	250	250	250	250	250
New PSD Major Source?	N	N	N	N	N	N

As shown in the table above, the potential to emit for the project, by itself, does not exceed any PSD major source threshold. Therefore Rule 2410 is not applicable and no further analysis is required.

10. Quarterly Net Emissions Change (QNEC)

The QNEC is calculated solely to establish emissions that are used to complete the District's PAS emissions profile screen.

No changes to the SLC of VOC emissions for wine storage and fermentation operations at the facility are proposed. Therefore, QNEC is equal to zero for each quarter for each permit unit.

VIII. Compliance

Rule 2201 New and Modified Stationary Source Review Rule

A. Best Available Control Technology (BACT)

1. BACT Applicability

BACT requirements are triggered on a pollutant-by-pollutant basis and on an emissions unit-by-emissions unit basis for the following*:

a. Any new emissions unit with a potential to emit exceeding two pounds per day,
b. The relocation from one Stationary Source to another of an existing emissions unit with a potential to emit exceeding two pounds per day,
c. Modifications to an existing emissions unit with a valid Permit to Operate resulting in an AIPE exceeding two pounds per day, and/or
d. Any new or modified emissions unit, in a stationary source project, which results in an SB 288 Major Modification or a Federal Major Modification, as defined by the rule.

*Except for CO emissions from a new or modified emissions unit at a Stationary Source with an SSPE2 of less than 200,000 pounds per year of CO.

a. New emissions units – PE > 2 lb/day

The applicant is proposing to install 128 new wine storage and fermentation tanks with a PE greater than 2 lb/day for VOC. Thus BACT is triggered for VOC for these emissions units.

b. Relocation of emissions units – PE > 2 lb/day

There are no emissions units being relocated from one stationary source to another, hence BACT is not triggered under this category.

c. Modification of emissions units – AIPE > 2 lb/day

As discussed in Section I above, there are no modified emissions units associated with this project; therefore BACT is not triggered.

d. SB 288/Federal Major Modification

As discussed in VII.C.7 and VII.C.8 above, this project constitutes a SB288 Major Modification and Federal Major Modification for VOC emissions. Therefore BACT is triggered for VOC for all emissions units in the project for which there is an emission increase.

2. BACT Guideline

BACT Guideline 5.4.14 applies to the wine fermentation tanks. (Appendix B)

BACT Guideline 5.4.13 applies to the wine storage tanks. (Appendix C)

3. Top-Down BACT Analysis

Per Permit Services Policies and Procedures for BACT, a Top-Down BACT analysis shall be performed as a part of the application review for each application subject to the BACT requirements pursuant to the District's NSR Rule.

Pursuant to the attached Top-Down BACT Analyses (Appendix B and C), since the technologically feasible options are not cost effective and pursuant to the attached Achieved-in-Practice Analysis (Appendix D), BACT has been satisfied with the following:

Fermentation

VOC: Temperature-Controlled Open Top Tank with Maximum Average Fermentation Temperature of 95 deg F.

The following condition will be included on the ATC's to ensure continued compliance with the BACT requirements:

- For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]

- The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201]

Storage

VOC: Insulated tank, pressure/vacuum valve set within 10% of the maximum allowable working pressure of the tank, "gas tight" tank operation and achieve and maintain a continuous storage temperature not exceeding 75 °F within 60 days of completion of fermentation.

Each of the proposed wine storage tanks is equipped with insulation or operated inside of an enclosed building, is equipped with a PVRV set to within 10% of the maximum allowable working pressure of the tank; operates in a gas-tight condition and the continuous storage temperature does not exceed 75 degrees F within 60 days of the completion of the fermentation cycle. Therefore, the proposed wine storage tanks meet the BACT requirements for this class and category of operation and no further discussion is required.

The following conditions will be included on the ATC's to ensure continued compliance with the BACT requirements:

- When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]

- The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]

B. Offsets

1. Offset Applicability

Pursuant to Section 4.5.3, offset requirements shall be triggered on a pollutant by pollutant basis and shall be required if the Post Project Stationary Source Potential to Emit (SSPE2) equals to or exceeds the offset threshold levels in Table 4-1 of Rule 2201. Facility emissions are already above the Offset and Major Source Thresholds for VOC emissions; therefore, offsets are triggered.

2. Quantity of Offsets Required

As discussed above, the facility is an existing Major Source for VOC and the SSPE2 is greater than the offset thresholds; therefore offset calculations will be required for this project.

The quantity of offsets in pounds per year for VOC is calculated as follows for sources with an SSPE1 greater than the offset threshold levels before implementing the project being evaluated.

Offsets Required (lb/year) = (Σ[PE2 – BE] + ICCE) x DOR, for all new or modified emissions units in the project,

Where,
PE2 = Post Project Potential to Emit, (lb/year)
BE = Baseline Emissions, (lb/year)
ICCE = Increase in Cargo Carrier Emissions, (lb/year)
DOR = Distance Offset Ratio

BE = Pre-project Potential to Emit for:

- Any unit located at a non-Major Source,
- Any Highly-Utilized Emissions Unit, located at a Major Source,
- Any Fully-Offset Emissions Unit, located at a Major Source, or
- Any Clean Emissions Unit, Located at a Major Source.

otherwise,

BE = Historic Actual Emissions (HAE)

Pursuant to District Policy APR 1420, *NSR Calculations for Units with Specific Limiting Conditions (3/12/07)*, the quantity of ERCs for a project will be determined by comparing the post project PE, which is the SLC, to the pre project BE for the SLC.

Additionally, the policy states that if the SLC is for a pollutant exceeding the Major Source threshold and any single unit under the SLC is not a Highly-Utilized, Fully-Offset, or Clean Emissions Units, then the sum of the actual emissions from all units in SLC will be used to determine the pre project BE.

As established in District Project N-1110749 for the existing tanks and the subsequent NSR project for all newly installed tanks, all tanks at this facility meet the District's determination of achieved-in-practice BACT (and are thus Clean Emission Units), therefore the pre project BE emissions are equal to the pre project PE emissions ($BE_{SLC} = PE1_{SLC}$).

Based on the information above, the emissions increase to be offset for this project should be calculated as follows:

Emissions Increase (lb/year) = $PE2_{SLC} - BE_{SLC}$

Where: $PE2_{SLC}$ = The post project SLC selected by the facility. In this project, $PE2_{SLC} = PE1_{SLC}$.

BE_{SLC} = 394,298 lb-VOC/year

Therefore,

Emissions Increase (lb/year) = $PE2_{SLC} - BE_{SLC}$
= 394,298 lb-VOC/year - 394,298 lb-VOC/year
= 0 lb-VOC/year

C. Public Notification

1. Applicability

Public noticing is required for:

a. New Major Sources, Federal Major Modifications, and SB288 Major Modifications,
b. Any new emissions unit with a Potential to Emit greater than 100 pounds during any one day for any one pollutant,
c. Any project which results in the offset thresholds being surpassed, and/or
d. Any project with an SSIPE of greater than 20,000 lb/year for any pollutant.

a. New Major Sources, Federal Major Modifications, and SB288 Major Modifications

New Major Sources are new facilities, which are also Major Sources. Since this is not a new facility, public noticing is not required for this project for New Major Source purposes.

As demonstrated in Sections VII.C.7 and VII.C.8, this project is an SB 288 and Federal Major Modification. Therefore, public noticing for SB 288 and Federal Major Modification purposes is required.

b. PE > 100 lb/day

Applications which include a new emissions unit with a PE greater than 100 pounds during any one day for any pollutant will trigger public noticing requirements. As seen in Section VII.C.2 above, this project includes new emissions units which have daily emissions greater than 100 lb/day; therefore public noticing for PE > 100 lb/day purposes is required.

c. Offset Threshold

The following table compares the SSPE1 with the SSPE2 in order to determine if any offset thresholds have been surpassed with this project.

Offset Threshold				
Pollutant	SSPE1 (lb/year)	SSPE2 (lb/year)	Offset Threshold	Public Notice Required?
VOC	> 20,000	> 20,000	20,000 lb/year	No

As detailed above, there were no thresholds surpassed with this project; therefore public noticing is not required for offset purposes.

d. SSIPE > 20,000 lb/year

Public notification is required for any permitting action that results in a Stationary Source Increase in Permitted Emissions (SSIPE) of more than 20,000 lb/year of any affected pollutant. According to District policy, the SSIPE is calculated as the Post Project Stationary Source Potential to Emit (SSPE2) minus the Pre-Project Stationary Source Potential to Emit (SSPE1), i.e. SSIPE = SSPE2 – SSPE1. The values for SSPE2 and SSPE1 are calculated according to Rule 2201, Sections 4.9 and 4.10, respectively. The SSIPE is compared to the SSIPE Public Notice thresholds in the following table:

Stationary Source Increase in Permitted Emissions [SSIPE] – Public Notice					
Pollutant	ΣSSPE2 (lb/year)	ΣSSPE1 (lb/year)	SSIPE (lb/year)	SSIPE Public Notice Threshold	Public Notice Required?
VOC	394,298	394,298	0	20,000 lb/year	No

As demonstrated above, the SSIPE for VOC was less than 20,000 lb/year; therefore public noticing for SSIPE purposes is not required.

2. Public Notice Action

As discussed above, public noticing is required for this project for SB 288 and Federal Major Modification and for new units with daily emissions exceeding 100 lb/day. Therefore, public notice documents will be submitted to the California Air Resources Board (CARB) and US Environmental Protection Agency (US EPA) and a public notice

will be published in a local newspaper of general circulation prior to the issuance of the ATCs for this equipment.

D. Daily Emission Limits (DELs)

DELs and other enforceable conditions are required by Rule 2201 to restrict a unit's maximum daily emissions, to a level at or below the emissions associated with the maximum design capacity. The DEL must be contained in the latest ATC and contained in or enforced by the latest PTO and enforceable, in a practicable manner, on a daily basis. DELs are also required to enforce the applicability of BACT.

Proposed Rule 2201 (DEL) Conditions:

For the proposed wine storage tank emissions units in this project, the DEL is enforced with the following conditions:

Storage:

- The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201]
- The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201]
- The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694]
- When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]
- When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

Fermentation:

- The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201]
- The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201]

In addition, in order to enforce the applicant's proposed annual VOC limit, the following conditions will be included on each of the wine storage tank ATC's within this project:

- Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC – 269,842 lb/year. [District Rule 2201]
- Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC – 394,298 lb/year. [District Rule 2201]
- On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Y
- On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201]
- Annual VOC emissions from wine fermentation operations shall be calculated using the following equation: E = 2.5 lb per 1000 gallons x annual white wine production (in 1000 gallons) + 6.2 lb per 1000 gallons x annual red wine production (in 1000 gallons). [District Rule 2201]
- Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201]
- The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201]

E. Compliance Assurance

1. Source Testing

Pursuant to District Policy APR 1705, source testing is not required to demonstrate compliance with Rule 2201.

2. Monitoring

No monitoring is required to demonstrate compliance with Rule 2201.

3. Recordkeeping

Recordkeeping is required to demonstrate compliance with the offsets, public notification and daily emission limit requirements of Rule 2201. Recordkeeping is also required for winery tanks pursuant to District Rule 4694, *Wine Fermentation and Storage Tanks*. For the proposed wine fermentation and storage tanks, the following conditions will be placed on the permits in addition to the recordkeeping requirements listed under the DEL section above:

- When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201]
- When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]
- For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]
- The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694]
- Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
- All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694]

4. Reporting

No reporting is required to demonstrate compliance with Rule 2201.

F. Ambient Air Quality Analysis (AAQA)

District Rule 2201, Section 4.15.1 requires that an ambient air quality analysis (AAQA) be conducted for the purpose of determining whether a new or modified Stationary Source will cause or make worse a violation of an air quality standard. However, since this project

involves only VOC and no ambient air quality standard exists for VOC, an AAQA is not required for this project.

G. Compliance Certification

District Rule 2201, Section 4.15.2 requires the owner of a new Major Source or a source undergoing a Federal Major Modification to demonstrate to the satisfaction of the District that all other Major Sources owned by such person and operating in California are in compliance or are on a schedule for compliance with all applicable emission limitations and standards. As discussed in Sections VIII-Rule 2201-C.8, this source is undergoing a Federal Major Modification, therefore this requirement is applicable. Included in Appendix E is Delicato's compliance certification.

H. Alternative Siting Analysis

Section 4.15.1 of this rule requires sources for which an analysis of alternative sites, sizes, and production processes is required under Section 173 of the Federal Clean Air Act, the applicant shall prepare an analysis functionally equivalent to the requirements of Division 13, Section 21000 et. seq. of the Public Resources Code.

This proposed project will be installed at an existing winery with permits (PTOs and ATCs) for 685 wine storage tanks (55,067,839 gallons) with 677 of those tanks permitted as storage and fermentation (54,399,839 gallons), located in a rural area of San Joaquin County. The existing facility is vertically integrated to receive bulk truck shipments of grapes, crush and press the grapes, ferment the juice to wine, and perform post fermentation processing to produce finished wine. To support these various operations the facility features a large amount of support equipment, services and structures such as raw material receiving stations, crushers, pumps and piping, filtering and refrigeration units, electric and natural gas utilities, warehouses, laboratories, shipping facilities and administration buildings.

The applicant proposes to install 128 new wine storage and fermentation tanks (10,384,000 gallons). The existing plant infrastructure and processing equipment including the crushing and pressing equipment are adequately sized to support operation of the proposed post project tank population. Installation of the project at an alternate site would not be practical or feasible based on:

- Since wine tanks operate synergistically in post-fermentation processing and blending, the potential production capacity of the new tanks could not be fully met by installing the new tanks at an alternate location.

- Use of an alternate project site would require installation of a complete new plant infrastructure and supporting processes and equipment to support the independent operation, thus duplicating the infrastructure already present at the existing plant. Construction of the project at an alternate site would be expected to produce a significantly greater environmental impact due to both 1) a much larger initial construction project and 2) incrementally larger on-going emissions and other impacts due to operation of redundant infrastructure and support systems as well as emissions

associated with product transportation required to achieve some degree of integration with the existing facility.

Rule 2410 Prevention of Significant Deterioration

The prevention of significant deterioration (PSD) program is a construction permitting program for new major stationary sources and major modifications to existing major stationary sources located in areas classified as attainment or in areas that are unclassifiable for any criteria air pollutant.

As demonstrated above, this project is not subject to the requirements of Rule 2410 due to a significant emission increase and no further discussion is required.

Rule 2520 Federally Mandated Operating Permits

This facility is subject to this Rule, and has received their Title V Operating Permit. Section 3.29 defines a significant permit modification as a "permit amendment that does not qualify as a minor permit modification or administrative amendment."

Section 3.20.5 states that a minor permit modification is a permit modification that is not a federal major modification, as defined in Rule 2201[(1)]. As discussed above, this project triggers a federal major modification. As a result, the proposed project constitutes a Significant Modification to the Title V Permit pursuant to Section 3.29.

As discussed above, the District will not issue these ATCs with a Certificate of Conformity (COC). Therefore, the facility must apply to modify their Title V permit with a Significant Modification, prior to operating with the proposed modifications. Continued compliance with this rule is expected. The following condition will be included on each ATC and will assure compliance with the requirements of Rule 2520:

- The permittee shall not implement the changes authorized in this Authority to Construct permit until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3]

Rule 4001 New Source Performance Standards (NSPS)

This rule incorporates NSPS from Part 60, Chapter 1, Title 40, Code of Federal Regulations (CFR); and applies to all new sources of air pollution and modifications of existing sources of air pollution listed in 40 CFR Part 60. However, no subparts of 40 CFR Part 60 apply to wine fermentation/storage tank operations.

[(1)] District Rule 2520, Section 3.20.5 actually states that a project shall not constitute a Title I modification, as defined in Rule 2201. In a previous version of Rule 2201, the term Title I modification was replaced with Federal Major Modification. However, at that time, the terminology in Rule 2520 was not updated to reflect the new Rule 2201 terms. Therefore, even though Rule 2520 references that a project triggering a Title I modification does not qualify as a Title V minor modification, it will be replaced with the term Federal Major Modification for the purposes of this project.

Rule 4002 National Emission Standards for Hazardous Air Pollutants (NESHAPs)

This rule incorporates NESHAPs from Part 61, Chapter I, Subchapter C, Title 40, CFR and the NESHAPs from Part 63, Chapter I, Subchapter C, Title 40, CFR; and applies to all sources of hazardous air pollution listed in 40 CFR Part 61 or 40 CFR Part 63. However, no subparts of 40 CFR Part 61 or 40 CFR Part 63 apply to wine fermentation/storage tank operations.

Rule 4102 Nuisance

Rule 4102 states that no air contaminant shall be released into the atmosphere which causes a public nuisance. Public nuisance conditions are not expected as a result of the proposed operations provided the equipment is well maintained. Therefore, the following condition will be listed on each permit to ensure compliance:

- {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

California Health & Safety Code 41700 (Health Risk Assessment)

District Policy APR 1905 – Risk Management Policy for Permitting New and Modified Sources specifies that for an increase in emissions associated with a proposed new source or modification, the District perform an analysis to determine the possible impact to the nearest resident or worksite.

Ethanol is not a HAP as defined by Section 44321 of the California Health and Safety Code. Therefore, there are no increases in HAP emissions associated with any emission units in this project, therefore a health risk assessment is not necessary and no further risk analysis is required.

Rule 4694 Wine Fermentation and Storage Tanks

The purpose of this rule is to reduce emissions of volatile organic compounds (VOC) from the fermentation and bulk storage of wine, or achieve equivalent reductions from alternative emission sources. This rule is applicable to all facilities with fermentation emissions in excess of 10 tons-VOC/year. The storage tank provisions of this rule apply to all tanks with capacity in excess of 5,000 gallons.

Section 5.1 requires the winery operator achieve Required Annual Emissions Reductions (RAER) equal to at least 35% of the winery's Baseline Fermentation Emissions (BFE). Per the definition of RAER in Section 3.25 of the Rule, the RAER may be achieved by any combination of Fermentation Emission Reductions (FER), Certified Emission Reductions (CER) or District Obtained Emission Reductions (DOER) as established in the facility's District-approved Rule 4694 Compliance Plan, due every three years on December 1st beginning in 2006. The facility has submitted the required plan to the District and is currently satisfying the required emission reductions in the form of Certified Emission Reductions.

The following condition listed on the facility-wide permit ensures compliance:

- A Three-Year Compliance Plan that demonstrates compliance with the requirements of Section 5.1 of District Rule 4694 (12/15/05) for each year of the applicable compliance period shall be submitted to the District by no later than December 1, 2006, and every three years thereafter on or before December 1. [District Rule 4694]

Section 5.2 places specific restrictions on wine storage tanks with 5,000 gallons or more in capacity when such tanks are not constructed of wood or concrete. Section 5.2.1 requires these tanks to be equipped and operated with a pressure-vacuum relief valve meeting all of the following requirements:

- The pressure-vacuum relief valve shall operate within 10% of the maximum allowable working pressure of the tank,
- The pressure-vacuum relief valve shall operate in accordance with the manufacturer's instructions, and
- The pressure-vacuum relief valve shall be permanently labeled with the operating pressure settings.
- The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21.

The following conditions will be listed on the permits for stainless steel tanks ≥ 5,000 gallons in capacity and used for storage to ensure compliance with the requirements of Section 5.2.1:

- When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694]

- When used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694]

Section 5.2.2 requires that the temperature of the stored wine be maintained at or below 75° F. The following condition will be placed on the permits for stainless steel tanks ≥ 5,000 gallons in capacity and used for storage to ensure compliance with the requirements of Section 5.2.2:

- When used for wine storage, the temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694]

Every three years, Section 6.1 and 6.2 require the facility to submit a Three-Year Compliance Plan and a Three-Year Compliance Plan Verification respectively. Section 6.3 requires that an

Annual Compliance Plan Demonstration be submitted to the District no later than February 1 of each year to show compliance with the applicable requirements of the Rule. Section 6.4.3 requires that all monitoring be performed for any Certified Emission Reductions as identified in the facility's Three-Year Compliance Plan and that the records of all monitoring be maintained.

The following conditions listed on the facility-wide permit ensure compliance:

- A Three-Year Compliance Plan that demonstrates compliance with the requirements of Section 5.1 of District Rule 4694 (12/15/05) for each year of the applicable compliance period shall be submitted to the District by no later than December 1, 2006, and every three years thereafter on or before December 1. [District Rule 4694]
- A Three-Year Compliance Plan Verification that demonstrates that the Three-Year Compliance Plan elements are in effect shall be submitted to the District by no later than July 1, 2007, and every three years thereafter on or before July 1. [District Rule 4694, 6.2]
- An Annual Compliance Plan Demonstration that shows compliance with the applicable requirements of this rule shall be submitted to the District by no later than February 1, 2008, and every year thereafter on or before February 1. [District Rule 4694]
- Operators using CER to mitigate fermentation emissions shall perform all monitoring and recordkeeping, as established in their approved Three-Year Compliance Plan, and shall maintain all records necessary to demonstrate compliance. [District Rule 4694]

Section 6.4.1 requires that records be kept for each fermentation batch. The following condition will be listed on the permits for each fermentation tank to ensure compliance:

- For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694]

Section 6.4.2 requires that weekly records be kept of wine volume and temperature in each storage tank. The following conditions will be listed on the permit for each storage tank to ensure compliance with the requirements of Section 6.4.2:

- When used for wine storage, the operator shall determine and record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694]

Section 6.4.3 requires that all monitoring be performed for any Certified Emission Reductions as identified in the facility's Three-Year Compliance Plan and that the records of all monitoring be maintained. The following condition listed on the facility-wide permit ensures compliance:

- Operators using CER to mitigate fermentation emissions shall perform all monitoring and recordkeeping, as established in their approved Three-Year Compliance Plan, and shall maintain all records necessary to demonstrate compliance. [District Rule 4694]

Section 6.4 requires that records required by this rule be maintained, retained on-site for a minimum of five years, and made available to the APCO upon request. The following conditions will be listed on all permits to ensure compliance:

- All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694]

California Health & Safety Code 42301.6 (School Notice)

The District has verified that this site is not located within 1,000 feet of a school. Therefore, pursuant to California Health and Safety Code 42301.6, a school notice is not required.

California Environmental Quality ACT (CEQA)

The California Environmental Quality Act (CEQA) requires each public agency to adopt objectives, criteria, and specific procedures consistent with CEQA Statutes and the CEQA Guidelines for administering its responsibilities under CEQA, including the orderly evaluation of projects and preparation of environmental documents. The San Joaquin Valley Unified Air Pollution Control District (District) adopted its *Environmental Review Guidelines* (ERG) in 2000. The basic purposes of CEQA are to:

- Inform governmental decision-makers and the public about the potential, significant environmental effects of proposed activities.
- Identify the ways that environmental damage can be avoided or significantly reduced.
- Prevent significant, avoidable damage to the environment by requiring changes in projects through the use of alternatives or mitigation measures when the governmental agency finds the changes to be feasible.
- Disclose to the public the reasons why a governmental agency approved the project in the manner the agency chose if significant environmental effects are involved.

The County of San Joaquin (County) is the public agency having principal responsibility for approving the project. As such, the County served as the Lead Agency (CCR §15367). In approving the project, the Lead Agency prepared and adopted a Negative Declaration. The Lead agency filed a Notice of Determination, stating that the environmental document was adopted pursuant to the provisions of CEQA and concluding that the project would not have a significant effect on the environment.

The District is a Responsible Agency for the project because of its discretionary approval power over the project via its Permits Rule (Rule 2010) and New Source Review Rule (Rule 2201), (CCR §15381). As a Responsible Agency the District complies with CEQA by considering the environmental document prepared by the Lead Agency, and by reaching its own conclusion on whether and how to approve the project (CCR §15096).

The District has considered the Lead Agency's environmental document and finds that it adequately characterizes the project's potential impact on air quality. In addition, all feasible and cost-effective control measures to reduce potential impacts on air quality resulting from project related stationary source emissions have been applied to the project as part of

BACT. Furthermore, the District has conducted an engineering evaluation of the project, this document, which demonstrates that Stationary Source emissions from the project would be reduced. Thus, the District finds that through a combination of project design elements, compliance with applicable District rules and regulations, and compliance with District air permit conditions, project specific stationary source emissions would be reduced to lessen the impacts on air quality. The District does not have authority over any of the other project impacts and has, therefore, determined that no additional findings are required (CEQA Guidelines §15096(h)).

Indemnification Agreement/Letter of Credit Determination

According to District Policy APR 2010 (CEQA Implementation Policy), when the District is the Lead or Responsible Agency for CEQA purposes, an indemnification agreement and/or letter of credit may be required. The decision to require an indemnity agreement and/or letter of credit are based on a case-by-case analysis of a particular project's potential for litigation risk, which in turn may be based on a project's potential to generate public concern, its potential for significant impacts, and the project proponent's ability to pay for the costs of litigation without a letter of credit, among other factors.

The proposed project is for an operation of public concern (fermentation tanks) in the Valley and triggers Best Available Control Technology (BACT). Therefore, the District determined that an Indemnification Agreement and Letter of Credit for the ATC project is required.

IX. Recommendation

Compliance with all applicable rules and regulations is expected. Pending a successful NSR Public Noticing period, issue Authorities to Construct N-266-822-0 through -949-0 subject to the permit conditions on the attached draft Authorities to Construct in Appendix D.

X. Billing Information

Annual Permit Fees			
ATC	Fee Schedule	Fee Description	Annual Fee
N-266-822-0 thru -837-0	3020-05-E	154,000 gallons	$258.00
N-266-838-0 thru -865-0	3020-05-E	103,000 gallons	$258.00
N-266-866-0 thru -915-0	3020-05-D	60,000 gallons	$194.00
N-266-916-0 thru -929-0	3020-05-D	74,000 gallons	$194.00
N-266-930-0 thru -949-0	3020-05-D	50,000 gallons	$194.00

XI. Appendices

A: TANKS 4.0d Runs and Summary
B: BACT Guideline 5.4.14 and Top Down BACT Analyses
C: BACT Guideline 5.4.13 and Top Down BACT Analyses
D: Achieved-In-Practice Analysis
E: Compliance Certification
F: Revised Draft ATCs
G: FYI-114
H: Public Comments and District Response
I: EPA Comments and District Response

				Output from Tank 4.0 total emissions no speciation	
Tank ID	% by Volume Alcohol	Average Ya	AMW Average	Total Pound of Emissions	Alcohol Emissions in pounds (Max Annual)
T-1 through T-16	20.0%	0.3879	28.88	755	467
T-17 through T-44	20.0%	0.3879	28.88	504	312
T-45 through T-94	20.0%	0.3879	28.88	294	182
T-95 through T-108	20.0%	0.3879	28.88	363	224
T-109 through T-128	20.0%	0.3879	28.88	299	185
				Total Pounds	32,144

				Output from Tank 4.0 total emissions no speciation	
Tank ID	% by Volume Alcohol	Average Ya	AMW Average	Total Pound of Emissions	Alcohol Emissions in pounds (Max Daily)
T-1 through T-16	20.0%	0.3879	28.88	3787.70	75.5
T-17 through T-44	20.0%	0.3879	28.88	2533.30	55.9
T-45 through T-94	20.0%	0.3879	28.88	1475.70	32.6
T-95 through T-108	20.0%	0.3879	28.88	1820.00	40.2
T-109 through T-128	20.0%	0.3879	28.88	1498.20	33.1
				Total Pounds	5,627.1

TANKS 4.0.9d
Emissions Report - Detail Format
Tank Indentification and Physical Characteristics

Identification

User Identification:	N-266-822-0 (T-1) Daily
City:	
State:	
Company:	
Type of Tank:	Vertical Fixed Roof Tank
Description:	

Tank Dimensions

Shell Height (ft):	40.00
Diameter (ft):	25.00
Liquid Height (ft) :	40.00
Avg. Liquid Height (ft):	39.00
Volume (gallons):	154,000.00
Turnovers:	121.00
Net Throughput(gal/yr):	18,634,000.00
Is Tank Heated (y/n):	Y

Paint Characteristics

Shell Color/Shade:	White/White
Shell Condition	Good
Roof Color/Shade:	White/White
Roof Condition:	Good

Roof Characteristics

Type:	Cone
Height (ft)	1.00
Slope (ft/ft) (Cone Roof)	0.08

Breather Vent Settings

Vacuum Settings (psig):	0.00
Pressure Settings (psig)	0.00

Meterological Data used in Emissions Calculations: Stockton, California (Avg Atmospheric Pressure = 14.72 psia)

TANKS 4.0.9d
Emissions Report - Detail Format
Liquid Contents of Storage Tank

N-266-822-0 (T-1) Daily - Vertical Fixed Roof Tank

Mixture/Component	Month	Daily Liquid Surf. Temperature (deg F) Avg.	Min.	Max.	Liquid Bulk Temp (deg F)	Vapor Pressure (psia) Avg.	Min.	Max.	Vapor Mol. Weight	Liquid Mass Fract.	Vapor Mass Fract.	Mol. Weight	Basis for Vapor Pressure Calculations
Wine 20.0 % Vol Alcohol	Jul	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304

TANKS 4.0.9d
Emissions Report - Detail Format
Detail Calculations (AP-42)

N-266-822-0 (T-1) Daily - Vertical Fixed Roof Tank

Month:	January	February	March	April	May	June	July	August	September	October	November	December
Standing Losses (lb):							0.0000					
Vapor Space Volume (cu ft):							654.4985					
Vapor Density (lb/cu ft):							0.0036					
Vapor Space Expansion Factor:							0.0000					
Vented Vapor Saturation Factor:							0.9520					
Tank Vapor Space Volume:												
Vapor Space Volume (cu ft):							654.4985					
Tank Diameter (ft):							25.0000					
Vapor Space Outage (ft):							1.3333					
Tank Shell Height (ft):							40.0000					
Average Liquid Height (ft):							39.0000					
Roof Outage (ft):							0.3333					
Roof Outage (Cone Roof)												
Roof Outage (ft):							0.3333					
Roof Height (ft):							1.0000					
Roof Slope (ft/ft):							0.0800					
Shell Radius (ft):							12.5000					
Vapor Density												
Vapor Density (lb/cu ft):							0.0036					
Vapor Molecular Weight (lb/lb-mole):							28.8820					
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):							0.7129					
Daily Avg. Liquid Surface Temp. (deg. R):							536.9700					
Daily Average Ambient Temp. (deg. F):							77.6500					
Ideal Gas Constant R (psia cuft / (lb-mol-deg R)):							10.731					
Liquid Bulk Temperature (deg. R):							536.9700					
Tank Paint Solar Absorptance (Shell):							0.1700					
Tank Paint Solar Absorptance (Roof):							0.1700					
Daily Total Solar Insulation Factor (Btu/sqft day):							2,688.0000					
Vapor Space Expansion Factor												
Vapor Space Expansion Factor:							0.0000					
Daily Vapor Temperature Range (deg. R):							0.0000					
Daily Vapor Pressure Range (psia):							0.0000					
Breather Vent Press. Setting Range(psia):							0.0000					
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):							0.7129					
Vapor Pressure at Daily Minimum Liquid Surface Temperature (psia):							0.7129					
Vapor Pressure at Daily Maximum Liquid Surface Temperature (psia):							0.7129					
Daily Avg. Liquid Surface Temp. (deg R):							536.9700					
Daily Min. Liquid Surface Temp. (deg R):							536.9700					
Daily Max. Liquid Surface Temp. (deg R):							536.9700					
Daily Ambient Temp. Range (deg. R):							33.5000					
Vented Vapor Saturation Factor												
Vented Vapor Saturation Factor:							0.9520					
Vapor Pressure at Daily Average Liquid: Surface Temperature (psia):							0.7129					
Vapor Space Outage (ft):							1.3333					
Working Losses (lb):							3,787.6530					

Vapor Molecular Weight (lb/lb-mole):	28.8820
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):	0.7129
Net Throughput (gal/mo.):	18,634,000.0000
Annual Turnovers:	121.0000
Turnover Factor:	0.4146
Maximum Liquid Volume (gal):	154,000.0000
Maximum Liquid Height (ft):	40.0000
Tank Diameter (ft):	25.0000
Working Loss Product Factor:	1.0000

Total Losses (lb):	3,787.6530

TANKS 4.0.9d
Emissions Report - Detail Format
Individual Tank Emission Totals

Emissions Report for: July

N-266-822-0 (T-1) Daily - Vertical Fixed Roof Tank

	Losses(lbs)		
Components	Working Loss	Breathing Loss	Total Emissions
Wine 20.0 % Vol Alcohol	3,787.65	0.00	3,787.65

TANKS 4.0.9d
Emissions Report - Detail Format
Tank Indentification and Physical Characteristics

Identification		
User Identification:	N-266-838-0 (T-17) Daily	
City:		
State:		
Company:		
Type of Tank:	Vertical Fixed Roof Tank	
Description:		
Tank Dimensions		
Shell Height (ft):		40.00
Diameter (ft):		21.00
Liquid Height (ft) :		40.00
Avg. Liquid Height (ft):		39.00
Volume (gallons):		103,000.00
Turnovers:		121.00
Net Throughput(gal/yr):		12,463,000.00
Is Tank Heated (y/n):	Y	
Paint Characteristics		
Shell Color/Shade:	White/White	
Shell Condition	Good	
Roof Color/Shade:	White/White	
Roof Condition:	Good	
Roof Characteristics		
Type:	Cone	
Height (ft)		1.00
Slope (ft/ft) (Cone Roof)		0.10
Breather Vent Settings		
Vacuum Settings (psig):		0.00
Pressure Settings (psig)		0.00

Meterological Data used in Emissions Calculations: Stockton, California (Avg Atmospheric Pressure = 14.72 psia)

TANKS 4.0.9d
Emissions Report - Detail Format
Liquid Contents of Storage Tank

N-266-838-0 (T-17) Daily - Vertical Fixed Roof Tank

Mixture/Component	Month	Daily Liquid Surf. Temperature (deg F) Avg.	Min.	Max.	Liquid Bulk Temp (deg F)	Vapor Pressure (psia) Avg.	Min.	Max.	Vapor Mol. Weight	Liquid Mass Fract.	Vapor Mass Fract.	Mol. Weight	Basis for Vapor Pressure Calculations
Wine 20.0 % Vol Alcohol	Jul	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304

TANKS 4.0.9d
Emissions Report - Detail Format
Detail Calculations (AP-42)

N-266-838-0 (T-17) Daily - Vertical Fixed Roof Tank

Month:	January	February	March	April	May	June	July	August	September	October	November	December
Standing Losses (lb):							0.0000					
Vapor Space Volume (cu ft):							461.8141					
Vapor Density (lb/cu ft):							0.0036					
Vapor Space Expansion Factor:							0.0000					
Vented Vapor Saturation Factor:							0.9520					
Tank Vapor Space Volume:												
Vapor Space Volume (cu ft):							461.8141					
Tank Diameter (ft):							21.0000					
Vapor Space Outage (ft):							1.3333					
Tank Shell Height (ft):							40.0000					
Average Liquid Height (ft):							39.0000					
Roof Outage (ft):							0.3333					
Roof Outage (Cone Roof)												
Roof Outage (ft):							0.3333					
Roof Height (ft):							1.0000					
Roof Slope (ft/ft):							0.1000					
Shell Radius (ft):							10.5000					
Vapor Density												
Vapor Density (lb/cu ft):							0.0036					
Vapor Molecular Weight (lb/lb-mole):							28.8820					
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):							0.7129					
Daily Avg. Liquid Surface Temp. (deg. R):							536.9700					
Daily Average Ambient Temp. (deg. F):							77.6500					
Ideal Gas Constant R (psia cuft / (lb-mol-deg R)):							10.731					
Liquid Bulk Temperature (deg. R):							536.9700					
Tank Paint Solar Absorptance (Shell):							0.1700					
Tank Paint Solar Absorptance (Roof):							0.1700					
Daily Total Solar Insulation Factor (Btu/sqft day):							2,688.0000					
Vapor Space Expansion Factor												
Vapor Space Expansion Factor:							0.0000					
Daily Vapor Temperature Range (deg. R):							0.0000					
Daily Vapor Pressure Range (psia):							0.0000					
Breather Vent Press. Setting Range(psia):							0.0000					
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):							0.7129					
Vapor Pressure at Daily Minimum Liquid Surface Temperature (psia):							0.7129					
Vapor Pressure at Daily Maximum Liquid Surface Temperature (psia):							0.7129					
Daily Avg. Liquid Surface Temp. (deg R):							536.9700					
Daily Min. Liquid Surface Temp. (deg R):							536.9700					
Daily Max. Liquid Surface Temp. (deg R):							536.9700					
Daily Ambient Temp. Range (deg. R):							33.5000					
Vented Vapor Saturation Factor												
Vented Vapor Saturation Factor:							0.9520					
Vapor Pressure at Daily Average Liquid: Surface Temperature (psia):							0.7129					
Vapor Space Outage (ft):							1.3333					
Working Losses (lb):							2,533.3004					

Vapor Molecular Weight (lb/lb-mole):	28.8820
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):	0.7129
Net Throughput (gal/mo.):	12,463,000.0000
Annual Turnovers:	121.0000
Turnover Factor:	0.4146
Maximum Liquid Volume (gal):	103,000.0000
Maximum Liquid Height (ft):	40.0000
Tank Diameter (ft):	21.0000
Working Loss Product Factor:	1.0000

Total Losses (lb):	2,533.3004

TANKS 4.0.9d
Emissions Report - Detail Format
Individual Tank Emission Totals

Emissions Report for: July

N-266-838-0 (T-17) Daily - Vertical Fixed Roof Tank

	Losses(lbs)		
Components	Working Loss	Breathing Loss	Total Emissions
Wine 20.0 % Vol Alcohol	2,533.30	0.00	2,533.30

TANKS 4.0.9d
Emissions Report - Detail Format
Tank Indentification and Physical Characteristics

Identification

User Identification:	N-266-866-0 (T-45) Daily
City:	
State:	
Company:	
Type of Tank:	Vertical Fixed Roof Tank
Description:	

Tank Dimensions

Shell Height (ft):	40.00
Diameter (ft):	16.00
Liquid Height (ft) :	40.00
Avg. Liquid Height (ft):	39.00
Volume (gallons):	60,000.00
Turnovers:	121.00
Net Throughput(gal/yr):	7,260,000.00
Is Tank Heated (y/n):	Y

Paint Characteristics

Shell Color/Shade:	White/White
Shell Condition	Good
Roof Color/Shade:	White/White
Roof Condition:	Good

Roof Characteristics

Type:	Cone
Height (ft)	1.00
Slope (ft/ft) (Cone Roof)	0.12

Breather Vent Settings

Vacuum Settings (psig):	0.00
Pressure Settings (psig)	0.00

Meterological Data used in Emissions Calculations: Stockton, California (Avg Atmospheric Pressure = 14.72 psia)

TANKS 4.0.9d
Emissions Report - Detail Format
Liquid Contents of Storage Tank

N-266-866-0 (T-45) Daily - Vertical Fixed Roof Tank

Mixture/Component	Month	Daily Liquid Surf. Temperature (deg F) Avg.	Min.	Max.	Liquid Bulk Temp (deg F)	Vapor Pressure (psia) Avg.	Min.	Max.	Vapor Mol. Weight.	Liquid Mass Fract.	Vapor Mass Fract.	Mol. Weight	Basis for Vapor Pressure Calculations
Wine 20.0 % Vol Alcohol	Jul	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304

TANKS 4.0.9d
Emissions Report - Detail Format
Detail Calculations (AP-42)

N-266-866-0 (T-45) Daily - Vertical Fixed Roof Tank

Month:	January	February	March	April	May	June	July	August	September	October	November	December
Standing Losses (lb):							0.0000					
Vapor Space Volume (cu ft):							268.0826					
Vapor Density (lb/cu ft):							0.0036					
Vapor Space Expansion Factor:							0.0000					
Vented Vapor Saturation Factor:							0.9520					
Tank Vapor Space Volume:												
Vapor Space Volume (cu ft):							268.0826					
Tank Diameter (ft):							16.0000					
Vapor Space Outage (ft):							1.3333					
Tank Shell Height (ft):							40.0000					
Average Liquid Height (ft):							39.0000					
Roof Outage (ft):							0.3333					
Roof Outage (Cone Roof)												
Roof Outage (ft):							0.3333					
Roof Height (ft):							1.0000					
Roof Slope (ft/ft):							0.1200					
Shell Radius (ft):							8.0000					
Vapor Density												
Vapor Density (lb/cu ft):							0.0036					
Vapor Molecular Weight (lb/lb-mole):							28.8820					
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):							0.7129					
Daily Avg. Liquid Surface Temp. (deg. R):							536.9700					
Daily Average Ambient Temp. (deg. F):							77.6500					
Ideal Gas Constant R (psia cuft / (lb-mol-deg R)):							10.731					
Liquid Bulk Temperature (deg. R):							536.9700					
Tank Paint Solar Absorptance (Shell):							0.1700					
Tank Paint Solar Absorptance (Roof):							0.1700					
Daily Total Solar Insulation Factor (Btu/sqft day):							2,688.0000					
Vapor Space Expansion Factor												
Vapor Space Expansion Factor:							0.0000					
Daily Vapor Temperature Range (deg. R):							0.0000					
Daily Vapor Pressure Range (psia):							0.0000					
Breather Vent Press. Setting Range(psia):							0.0000					
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):							0.7129					
Vapor Pressure at Daily Minimum Liquid Surface Temperature (psia):							0.7129					
Vapor Pressure at Daily Maximum Liquid Surface Temperature (psia):							0.7129					
Daily Avg. Liquid Surface Temp. (deg R):							536.9700					
Daily Min. Liquid Surface Temp. (deg R):							536.9700					
Daily Max. Liquid Surface Temp. (deg R):							536.9700					
Daily Ambient Temp. Range (deg. R):							33.5000					
Vented Vapor Saturation Factor												
Vented Vapor Saturation Factor:							0.9520					
Vapor Pressure at Daily Average Liquid: Surface Temperature (psia):							0.7129					
Vapor Space Outage (ft):							1.3333					
Working Losses (lb):							1,475.7090					

Vapor Molecular Weight (lb/lb-mole):	28.8820
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):	0.7129
Net Throughput (gal/mo.):	7,260,000.0000
Annual Turnovers:	121.0000
Turnover Factor:	0.4146
Maximum Liquid Volume (gal):	60,000.0000
Maximum Liquid Height (ft):	40.0000
Tank Diameter (ft):	16.0000
Working Loss Product Factor:	1.0000
Total Losses (lb):	1,475.7090

TANKS 4.0.9d
Emissions Report - Detail Format
Individual Tank Emission Totals

Emissions Report for: July

N-266-866-0 (T-45) Daily - Vertical Fixed Roof Tank

	Losses(lbs)		
Components	Working Loss	Breathing Loss	Total Emissions
Wine 20.0 % Vol Alcohol	1,475.71	0.00	1,475.71

TANKS 4.0.9d
Emissions Report - Detail Format
Tank Indentification and Physical Characteristics

Identification		
User Identification:	N-266-916-0 (T-95) Daily2	
City:		
State:		
Company:		
Type of Tank:	Vertical Fixed Roof Tank	
Description:		
Tank Dimensions		
Shell Height (ft):		28.00
Diameter (ft):		21.00
Liquid Height (ft) :		28.00
Avg. Liquid Height (ft):		27.00
Volume (gallons):		74,000.00
Turnovers:		121.00
Net Throughput(gal/yr):		8,954,000.00
Is Tank Heated (y/n):	Y	
Paint Characteristics		
Shell Color/Shade:	White/White	
Shell Condition	Good	
Roof Color/Shade:	White/White	
Roof Condition:	Good	
Roof Characteristics		
Type:	Cone	
Height (ft)		1.00
Slope (ft/ft) (Cone Roof)		0.10
Breather Vent Settings		
Vacuum Settings (psig):		0.00
Pressure Settings (psig)		0.00

Meterological Data used in Emissions Calculations: Stockton, California (Avg Atmospheric Pressure = 14.72 psia)

TANKS 4.0.9d
Emissions Report - Detail Format
Liquid Contents of Storage Tank

N-266-916-0 (T-95) Daily2 - Vertical Fixed Roof Tank

Mixture/Component	Month	Daily Liquid Surf. Temperature (deg F) Avg.	Min.	Max.	Liquid Bulk Temp (deg F)	Vapor Pressure (psia) Avg.	Min.	Max.	Vapor Mol. Weight.	Liquid Mass Fract.	Vapor Mass Fract.	Mol. Weight	Basis for Vapor Pressure Calculations
Wine 20.0 % Vol Alcohol	Jul	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304

TANKS 4.0.9d
Emissions Report - Detail Format
Detail Calculations (AP-42)

N-266-916-0 (T-95) Daily2 - Vertical Fixed Roof Tank

Month:	January	February	March	April	May	June	July	August	September	October	November	December
Standing Losses (lb):							0.0000					
Vapor Space Volume (cu ft):							461.8141					
Vapor Density (lb/cu ft):							0.0036					
Vapor Space Expansion Factor:							0.0000					
Vented Vapor Saturation Factor:							0.9520					
Tank Vapor Space Volume:												
Vapor Space Volume (cu ft):							461.8141					
Tank Diameter (ft):							21.0000					
Vapor Space Outage (ft):							1.3333					
Tank Shell Height (ft):							28.0000					
Average Liquid Height (ft):							27.0000					
Roof Outage (ft):							0.3333					
Roof Outage (Cone Roof)												
Roof Outage (ft):							0.3333					
Roof Height (ft):							1.0000					
Roof Slope (ft/ft):							0.1000					
Shell Radius (ft):							10.5000					
Vapor Density												
Vapor Density (lb/cu ft):							0.0036					
Vapor Molecular Weight (lb/lb-mole):							28.8820					
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):							0.7129					
Daily Avg. Liquid Surface Temp. (deg. R):							536.9700					
Daily Average Ambient Temp. (deg. F):							77.6500					
Ideal Gas Constant R (psia cuft / (lb-mol-deg R)):							10.731					
Liquid Bulk Temperature (deg. R):							536.9700					
Tank Paint Solar Absorptance (Shell):							0.1700					
Tank Paint Solar Absorptance (Roof):							0.1700					
Daily Total Solar Insulation Factor (Btu/sqft day):							2,688.0000					
Vapor Space Expansion Factor												
Vapor Space Expansion Factor:							0.0000					
Daily Vapor Temperature Range (deg. R):							0.0000					
Daily Vapor Pressure Range (psia):							0.0000					
Breather Vent Press. Setting Range(psia):							0.0000					
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):							0.7129					
Vapor Pressure at Daily Minimum Liquid Surface Temperature (psia):							0.7129					
Vapor Pressure at Daily Maximum Liquid Surface Temperature (psia):							0.7129					
Daily Avg. Liquid Surface Temp. (deg R):							536.9700					
Daily Min. Liquid Surface Temp. (deg R):							536.9700					
Daily Max. Liquid Surface Temp. (deg R):							536.9700					
Daily Ambient Temp. Range (deg. R):							33.5000					
Vented Vapor Saturation Factor												
Vented Vapor Saturation Factor:							0.9520					
Vapor Pressure at Daily Average Liquid: Surface Temperature (psia):							0.7129					
Vapor Space Outage (ft):							1.3333					
Working Losses (lb):							1,820.0411					

Vapor Molecular Weight (lb/lb-mole):	28.8820
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):	0.7129
Net Throughput (gal/mo.):	8,954,000.0000
Annual Turnovers:	121.0000
Turnover Factor:	0.4146
Maximum Liquid Volume (gal):	74,000.0000
Maximum Liquid Height (ft):	28.0000
Tank Diameter (ft):	21.0000
Working Loss Product Factor:	1.0000
Total Losses (lb):	1,820.0411

TANKS 4.0.9d
Emissions Report - Detail Format
Individual Tank Emission Totals

Emissions Report for: July

N-266-916-0 (T-95) Daily2 - Vertical Fixed Roof Tank

	Losses(lbs)		
Components	Working Loss	Breathing Loss	Total Emissions
Wine 20.0 % Vol Alcohol	1,820.04	0.00	1,820.04

TANKS 4.0.9d
Emissions Report - Detail Format
Tank Indentification and Physical Characteristics

Identification

User Identification:	N-266-930-0 (T-109) Daily
City:	
State:	
Company:	
Type of Tank:	Vertical Fixed Roof Tank
Description:	

Tank Dimensions

Shell Height (ft):	32.00
Diameter (ft):	18.00
Liquid Height (ft) :	32.00
Avg. Liquid Height (ft):	31.00
Volume (gallons):	60,914.13
Turnovers:	121.00
Net Throughput(gal/yr):	7,370,610.08
Is Tank Heated (y/n):	Y

Paint Characteristics

Shell Color/Shade:	White/White
Shell Condition	Good
Roof Color/Shade:	White/White
Roof Condition:	Good

Roof Characteristics

Type:	Cone
Height (ft)	1.00
Slope (ft/ft) (Cone Roof)	0.11

Breather Vent Settings

Vacuum Settings (psig):	0.00
Pressure Settings (psig)	0.00

Meterological Data used in Emissions Calculations: Stockton, California (Avg Atmospheric Pressure = 14.72 psia)

TANKS 4.0.9d
Emissions Report - Detail Format
Liquid Contents of Storage Tank

N-266-930-0 (T-109) Daily - Vertical Fixed Roof Tank

Mixture/Component	Month	Daily Liquid Surf. Temperature (deg F) Avg.	Min.	Max.	Liquid Bulk Temp (deg F)	Vapor Pressure (psia) Avg.	Min.	Max.	Vapor Mol. Weight	Liquid Mass Fract.	Vapor Mass Fract.	Mol. Weight	Basis for Vapor Pressure Calculations
Wine 20.0 % Vol Alcohol	Jul	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304

TANKS 4.0.9d
Emissions Report - Detail Format
Detail Calculations (AP-42)

N-266-930-0 (T-109) Daily - Vertical Fixed Roof Tank

Month:	January	February	March	April	May	June	July	August	September	October	November	December
Standing Losses (lb):							0.0000					
Vapor Space Volume (cu ft):							339.2920					
Vapor Density (lb/cu ft):							0.0036					
Vapor Space Expansion Factor:							0.0000					
Vented Vapor Saturation Factor:							0.9520					
Tank Vapor Space Volume:												
Vapor Space Volume (cu ft):							339.2920					
Tank Diameter (ft):							18.0000					
Vapor Space Outage (ft):							1.3333					
Tank Shell Height (ft):							32.0000					
Average Liquid Height (ft):							31.0000					
Roof Outage (ft):							0.3333					
Roof Outage (Cone Roof)												
Roof Outage (ft):							0.3333					
Roof Height (ft):							1.0000					
Roof Slope (ft/ft):							0.1100					
Shell Radius (ft):							9.0000					
Vapor Density												
Vapor Density (lb/cu ft):							0.0036					
Vapor Molecular Weight (lb/lb-mole):							28.8820					
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):							0.7129					
Daily Avg. Liquid Surface Temp. (deg. R):							536.9700					
Daily Average Ambient Temp. (deg. F):							77.6500					
Ideal Gas Constant R (psia cuft / (lb-mol-deg R)):							10.731					
Liquid Bulk Temperature (deg. R):							536.9700					
Tank Paint Solar Absorptance (Shell):							0.1700					
Tank Paint Solar Absorptance (Roof):							0.1700					
Daily Total Solar Insulation Factor (Btu/sqft day):							2,688.0000					
Vapor Space Expansion Factor												
Vapor Space Expansion Factor:							0.0000					
Daily Vapor Temperature Range (deg. R):							0.0000					
Daily Vapor Pressure Range (psia):							0.0000					
Breather Vent Press. Setting Range(psia):							0.0000					
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):							0.7129					
Vapor Pressure at Daily Minimum Liquid Surface Temperature (psia):							0.7129					
Vapor Pressure at Daily Maximum Liquid Surface Temperature (psia):							0.7129					
Daily Avg. Liquid Surface Temp. (deg R):							536.9700					
Daily Min. Liquid Surface Temp. (deg R):							536.9700					
Daily Max. Liquid Surface Temp. (deg R):							536.9700					
Daily Ambient Temp. Range (deg. R):							33.5000					
Vented Vapor Saturation Factor												
Vented Vapor Saturation Factor:							0.9520					
Vapor Pressure at Daily Average Liquid: Surface Temperature (psia):							0.7129					
Vapor Space Outage (ft):							1.3333					
Working Losses (lb):							1,498.1922					

Vapor Molecular Weight (lb/lb-mole):	28.8820
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):	0.7129
Net Throughput (gal/mo.):	7,370,610.0750
Annual Turnovers:	121.0000
Turnover Factor:	0.4146
Maximum Liquid Volume (gal):	60,914.1329
Maximum Liquid Height (ft):	32.0000
Tank Diameter (ft):	18.0000
Working Loss Product Factor:	1.0000
Total Losses (lb):	1,498.1922

TANKS 4.0.9d
Emissions Report - Detail Format
Individual Tank Emission Totals

Emissions Report for: July

N-266-930-0 (T-109) Daily - Vertical Fixed Roof Tank

	Losses(lbs)		
Components	Working Loss	Breathing Loss	Total Emissions
Wine 20.0 % Vol Alcohol	1,498.19	0.00	1,498.19

TANKS 4.0.9d
Emissions Report - Detail Format
Total Emissions Summaries - All Tanks in Report

Emissions Report for: July

Tank Identification		Losses (lbs)
N-266-822-0 (T-1) Daily	Vertical Fixed Roof Tank	3,787.65
N-266-838-0 (T-17) Daily	Vertical Fixed Roof Tank	2,533.30
N-266-866-0 (T-45) Daily	Vertical Fixed Roof Tank	1,475.71
N-266-916-0 (T-95) Daily2	Vertical Fixed Roof Tank	1,820.04
N-266-930-0 (T-109) Daily	Vertical Fixed Roof Tank	1,498.19
Total Emissions for all Tanks:		11,114.90

TANKS 4.0.9d
Emissions Report - Detail Format
Tank Indentification and Physical Characteristics

Identification

User Identification:	N-266-822-0 (T-1) Annual
City:	
State:	
Company:	
Type of Tank:	Vertical Fixed Roof Tank
Description:	

Tank Dimensions

Shell Height (ft):	40.00
Diameter (ft):	25.00
Liquid Height (ft) :	40.00
Avg. Liquid Height (ft):	39.00
Volume (gallons):	154,000.00
Turnovers:	10.00
Net Throughput(gal/yr):	1,540,000.00
Is Tank Heated (y/n):	Y

Paint Characteristics

Shell Color/Shade:	White/White
Shell Condition	Good
Roof Color/Shade:	White/White
Roof Condition:	Good

Roof Characteristics

Type:	Cone
Height (ft)	1.00
Slope (ft/ft) (Cone Roof)	0.08

Breather Vent Settings

Vacuum Settings (psig):	0.00
Pressure Settings (psig)	0.00

Meterological Data used in Emissions Calculations: Stockton, California (Avg Atmospheric Pressure = 14.72 psia)

TANKS 4.0.9d
Emissions Report - Detail Format
Liquid Contents of Storage Tank

N-266-822-0 (T-1) Annual - Vertical Fixed Roof Tank

Mixture/Component	Month	Daily Liquid Surf. Temperature (deg F) Avg.	Min.	Max.	Liquid Bulk Temp (deg F)	Vapor Pressure (psia) Avg.	Min.	Max.	Vapor Mol. Weight.	Liquid Mass Fract.	Vapor Mass Fract.	Mol. Weight	Basis for Vapor Pressure Calculations
Wine 20.0 % Vol Alcohol	Jan	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Feb	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Mar	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Apr	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	May	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Jun	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Jul	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Aug	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Sep	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Oct	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Nov	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Dec	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304

TANKS 4.0.9d
Emissions Report - Detail Format
Detail Calculations (AP-42)

N-266-822-0 (T-1) Annual - Vertical Fixed Roof Tank

Month:	January	February	March	April	May	June	July	August	September	October	November	December
Standing Losses (lb):	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vapor Space Volume (cu ft):	654.4985	654.4985	654.4985	654.4985	654.4985	654.4985	654.4985	654.4985	654.4985	654.4985	654.4985	654.4985
Vapor Density (lb/cu ft):	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036
Vapor Space Expansion Factor:	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vented Vapor Saturation Factor:	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520
Tank Vapor Space Volume:												
Vapor Space Volume (cu ft):	654.4985	654.4985	654.4985	654.4985	654.4985	654.4985	654.4985	654.4985	654.4985	654.4985	654.4985	654.4985
Tank Diameter (ft):	25.0000	25.0000	25.0000	25.0000	25.0000	25.0000	25.0000	25.0000	25.0000	25.0000	25.0000	25.0000
Vapor Space Outage (ft):	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333
Tank Shell Height (ft):	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000
Average Liquid Height (ft):	39.0000	39.0000	39.0000	39.0000	39.0000	39.0000	39.0000	39.0000	39.0000	39.0000	39.0000	39.0000
Roof Outage (ft):	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333
Roof Outage (Cone Roof)												
Roof Outage (ft):	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333
Roof Height (ft):	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
Roof Slope (ft/ft):	0.0800	0.0800	0.0800	0.0800	0.0800	0.0800	0.0800	0.0800	0.0800	0.0800	0.0800	0.0800
Shell Radius (ft):	12.5000	12.5000	12.5000	12.5000	12.5000	12.5000	12.5000	12.5000	12.5000	12.5000	12.5000	12.5000
Vapor Density												
Vapor Density (lb/cu ft):	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036
Vapor Molecular Weight (lb/lb-mole):	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129
Daily Avg. Liquid Surface Temp. (deg. R):	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700
Daily Average Ambient Temp. (deg. F):	45.0000	50.5000	54.0500	59.3000	66.7000	73.3000	77.6500	76.8000	72.7000	64.5500	53.0500	44.9500
Ideal Gas Constant R (psia cuft / (lb-mol-deg R)):	10.731	10.731	10.731	10.731	10.731	10.731	10.731	10.731	10.731	10.731	10.731	10.731
Liquid Bulk Temperature (deg. R):	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700
Tank Paint Solar Absorptance (Shell):	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700
Tank Paint Solar Absorptance (Roof):	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700
Daily Total Solar Insulation Factor (Btu/sqft day):	597.0000	939.0000	1,458.0000	2,004.0000	2,435.0000	2,684.0000	2,688.0000	2,368.0000	1,907.0000	1,315.0000	782.0000	538.0000
Vapor Space Expansion Factor												
Vapor Space Expansion Factor:	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Daily Vapor Temperature Range (deg. R):	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Daily Vapor Pressure Range (psia):	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Breather Vent Press. Setting Range(psia):	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129
Vapor Pressure at Daily Minimum Liquid Surface Temperature (psia):	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129
Vapor Pressure at Daily Maximum Liquid Surface Temperature (psia):	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129
Daily Avg. Liquid Surface Temp. (deg R):	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700
Daily Min. Liquid Surface Temp. (deg R):	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700
Daily Max. Liquid Surface Temp. (deg R):	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700
Daily Ambient Temp. Range (deg. R):	16.0000	20.4000	22.9000	27.2000	29.8000	31.6000	33.5000	32.2000	30.4000	27.5000	20.7000	15.7000
Vented Vapor Saturation Factor												
Vented Vapor Saturation Factor:	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520
Vapor Pressure at Daily Average Liquid: Surface Temperature (psia):	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129
Vapor Space Outage (ft):	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333
Working Losses (lb):	62.9178	62.9178	62.9178	62.9178	62.9178	62.9178	62.9178	62.9178	62.9178	62.9178	62.9178	62.9178

Vapor Molecular Weight (lb/lb-mole):	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129
Net Throughput (gal/mo.):	128,333.3333	128,333.3333	128,333.3333	128,333.3333	128,333.3333	128,333.3333	128,333.3333	128,333.3333	128,333.3333	128,333.3333	128,333.3333	128,333.3333
Annual Turnovers:	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000
Turnover Factor:	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
Maximum Liquid Volume (gal):	154,000.0000	154,000.0000	154,000.0000	154,000.0000	154,000.0000	154,000.0000	154,000.0000	154,000.0000	154,000.0000	154,000.0000	154,000.0000	154,000.0000
Maximum Liquid Height (ft):	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000
Tank Diameter (ft):	25.0000	25.0000	25.0000	25.0000	25.0000	25.0000	25.0000	25.0000	25.0000	25.0000	25.0000	25.0000
Working Loss Product Factor:	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
Total Losses (lb):	62.9178	62.9178	62.9178	62.9178	62.9178	62.9178	62.9178	62.9178	62.9178	62.9178	62.9178	62.9178

TANKS 4.0.9d
Emissions Report - Detail Format
Individual Tank Emission Totals

Emissions Report for: January, February, March, April, May, June, July, August, September, October, November, December

N-266-822-0 (T-1) Annual - Vertical Fixed Roof Tank

	Losses(lbs)		
Components	Working Loss	Breathing Loss	Total Emissions
Wine 20.0 % Vol Alcohol	755.01	0.00	755.01

TANKS 4.0.9d
Emissions Report - Detail Format
Tank Indentification and Physical Characteristics

Identification

User Identification:	N-266-838-0 (T-17) Annual
City:	
State:	
Company:	
Type of Tank:	Vertical Fixed Roof Tank
Description:	

Tank Dimensions

Shell Height (ft):	40.00
Diameter (ft):	21.00
Liquid Height (ft) :	40.00
Avg. Liquid Height (ft):	39.00
Volume (gallons):	103,000.00
Turnovers:	10.00
Net Throughput(gal/yr):	1,030,000.00
Is Tank Heated (y/n):	Y

Paint Characteristics

Shell Color/Shade:	White/White
Shell Condition	Good
Roof Color/Shade:	White/White
Roof Condition:	Good

Roof Characteristics

Type:	Cone
Height (ft)	1.00
Slope (ft/ft) (Cone Roof)	0.10

Breather Vent Settings

Vacuum Settings (psig):	0.00
Pressure Settings (psig)	0.00

Meterological Data used in Emissions Calculations: Stockton, California (Avg Atmospheric Pressure = 14.72 psia)

TANKS 4.0.9d
Emissions Report - Detail Format
Liquid Contents of Storage Tank

N-266-838-0 (T-17) Annual - Vertical Fixed Roof Tank

Mixture/Component	Month	Daily Liquid Surf. Temperature (deg F) Avg.	Min.	Max.	Liquid Bulk Temp (deg F)	Vapor Pressure (psia) Avg.	Min.	Max.	Vapor Mol. Weight.	Liquid Mass Fract.	Vapor Mass Fract.	Mol. Weight	Basis for Vapor Pressure Calculations
Wine 20.0 % Vol Alcohol	Jan	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Feb	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Mar	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Apr	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	May	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Jun	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Jul	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Aug	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Sep	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Oct	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Nov	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Dec	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304

TANKS 4.0.9d
Emissions Report - Detail Format
Detail Calculations (AP-42)

N-266-838-0 (T-17) Annual - Vertical Fixed Roof Tank

Month:	January	February	March	April	May	June	July	August	September	October	November	December
Standing Losses (lb):	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vapor Space Volume (cu ft):	461.8141	461.8141	461.8141	461.8141	461.8141	461.8141	461.8141	461.8141	461.8141	461.8141	461.8141	461.8141
Vapor Density (lb/cu ft):	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036
Vapor Space Expansion Factor:	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vented Vapor Saturation Factor:	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520
Tank Vapor Space Volume:												
Vapor Space Volume (cu ft):	461.8141	461.8141	461.8141	461.8141	461.8141	461.8141	461.8141	461.8141	461.8141	461.8141	461.8141	461.8141
Tank Diameter (ft):	21.0000	21.0000	21.0000	21.0000	21.0000	21.0000	21.0000	21.0000	21.0000	21.0000	21.0000	21.0000
Vapor Space Outage (ft):	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333
Tank Shell Height (ft):	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000
Average Liquid Height (ft):	39.0000	39.0000	39.0000	39.0000	39.0000	39.0000	39.0000	39.0000	39.0000	39.0000	39.0000	39.0000
Roof Outage (ft):	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333
Roof Outage (Cone Roof)												
Roof Outage (ft):	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333
Roof Height (ft):	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
Roof Slope (ft/ft):	0.1000	0.1000	0.1000	0.1000	0.1000	0.1000	0.1000	0.1000	0.1000	0.1000	0.1000	0.1000
Shell Radius (ft):	10.5000	10.5000	10.5000	10.5000	10.5000	10.5000	10.5000	10.5000	10.5000	10.5000	10.5000	10.5000
Vapor Density												
Vapor Density (lb/cu ft):	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036
Vapor Molecular Weight (lb/lb-mole):	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129
Daily Avg. Liquid Surface Temp. (deg. R):	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700
Daily Average Ambient Temp. (deg. F):	45.0000	50.5000	54.0500	59.3000	66.7000	73.3000	77.6500	76.8000	72.7000	64.5500	53.0500	44.9500
Ideal Gas Constant R (psia cuft / (lb-mol-deg R)):	10.731	10.731	10.731	10.731	10.731	10.731	10.731	10.731	10.731	10.731	10.731	10.731
Liquid Bulk Temperature (deg. R):	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700
Tank Paint Solar Absorptance (Shell):	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700
Tank Paint Solar Absorptance (Roof):	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700
Daily Total Solar Insulation Factor (Btu/sqft day):	597.0000	939.0000	1,458.0000	2,004.0000	2,435.0000	2,684.0000	2,688.0000	2,368.0000	1,907.0000	1,315.0000	782.0000	538.0000
Vapor Space Expansion Factor												
Vapor Space Expansion Factor:	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Daily Vapor Temperature Range (deg. R):	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Daily Vapor Pressure Range (psia):	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Breather Vent Press. Setting Range(psia):	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129
Vapor Pressure at Daily Minimum Liquid Surface Temperature (psia):	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129
Vapor Pressure at Daily Maximum Liquid Surface Temperature (psia):	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129
Daily Avg. Liquid Surface Temp. (deg R):	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700
Daily Min. Liquid Surface Temp. (deg R):	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700
Daily Max. Liquid Surface Temp. (deg R):	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700
Daily Ambient Temp. Range (deg. R):	16.0000	20.4000	22.9000	27.2000	29.8000	31.6000	33.5000	32.2000	30.4000	27.5000	20.7000	15.7000
Vented Vapor Saturation Factor												
Vented Vapor Saturation Factor:	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520
Vapor Pressure at Daily Average Liquid: Surface Temperature (psia):	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129
Vapor Space Outage (ft):	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333
Working Losses (lb):	42.0814	42.0814	42.0814	42.0814	42.0814	42.0814	42.0814	42.0814	42.0814	42.0814	42.0814	42.0814

Vapor Molecular Weight (lb/lb-mole):	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129
Net Throughput (gal/mo.):	85,833.3333	85,833.3333	85,833.3333	85,833.3333	85,833.3333	85,833.3333	85,833.3333	85,833.3333	85,833.3333	85,833.3333	85,833.3333	85,833.3333
Annual Turnovers:	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000
Turnover Factor:	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
Maximum Liquid Volume (gal):	103,000.0000	103,000.0000	103,000.0000	103,000.0000	103,000.0000	103,000.0000	103,000.0000	103,000.0000	103,000.0000	103,000.0000	103,000.0000	103,000.0000
Maximum Liquid Height (ft):	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000
Tank Diameter (ft):	21.0000	21.0000	21.0000	21.0000	21.0000	21.0000	21.0000	21.0000	21.0000	21.0000	21.0000	21.0000
Working Loss Product Factor:	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
Total Losses (lb):	42.0814	42.0814	42.0814	42.0814	42.0814	42.0814	42.0814	42.0814	42.0814	42.0814	42.0814	42.0814

TANKS 4.0.9d
Emissions Report - Detail Format
Individual Tank Emission Totals

Emissions Report for: January, February, March, April, May, June, July, August, September, October, November, December

N-266-838-0 (T-17) Annual - Vertical Fixed Roof Tank

	Losses(lbs)		
Components	Working Loss	Breathing Loss	Total Emissions
Wine 20.0 % Vol Alcohol	504.98	0.00	504.98

TANKS 4.0.9d
Emissions Report - Detail Format
Tank Indentification and Physical Characteristics

Identification

User Identification:	N-266-866-0 (T-45) Annual
City:	
State:	
Company:	
Type of Tank:	Vertical Fixed Roof Tank
Description:	

Tank Dimensions

Shell Height (ft):	40.00
Diameter (ft):	16.00
Liquid Height (ft) :	40.00
Avg. Liquid Height (ft):	39.00
Volume (gallons):	60,000.00
Turnovers:	10.00
Net Throughput(gal/yr):	600,000.00
Is Tank Heated (y/n):	Y

Paint Characteristics

Shell Color/Shade:	White/White
Shell Condition	Good
Roof Color/Shade:	White/White
Roof Condition:	Good

Roof Characteristics

Type:	Cone
Height (ft)	1.00
Slope (ft/ft) (Cone Roof)	0.12

Breather Vent Settings

Vacuum Settings (psig):	0.00
Pressure Settings (psig)	0.00

Meterological Data used in Emissions Calculations: Stockton, California (Avg Atmospheric Pressure = 14.72 psia)

TANKS 4.0.9d
Emissions Report - Detail Format
Liquid Contents of Storage Tank

N-266-866-0 (T-45) Annual - Vertical Fixed Roof Tank

Mixture/Component	Month	Daily Liquid Surf. Temperature (deg F) Avg.	Min.	Max.	Liquid Bulk Temp (deg F)	Vapor Pressure (psia) Avg.	Min.	Max.	Vapor Mol. Weight	Liquid Mass Fract.	Vapor Mass Fract.	Mol. Weight	Basis for Vapor Pressure Calculations
Wine 20.0 % Vol Alcohol	Jan	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Feb	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Mar	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Apr	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	May	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Jun	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Jul	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Aug	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Sep	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Oct	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Nov	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Dec	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304

TANKS 4.0.9d
Emissions Report - Detail Format
Detail Calculations (AP-42)

N-266-866-0 (T-45) Annual - Vertical Fixed Roof Tank

Month:	January	February	March	April	May	June	July	August	September	October	November	December
Standing Losses (lb):	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vapor Space Volume (cu ft):	268.0826	268.0826	268.0826	268.0826	268.0826	268.0826	268.0826	268.0826	268.0826	268.0826	268.0826	268.0826
Vapor Density (lb/cu ft):	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036
Vapor Space Expansion Factor:	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vented Vapor Saturation Factor:	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520
Tank Vapor Space Volume:												
Vapor Space Volume (cu ft):	268.0826	268.0826	268.0826	268.0826	268.0826	268.0826	268.0826	268.0826	268.0826	268.0826	268.0826	268.0826
Tank Diameter (ft):	16.0000	16.0000	16.0000	16.0000	16.0000	16.0000	16.0000	16.0000	16.0000	16.0000	16.0000	16.0000
Vapor Space Outage (ft):	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333
Tank Shell Height (ft):	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000
Average Liquid Height (ft):	39.0000	39.0000	39.0000	39.0000	39.0000	39.0000	39.0000	39.0000	39.0000	39.0000	39.0000	39.0000
Roof Outage (ft):	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333
Roof Outage (Cone Roof)												
Roof Outage (ft):	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333
Roof Height (ft):	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
Roof Slope (ft/ft):	0.1200	0.1200	0.1200	0.1200	0.1200	0.1200	0.1200	0.1200	0.1200	0.1200	0.1200	0.1200
Shell Radius (ft):	8.0000	8.0000	8.0000	8.0000	8.0000	8.0000	8.0000	8.0000	8.0000	8.0000	8.0000	8.0000
Vapor Density												
Vapor Density (lb/cu ft):	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036
Vapor Molecular Weight (lb/lb-mole):	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129
Daily Avg. Liquid Surface Temp. (deg. R):	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700
Daily Average Ambient Temp. (deg. F):	45.0000	50.5000	54.0500	59.3000	66.7000	73.3000	77.6500	76.8000	72.7000	64.5500	53.0500	44.9500
Ideal Gas Constant R (psia cuft / (lb-mol-deg R)):	10.731	10.731	10.731	10.731	10.731	10.731	10.731	10.731	10.731	10.731	10.731	10.731
Liquid Bulk Temperature (deg. R):	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700
Tank Paint Solar Absorptance (Shell):	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700
Tank Paint Solar Absorptance (Roof):	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700
Daily Total Solar Insulation Factor (Btu/sqft day):	597.0000	939.0000	1,458.0000	2,004.0000	2,435.0000	2,684.0000	2,688.0000	2,368.0000	1,907.0000	1,315.0000	782.0000	538.0000
Vapor Space Expansion Factor												
Vapor Space Expansion Factor:	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Daily Vapor Temperature Range (deg. R):	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Daily Vapor Pressure Range (psia):	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Breather Vent Press. Setting Range(psia):	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129
Vapor Pressure at Daily Minimum Liquid Surface Temperature (psia):	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129
Vapor Pressure at Daily Maximum Liquid Surface Temperature (psia):	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129
Daily Avg. Liquid Surface Temp. (deg R):	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700
Daily Min. Liquid Surface Temp. (deg R):	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700
Daily Max. Liquid Surface Temp. (deg R):	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700
Daily Ambient Temp. Range (deg. R):	16.0000	20.4000	22.9000	27.2000	29.8000	31.6000	33.5000	32.2000	30.4000	27.5000	20.7000	15.7000
Vented Vapor Saturation Factor												
Vented Vapor Saturation Factor:	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520
Vapor Pressure at Daily Average Liquid: Surface Temperature (psia):	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129
Vapor Space Outage (ft):	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333
Working Losses (lb):	24.5134	24.5134	24.5134	24.5134	24.5134	24.5134	24.5134	24.5134	24.5134	24.5134	24.5134	24.5134

Vapor Molecular Weight (lb/lb-mole):	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129
Net Throughput (gal/mo.):	50,000.0000	50,000.0000	50,000.0000	50,000.0000	50,000.0000	50,000.0000	50,000.0000	50,000.0000	50,000.0000	50,000.0000	50,000.0000	50,000.0000
Annual Turnovers:	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000
Turnover Factor:	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
Maximum Liquid Volume (gal):	60,000.0000	60,000.0000	60,000.0000	60,000.0000	60,000.0000	60,000.0000	60,000.0000	60,000.0000	60,000.0000	60,000.0000	60,000.0000	60,000.0000
Maximum Liquid Height (ft):	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000	40.0000
Tank Diameter (ft):	16.0000	16.0000	16.0000	16.0000	16.0000	16.0000	16.0000	16.0000	16.0000	16.0000	16.0000	16.0000
Working Loss Product Factor:	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
Total Losses (lb):	24.5134	24.5134	24.5134	24.5134	24.5134	24.5134	24.5134	24.5134	24.5134	24.5134	24.5134	24.5134

TANKS 4.0.9d
Emissions Report - Detail Format
Individual Tank Emission Totals

Emissions Report for: January, February, March, April, May, June, July, August, September, October, November, December

N-266-866-0 (T-45) Annual - Vertical Fixed Roof Tank

	Losses(lbs)		
Components	Working Loss	Breathing Loss	Total Emissions
Wine 20.0 % Vol Alcohol	294.16	0.00	294.16

TANKS 4.0.9d
Emissions Report - Detail Format
Tank Indentification and Physical Characteristics

Identification

User Identification:	N-266-916-0 (T-95) Annual
City:	
State:	
Company:	
Type of Tank:	Vertical Fixed Roof Tank
Description:	

Tank Dimensions

Shell Height (ft):	28.00
Diameter (ft):	21.00
Liquid Height (ft) :	28.00
Avg. Liquid Height (ft):	27.00
Volume (gallons):	74,000.00
Turnovers:	10.00
Net Throughput(gal/yr):	740,000.00
Is Tank Heated (y/n):	Y

Paint Characteristics

Shell Color/Shade:	White/White
Shell Condition	Good
Roof Color/Shade:	White/White
Roof Condition:	Good

Roof Characteristics

Type:	Cone
Height (ft)	1.00
Slope (ft/ft) (Cone Roof)	0.10

Breather Vent Settings

Vacuum Settings (psig):	0.00
Pressure Settings (psig)	0.00

Meterological Data used in Emissions Calculations: Stockton, California (Avg Atmospheric Pressure = 14.72 psia)

TANKS 4.0.9d
Emissions Report - Detail Format
Liquid Contents of Storage Tank

N-266-916-0 (T-95) Annual - Vertical Fixed Roof Tank

Mixture/Component	Month	Daily Liquid Surf. Temperature (deg F) Avg.	Min.	Max.	Liquid Bulk Temp (deg F)	Vapor Pressure (psia) Avg.	Min.	Max.	Vapor Mol. Weight	Liquid Mass Fract.	Vapor Mass Fract.	Mol. Weight	Basis for Vapor Pressure Calculations
Wine 20.0 % Vol Alcohol	Jan	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Feb	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Mar	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Apr	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	May	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Jun	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Jul	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Aug	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Sep	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Oct	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Nov	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Dec	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304

TANKS 4.0.9d
Emissions Report - Detail Format
Detail Calculations (AP-42)

N-266-916-0 (T-95) Annual - Vertical Fixed Roof Tank

Month:	January	February	March	April	May	June	July	August	September	October	November	December
Standing Losses (lb):	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vapor Space Volume (cu ft):	461.8141	461.8141	461.8141	461.8141	461.8141	461.8141	461.8141	461.8141	461.8141	461.8141	461.8141	461.8141
Vapor Density (lb/cu ft):	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036
Vapor Space Expansion Factor:	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vented Vapor Saturation Factor:	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520
Tank Vapor Space Volume:												
Vapor Space Volume (cu ft):	461.8141	461.8141	461.8141	461.8141	461.8141	461.8141	461.8141	461.8141	461.8141	461.8141	461.8141	461.8141
Tank Diameter (ft):	21.0000	21.0000	21.0000	21.0000	21.0000	21.0000	21.0000	21.0000	21.0000	21.0000	21.0000	21.0000
Vapor Space Outage (ft):	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333
Tank Shell Height (ft):	28.0000	28.0000	28.0000	28.0000	28.0000	28.0000	28.0000	28.0000	28.0000	28.0000	28.0000	28.0000
Average Liquid Height (ft):	27.0000	27.0000	27.0000	27.0000	27.0000	27.0000	27.0000	27.0000	27.0000	27.0000	27.0000	27.0000
Roof Outage (ft):	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333
Roof Outage (Cone Roof)												
Roof Outage (ft):	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333
Roof Height (ft):	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
Roof Slope (ft/ft):	0.1000	0.1000	0.1000	0.1000	0.1000	0.1000	0.1000	0.1000	0.1000	0.1000	0.1000	0.1000
Shell Radius (ft):	10.5000	10.5000	10.5000	10.5000	10.5000	10.5000	10.5000	10.5000	10.5000	10.5000	10.5000	10.5000
Vapor Density												
Vapor Density (lb/cu ft):	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036
Vapor Molecular Weight (lb/lb-mole):	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129
Daily Avg. Liquid Surface Temp. (deg. R):	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700
Daily Average Ambient Temp. (deg. F):	45.0000	50.5000	54.0500	59.3000	66.7000	73.3000	77.6500	76.8000	72.7000	64.5500	53.0500	44.9500
Ideal Gas Constant R (psia cuft / (lb-mol-deg R)):	10.731	10.731	10.731	10.731	10.731	10.731	10.731	10.731	10.731	10.731	10.731	10.731
Liquid Bulk Temperature (deg. R):	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700
Tank Paint Solar Absorptance (Shell):	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700
Tank Paint Solar Absorptance (Roof):	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700
Daily Total Solar Insulation Factor (Btu/sqft day):	597.0000	939.0000	1,458.0000	2,004.0000	2,435.0000	2,684.0000	2,688.0000	2,368.0000	1,907.0000	1,315.0000	782.0000	538.0000
Vapor Space Expansion Factor												
Vapor Space Expansion Factor:	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Daily Vapor Temperature Range (deg. R):	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Daily Vapor Pressure Range (psia):	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Breather Vent Press. Setting Range(psia):	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129
Vapor Pressure at Daily Minimum Liquid Surface Temperature (psia):	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129
Vapor Pressure at Daily Maximum Liquid Surface Temperature (psia):	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129
Daily Avg. Liquid Surface Temp. (deg R):	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700
Daily Min. Liquid Surface Temp. (deg R):	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700
Daily Max. Liquid Surface Temp. (deg R):	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700
Daily Ambient Temp. Range (deg. R):	16.0000	20.4000	22.9000	27.2000	29.8000	31.6000	33.5000	32.2000	30.4000	27.5000	20.7000	15.7000
Vented Vapor Saturation Factor												
Vented Vapor Saturation Factor:	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520
Vapor Pressure at Daily Average Liquid: Surface Temperature (psia):	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129
Vapor Space Outage (ft):	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333
Working Losses (lb):	30.2332	30.2332	30.2332	30.2332	30.2332	30.2332	30.2332	30.2332	30.2332	30.2332	30.2332	30.2332

Vapor Molecular Weight (lb/lb-mole):	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129
Net Throughput (gal/mo.):	61,666.6667	61,666.6667	61,666.6667	61,666.6667	61,666.6667	61,666.6667	61,666.6667	61,666.6667	61,666.6667	61,666.6667	61,666.6667	61,666.6667
Annual Turnovers:	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000
Turnover Factor:	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
Maximum Liquid Volume (gal):	74,000.0000	74,000.0000	74,000.0000	74,000.0000	74,000.0000	74,000.0000	74,000.0000	74,000.0000	74,000.0000	74,000.0000	74,000.0000	74,000.0000
Maximum Liquid Height (ft):	28.0000	28.0000	28.0000	28.0000	28.0000	28.0000	28.0000	28.0000	28.0000	28.0000	28.0000	28.0000
Tank Diameter (ft):	21.0000	21.0000	21.0000	21.0000	21.0000	21.0000	21.0000	21.0000	21.0000	21.0000	21.0000	21.0000
Working Loss Product Factor:	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
Total Losses (lb):	30.2332	30.2332	30.2332	30.2332	30.2332	30.2332	30.2332	30.2332	30.2332	30.2332	30.2332	30.2332

TANKS 4.0.9d
Emissions Report - Detail Format
Individual Tank Emission Totals

Emissions Report for: January, February, March, April, May, June, July, August, September, October, November, December

N-266-916-0 (T-95) Annual - Vertical Fixed Roof Tank

	Losses(lbs)		
Components	Working Loss	Breathing Loss	Total Emissions
Wine 20.0 % Vol Alcohol	362.80	0.00	362.80

TANKS 4.0.9d
Emissions Report - Detail Format
Tank Indentification and Physical Characteristics

Identification

User Identification:	N-266-930-0 (T-109) Annual
City:	
State:	
Company:	
Type of Tank:	Vertical Fixed Roof Tank
Description:	

Tank Dimensions

Shell Height (ft):	32.00
Diameter (ft):	18.00
Liquid Height (ft) :	32.00
Avg. Liquid Height (ft):	31.00
Volume (gallons):	60,914.13
Turnovers:	10.00
Net Throughput(gal/yr):	609,141.33
Is Tank Heated (y/n):	Y

Paint Characteristics

Shell Color/Shade:	White/White
Shell Condition	Good
Roof Color/Shade:	White/White
Roof Condition:	Good

Roof Characteristics

Type:	Cone
Height (ft)	1.00
Slope (ft/ft) (Cone Roof)	0.11

Breather Vent Settings

Vacuum Settings (psig):	0.00
Pressure Settings (psig)	0.00

Meterological Data used in Emissions Calculations: Stockton, California (Avg Atmospheric Pressure = 14.72 psia)

TANKS 4.0.9d
Emissions Report - Detail Format
Liquid Contents of Storage Tank

N-266-930-0 (T-109) Annual - Vertical Fixed Roof Tank

Mixture/Component	Month	Daily Liquid Surf. Temperature (deg F) Avg.	Min.	Max.	Liquid Bulk Temp (deg F)	Vapor Pressure (psia) Avg.	Min.	Max.	Vapor Mol. Weight	Liquid Mass Fract.	Vapor Mass Fract.	Mol. Weight	Basis for Vapor Pressure Calculations
Wine 20.0 % Vol Alcohol	Jan	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Feb	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Mar	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Apr	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	May	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Jun	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Jul	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Aug	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Sep	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Oct	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Nov	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304
Wine 20.0 % Vol Alcohol	Dec	77.30	77.30	77.30	77.30	0.7129	0.7129	0.7129	28.8820			20.00	Option 1: VP70 = .55047 VP80 = .77304

TANKS 4.0.9d
Emissions Report - Detail Format
Detail Calculations (AP-42)

N-266-930-0 (T-109) Annual - Vertical Fixed Roof Tank

Month:	January	February	March	April	May	June	July	August	September	October	November	December
Standing Losses (lb):	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vapor Space Volume (cu ft):	339.2920	339.2920	339.2920	339.2920	339.2920	339.2920	339.2920	339.2920	339.2920	339.2920	339.2920	339.2920
Vapor Density (lb/cu ft):	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036
Vapor Space Expansion Factor:	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vented Vapor Saturation Factor:	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520
Tank Vapor Space Volume:												
Vapor Space Volume (cu ft):	339.2920	339.2920	339.2920	339.2920	339.2920	339.2920	339.2920	339.2920	339.2920	339.2920	339.2920	339.2920
Tank Diameter (ft):	18.0000	18.0000	18.0000	18.0000	18.0000	18.0000	18.0000	18.0000	18.0000	18.0000	18.0000	18.0000
Vapor Space Outage (ft):	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333
Tank Shell Height (ft):	32.0000	32.0000	32.0000	32.0000	32.0000	32.0000	32.0000	32.0000	32.0000	32.0000	32.0000	32.0000
Average Liquid Height (ft):	31.0000	31.0000	31.0000	31.0000	31.0000	31.0000	31.0000	31.0000	31.0000	31.0000	31.0000	31.0000
Roof Outage (ft):	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333
Roof Outage (Cone Roof)												
Roof Outage (ft):	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333	0.3333
Roof Height (ft):	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
Roof Slope (ft/ft):	0.1100	0.1100	0.1100	0.1100	0.1100	0.1100	0.1100	0.1100	0.1100	0.1100	0.1100	0.1100
Shell Radius (ft):	9.0000	9.0000	9.0000	9.0000	9.0000	9.0000	9.0000	9.0000	9.0000	9.0000	9.0000	9.0000
Vapor Density												
Vapor Density (lb/cu ft):	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036	0.0036
Vapor Molecular Weight (lb/lb-mole):	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129
Daily Avg. Liquid Surface Temp. (deg. R):	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700
Daily Average Ambient Temp. (deg. F):	45.0000	50.5000	54.0500	59.3000	66.7000	73.3000	77.6500	76.8000	72.7000	64.5500	53.0500	44.9500
Ideal Gas Constant R (psia cuft / (lb-mol-deg R)):	10.731	10.731	10.731	10.731	10.731	10.731	10.731	10.731	10.731	10.731	10.731	10.731
Liquid Bulk Temperature (deg. R):	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700
Tank Paint Solar Absorptance (Shell):	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700
Tank Paint Solar Absorptance (Roof):	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700	0.1700
Daily Total Solar Insulation Factor (Btu/sqft day):	597.0000	939.0000	1,458.0000	2,004.0000	2,435.0000	2,684.0000	2,688.0000	2,368.0000	1,907.0000	1,315.0000	782.0000	538.0000
Vapor Space Expansion Factor												
Vapor Space Expansion Factor:	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Daily Vapor Temperature Range (deg. R):	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Daily Vapor Pressure Range (psia):	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Breather Vent Press. Setting Range(psia):	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129
Vapor Pressure at Daily Minimum Liquid Surface Temperature (psia):	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129
Vapor Pressure at Daily Maximum Liquid Surface Temperature (psia):	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129
Daily Avg. Liquid Surface Temp. (deg R):	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700
Daily Min. Liquid Surface Temp. (deg R):	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700
Daily Max. Liquid Surface Temp. (deg R):	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700	536.9700
Daily Ambient Temp. Range (deg. R):	16.0000	20.4000	22.9000	27.2000	29.8000	31.6000	33.5000	32.2000	30.4000	27.5000	20.7000	15.7000
Vented Vapor Saturation Factor												
Vented Vapor Saturation Factor:	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520	0.9520
Vapor Pressure at Daily Average Liquid: Surface Temperature (psia):	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129
Vapor Space Outage (ft):	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333	1.3333
Working Losses (lb):	24.8869	24.8869	24.8869	24.8869	24.8869	24.8869	24.8869	24.8869	24.8869	24.8869	24.8869	24.8869

Vapor Molecular Weight (lb/lb-mole):	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820	28.8820
Vapor Pressure at Daily Average Liquid Surface Temperature (psia):	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129	0.7129
Net Throughput (gal/mo.):	50,761.7774	50,761.7774	50,761.7774	50,761.7774	50,761.7774	50,761.7774	50,761.7774	50,761.7774	50,761.7774	50,761.7774	50,761.7774	50,761.7774
Annual Turnovers:	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000	10.0000
Turnover Factor:	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
Maximum Liquid Volume (gal):	60,914.1329	60,914.1329	60,914.1329	60,914.1329	60,914.1329	60,914.1329	60,914.1329	60,914.1329	60,914.1329	60,914.1329	60,914.1329	60,914.1329
Maximum Liquid Height (ft):	32.0000	32.0000	32.0000	32.0000	32.0000	32.0000	32.0000	32.0000	32.0000	32.0000	32.0000	32.0000
Tank Diameter (ft):	18.0000	18.0000	18.0000	18.0000	18.0000	18.0000	18.0000	18.0000	18.0000	18.0000	18.0000	18.0000
Working Loss Product Factor:	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
Total Losses (lb):	24.8869	24.8869	24.8869	24.8869	24.8869	24.8869	24.8869	24.8869	24.8869	24.8869	24.8869	24.8869

TANKS 4.0.9d
Emissions Report - Detail Format
Individual Tank Emission Totals

Emissions Report for: January, February, March, April, May, June, July, August, September, October, November, December

N-266-930-0 (T-109) Annual - Vertical Fixed Roof Tank

	Losses(lbs)		
Components	Working Loss	Breathing Loss	Total Emissions
Wine 20.0 % Vol Alcohol	298.64	0.00	298.64

TANKS 4.0.9d
Emissions Report - Detail Format
Total Emissions Summaries - All Tanks in Report

Emissions Report for: January, February, March, April, May, June, July, August, September, October, November, December

Tank Identification		Losses (lbs)
N-266-822-0 (T-1) Annual	Vertical Fixed Roof Tank	755.01
N-266-838-0 (T-17) Annual	Vertical Fixed Roof Tank	504.98
N-266-866-0 (T-45) Annual	Vertical Fixed Roof Tank	294.16
N-266-916-0 (T-95) Annual	Vertical Fixed Roof Tank	362.80
N-266-930-0 (T-109) Annual	Vertical Fixed Roof Tank	298.64
Total Emissions for all Tanks:		2,215.59

Appendix A

TANKS 4.0d Runs and Summary

Appendix B

BACT Guideline 5.4.14 and Top Down BACT Analysis

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 5.4.14*

Last Update: 10/06/2009

Wine Fermentation Tank

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	Temperature-Controlled Open Top Tank with Maximum Average Fermentation Temperature of 95 deg F	1. Capture of VOCs and Thermal Oxidation or Equivalent (88% control) 2. Capture of VOCs and Carbon Adsorption or Equivalent (86% control) 3. Capture of VOCs and Absorption or Equivalent (81% control) 4. Capture of VOCs and Condensation or Equivalent (81% control)	

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in s a state implementation plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

Top Down BACT Analysis for VOCs from Wine Fermentation Operations

Step 1 - Identify All Possible Control Technologies

SJVUAPCD BACT Clearinghouse guideline 5.4.14 identifies the following control options for wine fermentation tanks as follows:

1) Capture of VOCs and thermal oxidation or equivalent (88% control) – Technologically Feasible
2) Capture of VOCs and carbon adsorption or equivalent (86% control) – Technologically Feasible
3) Capture of VOCs and absorption or equivalent (81% control) – Technologically Feasible
4) Capture of VOCs and condensation or equivalent (81% control) – Technologically Feasible
5) Temperature-Controlled Open Top Tank with Maximum Average Fermentation Temperature of 95 deg F – Achieved in Practice

As mentioned above, BACT guideline 5.4.14 (10/6/2009) lists both absorption (scrubber) and condensation systems as technologically feasible options for the control of VOC emissions from wine fermentation operations. Since 2009, there has been substantial development of these two control technologies, prompting the District to perform an analysis to determine whether these technologies can now be considered Achieved in Practice. As demonstrated in the Achieved in Practice analysis in Appendix D, these technologies do not yet meet the criteria to be considered as Achieved in Practice. Therefore, the technologies will be considered technologically feasible and a cost analysis will be performed for these technologies.

Step 2 - Eliminate Technologically Infeasible Options

None of the above listed technologies are technologically infeasible.

Step 3 - Rank Remaining Control Technologies by Control Effectiveness

Rank by Control Effectiveness		
Rank	Control	Overall Capture & Control Efficiency(*)
1	Capture of VOCs and thermal or catalytic oxidation or equivalent	88%(**)
2	Capture of VOCs and carbon adsorption or equivalent	86%
3	Capture of VOCs and absorption or equivalent	81%
4	Capture of VOCs and condensation or equivalent	81%
5	Temperature-Controlled Open Top Tank with Maximum Average Fermentation Temperature of 95 deg F	Baseline (Achieved-in-Practice)

(*) Capture efficiency (90%) x removal efficiency for control device.

(**) Following recent District practice, thermal and catalytic oxidation will be ranked together.

Step 4 - Cost Effectiveness Analysis

A cost effective analysis must be performed for all control options that have not been determined to be achieved in practice in the list from Step 3 above, in the order of their ranking, to determine the cost effective option with the lowest emissions.

District BACT Policy APR 1305 establishes annual cost thresholds for imposed control based upon the amount of pollutants reduced by the controls. If the cost of control is at or below the threshold, it is considered a cost effective control. If the cost exceeds the threshold, it is not cost effective and the control is not required. Per District BACT Policy, the maximum cost limit for VOC reduction is $17,500 per ton of VOC emissions reduced.

BACT Analysis Assumptions – All Control Options

- Sales Tax: This facility is located in Manteca, CA, which has a current sales tax rate of 8.5%. However, pollution control equipment qualifies for a partial tax exemption in California. According to the following link, the tax exemption rate is 4.1875%, http://www.boe.ca.gov/sutax/manufacturing_exemptions.htm#Purchasers . Therefore, the sales tax rate used in this analysis will be set equal to 4.3125% (8.5% - 4.1875%).
- Due to the unsteady state operation of fermentation tanks, initial source testing is expected to be a significant technical operation with significant expense, conducted over the fermentation cycle rather than the typical three 30-minute steady state measurements. An additional cost of $15,000 per control unit will be assumed for initial source testing.
- Annual source testing will also be required. It is assumed that only one representative control unit will require testing each year. An annual charge of $15,000 will be included.
- Project Contingency: For detailed estimates, the Association for the Advancement of Cost Engineering International recommends a contingency factor of 15%, while the Electric Power Research Institute recommends a contingency of 10% to 20% (ftp://ftp.repec.org/opt/ReDIF/RePEc/sip/04-005.pdf). Therefore, a cost contingency of 15% will be applied to the detailed estimates provided in these cost analyses. Additionally, since both the direct and indirect costs are detailed estimates and both of these categories of costs have uncertainty associated with them, the contingency will be applied to both the direct and indirect costs.
- Owner's Cost is the cost to cover the project management, internal engineering and operations planning required to implement a significant new process technology of this scale in a commercial winery. No Owner's Cost was specifically requested by the facility at this time; therefore, as a conservative estimate, the Owner's Cost will be set equal to $0 for the purposes of this BACT analysis.
- In order to capture fermentation emissions from wine fermentation tanks, it is necessary to enclose the tanks and duct the captured vapors to the control device. An increase in back pressure can result from enclosing the control device and adding the duct work and control system. Increases in back pressure to the tanks causes additional CO_2 absorption into the wine, resulting in the possibility of an effervescent reaction and a foam over event. To proactively prevent catastrophic events like foam overs, it is necessary to monitor back pressure and temperature of the tanks and take immediate action if the back pressure rises

to critical levels that suggest a foam over is about to occur. The cost of the equipment to monitor the pressure and temperature are included in the Programming Controller Logic (PCL) cost. In District Project C-1133347, a PCL cost of $10,000 per control system was provided to the District. This cost will be used to estimate PCL costs for the currently proposed project.

- In determining the labor costs for the cost analyses, three shifts is assumed to be appropriate for a control system wine fermentation tanks, since the emission rate from fermentation varies more and is less stable than the emission rate from wine storage.

Maximum Vapor Flow Rate

Based on the kinetic model provided by the facility, maximum CO2 production rate for each fermentation tank battery is summarized as follows:

Tank I.D.	ATC #	Nominal Capacities	Max CO2 Flowrate for Entire Tank Battery (scfm)	Max CO2 + Fresh Air for Entire Tank Battery (scfm)
T-1 thru T-16	N-266-822-0 thru -837-0	154,000 gallons	12,695	17,869
T-17 thru T-44	N-266-838-0 thru -865-0	103,000 gallons	14,858	20,915
T-45 thru T-64	N-266-866-0 thru -885-0	60,000 gallons	6,182	8,702
T-65 thru T-84	N-266-886-0 thru -905-0	60,000 gallons	6,182	8,702
T-85 thru T-94	N-266-906-0 thru -915-0	60,000 gallons	3,091	4,350
T-95 thru T-108	N-266-916-0 thru -929-0	70,000 gallons	5,337	7,511
T-109 thru T-128	N-266-930-0 thru -949-0	50,000 gallons	5,152	7,252
Total			53,497	75,301

Uncontrolled Fermentation Emissions

Delicato is proposing to establish a combined VOC emission limit for all fermentation and storage tanks proposed in this project which will be incorporated into the existing facility-wide combined VOC emissions limit for all wine storage and fermentation operations at the facility. Therefore, for the purposes of this cost effectiveness analysis, uncontrolled fermentation VOC emissions will be set equal to the combined total VOC emissions allowed under the new combined limit for storage and fermentation operations.

Uncontrolled PE from Section VII.C.2 = 269,842 lb-VOC/year

Collection System Capital Investment (based on ductwork and clean-in-place system)

A common feature of all technically feasible options is that they require installation of a collection system for delivering the VOCs from the tanks to the control device(s). Therefore, the following collection system analysis and cost estimate will be used in the cost effectiveness analysis for each control option.

Basis of Cost Information for Collection System

- The costs for the ductwork and the required clean-in-place system are based on information from the 2005 Eichleay Study. The 2005 Eichleay study was used in development of District Rule 4694 Wine Fermentation and Storage Tanks and includes substantial information on the costs and details of the potential application of VOC controls to wineries and addresses many of the technical issues of the general site specific factors for wineries.
- The District performed a cost survey of stainless steel ducting/piping and found that the values stated in the Eichleay report including the cost of inflation (applied as stated below) were cheaper; therefore, as a conservative estimate, the District will use the cost of ducting/piping from the Eichleay report which will include ducting, fittings, bolt up, handle, and install. A summary of the survey is included in Attachment B2.
- Eichleay's cost estimate for ducting included the duct, fittings, bolt up, handle and install; therefore, the District did not allow the additional costs for foundations & supports, handling & erection, electrical, piping or painting, as allowed by the EPA Cost Manual.
- The facility provided a ducting cost estimate which included a redundant ducting system and redundant ducting isolation components to allow the emission control systems to continue to be operated in the event of a foam-over. The District found these redundant systems to be unnecessary and the effects of a foam-over could be mitigated or minimized with smart valving and backflow preventer design integrated into the attached ducting layout diagrams in Attachment B1. Therefore, redundant ducting has been removed from the cost estimate for the purposes of this top down BACT analysis.
- The collection system will consist of stainless steel place ductwork (stainless steel is required due to food grade product status) with isolation valving, connecting the tanks to a common manifold system which ducts the combined vent to the common control device. The cost of dampers and isolation valving, installed in the ductwork, will be included in the cost estimate.
- A minimum duct size is established at six inches diameter at each tank to provide adequate strength for spanning between supports.
- One of the major concerns of a manifold duct system is microorganisms spoiling the product, and transferring from one tank to another. It is necessary to design into the system a positive disconnect of the ducting system when the tanks are not being filled. There are a number of ways this can be done. In this case, an automatic butterfly valve with a physical spool to disconnect the tank from the duct will be utilized.
- Additionally, the facility included an inflation amount of 2.75% per year from 2005 through 2015 to adjust the Eichleay cost to present value. The District found this inflation value to be unfounded and was replaced with an inflation amount of 21.93% for the period of 2005 to 2016 taken from United States Department of Labor Bureau of

Labor Statistics' CIP Inflation Calculator:
http://www.bls.gov/data/inflation_calculator.htm.

Capital Cost of Ductwork

As detailed in the tank layout sketches and the ductwork cost calculations included in Attachment B1, the cost for each tank group is summarized below:

Tank Group T-1 to T-16 (Permits N-266-822-0 thru -837-0):

Connection from tank to main duct = 16 tanks x 60 feet x $103.25/foot = $99,120
Main duct for fermenters = $118,924
1 Knockout drum = $46,300
Unit installed cost for 6 inch butterfly valve = $2,125/valve x 16 valves x 1 system = $34,000
Unit installed cost one foot removable spool = $500/tank x 16 tanks x 1 system = $8,000
Duct support allowance = $60,000

Total for Group T-1 to T-16 = $99,120 + $118,930 + $46,300 + $34,000 + $8,000 + $60,000
= $366,344

Tank Group T-17 to T-44 (Permits N-266-838-0 thru -865-0):

Connection from tank to main duct = 28 tanks x 56 feet x $103.25/foot = $161,896
Main duct for fermenters = $161,093
1 Knockout drum = $46,300
Unit installed cost for 6 inch butterfly valve = $2,125/valve x 28 valves x 1 system = $60,000
Unit installed cost one foot removable spool = $500/tank x 28 tanks x 1 system = $13,500
Duct support allowance = $60,000

Total for Group T-17 to T-44 = $161,896 + $161,093 + $46,300 + $60,000 + $13,500 + $60,000
= $502,789

Tank Group T-45 to T-64 (Permits N-266-866-0 thru -885-0):

Connection from tank to main duct = 20 tanks x 48 feet x $62.17/foot = $59,683
Main duct for fermenters = $66,783
1 Knockout drum = $46,300
Unit installed cost for 6 inch butterfly valve = $2,125/valve x 20 valves x 1 system = $42,500
Unit installed cost one foot removable spool = $500/tank x 20 tanks x 1 system = $10,000
Duct support allowance = $80,000

Total for Group T-45 to T-64 = $59,683 + $66,783 + $46,300 + $42,500 + $10,000 + $80,000
= $305,266

Tank Group T-65 to T-84 (Permits N-266-866-0 thru -915-0):

Connection from tank to main duct = 20 tanks x 48 feet x $62.17/foot = $59,683

Main duct for fermenters = $66,783
1 Knockout drum = $46,300
Unit installed cost for 6 inch butterfly valve = $2,125/valve x 20 valves x 1 system = $42,500
Unit installed cost one foot removable spool = $500/tank x 20 tanks x 1 system = $10,000
Duct support allowance = $80,000

Total for Group T-65 to T-84 = $59,683 + $66,783 + $46,300 + $42,500 + $10,000 + $80,000
= $305,266

Tank Group T-85 to T-94 (Permits N-266-906-0 thru -915-0):

Connection from tank to main duct = 10 tanks x 48 feet x $62.17/foot = $29,842
Main duct for fermenters = $28,116
1 Knockout drum = $46,300
Unit installed cost for 6 inch butterfly valve = $2,125/valve x 10 valves x 1 system = $21,250
Unit installed cost one foot removable spool = $500/tank x 10 tanks x 1 system = $5,000
Duct support allowance = $60,000

Total for Group T-45 to T-94 = $29,842 + $28,116 + $46,300 + $21,250 + $5,000 + $60,000
= $190,508

Tank Group T-95 to T-108 (Permits N-266-916-0 thru -929-0):

Connection from tank to main duct = 14 tanks x 46 feet x $62.17/foot = $40,037
Main duct for fermenters = $59,898
1 Knockout drum = $46,300
Unit installed cost for 6 inch butterfly valve = $2,125/valve x 14 valves x 1 system = $29,750
Unit installed cost one foot removable spool = $500/tank x 14 tanks x 1 system = $7,000
Duct support allowance = $60,000

Total for Group T-17 to T-44 = $40,037 + $59,898 + $46,300 + $29,750 + $7,000 + $60,000
= $242,985

Tank Group T-109 to T-128 (Permits N-266-930-0 thru -949-0):

Connection from tank to main duct = 20 tanks x 55 feet x $62.17/foot = $68,387
Main duct for fermenters = $57,453
1 Knockout drum = $46,300
Unit installed cost for 6 inch butterfly valve = $2,125/valve x 20 valves x 1 system = $42,500
Unit installed cost one foot removable spool = $500/tank x 20 tanks x 1 system = $10,000
Duct support allowance = $60,000

Total for Group T-17 to T-44 = $68,387 + $57,453 + $46,300 + $42,500 + $10,000 + $60,000
= $284,640

Tank I.D.	ATC #	Total Ducting Cost Including Support Allowance
T-1 thru T-16	N-266-822-0 thru -837-0	$366,344
T-17 thru T-44	N-266-838-0 thru -865-0	502,789
T-45 thru T-64	N-266-866-0 thru -885-0	305,266
T-65 thru T-84	N-266-886-0 thru -905-0	305,266
T-85 thru T-94	N-266-906-0 thru -915-0	190,508
T-95 thru T-108	N-266-916-0 thru -929-0	242,985
T-109 thru T-128	N-266-930-0 thru -949-0	284,640
Total		$2,197,798

Capital Cost of Ductwork for Wine Fermentation Tanks	
Cost Description	Cost ($)
Duct Estimate from Eichleay Study 2005 Data	$2,197,798
Adjusting factor for inflation from 2005 dollars to 2015 dollars (21.93% total increase)	1.2193
Inflation adjusted duct cost	$2,679,775
The following cost data is taken from EPA Control Cost Manual, Sixth Edition (EPA/452/B-02-001).	
Direct Costs	
Base Equipment Costs (Ductwork) See Above	$2,679,775
Instrumentation (not required)	-
Sales Tax - 4.3125% of base equipment	$115,565
Freight - 5% of base equipment	$133,989
Purchased equipment cost (PEC)	**$2,929,329**
Foundations & supports 8% (allowance already included in Base Equipment Costs)	-
Handling & erection 14% (already included in Eichleay cost estimate)	-
Electrical 4% (not required)	-
Piping 2% (not required)	-
Painting 1% (not required)	-
Insulation - 1% of PEC	$29,293
Direct installation costs (DIC)	**$29,293**
Total Direct Costs (DC) (PEC + DIC)	**$2,958,622**
Indirect Costs	
Engineering - 10% of PEC	$292,933
Construction and field expenses - 5% of PEC	$146,466
Contractor Fees - 10% of PEC	$292,933
Start-up - 2% of PEC	$58,587
Performance Test - 1% of PEC	$29,293
Total Indirect Costs (IC)	**$820,212**
Subtotal Capital Investment (SCI) (DC + IC)	**$3,778,834**
Contingencies - 15% of SCI	$566,825
Total Capital Investment (TCI) (SCI + Contingency)	**$4,345,659**

Capital Cost Clean-In-Place (CIP) System

A ducting system on a tank farm must have this system to maintain sanitation and quality of the product. The cost of operation of the CIP system has not been estimated. Operation of a CIP system, using typical cleaning agents, will raise disposal and wastewater treatment costs. Most likely, these costs will be significant.

Capital Cost of Clean-In-Place (CIP) System for Wine Fermentation Tanks	
Cost Description	Cost ($)
Current cost of CIP system ($200,000 x 7 control device locations)	$1,400,000
The following cost data is taken from EPA Control Cost Manual, Sixth Edition (EPA/452/B-02-001).	
Direct Costs	
Base Equipment Costs (CIP System) See Above	$1,400,000
Instrumentation - 10% of base equipment	$140,000
Sales Tax - 4.3125% of base equipment	$60,375
Freight - 5% of base equipment	$70,000
Purchased equipment cost (PEC)	**$1,670,375**
Foundations & supports - 8% of PEC	$133,630
Handling & erection - 14% of PEC	$233,853
Electrical - 4% of PEC	$66,815
Piping - (included in Base Equipment Costs)	-
Painting - 1% of PEC	$16,704
Insulation - 1% of PEC	$16,704
Direct installation costs (DIC)	**$467,706**
Total Direct Costs (DC) (PEC + DIC)	**$2,138,081**
Indirect Costs	
Engineering - 10% of PEC	$167,038
Construction and field expenses - 5% of PEC	$83,519
Contractor fees - 10% of PEC	$167,038
Start-up - 2% of PEC	$33,408
Performance test - 1% of PEC	$16,704
Total Indirect Costs (IC)	**$467,707**
Subtotal Capital Investment (SCI) (DC + IC)	**$2,605,788**
Contingencies - 15% of SCI	$390,868
Total Capital Investment (TCI) (SCI + Contingency)	**$2,996,656**

Annualized Capital Costs

Total capital costs = Ductwork + CIP System
= $4,345,659 + $2,996,656
= $7,342,315

Annualized Capital Investment = Initial Capital Investment x Amortization Factor

Amortization Factor = $\left[\frac{0.1(1.1)^{10}}{(1.1)^{10}-1}\right]$ = 0.163 per District policy, amortizing over 10 years at 10%

Therefore,

Annualized Capital Investment = $7,342,315 x 0.163 ≈ $1,196,800

Option 1 – Collection of VOCs and control by thermal or catalytic oxidation (88% collection & control)

Thermal or Catalytic Oxidizer Capital Cost

The total capital investment for a Regenerative Thermal Oxidizer (RTO) was provided by a vendor on December 10, 2015 and also by a separate independent vendor on November 13, 2015 in the amount of just under $3 million for stainless steel construction and $5 million respectively. Conservatively, the District will use a cost of $2.5 million.

Thermal or Catalytic Oxidation Capital Cost	
Cost Description	Cost ($)
Regenerative Thermal Oxidizer cost (7 units)	$2,500,000
Installation cost (not included)	-
The following cost data is taken from EPA Control Cost Manual, Sixth Edition (EPA/452/B-02-001).	
Direct Costs	
Base Equipment Costs (Regenerative Thermal Oxidizer System) See Above	$2,500,000
Instrumentation - 10% of base equipment	$250,000
Sales Tax - 4.3125% of base equipment	$107,813
Freight - 5% of base equipment	$125,000
Purchased equipment cost (PEC)	**$2,982,813**
Foundations & supports - 8% of PEC	$238,625
Handling & erection - 14% of PEC	$417,594
Electrical - 4% of PEC	$119,313
Piping - accounted for in ductwork cost	-
Painting - 1% of PEC	$29,828
Insulation - 1% of PEC	$29,828
PCL/Programming - 7 units x $10,000	$70,000
Direct Installation Costs (DIC)	**$905,188**
Total Direct Costs (DC) (PEC + DIC)	**$3,888,001**
Indirect Costs	
Engineering - 10% of PEC	$298,281
Construction and field expenses - 5% of PEC	$149,141
Contractor fees - 10% of PEC	$298,281
Start-up - 2% of PEC	$59,656
Initial Source Testing - 7 units x $15,000/unit	$105,000
Owner's Cost (No cost data provided)	-
Total Indirect Costs (IC)	**$910,359**
Subtotal Capital Investment (SCI) (DC + IC)	**$4,798,360**
Contingencies - 15% of SCI	$719,754
Total Capital Investment (TCI) (SCI + Contingency)	**$5,518,114**

Annualized Capital Costs

Annualized Capital Investment = Initial Capital Investment x Amortization Factor

Amortization Factor = $\left[\frac{0.1(1.1)^{10}}{(1.1)^{10}-1}\right]$ = 0.163, amortizing over 10 years at 10%

Therefore,

Annualized Capital Investment = $5,518,114 x 0.163 = $899,453

Operation and Maintenance Costs

The Direct annual costs include labor (operating, supervisory, and maintenance), maintenance materials, electricity, and fuel.

Heat of Combustion for waste gas stream -dh(c):

heat of combustion -dHc	= 11,800 Btu/lb for ethanol
Daily VOC emissions rate	= 28,589.9 lb/day per Section VII.C.2
Blower flow rate	= 75,301 scfm (based on kinetic model, with oxygen)
	= 108,433,440 ft^3/day

-dh(c) = 28,589.9 lb/day x 11,800 Btu/lb / 108,433,440 ft^3/day
= 3.1 Btu/ft^3

Assuming the waste gas is principally air, with a molecular weight of 28.97 and a corresponding density of 0.0739 lb/scf, the heat of combustion per pound of incoming waste gas is:

-dh(c) = 3.1 Btu/ft^3 / 0.0739 lb/ft^3
= 41.9 Btu/lb

Fuel Flow Requirement

$$Q(fuel) = \frac{Pw*Qw*\{Cp*[1.1Tf-Tw-0.1Tr]-[-dh(c)]\}}{\rho(af) * [-dh(m) - 1.1\ Cp * (Tf - Tr)]}$$

Where

Pw	=	0.0739 lb/ft^3
Cp	=	0.255 Btu/lb-°F
Qw	=	75,301 scfm
-dh(m)	=	11,800 Btu/lb for ethanol
Tr	=	77°F (per EPA Cost Manual)
ρ(af)	=	0.0408 lb/ft^3 m, methane at 77°F, 1 atm
Tf	=	1600°F
Tw	=	1525°F
-dh(c)	=	41.9 Btu/lb

$$Q = \frac{0.0739 * 75{,}301 * \{0.255 * [1.1 * 1{,}600 - 1{,}525 - 0.1*77] - 41.9\}}{0.0408 * [11{,}800 - 1.1 * 0.255 * (1{,}600 - 77)]}$$

$$= 89{,}378 \div 464 = 193 \text{ ft}^3/\text{min}$$

Fuel Costs

The cost for natural gas shall be based upon the average price of natural gas sold to "Commercial Consumers" in California for the years 2013, 2013 and 2015.[2]

2015 = $7.98/thousand ft^3 total monthly average
2014 = $9.05/thousand ft^3 total monthly average
2013 = $7.81/thousand ft^3 total monthly average
Average for three years = $8.28/thousand ft^3 total monthly average

Fuel Cost = 193 cfm x 1440 min/day x 90 day/year x $8.28/1000 ft^3
= $207,106/year

Electricity Requirement

$$\text{Power}_{fan} = \frac{1.17*10^{-4}\ Qw*\ \Delta P}{\in}$$

Where
ΔP = Pressure drop Across system = 4 in. H_2O
$\in$ = Efficiency for fan and motor = 0.6
Qw = 75,301 scfm

$$\text{Power}_{fan} = \frac{1.17 * 10^{-4} * 75{,}301 \text{ cfm} * 4 \text{ in. } H_2O}{0.60}$$

$$= 58.7 \text{ kW}$$

Electricity Costs

Average cost of electricity to commercial users in California[3]:

2015 Average = $0.1579/kWh

Electricity Cost = 58.7 kW x 24 hours/day x 90 days/year x $0.1579/kWh = $20,021 /year

---

[2] Energy Information Administration/Natural Gas; Average Price of Natural Gas Sold to Commercial Consumers by State, 2013 - 2015

[3] Energy Information Administration/Electric Power; Average Retail Price of Electricity to Ultimate Customers by End-Use Sector, by State, 2015 http://www.eia.gov/electricity/data/browser/#/topic/7?agg=0,1&geo=000000000004&endsec=vg&freq=A&start=2001&end=2015&ctype=linechart&ltype=pin&rtype=s&maptype=0&rse=0&pin=

Total Operating and Maintenance Costs

Annual Costs (Based on: EPA Air Pollution Control Cost Manual, Sixth Edition (January 2002), Section 3.2: VOC Destruction Controls, Chapter 2: Incinerators (September 2000), Table 2.10 - Annual Costs for Thermal and Catalytic Incinerators Example Problem. United States Environmental Protection Agency Office of Air Quality Planning and Standards. Research Triangle Park, North Carolina 27711. EPA/452/B-02-001)[4]

Thermal Oxidizer Annual Costs			
Direct Annual Cost (DAC)			
Operating Labor			
Operator	0.5 hr/shift	$18.50/hr x 0.5 hr/shift x 3 shift/day x 90 days/year x 7 units	$17,483
Supervisor	15% of operator		$2,622
Maintenance			
Labor	0.5 h/shift	$18.50/hr x 0.5 hr/shift x 3 shift/day x 90 days/year x 7 units	$17,483
Maintenance	100% of labor		$17,483
Utility			
Natural Gas	see calculation above		$207,106
Electricity	see calculation above		$20,021
Total DAC			**$282,198**
Indirect Annual Cost (IAC)			
Overhead	60% of Labor Cost	0.6 x ($17,483 + $2,622 + $17,483 + $17,483)	$33,043
Administrative	2% TCI		$110,362
Property Taxes	1% TCI		$55,181
Insurance	1% TCI		$55,181
Annual Source Test	One representative test/year @ $15,000		$15,000
Total IAC			**$268,767**
Annual Cost (DAC + IAC)			**$550,965**

Total Annual Cost = Regenerative Thermal Oxidizer System + (Ductwork + CIP System) + Annual Cost
= $899,453 + $1,196,800 + $550,965
= $2,647,218

Emission Reductions

Annual Emission Reduction = Uncontrolled Emissions x 0.88
= 269,842 lb-VOC/year x 0.88 x ton/2,000 lb
= 118.7 tons-VOC/year

[4] http://epa.gov/ttn/catc/dir1/cs3-2ch2.pdf

Cost Effectiveness

Cost Effectiveness = $2,647,218/year ÷ 118.7 tons-VOC/year
= $22,302/ton-VOC

The analysis demonstrates that the annualized purchase cost of the regenerative thermal oxidizer system, collection system ductwork and CIP equipment, and annual costs alone results in a cost effectiveness which exceeds the District's Guideline of $17,500/ton-VOC. Therefore this option is not cost-effective and will not be considered for this project.

Option 2 – Collection of VOCs and control by carbon adsorption (86% collection and control)

Design Basis

- Conservatively, additional costs not included at this time for additional equipment necessary for a fully functioning control system include, but are not limited to, the following:
  - The cost for a tank to collect the condensed ethanol laden steam from regeneration of the carbon bed.
  - Annual steam costs required to regenerate the carbon beds.
  - Annual cooling water costs required to condense the ethanol laden steam from regeneration of the carbon beds and the condenser equipment.
  - Electricity costs of system fans, bed drying/cooling fans and cooling water pumps.
- Ethanol laden water is a byproduct produced when the carbon is regenerated with steam and the ethanol laden steam is condensed. The collected ethanol laden water will need to be disposed of and can be a significant cost; however, conservatively, the costs will not be included at this time.

Capital Cost for Carbon Adsorption Equipment

The District contacted suppliers of carbon adsorption systems to obtain cost estimates for a system designed to handle the total flow rate from the fermentation tanks being proposed under this project. However, as of the time of this analysis, the District has not yet received replies from the carbon adsorption system suppliers. Therefore, the equipment cost for a carbon adsorption system used in this analysis will be based on the cost of a budgetary estimate for a 1,000 cfm system controlling wine fermentation tanks supplied by David Drewelow of Drewelow Remediation Equipment, Inc. on February 3, 2015 of $80,000 to $85,000. This system would include a gas/liquid separator, an inline filter, blower, exhaust silencer and air to air heat exchanger. Therefore, the cost for a carbon adsorption system handling 1,000 cfm will be conservatively estimated to be $80,000.

As shown above, the airflow rates of the control systems needed to control the fermentation tank groups in this project are larger than 1,000 cfm. In order to estimate the capital cost of the carbon adsorption system equipment needed for each tank group, the cost value

referenced above will need to be scaled. To be conservative, the cost will not be scaled linearly, but instead, the cost will be adjusted up to the required flow rate using the 6/10 power rule[5]. The 6/10 power rule is a way to account for economies of scale (the larger the equipment is, the lower the cost of equipment per unit of capacity[6]) and is considered generally accurate to within ± 20%. To account for the accuracy within ± 20% and to address EPA's concern with using this scaling method as expressed in their comments made on Project N-1133555, the District will conservatively use a modified 6/10 power rule and adjust the scaled cost down by 20%. A sample modified 6/10 power rule calculation for tank group T-1 thru T-16 is shown below and results in the following estimated capitol cost for a carbon adsorption system designed to handle 12,695 cfm:

Capitol Cost $= Cost_{base} \times [(Capacity_{new}/Capacity_{base})^{0.6}] \times (1 - 0.2)_{Accuracy\ Adjustment}$
$= \$80,000 \times [(12,695 /1,000)^{0.6}] \times 0.8$
$= \$294,008$

Tank I.D.	ATC #	Max CO2 Flowrate for Entire Tank Battery (scfm)	Capital Cost ($)
T-1 thru T-16	N-266-822-0 thru -837-0	12,695	$294,008
T-17 thru T-44	N-266-838-0 thru -865-0	14,858	$323,114
T-45 thru T-64	N-266-866-0 thru -885-0	6,182	$190,923
T-65 thru T-84	N-266-886-0 thru -905-0	6,182	$190,923
T-85 thru T-94	N-266-906-0 thru -915-0	3,091	$125,962
T-95 thru T-108	N-266-916-0 thru -929-0	5,337	$174,807
T-109 thru T-128	N-266-930-0 thru -949-0	5,152	$171,146
Total			$1,470,883

Capital Cost for Carbon for System

Annual Emission Reduction = Fermentation Emissions x 0.86
= 269,842 lb-VOC/year x 0.86
= 232,064 lb-VOC/year

Assume a working bed capacity of 20% for carbon (weight of vapor per weight of carbon)

Carbon required = 232,064 lb-VOC/year x 1/0.20
= 1,160,320 lb carbon

David Drewelow also provided a cost of $1.25/lb of carbon which does not include any delivery or servicing fees.

Annual carbon cost = $1.25/lb = $1.25/lb x 1,160,320 lb carbon = $1,450,400

[5] See the following websites for additional information: http://www.pdhonline.org/courses/g127/g127content.pdf
[6] http://faculty.ksu.edu.sa/5556/Documents/Chapter%205.ppt

Carbon Adsorption Capital Cost		
Cost Description	Equipment Cost ($)	Carbon Cost ($)
Carbon Adsorption System Cost	$1,470,883	-
Water alcohol tank cost (not included)	-	-
Carbon Capital Cost (see above)	-	$1,450,400
The following cost data is based on the EPA Air Pollution Control Cost Manual, Sixth Edition (January 2002) (EPA/452/B-02-001).		
Direct Costs		
Base Equipment Costs - See Above	$1,470,883	$1,450,400
Instrumentation - 10% of base equipment	$147,088	-
Sales Tax - 4.3125% of base equipment	$63,432	$62,549
Freight - 5% of base equipment	$73,544	$72,520
Purchased Equipment Cost (PEC)	**$1,754,947**	**$1,585,469**
Foundations & supports - 8% of PEC	$140,396	-
Handling & erection - 14% of PEC	$245,693	-
Electrical - 4% of PEC	$70,198	-
Piping - accounted for in ductwork cost	-	-
Painting - 1% of PEC	$17,549	-
Insulation - 1% of PEC	$17,549	-
PCL/Programming – 7 units x $10,000	$70,000	-
Direct installation costs (DIC)	**$561,385**	**$0**
Total Direct Costs (DC) (PEC + DIC)	**$2,316,332**	**$1,585,469**
Indirect Costs		
Engineering - 10% of PEC	$175,495	-
Construction and field expenses - 5% of PEC	$87,747	-
Contractor fees - 10% of PEC	$175,495	-
Start-up - 2% of PEC	$35,099	-
Initial Source Testing - 7 units x $15,000/unit	$105,000	-
Owner's Cost (No cost data provided)	-	-
Total Indirect Costs (IC)	**$578,836**	**$0**
Total Capital Investment (TCI) (DC + IC)	**$2,316,332**	**$1,585,469**
Contingencies - 15% of TCI of Equipment Cost	$347,450	-
TCI including Contingencies	**$2,663,782**	**$1,585,469**

Annualized Capital Cost for Carbon Adsorption Equipment

Annualized Capital Investment = Initial Capital Investment x Amortization Factor

Amortization Factor = $\left[\frac{0.1(1.1)^{10}}{(1.1)^{10}-1}\right]$ = 0.163 per District policy, amortizing over 10 years at 10%

Therefore,

Annualized Capital Investment for Carbon Adsorption Equipment = $2,663,782 x 0.163 = $434,196.

Annualized Cost for Carbon for System

The EPA Air Pollution Control Cost Manual, Sixth Edition (January 2002), Section 3.1: VOC Recapture Controls, Chapter 1: Carbon Adsorbers (September 1999)[7] states, "*A typical life for the carbon is five years. However, if the inlet contains VOCs that are very difficult to desorb, tend to polymerize, or react with other constituents, a shorter carbon lifetime— perhaps as low as two years—would be likely.*"

Assuming the maximum carbon life of five years and a 10% interest rate the capitol recovery cost for the carbon =

$\left[\frac{0.1(1.1)^{5}}{(1.1)^{5}-1}\right]$ = 0.264 over 5 years at 10% interest

Therefore,

Annualized Capital Investment for Carbon for System = $1,585,469 x 0.264 = $418,564

Annualized Cost of Carbon Adsorption Equipment + Annualized Cost of Carbon for System

Annualized Capital Cost for Carbon Adsorption System = $434,196 + $418,564 = $852,760

Total Operation and Maintenance Costs

The annual operation and maintenance costs for the carbon adsorption system are based on the information given in the EPA Air Pollution Control Cost Manual, Sixth Edition (January 2002), Section 3.1: VOC Recapture Controls, Chapter 1: Carbon Adsorbers (September 1999)[7]. No value will be given for the ethanol that may be potentially recovered since this ethanol could actually result in additional disposal costs, which will also not be quantified in this analysis.

[7] EPA Air Pollution Control Cost Manual, Sixth Edition (January 2002), Section 3.1: VOC Recapture Controls, Chapter 1: Carbon Adsorbers (September 1999). United States Environmental Protection Agency Office of Air Quality Planning and Standards. Research Triangle Park, North Carolina 27711. EPA/452/B-02-001. http://epa.gov/ttn/catc/dir1/cs3-1ch1.pdf.

Total Annual Costs for Carbon Adsorption

Carbon Adsorption Annual Costs			
Direct Annual Cost (DAC)			
Operating Labor			
Operator	0.5 hr/shift	$18.50/hr x 0.5 hr/shift x 3 shift/day x 90 days/year x 7 units	$17,483
Supervisor	15% of operator		$2,622
Maintenance			
Labor	0.5 h/shift	$18.50/hr x 0.5 hr/shift x 3 shift/day x 90 days/year x 7 units	$17,483
Maintenance	100% of labor		$17,483
Utility			
Steam	Not included at this time		$0
Cooling Water	Not included at this time		$0
Electricity	Not included at this time		$0
Total DC			**$55,071**
Indirect Annual Cost (IAC)			
Overhead	60% of Labor Cost	0.6 x ($17,483 + $2,622 + $17,483 + $17,483)	$33,043
Administrative	2% TCI (equipment cost + carbon cost)		$84,985
Property Taxes	1% TCI (equipment cost + carbon cost)		$42,492
Insurance	1% TCI (equipment cost + carbon cost)		$42,492
Annual Source Test	One representative test/year @ $15,000		$15,000
Total IC			**$218,012**
Annual Cost (DAC + IAC)			**$273,083**

Total Annual Cost = Carbon Adsorption Capital Cost + (Ductwork + CIP System) + Annual Cost
= $852,760+ $1,196,800 + $273,083
= $2,322,643

Emission Reductions

Annual Emission Reduction = Uncontrolled Emissions x 0.86
= 269,842 lb-VOC/year x 0.86 x ton/2,000 lb
= 116.0 tons-VOC/year

Cost Effectiveness

Cost Effectiveness = $2,322,643/year ÷ 116.0 tons-VOC/year
= $20,023/ton-VOC

The analysis demonstrates that the annualized purchase cost of the carbon adsorption system, collection system ductwork and CIP equipment, and annual costs alone results in a cost

effectiveness which exceeds the District's Guideline of $17,500/ton-VOC. Therefore this option is not cost-effective and will not be considered for this project.

Option 3 - Collection of VOCs and control by absorption (81% collection & control)

Design Basis

- The District contacted Maurice McIntosh and Ad Verkuylen of NohBell Corporation on March 16, 2016 to allow NohBell Corporation an opportunity to provide cost information for this project. The District did not receive updated cost information from NohBell Corporation; therefore, cost estimates from NohBell Corporation will not be included as a part of this BACT analysis.
- Recovered ethanol storage tank = $40,000/tank group (installed, as proposed in Project C-1133347)
- Connected electrical load for each unit is 2.5 horsepower which is assumed to operate continuously for 90 days.
- Electric power cost = $0.1579/kWh (see regenerative thermal oxidizer Top Down BACT Analysis section above)
- Since the EPA Control Cost Manual does not contain a section for wet scrubbers controlling VOCs, conservatively, the costs in addition to the base equipment costs, will be estimated from the Wet Scrubbers for Particulate Matter control from the EPA Control Cost Manual.

Equipment Cost Scrubber

The total capital investment cost for a scrubber (absorption technology) was provided by Anguil Environmental Systems on November 13, 2015 as follows:

Tank I.D.	ATC #	Anguil Cost
T-1 thru T-16	N-266-822-0 thru -837-0	$300,000
T-17 thru T-44	N-266-838-0 thru -865-0	$315,000
T-45 thru T-64	N-266-866-0 thru -885-0	$230,000
T-65 thru T-84	N-266-886-0 thru -905-0	$230,000
T-85 thru T-94	N-266-906-0 thru -915-0	$180,000
T-95 thru T-108	N-266-916-0 thru -929-0	$220,000
T-109 thru T-128	N-266-930-0 thru -949-0	$220,000
Total		$1,695,000

Scrubber Capital Cost	
Cost Description	Cost ($)
Refrigerated Scrubber Systems (seven units)	$1,695,000
The following cost data is taken from EPA Control Cost Manual, Sixth Edition (EPA/452/B-02-001).	
Direct Costs	
Base Equipment Costs (Scrubber Systems) See Above	$1,695,000
Instrumentation - 10% of base equipment	$169,500
Sales Tax - 4.3125% of base equipment	$73,097
Freight - 5% of base equipment	$84,750
Purchased equipment cost (PEC)	**$2,022,347**
Foundations & supports – 6% of PEC	$121,341
Handling & erection - 40% of PEC	$808,939
Electrical - 1% of PEC	$20,223
Piping - accounted for in ductwork cost	-
Painting - 1% of PEC	$20,223
Insulation - 3% of PEC	$60,670
PCL/Programming - 7 units x $10,000	$70,000
Recovered Ethanol Storage Tank (installed) ($40,000 x 7 tank groups)	$280,000
Direct Installation Costs (DIC)	**$1,381,396**
Total Direct Costs (DC) (PEC + DIC)	**$3,403,743**
Indirect Costs	
Engineering - 10% of PEC	$202,235
Construction and field expenses - 10% of PEC	$202,235
Contractor fees - 10% of PEC	$202,235
Start-up - 1% of PEC	$20,223
Initial Source Testing - 7 units x $15,000/unit	$105,000
Owner's Cost (No cost data provided)	-
Total Indirect Costs (IC)	**$731,928**
Subtotal Capital Investment (SCI) (DC + IC)	**$4,135,671**
Contingencies - 15% of SCI	$620,351
Total Capital Investment (TCI) (SCI + Contingency)	**$4,756,022**

Annualized Capital Costs

Annualized Capital Investment = Initial Capital Investment x Amortization Factor

Amortization Factor = $\left[\frac{0.1(1.1)^{10}}{(1.1)^{10}-1}\right]$ = 0.163 per District policy, amortizing over 10 years at 10%

Therefore,

Annualized Capital Investment = $4,756,022 x 0.163 = $775,232

Wastewater Disposal Costs

Additionally, the water scrubber will generate ethanol-laden wastewater containing 109.3 tons-ethanol annually (269,842 lb/year (uncontrolled fermentation emissions) x 0.81 ÷ 2000). Assuming a 10% solution, approximately 330,211 gallons of waste water (109.3 ton-ethanol x 2000 lb/ton x gal/6.62 lb ÷ 0.10) will be generated annually. Per Project C-1133347, an allowance of $0.08 per gallon (not including inflation) is applied for disposal costs.

Annual disposal costs = 330,211 gallons x $0.08/gallon = $26,417.

Total Operation and Maintenance Costs

Scrubber Annual Costs			
Direct Annual Cost (DAC)			
Operating Labor			
Operator	0.5 hr/shift	$18.50/hr x 0.5 hr/shift x 3 shift/day x 90 days/year x 7 units	$17,483
Supervisor	15% of operator		$2,622
Maintenance			
Labor	0.5 h/shift	$18.50/hr x 0.5 hr/shift x 3 shift/day x 90 days/year x 7 units	$17,483
Maintenance	100% of labor		$17,483
Utility			
Natural Gas			$0
Electricity	7 units x 2.5 hp x 0.746 kW/hp x 90 days/year x 24 hr/day = 28,199 kWh/yr	$0.1579/kWh	$4,453
Total DAC			**$59,524**
Indirect Annual Cost (IAC)			
Overhead	60% of Labor Cost	0.6 x ($17,483 + $2,622 + $17,483 + $17,483)	$33,043
Administrative	2% TCI		$95,120
Property Taxes	1% TCI		$47,560
Insurance	1% TCI		$47,560
Annual Source Test	One representative test/year @ $15,000		$15,000
Total IAC			**$238,283**
Annual Cost (DAC + IAC)			**$297,807**

Total Annual Cost = Scrubber System + (Ductwork + CIP System) + Wastewater Disposal + Annual Cost
= $775,232 + $1,196,800 + $26,417 + $297,807
= $2,296,256

Emission Reductions

The District's BACT Guideline identifies an overall collection and control efficiency of 81% for absorption systems.

Annual Emission Reduction = Uncontrolled Emissions x 0.81
= 269,842 lb-VOC/year x 0.81/2,000 lb
= 109.3 lb-VOC/year

Cost Effectiveness

Cost Effectiveness = Total Annual Cost ÷ Annual Emission Reductions

Cost Effectiveness = $2,296,256/year ÷ 109.3 tons-VOC/year
= $21,009/ton-VOC

The analysis demonstrates that the annualized purchase cost of the water scrubber, collection system ductwork and CIP equipment and annual costs alone results in a cost effectiveness which exceeds the District's Guideline of $17,500/ton-VOC. Therefore this option is not cost-effective and will not be considered for this project.

Option 4 - Capture of VOCs and condensation (81% collection & control)

Design Basis

- Although the EcoPAS LLC (EcoPAS) condenser (PAS-100) units have not been demonstrated at the scale of operation as proposed by this project, the District will conservatively assume that the equipment and cost proposed by EcoPAS will meet the duty requirements for the project.
- A glycol chiller would be required for this operation; however, a cost to modify the winery chilling system was not provided. Therefore, the final cost analysis does not include the cost of a glycol chiller, which would be required to operate the system.
- This control technology recovers ethanol which potentially requires additional cost to dispose of. The District currently knows of two winery facilities that recover ethanol: Central Coast Wine Services in and Terravant Winery, both within Santa Barbara County. Information from the Santa Barbara County APCD indicates that neither facility generates any revenue from the recovered ethanol. Central Coast Wine Services sends their recovered ethanol to a facility in San Luis Obispo that refines the recovered ethanol into motor vehicle fuels and Terravant Winery utilizes a UV system to destroy the ethanol. Although EcoPAS claims that there is value in the recovered ethanol in a future market that may be developed; the District will conservatively assume that there is no cost required to dispose/treat the recovered ethanol nor is there a value in the recovered ethanol.

Equipment Cost Refrigerated Condenser

Due to the large number of winery tanks in this project and the large volume of those tanks, it is necessary to use multiple PAS-100 units to control the emissions from each tank group. Pricing for the PAS-100 units will be based on project specific pricing received from EcoPAS on March 28, 2016.

In addition to the base equipment cost (as referred to as CapEx by EcoPAS), EcoPAS provided additional cost for stainless steel ducting, installation cost (which includes hoses, capture vessels, pressure release valves, instrumentation, freight, taxes, and engineering) and annual cost (which includes both direct and indirect costs, labor, testing, maintenance, overhead and administration). The District has requested a detailed breakdown of the cost of each component of each cost category from the vendor but has yet to receive the additional information; therefore, the base equipment cost will be used as provided by the vendor and remaining costs associated with the installation of refrigerated condensers will be taken from other sources such as the Eichleay Report and the EPA Control Cost Manual, Sixth Edition (EPA/452/B-02-001).

Condensation	
Cost Description	Cost ($)
Cost of Refrigerated Condenser system (42 PAS-100 Units)	$8,190,000
The following cost data is taken from EPA Control Cost Manual, Sixth Edition (EPA/452/B-02-001).	
Direct Costs	
Base Equipment Costs (Condenser) See Above	$8,190,000
Instrumentation - 10% of base equipment	$819,000
Sales Tax - 4.3125% of base equipment	$353,194
Freight - 5% of base equipment	$409,500
Purchased equipment cost (PEC)	**$9,771,694**
Foundations & supports - 14% of PEC	$1,368,037
Handling & erection - 8% of PEC	$781,736
Electrical - 8% of PEC	$781,736
Piping - accounted for in ductwork cost	-
Painting - 1% of PEC	$97,717
Insulation - 10% of PEC	$977,169
PCL/Programming - 42 units x $10,000	$420,000
Direct installation costs (DIC)	**$4,426,395**
Total Direct Costs (DC) (PEC + DIC)	**$14,198,089**
Indirect Costs	
Engineering - 10% of PEC	$977,169
Construction and field expenses - 5% of PEC	$488,585
Contractor fees - 10% of PEC	$977,169
Start-up - 2% of PEC	$195,434
Source Testing - 42 units x $15,000/unit	$630,000
Owner's Cost (No cost data provided)	-
Total Indirect Costs (IC)	**$3,268,357**
Subtotal Capital Investment (SCI) (DC + IC)	**$17,466,446**
Contingencies - 15% of SCI	$2,619,967
Total Capital Investment (TCI) (SCI + Contingency)	**$20,086,413**

Annualized Capital Costs

Annualized Capital Investment = Initial Capital Investment x Amortization Factor

Amortization Factor = $\left[\frac{0.1(1.1)^{10}}{(1.1)^{10}-1}\right]$ = 0.163, amortizing over 10 years at 10%

Therefore,

Annualized Capital Investment = $20,086,413 x 0.163 = $3,274,085

Total Operation and Maintenance Costs

Condensation Annual Costs			
Direct Annual Cost (DAC)			
Operating Labor			
Operator	0.5 hr/shift	$18.50/hr x 0.5 hr/shift x 3 shift/day x 90 days/year x 42 units	$104,895
Supervisor	15% of operator		$15,734
Maintenance			
Labor	0.5 h/shift	$18.50/hr x 0.5 hr/shift x 3 shift/day x 90 days/year x 42 units	$104,895
Maintenance	100% of labor		$104,895
Chiller (Glycol)			
Not included at this time			-
Utility (Electricity)			
Not included at this time			-
Total DAC			**$330,419**
Indirect Annual Cost (IAC)			
Overhead	60% of Labor Cost	0.6 x ($104,895 + $15,734 + $104,895 + $104,895)	$198,251
Administrative	2% TCI		$401,728
Property Taxes	1% TCI		$200,864
Insurance	1% TCI		$200,864
Total IAC			**$1,001,707**
Annual Cost (DAC + IAC)			**$1,332,126**

Total Annual Cost = Condenser System+ (Ductwork + CIP System) + Annual Costs
= $3,152,525 + $1,196,800 + $1,332,126
= $5,681,451

Emission Reductions

The District's BACT Guideline identifies an overall collection and control efficiency of 81% for absorption systems.

Annual Emission Reduction = Uncontrolled Emissions x 0.81
= 269,842 lb-VOC/year x 0.81/2,000 lb
= 109.3 lb-VOC/year

Cost Effectiveness

Cost Effectiveness = Total Annual Cost ÷ Annual Emission Reductions

Cost Effectiveness = $5,681,451/year ÷ 109.3 tons-VOC/year
= $51,980/ton-VOC

The analysis demonstrates that the annualized purchase cost of the refrigerated condenser system, collection system ductwork and CIP equipment and annual costs alone results in a cost effectiveness which exceeds the District's Guideline of $17,500/ton-VOC. Therefore this option is not cost-effective and will not be considered for this project.

Option 5 - Temperature Controlled Open Top Tank with Maximum Average Fermentation Temperature of 95 deg F)

The only remaining control option in step 3 above has been deemed AIP for this class and category of source and per the District BACT policy is required regardless of the cost. Therefore, a cost effectiveness analysis is not required.

Step 5 – Select BACT

All identified feasible options with control efficiencies higher than the option proposed by the facility have been shown to not be cost effective. The facility has proposed Option 1, temperature-controlled open top tank with maximum average fermentation temperature of 95 deg F. These BACT requirements will be placed on the permits as enforceable conditions.

Attachment B1

Ducting Layout Diagrams and Ducting Cost Estimates

1) The tanks in this and other diagrams are graphically shown as the same size for convenience of the spread sheet layout. The numbers in the cells around the tank layout reflect spacing and tank dimensions from the data base and Delicato lay out drawing.

2) Red dashed line is the most probable duct routing.

3) All tanks are rated for fermentation and storage.

4) At the time of this BACT analysis tank numbers were not shown on the Lay out drawing. The tank numbers shown in this and other parts of this analysis are subject to change.

5) Main ducts set at about 10 feet above



Diameter in Feet	25.00
Shell Height in Feet	40.00

Notes	Beginning Tank Numbers	Ending Tank Numbers	Length Between Nodes	From Top Tank Connection to Main Duct Length in Feet	Design Duct Velocity from Eichleay Feet/Second	Gas Flow Rate Storage Fill	Fermentation CFM at maximum CO2 rate from kinetic model	Duct size diameter in inches at node	Nominal Duct Size diameter in inches (See comments)	Number of Tanks feeding Ending Node	Total Number of Tanks to connect	Total feet	Cost Per Foot from Eichleay (See Comments)	Cost	Comments
Note 1: Tank Connection to Main Ducting. Red fermentation, white fermentation, and storage can be done in each tank.															
	Note 1	Note 1	Note 3	60	40	Note 2	793	7.79	8.00		16	960	$103.25	$99,122	

Note 2: All tanks are for Red Fermentation, White Fermentation, and Storage. Red Fermentation gas flow rates are used for the BACT analysis. Storage flows are shown on the storage flow tab for information only on a per tank bases.

Note 3: The length between nodes is the distance between the center of the circle representing the tank and its adjacent tank. Refer to tank number columns for location.

	Beginning Tank Numbers	Ending Tank Numbers	Length Between Nodes	From Top Tank Connection to Main Duct Length in Feet	Design Duct Velocity from Eichleay Feet/Second	Gas Flow Rate Storage Fill	Fermentation CFM at maximum CO2 rate from kinetic model	Duct size diameter in inches at node	Nominal Duct Size diameter in inches (See comments)	Number of Tanks feeding Ending Node	Total Number of Tanks to connect	Total feet	Cost Per Foot from Eichleay (See Comments)	Cost	Comments
Note 4: Tanks T-1 through T-16	T-1/T-2	T-3/T-4	31.33	Note 5	40	Note 2	1,587	11.01	12.00	2	16	31.33	$143.83	$4,506.09	
	T-3/T-4	T-5/T-6	31.33	Note 5	40	Note 2	3,174	15.57	16.00	4		31.33	$204.52	$6,407.64	
Note 5: The top of tank ducting to the main duct is calculated in row 2.															
	T-5/T-6	T-7/T-8	31.33	Note 5	40	Note 2	4,760	19.07	20.00	6		31.33	$309.38	$9,692.72	
	T-7/T-8	●	68.46	Note 5	40	Note 2	6,347	22.02	22.00	8		68.46	$306.44	$20,978.27	
	T-9/T-10	T-11/T-12	31.33	Note 5	40	Note 2	1,587	11.01	12.00	2		31.33	$143.83	$4,506.09	
	T-11/T-12	T-13/T-14	31.33	Note 5	40	Note 2	3,174	15.57	16.00	4		31.33	$204.52	$6,407.64	
	T-13/T-14	T-15/T-16	31.33	Note 5	40	Note 2	4,760	19.07	20.00	6		31.33	$309.38	$9,692.72	
	T-15/T-16	●	68.46	Note 5	40	Note 2	6,347	22.02	22.00	8		68.46	$306.44	$20,978.27	
	●	Emission Controls	75.00	Note 5	40	Note 2	12,695	31.14	32.00	16		75.00	$476.73	$35,754.75	
													Sum	$118,924	

Redundant Main Duct for CIP on Fermenters Only	$0	
1 Knock drums (7000 gallons) for foam overs on fermenters	$46,300	Eichleay
Ducting Isolation Components for all tanks	$42,000	Previous Work
The main process pipe ways will need some modification to support the emission ducting systems.	$60,000	Allowance

Ducting Cost	$306,346
Support Allowance	$60,000
Total	$366,346

1) The tanks in this and other diagrams are graphically shown as the same size for convenience of the spread sheet layout. The numbers in the cells around the tank layout reflect spacing and tank dimensions from the data base and Delicato lay out drawing.

2) Red dashed line is the most probable duct routing

3) All tanks are rated for fermentation and storage.

4) At the time of this BACT analysis tank numbers were not shown on the Lay out drawing. The tank numbers shown in this and other parts of this analysis are subject to change.

5) Main ducts set at about 10 feet above ground.



Notes	Beginning Tank Numbers	Ending Tank Numbers	Length Between Nodes	From Top Tank Connection to Main Duct Length in Feet	Design Duct Velocity from Eichleay Feet/Second	Gas Flow Rate Storage Fill	Fermentation CFM at maximum CO2 rate from kinetic model	Duct size diameter in inches at node	Nominal Duct Size diameter in inches (See comments)	Number of Tanks feeding Ending Node	Total Number of Tanks to connect	Total feet	Cost Per Foot from Eichleay (See Comments)	Cost	Comments
Note 1: Tank Connection to Main Ducting. Red fermentation, white fermentation, and storage can be done in each tank.															
	Note 1	Note 1	Note 3	56	40	Note 2	530.66	6.37	8.00		28	1,568	$103.25	$161,899.19	

Note 2: All tanks are for Red Fermentation, White Fermentation, and Storage. Red Fermentation gas flow rates are used for the BACT analysis. Storage flows are shown on the storage flow tab for information only on a per tank bases.

Note 3: The length between nodes is the distance between the center of the circle representing the tank and its adjacent tank. Refer to tank number columns for location.

	Beginning Tank Numbers	Ending Tank Numbers	Length Between Nodes	From Top Tank Connection to Main Duct Length in Feet	Design Duct Velocity from Eichleay Feet/Second	Gas Flow Rate Storage Fill	Fermentation CFM at maximum CO2 rate from kinetic model	Duct size diameter in inches at node	Nominal Duct Size diameter in inches (See comments)	Number of Tanks feeding Ending Node	Total Number of Tanks to connect	Total feet	Cost Per Foot from Eichleay (See Comments)	Cost	Comments
Note 4: Tanks T-17 through T-44	T-27/T-28	T-26/T-25	25.00	Note 5	40	Note 2	1,061	9.00	10.00	2	28	25.00	$144.33	$3,608.33	
	T-26/T-25	T-24/T-23	25.50	Note 5	40	Note 2	2,123	12.73	14.00	4		25.50	$174.17	$4,441.43	
Note 5: The top of tank ducting to the main duct is calculated in row 2.	T-24/T-23	T-22/T-21	25.00	Note 5	40	Note 2	3,184	15.60	16.00	6		25.00	$204.52	$5,113.02	
	T-22/T-21	T-20/T-19	25.50	Note 5	40	Note 2	4,245	18.01	18.00	8		25.50	$251.38	$6,410.13	
	T-20/T-19	T-17/T-18	25.00	Note 5	40	Note 2	5,307	20.13	20.00	10		25.00	$309.38	$7,734.38	
	T-17/T-18		20.50	Note 5	40	Note 2	6,368	22.06	22.00	12		20.50	$306.44	$6,282.02	
	T-44/T-43	T-41/T-42	25.00	Note 5	40	Note 2	1,061	9.00	10.00	2		25.00	$144.33	$3,608.33	
	T-41/T-42	T-39/T-40	25.50	Note 5	40	Note 2	2,123	12.73	14.00	4		25.50	$174.17	$4,441.43	
	T-39/T-40	T-37/T-38	25.00	Note 5	40	Note 2	3,184	15.60	16.00	6		25.00	$204.52	$5,113.02	
	T-37/T-38	T-35/T-36	25.50	Note 5	40	Note 2	4,245	18.01	18.00	8		25.50	$251.38	$6,410.13	
	T-35/T-36	T-33/T-34	25.00	Note 5	40	Note 2	5,307	20.13	22.00	10		25.00	$306.44	$7,661.00	
	T-33/T-34	T-32/T-31	25.50	Note 5	40	Note 2	6,368	22.06	22.00	12		25.50	$306.44	$7,814.22	
	T-32/T-31	T-29/T-30	25.00	Note 5	40	Note 2	7,429	23.82	24.00	14		25.00	$397.67	$9,941.67	
	T-29/T-30		117.58	Note 5	40	Note 2	8,490	25.47	26.00	16		117.58	$397.67	$46,758.84	
		Emission Controls	75.00	Note 5	40	Note 2	14,858	33.69	34.00	28		75.00	$476.73	$35,754.75	
													Sum	$161,093	

Redundant Main Duct for CIP on Fermenters Only		$0	
1 Knock drums (7000 gallons) for foam overs on fermenters		$46,300	Eichleay
Ducting Isolation Components for all tanks with redundant main (X2)		$73,500	Previous Work
The main process pipe ways will need some modification to support the emission ducting systems.		$60,000	Allowance
Ducting Cost		$442,792	
Support Allowance		$60,000	
	Total	**$502,792**	

1) The tanks in this and other diagrams are graphically shown as the same size for convenience of the spread sheet layout. The numbers in the cells around the tank layout reflect spacing and tank dimensions from the data base and Delicato lay out drawing.

2) Red dashed line is the most probable duct routing.

3) All tanks are rated for fermentation and storage.

4) At the time of this BACT analysis tank numbers were not shown on the Lay out drawing. The tank numbers shown in this and other parts of this analysis are subject to change.

5) Main ducts set at about 10 feet above ground.



Notes	Beginning Tank Numbers	Ending Tank Numbers	Length Between Nodes	From Top Tank Connection to Main Duct Length in Feet	Design Duct Velocity from Eichleay Feet/Second	Gas Flow Rate Storage Fill	Fermentation CFM at maximum CO2 rate from kinetic model	Duct size diameter in inches at node	Nominal Duct Size diameter in inches (See comments)	Number of Tanks feeding Ending Node	Total Number of Tanks to connect	Total feet	Cost Per Foot from Eichleay (See Comments)	Cost	Comments
Note 1: Tank Connection to Main Ducting. Red fermentation, white fermentation, and storage can be done in each tank.															
	Note 1	Note 1	Note 3	48.0	40	Note 2	309	4.86	6.00		50	2,400	$62.17	$149,210	

Note 2: All tanks are for Red Fermentation, White Fermentation, and Storage. Red Fermentation gas flow rates are used for the BACT analysis. Storage flows are shown on the storage flow tab for information only on a per tank bases.

Note 3: The length between nodes is the distance between the center of the circle representing the tank and its adjacent tank. Refer to tank number columns for location.

	Beginning Tank Numbers	Ending Tank Numbers	Length Between Nodes	From Top Tank Connection to Main Duct Length in Feet	Design Duct Velocity from Eichleay Feet/Second	Gas Flow Rate Storage Fill	Fermentation CFM at maximum CO2 rate from kinetic model	Duct size diameter in inches at node	Nominal Duct Size diameter in inches (See comments)	Number of Tanks feeding Ending Node	Total Number of Tanks to connect	Total feet	Cost Per Foot from Eichleay (See Comments)	Cost	Comments
Note 4: Tanks T-45 through T-94	T-93/T-94	T-91/T-92	23.00	Note 5	40	Note 2	618	6.87	8.00	2	10	23	$103.25	$2,374.80	
	T-91/T-92	T-89/Y-90	22.50	Note 5	40	Note 2	1,236	9.72	10.00	4		23	$144.33	$3,247.50	
Note 5: The top of tank ducting to the main duct is calculated in row 2.	T-89/Y-90	T-87/T-88	22.50	Note 5	40	Note 2	1,855	11.90	12.00	6		23	$143.83	$3,236.10	
	T-87/T-88	T-85/T-86	22.50	Note 5	40	Note 2	2,473	13.74	14.00	8		23	$174.17	$3,918.91	
	T-85/T-86	Emission Controls	75.00	Note 5	40	Note 2	3,091	15.37	16.00	10		75	$204.52	$15,339.06	
													Sum	$28,116.37	

Redundant Main Duct for CIP on Fermenters Only		$0	
1 Knock drums (7000 gallons) for foam overs on fermenters		$46,300	Eichleay
Ducting Isolation Components for all tanks with redundant main (X2)		$26,250	Previous Work
The main process pipe ways will need some modification to support the emission ducting systems		$60,000	Allowance
Ducting Cost		$100,666	
Support Allowance		$60,000	
	Total	**$160,666**	

Beginning Tank Numbers	Ending Tank Numbers	Length Between Nodes	From Top Tank Connection to Main Duct Length in Feet	Design Duct Velocity from Eichleay Feet/Second	Gas Flow Rate Storage Fill	Fermentation CFM at maximum CO2 rate from kinetic model	Duct size diameter in inches at node	Nominal Duct Size diameter in inches (See comments)	Number of Tanks feeding Ending Node	Total Number of Tanks to connect	Total feet	Cost Per Foot from Eichleay (See Comments)	Cost	Comments
T-83/T-84	T-81/T-82	22.50	Note 5	40	Note 2	618	6.87	8.00	2	20	23	$103.25	$2,323.17	
T-81/T-82	T-79/T-80	22.50	Note 5	40	Note 2	1,236	9.72	10.00	4		23	$144.33	$3,247.50	
T-79/T-80	T-77/T-78	22.50	Note 5	40	Note 2	1,855	11.90	12.00	6		23	$143.83	$3,236.10	
T-77/T-78	T-75/T-76	22.50	Note 5	40	Note 2	2,473	13.74	14.00	8		23	$174.17	$3,918.91	
T-75/T-76	T-73/T-74	22.50	Note 5	40	Note 2	3,091	15.37	16.00	10		23	$204.52	$4,601.72	
T-73/T-74	T-71/T-72	22.50	Note 5	40	Note 2	3,709	16.83	18.00	12		23	$251.38	$5,656.00	
T-71/T-72	T-69/T-70	22.50	Note 5	40	Note 2	4,328	18.18	20.00	14		23	$309.38	$6,960.94	
T-69/T-70	T-67/T-68	22.50	Note 5	40	Note 2	4,946	19.44	20.00	16		23	$309.38	$6,960.94	
T-67/T-68	T-65/T-66	22.50	Note 5	40	Note 2	5,564	20.62	22.00	18		23	$306.44	$6,894.90	
T-65/T-66	Emission Controls	75.00	Note 5	40	Note 2	6,182	21.73	22.00	20		75	$306.44	$22,983.00	
												Sum	$66,783.17	

Redundant Main Duct for CIP on Fermenters Only		$0	
1 Knock drums (7000 gallons) for foam overs on fermenters		$46,300	Eichleay
Ducting Isolation Components for all tanks with redundant main (X2)		$52,500	Previous Work
The main process pipe ways will need some modification to support the emission ducting systems		$80,000	Allowance
	Ducting Cost	$165,583	
	Support Allowance	$80,000	
	Total	**$245,583**	

Beginning Tank Numbers	Ending Tank Numbers	Length Between Nodes	From Top Tank Connection to Main Duct Length in Feet	Design Duct Velocity from Eichleay Feet/Second	Gas Flow Rate Storage Fill	Fermentation CFM at maximum CO2 rate from kinetic model	Duct size diameter in inches at node	Nominal Duct Size diameter in inches (See comments)	Number of Tanks feeding Ending Node	Total Number of Tanks to connect	Total feet	Cost Per Foot from Eichleay (See Comments)	Cost	Comments
T-45/T-46	T-47/T-48	22.50	Note 5	40	Note 2	618	6.87	8.00	2	20	23	$103.25	$2,323.17	
T-47/T-48	T-49/T-50	22.50	Note 5	40	Note 2	1,236	9.72	10.00	4		23	$144.33	$3,247.50	
T-49/T-50	T-51/T-52	22.50	Note 5	40	Note 2	1,855	11.90	12.00	6		23	$143.83	$3,236.10	
T-51/T-52	T-53/T-54	22.50	Note 5	40	Note 2	2,473	13.74	14.00	8		23	$174.17	$3,918.91	
T-53/T-54	T-55/T-56	22.50	Note 5	40	Note 2	3,091	15.37	16.00	10		23	$204.52	$4,601.72	
T-55/T-56	T-57/T-58	22.50	Note 5	40	Note 2	3,709	16.83	18.00	12		23	$251.38	$5,656.00	
T-57/T-58	T-59/T-60	22.50	Note 5	40	Note 2	4,328	18.18	20.00	14		23	$309.38	$6,960.94	
T-59/T-60	T-61/T-62	22.50	Note 5	40	Note 2	4,946	19.44	20.00	16		23	$309.38	$6,960.94	
T-61/T-62	T-63/T-64	22.50	Note 5	40	Note 2	5,564	20.62	22.00	18		23	$306.44	$6,894.90	
T-63/T-64	Emission Controls	75.00	Note 5	40	Note 2	6,182	21.73	22.00	20		75	$306.44	$22,983.00	
												Sum	$66,783.17	

Redundant Main Duct for CIP on Fermenters Only		$0	
1 Knock drums (7000 gallons) for foam overs on fermenters		$46,300	Eichleay
Ducting Isolation Components for all tanks with redundant main		$52,500	Previous Work
The main process pipe ways will need some modification to support the emission ducting systems		$80,000	Allowance

Sum of All Main Ducts This Tab	**$651,832**
Sum of All 50 Tank Connections	**$149,210**
Grand Total This Tab	**$801,042**

Ducting Cost		**$165,583**
Support Allowance		**$80,000**
	Total	$245,583

1) The tanks in this and other diagrams are graphically shown as the same size for convenience of the spread sheet layout. The numbers in the cells around the tank layout reflect spacing and tank dimensions from the data base and Delicato lay out drawing.

2) Red dashed line is the most probable duct routing

3) All tanks are rated for fermentation and storage.

4) At the time of this BACT analysis tank numbers were not shown on the Lay out drawing. The tank numbers shown in this and other parts of this analysis are subject to change.

5) Main ducts set at about 10 feet above ground.



Diameter in Feet	21.00
Shell Height in Feet	28.00
Main Duct Connection Length in Feet	75.00

Total tanks in bubble this sketch 14

Notes	Beginning Tank Numbers	Ending Tank Numbers	Length Between Nodes	From Top Tank Connection to Main Duct Length in Feet	Design Duct Velocity from Eichleay Feet/Second	Gas Flow Rate Storage Fill	Fermentation CFM at maximum CO2 rate from kinetic model	Duct size diameter in inches at node	Nominal Duct Size diameter in inches (See comments)	Number of Tanks feeding Ending Node	Total Number of Tanks to connect	Total feet	Cost Per Foot from Eichleay (See Comments)	Cost	Comments
Note 1: Tank Connection to Main Ducting. Red fermentation, white fermentation, and storage can be done in each tank.															
	Note 1	Note 1	Note 3	46.0	40	Note 2	381	5.40	6.00		14	644	$62.17	$40,037.95	

Note 2: All tanks are for Red Fermentation, White Fermentation, and Storage. Red Fermentation gas flow rates are used for the BACT analysis. Storage flows are shown on the storage flow tab for information only on a per tank bases.

Note 3: The length between nodes is the distance between the center of the circle representing the tank and its adjacent tank. Refer to tank number columns for location.

	Beginning Tank Numbers	Ending Tank Numbers	Length Between Nodes	From Top Tank Connection to Main Duct Length in Feet	Design Duct Velocity from Eichleay Feet/Second	Gas Flow Rate Storage Fill	Fermentation CFM at maximum CO2 rate from kinetic model	Duct size diameter in inches at node	Nominal Duct Size diameter in inches (See comments)	Number of Tanks feeding Ending Node	Total Number of Tanks to connect	Total feet	Cost Per Foot from Eichleay (See Comments)	Cost	Comments
Note 4: Tanks T-95 through T-108	T-95	T-96	26.50	Note 5	40	Note 2	381	5.40	6.00	1	14	27	$62.17	$1,647.52	
	T-96	T-97	26.50	Note 5	40	Note 2	762	7.63	8.00	2		27	$103.25	$2,736.18	
Note 5: The top of tank ducting to the main duct is calculated in row 2.															
	T-97	T-98	26.50	Note 5	40	Note 2	1,144	9.35	10.00	3		27	$144.33	$3,824.83	
	T-98	T-99/T-100	26.50	Note 5	40	Note 2	1,525	10.79	12.00	4		27	$143.83	$3,811.41	
	T-99/T-100	T-101/T-103	26.50	Note 5	40	Note 2	2,287	13.22	14.00	6		27	$174.17	$4,615.60	
	T-101/T-103	T-103/T-104	26.50	Note 5	40	Note 2	3,050	15.26	16.00	8		27	$204.52	$5,419.80	
	T-103/T-104	T-105/T-106	26.50	Note 5	40	Note 2	3,812	17.07	18.00	10		27	$251.38	$6,661.51	
	T-105/T-106	T-107/T-108	26.50	Note 5	40	Note 2	4,575	18.69	20.00	12		27	$309.38	$8,198.44	
	T-107/T-108	Emission Controls	75.00	Note 5	40	Note 2	5,337	20.19	22.00	14		75	$306.44	$22,983.00	
													Sum	$59,898.30	

Redundant Main Duct for CIP on Fermenters Only	$0	
1 Knock drums (7000 gallons) for foam overs on fermenters	$46,300	Eichleay
Ducting Isolation Components for all tanks with redundant main (X2)	$36,750	Previous Work
The main process pipe ways will need some modification to support the emission ducting systems	$60,000	Allowance
Ducting Cost	$182,986	
Support Allowance	$60,000	
Total	**$242,986**	

1) The tanks in this and other diagrams are graphically shown as the same size for convenience of the spread sheet layout. The numbers in the cells around the tank layout reflect spacing and tank dimensions from the data base and Delicato lay out drawing.

2) Red dashed line is the most probable duct routing.

3) All tanks are rated for fermentation and storage.

4) At the time of this BACT analysis tank numbers were not shown on the Lay out drawing. The tank numbers shown in this and other parts of this analysis are subject to change.

5) Main ducts set at about 10 feet above ground.

Total tanks in bubble this sketch 20



Diameter in Feet 18.00

Shell Height in Feet 32.00

48.00 Center to Center of Tanks in Feet (Typical)

Main Duct Connection Length in Feet 75.00

CIP and **Emission Control Units**

Notes	Beginning Tank Numbers	Ending Tank Numbers	Length Between Nodes	From Top Tank Connection to Main Duct Length in Feet	Design Duct Velocity from Eichleay Feet/Second	Gas Flow Rate Storage Fill	Fermentation CFM at maximum CO2 rate from kinetic model	Duct size diameter in inches at node	Nominal Duct Size diameter in inches (See comments)	Number of Tanks feeding Ending Node	Total Number of Tanks to connect	Total feet	Cost Per Foot from Eichleay (See Comments)	Cost	Comments
Note 1: Tank Connection to Main Ducting. Red fermentation, white fermentation, and storage can be done in each tank.															
	Note 1	Note 1	Note 3	55.0	40	Note 2	258	4.44	6.00		20	1,100	$62.17	$68,387.80	

Note 2: All tanks are for Red Fermentation, White Fermentation, and Storage. Red Fermentation gas flow rates are used for the BACT analysis. Storage flows are shown on the storage flow tab for information only on a per tank bases.

Note 3: The length between nodes is the distance between the center of the circle representing the tank and its adjacent tank. Refer to tank number columns for location.

	Beginning Tank Numbers	Ending Tank Numbers	Length Between Nodes	From Top Tank Connection to Main Duct Length in Feet	Design Duct Velocity from Eichleay Feet/Second	Gas Flow Rate Storage Fill	Fermentation CFM at maximum CO2 rate from kinetic model	Duct size diameter in inches at node	Nominal Duct Size diameter in inches (See comments)	Number of Tanks feeding Ending Node	Total Number of Tanks to connect	Total feet	Cost Per Foot from Eichleay (See Comments)	Cost	Comments
Note 4: Tanks T-109 through T-128	T-109/T-110	T-111/T-112	19.50	Note 5	40	Note 2	515	6.27	8.00	2	16	20	$103.25	$2,013.41	
	T-111/T-112	T-113/T-114	19.50	Note 5	40	Note 2	1,030	8.87	10.00	4		20	$144.33	$2,814.50	
Note 5: The top of tank ducting to the main duct is calculated in row 2.	T-113/T-114	T-115/T-116	19.50	Note 5	40	Note 2	1,546	10.87	12.00	6		20	$143.83	$2,804.62	
	T-115/T-116	T-117/T-118	19.50	Note 5	40	Note 2	2,061	12.55	14.00	8		20	$174.17	$3,396.39	
	T-117/T-118	T-119/T-120	19.50	Note 5	40	Note 2	2,576	14.03	14.00	10		20	$174.17	$3,396.39	
	T-119/T-120	T-121/T-122	19.50	Note 5	40	Note 2	3,091	15.37	16.00	12		20	$204.52	$3,988.16	
	T-121/T-122	T-123/T-124	19.50	Note 5	40	Note 2	3,606	16.60	18.00	14		20	$251.38	$4,901.87	
	T-123/T-124	T-125/T-126	19.50	Note 5	40	Note 2	4,122	17.74	18.00	16		20	$251.38	$4,901.87	
	T-125/T-126	T-127/T-128	19.50	Note 5	40	Note 2	4,637	18.82	20.00	18		20	$309.38	$6,032.81	
	T-127/T-128	Emission Controls	75.00	Note 5	40	Note 2	5,152	19.84	20.00	20		75	$309.38	$23,203.13	
													Sum	$57,453.14	

Redundant Main Duct for CIP on Fermenters Only	$0	
1 Knock drums (7000 gallons) for foam overs on fermenters	$46,300	Eichleay
Ducting Isolation Components for all tanks with redundant main (X1)	$52,500	Previous Work
The main process pipe ways will need some modification to support the emission ducting systems	$60,000	Allowance

Ducting Cost	$224,641
Support Allowance	$60,000
Total	$284,641

Attachment B2

Comparison of Stainless Steel Ducting Costs

Ducting/Piping Cost Comparison

Duct Size Diameter (in.)	2"	3"	4"	6"	8"	10"	12"	14"	16"	18"	20"	22"	24"	28"
Eichleay - Ducting/Piping Only $/Foot	--	--	--	$23.17	$38.59	$54.00	$62.00	$65.50	$69.00	$86.00	$92.00	$99.00	$106.00	$119.00
Eichleay - Ducting/Piping Only $/Foot Including 21.93% for Inflation	--	--	--	$28.25	$47.05	$65.84	$75.60	$79.86	$84.13	$104.86	$112.18	$120.71	$129.25	$145.10
Average $/Foot from District Cost Survey	$15.49	$30.85	$27.67	$44.13	$37.50	$33.13	$93.75	$181.70	$216.50	$189.02	$308.40	--	$193.99	--
Average $/Foot from District Cost Survey from Suppliers of Both 3" and 6"	--	$30.85	--	$57.26	--	--	--	--	--	--	--	--	--	--

Ducting/Piping Costs based on Eichleay Report

Note: Minimum of 6" Diameter for Structural Support														
Duct Size Diameter (in.)	2"	3"	4"	6"	8"	10"	12"	14"	16"	18"	20"	22"	24"	28"
Ducting/Piping Only $/Foot	--	--	--	$23.17	$38.59	$54.00	$62.00	$65.50	$69.00	$86.00	$92.00	$99.00	$106.00	$119.00
Ducting + Fittings, Bolt Up, Handling, & Install $/Foot	--	--	--	$62.17	$103.25	$144.33	$143.83	$174.17	$204.52	$251.38	$309.38	$306.44	$397.67	$476.73
Ducting + Fittings, Bolt Up, Handling, & Install $/Foot	--	--	--	$62.17	$103.25	$144.33	$143.83	$174.17	$204.52	$251.38	$309.38	$306.44	$397.67	$476.73

Supplier: Grainger (http://www.grainger.com) **Location: Fresno, CA and Ceres, CA**

Schedule 10													
Duct Size Diameter (in.)	2"	3"	4"	6"	8"	10"	12"	14"	16"	18"	20"	22"	24"
Price ($)	$229.50	$387.75	$587.50	--	--	--	--		--	--	--	--	--
Length (feet)	10	10	10	--	--	--	--		--	--	--	--	--
Price/Foot ($)	$22.95	$38.78	$58.75	--	--	--	--		--	--	--	--	--

Supplier: Stockton Pipe and & Supply Inc (http://www.stocktonpipe.net) **Location: Stockton, CA**

Note: Sizes over 12" Diameter need to be ordered from Mill													
0.109" thickness tube or Schedule 10 Pipe													
Duct Size Diameter (in.)	2"	3"	4"	6"	8"	10"	12"	14"	16"	18"	20"	22"	24"
Price ($)	--	--	--	--	--	$700.00	$840.00	--	--	--	--	--	$3,159.60
Length (feet)	--	--	--	--	--	20	20	--	--	--	--	--	20
Price/Foot ($)	--	--	--	--	--	$35.00	$42.00	--	--	--	--	--	$157.98

Supplier: Valley Iron Inc (http://www.stocktonpipe.net) **Location: Fresno, CA**

Note: Sch 10 T-304 20'													
Schedule 10 Pipe													
Duct Size Diameter (in.)	2"	3"	4"	6"	8"	10"	12"	14"	16"	18"	20"	22"	24"
Length (feet)	--	--	20	20	20	20	--	--	--	--	--	--	--
Price/Foot ($)	--	--	$10.75	$16.90	$26.00	$33.90	--	--	--	--	--	--	--

Supplier: Del Paso Pipe & Steel Inc. (http://www.delpasopipeandsteel.com/) **Location: Sacramento, CA**

Schedule 5/10 Pipe:													
Duct Size Diameter (in.)	2"	3"	4"	6"	8"	10"	12"	14"	16"	18"	20"	22"	24"
Price Quote: $9/lb												--	
Estimated Price/Foot	--	--	--	--	--	--	$217.00	$250.00	$286.00	$322.00	$432.00	--	--
												--	

Supplier: Hayward Pipe & Supply Co. Inc (http://www.haywardpipe.com/) **Location: Hayward, CA**

Note: large diamter pipe ships from Texas, FREIGHT NOT QUOTED - Additional Shipping Costs apply													
Schedule 10 Pipe													
Duct Size Diameter (in.)	2"	3"	4"	6"	8"	10"	12"	14"	16"	18"	20"	22"	24"
Price ($)	--	--	--	--	--	--	$1,540.00	$2,268.00	$2,940.00	$3,276.00	$3,696.00	--	--
Length (feet)	--	--	--	--	--	--	20	20	20	20	20	--	--
Price/Foot ($)	--	--	--	--	--	--	$77.00	$113.40	$147.00	$163.80	$184.80	--	--

Supplier: OnlineMetals.com (http://www.onlinemetals.com/) **Location: Nearest Warehouse - Los Angeles, CA**

Schedule 10 Pipe													
Duct Size Diameter (in.)	2"	3"	4"	6"	8"	10"	12"	14"	16"	18"	20"	22"	24"
Price ($)	$78.28	$108.97	$160.34	$288.00	$520.00	--	--	--	--	--	--	--	--
Length (feet)	8	8	8	8	8	--	--	--	--	--	--	--	--
Price/Foot ($)	$9.79	$13.62	$20.04	$36.00	$65.00	--	--	--	--	--	--	--	--
Weldeds Stainless Tube 304/304L (2" OD, 0.12" Wall; 3" OD, 0.12" Wall; 6", 0.12")													
Duct Size Diameter (in.)	2"	3"	4"	6"	8"	10"	12"	14"	16"	18"	20"	22"	24"
Price ($)	$109.86	$321.34	--	$628.16	--	--	--	--	--	--	--	--	--
Length (feet)	8	8	--	8	--	--	--	--	--	--	--	--	--
Price/Foot ($)	$13.73	$40.17	--	$78.52	--	--	--	--	--	--	--	--	--

Supplier: Lone Star Supply Co **Location: Dickinson, TX**

Note: Additional shipping costs													
Schedule 10 Welded Pipe													
Duct Size Diameter (in.)	2"	3"	4"	6"	8"	10"	12"	14"	16"	18"	20"	22"	24"
Price/Foot ($)	--	--	$16.45	$19.60	$21.50	$30.50	$39.00	--	--	$81.25	--	--	$230.00
												--	

Supplier: Global Technology and Engineering **Location: Excelsior Springs, MO**

Note: Additional shipping Costs													
11 Gauge Tubing													
Duct Size Diameter (in.)	2"	3"	4"	6"	8"	10"	12"	14"	16"	18"	20"	22"	24"
Price ($)	--	--	$226.58	$487.40	--	--	--	--	--	--	--	--	--
Length (feet)	--	--	7	7	--	--	--	--	--	--	--	--	--
Price/Foot ($)	--	--	$32.37	$69.63	--	--	--	--	--	--	--	--	--

Appendix C

BACT Guideline 5.4.13 and Top Down BACT Analysis

San Joaquin Valley
Unified Air Pollution Control District

Best Available Control Technology (BACT) Guideline 5.4.13*

Last Update: 09/26/2011

Wine Storage Tank - Non-Wood Material**

Pollutant	Achieved in Practice or contained in the SIP	Technologically Feasible	Alternate Basic Equipment
VOC	1. Insulation or Equivalent***, Pressure Vacuum Relief Valve (PVRV) set within 10% of the maximum allowable working pressure of the tank; "gas-tight" tank operation; and continuous storage temperature not exceeding 75 degrees F, achieved within 60 days of completion of fermentation.	1. Capture of VOCs and thermal or catalytic oxidation or equivalent (98% control) 2. Capture of VOCs and carbon adsorption or equivalent (95% control) 3. Capture of VOCs and absorption or equivalent (90% control) 4. Capture of VOCs and condensation or equivalent (70% control)	

**This guideline is applicable to a wine storage tank that is not constructed out of wooden materials.
***Tanks made of heat-conducting materials such as stainless steel may be insulated or stored indoors (in a completely enclosed building, except for vents, doors and other essential openings) to limit exposure ot diurnal temperature variations. Tanks made entirely of non-conducting materials such as concrete (except for fittings) are considered self-insulating.

BACT is the most stringent control technique for the emissions unit and class of source. Control techniques that are not achieved in practice or contained in s a state implementation plan must be cost effective as well as feasible. Economic analysis to demonstrate cost effectiveness is required for all determinations that are not achieved in practice or contained in an EPA approved State Implementation Plan.

***This is a Summary Page for this Class of Source**

Top-Down BACT Analysis for VOCs from Wine Storage Operations

Step 1 - Identify All Possible Control Technologies

The SJVUAPCD BACT Clearinghouse guideline 5.4.13 identifies achieved in practice and technologically feasible BACT for wine storage tanks as follows:

1) Insulation or Equivalent**, Pressure Vacuum Relief Valve (PVRV) set within 10% of the maximum allowable working pressure of the tank; "gas-tight" tank operation; and continuous storage temperature not exceeding 75 degrees F, achieved within 60 days of completion of fermentation.
2) Capture of VOCs and thermal or catalytic oxidation or equivalent (98% control)
3) Capture of VOCs and carbon adsorption or equivalent (95% control)
4) Capture of VOCs and absorption or equivalent (90% control)
5) Capture of VOCs and condensation or equivalent (70% control)

***Tanks made of heat-conducting materials such as stainless steel may be insulated or stored indoors (in a completely enclosed building, except for vents, doors and other essential openings) to limit exposure to diurnal temperature variations. Tanks made entirely of non-conducting materials such as concrete and wood (except for fittings) are considered self-insulating.*

Step 2 - Eliminate Technologically Infeasible Options

None of the above listed technologies are technologically infeasible.

Step 3 - Rank Remaining Control Technologies by Control Effectiveness

Rank by Control Effectiveness		
Rank	Control	Overall Capture & Control Efficiency
1	Capture of VOCs and thermal or catalytic oxidation or equivalent	98%(*)
2	Capture of VOCs and carbon adsorption or equivalent	95%
3	Capture of VOCs and absorption or equivalent	90%
4	Capture of VOCs and condensation or equivalent	70%
5	Insulation or Equivalent, Pressure Vacuum Relief Valve (PVRV) set within 10% of the maximum allowable working pressure of the tank; "gas-tight" tank operation; and continuous storage temperature not exceeding 75 degrees F, achieved within 60 days of completion of fermentation	Baseline (Achieved-in-Practice)

(*) Following recent District practice, thermal and catalytic oxidation will be ranked together.

Step 4 - Cost Effectiveness Analysis

A cost effective analysis must be performed for all control options that have not been determined to be achieved in practice in the list from Step 3 above, in the order of their ranking, to determine the cost effective option with the lowest emissions.

District BACT Policy APR 1305 establishes annual cost thresholds for imposed control based upon the amount of pollutants reduced by the controls. If the cost of control is at or below the threshold, it is considered a cost effective control. If the cost exceeds the threshold, it is not cost effective and the control is not required. Per District BACT Policy, the maximum cost limit for VOC reduction is $17,500 per ton of VOC emissions reduced.

BACT Analysis Assumptions – All Control Options

- It is expected that if control systems were required to be installed on a wine storage *and* fermentation tank, that a winery would install a system capable of controlling the worst case (highest) emissions which are fermentation emissions. Therefore the ductwork, clean-in-place systems and all control systems would need to be adequately sized to control the fermentation emissions. As such, the size, cost and number of control devices necessary to control storage emissions will be the same as was determined in the fermentation top down BACT analysis in Appendix B.
- As stated above, all the cost from the fermentation analysis in Appendix B apply to this top down BACT analysis except for the annual labor, utility and maintenance costs. Fermentation is expected to only operate for 90 days out of the year whereas storage operations can occur all year round; therefore, the annual labor and maintenance will be recalculated in this Appendix accordingly.
- In determining the labor costs for the cost analyses, two shifts are assumed to be appropriate for a control system serving wine storage tanks.

Uncontrolled Storage Emissions

Delicato is proposing to establish a combined VOC emission limit for all fermentation and storage tanks proposed in this project which will be incorporated into the existing facility-wide combined VOC emissions limit for all wine storage and fermentation operations at the facility. Therefore, for the purposes of this cost effectiveness analysis, uncontrolled storage VOC emissions will be set equal to the combined total VOC emissions allowed under the new combined limit for storage and fermentation operations.

Uncontrolled PE from Section VII.C.2 = 269,842 lb-VOC/year

Collection System Capital Investment (based on ductwork and clean-in-place system)

A common feature of all technically feasible options is that they require installation of a collection system for delivering the VOCs from the tanks to the common control device(s) and a clean-in-place (CIP) system to maintain sanitation and quality of the product.

As calculated in Appendix B, the total annualized capital investment for the collection system = $1,196,800.

Option 1 – Collection of VOCs and control by thermal or catalytic oxidation (98% collection & control)

Total Annual Cost

As calculated in Appendix B, with a total capital investment (TCI) of $5,518,114, the annualized capital cost for the regenerative thermal oxidizer system = $899,453.

Operation and Maintenance Costs

The Direct annual costs include labor (operating, supervisory, and maintenance), maintenance materials, electricity, and fuel.

Heat of Combustion for waste gas stream -dh(c):

heat of combustion -dHc	= 11,800 Btu/lb for ethanol
Daily VOC emissions rate	= 28,589.9 lb/day per Section VII.C.2
Blower flow rate	= 75,301 scfm (based on kinetic model, with oxygen)
	= 108,433,440 ft^3/day

-dh(c) = 28,589.9 lb/day x 11,800 Btu/lb / 108,433,440 ft^3/day
= 3.1 Btu/ft^3

Assuming the waste gas is principally air, with a molecular weight of 28.97 and a corresponding density of 0.0739 lb/scf, the heat of combustion per pound of incoming waste gas is:

-dh(c) = 3.1 Btu/ft^3 / 0.0739 lb/ft^3
= 41.9 Btu/lb

Fuel Flow Requirement

$$Q(fuel) = \frac{Pw*Qw*\{Cp*[1.1Tf-Tw-0.1Tr]-[-dh(c)]\}}{\rho(af) * [-dh(m) - 1.1\ Cp * (Tf - Tr)]}$$

Where
- Pw = 0.0739 lb/ft^3
- Cp = 0.255 Btu/lb-°F
- Qw = 75,301 scfm
- -dh(m) = 11,800 Btu/lb for ethanol
- Tr = 77°F (per EPA Cost Manual)
- ρ(af) = 0.0408 lb/ft^3 m, methane at 77°F, 1 atm
- Tf = 1600°F
- Tw = 1525°F
- -dh(c) = 41.9 Btu/lb

$$Q = \frac{0.0739 * 75{,}301 * \{0.255 * [1.1 * 1{,}600 - 1{,}525 - 0.1*77] - 41.9\}}{0.0408 * [11{,}800 - 1.1 * 0.255 * (1{,}600 - 77)]}$$

$$= 89{,}378 \div 464 = 193\ ft^3/min$$

Fuel Costs

The cost for natural gas shall be based upon the average price of natural gas sold to "Commercial Consumers" in California for the years 2013, 2013 and 2015.[8]

2015 = $7.98/thousand ft^3 total monthly average
2014 = $9.05/thousand ft^3 total monthly average
2013 = $7.81/thousand ft^3 total monthly average
Average for three years = $8.28/thousand ft^3 total monthly average

Fuel Cost = 193 cfm x 2 shifts/day x 8 hrs/shift x 60 min/hr x 365 day/year x $8.28/1000 ft^3
= $559,953/year

Electricity Requirement

$$Power_{fan} = \frac{1.17*10^{-4}\ Qw*\Delta P}{\in}$$

Where
- ΔP = Pressure drop Across system = 4 in. H_2O
- ∈ = Efficiency for fan and motor = 0.6
- Qw = 75,301 scfm

[8] Energy Information Administration/Natural Gas; Average Price of Natural Gas Sold to Commercial Consumers by State, 2013 - 2015

$$\text{Power}_{fan} = \frac{1.17 * 10^{-4} * 75{,}301 \text{ cfm} * 4 \text{ in. } H_2O}{0.60}$$

$$= 58.7 \text{ kW}$$

Electricity Costs

Average cost of electricity to commercial users in California[9]:

2015 Average = $0.1579/kWh

Electricity Cost = 58.7 kW x 2 shifts/day x 8 hrs/shift x 365 day/year x $0.1579/kWh
= $54,129 /year

Total Operating and Maintenance Costs

Annual Costs (Based on: EPA Air Pollution Control Cost Manual, Sixth Edition (January 2002), Section 3.2: VOC Destruction Controls, Chapter 2: Incinerators (September 2000), Table 2.10 - Annual Costs for Thermal and Catalytic Incinerators Example Problem. United States Environmental Protection Agency Office of Air Quality Planning and Standards. Research Triangle Park, North Carolina 27711. EPA/452/B-02-001)[10]

[9] Energy Information Administration/Electric Power; Average Retail Price of Electricity to Ultimate Customers by End-Use Sector, by State, 2015 http://www.eia.gov/electricity/data/browser/#/topic/7?agg=0,1&geo=000000000004&endsec=vg&freq=A&start=2001&end=2015&ctype=linechart&ltype=pin&rtype=s&maptype=0&rse=0&pin=

[10] http://epa.gov/ttn/catc/dir1/cs3-2ch2.pdf

Thermal Oxidizer Annual Costs			
Direct Annual Cost (DAC)			
Operating Labor			
Operator	0.5 hr/shift	$18.50/hr x 0.5 hr/shift x 2 shift/day x 365 days/year x 7 units	$47,268
Supervisor	15% of operator		$7,090
Maintenance			
Labor	0.5 h/shift	$18.50/hr x 0.5 hr/shift x 2 shift/day x 365 days/year x 7 units	$47,268
Maintenance	100% of labor		$47,268
Utility			
Natural Gas	see calculation above		$559,953
Electricity	see calculation above		$54,129
Total DAC			**$762,976**
Indirect Annual Cost (IAC)			
Overhead	60% of Labor Cost	0.6 x ($47,268+ $7,090 + $47,268 + $47,268)	$89,336
Administrative	2% TCI		$110,362
Property Taxes	1% TCI		$55,181
Insurance	1% TCI		$55,181
Annual Source Test	One representative test/year @ $15,000		$15,000
Total IAC			**$325,060**
Annual Cost (DAC + IAC)			**$1,088,036**

Total Annual Cost = Regenerative Thermal Oxidizer System + (Ductwork + CIP System) + Annual Cost
= $899,453 + $1,196,800 + $1,088,036
= $3,184,289

Emission Reductions

Annual Emission Reduction = Uncontrolled Emissions x 0.98
= 269,842 lb-VOC/year x 0.98 x ton/2,000 lb
= 132.2 tons-VOC/year

Cost Effectiveness

Cost Effectiveness = $3,184,289/year ÷ 132.2 tons-VOC/year
= $24,087/ton-VOC

The analysis demonstrates that the annualized purchase cost of the regenerative thermal oxidizer system, collection system ductwork and CIP equipment, and annual costs alone

results in a cost effectiveness which exceeds the District's Guideline of $17,500/ton-VOC. Therefore this option is not cost-effective and will not be considered for this project.

Option 2 – Collection of VOCs and control by carbon adsorption (95% collection and control)

Total Annual Cost

As calculated in Appendix B, with a total capital investment (TCI) of $4,249,251, the annualized capital cost for the regenerative thermal oxidizer system = $852,760.

Operation and Maintenance Costs

Carbon Adsorption Annual Costs			
Direct Annual Cost (DAC)			
Operating Labor			
Operator	0.5 hr/shift	$18.50/hr x 0.5 hr/shift x 2 shift/day x 365 days/year x 7 units	$47,268
Supervisor	15% of operator		$7,090
Maintenance			
Labor	0.5 h/shift	$18.50/hr x 0.5 hr/shift x 2 shift/day x 365 days/year x 7 units	$47,268
Maintenance	100% of labor		$47,268
Utility			
Steam	Not included at this time		$0
Cooling Water	Not included at this time		$0
Electricity	Not included at this time		$0
Total DC			**$148,894**
Indirect Annual Cost (IAC)			
Overhead	60% of Labor Cost	0.6 x ($47,268+ $7,090 + $47,268 + $47,268)	$89,336
Administrative	2% TCI (equipment cost + carbon cost)		$84,985
Property Taxes	1% TCI (equipment cost + carbon cost)		$42,493
Insurance	1% TCI (equipment cost + carbon cost)		$42,493
Annual Source Test	One representative test/year @ $15,000		$15,000
Total IC			**$274,307**
Annual Cost (DAC + IAC)			**$423,201**

Total Annual Cost = Carbon Adsorption Capital Cost + (Ductwork + CIP System) + Annual Cost
= $852,760+ $1,196,800 + $423,201
= $2,472,761

Emission Reductions

Annual Emission Reduction = Uncontrolled Emissions x 0.95
= 269,842 lb-VOC/year x 0.95 x ton/2,000 lb
= 128.2 tons-VOC/year

Cost Effectiveness

Cost Effectiveness = $2,472,761/year ÷ 128.2 tons-VOC/year
= $19,288/ton-VOC

The analysis demonstrates that the annualized purchase cost of the carbon adsorption system, collection system ductwork and CIP equipment, and annual costs alone results in a cost effectiveness which exceeds the District's Guideline of $17,500/ton-VOC. Therefore this option is not cost-effective and will not be considered for this project.

Option 3 - Collection of VOCs and control by absorption or equivalent (90% collection & control)

Total Annual Cost

As calculated in Appendix B, with a total capital investment (TCI) of $4,756,022, the annualized capital cost for the scrubber system = $775,232.

Wastewater Disposal Costs

Additionally, the water scrubber will generate ethanol-laden wastewater containing 121.4 tons-ethanol annually (269,842 lb/year (uncontrolled fermentation emissions) x 0.90 ÷ 2000). Assuming a 10% solution, approximately 366,767 gallons of waste water (121.4 ton-ethanol x 2000 lb/ton x gal/6.62 lb ÷ 0.10) will be generated annually. Per Project C-1133347, an allowance of $0.08 per gallon (not including inflation) is applied for disposal costs.

Annual disposal costs = 366,767 gallons x $0.08/gallon = $29,341.

Total Operation and Maintenance Costs

Scrubber Annual Costs			
Direct Annual Cost (DAC)			
Operating Labor			
Operator	0.5 hr/shift	$18.50/hr x 0.5 hr/shift x 2 shift/day x 365 days/year x 7 units	$47,268
Supervisor	15% of operator		$7,090
Maintenance			
Labor	0.5 h/shift	$18.50/hr x 0.5 hr/shift x 2 shift/day x 275 days/year x 7 units	$47,268
Maintenance	100% of labor		$47,268
Utility			
Natural Gas			$0
Electricity	7 units x 2.5 hp x 0.746 kW/hp x 365 days/year x 16 hr/day = 82,341 kWh/yr	$0.1579/kWh	$13,002
Total DAC			**$161,896**
Indirect Annual Cost (IAC)			
Overhead	60% of Labor Cost	0.6 x ($47,268+ $7,090 + $47,268 + $47,268)	$89,336
Administrative	2% TCI		$95,120
Property Taxes	1% TCI		$47,560
Insurance	1% TCI		$47,560
Annual Source Test	One representative test/year @ $15,000		$15,000
Total IAC			**$294,576**
Annual Cost (DAC + IAC)			**$456,472**

Total Annual Cost = Scrubber System + (Ductwork + CIP System) + Wastewater Disposal + Annual Cost
= $775,232 + $1,196,800 + $29,341 + $456,472
= $2,457,845

Emission Reductions

The District's BACT Guideline identifies an overall collection and control efficiency of 81% for absorption systems.

Annual Emission Reduction = Uncontrolled Emissions x 0.90
= 269,842 lb-VOC/year x 0.90/2,000 lb
= 121.4 lb-VOC/year

Cost Effectiveness

Cost Effectiveness = Total Annual Cost ÷ Annual Emission Reductions

Cost Effectiveness = $2,457,845/year ÷ 121.4 tons-VOC/year
= $20,246/ton-VOC

The analysis demonstrates that the annualized purchase cost of the water scrubber, collection system ductwork and CIP equipment and annual costs alone results in a cost effectiveness which exceeds the District's Guideline of $17,500/ton-VOC. Therefore this option is not cost-effective and will not be considered for this project.

Option 4 - Capture of VOCs and condensation (70% collection & control)

Total Annual Cost

As calculated in Appendix B, with a total capital investment (TCI) of $20,086,413, the annualized capital cost for the condensation system = $3,274,085.

Total Operation and Maintenance Costs

Condensation Annual Costs			
Direct Annual Cost (DAC)			
Operating Labor			
Operator	0.5 hr/shift	$18.50/hr x 0.5 hr/shift x 2 shift/day x 365 days/year x 42 units	$283,605
Supervisor	15% of operator		$42,541
Maintenance			
Labor	0.5 h/shift	$18.50/hr x 0.5 hr/shift x 2 shift/day x 365 days/year x 42 units	$283,605
Maintenance	100% of labor		$283,605
Chiller (Glycol)			
Not included at this time			-
Utility (Electricity)			
Not included at this time			-
Total DAC			**$893,356**
Indirect Annual Cost (IAC)			
Overhead	60% of Labor Cost	0.6 x ($283,605 + $42,541 + $283,605 + $283,605)	$536,014
Administrative	2% TCI		$401,728
Property Taxes	1% TCI		$200,864
Insurance	1% TCI		$200,864
Total IAC			**$1,339,470**
Annual Cost (DAC + IAC)			**$2,232,826**

Total Annual Cost = Condenser System + (Ductwork + CIP System) + Annual Costs

= $3,274,085 + $1,196,800 + $2,232,826
= $6,703,711

Emission Reductions

The District's BACT Guideline identifies an overall collection and control efficiency of 70% for absorption systems.

Annual Emission Reduction = Uncontrolled Emissions x 0.70
= 269,842 lb-VOC/year x 0.70/2,000 lb
= 94.4 lb-VOC/year

Cost Effectiveness

Cost Effectiveness = Total Annual Cost ÷ Annual Emission Reductions

Cost Effectiveness = $6,703,711/year ÷ 94.4 tons-VOC/year
= $71,014/ton-VOC

The analysis demonstrates that the annualized purchase cost of the refrigerated condenser system, collection system ductwork and CIP equipment and annual costs alone results in a cost effectiveness which exceeds the District's Guideline of $17,500/ton-VOC. Therefore this option is not cost-effective and will not be considered for this project.

Option 5 - Insulation, PVRV, "Gas-Tight" Tank Operation, and Storage Temperature not Exceeding 75 deg F, Achieved within 60 days of Completion of Fermentation

The only remaining control option in step 3 above has been deemed AIP for this class and category of source and per the District BACT policy is required regardless of the cost. Therefore, a cost effectiveness analysis is not required.

Step 5 - Select BACT

All identified feasible options with control efficiencies higher than the option proposed by the facility have been shown to not be cost effective. The facility has proposed Option 1, insulated tank, pressure/vacuum valve set within 10% of the maximum allowable working pressure of the tank, "gas tight" tank operation and achieve and maintain a continuous storage temperature not exceeding 75°F within 60 days of completion of fermentation. These BACT requirements will be placed on the ATC as enforceable conditions.

Attachment C1

Ducting Layout Diagrams and Ducting Cost Estimates

1) The tanks in this and other diagrams are graphically shown as the same size for convenience of the spread sheet layout. The numbers in the cells around the tank layout reflect spacing and tank dimensions from the data base and Delicato lay out drawing.

2) Red dashed line is the most probable duct routing.

3) All tanks are rated for fermentation and storage.

4) At the time of this BACT analysis tank numbers were not shown on the Lay out drawing. The tank numbers shown in this and other parts of this analysis are subject to change.

5) Main ducts set at about 10 feet above



Diameter in Feet	25.00
Shell Height in Feet	40.00

Notes	Beginning Tank Numbers	Ending Tank Numbers	Length Between Nodes	From Top Tank Connection to Main Duct Length in Feet	Design Duct Velocity from Eichleay Feet/Second	Gas Flow Rate Storage Fill	Fermentation CFM at maximum CO2 rate from kinetic model	Duct size diameter in inches at node	Nominal Duct Size diameter in inches (See comments)	Number of Tanks feeding Ending Node	Total Number of Tanks to connect	Total feet	Cost Per Foot from Eichleay (See Comments)	Cost	Comments
Note 1: Tank Connection to Main Ducting. Red fermentation, white fermentation, and storage can be done in each tank.	Note 1	Note 1	Note 3	60	40	Note 2	793	7.79	6.00		16	960	$33.57	$32,229	Reduced to 3 inch size due to low gas flow

Note 2: All tanks are for Red Fermentation, White Fermentation, and Storage. Red Fermentation gas flow rates are used for the BACT analysis. Storage flows are shown on the storage flow tab for information only on a per tank bases.

Note 3: The length between nodes is the distance between the center of the circle representing the tank and its adjacent tank. Refer to tank number columns for location.

	Beginning Tank Numbers	Ending Tank Numbers	Length Between Nodes	From Top Tank Connection to Main Duct Length in Feet	Design Duct Velocity from Eichleay Feet/Second	Gas Flow Rate Storage Fill	Fermentation CFM at maximum CO2 rate from kinetic model	Duct size diameter in inches at node	Nominal Duct Size diameter in inches (See comments)	Number of Tanks feeding Ending Node	Total Number of Tanks to connect	Total feet	Cost Per Foot from Eichleay (See Comments)	Cost	Comments
Note 4: Tanks T-1 through T-16	T-1/T-2	T-3/T-4	31.33	Note 5	40	Note 2	1,587	11.01	6.00	2	16	31.33	$62.17	$1,947.81	
	T-3/T-4	T-5/T-6	31.33	Note 5	40	Note 2	3,174	15.57	6.00	4		31.33	$62.17	$1,947.81	
Note 5: The top of tank ducting to the main duct is calculated in row 2.	T-5/T-6	T-7/T-8	31.33	Note 5	40	Note 2	4,760	19.07	6.00	6		31.33	$62.17	$1,947.81	Main Duct Set at 6 inch size due to structural spans and uncertainty of the number of pumps pumping
	T-7/T-8	●	68.46	Note 5	40	Note 2	6,347	22.02	6.00	8		68.46	$62.17	$4,256.08	
	T-9/T-10	T-11/T-12	31.33	Note 5	40	Note 2	1,587	11.01	6.00	2		31.33	$62.17	$1,947.81	
	T-11/T-12	T-13/T-14	31.33	Note 5	40	Note 2	3,174	15.57	6.00	4		31.33	$62.17	$1,947.81	
	T-13/T-14	T-15/T-16	31.33	Note 5	40	Note 2	4,760	19.07	6.00	6		31.33	$62.17	$1,947.81	
	T-15/T-16	●	68.46	Note 5	40	Note 2	6,347	22.02	6.00	8		68.46	$62.17	$4,256.08	
	●	Emission Controls	75.00	Note 5	40	Note 2	12,695	31.14	6.00	16		75.00	$62.17	$4,662.80	
													Sum	$24,862	

Redundant Main Duct for CIP on Fermenters Only		$0	
1 Knock drums (7000 gallons) for foam overs on fermenters		$0	Eichleay
Ducting Isolation Components for all tanks		$42,000	Previous Work
The main process pipe ways will need some modification to support the emission ducting systems.		$60,000	Allowance
Ducting Cost		$99,091	
Support Allowance		$60,000	
	Total	$159,091	

1) The tanks in this and other diagrams are graphically shown as the same size for convenience of the spread sheet layout. The numbers in the cells around the tank layout reflect spacing and tank dimensions from the data base and Delicato lay out drawing.

2) Red dashed line is the most probable duct routing

3) All tanks are rated for fermentation and storage.

4) At the time of this BACT analysis tank numbers were not shown on the Lay out drawing. The tank numbers shown in this and other parts of this analysis are subject to change.

5) Main ducts set at about 10 feet above ground.



Notes	Beginning Tank Numbers	Ending Tank Numbers	Length Between Nodes	From Top Tank Connection to Main Duct Length in Feet	Design Duct Velocity from Eichleay Feet/Second	Gas Flow Rate Storage Fill	Fermentation CFM at maximum CO2 rate from kinetic model	Duct size diameter in inches at node	Nominal Duct Size diameter in inches (See comments)	Number of Tanks feeding Ending Node	Total Number of Tanks to connect	Total feet	Cost Per Foot from Eichleay (See Comments)	Cost	Comments
Note 1: Tank Connection to Main Ducting. Red fermentation, white fermentation, and storage can be done in each tank.															Reduced to 3 inch size due to low gas flow
	Note 1	Note 1	Note 3	56	40	Note 2	530.66	6.37	6.00		28	1,568	$33.57	$52,641.20	

Note 2: All tanks are for Red Fermentation, White Fermentation, and Storage. Red Fermentation gas flow rates are used for the BACT analysis. Storage flows are shown on the storage flow tab for information only on a per tank bases.

Note 3: The length between nodes is the distance between the center of the circle representing the tank and its adjacent tank. Refer to tank number columns for location.

	Beginning Tank Numbers	Ending Tank Numbers	Length Between Nodes	From Top Tank Connection to Main Duct Length in Feet	Design Duct Velocity from Eichleay Feet/Second	Gas Flow Rate Storage Fill	Fermentation CFM at maximum CO2 rate from kinetic model	Duct size diameter in inches at node	Nominal Duct Size diameter in inches (See comments)	Number of Tanks feeding Ending Node	Total Number of Tanks to connect	Total feet	Cost Per Foot from Eichleay (See Comments)	Cost	Comments
Note 4: Tanks T-17 through T-44	T-27/T-28	T-26/T-25	25.00	Note 5	40	Note 2	1,061	9.00	6.00	2	28	25.00	$62.17	$1,554.27	
	T-26/T-25	T-24/T-23	25.50	Note 5	40	Note 2	2,123	12.73	6.00	4		25.50	$62.17	$1,585.35	
Note 5: The top of tank ducting to the main duct is calculated in row 2.	T-24/T-23	T-22/T-21	25.00	Note 5	40	Note 2	3,184	15.60	6.00	6		25.00	$62.17	$1,554.27	
	T-22/T-21	T-20/T-19	25.50	Note 5	40	Note 2	4,245	18.01	6.00	8		25.50	$62.17	$1,585.35	
	T-20/T-19	T-17/T-18	25.00	Note 5	40	Note 2	5,307	20.13	6.00	10		25.00	$62.17	$1,554.27	
	T-17/T-18	●	20.50	Note 5	40	Note 2	6,368	22.06	6.00	12		20.50	$62.17	$1,274.50	
	T-44/T-43	T-41/T-42	25.00	Note 5	40	Note 2	1,061	9.00	6.00	2		25.00	$62.17	$1,554.27	Main Duct Set at 6 inch size due to structural spans and uncertainty of the number of pumps pumping
	T-41/T-42	T-39/T-40	25.50	Note 5	40	Note 2	2,123	12.73	6.00	4		25.50	$62.17	$1,585.35	
	T-39/T-40	T-37/T-38	25.00	Note 5	40	Note 2	3,184	15.60	6.00	6		25.00	$62.17	$1,554.27	
	T-37/T-38	T-35/T-36	25.50	Note 5	40	Note 2	4,245	18.01	6.00	8		25.50	$62.17	$1,585.35	
	T-35/T-36	T-33/T-34	25.00	Note 5	40	Note 2	5,307	20.13	6.00	10		25.00	$62.17	$1,554.27	
	T-33/T-34	T-32/T-31	25.50	Note 5	40	Note 2	6,368	22.06	6.00	12		25.50	$62.17	$1,585.35	
	T-32/T-31	T-29/T-30	25.00	Note 5	40	Note 2	7,429	23.82	6.00	14		25.00	$62.17	$1,554.27	
	T-29/T-30	●	117.58	Note 5	40	Note 2	8,490	25.47	6.00	16		117.58	$62.17	$7,310.22	
	●	Emission Controls	75.00	Note 5	40	Note 2	14,858	33.69	6.00	28		75.00	$62.17	$4,662.80	
													Sum	$32,054	

Redundant Main Duct for CIP on Fermenters Only	$0	
1 Knock drums (7000 gallons) for foam overs on fermenters	$0	Eichleay
Ducting Isolation Components for all tanks with redundant main (X2)	$73,500	Previous Work
The main process pipe ways will need some modification to support the emission ducting systems.	$60,000	Allowance

Ducting Cost	$158,195
Support Allowance	$60,000
Total	**$218,195**

1) The tanks in this and other diagrams are graphically shown as the same size for convenience of the spread sheet layout. The numbers in the cells around the tank layout reflect spacing and tank dimensions from the data base and Delicato lay out drawing.

2) Red dashed line is the most probable duct routing.

3) All tanks are rated for fermentation and storage.

4) At the time of this BACT analysis tank numbers were not shown on the Lay out drawing. The tank numbers shown in this and other parts of this analysis are subject to change.

5) Main ducts set at about 10 feet above ground.



Notes	Beginning Tank Numbers	Ending Tank Numbers	Length Between Nodes	From Top Tank Connection to Main Duct Length in Feet	Design Duct Velocity from Eichleay Feet/Second	Gas Flow Rate Storage Fill	Fermentation CFM at maximum CO2 rate from kinetic model	Duct size diameter in inches at node	Nominal Duct Size diameter in inches (See comments)	Number of Tanks feeding Ending Node	Total Number of Tanks to connect	Total feet	Cost Per Foot from Eichleay (See Comments)	Cost	Comments
Note 1: Tank Connection to Main Ducting. Red fermentation, white fermentation, and storage can be done in each tank.															
	Note 1	Note 1	Note 3	48.0	40	Note 2	309	4.86	6.00		50	2,400	$33.57	$80,573	Reduced to 3 inch size due to low gas flow

Note 2: All tanks are for Red Fermentation, White Fermentation, and Storage. Red Fermentation gas flow rates are used for the BACT analysis. Storage flows are shown on the storage flow tab for information only on a per tank bases.

Note 3: The length between nodes is the distance between the center of the circle representing the tank and its adjacent tank. Refer to tank number columns for location.

	Beginning Tank Numbers	Ending Tank Numbers	Length Between Nodes	From Top Tank Connection to Main Duct Length in Feet	Design Duct Velocity from Eichleay Feet/Second	Gas Flow Rate Storage Fill	Fermentation CFM at maximum CO2 rate from kinetic model	Duct size diameter in inches at node	Nominal Duct Size diameter in inches (See comments)	Number of Tanks feeding Ending Node	Total Number of Tanks to connect	Total feet	Cost Per Foot from Eichleay (See Comments)	Cost	Comments
Note 4: Tanks T-45 through T-94	T-93/T-94	T-91/T-92	23.00	Note 5	40	Note 2	618	6.87	6.00	2	10	23	$62.17	$1,429.93	
	T-91/T-92	T-89/Y-90	22.50	Note 5	40	Note 2	1,236	9.72	6.00	4		23	$62.17	$1,398.84	
Note 5: The top of tank ducting to the main duct is calculated in row 2.	T-89/Y-90	T-87/T-88	22.50	Note 5	40	Note 2	1,855	11.90	6.00	6		23	$62.17	$1,398.84	Main Duct Set at 6 inch size due to structural spans and uncertainty of the number of pumps pumping
	T-87/T-88	T-85/T-86	22.50	Note 5	40	Note 2	2,473	13.74	6.00	8		23	$62.17	$1,398.84	
	T-85/T-86	Emission Controls	75.00	Note 5	40	Note 2	3,091	15.37	6.00	10		75	$62.17	$4,662.80	
													Sum	$10,289.26	

Redundant Main Duct for CIP on Fermenters Only	$0	
1 Knock drums (7000 gallons) for foam overs on fermenters	$0	Eichleay
Ducting Isolation Components for all tanks with redundant main (X2)	$26,250	Previous Work
The main process pipe ways will need some modification to support the emission ducting systems.	$60,000	Allowance
Ducting Cost	$36,539	
Support Allowance	$60,000	
Total	$96,539	

Beginning Tank Numbers	Ending Tank Numbers	Length Between Nodes	From Top Tank Connection to Main Duct Length in Feet	Design Duct Velocity from Eichleay Feet/Second	Gas Flow Rate Storage Fill	Fermentation CFM at maximum CO2 rate from kinetic model	Duct size diameter in inches at node	Nominal Duct Size diameter in inches (See comments)	Number of Tanks feeding Ending Node	Total Number of Tanks to connect	Total feet	Cost Per Foot from Eichleay (See Comments)	Cost	Comments
T-83/T-84	T-81/T-82	22.50	Note 5	40	Note 2	618	6.87	6.00	2	20	23	$62.17	$1,398.84	
T-81/T-82	T-79/T-80	22.50	Note 5	40	Note 2	1,236	9.72	6.00	4		23	$62.17	$1,398.84	
T-79/T-80	T-77/T-78	22.50	Note 5	40	Note 2	1,855	11.90	6.00	6		23	$62.17	$1,398.84	
T-77/T-78	T-75/T-76	22.50	Note 5	40	Note 2	2,473	13.74	6.00	8		23	$62.17	$1,398.84	Main Duct Set at 6 inch
T-75/T-76	T-73/T-74	22.50	Note 5	40	Note 2	3,091	15.37	6.00	10		23	$62.17	$1,398.84	size due to structural spans
T-73/T-74	T-71/T-72	22.50	Note 5	40	Note 2	3,709	16.83	6.00	12		23	$62.17	$1,398.84	and uncertainty of the
T-71/T-72	T-69/T-70	22.50	Note 5	40	Note 2	4,328	18.18	6.00	14		23	$62.17	$1,398.84	number of pumps pumping
T-69/T-70	T-67/T-68	22.50	Note 5	40	Note 2	4,946	19.44	6.00	16		23	$62.17	$1,398.84	
T-67/T-68	T-65/T-66	22.50	Note 5	40	Note 2	5,564	20.62	6.00	18		23	$62.17	$1,398.84	
T-65/T-66	Emission Controls	75.00	Note 5	40	Note 2	6,182	21.73	6.00	20		75	$62.17	$4,662.80	
												Sum	$17,252.38	

Redundant Main Duct for CIP on Fermenters Only		$0	
1 Knock drums (7000 gallons) for foam overs on fermenters		$0	Eichleay
Ducting Isolation Components for all tanks with redundant main (X2)		$52,500	Previous Work
The main process pipe ways will need some modification to support the emission ducting systems.		$80,000	Allowance
Ducting Cost		$69,752	
Support Allowance		$80,000	
	Total	$149,752	

Beginning Tank Numbers	Ending Tank Numbers	Length Between Nodes	From Top Tank Connection to Main Duct Length in Feet	Design Duct Velocity from Eichleay Feet/Second	Gas Flow Rate Storage Fill	Fermentation CFM at maximum CO2 rate from kinetic model	Duct size diameter in inches at node	Nominal Duct Size diameter in inches (See comments)	Number of Tanks feeding Ending Node	Total Number of Tanks to connect	Total feet	Cost Per Foot from Eichleay (See Comments)	Cost	Comments
T-45/T-46	T-47/T-48	22.50	Note 5	40	Note 2	618	6.87	6.00	2	20	23	$62.17	$1,398.84	
T-47/T-48	T-49/T-50	22.50	Note 5	40	Note 2	1,236	9.72	6.00	4		23	$62.17	$1,398.84	
T-49/T-50	T-51/T-52	22.50	Note 5	40	Note 2	1,855	11.90	6.00	6		23	$62.17	$1,398.84	
T-51/T-52	T-53/T-54	22.50	Note 5	40	Note 2	2,473	13.74	6.00	8		23	$62.17	$1,398.84	Main Duct Set at 6 inch
T-53/T-54	T-55/T-56	22.50	Note 5	40	Note 2	3,091	15.37	6.00	10		23	$62.17	$1,398.84	size due to structural spans
T-55/T-56	T-57/T-58	22.50	Note 5	40	Note 2	3,709	16.83	6.00	12		23	$62.17	$1,398.84	and uncertainty of the
T-57/T-58	T-59/T-60	22.50	Note 5	40	Note 2	4,328	18.18	6.00	14		23	$62.17	$1,398.84	number of pumps pumping
T-59/T-60	T-61/T-62	22.50	Note 5	40	Note 2	4,946	19.44	6.00	16		23	$62.17	$1,398.84	
T-61/T-62	T-63/T-64	22.50	Note 5	40	Note 2	5,564	20.62	6.00	18		23	$62.17	$1,398.84	
T-63/T-64	Emission Controls	75.00	Note 5	40	Note 2	6,182	21.73	6.00	20		75	$62.17	$4,662.80	
												Sum	$17,252.38	

Redundant Main Duct for CIP on Fermenters Only		$0	
1 Knock drums (7000 gallons) for foam overs on fermenters		$0	Eichleay
Ducting Isolation Components for all tanks with redundant main		$52,500	Previous Work
The main process pipe ways will need some modification to support the emission ducting systems.		$80,000	Allowance

Sum of All Main Ducts This Tab	$396,043
Sum of All 50 Tank Connections	$80,573
Grand Total This Tab	$476,616

Ducting Cost		$69,752
Support Allowance		$80,000
	Total	$149,752

1) The tanks in this and other diagrams are graphically shown as the same size for convenience of the spread sheet layout. The numbers in the cells around the tank layout reflect spacing and tank dimensions from the data base and Delicato lay out drawing.

2) Red dashed line is the most probable duct routing

3) All tanks are rated for fermentation and storage.

4) At the time of this BACT analysis tank numbers were not shown on the Lay out drawing. The tank numbers shown in this and other parts of this analysis are subject to change.

5) Main ducts set at about 10 feet above ground.



Diameter in Feet	21.00
Shell Height in Feet	28.00
Main Duct Connection Length in Feet	75.00

Total tanks in bubble this sketch 14

Notes	Beginning Tank Numbers	Ending Tank Numbers	Length Between Nodes	From Top Tank Connection to Main Duct Length in Feet	Design Duct Velocity from Eichleay Feet/Second	Gas Flow Rate Storage Fill	Fermentation CFM at maximum CO2 rate from kinetic model	Duct size diameter in inches at node	Nominal Duct Size diameter in inches (See comments)	Number of Tanks feeding Ending Node	Total Number of Tanks to connect	Total feet	Cost Per Foot from Eichleay (See Comments)	Cost	Comments
Note 1: Tank Connection to Main Ducting. Red fermentation, white fermentation, and storage can be done in each tank.	Note 1	Note 1	Note 3	46.0	40	Note 2	381	5.40	6.00		14	644	$33.57	$21,620.49	Reduced to 3 inch size due to low gas flow

Note 2: All tanks are for Red Fermentation, White Fermentation, and Storage. Red Fermentation gas flow rates are used for the BACT analysis. Storage flows are shown on the storage flow tab for information only on a per tank bases.

Note 3: The length between nodes is the distance between the center of the circle representing the tank and its adjacent tank. Refer to tank number columns for location.

Note 4: Tanks T-95 through T-108

Note 5: The top of tank ducting to the main duct is calculated in row 2.

Beginning Tank Numbers	Ending Tank Numbers	Length Between Nodes	From Top Tank Connection to Main Duct Length in Feet	Design Duct Velocity from Eichleay Feet/Second	Gas Flow Rate Storage Fill	Fermentation CFM at maximum CO2 rate from kinetic model	Duct size diameter in inches at node	Nominal Duct Size diameter in inches (See comments)	Number of Tanks feeding Ending Node	Total Number of Tanks to connect	Total feet	Cost Per Foot from Eichleay (See Comments)	Cost	Comments
T-95	T-96	26.50	Note 5	40	Note 2	381	5.40	6.00	1	14	27	$62.17	$1,647.52	
T-96	T-97	26.50	Note 5	40	Note 2	762	7.63	6.00	2		27	$62.17	$1,647.52	
T-97	T-98	26.50	Note 5	40	Note 2	1,144	9.35	6.00	3		27	$62.17	$1,647.52	Main Duct Set at 6 inch size due to structural spans and uncertainty of the number of pumps pumping
T-98	T-99/T-100	26.50	Note 5	40	Note 2	1,525	10.79	6.00	4		27	$62.17	$1,647.52	
T-99/T-100	T-101/T-103	26.50	Note 5	40	Note 2	2,287	13.22	6.00	6		27	$62.17	$1,647.52	
T-101/T-103	T-103/T-104	26.50	Note 5	40	Note 2	3,050	15.26	6.00	8		27	$62.17	$1,647.52	
T-103/T-104	T-105/T-106	26.50	Note 5	40	Note 2	3,812	17.07	6.00	10		27	$62.17	$1,647.52	
T-105/T-106	T-107/T-108	26.50	Note 5	40	Note 2	4,575	18.69	6.00	12		27	$62.17	$1,647.52	
T-107/T-108	Emission Controls	75.00	Note 5	40	Note 2	5,337	20.19	6.00	14		75	$62.17	$4,662.80	
												Sum	$17,843.00	

Redundant Main Duct for CIP on Fermenters Only		$0	
1 Knock drums (7000 gallons) for foam overs on fermenters		$0	Eichleay
Ducting Isolation Components for all tanks with redundant main (X2)		$36,750	Previous Work
The main process pipe ways will need some modification to support the emission ducting systems		$60,000	Allowance
Ducting Cost		$76,213	
Support Allowance		$60,000	
	Total	**$136,213**	

1) The tanks in this and other diagrams are graphically shown as the same size for convenience of the spread sheet layout. The numbers in the cells around the tank layout reflect spacing and tank dimensions from the data base and Delicato lay out drawing.

2) Red dashed line is the most probable duct routing.

3) All tanks are rated for fermentation and storage.

4) At the time of this BACT analysis tank numbers were not shown on the Lay out drawing. The tank numbers shown in this and other parts of this analysis are subject to change.

5) Main ducts set at about 10 feet above ground.

Total tanks in bubble this sketch 20



Diameter in Feet 18.00

Shell Height in Feet 32.00

48.00 Center to Center of Tanks in Feet (Typical)

Main Duct Connection Length in Feet 75.00

CIP and **Emission Control Units**

Notes	Beginning Tank Numbers	Ending Tank Numbers	Length Between Nodes	From Top Tank Connection to Main Duct Length in Feet	Design Duct Velocity from Eichleay Feet/Second	Gas Flow Rate Storage Fill	Fermentation CFM at maximum CO2 rate from kinetic model	Duct size diameter in inches at node	Nominal Duct Size diameter in inches (See comments)	Number of Tanks feeding Ending Node	Total Number of Tanks to connect	Total feet	Cost Per Foot from Eichleay (See Comments)	Cost	Comments
Note 1: Tank Connection to Main Ducting. Red fermentation, white fermentation, and storage can be done in each tank.															
	Note 1	Note 1	Note 3	55.0	40	Note 2	258	4.44	6.00		20	1,100	$33.57	$36,929.41	Reduced to 3 inch size due to low gas flow

Note 2: All tanks are for Red Fermentation, White Fermentation, and Storage. Red Fermentation gas flow rates are used for the BACT analysis. Storage flows are shown on the storage flow tab for information only on a per tank bases.

Note 3: The length between nodes is the distance between the center of the circle representing the tank and its adjacent tank. Refer to tank number columns for location.

	Beginning Tank Numbers	Ending Tank Numbers	Length Between Nodes	From Top Tank Connection to Main Duct Length in Feet	Design Duct Velocity from Eichleay Feet/Second	Gas Flow Rate Storage Fill	Fermentation CFM at maximum CO2 rate from kinetic model	Duct size diameter in inches at node	Nominal Duct Size diameter in inches (See comments)	Number of Tanks feeding Ending Node	Total Number of Tanks to connect	Total feet	Cost Per Foot from Eichleay (See Comments)	Cost	Comments
Note 4: Tanks T-109 through T-128	T-109/T-110	T-111/T-112	19.50	Note 5	40	Note 2	515	6.27	6.00	2	16	20	$62.17	$1,212.33	
	T-111/T-112	T-113/T-114	19.50	Note 5	40	Note 2	1,030	8.87	6.00	4		20	$62.17	$1,212.33	
Note 5: The top of tank ducting to the main duct is calculated in row 2.	T-113/T-114	T-115/T-116	19.50	Note 5	40	Note 2	1,546	10.87	6.00	6		20	$62.17	$1,212.33	
	T-115/T-116	T-117/T-118	19.50	Note 5	40	Note 2	2,061	12.55	6.00	8		20	$62.17	$1,212.33	Main Duct Set at 6 inch size due to structural spans and uncertainty of the number of pumps pumping
	T-117/T-118	T-119/T-120	19.50	Note 5	40	Note 2	2,576	14.03	6.00	10		20	$62.17	$1,212.33	
	T-119/T-120	T-121/T-122	19.50	Note 5	40	Note 2	3,091	15.37	6.00	12		20	$62.17	$1,212.33	
	T-121/T-122	T-123/T-124	19.50	Note 5	40	Note 2	3,606	16.60	6.00	14		20	$62.17	$1,212.33	
	T-123/T-124	T-125/T-126	19.50	Note 5	40	Note 2	4,122	17.74	6.00	16		20	$62.17	$1,212.33	
	T-125/T-126	T-127/T-128	19.50	Note 5	40	Note 2	4,637	18.82	6.00	18		20	$62.17	$1,212.33	
	T-127/T-128	Emission Controls	75.00	Note 5	40	Note 2	5,152	19.84	6.00	20		75	$62.17	$4,662.80	
													Sum	$15,573.77	

Redundant Main Duct for CIP on Fermenters Only		$0	
1 Knock drums (7000 gallons) for foam overs on fermenters		$0	Eichleay
Ducting Isolation Components for all tanks with redundant main (X1)		$52,500	Previous Work
The main process pipe ways will need some modification to support the emission ducting systems		$60,000	Allowance
	Ducting Cost	$105,003	
	Support Allowance	$60,000	
	Total	$165,003	

Appendix D

Achieved-in-Practice Analysis

SAN JOAQUIN VALLEY UNIFIED AIR POLLUTION CONTROL DISTRICT MEMO

DATE: February 9, 2015 (Revised May 9, 2016)

TO: Dave Warner, Deputy APCO

FROM: Nick Peirce, Permit Services Manager
James Harader, Senior Air Quality Engineer
Jag Kahlon, Air Quality Engineer

SUBJECT: Achieved in Practice Analysis for Emission Control Technologies Used to Control VOC Emissions from Wine Fermentation Tanks

Introduction

The purpose of this analysis is to determine whether there is any control technologies that can be considered to be Achieved in Practice BACT for controlling fermentation VOC emissions from wine fermentation tanks. If determined to be achieved in practice, the San Joaquin Valley Air Pollution Control District (District) would require the use of such technology for wine fermentation tanks when BACT is triggered, without any consideration of the cost effectiveness of the control technology. The District's achieved in practice BACT is functionally equivalent to Federal EPA's Lowest Achievable Emission Rate requirements outlined in Federal Non-Attainment NSR documents.

LAER

The emission control requirement for new Major Sources and Federal Major Modifications in non-attainment areas is that the emission units meet the lowest achievable emission rate (LAER). LAER is the most stringent emission limitation from either of the following:

1. The most stringent emission limitation contained in the implementation plan of any State for such class and category of source; or
2. The most stringent emission limitation achieved in practice by such class or category of source.

In no event can the LAER requirement be less stringent than Federal New Source Performance Standards (NSPS), if there is an NSPS applicable to the type of source being evaluated.

In the case of wine fermentation tanks, the District did not identify any SIP that would require the use of add-on control systems. Therefore, add-on control systems can only be required as LAER for wine fermentation if they are determined to be achieved in practice for the source category.

Achieved in Practice Criteria

The term "achieved in practice" appears to be subject to interpretation since it is not defined in the federal statutes or regulations. As a result, there are few objective regulatory criteria to constrain the form of an achieved in practice determination. The following discussion outlines the achieved in practice criteria that is used by the District for determining LAER.

In a February 28, 1989 memorandum titled "Guidance on Determining Lowest Achievable Emission Rate (LAER), EPA provided the following guidance concerning the economic feasibility of LAER:

> *Traditionally, little weight has been given to economics in LAER determinations, and this continues to be the case. The extract in your memorandum from the record of the House and Senate discussion of the Clean Air Act (Act) contains the sentence:*
>
> > *"If the cost of a given control strategy is so great that a new major source could not be built or operated, then such a control would not be achievable and could not be required by the Administrator."*
>
> *We interpret this statement in the record to be used in a generic sense. That is, that no new plants could be built in that industry if emission limits were based on levels achievable only with the subject control technology. However, if some other plant in the same (or comparable) industry uses that control technology, then such use constitutes de facto evidence that the economic cost to the industry of that technology control is not prohibitive. Thus, for a new source in that same industry, LAER costs should be considered only to the degree that they reflect unusual circumstances which, in some manner, differentiate the cost of control for that source from the costs of control for the rest of that industry. These unusual circumstances should be thoroughly analyzed to ensure that they really do represent compelling reasons for not requiring a level of control that similar sources are using. Therefore, when discussing costs, applicants should compare the cost of control for the proposed source to the costs for source(s) already using that level of control.*

The statement *"If some other plant in the same (or comparable) industry uses that control technology, then such use constitutes de facto evidence that the economic cost to the industry of that technology control is not prohibitive"* is only true if the plant using that control technology purchased or leased that control technology. Scenarios where the purchase/lease of the control technology was subsidized with grant money, or where the plant allowed the control vendor to operate and test their equipment on-site without actually purchasing/leasing the control technology do not constitute evidence that the economic cost to the industry due to use of that technology control is not prohibitive. Therefore, the District's historical position is that a control technology must have been purchased or leased by the plant in order for that installation of the control technology to be considered as achieved in practice.

EPA Region IX has previously stated that the successful operation of a new control technology for six months constitutes achieved in practice. This position was established in an August 25, 1997 letter from David Howekamp of US EPA Region IX to Moshen Nazemi of South Coast Air Quality Management District. This guidance is reflected in the South Coast Air Quality Management District's BACT Policy, which includes the following criteria for determining whether a control technology is achieved in practice:

> *Reliability: All control technologies must have been installed and operated reliably for at least six months. If the operator did not require the basic equipment to operate daily, then the equipment must have at least 183 cumulative days of operation. During this period, the basic equipment must have operated: 1) at a minimum of 50% design capacity; or 2) in a manner that is typical of the equipment in order to provide an expectation of continued reliability of the control technology.*

For wine fermentation tanks, the District has taken the position that successful operation of a control device for one full fermentation season is satisfactory for qualifying a control as achieved in practice. The requirement of one full fermentation season is considerably more conservative than the 6-month requirement, since the fermentation season typically lasts only two to three months.

The term "successful operation" is not tightly defined. The District considers the following when determining whether a control technology has been successfully operated for achieved in practice BACT determinations:

1. Was the control technology operated in the same manner that would be required by the District if the control technology was required for BACT?
2. How reliable has the control technology been over the life of its use?
3. Has the control technology been verified to perform effectively over the range of operation expected for that type of equipment? Was the effectiveness verified by performance test(s), when possible, or using other performance data?

Other typical considerations that the District considers when making an achieved in practice BACT determination include:

1. Is the control technology commercially available from at least one vendor?
2. On what class and category of source has the control technology been demonstrated?

In summary, the following criteria are used for determining whether a control technology is achieved in practice for wine fermentation:

1. Did the plant using the control technology purchase/lease the equipment? Was that purchase/lease subsidized?
2. Was the control technology operated for at least one fermentation season?
3. Was the control technology operated in the same manner that would be required by the District for BACT purposes?
4. How reliable has the control technology been during its use at the plant?

5. Has the control technology been verified to perform effectively over the range of operation expected for that type of equipment? Was the effectiveness verified by performance test(s), when possible, or other performance data?
6. Is the control technology commercially available from at least one vendor?
7. On what class and category of source has the control technology been demonstrated?

Achieved in Practice Analysis for Known Installations of Wine Fermentation Control Technologies

The following is an analysis of each known installation of an emission control technology to control VOC emissions from wine fermentation tanks and whether that installation can be considered achieved in practice.

Terravant Wine Company (2008 – Current)

Terravant Wine Company submitted an Authority to Construct application for a wine processing facility to the Santa Barbara County Air Pollution Control District (SBCAPCD) on September 20, 2007. The application was deemed complete on October 19, 2007. The fermentation tanks triggered BACT; however, the SBCAPCD evaluation determined BACT to be infeasible. However, this project also triggered offsets and Terravant Wine Company electively proposed to install a packed bed water scrubber with UV/hydrogen peroxide controls to control VOC emissions from the wine fermentation tanks. Proposing the control would reduce VOC emissions to a level below the SBCAPCD offset threshold. The control technology is only required to run sufficiently to reduce emissions to stay below the offset threshold – it is not required to be operated all of the time, as is BACT-required equipment.

The packed bed water scrubber was installed in 2008 and began operation in 2008, with a 95% control efficiency requirement on the Authority to Construct permit. However, in 2008, the unit failed to meet the 95% control efficiency requirement. Prior to the 2009 season, Terravant Wine Company was issued a revised Authority to Construct permit that reduced the control efficiency requirement to 75%. However, the unit has not been able to consistently demonstrate compliance with the 75% control efficiency requirement. The effectiveness of the packed bed scrubber has varied considerably over its life, and has been measured to be as low as 49% control efficiency. During discussions, SBCAPCD staff indicated that this facility has been issued a Notice of Violation for non-compliance with their permitted emission limits and they would not recommend that any wineries use this control technology for the control of fermentation tank emissions, as it has proven to be unreliable. Finally, the control technology used by Terravant Winery is custom designed, and is not a commercially available off-the-shelf type of unit.

The packed bed scrubber technology does not meet the achieved in practice criteria since this control technology has not been operating in compliance with its permit requirements, its effectiveness is highly variable, and the control technology is not commercially available.

EcoPAS, LLC (2009)

EcoPAS conducted testing of their passive alcohol system, which is consendation-based emission control system, at a winery located within the San Luis Obispo County Air Pollution Control District. The purpose of this installation was to conduct full-scale testing of the passive alcohol system on red wine fermentation tanks. The District was unable to verify whether the winery purchased the system.

Since the District could not verify that the winery purchased the control system, this installation doesn't meet the first criteria listed to be considered as achieved in practice. Furthermore, the unit was operated for experimental testing of the control device. In the District's experience, during experimental testing/trial runs, a control technology does not typically operate in the same manner as would be required by BACT, so the District has not historically considered experimental test/trial installations to constitute achieved in practice BACT.

Central Coast Wine Services (2009)

In 2009, Santa Barbara County Air Pollution Control District (SBCAPCD) determined that Central Coast Wine Services (CCWS) was operating without a permit. They required CCWS to submit an application for an Authority to Construct such that the winery would be in compliance with SBCAPCD Rules and Regulations. Based on the emission estimates for the facility, the facility was triggering Best Available Control Technology Requirements and Offsets. At that time, the SBCAPCD determined that BACT, while technologically feasible, was not cost effective. SBCAPCD issued an Authority to Construct/Permit to Operate on June 5, 2009 for the winery.

CCWS was allowed to exceed the offset thresholds during the fall 2009 harvest season in order to test potential control technologies. Three companies were invited to participate in testing of prototype emission control equipment, but only NohBell Corporation elected to install and test fugitive ethanol control equipment.

NohBell Corporation engineered and tested a full scale NoMoVo 1.0 system on a 50 ton tank at the CCWS plant. NoMoVo documents describe the equipment as successful, with full scale trials proceeding. After the 2009 season, NoMoVo documents indicate that CCWS decided to move the plant and equipment.

This installation does not meet the requirements to be considered achieved in practice. First, the facility does not appear to have purchased/leased the control system, nor did they intend to continue operating the system. This is evident by their decision to discontinue use of the system in the following year. Second, no data has been submitted to the District to demonstrate that the unit was continuously operated in the same manner that the District would require the system to operate if it were considered achieved in practice BACT. The purpose of this installation was to perform initial testing and trial runs of the control technology. In the District's experience, during experimental testing/trial runs, a control technology does not typically operate in the same manner as

would be required by BACT, so the District has not historically considered experimental test/trial installations to constitute achieved in practice BACT. Furthermore, the type of records necessary to demonstrate continuous operation of the system was not required by the SBCAPCD permit. Finally, the SBCAPCD permit did not include testing requirements to sufficiently demonstrate the effectiveness of the system.

Kendall Jackson Oakville (2010)

Kendall Jackson Winery belongs to Jackson Family Wines Inc (JFW), and is located in Oakville, California. This winery is in Bay Area Air Quality Management District (BAAQMD). BAAQMD does not require permits for wine fermentation or storage operations. Their Regulation 2, Rule 1, 117.9 and 117.10 has exemptions for wine storage and fermentation operations.

In 2010, NohBell installed a NoMoVo 2.0 system at the Kendall Jackson Winery. The system was connected to a 10,000 gallon fermentation tank and operated on a trial basis during the 2010 crush season. Pursuant to Brian Kosi, Winemaker at Kedall-Jackson Oakville, JFW never purchased the NoMoVo technology. The NoMoVo slurry was treated by the facilities on-site wastewater treatment system.

This installation does not meet the requirements of achieved in practice BACT. First, the system was never owned/leased by the winery. Secondly, the unit was operated for the purposes of testing/trial runs to evaluate the control technology. In the District's experience, during experimental testing/trial runs, a control technology does not typically operate in the same manner as would be required by BACT, so the District has not historically considered experimental test/trial installations to constitute achieved in practice BACT. Furthermore, BAAQMD does not have any record of source tests occurring during the 2010 crush season; therefore, the effectiveness for this installation was not established.

Kendall Jackson Oakville (2011-2013)

In its 2010 clean air plan, the BAAQMD included a further study measure (FSM 14 – Winery Fermentation) to examine whether ethanol emissions from Bay Area wine production could be cost-effectively reduced. On 9/26/11, the BAAQMD signed a Research Sponsorship Agreement (Contract No. 2011-126) with NohBell to help develop its technology to capture volatile organic compounds emitted by wine fermentation tanks at Kendall Jackson Oakville. The contract states that *"District (BAAQMD) wishes to support NohBell's effort to demonstrate the technology at JFW winery and wishes to verify the function and cost-effectiveness of the technology and acquire data to help DISTRICT (BAAQMD) determine whether the equipment could be cost effectively employed more widely in the wine industry".* NoMoVo submitted a project budget estimate of $118,750 for its NoMoVo 2.0 upgrades, pump upgrades, and related work at the plant. The BAAQMD contract promised $50,000 towards this effort, to be paid in installments directly to NohBell Corporation. Furthermore, Brian Kosi of Kendall-Jackson Oakville confirmed that the facility never purchased the NoMoVo system from NohBell and confirmed that the system has been removed from the site by NohBell.

For 2011, NohBell Corporation planned to conduct trials of the upgraded NoMoVo 2.0 system on 10 fermentation tanks. Six to eight trials were anticipated, operating on 4-6 day cycles. The trial runs were scheduled to be primarily conducted while fermenting red wines. The District was unable to obtain operational data for the 2012 and 2013 fermentation seasons for this equipment. Following the 2013 crush season, the equipment was removed and transferred to Constellation Wines in Monterey, CA.

This installation does not pass the first criteria of LAER, since the facility never owned the system and since the installation and operation of the control technology by NohBell was subsidized by a Research Sponsorship Agreement with BAAQMD. Furthermore, operation of the control technology at this facility was for trials/testing of the effectiveness of the control technology. In the District's experience, during experimental testing/trial runs, a control technology does not typically operate in the same manner as would be required by BACT, so the District has not historically considered experimental test/trial installations to constitute achieved in practice BACT. Finally, the unit was removed, which indicates that this wasn't intended as a permanent installation. For these reasons, the District does not consider this installation to be achieved in practice.

J. Lohr Vineyard and Winery (2013)

NohBell Corporation has indicated that they operated a NoMoVo system at J. Lohr Winery in Paso Robles during 2013 crush season. The District contacted J. Lohr Winery to obtain more information regarding this installation. J. Lohr Winery personnel stated that they considered this to be a pilot type testing operation. J. Lohr Winery did not purchase or lease the system. The unit operated during the 2013 crush season on fermentation tanks that were processing red wine. After the 2013 crush season, the system was removed and no longer operates at this site. San Luis Obispo Air Pollution Control District (SLOAPCD) had no knowledge that this unit was installed at this winery and no Authority to Construct or permit exemption was issued for this equipment.

This installation does not pass the first criteria of LAER, since the facility never purchased/leased the equipment. Furthermore, operation of the control technology at this facility was for trials/testing of the effectiveness of the control technology at this facility. In the District's experience, during experimental testing/trial runs, a control technology does not typically operate in the same manner as would be required by BACT, so the District has not historically considered experimental test/trial installations to constitute achieved in practice BACT. Finally, the unit was removed, which indicates that this wasn't intended as a permanent installation. For these reasons, the District does not consider this installation to be achieved in practice.

Constellation Winery dba Gonzales Winery (2013)

During the 2013 crush season, a NoMoVo unit was installed on a 39,000 gallon fermentation tank at Constellation Brands U.S. Operations, Inc. dba Gonzales Winery in Monterey, CA. The control technology was installed and operated as a "pilot operation". Monterey Bay Unified Air Pollution Control District (MBUAPCD) compliance staff noticed the NoMoVo unit operating on-site without authorization from MBUAPCD and issued a notice of violation. Gonzales Winery submitted an Authority to Construct application; however, prior to processing that application, the facility notified MBUAPCD that the equipment had been removed from the site. The equipment operated at the site for a partial season for pilot testing purposes. MBUAPCD could not verify whether Gonzales Winery purchased or leased the equipment.

The District was unable to verify whether Gonzales Winery purchased or leased the NoMoVo unit. Furthermore, operation of the control technology at this facility was for trials/testing of the effectiveness of the control technology at this facility. In the District's experience, during experimental testing/trial runs, a control technology does not typically operate in the same manner as would be required by BACT, so the District has not historically considered experimental test/trial installations to constitute achieved in practice BACT. Finally, the unit was removed, which indicates that this wasn't intended as a permanent installation. For these reasons, the District does not consider this installation to be achieved in practice.

Vinwood Cellars Kenwood (2013)

The District has found documents indicating that a NoMoVo system was installed on four 15,000 gallon fermentation tanks at Vinwood Cellars Kenwood in Sonoma county, and the system was operated during the 2013 season. District staff attempted to contact Vinwood Cellars; however, the staff at Vinwood Cellars was unable to verify information for this installation. BAAQMD had no knowledge of this installation, as they do not require permits for wine tanks, so they were unable to verify this installation. Furthermore, since this installation was not subject to permit requirements, BAAQMD has no operational history or test data for this site. While BAAQMD administered source tests at Kendall Jackson Oakville winery, they have no records of any source testing of the NoMoVo system at Vinwood Cellars Kenwood.

This installation has not met the requirements of achieved in practice. First, it has yet to be confirmed that the winery actually purchased the NoMoVo system. Second, BAAQMD has no test records to verify the effectiveness of the NoMoVo system at this site. Finally, the operational history of the unit at this site is not available to determine whether it was operated in the same manner as a unit would be if it were installed as BACT.

Central Coast Wine Services (2013)

On August 5, 2013, CCWS electively applied to install a NoMoVo wine emission capture and control system to control ethanol emissions from fermentation activities at their wine center. The existing fermentation tanks at the facility ranged in capacity from 350 gallons to 20,887 gallons. On September 23, 2013, a final ATC (ATC 14257) was issued for the installation of the NoMoVo system, and the unit began operation in September 27, 2013. The installation of this unit allowed CCWS to increase daily wine fermentation while remaining under their existing daily and annual facility-wide VOC emission limits. A Permit to Operate (PTO 14257) was issued on December 13, 2013. PTO 14257 states: "*The NoMoVo system is optional and may be used at CCWS' discretion*". Thus, the permit does not require continuous operation of the NoMoVo system. The NoMoVo system is portable. The system can be attached to four or five fermentation tanks at a time via flexible hoses. The facility is allowed to move the NoMoVo system around, as desired, to capture emissions from the tanks where fermentation is taking place. However, there is no requirement to keep the NoMoVo system attached to a tank and operate it for the full fermentation cycle of that tank. Thus, the District was unable to confirm that the unit was operated in the continuous manner that would be required if the District considered NoMoVo to be achieved in practice BACT.

SBCAPCD PTO 14257 does not include a control efficiency requirement, does not include any source testing requirements to verify the control effectiveness of the control system. The effectiveness of the control has only been estimated using the density change of the NoMoVo slurry to estimate the quantity of ethanol capture, and using a theoretical calculation of the quantity of ethanol that would be emitted if the tanks were uncontrolled. Inlet and outlet air quality testing has not been performed for this particular installation.

Finally, the disposal of the NoMoVo slurry is an important consideration when determining the effectiveness of the control system. If the slurry is disposed of in a manner that re-emits the ethanol into the atmosphere, then the effectiveness of the control is diminished. Until August 2014, the CCWS facility disposed of the NoMoVo slurry in their on-site wastewater treatment facility. On August 21, 2014, SBCAPCD sent a letter to CCWS informing them that they have concerns over the treatment of the NoMoVo slurry. Specifically, SBAPCD was concerned about the potential for stripping of ethanol to the atmosphere during the on-site waste water treatment process. The SBCAPCD letter states "*In conclusion, after August 29, 2014, the District will not recognize emission reductions claimed based on the use of any of your NoMoVo systems (existing or new) at the facility until CCWS has a District-approved on-site or off-site ethanol disposal method in place*". On August 27th, 2014, SBCAPCD approved the disposal of the NoMoVo slurry at Southern California Waste Water, an off-site facility in Santa Paula, California. In November, 2014, a vacuum truck carrying toxic chemicals from an unrelated facility exploded spreading about 1200 gallons of chemical waste including sulfuric acid and highly combustible organic peroxide. Since that incident, Southern California Waste Water has discontinued the acceptance of waste from all of their clients, so this disposal option is no longer available for the waste generated by CCWS.

The waste is now shipped to a distillery, which distills the ethanol and converts it into vehicle fuel. SBCAPCD has yet to approve the disposal of the NoMoVo slurry to the on-site wastewater facility. Consequently, the overall effectiveness of the system, including any ethanol re-emitted into the atmosphere during disposal, has yet to be sufficiently determined.

Since the control technology has not been demonstrated to operate in a manner that would be required by BACT and the overall effectiveness of the control technology has yet to be sufficiently determined, the District does not consider this installation to be achieved in practice.

Central Coast Wine Services (2014/2015)

In 2014, CCWS submitted an Authority to Construct application for the installation of 40 new tanks, ranging in capacity from 7,407 gallons to 20,628 gallons. The proposal triggered BACT. CCWS decided to forego the normal BACT Analysis, and electively proposed to install six NoMoVo systems to control VOC emissions from the tanks, when the tanks were fermenting wine. A final ATC, (ATC 14350) was issued on July 28, 2014 and the tanks were installed for the 2014 season.

Unlike the previous installations of NoMoVo at this facility, the ATC requires use of the NoMoVo system on these tanks while fermentation is taking place, the permit requires a minimum capture and control efficiency, and the permit requires source testing to verify the effectiveness of the NoMoVo system. However, these tanks have yet to be used for fermentation and the effectiveness has yet to be determined for this installation of the NoMoVo system. An email from Richard Mather of CCWS to David Harris of SBCAPCD, dated September 16, 2014, states:

> *We won't be using the new tanks for fermentation this year, but since our ATC permit only gives us until August 1, 2015 to fulfill the source test plan, we will need to conduct the test this fall before our last fermentation. It would be highly unlikely that we would be conducting fermentation next year before August 1. Since harvest is progressing rapidly, we probably only have several weeks of fermentation left this year.*

Prior to the 2015 season, CCWS received another Authority to Construct for the 40 new tanks that allowed the use of either NoMoVo or EcoPAS control systems. The new Authority to Construct continued to require inlet/outlet testing of the control system. However, that Authority to Construct was later cancelled due to both technology vendors objecting to perform the required source tests to demonstrate the control efficiency of their respective systems. Rather, CCWS was issued a new ATC allowing only 10 of the 40 tanks to be used for fermentation, and limiting fermentation to white wine only. With those changes to the permits, BACT was no longer triggered and the requirement to demonstrate the actual control efficiency was removed from the permits. Additionally, the use of the NoMoVo or EcoPAS control systems was no longer required; rather, the permit allowed for optional use on the 10 tanks that are allowed to ferment white wine.

The refusal of the control vendors to demonstrate the actual control efficiency raises significant questions and concerns over the vendors' control efficiency claims. The Valley Air District cannot, in good faith, require controls which the vendors refuse to validate. The District's concern is that, if the vendors of this technology are aware that claims of the control efficiency are potentially overstated, but they also know that EPA is about to require their technology to be installed on a widespread basis, they gain no advantage by demonstrating their actual control efficiency. Since the effectiveness was yet again not demonstrated in 2015, and for the reasons stated in the 2013 evaluation of the use of controls at CCWS, the criteria of Achieved in Practice have yet to be satisfied for these installations.

Conclusion

For the reasons listed in the above discussions of each control installation, none of the installations have met all of the criteria necessary for the control technology to be considered as achieved in practice BACT or federal LAER.

Appendix E

Compliance Certification

San Joaquin Valley
Unified Air Pollution Control District

TITLE V MODIFICATION - COMPLIANCE CERTIFICATION FORM

I. TYPE OF PERMIT ACTION (Check appropriate box)

[X] SIGNIFICANT PERMIT MODIFICATION
[ ] MINOR PERMIT MODIFICATION
[ ] ADMINISTRATIVE AMENDMENT

COMPANY NAME: Delicato Family Vineyards	FACILITY ID: N-266
1. Type of Organization:[X] Corporation [ ] Sole Ownership [ ] Government [ ] Partnership [ ] Utility	
2. Owner's Name: Chris Indelicato	
3. Agent to the Owner: John Yarborough	

II. COMPLIANCE CERTIFICATION (Read each statement carefully and initial **all** circles for confirmation):

(O) Based on information and belief formed after reasonable inquiry, the equipment identified in this application will continue to comply with the applicable federal requirement(s).

(O) Based on information and belief formed after reasonable inquiry, the equipment identified in this application will comply with applicable federal requirement(s) that will become effective during the permit term, on a timely basis.

(O) Corrected information will be provided to the District when I become aware that incorrect or incomplete information has been submitted.

(O) Based on information and belief formed after reasonable inquiry, information and statements in the submitted application package, including all accompanying reports, and required certifications are true accurate and complete.

I declare, under penalty of perjury under the laws of the state of California, that the forgoing is correct and true:

Signature of Responsible Official

6/3/15

Date

John Yarborough

Name of Responsible Official (please print)

VP of Winery Operations

Title of Responsible Official (please print)

Appendix F

Revised Draft ATCs

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-831-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
154,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-10) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

Northern Regional Office • 4800 Enterprise Way • Modesto, CA 95356-8718 • (209) 557-6400 • Fax (209) 557-6475

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-832-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
154,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-11) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-832-0 : Dec 14 2016 10:36AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-833-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
154,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-12) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

Northern Regional Office • 4800 Enterprise Way • Modesto, CA 95356-8718 • (209) 557-6400 • Fax (209) 557-6475

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-834-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
154,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-13) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-834-0 : Dec 14 2016 10:30AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-835-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
154,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-14) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-835-0 : Dec 14 2016 10:36AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-836-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
154,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-15) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

N-266-836-0 : Dec 14 2016 10:36AM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-837-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
154,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-16) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-837-0 : Dec 14 2016 10:36AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-838-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-17) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-838-0 : Dec 14 2016 10:36AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-839-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-18) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-839-0 : Dec 14 2016 10:36AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-840-0 **ISSUANCE DATE:** DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-19) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-840-0 Dec 14 2016 10:36AM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-841-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-20) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-841-0 Dec 14 2016 10:36AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-842-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-21) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-842-0 : Dec 14 2016 10:36AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-843-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-22) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-843-0 : Dec 14 2016 10:36AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-844-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-23) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

Northern Regional Office • 4800 Enterprise Way • Modesto, CA 95356-8718 • (209) 557-6400 • Fax (209) 557-6475

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-845-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-24) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-845-0 : Dec 14 2016 10:36AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-846-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-25) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

N-266-846-0 : Dec 14 2016 10:36AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-847-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-26) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-847-0 : Dec 14 2016 10:36AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-848-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-27) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-848-0 : Dec 14 2016 10:36AM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-849-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-28) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

Northern Regional Office • 4800 Enterprise Way • Modesto, CA 95356-8718 • (209) 557-6400 • Fax (209) 557-6475

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-850-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-29) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-850-0 : Dec 14 2016 10:36AM -- GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-851-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-30) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-851-0 : Dec 14 2016 10:36AM -- GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-852-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-31) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-852-0 : Dec 14 2016 10:36AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-853-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-32) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

N-266-853-0 : Dec 14 2016 10:36AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-854-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-33) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-854-0 : Dec 14 2016 10:36AM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-855-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-34) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

Northern Regional Office • 4800 Enterprise Way • Modesto, CA 95356-8718 • (209) 557-6400 • Fax (209) 557-6475

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-856-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-35) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-856-0 : Dec 14 2016 10:36AM -- GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-857-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-36) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

Northern Regional Office • 4800 Enterprise Way • Modesto, CA 95356-8718 • (209) 557-6400 • Fax (209) 557-6475

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-858-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-37) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-858-0 Dec 14 2016 10:36AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit
21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit
22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-859-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-38) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

Northern Regional Office • 4800 Enterprise Way • Modesto, CA 95356-8718 • (209) 557-6400 • Fax (209) 557-6475

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-860-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-39) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

Northern Regional Office • 4800 Enterprise Way • Modesto, CA 95356-8718 • (209) 557-6400 • Fax (209) 557-6475

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, . calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-861-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-40) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

Northern Regional Office • 4800 Enterprise Way • Modesto, CA 95356-8718 • (209) 557-6400 • Fax (209) 557-6475

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-862-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-41) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

Northern Regional Office • 4800 Enterprise Way • Modesto, CA 95356-8718 • (209) 557-6400 • Fax (209) 557-6475

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-863-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-42) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-863-0 : Dec 14 2016 10:35AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-864-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-43) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

Northern Regional Office • 4800 Enterprise Way • Modesto, CA 95356-8718 • (209) 557-6400 • Fax (209) 557-6475

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-865-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
103,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-44) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 40 feet in height with a proposed volume of 103,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-865-0 : Dec 14 2016 10:35AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-866-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-45) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

Northern Regional Office • 4800 Enterprise Way • Modesto, CA 95356-8718 • (209) 557-6400 • Fax (209) 557-6475

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-867-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-46) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-867-0 : Dec 14 2016 10:36AM -- GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-868-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-47) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-868-0 : Dec 14 2016 10:36AM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit
21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit
22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-869-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-48) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-869-0 Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-870-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-49) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-870-0 : Dec 14 2010 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-871-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-50) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-871-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-872-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-51) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-872-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-873-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-52) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-873-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-874-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-53) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

Northern Regional Office • 4800 Enterprise Way • Modesto, CA 95356-8718 • (209) 557-6400 • Fax (209) 557-6475

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-875-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-54) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-875-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-876-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-55) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-876-0 : Dec 14 2016 10:37AM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-877-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-56) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-877-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-878-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-57) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

Northern Regional Office • 4800 Enterprise Way • Modesto, CA 95356-8718 • (209) 557-6400 • Fax (209) 557-6475

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-879-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-58) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

N-266-879-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-880-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-59) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

N-266-880-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-881-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-60) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-881-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-882-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-61) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

N-266-882-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-883-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-45) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-883-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-884-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-63) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-884-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-885-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-64) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-885-0 : Dec 14 2016 10:37AM -- GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-886-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-65) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-886-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-887-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-66) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

N-266-887-0 Dec 14 2016 10:37AM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-888-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-67) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

Northern Regional Office • 4800 Enterprise Way • Modesto, CA 95356-8718 • (209) 557-6400 • Fax (209) 557-6475

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-889-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-68) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-889-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-890-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-69) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

N-266-890-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-891-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-70) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-891-0 Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-892-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-71) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

N-266-892-0 : Dec 14 2010 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-893-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-72) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-893-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-894-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-73) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-894-0 : Dec 14 2016 10:37AM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-895-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-74) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-895-0 : Dec 14 2016 10:37AM – GARCIAJ | Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-896-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-75) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-896-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-897-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-76) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

N-266-897-0 : Dec 14 2016 10:37AM -- GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-898-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-77) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-898-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-899-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-78) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-899-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-900-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-79) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-900-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-901-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-80) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

Northern Regional Office • 4800 Enterprise Way • Modesto, CA 95356-8718 • (209) 557-6400 • Fax (209) 557-6475

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-902-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-81) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-902-0 : Dec 14 2016 10:37AM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-903-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-82) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-903-0 : Dec 14 2016 10:37AM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-904-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-83) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-904-0 Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-905-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-84) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

N-266-905-0 Dec 14 2016 10:37AM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-906-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-85) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-906-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-907-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-86) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-907-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-908-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-87) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

N-266-908-0 : Dec 14 2016 10:37AM -- GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-909-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-88) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

N-266-909-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-910-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-89) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-910-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-911-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-90) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-911-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-912-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-91) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

N-266-912-0 : Dec 14 2016 10:37AM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-913-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-92) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

N-266-913-0 Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-914-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-93) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-914-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-915-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
60,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-94) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 16 feet in diameter and 40 feet in height with a proposed volume of 60,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

Northern Regional Office • 4800 Enterprise Way • Modesto, CA 95356-8718 • (209) 557-6400 • Fax (209) 557-6475

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-916-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
74,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-95) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 28 feet in height with a proposed volume of 74,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-916-0 Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-917-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
74,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-96) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 28 feet in height with a proposed volume of 74,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-917-0 : Dec 14 2016 10:37AM -- GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-918-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
74,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-97) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 28 feet in height with a proposed volume of 74,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-918-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-919-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
74,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-98) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 28 feet in height with a proposed volume of 74,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-919-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-920-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
74,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-99) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 28 feet in height with a proposed volume of 74,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-920-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-921-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
74,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-100) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 28 feet in height with a proposed volume of 74,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

N-266-921-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-922-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
74,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-101) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 28 feet in height with a proposed volume of 74,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-922-0 Dec 14 2016 10:37AM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-923-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
74,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-102) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 28 feet in height with a proposed volume of 74,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-923-0 Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-924-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
74,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-103) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 28 feet in height with a proposed volume of 74,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-924-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-925-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
74,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-104) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 28 feet in height with a proposed volume of 74,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-925-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-926-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
74,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-105) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 28 feet in height with a proposed volume of 74,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-926-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-927-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
74,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-106) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 28 feet in height with a proposed volume of 74,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-927-0 : Dec 14 2016 10:37AM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-928-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
74,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-107) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 28 feet in height with a proposed volume of 74,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

Northern Regional Office • 4800 Enterprise Way • Modesto, CA 95356-8718 • (209) 557-6400 • Fax (209) 557-6475

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-929-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
74,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-108) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 21 feet in diameter and 28 feet in height with a proposed volume of 74,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-929-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-930-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-109) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-930-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-931-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-110) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-931-0 Dec 14 2016 10:37AM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-932-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-111) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-932-0 Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit
21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit
22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit
23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-933-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-112) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-933-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-934-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-113) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

N-266-934-0 Dec 14 2016 10:37AM -- GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-935-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-114) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

N-266-935-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-936-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-115) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-936-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-937-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-116) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-937-0 : Dec 14 2016 10:37AM -- GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-938-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-117) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

Northern Regional Office • 4800 Enterprise Way • Modesto, CA 95356-8718 • (209) 557-6400 • Fax (209) 557-6475

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-939-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-118) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

Northern Regional Office • 4800 Enterprise Way • Modesto, CA 95356-8718 • (209) 557-6400 • Fax (209) 557-6475

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-940-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-119) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-940-0 : Dec 14 2016 10:37AM -- GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-941-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-120) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-941-0 Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-942-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-121) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-942-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-943-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-122) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

Northern Regional Office • 4800 Enterprise Way • Modesto, CA 95356-8718 • (209) 557-6400 • Fax (209) 557-6475

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-944-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-123) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-944-0 Dec 14 2016 10:37AM -- GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-945-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-124) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

Northern Regional Office • 4800 Enterprise Way • Modesto, CA 95356-8718 • (209) 557-6400 • Fax (209) 557-6475

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-946-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-125) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

Northern Regional Office • 4800 Enterprise Way • Modesto, CA 95356-8718 • (209) 557-6400 • Fax (209) 557-6475

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-947-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-126) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

N-266-947-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-948-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-127) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-948-0 : Dec 14 2016 10:37AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-949-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
50,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-128) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 18 feet in diameter and 32 feet in height with a proposed volume of 50,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-949-0 : Dec 14 2016 10:37AM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-822-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
154,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-1) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-822-0 : Dec 14 2016 10:36AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-823-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
154,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-2) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-823-0 : Dec 14 2016 10:36AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-824-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
154,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-3) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

N-266-824-0 : Dec 14 2016 10:36AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-825-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
154,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-4) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-825-0 Dec 14 2016 10:36AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-826-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
154,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-5) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-826-0 Dec 14 2016 10:36AM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-827-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
154,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-6) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

Northern Regional Office • 4800 Enterprise Way • Modesto, CA 95356-8718 • (209) 557-6400 • Fax (209) 557-6475

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-828-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
154,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-7) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-828-0 : Dec 14 2016 10:38AM – GARCIAJ : Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-829-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
154,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-8) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services
N-266-829-0 Dec 14 2016 10:35AM – GARCIAJ Joint Inspection NOT Required

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit

7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit

8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit

9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit

10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit

11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit

13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit

14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit

15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit

16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit

17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

AUTHORITY TO CONSTRUCT

DRAFT

PERMIT NO: N-266-830-0

ISSUANCE DATE: DRAFT

LEGAL OWNER OR OPERATOR: DELICATO VINEYARDS
MAILING ADDRESS: 12001 S HIGHWAY 99
MANTECA, CA 95336

LOCATION: 12001 S HIGHWAY 99
MANTECA, CA 95336

EQUIPMENT DESCRIPTION:
154,000 GALLON NOMINAL STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK # T-9) WITH PRESSURE/VACUUM VALVE AND INSULATION

CONDITIONS

1. The permittee shall not implement the changes authorized in this Authority to Construct until a final Part 70 permit amendment is issued by the District. [District Rule 2520, 6.3] Federally Enforceable Through Title V Permit
2. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
3. The nominal tank dimensions are 25 feet in diameter and 40 feet in height with a proposed volume of 154,000 gallons. The permittee shall submit to the District the gauge volume of the tank within 30 days of the actual tank capacity measurement. [District Rule 2201] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
5. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit

CONDITIONS CONTINUE ON NEXT PAGE

YOU MUST NOTIFY THE DISTRICT COMPLIANCE DIVISION AT (209) 557-6400 WHEN CONSTRUCTION IS COMPLETED AND PRIOR TO OPERATING THE EQUIPMENT OR MODIFICATIONS AUTHORIZED BY THIS AUTHORITY TO CONSTRUCT. This is NOT a PERMIT TO OPERATE. Approval or denial of a PERMIT TO OPERATE will be made after an inspection to verify that the equipment has been constructed in accordance with the approved plans, specifications and conditions of this Authority to Construct, and to determine if the equipment can be operated in compliance with all Rules and Regulations of the San Joaquin Valley Unified Air Pollution Control District. Unless construction has commenced pursuant to Rule 2050, this Authority to Construct shall expire and application shall be cancelled two years from the date of issuance. The applicant is responsible for complying with all laws, ordinances and regulations of all other governmental agencies which may pertain to the above equipment.

Seyed Sadredin, Executive Director / APCO

DRAFT

Arnaud Marjollet, Director of Permit Services

Northern Regional Office • 4800 Enterprise Way • Modesto, CA 95356-8718 • (209) 557-6400 • Fax (209) 557-6475

6. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
7. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The ethanol content of wine stored in this tank shall not exceed 20 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The maximum daily wine storage throughput shall not exceed 4 times the nominal tank capacity stated in the equipment description. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Annual emissions from all wine fermentation and storage tanks listed under permits N-266-822 through N-266-949, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 269,842 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Facility-wide annual emissions from all wine fermentation and storage tanks, calculated on a twelve month rolling basis, shall not exceed the following limit: VOC - 394,298 lb/year. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The annual VOC emissions from wine fermentation in this tank, calculated on a 12 month rolling basis, shall be determined by the following formula: Annual Fermentation VOC emissions = 2.5 lb-VOC/1,000 gallons x Annual White Wine Production (in 1,000 gallons) + 6.2 lb-VOC/1,000 gallons x Annual Red Wine Production (in 1,000 gallons). [District Rule 2201] Federally Enforceable Through Title V Permit
14. Total annual VOC emissions from wine storage operations shall be determined either as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit; or as the emissions for total annual wine movements and a single storage emissions factor, calculated using the equation(s) specified within this permit, based on the average ethanol content of the total annual wine movements. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The annual VOC wine storage emission factor for each wine ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; P is the volume percent ethanol of the wine being transferred; a = -0.38194; b = 0.97917; and c = 0. [District Rule 2201] Federally Enforceable Through Title V Permit
16. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
17. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
18. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

CONDITIONS CONTINUE ON NEXT PAGE

19. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume and ethanol content of each wine movement; and the calculated 12 month rolling wine throughput rate for fermentation operations (gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit

20. On a monthly basis, the permittee shall calculate and record the VOC emissions from the wine fermentation and storage operations in pounds from the tanks under permits N-266-822 through N-266-949 for the rolling 12-month period including calculation methods and parameters used. The VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from each tank. [District Rule 2201] Federally Enforceable Through Title V Permit

21. On a monthly basis, the permittee shall calculate and record the facility-wide VOC emissions from all wine fermentation and storage operations in pounds for the rolling 12-month period including calculation methods and parameters used. The facility-wide VOC emissions shall be calculated by summing the VOC emissions from the previous 12 months from every permitted wine fermentation and/or storage tank at this facility. [District Rule 2201] Federally Enforceable Through Title V Permit

22. If the emissions calculated for any rolling 12-month period exceed the annual emissions limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the annual emissions limit for that rolling 12-month period will be deemed to have occurred so long as the calendar year emissions are below the annual emissions limitation. [District Rule 2201] Federally Enforceable Through Title V Permit

23. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit

24. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

DRAFT

Appendix G

FYI-114

FYI-114

SAN JOAQUIN VALLEY UNIFIED AIR POLLUTION CONTROL DISTRICT

DATE: March 8, 2007 (Revised 09/14/09) (Revised 8/10/11) (Revised 6/13/12)

TO: Permit Services Staff

FROM: Dennis Roberts

SUBJECT: VOC Emission Factors for Wine Fermentation and Storage Tanks

Winery tank operations generally consist of two separate emissions units; 1) fermentation and 2) storage of wine and spirits. Any particular tank may be permitted to perform one or both of these operations. The emissions from each emission unit are appropriately combined to yield the Potential to Emit for the tank (permit unit).

Emissions from fermentation operations are estimated using emission factors which have been developed based on a recognized fermentation model and are presented herein. For wine storage operations, emissions can be determined in general by modeling the storage tank operation using the EPA's Tanks 4.0 software (modeling procedures and an ethanol/water data base have been established as described in FYI-295 (*Modeling Emissions from Wine Storage Tanks).* However, the majority of wine storage tanks located in the District are insulated storage tanks which do not have a requirement for refrigeration (ambient storage temperature). For this classification of tank the storage emission factor, as calculated by the Tanks 4.0 model, is a function of ethanol content only. For this case the tabular emission factors presented herein are applicable (note that storage tanks which are un-insulated and/or which have NSR limits on the tank operating temperature should be estimated by the emissions modeling per FYI-295).

Wine Storage Tanks

Wine storage tanks perform two functions in the winery:

- Facilitation of post-fermentation processing operations such as racking, filtration, malolactic fermentation and bottling. In this role, the typical storage tank is filled and emptied several times per year with the wine being transferred from tank to tank. Many of these operations occur prior to chilling of the wine. Emissions from such operations are "working losses" which occur as a result of the displacement of the vapor space of the tank into the atmosphere during the filling operations. For insulated tanks (or tanks installed in a climate-controlled building), working losses are a function only of the ethanol content, the ambient temperature and the tank throughput.

- Static storage of wine between processing operations up to the final operation of bottling. In this operation, a common objective is to avoid oxidation of the wine by both minimizing the wine temperature and the exposure of the wine to air. In such cases, the wine may be maintained at a temperature below ambient, often in the range of 35-40 °F, however, since the tank cannot be always maintained at this temperature due to processing considerations, the lower temperatures are not an NSR condition on the permit . Also, the tanks are typically maintained at as high a liquid level as possible to minimize contact with oxygen. Emissions from static storage are

"breathing losses" which are the result of diurnal heating and cooling caused by the effect of daily variations in atmospheric conditions on the contents of the tank. For a well-insulated tank, equipped with a pressure/vacuum relief valve per the requirements of District Rule 4694, breathing losses are considered to be negligible since the insulation serves to maintain a relatively uniform temperature inside the tank while the pressure/vacuum valve serves to contain small internal variations, preventing escape of vapor to the atmosphere.

Table 1 presents emission factors for wine and spirits storage in ambient temperature tanks (non-refrigerated), equipped with insulation and/or located in a climate-controlled building. The tabular values have been developed using the District's emissions modeling procedure for wine and spirits tanks (see FYI-295). As shown, different emission factors are presented for tanks located in the three different regions of the District based upon higher ambient temperatures in the southern part of the Central Valley. All factors represent working losses only since breathing losses are considered negligible as discussed above. Emission factors for concentrations not listed in Table 1 may be interpolated from the table.

Table 1: Emission Factors for Wine and Spirits Storage Tanks by Region in the San Joaquin Valley lb-VOC per 1,000 gallons of throughput						
Applicability:	1. Vertical Fixed-Roof tank, insulated or located in climate-controlled building 2. Ambient temperature storage					
	Southern Region		Central Region		Northern Region	
Vol %	Annual	Daily	Annual	Daily	Annual	Daily
2	0.016	0.029	0.015	0.027	0.014	0.024
4	0.033	0.062	0.032	0.057	0.030	0.051
6	0.052	0.099	0.050	0.092	0.047	0.081
8	0.074	0.141	0.071	0.130	0.067	0.116
10	0.098	0.187	0.094	0.173	0.088	0.154
12	0.125	0.239	0.120	0.221	0.112	0.196
14	0.143	0.273	0.137	0.252	0.128	0.223
16	0.159	0.302	0.153	0.280	0.143	0.248
18	0.176	0.334	0.169	0.310	0.159	0.275
20	0.195	0.368	0.187	0.341	0.175	0.303
22	0.215	0.404	0.207	0.375	0.194	0.333
24	0.237	0.443	0.227	0.412	0.213	0.366
26	0.251	0.470	0.242	0.436	0.227	0.388
28	0.264	0.494	0.254	0.458	0.238	0.408
30	0.278	0.518	0.267	0.481	0.251	0.428
32	0.293	0.544	0.281	0.506	0.264	0.450
34	0.308	0.572	0.296	0.531	0.278	0.473
36	0.324	0.600	0.312	0.559	0.293	0.498
38	0.335	0.620	0.323	0.577	0.303	0.514
40	0.347	0.640	0.334	0.595	0.313	0.530
42	0.358	0.660	0.345	0.614	0.324	0.546
44	0.371	0.681	0.357	0.634	0.335	0.565
46	0.384	0.703	0.370	0.655	0.348	0.584
48	0.396	0.724	0.381	0.674	0.359	0.602
50	0.405	0.738	0.390	0.688	0.367	0.615
52	0.415	0.754	0.400	0.703	0.376	0.628
54	0.425	0.770	0.410	0.718	0.386	0.642
56	0.436	0.788	0.420	0.734	0.396	0.657
58	0.447	0.805	0.431	0.751	0.406	0.673
60	0.455	0.818	0.438	0.764	0.413	0.684
62	0.462	0.832	0.446	0.777	0.420	0.695
64	0.471	0.847	0.454	0.790	0.427	0.708
66	0.479	0.863	0.462	0.805	0.435	0.721
68	0.489	0.879	0.471	0.820	0.443	0.735
70	0.497	0.896	0.479	0.836	0.451	0.748
72	0.507	0.914	0.488	0.853	0.460	0.763
74	0.517	0.933	0.498	0.871	0.468	0.779
76	0.527	0.954	0.508	0.890	0.478	0.796
78	0.539	0.976	0.519	0.910	0.489	0.814
80	0.552	1.000	0.531	0.932	0.500	0.833
82	0.566	1.025	0.545	0.955	0.513	0.855
84	0.581	1.052	0.559	0.981	0.526	0.877
86	0.598	1.083	0.576	1.010	0.542	0.903
88	0.617	1.120	0.595	1.044	0.559	0.934
90	0.639	1.161	0.616	1.082	0.579	0.967
92	0.663	1.206	0.639	1.124	0.601	1.004
94	0.694	1.261	0.669	1.175	0.629	1.050
96	0.742	1.339	0.715	1.249	0.673	1.118
98	0.786	1.409	0.757	1.315	0.714	1.179
100	0.838	1.534	0.807	1.437	0.762	1.278

For purposes of calculating actual annual emissions, the annual data in Table 1 have been curve-fitted based on an equation of the form $E_f = ap^2 + bp + c$, where p = vol% ethanol (e.g., 20% = 0.20). The constants for the equation are as follows:

Constants for Emission Factor Correlation $E_f = ap^2 + bp + c$ p = volume percentage ethanol			
Southern Region			
Concentration Range	**a**	**b**	**c**
0 to 24%	-0.45139	1.0958	0
>24 to 66%	-0.47357	1.0088	0.019486
>66% to 92%	1.5279	-1.7467	0.97149
>92% to 100%	6.7857	-10.819	4.8713
Central Region			
Concentration Range	**a**	**b**	**c**
0 to 24%	-0.45139	1.0542	0
>24 to 66%	-0.45117	0.96968	0.018554
>66% to 92%	1.5254	-1.7662	0.96812
>92% to 100%	6.4286	-10.223	4.6016
Northern Region			
Concentration Range	**a**	**b**	**c**
0 to 24%	-0.38194	0.97917	0
>24 to 66%	-0.42159	0.91316	0.016237
>66% to 92%	1.3799	-1.5774	0.87906
>92% to 100%	6.6071	-10.651	4.8061

The mathematical correlation for concentrations up to 24% provides a slightly conservative estimate of the emission factor relative to the data in Table 1 based on smoothing the impact of the linear interpolation process employed in development of the ethanol/water data base used for modeling wine tank emissions in EPA Tanks 4.0. Mathematical correlations for concentrations greater than 24% are based on a least square analysis of the data in Table 1.

Use of Table I and correlations to estimate emissions insulated wine storage tank subject to ambient temperature is demonstrated by the following examples:

Example 1 (wine storage tank with daily and annual throughput limits and maximum ethanol content) – estimate the potential to emit for an insulated 100,000 gallon nominal capacity steel storage tank to store wine with maximum concentration of 14 vol% ethanol . Maximum daily throughput is one tank turn or 100,000 gallons/day. Maximum annual throughput will be 600,000 gallons per year. The tank will be installed in a facility located in the Southern Region.

For a storage tank located in the Southern Region and handling up to 14% ethanol, the annual emission factor is 0.143 lb-VOC/1000 gallons throughput and the daily emission factor is 0.273 lb-VOC/1000 gallons throughput.

Daily PE = 100,000 gallons/day x 0.273 lb-VOC/1000 gallons = 27.3 lb-VOC/day

Annual PE = 600,000 gallons/year x 0.143 lb-VOC/1000 gallons = 86 lb-VOC/year

DEL conditions for this example would be:

- *Ethanol content of wine in this tank shall not exceed 14.0 percent by volume. [District Rule 2201]*
- *Tank throughput shall not exceed either of the following limits: 100,000 gallons in any one day or 600,000 gallons per year. [District Rule 2201]*

Example 2 (wine and spirits storage tank subject to a daily throughput limit and an SLC limit on annual emissions)– – estimate the potential to emit for an insulated 100,000 gallon nominal capacity steel storage tank to store spirits with maximum concentration of 80 vol% ethanol. Maximum allowed annual emissions for the tanks in the SLC are 10,000 lb/year. Maximum daily throughput is one tank turn or 100,000 gallons/day. The tank will be installed in a facility located in the Northern Region.

For a storage tank located in the Northern Region and handling up to 80% ethanol, the daily emission factor is 0.833 lb-VOC/1000 gallons throughput. Since the annual emissions are constrained by the SLC, an annual emission factor is not needed for the PE calculation but will be placed on the permit for purposes of demonstrating annual compliance on an ongoing basis. Since the ethanol concentration can vary from 0% to 80%, three separate correlation equations are required to cover the potential range:

For concentration p = 0 – 24%: $E_f = ap^2 + bp + c$

a = -0.38194
b = 0.97917
c = 0

For concentration p = 24% < p < 66%: $E_f = ap^2 + bp + c$

a = -0.42159
b = 0.91316
c = 0.016237

For concentration p = 66% < p < 80%: $E_f = ap^2 + bp + c$

a = 1.3799
b = -1.5774
c = 0.87906

Daily PE = 100,000 gallons/day x 0.833 lb-VOC/1000 gallons = 83.3 lb-VOC/day

DEL conditions for this example would be:

- *Ethanol content of wine or spirits in this tank shall not exceed 80.0 percent by volume. [District Rule 2201]*
- *Tank throughput shall not exceed 100,000 gallons in any one day. [District Rule 2201]*
- *Combined annual VOC emissions from all wine storage operations under permit units X-XXXX-XXX through X-XXXX-XXX shall not exceed 10,000 pounds per year. [District Rule 2201]*
- *Combined annual VOC emissions from wine storage operations under permit units X-XXXX-XXX through X-XXXX-XXX shall be determined as the sum of the emissions for each individual wine movement based on the volume transferred in each wine movement and the batch-specific wine storage emission factor calculated using the equation(s) specified within this permit. [District Rule 2201]*
- *The annual VOC wine storage emission factor for each wine or spirits ethanol content shall be calculated using the following equation: EF = a * P^2 + b*P + c; where EF is the VOC emission factor in pounds of VOC per 1000 gallons of wine throughput; and P is the volume percent ethanol of the wine being transferred. For concentrations up to and including 24 volume %,* a = -0.38194, b = 0.97917 and c = 0. *For concentrations greater than 24 volume % up to and including 66 volume% ,* a = -0.42159, b = 0.91316 and c = 0.016237. *For concentrations greater than 66 volume % up to and including 80 volume %,* a = 1.3799, b = -1.5774 and c = 0.87906. *[District Rule 2201]*

Wine Fermentation Tanks

During the wine fermentation process, sugar in the grape juice reacts with yeast to form alcohol (ethanol) and carbon dioxide (CO_2) gas. Ethanol is emitted into the atmosphere through evaporation. According to Williams and Boulton[1], the only important mechanism for ethanol loss is equilibrium evaporation into the escaping CO_2 stream. The physical entrainment of ethanol droplets in the CO_2 gas is insignificant in modern enclosed fermentation vessels. These researchers' model indicates that as fermentation temperature increases, ethanol loss increases exponentially. Since red wines are fermented at significantly higher temperatures than white wine, a different emission factor is required for each case.

Annual Fermentation Emission Factors

The California Air Resources Board (CARB) has established annual emission factors for fermentation of both red and white wines, based on the computer model developed by Williams and Boulton. The emission factors were developed for purposes of emission

[1] L.A. Williams and R. Boulton, Modeling and Prediction of Evaporative Ethanol Loss During Wine Fermentation, American Journal of Enology and Vitriculture, 32:234-242, (1983).

inventory estimation and represent a typical wine fermentation operation based on average fermentation temperatures and average initial sugar concentrations (°Brix) and are presented in Emissions Inventory Procedural Manual, Section 5.1, Air Resources Board, 1997. These factors have been adopted by the District in Rule 4694, *Wine Fermentation and Storage Tanks*. The established factors are as follows:

Red Wine Fermentation:	6.2 lb-VOC/1000 gallons fermented per year (78 °F fermentation temperature, 21.8 °Brix)
White Wine Fermentation:	2.5 lb-VOC/1000 gallons fermented per year (58 °F fermentation temperature, 20.4 °Brix)

Daily Fermentation Emission Factors

The District has developed factors for daily Potential to Emit using the previously-referenced research by Williams and Boulton (see Appendix A). To ensure the factors represent true Potential to Emit, the daily emission factors were developed based on typical maximum fermentation temperatures and starting sugar concentrations rather than average values:

Red Wine Fermentation:	3.46 lb-VOC/1000 gallons tank capacity per day (85 °F fermentation temperature, 22.5 °Brix)
White Wine Fermentation:	1.62 lb-VOC/1000 gallons tank capacity per day (70 °F fermentation temperature, 22.5 °Brix)

Example 3 (fermentation tank) - estimate the daily and annual potential to emit for a 200,000 gallon nominal capacity fermentation tank to exclusively ferment red wine. Maximum fermentation throughput will be 900,000 gallons red wine per year. The tank will not be used for storage.

Daily $PE_{fermentation}$ = 3.46 lb-VOC/day per 1000 gallons nominal tank capacity x 200 Mgal nominal

Daily $PE_{fermentation}$ = 692.1 lb/day

Daily PE = Daily $PE_{fermentation}$ = 692.1 lb/day

Annual PE = 6.2 lb-VOC per 1000 gallons fermented x 900 Mgal/year = 5,580 lb-VOC/yr

Example 5 (fermentation and storage tank) - estimate the daily and annual potential to emit for a 100,000 gallon nominal capacity fermentation tank to ferment red wine. Maximum fermentation throughput will be 450,000 gallons red wine per year. The tank will also be used for storage identical with example 1:

In this case,

Daily PE = the larger of either Daily $PE_{fermentation}$ or Daily $PE_{storage}$

And.

Annual PE = Annual $PE_{fermentation}$ + Annual $PE_{storage}$

Calculating the Daily PE:

Daily $PE_{fermentation}$ = 3.46 lb-VOC/day per 1000 gallons nominal tank capacity x 100 Mgal nominal

Daily $PE_{fermentation}$ = 346.0 lb-VOC/day

From example 1,

Daily $PE_{storage}$ = 27.3 lb-VOC/day

Therefore,

Daily PE = 346.0 lb/day

Calculating the Annual PE:

Annual $PE_{fermentation}$ = 6.2 lb-VOC per 1000 gallons fermented x 450 Mgal/year = 2,790 lb-VOC/yr

From example 1,

Annual $PE_{storage}$ = 97 lb-VOC/year

Therefore,

Annual PE = 2,790 + 97 = 2,887 lb/year

Appendix A

Daily Emission Factor for Wine Fermentation

Appendix A

The emission factor for daily PE is based on the following:

- Estimation of maximum daily fermentation emissions is based on Figure 7 from the Williams and Boulton work referenced in the body of this document.
- Maximum red wine fermentation temperature is assumed to be 85 °F.
- Maximum white wine fermentation temperature is assumed to be 70 °F.
- Maximum working capacity of a red wine fermenter is 80% of tank maximum capacity.
- Maximum working capacity of a white wine fermenter is 95% of tank maximum capacity.

Figure 7 from Williams and Boulton indicates the ethanol emission rate (mg per hour per liter of wine) versus time for various fermentation temperatures. The total emissions in mg per liter of wine for any time period is the area under the curve. Thus, for any given temperature, figure 7 can be graphically integrated over the 24 hour period during which maximum emissions occur. A copy of figure 7 is attached which indicates the integration interval for red wine (85 °F) and for white wine (70 °F). Results of integration of Figure 7 are presented in the following table:

Graphical Integration Results to Determine Daily Fermentation Emission Factor from Figure 7 of Williams and Boulton

	Red Wine	White Wine
Maximum 24 hour Emissions (mg/liter of wine per day)	518.6	203.9
Maximum 24 hour Emissions (1b/1000 gallons of wine per day)	4.33	1.70
Maximum Batch Size (% of Tank Capacity)	80%	95%
Daily Emission Factor (lb/1000 gallons tank capacity per day)	3.46	1.62

Appendix A



Fig. 7. The influence of fermentation temperature on a) the fermentation rate, b) the vapor phase ethanol concentration, and c) the rate of ethanol emission. (Initial sugar content of 22.5°Brix, isothermal fermentation at indicated temperature.)

Appendix A



Fig. 7. The influence of fermentation temperature on a) the fermentation rate, b) the vapor phase ethanol concentration, and c) the rate of ethanol emission. (Initial sugar content of 22.5°Brix, isothermal fermentation at indicated temperature.)

Appendix H

Public Comments and District Response

Public Comments and District Responses

EcoPAS Comment #1:

The EPA has stated that multiple control technologies have been achieved in practice for this category of source, and therefore any valid ATC must comply with a determination of lowest achievable emissions rate (LAER).

District Response to EcoPAS Comment #1:

While we agree that these installations must comply with LAER (equivalent to the District's BACT), we disagree that multiple control technologies have been Achieved in Practice for this category of source. The District performed a detailed analysis for each of the existing and past installations of a control technology used to control fermentation emissions from wine tanks and determined that none of those installations meet all of the necessary criteria to be considered Achieved in Practice. A copy of the District's analysis, entitled "Achieved in Practice Memo", was included in Appendix D of the application review in the preliminary notice package and provides further details regarding the District's determination.

EcoPAS Comment #2:

The proposed project's cost analysis is vastly divergent from ours. For example, our estimate of total installation costs of this relatively small control system is $1,981,431, while the project estimate is $19,238,728 (a factor of 10 times higher).

Additionally, the proposed ATC states that the District requested a detailed breakdown of the cost of each component of each cost category from the vendor but has not received the requested information. We apologize for this misunderstanding. After receiving revised and expanded documentation from EcoPAS on March 28th, District engineers informed us in writing that they had no further questions, but would contact us if they had any unanswered questions. From the proposed ATC, we now understand that the District required further details on how specific costs were allocated to each category. (Attached Table with breakdown of costs)

A portion of the cost divergence is a function of the differences between our "potential to emit" calculations (based on District direction on turns and emissions factors), and the new "Specific Limiting Condition" (which would appear to require less condensing capacity).

District Response to EcoPAS Comment #2

As explained in meetings between Patrick Thompson and District staff on March 21 in Modesto and March 22 in Fresno, the District requires a detailed, itemized cost breakdown in order to fully evaluate the cost effectiveness of the installation and operation of the PAS-100 condenser(s), and also to determine the appropriate cost values for each category. Most of the costs used in the District's analysis were obtained from EPA's Air Pollution Control Cost Manual, Sixth Edition (EPA/452/B-02-001).

The District has reviewed the revised itemized cost estimate that EcoPAS submitted within their July 6, 2016 comment letter, and observed that all of the itemized costs provided by EcoPAS were significantly lower than those either obtained from EPA's Air Pollution Control Cost Manual or than those the District could independently verify.

The District notes that there are several reasons for the differences between EcoPAS's cost estimate and the District's cost estimate.

1. The itemized cost estimate submitted by EcoPAS assumes that the installation of their control technology would not result in any costs for engineering, construction and field expenses, start-up, painting, insulation, maintenance, overhead, property taxes, and insurance. While EcoPAS provided no justification for their assumption of no cost for these items, the costs used by the District for these categories were obtained directly from EPA's Air Pollution Control Cost Manual. Without adequate justification for why the costs for these categories should be set equal to zero, and having been provided no valid and justified alternative cost estimates for these categories, the District believes it is reasonable and appropriate to include the costs for these categories obtained from EPA's Air Pollution Control Cost Manual.

2. The itemized cost estimate submitted by EcoPAS included costs for instrumentation, freight, foundation and supports, handling and erection, electrical, contractor fees and administration, all of which are significantly lower than the District's estimated the costs for these categories, which were obtained from EPA's Air Pollution Control Cost Manual. Since EcoPAS provided no justification for why their costs are so much lower than the expected norm provided by the EPA Air Pollution Control Cost Manual, the District believes that the EPA Air Pollution Control Cost Manual remains the best source of costs for these categories.

3. The itemized cost estimate submitted by EcoPAS assumes that the installation of new, never-before-used emission control equipment, which may require a facility to significantly alter its traditional wine making processes will not result in any production-related costs to the owner, and EcoPAS provides no allowances for a contingency fund. Furthermore, EcoPAS provided no justification for these assumptions. The District believes the inclusion of an owner's cost is appropriate; therefore, the District included the owner's cost in its cost analysis, as it has in past cost analyses for wine fermentation tanks. Additionally, the District believes it is necessary and appropriate to include a cost for contingencies. This is especially true considering that this would be the first installation of this control technology at a large winery, and would likely require significant redesign of wine fermentation tanks as well as the manner in which ingredients are added and recirculated in the fermentation tanks. Furthermore, the contingency cost utilized in the District's application review was based on reasonable estimates published by the Association for the Advancement of Cost Engineering International and the Electric Power Research Institute. Therefore, the District believes it is reasonable and appropriate to include these costs in its analysis.

4. The itemized cost estimate submitted by EcoPAS includes cost estimates for PLC Programming and source testing that are lower than the District's estimates. The District estimates were based on information previously submitted by the wine industry. Again, EcoPAS provided no justification or reference for their cost numbers. On the other hand, the large wineries in the Central Valley commonly use PCL controllers as well as extensive process instrumentation for all of their process operations, and they routinely conduct source testing on several of their emission units, so the District believes the wine industry is in the best position to provide reasonable estimates of costs for PLC programming and source testing. Therefore, the District utilized the cost estimates provided by the wine industry for these categories.

5. The EcoPAS cost estimate for stainless steel ducting is significantly lower than the District's cost estimate. While EcoPAS provided no justification for their supplied cost numbers, it should be noted that the District independently contacted several local stainless steel ducting vendors to inform our investigations into the actual costs for various sized, food grade stainless steel ducting and then compared the results with those obtained from the Eichleay Report, which was used the development of District Rule 4694. This comparison revealed that the use of inflation-adjusted costs from the Eichleay Report is appropriate (and lower than costs resulting from the District's own investigations) for estimating the cost of stainless steel duct work for this application. Specifically, the District's cost estimate was based on the length and size of ductwork necessary to duct vapors from the tanks to the control devices, the number of valves necessary to connect each tank to the piping manifold, and the inflation-adjusted stainless steel ducting costs per linear foot provided by the Eichleay Report (2005).

   One potential explanation for the difference in cost would be the proposed location of the control devices. Clearly, the farther a control device is located from the tank farm, the longer the duct runs must be, which increases ducting costs. While it can result in longer duct runs, large wineries such as those in the Central Valley generally prefer to centrally locate equipment as much as possible to increase operational efficiency. Centrally locating control equipment may also be necessary in some instances, as locating the control equipment as close to the tanks as possible might interfere with normal operation of the wine making processes, impede personnel and vehicle traffic, pose additional safety hazards, etc. For this specific project, the control equipment was assumed to be located as close to the tank farm as practicable given the winery's layout, minimizing the length of the duct runs as much as possible; therefore, the location of the control equipment isn't a likely explanation for difference in the District's ducting cost estimate versus EcoPAS's ducting cost estimate. Nevertheless, since EcoPAS provided no justification for their ducting cost numbers, the District believes the ducting costs used for this specific project are reasonable and appropriate.

6. Finally, the EcoPAS cost estimate assumes that a clean-in-place system is not necessary for this application since CO_2 and EtOH vapors act as a natural cleaning agent and the lack of oxygen and nutrients contribute to the inherent system cleanliness. However, CO_2 and EtOH vapors cannot adequately clean the emission control ductwork if there is an unexpected transient fermentation event (e.g. a foam-

over), which have occurred at wineries with large tanks permitted within the District. In the event of a foam-over, the emission control ductwork would not only be contaminated with fermenting wine; the emission control ductwork would also be contaminated with grape skins and other solid materials that could clog the ductwork. The solid materials must be physically removed from the emission control ductwork and the ductwork properly sanitized prior to bringing the tanks back into operation; otherwise, the materials in the ductwork could potential contaminate the product in the wine tanks or even plug the ductwork.

Without a clean-in-place system, the ductwork would need to be disassembled, removed, cleaned, and then reinstalled. This would significantly increase the time required to bring the tanks and the emission control system serving the tanks back to an operational status following a foam-over event. The inclusion of a clean-in-place system ensures that the emission control equipment is in operation as often as possible, thus minimizing uncontrolled emissions to the atmosphere. For these reasons, the District believes it is both reasonable and appropriate to utilize a clean-in-place system for any emission control installation at a large winery and has therefore included the cost for such a system in its cost estimate.

Based on the data available to the District, the District has determined that the use of a condensation system is not cost effective for this project.

7. Additionally, in late comments, EcoPAS has noted that a portion of the cost divergence is due to the differences in the District's potential to emit calculations and EcoPAS's interpretation of the project's proposed Specific Limiting Condition (SLC), and states that the presence of the SLC allows for a reduction in condensing capacity versus what was provided in their initial cost estimate. The SLC only limits overall annual emissions from the proposed 128 new tanks but does not limit the maximum potential on any given day within a rolling 12 month period. Furthermore, valley wineries typically receive large quantities of grapes over a relatively short period of time during the harvest season, so the winery may not be able to stagger their fermentation operations to accommodate a condensing system that is undersized to handle the maximum fermentation capacity. Therefore, reducing the number of control devices needed to only capture and control the limited annual emissions would not be sufficient to capture and control the maximum potential to emit during any given day as is required by New Source Review.

   Nonetheless, considering responses #1 - 6 above for the District Response to EcoPAS Comment #2, even this undersized condensation system is not cost effective for this project.

EcoPAS Comment #3:

EcoPAS is willing to install and support a control system at our expense, with the applicant paying only for tons of VOCs actually captured.

a. EcoPAS is willing to fund a District study, using an objective 3rd-party engineering firm with wine industry experience, to determine reasonable installation and operation costs.
b. EcoPAS is willing to provide a guarantee of cost effectiveness. We will guarantee that total $/ton is less than the District's threshold, and be directly liable if actual costs exceed the unbiased engineering firm's estimates
c. Applicant may also share in byproduct revenues (if so desired).

District Response to EcoPAS Comment #3

EcoPAS is welcome to pursue and coordinate such a partnership with the wine industry in the Central Valley, and the District would be a willing and interested party to a cooperative effort. The data obtained from such an experiment would be very useful for future evaluations of the control technology, its compatibility with winery operations, and the potential for the service-type relationship described above. However, New Source Review does not provide any mechanism that would allow the District to compel the wine industry to participate in such a partnership.

EcoPAS Comment #4

The author is curious if this (Indemnification Agreement and Letter of Credit) is a common permit requirement? At first glance, it gives the impression that the District is concerned this ATC issuance will generate CEQA liability, and therefore is requiring applicant to bear legal responsibility. Would actual controls eliminate the need for indemnification and letter of credit?

District Response to EcoPAS Comment #4

The District requires indemnification from applicants when specific permitting proposals have an elevated potential for litigation. The decision to require an indemnification agreement and letter of credit is a case-by-case risk management decision, based on the particulars of each permitting proposal. Because the emission controls analyzed are not cost-effective and therefore cannot be required by the District, the decision regarding whether installing controls would minimize legal risk is a business decision to be made by the winery.

EcoPAS Comment #5:

The recently adopted plan for Ozone attainment states that "...the District commits to amend Rule 4694 to include additional requirements to further reduce emissions from wine fermentation processes as appropriate by December 31, 2018." Each year we get only one chance (the late-summer early-fall crush) to evaluate fermentation emissions control technologies. We submit that this new source review and proposed permit is an excellent

opportunity for industry and regulators to work together to further validate actual economic feasibility of implementing real emission control technologies.

District Response to EcoPAS Comment #5

Comment noted. The District looks forward to working with all interested parties during the referenced rule development and permit issuance processes.

NOTE: While the following additional comments from EcoPAS were received after the 30-day public comment period had concluded for this project and were not specifically directed towards this project, the District's response to these additional comments has been proactively included within this project evaluation.

EcoPAS Comment #6:

Our experience is that the CO2 and EtOH vapor act as a natural cleaning agent, and that CIP systems are an unnecessary expense. The EtOH vapor % is comparable to solvent systems, and the lack of oxygen and nutrients further adds to the inherent system cleanliness. This is experience is supported by end-of-crush test results from a full season of operation without CIP. However, if the applicant desires the expense of a CIP system, we are eager to consider the integration of such a system. Preliminary estimates of a suitable CIP system are well below $1M. As an optional item not necessary for the safe operation of the PAS, a CIP should not be part of the cost-effectiveness analysis.

District Response to EcoPAS Comment #6:

Please refer to the District Response to EcoPAS Comment #2, Item 6 above for the District's response to this comment.

EcoPAS Comment #7:

Our estimates assume some variant of a service model under which EcoPAS would:

- Enter into a long-term agreement to provide capture service at cost/ton below the district's threshold of cost effectiveness.
- Bear *all* operational costs (direct, indirect, operation, and maintenance)
- Bear liability for any operation mishaps or damages
- Share revenues from captured aromatic condensate (up to and exceeding the cost/ton of the emissions).

Under this model, we have left line items as zero that would be included in our costs. These include painting, insulation, engineering, construction, startup, owner's cost, contingency, operating costs, property taxes, and insurance, and should include sales tax and freight (left in for comparison purposes). We apologize for the challenges in comparing our cost estimates to the format used by the District, and would only ask in the future to be involved more fully in the District's cost analysis.

District Response to Comment #7:

Please refer to the District Response to EcoPAS Comments #2 and #3 above. Specifically, the District expects the facility will incur significant engineering, construction, start up, owner's cost, contingency costs, operating costs, property taxes, and insurance costs for this installation. Furthermore, New Source Review does not provide any mechanism that would allow the District to compel the wine industry to participate in such a service model partnership.

EcoPAS Comment #8:

A variety of methods have been used to apply the various EPA cost estimation methodologies to condensers. For this analysis, the District appears to use the most expensive possible method, arriving at a Total Capital Investment (TCI) of ~2.4X purchased equipment cost (PEC). The EPA Manual states that "For packaged systems, total capital investment = 1.15PEC" (EPA AIR POLLUTION CONTROL COST MANUAL, Sixth Edition, Section 3.1, VOC Recapture Controls, page 2-23). Our actual estimate is that TCI for this project is ~1.2PEC, higher than the suggested EPA factor, but far lower than the District's estimate. It is also common to use much longer useful life spans and lower cost of money estimates, but this is mostly a function of actual desire to adopt controls.

District Response to EcoPAS Comment #8:

The District considers a "packaged system" to be one where the technology in question is commonly used in the industry. The PAS-100 system has never been utilized at a large winery of this nature. Given the uncertainties associated with the use of this technology, the District believes that use of such a system would necessarily require a custom installation, and that the cost factors from EPA's Air Pollution Control Cost Manual used in the analysis provided in the preliminary notice are appropriate.

Furthermore, the District believes the use of a system cost estimate of 1.15PEC would highly underestimate the costs. The District's research leads us to believe that the contingency cost alone is at least 0.15PEC for this type of installation, leaving zero dollars for foundation & supports, handling and erection, electrical, insulation, painting, engineering, construction and field expenses, contractor fees, start-up, and initial performance testing.

Appendix I

EPA Comments and District Response

EPA Comments and District Responses

"Enclosure 1" EPA Comments

The Central Coast Winery Service (CCWS) was issued a permit to construct and operate a (will insert name of control device from SB permit, rather than name vendor) in 2013 to control emissions from a portion of their wine fermentation operations. This equipment has been leased by the facility and has been in use during each crush season since 2103 (three seasons). The facility proposed use of this control equipment, not to meet any applicable BACT/LAER requirements, but instead to ensure their daily emissions remained below 55 lbs/day, which is the emission threshold for triggering BACT and offset requirements in the Santa Barbara County Air Pollution Control District (APCD). The fact that the source was not required to achieve emission reductions to satisfy a new source review (NSR) requirement and instead used the controls to avoid an applicable requirement, does not factor into the evaluation of whether a specific emission reduction rate has been achieved in practice. Similarly, the fact that the source only used the equipment as needed to comply with their 55 lb/day emission limit, does not affect whether a certain control rate has been AIP. EPA has reviewed the records from CCWS regarding their wine fermentation operations and using mass balance calculations have determined that the use of add-on controls during portions of the fermentation process have resulted in emission reductions of 76.6%. The demonstrated use of add-on controls to reduce emissions by 76.6% represents the lowest achievable emission rate for wine fermentation operations. The District has raised a concern that an ATC issued by the Santa Barbara County APCD to require the use of add-on controls to satisfy a BACT requirement was cancelled by the source, and thus cannot be relied on when considering whether the use of add-on controls at this facility have been AIP. While it is correct that an ATC allowing emissions at the facility to exceed 55lbs/day (thus triggering BACT) was cancelled, this did not affect the use of otherwise permitted control devices to reduce emissions from their wine fermentation operations. Lastly, EPA wants to address the District's concern that the control equipment at this facility has not been formally source tested. First we note that this control equipment was previously source tested by the Bay Area Air Quality Management District while in use at another facility and was able to achieve a control efficiency of greater than 99% using a direct measurement inlet and outlet source test. Second, due to the batch nature of the operation and the non-steady state of the wine fermentation process, source testing may not be the best way to accurately measure achieved emission reductions. Instead, emission calculations using mass-balance may be a better way to measure the actual emissions reductions achieved by the control device. Mass-balance calculations were used to determine the overall control efficiency of 76.6% for the batch wine fermentation process at this facility. Therefore, this same approach should be used to apply LAER to each of the proposed permits for wine fermentation operations. The Terravant Winery was issued a permit to construct and operate a packed bed water scrubber in 2008 to control emissions from their wine fermentation operations. This custom designed control equipment is owned by the facility and has been in use during every crush season since 2008 (7 seasons). Similar to the Terravant facility, the control equipment was not installed to meet any applicable BACT/LAER requirements, but to comply with a daily emission limit of 55 lbs/day. As stated above in our summary of the Terravant operation, the fact that these controls were not required to meet BACT/LAER, or required to be used at all times does not

affect a determination of whether the use of such controls has been achieved in practice. While the installed control equipment was expected to achieve a 95% control efficiency, the source has only been able to maintain a 49% control efficiency on a consistent basis according to source test reports. The Santa Barbara County APCD has indicated that most issues related to the achieved control efficiency are likely due to operator error, given that water scrubbers are a well-established, high-efficiency control device for controlling ethanol emissions. For the purposes of evaluating whether the use of this control equipment can be considered AIP, the evaluation criteria is whether a source was able to achieve a certain level of control over a reasonable operating period. The District and EPA have already agreed that the reasonable operating period is a complete crush season. The facility has been able to achieve a minimum control efficiency of at least 47.6% over the seven seasons it has been in use. Therefore, for wine fermentation tanks, EPA believes that the lowest achievable emission rate which has been AIP, based on the demonstrated emission reductions achieved at the Terravant facility, is a 47.6% control efficiency, as measured by Santa Barbara County APCD source testing.

District Response to "Enclosure 1" EPA Comments

The District does not dispute that scrubbers and condensers used at CCWS can capture ethanol emissions, nor does the District dispute that Terravant's custom-designed UV treatment system may reduce ethanol emissions, and in fact the District analyzed whether the installation of such controls were cost effective and determined that they were not. However, as consistently stated in response to EPA comments on previous wine fermentation projects, the District strongly disagrees that the control systems employed at CCWS and Terravant support EPA's conclusion that the technology is achieved-in-practice BACT/LAER for wine fermentation operations in the San Joaquin Valley (Valley).

EPA's own long-standing position is that BACT/LAER requirements must be applied during the entire operation cycle of an emission unit, including startup and shutdown and other transient periods during the source operation. This position has repeatedly been expressed in guidance set forth by EPA, including determinations that BACT requirements cannot be waived or otherwise ignored during startup and shutdown periods (See PSD Appeal No. 02-12 and PSD Appeal No. 99-1), but this guidance is now being ignored by EPA.

Based on this guidance, a determination that a control is "achieved in practice" BACT should examine BACT for all periods of operation. Therefore, when evaluating whether a wine fermentation control system installation such as that employed at the CCWS facility has actually established achieved in practice BACT, it is important consider whether that control system was employed over the entire fermentation cycle. In this particular case, all that can be said is that a narrow window of peak emissions of the fermentation cycle has been controlled, and that these emissions reductions are not REQUIRED at all. Clearly, these conditions meet neither District nor EPA requirements for the application of BACT/LAER. In summary, it is inappropriate, by both EPA policy and common sense, to consider an occasional and intermittent control as a demonstration that a particular level of control has been "achieved in practice" for all periods of operations of a similar source.

Central Coast Wine Services (CCWS)

Email correspondence with Santa Barbara County Air Pollution Control District (SBCAPCD) on March 9, 2015, indicates that the control system currently employed by CCWS does not capture and control emissions for the entire fermentation cycle. Furthermore, the same correspondence indicates that the operator must sometimes delay connecting a tank at the beginning of the fermentation process in order to keep another tank connected to capture the second half of the fermentation process. Thus, the control systems at CCWS are not designed to and cannot physically control emissions from the tanks it serves for the entire fermentation cycle as would be required by both the District and the EPA for BACT/LAER purposes.

Additionally, the District believes the purported 76.6% control efficiency for the CCWS installation was neither adequately established nor verified. The actual performance of the emission control system employed at CCWS has not been tested during their fermentation operations; rather, CCWS estimates the control performance via mass balance using the quantity of ethanol captured together with several unverified assumptions. The uncontrolled emission rate is an assumption based on emission factors that were derived from modeling predictions of ethanol loss during wine fermentation by L.A. Williams and R. Boulton, as published in the American Journal of Enology and Viticulture in 1983. The 76.6% control efficiency was then calculated using these data. The emission factors derived from the modeling rely on multiple assumptions, including assumed fermentation temperatures, fermentation times, and initial sugar contents (°Brix) for the fermenting wine. In reality, the fermentation temperature, fermentation time, and initial sugar content varies based on the wine being produced. The actual uncontrolled fermentation emissions from different wine products may deviate significantly from the derived emission factors. Therefore, the District believes the calculated 76.6% control efficiency is not a reliable basis for the establishment of an achieved in practice control efficiency standard that can be applied broadly across the entire wine industry. The only reliable method for determining a precise control efficiency standard is to conduct source testing at the inlet and outlet of the control system over an entire fermentation cycle, along with measurement of the quantity of ethanol captured. To date, no such testing has been conducted for the fermentation emission control system employed at the CCWS facility, so it is the District's position that a precise control efficiency standard cannot be established based on this installation.

The District believes that EPA, in formulating its position regarding the control efficiency achieved by the control system employed at the CCWS facility, is not acknowledging the myriad assumptions and other unverified factors used to estimate the system's performance. Furthermore, EPA appears to completely disregard its historical position that a technology employed as BACT/LAER must be employed to all portions of the operation, and if not, separate BACT/LAER determinations must be made for the times the main BACT control technology cannot be applied (such as during startup, shutdown, etc.). For these reasons, the District does not agree that the use of add-on controls at the CCWS facility represents an achieved in practice lowest achievable emission rate for wine fermentation operations, and continues to believe that the District's determination of achieved in practice BACT and its analysis of the cost effectiveness of these controls were appropriate, logical, and correct.

Terravant Winery

The fermentation tanks at Terravant Winery are small enough to be located within a building. Room air from this building is captured and then routed to a custom-designed water scrubber that captures the ethanol into a water solution, which is subsequently treated with a custom-designed UV treatment system. It is important to note that the building in which Terravant's fermentation tanks are located was not designed to be a Permanent Total Enclosure pursuant to EPA Method 204. Moreover, Section 3.7 of District Rule 1020 (Definitions) defines Atmosphere as follows:

Atmosphere: *the air that envelops or surrounds the earth.* ***Where air pollutants are emitted into a building or structure not designed specifically as a piece of air pollution control equipment, such emissions into the building or structure shall be considered emissions into the atmosphere.***

Therefore, in order for a building that encloses the fermentation tanks to be considered part of an emission capture and control system, District rules require that the building be designed as a Permanent Total Enclosure. As such, the District cannot consider the Terravant's fermentation tanks to be fully enclosed. Furthermore, to the District's knowledge, no one conducts wine fermentation operations inside a building that was designed according to EPA Method 204.

The permitted wineries within the District are magnitudes larger in size than the Terravant facility, so it is simply not practical to enclose their fermentation tanks in a building and then capture and control the room air. In fact, large wineries in the Valley are operating on several acre properties, using 100's of very large fermentation tanks, each with a capacity exceeding 50,000 gallons. Such very large operations cannot conceivably be enclosed in an enclosed building served by a vapor control system. Therefore, the District does not agree that Terravant Winery's capture and control system could be practically applied to the large wineries located in the District. Consequently, the only other viable option for the large fermentation tanks commonly used in Valley wineries is to fully enclose each individual fermentation tank and to capture emissions directly and the control system.

Additional District Concerns

Fully enclosing and sealing tanks during fermentation, as would be required to employ emission capture and control technologies on fermentation tanks in the Valley, can adversely affect the winemaking process. As noted in the background document for EPA AP-42 Section 9.12, Wines and Brandy (October 1995):

> *At peak fermentation activity, the juice is saturated or super-saturated with carbon dioxide. Increased pressure placed on the system (tank) may cause foaming-over in the event of an abrupt agitation.*

Enclosing and sealing a fermentation tank and routing the tank vapors to ductwork and a control system results in a back pressure, which is increased pressure on the system. The increased pressure increases the solubility of CO_2 gas into the juice. With more CO_2 gas in the juice, the probability of a foam over event during agitation increases.

Furthermore, the District believes that fermentation tank size is an important consideration when evaluating whether or not an emission control strategy is achieved-in-practice/LAER or even viable at all. The District is well aware of EPA's previously-stated ideological position that the size of a wine fermentation tank is not a consideration for determining LAER. However, large fermentation tanks are more prone to undesirable transient effervescent reactions (commonly referred to as "foam overs"). Characteristics that make large tanks more prone to foam overs are:

1. Large wine fermentation tanks have lower surface area to volume ratios. With less surface area and more CO_2, CO_2 is less easily released from the juice. As a result, large tanks require much more care (agitating, pumping, etc.) to ensure CO_2 is released from the juice to prevent foam overs.

2. Temperature gradients up to 18 degrees Fahrenheit have been observed in large tanks, whereas small tanks typically have minimal temperature gradients. A higher temperature gradient can cause bubbles in the tanks to experience a higher hydraulic pressure at the bottom of the tank, compared to the top, which can cause the bubbles to expand as they rise to the top of the tank. The expansion of the bubbles contributes to foam production in large tanks, increasing the probability of a foam over event.

Essentially, when evaluating achieved-in-practice BACT/LAER for wine fermentation tanks, it is important to fully understand all of the variables involved such as tank size, temperature gradients, tank pressure, etc., and how those factors, both individually and collectively, may potentially affect the fermentation process and overall wine quality. In fact, the District disagrees with EPA's position regarding the status of wine fermentation control systems. The District's position is that currently there are not enough data to determine whether a fully enclosed and sealed wine fermentation tank vented to an emission control system will have an adverse effect on wine production.

Indeed, the District's primary concern is what effect the presence of an emission control system and a fully enclosed and sealed tank will have on the wine fermentation process. Enclosing and sealing the tank may affect the final product quality. Additionally, enclosing and sealing the tanks creates backpressure that can increase the risk of an effervescent reaction (i.e. a "foam over"). A foam over event can result in a significant loss in tank contents, costing a winery significant revenue.

It is possible these concerns could be alleviated if the tank pressure could be successfully managed such that it does not compromise the wine fermentation process. However, the commercially available systems are passive systems that do not actively control back pressure. Furthermore, neither the CCWS nor Terravant facilities utilize fully enclosed and sealed fermentation tanks during the entire fermentation cycle. In fact, to the District's knowledge, no winery has ever conducted full scale wine fermentation in a fully enclosed and sealed tank connected to a control system throughout an entire fermentation cycle over an entire fermentation season. So there simply are no data available to evaluate the effect a fully enclosed and sealed tank would have on the wine fermentation process.

In summary, the addition of emission controls to fermentation tanks may negatively impact wine quality, and the implementation of fermentation controls may result in the loss of product due to increasing the probability of foam over events. Knowing these inherent risks, the District believes an exhaustive evaluation of the fermentation process is required to assess the applicability of wine fermentation controls to large winery fermentation tanks. The District believes additional research must be performed in the areas of fermentation tank design, product piping and pumping configuration design, vapor ducting design, and active feedback control algorithm design for variable speed drives for the blowers controlling the fermentation tank ventilation to manage the back pressure before fermentation controls can reliably be applied to large wine fermentation tanks. Therefore, the District continues to believe that based on the stage of understanding of the wine fermentation operation and the emission control process, the current facts do not support the determination that the commercially available wine fermentation controls are achieved-in-practice BACT/LAER for the large wine fermentation tanks installed in the central valley.

Enclosure #2 EPA Comments:

1. EPA comment letter for E&J Gallo, Project No. N-1131615, dated October 21, 2013.
2. EPA comment letter for E&J Gallo, Project No. N-1133659, dated May 5, 2014.
3. EPA comment letter for Bear Creek Winery, Project No. N-1133555, dated June 16,
4. EPA comment letter for E&J Gallo, Project No. N-1133347, dated May 8, 2015.

District Response to EcoPAS Comment #2

In enclosure 2, EPA attached comments to previous projects that have since been finalized. The District responded to those comments in each of the previous permitting actions.