



San Joaquin Valley

AIR POLLUTION CONTROL DISTRICT



MAY 19 2017

Mr. Neil McDougald
E & J Gallo Winery
5610 E Olive Ave
Fresno, CA 93727

**Re: Notice of Preliminary Decision – Title V Permit Renewal
District Facility # C-447
Project # 1153001**

Dear Mr. McDougald:

Enclosed for your review and comment is the District's analysis of the application to renew the Federally Mandated Operating Permit for E & J Gallo Winery located at 5610 E. Olive Avenue, Fresno, California.

The notice of preliminary decision for this project will be published approximately three days from the date of this letter. After addressing all comments made during the 30-day public notice and the 45-day EPA comment periods, the District intends to issue the renewed Federally Mandated Operating Permit. Please submit your written comments on this project within the 30-day public comment period, as specified in the enclosed public notice.

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Errol Villegas, Permit Services Manager, at (559) 230-5900.

Sincerely,

Arnaud Marjollet
Director of Permit Services

Enclosures

cc: Tung Le, CARB (w/enclosure) via email
cc: Gerardo C. Rios, EPA (w/enclosure) via email
cc: Kim Burns, E & J Gallo Winery (w/enclosure) via email

Sayed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

SAN JOAQUIN VALLEY AIR POLLUTION CONTROL DISTRICT

Proposed Title V Permit Renewal Evaluation E & J Gallo Winery C-447

TABLE OF CONTENTS

I.	PROPOSAL.....	2
II.	FACILITY LOCATION	2
III.	EQUIPMENT LISTING	2
IV.	GENERAL PERMIT TEMPLATE USAGE	3
V.	SCOPE OF EPA AND PUBLIC REVIEW	3
VI.	FEDERALLY ENFORCEABLE REQUIREMENTS	3
VII.	REQUIREMENTS NOT FEDERALLY ENFORCEABLE	7
VIII.	PERMIT REQUIREMENTS	7
IX.	PERMIT SHIELD	45
X.	CALIFORNIA ENVIRONMENTAL QUALITY ACT.....	46
XI.	PERMIT CONDITIONS	46
ATTACHMENTS		46
A.	DRAFT RENEWED TITLE V OPERATING PERMIT	
B.	PREVIOUS TITLE V OPERATING PERMIT	
C.	DETAILED FACILITY LIST	

TITLE V PERMIT RENEWAL EVALUATION

Winery

Engineer: Dustin Brown
Date: May 18, 2017

Facility Number: C-447
Facility Name: E & J Gallo Winery
Mailing Address: 5610 E. Olive Avenue
Fresno, CA 93727

Contact Name: Neil McDougald
Phone: (559) 458-2584

Responsible Official: Mr. Neil McDougald
Title: Plant Manager

Project #: C-1153001
Deemed Complete: January 21, 2016

I. PROPOSAL

E & J Gallo Winery was issued their last renewed Title V permit on December 20, 2011. As required by District Rule 2520, the applicant is requesting a permit renewal. The existing Title V permit will be reviewed and modified to reflect all applicable District and federal rules that have been updated, removed, or added since the issuance of the facility's last renewed Title V permit.

The purpose of this evaluation is to provide the legal and factual basis for all updated applicable requirements and to determine if the facility will comply with these updated requirements. It also specifically identifies all additions, deletions, and/or changes made to permit conditions or equipment descriptions.

II. FACILITY LOCATION

E & J Gallo Winery is located at 5610 E. Olive Avenue in Fresno, CA.

III. EQUIPMENT LISTING

A detailed facility printout listing all permitted equipment at the facility is included as Attachment C.

IV. GENERAL PERMIT TEMPLATE USAGE

The applicant is not proposing to use any model general permit templates as a part of this Title V renewal project.

V. SCOPE OF EPA AND PUBLIC REVIEW

The applicant is not requesting any model general permit templates. Therefore, all Federally Enforceable conditions in this current Title V permit will be subject to EPA and public review.

VI. FEDERALLY ENFORCEABLE REQUIREMENTS

A. Rules Updated or Evaluated

- District Rule 2020, Exemptions
(amended August 18, 2011 ⇒ amended December 18, 2014)
- District Rule 2201, New and Modified Stationary Source Review Rule
(amended December 18, 2008 ⇒ amended February 18, 2016)
- District Rule 2520, Federally Mandated Operating Permits
(amended June 21, 2001)

District Rule 4621, Gasoline Transfer Into Stationary Storage Containers, Delivery Vessels, and Bulk Plants
(amended December 20, 2007 ⇒ amended December 19, 2013)

- District Rule 4622, Gasoline Transfer Into Motor Vehicle Fuel Tanks
(amended December 20, 2007 ⇒ amended December 19, 2013)
- District Rule 4702, Internal Combustion Engines
(amended August 18, 2011 ⇒ amended November 14, 2013)
- 40 CFR Part 60, Subpart Db, Standards of Performance for Industrial-Commercial-Institutional Steam Generating Units
(amended February 27, 2014)
- 40 CFR Part 60, Subpart Dc, Standards of Performance for Small Industrial-Commercial-Institutional Steam Generating Units
(amended February 16, 2012)

- 40 CFR Part 60, Subpart III, Standards of Performance for Stationary Compression Ignition Internal Combustion Engines
(amended July 7, 2016)
- 40 CFR Part 64, Compliance Assurance Monitoring
(adopted October 22, 1997)
- 40 CFR Part 82, Subpart B, Servicing of Motor Vehicle Air Conditioners
(amended June 25, 2013)
- 40 CFR Part 82, Subpart F, Recycling and Emissions Reductions
(amended April 10, 2015)

B. Rules Removed

There have been no rules removed since the last renewed Title V permit was issued.

C. Rules Added

- District Rule 2410, Prevention of Significant Deterioration
(adopted June 16, 2011)
- District Rule 4566, Organic Material Composting Operations
(adopted August 18, 2011)

D. Rules Not Updated

- District Rule 1070, Inspections
(amended December 17, 1992)
- District Rule 1080, Stack Monitoring
(amended December 17, 1992)
- District Rule 1081, Source Sampling
(amended December 16, 1993)
- District Rule 1100, Equipment Breakdown (Non-SIP replacement for Fresno County Rule 110)
(amended December 17, 1992)
- District Rule 1160, Emission Statements
(amended November 18, 1992)

- District Rule 2010, Permits Required
(amended December 17, 1992)
- District Rule 2031, Transfer of Permits
(amended December 17, 1992)
- District Rule 2040, Applications
(amended December 17, 1992)
- District Rule 2070, Standards for Granting Applications
(amended December 17, 1992)
- District Rule 2080, Conditional Approval
(amended December 17, 1992)
- District Rule 4101, Visible Emissions
(amended February 17, 2005)
- District Rule 4201, Particulate Matter Concentration
(amended December 17, 1992)
- District Rule 4202, Particulate Matter Emission Rate
(amended December 17, 1992)
- District Rule 4301, Fuel Burning Equipment
(amended December 17, 1992)
- District Rule 4305, Boilers, Steam Generators and Process Heaters – Phase 2
(amended August 21, 2003)
- District Rule 4306, Boilers, Steam Generators and Process Heaters – Phase 3
(amended October 16, 2008)
- District Rule 4311, Flares
(amended June 18, 2009)
- District Rule 4320, Advanced Emission Reduction Options for Boilers, Steam Generators and Process Heaters Greater Than 5.0 MMBtu/hr
(adopted October 16, 2008)
- District Rule 4601, Architectural Coatings
(amended December 17, 2009)

- District Rule 4603, Surface Coating of Metal Parts and Products, Plastic Parts and Products, and Pleasure Crafts
(amended September 17, 2009)
- District Rule 4694, Wine Fermentation and Storage Tanks
(amended December 15, 2005)
- District Rule 4801, Sulfur Compounds (Non-SIP replacement for Fresno County Rule 106)
(amended December 17, 1992)
- District Rule 8011, Fugitive Dust General Requirements
(amended August 19, 2004)
- District Rule 8021, Fugitive Dust Requirements for Control of Fine Particulate Matter (PM10) from Construction, Demolition, Excavation, and Extraction Activities
(amended August 19, 2004)
- District Rule 8031, Fugitive Dust Requirements for Control of Fine Particulate Matter (PM10) from Handling and Storage of Bulk Materials
(amended August 19, 2004)
- District Rule 8041, Fugitive Dust Requirements for Control of Fine Particulate Matter (PM10) from Carryout and Trackout
(amended August 19, 2004)
- District Rule 8051, Fugitive Dust Requirements for Control of Fine Particulate Matter (PM10) from Open Areas
(amended August 19, 2004)
- District Rule 8061, Fugitive Dust Requirements for Control of Fine Particulate Matter (PM10) from Paved and Unpaved Roads
(amended August 19, 2004)
- District Rule 8071, Fugitive Dust Requirements for Control of Fine Particulate Matter (PM10) from Unpaved Vehicle/Equipment Areas
(amended September 16, 2004)
- 40 CFR Part 61, Subpart M, National Emissions Standards for Asbestos
(amended July 20, 2004)
- 40 CFR Part 68, Chemical Accident Prevention Provisions
(amended April 9, 2004)

VII. REQUIREMENTS NOT FEDERALLY ENFORCEABLE

For each Title V source, the District issues a single permit that contains the Federally Enforceable requirements, as well as the District-only requirements. The District-only requirements are not a part of the Title V Operating Permits. The terms and conditions that are part of the facility's Title V permit are designated as "Federally Enforceable Through Title V Permit."

For this facility, the following are not Federally Enforceable and will not be discussed in further detail:

A. Rules Added

No rules were added.

B. Rules Not Updated

- District Rule 4102, Nuisance
(*amended December 17, 1992*)
- District Rule 4694, Wine Fermentation and Storage Tanks
(*adopted December 15, 2005*)
- CCR 92200, CCR 92500, CCR 92530 and CCR 92540, Abrasive Blasting Operations
- CCR 93115, Airborne Toxic Control Measure (ATCM) for Stationary Compression-Ignition Engines
(*adopted May 19, 2011*)
- CCR 93116, Airborne Toxic Control Measure (ATCM) for Portable Engines Rated at 50 Horsepower and Greater
(*adopted February 19, 2011*)

VIII. PERMIT REQUIREMENTS

The purpose of this evaluation is to review changes to Federally Enforceable requirements; therefore, this compliance section will only address rules that have been amended or added since the issuance of the last Title V permit renewal in 2011.

A. District Rule 2020 – Exemptions

District Rule 2020 lists equipment which is specifically exempt from obtaining permits and specifies recordkeeping requirements to verify such exemptions. The amendments to this rule do not have any effect on current permit requirements and will therefore not be addressed in this evaluation.

B. District Rule 2201– New and Modified Stationary Source Review Rule

District Rule 2201 has been amended since this Title V permit was last renewed. However, the requirements of this rule are only triggered at the time the source undergoes a modification. All applicable requirements from any NSR permit actions have already been incorporated into the current Title V permit. Therefore, the updated requirements of this rule are not applicable at this time.

C. District Rule 2410 – Prevention of Significant Deterioration

District Rule 2410 has been newly adopted since this Title V permit was last renewed. However, the requirements of this rule are only triggered at the time the source undergoes a modification. The requirements of this rule cannot be triggered by the renewal of a Title V permit, since permit renewal does not involve any construction or modification of the stationary source. Therefore, the newly adopted requirements of this rule are not applicable at this time.

D. District Rule 2520 – Federally Mandated Operating Permits

District Rule 2520 has not been amended since this Title V permit was last renewed. However, EPA has provided the District with comments on other Title V permits and indicated that the District was issuing permits without appropriate and practical recordkeeping requirements for annual emissions limitations. According to EPA policy, annual emission limits must be practically enforceable, which also goes on to say that to be practically enforceable, annual limits must be enforced on a short-term basis.

The District had previously committed to 12-month rolling recordkeeping to enforce annual limits in all Title V permits. In accordance with that committal, the District has developed conditions to address EPA's concerns regarding practically enforceable annual emission and throughput limits. Therefore, the following conditions have been modified and/or added to the permits at this facility.

Permits	Conditions
C-447-16-4	14 and 18
C-447-23-7	7 and 15
C-447-230-3	1 and 4
C-447-233-3	15 and 17
C-447-267-3	10 and 13
C-447-268-2	6 and 11
C-447-269-2	4 and 10
C-447-271-2 and '-273-2 through '-277-2, '-279-2 through '-283-2, '-285-2 through '-289-2, and '-291-2 through '-294-2	5, 7, 8, 13 and 15
C-447-272-2, '-278-2, '-284-2, '-290-2, and '-296-2 through '-327-2	4, 6, and 9

Greenhouse Gas Discussion

There are no federally applicable Greenhouse Gas (GHG) requirements for this source. It should be noted that the Mandatory Greenhouse Gas Reporting rule (40 CFR Part 98) is not included in the definition of an applicable requirement within Title V (per 40 CFR 71.2). Therefore, there will be no further discussion of GHG in this evaluation.

E. District Rule 4566 – Organic Material Composting Operations

The purpose of this rule is to limit the emissions of volatile organic compounds (VOC) from composting operations. Per Section 2.0, this rule applies to composting facilities that compost and/or stockpile organic material.

This facility receives, stores, mixes, and composts green waste organic materials. Therefore, the facility's green waste organic materials receiving, storage, and mixing operation (permit C-447-268) and open windrow composting operation (permit C-447-269) are subject to the requirements of this rule.

Section 5.1 specifies the requirements for stockpiles. Section 5.1.1 requires a composting operation, with a total throughput of less than 100,000 wet tons per year of organic material, to comply with one of the following within ten (10) days of receipt of organic material at the facility:

1. Remove the organic material from the facility;
2. Start the active phase of composting;
3. Cover the organic material with a waterproof cover that has at least a six-feet (6') overlap of adjacent sheets and be securely anchored; or
4. Implement an APCO approved alternative mitigation measure, not listed above.

This facility is limited to a throughput of less than 100,000 tons of organic material stockpiled per year. The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of this section:

Permit	Conditions
C-447-268-2	6 and 9

Section 5.1.2 specifies requirements for a composting operation with a total throughput of greater than or equal to 100,000 wet tons per year of organic material. This facility is limited to an organic material stockpiled of less than 100,000 wet tons per year. Therefore, the requirements of this section are not applicable.

Section 5.2.1 requires the operator of a composting operation with a total throughput of less than 200,000 wet tons per year of organic material to comply with one of the following during the active phase of composting:

1. For windrow composting only, implement at least three turns during the active phase and one of the mitigation measures for the Watering Systems in Table 1.
2. Implement an APCO and EPA approved alternative mitigation measure that demonstrates at least a 19% reduction, by weight, in VOC emissions.

Based on information in project C-1120336, the facility chose to comply with item 1 above with the use of an integrated watering system. The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of this section:

Permit	Conditions
C-447-269-2	7 through 10

Section 5.2.2 specifies requirements for a composting operation with a total throughput of greater than or equal to 200,000 wet tons per year of organic material. This facility is limited to an organic material throughput of less than 200,000 wet tons per year. Therefore, the requirements of this section are not applicable.

Section 6.1 requires an operator to submit a Facility Emission Mitigation Plan (FEMP) along with an Authority to Construct (ATC) application, in accordance with Rule 2010 (Permits Required), to incorporate the approved mitigation measures from the facility's FEMP as applicable permit conditions. The operator has satisfied these requirements with the submission of their FEMP along with the ATC permit applications under project C-1120336.

Section 6.3.2 requires an operator subject to this rule to maintain an operations log. The operations log shall include the following information on a daily basis: (a). The date the organic material arrives on site; (b). The type of organic material received on site; and (c). The weight (in wet tons) of each type of organic material received on site.

Section 6.3.3 requires an operator of a composting facility subject to the stockpile requirements to maintain an operations log, which includes the following information on a daily basis: (a). The date of which each stockpile was initially formed; (b). The date and action taken on each stockpile to satisfy the stockpile requirements; and (c). Other information necessary to determine compliance with the requirements.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of these sections:

Permit	Condition
C-447-268-2	10

Section 6.3.4.1 requires an operator of a composting facility subject to the composting requirements for a watering system to maintain an operations log, which includes the following information on a daily basis: (a). Record the date and time the organic material from the windrow was tested for compliance; (b). Indicate whether the windrow passes the ball test and, if applicable, all corrective actions taken; (c). Record the date and time the windrow was turned; (d). Record other information necessary to determine compliance with the requirements.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-447-269-2	10

Section 6.3.5 requires an operator to retain all applicable records, as specified in the recordkeeping requirements of Section 6.0, on site for a period of five years and the records shall be made available to the APCO upon request.

The following condition on the draft renewed permits is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-447-268-2	12
C-447-269-2	11

F. District Rule 4621 – Gasoline Transfer Into Stationary Storage Containers, Delivery Vessels, and Bulk Plants

The purpose of this rule is to limit VOC emissions from stationary storage containers, delivery vessels and bulk plants and to provide the administrative requirements for determining compliance with this rule. Therefore, the requirements of this rule apply to the gasoline dispensing operations under permits C-447-9-6 and ‘-21-3.

Section 5.1 states that loading equipment and vapor collection equipment shall be installed, maintained, and operated such that it is leak-free, with no excess organic liquid drainage at disconnect.

Section 3.19.2 defines a leak as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration or total organic compound greater than 10,000 ppmv, as methane, above background when measured in accordance with the test method in Section 6.4.3. Any liquid or gas coming from a component undergoing repair or replacement, or during sampling of process fluid from a component or equipment into a container is not considered sampling of a leak provided such activities are accomplished as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere.

The following conditions on the draft renewed permits are a mechanism to ensure compliance with the requirements of these sections:

Permit	Conditions
C-447-9-6	4 and 5
C-447-21-3	5 and 6

Section 5.2.1 states that no person shall transfer, or permit the transfer, of gasoline from any delivery vessel into any stationary storage container subject to the requirements of this rule unless such container is equipped with an ARB certified permanent submerged fill pipe and utilizes an ARB certified Phase I vapor recovery system that is maintained and operated according to manufacturer specifications and the applicable ARB Executive Order.

In addition, ARB has the additional certification requirements, including applicable rules and regulations of the Division of Measurement Standards, the Department of Food and Agriculture, the Office of the State Fire Marshal, the Department of Forestry and Fire Protection, the Division of Occupational Safety and Health, the Department of Industrial Relations, and the Division of Water Quality of the State Water Resources Control Board that have been made conditions of the certification.

The following condition on the draft renewed permits is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-447-9-6 and '-21-3	1

Section 5.4.1 states that all aboveground storage containers shall be constructed and maintained in a leak-free condition.

The following condition on the draft renewed permits is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-447-9-6	3
C-447-21-3	4

Section 5.4.3 specifies requirements for aboveground storage containers that contain aviation gasoline. This facility does not handle aviation gasoline. Therefore, the requirements of this section are not applicable.

Section 5.4.4 states that operators of an aboveground storage container not located at a bulk plant shall conduct and pass a “Static Leak Test” (reference Section 6.4.8) performance test to determine compliance at least once every 36 months, (no more than 30 days before or after the required performance test date) unless otherwise required under ARB Executive Order.

The following conditions on the draft renewed permits are a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-447-9-6	10
C-447-21-3	17

Section 5.5 states that all Phase I vapor recovery systems shall be inspected according to the frequency specified in Table 1. The person conducting the inspections shall, at a minimum, verify that the fill caps and vapor caps are not missing, damaged, or loose, that the fill cap gasket and vapor cap gaskets are not missing or damaged, that the fill adapter and vapor adapter are securely attached to the risers, that, where applicable, the spring-loaded submerged fill tube seals properly against the coaxial tubing, and the dry break (poppet-valve) is not missing or damaged and that the submerged fill tube is not missing or damaged.

The following conditions on the draft renewed permits are a mechanism to ensure compliance with the requirements of this section:

Permit	Conditions
C-447-9-6	7 and 8
C-447-21-3	11 and 12

Section 5.6 specifies requirements for bulk plants. This facility is not a bulk plant. Therefore, the requirements of this section are not applicable.

Section 5.7.2 states that no person shall operate, or allow the operation of a delivery vessel unless valid State of California decals which attest to the vapor integrity of the container are displayed.

The following condition on the draft renewed permits is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-447-9-6	6
C-447-21-3	7

Section 6.1.4 states that all records required to demonstrate compliance with the requirements of this rule shall be retained on the premises for a minimum of five years and made available on site during normal business hours to the APCO, ARB, or EPA, and submitted to the APCO, ARB, or EPA upon request.

The following condition on the draft renewed permits is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-447-9-6	18
C-447-21-3	30

Section 6.2.3 states “Operators shall notify the District at least seven days prior to any performance testing.”

Section 6.2.4 states “Operators shall submit all performance test results to the District within 30 days of test completion.”

The following condition on the draft renewed permits is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-447-9-6	12
C-447-21-3	23

Section 6.3.1 states that installation and maintenance contractors shall be certified by the ICC for Vapor Recovery System Installation and Repair (VI) and make available onsite proof of ICC certification for VI, and have and make available on site proof of any and all certifications required by the Executive Order and installation and operation manual in order to install or maintain specific systems, or work under the direct and personal supervision of an individual physically present at the work site who possesses and makes available onsite a current certificate from the ICC, indicating he or she has passed the VI exam and all certifications required by the applicable Executive Order.

Section 6.3.2 states that All ICC certifications shall be renewed every 24 months by passing the appropriate exam specific to the certification being sought.

The following conditions on the draft renewed permits are a mechanism to ensure compliance with the requirements of these sections:

Permit	Conditions
C-447-9-6	13 and 14
C-447-21-3	21 and 22

Section 6.3.3 states that Gasoline Dispensing Facility Testers wishing to conduct vapor recovery system testing and repair at facilities located within the District, shall be in full compliance with District Rule 1177 (Gasoline Dispensing Facility Tester Certification).

The following condition on the draft renewed permits is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-447-9-6	15
C-447-21-3	20

G. District Rule 4622 – Gasoline Transfer Into Motor Vehicle Fuel Tanks

The purpose of this rule is to limit emissions of gasoline vapors from the transfer of gasoline into motor vehicle fuel tanks. This rule applies to any gasoline storage and dispensing operation or mobile fueler from which gasoline is transferred into motor vehicle fuel tanks. Therefore, the requirements of this rule apply to the gasoline dispensing operations under permits C-447-9-6 and '-21-3.

C-447-9-6 (phase II vapor recovery system exempt tank):

Section 4.1 states that except for the provisions of Section 6.1.1 and 6.1.2, the requirements of this rule shall not apply to the transfer of gasoline into motor vehicle fuel tanks from any existing storage container, with an aggregate dispensing throughput of:

- Less than or equal to 24,000 gallons per calendar year; and
- Less than or equal to 10,000 gallons in any consecutive 30-day period.
- Any facility which exceeds the throughput limitations specified above shall be subject to the provisions of this rule on and after the date the throughput limitations were exceeded and shall be in compliance according to the schedule in Section 7.1.

The gasoline dispensing operation under permit C-447-9-6 is limited to the throughput rates specified above. Therefore, this unit is only subject to the provisions of 6.1.1 and 6.1.2 of this rule. The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-447-9-6	16

Section 6.1.1 states that gasoline dispensing operations that are exempt under Section 4.1 shall maintain gasoline throughput records which will allow the gasoline throughput for any 30-day period to be continuously determined. These records shall be maintained on the premises as long as exempt status is claimed.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-447-9-6	17

Section 6.1.2 states that any gasoline dispensing operation previously exempt under Section 4.1 whose gasoline throughput exceeds the exemption levels shall notify the District within 30 days of the date of exceeding the exemption levels.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-447-9-6	16

C-447-21-3 (tank equipped with phase II vapor recovery):

Section 3.28 defines a retail gasoline outlet as an establishment at which gasoline is sold or offered for sale to the general public for use in motor vehicles. This facility does not sell gasoline to the general public.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-447-21-3	2

Section 5.1 states that a person shall not transfer or permit the transfer of gasoline from any stationary storage container, or from any mobile fueler with a capacity greater than 120 gallons, into a motor vehicle fuel tank with a capacity greater than 5 gallons, unless the gasoline dispensing unit used to transfer the gasoline is equipped with and has in operation an ARB certified Phase II vapor recovery system.

Section 5.1.1 states that all ARB certified Phase II vapor recovery systems shall be maintained according to ARB certifications and the manufacturer specifications applicable to the system. Since the facility operates this tank with an ARB certified Phase II vapor recovery system, requirements of this section are satisfied and compliance is expected.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-447-21-3	1

Section 5.1.2 states that all ARB certified Phase II vapor recovery systems and gasoline dispensing equipment shall be maintained without leaks as determined by EPA Test Method 21 (reference Section 6.5.4).

Section 3.17 defines a leak as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration or total organic compound greater than 10,000 ppmv, as methane, above background when measured in accordance with EPA Test Method 21. Any liquid or gas coming from a component undergoing repair or replacement, or during sampling of process fluid from a component or equipment into a container is not considered sampling of a leak provided such activities are accomplished as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere.

The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of these sections:

Permit	Conditions
C-447-21-3	5 and 6

Section 5.2.1 states that any gasoline dispensing system subject to this rule shall comply with the provisions of this rule at the time of installation. As shown in this evaluation, this gasoline dispensing operation is not being installed as a part of this project and is in compliance with the requirements of this rule. Therefore, the requirements of this section have been satisfied.

Section 5.2.2 states that operators shall have all underground storage container installations and all underground piping configurations inspected by the APCO prior to backfilling. This tank is an aboveground storage tank. Therefore, the requirements of this section are not applicable.

Section 5.2.3 states that installation and maintenance contractors shall, be certified by the ICC for Vapor Recovery System Installation and Repair by June 20, 2008, renew the ICC certification for Vapor Recovery System Installation and Repair every 24 months, make available onsite proof of ICC certification, and have and make available on site proof of any and all certifications required by the Executive Order and installation and operation manual in order to install or maintain specific systems.

Section 5.2.4 states "in lieu of complying with Sections 5.2.3.1 through 5.2.3.4, installation and maintenance contractors may work under the direct and personal supervision of an individual physically present at the work site who possesses and makes available on site current certifications from the ICC, indicating he or she has passed the ICC Vapor Recovery System Installation and Repair exam and all other certifications required by the applicable Executive Order."

The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of these sections:

Permit	Conditions
C-447-21-3	21 and 22

Section 5.2.5 states that notwithstanding any provisions of this rule, any gasoline dispensing operation which has installed and obtained a permit to operate an ARB certified Phase II vapor recovery system shall continue to use such system and shall maintain the system and all of its components in good-repair in order that such system can continue to comply with the certification recovery efficiency.

The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of this section:

Permit	Conditions
C-447-21-3	1 and 8

Section 5.2.6 states that any ARB certified Phase II vapor recovery system that has been installed shall not be removed regardless of the amount of gasoline dispensed or how the gasoline is delivered to the operation. Permit C-447-21 requires the above ground tank to be equipped with a Phase II vapor recovery system. In order to remove the system, E & J Gallo Winery would be required to submit an Authority to Construct application to request that change to this operation and the District would fully evaluate their request under that application. Therefore, the requirements of this section have been satisfied.

Section 5.3.1 states that the owner or operator of an ARB certified Phase II vapor recovery system shall conduct periodic maintenance inspections to ensure that components of the vapor recovery system are in proper operating condition.

Section 5.3.2 states that the frequency of inspections shall be based on the operation's largest monthly gasoline throughput from the previous calendar year as indicated in Table 1.

Section 5.3.3 states that the frequency of vapor path inspections shall be based on the amount of gasoline dispensed by the operation in a calendar month as indicated in Table 1.

Section 5.3.4 states that the person conducting the inspections shall at a minimum, verify that the fueling instructions required by Section 5.5 are clearly displayed with the appropriate toll-free complaint phone number and toxic warning signs, that the following nozzle components are in place and in good condition as specified in ARB Executive Orders: faceplate/facecone, bellows, latching device spring, vapor check valve, spout (proper diameter/vapor collection holes), insertion interlock mechanism, automatic shut-off mechanism, hold open latch, that the hoses are not torn, flattened or crimped, that the vapor path of coaxial hoses associated with bellows equipped nozzles does not contain more than 100 ml of liquid and that the vapor processing unit is functioning properly, for operations that are required to have or possess such a unit.

The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of these sections:

Permit	Conditions
C-447-21-3	11 and 13

Section 5.4.1 states that no person shall operate any ARB certified Phase II vapor recovery system or any portion thereof that has a major defect or an equipment defect that is identified in any applicable ARB Executive Order, until: the defect has been repaired, replaced, or adjusted as necessary to correct the defect; the District has been notified, and the District has reinspected the system or authorized the system for use. Such authorization shall not include the authority to operate the equipment prior to the correction of the defective components; and all major defects, after repair, are duly entered into the Operations and Maintenance (O&M) manual.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-447-21-3	8

Section 5.4.2 states that upon identification of any major defects, the owner or operator shall tag "Out-of-Order" all dispensing equipment for which vapor recovery has been impaired.

Section 5.4.2.1 states that tagged equipment shall be rendered inoperable and the tag(s) shall not be removed until the defective equipment has been repaired, replaced, or adjusted, as necessary.

Section 5.4.2.2 states that in the case of defects identified by the District, tagged equipment shall be rendered inoperable, and the tag shall not be removed until the District has been notified of the repairs, and the District has either reinspected the system or authorized the tagged equipment for use.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of these sections:

Permit	Condition
C-447-21-3	9

Section 5.4.4 states that in the event of a separation due to a drive off, the owner or operator shall complete one of the following, unless otherwise specified in the applicable ARB Executive Order, and document the activities in accordance with Section 6.2, before placing the affected equipment back in service:

- 1) Conduct a visual inspection of the affected equipment, perform qualified repairs on any damaged components, and conduct applicable re-verification tests pursuant to Sections 6.5.1.1 and 6.5.1.4, or
- 2) Conduct a visual inspection of the affected equipment and replace the affected nozzles, coaxial hoses, breakaway couplings, and any other damaged components with new or certified rebuilt components that are ARB certified, before placing affected equipment back in service.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-447-21-3	14

Section 5.5 is applicable to retail gasoline outlets. The tank operated at this facility is not used as a retail gasoline outlet. Therefore, the requirements of this section are not applicable.

Section 5.6 states that no person shall top off a motor vehicle fuel tank.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-447-21-3	3

Sections 5.7 and 5.8 establish requirements for hold-open gasoline dispensing nozzle latches utilized for retail gasoline outlets. The tank operated at this facility is not used as a retail gasoline outlet. Therefore, the requirements of these sections are not applicable.

Section 5.9 states that no owner or operator shall tamper with, or permit tampering with, the system in a manner that would impair the operation of effectiveness of the system.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-447-21-3	1

Section 5.10 states that all liquid removal devices required by ARB Executive Order shall be maintained to achieve a minimum liquid removal rate of five milliliters per gallon. This standard shall apply at dispensing rates exceeding five gallons per minute, unless a higher removal rate is specified in the applicable Executive Order.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-447-21-3	19

Section 5.11 establishes requirements for mobile fuelers. The tank operated at this facility is not used as part of a mobile fueler. Therefore, the requirements of this section are not applicable.

Section 5.12 requires that vapor condensate traps shall be used, if necessary, to keep the vapor return piping clear of any liquid blockage from the remote dispenser to the aboveground storage tank or when it is not possible to achieve the necessary slope from the dispenser to the underground storage tank. The aboveground storage tank is not equipped with a liquid condensate trap. Therefore, the requirements of this section are not applicable.

Section 5.13 establishes requirements for in-station diagnostics (ISD) systems. ISD systems are not required for aboveground gasoline storage tanks. Therefore, the requirements of this section do not apply.

Section 6.1 specifies recordkeeping and reporting requirements for gasoline dispensing systems that are exempt from installing a Phase II vapor recovery system. This gasoline dispensing system is equipped with a Phase II vapor recovery system. Therefore, the requirements of this section do not apply.

Section 6.2.1 requires that operators shall retain the test result verification that each ARB certified Phase II vapor recovery system meets or exceeds the requirements of the tests specified in Section 6.5. These verifications shall be maintained for at least five years. These test results shall be dated and shall contain the names, addresses, and telephone numbers of the companies responsible for system installation and testing.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-447-21-3	24

Section 6.2.2 requires a person who performs repairs on any ARB certified Phase I or Phase II vapor recovery system shall provide to the owner or operator a repair log, which the owner or operator shall maintain on the premises for at least five years and which shall include all of the following:

- 1) Date and time of each repair;
- 2) The name and applicable certification numbers of the person(s) who performed the repair, and, if applicable, the name, address and phone number of the person's employer;
- 3) Description of service performed;
- 4) Each component that was repaired, serviced, or removed;
- 5) Each component that was installed as replacement, if applicable;
- 6) Receipts or other documents for parts used in the repair and, if applicable, work orders which shall include the name and signature of the person responsible for performing the repairs.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-447-21-3	25

Section 6.2.3 requires each operator who is required to perform periodic maintenance inspections under Section 5.3 shall maintain monthly gasoline throughput records on the premises for a minimum of five years, make them available on site during normal business hours to the APCO, ARB, or EPA, and submit them to the APCO, ARB, or EPA upon request.

The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of this section:

Permit	Conditions
C-447-21-3	29 and 30

Section 6.3.1 requires that the owner or operator of a gasoline dispensing operation shall maintain an O&M Manual in accordance with Section 6.3.

Section 6.3.2 requires that the O&M manual shall be kept at the dispensing operation and made available to any person who operates, inspects, maintains, repairs, or tests the equipment at the operation as well as to District personnel upon request.

Section 6.3.3 requires that the O&M manual shall, at a minimum, include the following current information:

- 1) copies of all vapor recovery performance tests,
- 2) all applicable ARB Executive Orders, Approval Letters, and District Permits,
- 3) manufacturer's specifications and instructions for installation, operation, repair, and maintenance required pursuant to ARB Certification Procedure CP-201, and any additional instruction provided by the manufacturer,
- 4) system and/or component testing requirements, including test schedules and passing criteria for each of the standard tests listed in Section 6.0. The owner/operator may include any non-ARB required diagnostic and other tests as part of the testing requirements, and
- 5) additional O&M instructions, if any, that are designed to ensure compliance with the applicable rules, regulations, ARB Executive Orders, and District permit conditions, including replacement schedules for failure or wear prone components.

Section 6.3.4 requires owners or operators of gasoline dispensing operations shall document the periodic maintenance inspection program in the O&M manual.

The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of these sections:

Permit	Conditions
C-447-21-3	10 and 26

Section 6.4.1 requires that operators shall comply with the ARB certified Phase II vapor recovery system performance tests specified in Sections 6.4.1.1 through 6.4.1.4 and shall conduct all applicable performance tests at start up and thereafter (no more than 30 days before or after the required compliance testing date) as required by ARB Executive Order and installation and operation manuals.

Section 6.4.1.1 requires that an operator shall conduct and pass a Static Leak Test of the ARB certified Phase II vapor recovery system at least once every twelve months.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-447-21-3	17

Section 6.4.1.2 requires that an operator shall conduct and pass a Dynamic Back-Pressure Test of the ARB certified Phase II vapor recovery system at least once every twelve months except for those aboveground storage tanks that have integral dispensers (non-remote), unless otherwise required under ARB Executive Order. All balance Phase II systems require integral dispensers (top or side mounted). The only balance system that allows a non-integral dispenser is Petro Vault (G-70-130-A) and the maximum distance of the dispenser from the base of the tank is 2 feet which is not considered a remote dispenser. Therefore, balance Phase II systems cannot have a remote dispenser and thus no Dynamic Back-Pressure Test is required for balance Phase II systems.

Section 6.4.1.3 requires that for ARB certified Phase II vapor recovery systems with bellows-less nozzles, conduct and pass, as applicable, an Air-to-Liquid Volume Ratio Test or a Vapor-to-Liquid Ratio Test at least once every six months. This gasoline dispensing system is not equipped with bellows-less nozzles. Therefore, the requirements of this section are not applicable.

Section 6.4.1.4 requires that for ARB certified Phase II vapor recovery systems with a liquid removal device required by ARB Executive Orders, conduct and pass a Liquid Removal Test whenever the liquid in the vapor path exceeds 100 ml of liquid. The amount of liquid in the vapor path shall be determined in accordance with the procedure specified in Section 5.3.5.4. This gasoline dispensing system is not equipped with a liquid removal device. Therefore, the requirements of this section are not applicable.

Section 6.4.2 requires that the person responsible for conducting the tests specified in Section 6.4 shall use calibrated equipment meeting the calibration range and calibration intervals specified by the manufacturer, ARB Executive Order, or ARB test procedure.

Section 6.4.3 requires that each person responsible for conducting tests specified in Section 6.5 shall be in full compliance with all provisions of Rule 1177 (Gasoline Dispensing Facility Tester Certification).

Section 6.4.4 requires that each gasoline dispensing operation shall notify the District at least seven days prior to any performance testing.

Section 6.4.5 requires that each ARB certified Phase II vapor recovery system shall be tested within 60 days of completion of installation or modification.

The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of these sections:

Permit	Conditions
C-447-21-3	19 and 23

Section 6.5.1 requires that tests shall be conducted in accordance with the latest version of the following ARB and EPA approved test methods, or their equivalents as approved by the EPA, and the APCO.

Section 6.5.1.2 requires that Dynamic Back-Pressure Test be conducted using ARB method TP-201.4.

Section 6.5.1.3 requires that Air-to-Liquid Volume Ratio Test be conducted using ARB method TP-201.5.

Section 6.5.1.4 requires that Liquid Removal Test be conducted using ARB method TP-201.6C.

Section 6.5.1.5 requires that Static Leak Test for Aboveground Tanks be conducted using ARB method TP-206.3 or TP-201.3B, as applicable.

The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of these sections:

Permit	Conditions
C-447-21-3	16 and 17

H. District Rule 4702 – Internal Combustion Engines

The purpose of this rule is to limit the emissions of nitrogen oxides (NO_x), carbon monoxide (CO), volatile organic compounds (VOC), and sulfur oxides (SO_x) from internal combustion engines.

This rule applies to any internal combustion engine rated at 25 brake horsepower or greater. Therefore, the requirements of this rule apply to the 138 bhp transportable IC engine operating under permit C-447-23-7 and the 130 bhp emergency IC engine operating under permit C-447-267-3.

C-447-23-7 (transportable IC engine powering a rotary screener):

Section 5.1 establishes requirements for engines rated between 25 bhp and 50 bhp. The transportable IC engine operated at this facility is rated at 138 bhp. Therefore, the requirements of this section are not applicable to this engine.

Section 5.2 establishes emission requirements for engines rated at greater than 50 bhp. Section 5.2.4 establishes the emission limits for certified compression-ignited engines.

Engine Type	Emission Limit/ Standard	Compliance Date
1. Non-Certified Compression-Ignited Engine		
a. Greater than 50 bhp but not more than 500 bhp	EPA Tier 3 or Tier 4	1/1/2010
b. Greater than 500 bhp but not more than 750 bhp and less than 1000 annual operating hours	EPA Tier 3	1/1/2010
c. Greater than 750 bhp and less than 1000 annual operating hours	EPA Tier 4	7/1/2011
d. Greater than 500 bhp and greater than or equal to 1000 annual operating hours	80 ppm NO _x , 2,000 ppm CO, 750 ppm VOC	1/1/2008 or, if owner has an agreement to electrify, comply by 1/1/2010
2. Certified Compression-Ignited Engine		
a. EPA Certified Tier 1 or Tier 2 Engine	EPA Tier 4	1/1/2015 or 12 years after installation date, but not later than 6/1/2018
b. EPA Certified Tier 3 or Tier 4 Engine	Meet Certified Compression-Ignited Engine Standard in effect at time of installation	At time of installation

This engine is a Tier 3 certified diesel-fired IC engine (as identified in the unit's equipment description). In addition, the following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of this section:

Permit	Conditions
C-447-23-7	10 and 11

Section 5.3 specifies requirements for units equipped with continuous emission monitoring systems (CEMS). This engine is not equipped with a CEMS. Therefore, the requirements of this section are not applicable.

Sections 5.4 and 5.5 specify requirements for engines that utilize the percent emission reduction option to comply with the NO_x emission requirements of Section 5.2. This engine does not utilize the percent emission reduction option to comply with the NO_x emission requirements of Section 5.2. Therefore, the requirements of these sections are not applicable.

Section 5.6 specifies requirements for operators that elect to pay an annual fee in lieu of complying with the NO_x emission limits specified in this rule. This engine complies with the NO_x emission limits specified in the rule. Therefore, the annual fee payment requirements of this section are not applicable.

Section 5.7 specifies emission control requirements for sulfur oxides (SO_x). Operators of non-agricultural operation (AO) spark-ignited engines and non-AO compression ignited engines shall comply with one of the following:

- 5.7.1 Operate the engine exclusively on PUC-quality natural gas, commercial propane, butane, or liquefied petroleum gas, or a combination of such gases; or
- 5.7.2 Limit gaseous fuel sulfur content to no more than five (5) grains of total sulfur per one hundred (100) standard cubic feet; or
- 5.7.3 Use California Reformulated Gasoline for gasoline-fired spark-ignited engines; or
- 5.7.4 Use California Reformulated Diesel for compression-ignited engines; or
- 5.7.5 Operate the engine on liquid fuel that contains no more than 15 ppm sulfur, as determined by the test method specified in Section 6.4.6; or
- 5.7.6 Install and properly operate an emission control system that reduces SO_x emissions by at least 95% by weight, as determined by the test method specified in Section 6.4.6.

This engine is operated only on CARB certified diesel fuel. The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirement of this section:

Permit	Condition
C-447-23-7	9

Section 5.8 specifies monitoring requirements for non-AO spark-ignited engines and any engine subject to the alternative emission control plan (AECPP) requirements of Section 8.0. This engine is a compression-ignited engine and is not subject to the AECPP requirements of Section 8.0. Therefore, the requirements of this section are not applicable.

Section 5.9 establishes monitoring requirements for all other engines that are not subject to Section 5.8 above. Section 5.9.1 requires that the operator of a compression-ignited engine subject to the emission requirements of Section 5.2 comply with the requirements specified in Sections 5.9.2 through 5.9.5.

- 5.9.2 Properly operate and maintain each engine as recommended by the engine manufacturer or emission control system supplier.
- 5.9.3 Monitor the operational characteristics of each engine as recommended by the engine manufacturer or emission control system supplier.
- 5.9.4 Install and operate a nonresettable elapsed time meter.
- 5.9.5 The requirements of this section are applicable to AO spark-ignited engines that have been retro-fitted with a NO_x exhaust control device. This engine is a compression-ignited engine and is not equipped with any add-on control devices for NO_x emissions. Therefore, the requirements of this section are not applicable.

The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of these sections:

Permit	Conditions
C-447-23-7	3, 5, and 13

Section 6.1 establishes requirements for emission control plans for each engine. The engine in this project is already subject to, and complying with, the requirements of this rule. Therefore, the emission control plan requirements are not applicable at this time.

Section 6.2 requires that except for engines subject to Section 4.0, the owner of an engine subject to the requirements of Section 5.2 shall maintain an engine operating log to demonstrate compliance with this rule. This information shall be retained for a period of at least five years, shall be readily available, and be made available to the APCO upon request. The engine-operating log shall include, on a monthly basis, the following information:

- Total hours of operation,
- Type of fuel used,
- Maintenance or modifications performed,
- Monitoring data,
- Compliance source test results, and
- Any other information necessary to demonstrate compliance with this rule.

The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of this section:

Permit	Conditions
C-447-23-7	14 and 16

Section 6.3 establishes compliance testing requirements for engines that have been retrofitted with an exhaust control device, engines subject to Section 8.0; an AO spark-ignited engine that is subject to the requirements of Section 8.0; or an AO spark-ignited engine that has been retrofitted with a catalytic emission control and is not subject to the requirements of Section 8.0. This engine is a compression-ignited engine and is not subject to the requirements of Section 8.0. Therefore, the compliance testing requirements of this section are not applicable.

Section 6.4 specifies the appropriate test methods to be used for units subject to the compliance testing requirements specified in Section 6.3 above. This engine is not required to perform compliance testing in accordance with Section 6.3 above. Therefore, the requirements of this section are not applicable.

Section 6.5 establishes inspection and monitoring (I&M) plan requirements for engines that have been retrofitted with an exhaust control device, engines subject to Section 8.0; an AO spark-ignited engine that is subject to the requirements of Section 8.0; or an AO spark-ignited engine that has been retrofitted with a catalytic emission control and is not subject to the requirements of Section 8.0. This engine is a compression-ignited engine and is not subject to the requirements of Section 8.0. Therefore, the compliance testing requirements of this section are not applicable.

C-447-267-3 (emergency IC engine powering a firewater pump):

Pursuant to Section 4.3, except for the requirements of Section 6.2.3, the requirements of this rule shall not apply to an internal combustion engine that meets the following conditions:

- 1) The engine is operated exclusively to preserve or protect property, human life, or public health during a disaster or state of emergency, such as a fire or flood, and
- 2) Except for operations associated with Section 4.3.1.1, the engine is limited to operate no more than 100 hours per calendar year as determined by an operational nonresettable elapsed operating time meter, for periodic maintenance, periodic readiness testing, and readiness testing during and after repair work of the engine, and
- 3) The engine is operated with a nonresettable elapsed operating time meter. In lieu of installing a nonresettable time meter, the owner of an engine may use an alternative device, method, or technique, in determining operating time provided that the alternative is approved by the APCO. The owner of the engine shall properly maintain and operate the time meter or alternative device in accordance with the manufacturer's instructions.

Section 6.2.3 requires that an owner claiming an exemption under Section 4.2 or Section 4.3 shall maintain annual operating records. This information shall be retained for at least five years, shall be readily available, and submitted to the APCO upon request and at the end of each calendar year in a manner and form approved by the APCO. The records shall include, but are not limited to, the following:

- Total hours of operation,
- The type of fuel used,
- The purpose for operating the engine,
- For emergency standby engines, all hours of non-emergency and emergency operation shall be reported, and
- Other support documentation necessary to demonstrate claim to the exemption.

The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of these sections.

Permit	Conditions
C-447-267-3	3, 7, 10, 11, 13, and 14

I. 40 CFR Part 60, Subpart Db– Standards of Performance for Industrial-Commercial-Institutional Steam Generating Units

This subpart establishes requirements for steam generating units that have a heat input capacity of greater than 100 MMBtu/hr. The boiler operating under permit C-447-2-19 has a maximum rating of 142.0 MMBtu/hr boiler under permit. Therefore, the requirements of this subpart apply to this boiler. Since the time that the permit was last modified, some sections of this subpart have been amended. However, the sections which were amended do not affect any of the conditions on permit C-447-2-19. Therefore, a full breakdown of the requirements of this subpart will not be included in this evaluation.

The following conditions were taken from the current permit for this boiler and will be included on the renewed permit as a mechanism to ensure continued compliance with the requirements of this subpart.

Permit	Conditions
C-447-2-19	7, 28, 30, 33, 34, 40, 41, and 43

J. 40 CFR Part 60, Subpart Dc– Standards of Performance for Small Industrial-Commercial-Institutional Steam Generating Units

This subpart establishes requirements for steam generating units that have a heat input capacity of less than 100 MMBtu/hr and that commenced construction, modification, or reconstruction after June 9, 1989. The facility has one 62.0 MMBtu/hr boiler operating under permit C-447-1-13 and two 99 MMBtu/hr boilers operating under permits C-447-295-2 and '-329-1. The boiler operating under permit C-447-1-13 was constructed prior to June 9, 1989 and has not undergone a modification or reconstruction since that time. Therefore, the requirements of this subpart are not applicable to this boiler. The other two boilers were constructed after June 9, 1989. Therefore, the requirements of this subpart apply to these two boilers. Since the time that these permits were last modified, some sections of this subpart have been amended. However, the sections which were amended do not affect any of the conditions on these permits. Therefore, a full breakdown of the requirements of this subpart will not be included in this evaluation.

The following conditions were taken from the current permits for these boilers and will be included on the renewed permits as a mechanism to ensure continued compliance with the requirements of this subpart.

Permit	Conditions
C-447-295-2	4 and 34
C-447-329-1	4 and 42

K. 40 CFR Part 60, Subpart IIII – Standards of Performance for Stationary Compression Ignition Internal Combustion Engines

This subpart establishes requirements for manufacturers, owners, and operators of stationary compression ignition engines that were constructed after July 11, 2005. The 130 bhp diesel fired emergency engine powering a firewater pump operating under permit C-447-267-3 is the only unit subject to the requirements of this subpart at this facility. Since the time that the permit was last modified, some sections of this subpart have been amended. However, the sections which were amended do not affect any of the conditions on permit C-447-267-3. Therefore, a full breakdown of the requirements of this subpart will not be included in this evaluation.

The following conditions were taken from the current permit for this emergency IC engine and will be included on the renewed permit as a mechanism to ensure continued compliance with the requirements of this subpart.

Permit	Conditions
C-447-267-3	3, 4, 5, 6, 7, and 10

L. 40 CFR Part 64 - CAM

§64.2 – Applicability

This section requires Compliance Assurance Monitoring (CAM) for units that meet the following three criteria:

- 1) the unit must have an emission limit for the pollutant;
- 2) the unit must have add-on controls for the pollutant; these are devices such as flue gas recirculation (FGR), baghouses, and catalytic oxidizers; and
- 3) the unit must have a pre-control potential to emit of greater than the major source thresholds.

Pollutant	Major Source Threshold (lb/year)
VOC	20,000
NO _x	20,000
CO	200,000
PM ₁₀	140,000
SO _x	140,000

a. C-447-1 – 62.0 MMBtu/hr Biogas/Natural Gas Fired Boiler

The permit for this boiler contains emission limits for NO_x, CO, VOC, PM₁₀ and SO_x emissions. However, this boiler is not equipped with any add on control devices for CO, VOC, PM₁₀ or SO_x emissions. Therefore, the CAM requirements of 40 CFR 64 are not applicable for these pollutants and no further discussion is required.

This boiler is equipped with a flue gas recirculation system (FGR) and a selective catalytic reduction system for NO_x emission control. Typically the District assumes that an FGR system in combination with an SCR system will achieve 90% control for the NO_x emissions generated in a natural gas fired boiler. Therefore, the uncontrolled NO_x emission rate from this boiler can be determined using the boiler heat input rate, the controlled NO_x emission factor, the control efficiency of the SCR/FGR system, and a worst case operating scenario of 8,760 hours/year.

NO_x Emissions:

Emission Factor = 0.008 lb/MMBtu

Heat Input Rating = 62.0 MMBtu/hr

FGR+SCR Control Efficiency = 90%

Annual Uncontrolled PE = $[0.008 \text{ lb/MMBtu} \times 62 \text{ MMBtu/hour} \times 8,760 \text{ hours/year}] / (1 - 0.90)$

Annual Uncontrolled PE = 43,450 lb/year

As shown above, the uncontrolled PE for NO_x emissions is greater than the major source threshold. Therefore, this boiler is subject to the requirements of 40 CFR 64.

b. C-447-2 – 142 MMBtu/hr Natural Gas Fired Boiler

The permit for this boiler contains emission limits for NO_x, CO, VOC, PM₁₀ and SO_x emissions. However, this boiler is not equipped with any add on control devices for CO, VOC, PM₁₀ or SO_x emissions. Therefore, the CAM requirements of 40 CFR 64 are not applicable for these pollutants and no further discussion is required.

This boiler is equipped with a Continuous Emission Monitoring System (CEMS) for NO_x emissions. In accordance with District practice, units equipped with a CEMS system are exempt from CAM requirements. Therefore, this unit is exempt from CAM requirements for NO_x emissions.

Therefore, this boiler is not subject to the requirements of 40 CFR 64.

c. C-447-5, '-6 and '-8 – Diatomaceous Earth Storage Silos #1, #2 and #3, Each Served by a Dust Collector or Baghouse

The permits for these storage silos do not contain emission limitations for any pollutant. Therefore, the CAM requirements of 40 CFR 64 are not applicable and no further discussion is required.

d. C-447-9 – Gasoline Dispensing Operation with 500 Gallon Aboveground Storage Tank

The permit for this gasoline dispensing operation does not contain emission limitations for any pollutant. Therefore, the CAM requirements of 40 CFR 64 are not applicable and no further discussion is required.

e. C-447-10, thru '-14 and '-17 thru '-20 – Abrasive Blasting Operations

These abrasive blasting permits do not contain emission limitations for any pollutant. Therefore, the CAM requirements of 40 CFR 64 are not applicable and no further discussion is required.

f. C-447-16 – Metal Parts and Products Coating Operation

This metal parts and products coating operation only has permitted VOC and PM₁₀ emission limits. However, the coating operation is not equipped with any add on control devices for VOC emissions. Therefore, the CAM requirements of 40 CFR 64 are not applicable to this pollutant and no further discussion is required.

The operation is served by a paint spray booth with dry exhaust filters for PM₁₀ emission control. Pursuant to current District policy and practice, the dry exhaust filters will achieve 95% PM₁₀ emission control. Therefore, the uncontrolled PM₁₀ emission rate from this operation can be determined using the annual emission limit on the current permit and the control efficiency of the dry exhaust filters.

PM₁₀ Emissions:

Annual Emissions = 2,600 lb/year (1.3 tons/year)

Dry Filter Control Efficiency = 95%

Annual Uncontrolled PE = 2,600 lb/year / (1 – 0.95)

Annual Uncontrolled PE = 52,000 lb/year

As shown above, the uncontrolled PE for PM₁₀ emissions is less than the major source threshold. Therefore, this metal parts and products coating operation is not subject to the requirements of 40 CFR 64 for this pollutant and no further discussion is required.

g. C-447-21 – Gasoline Dispensing Operation with 1,000 Gallon Aboveground Storage Tank

The permit for this gasoline dispensing operation does not contain emission limitations for any pollutant. Therefore, the CAM requirements of 40 CFR 64 are not applicable and no further discussion is required.

h. C-447-23 – 138 BHP Transportable Diesel Fired IC Engine Powering a Trommel Screen

The engine generates NO_x, CO, VOC, PM₁₀ and SO_x emissions. The trommel screen also generates PM₁₀ emissions. The permit contains emission limits for all of these pollutants. However, neither the engine or the trommel screen are equipped with an add on control device. Therefore, the CAM requirements of 40 CFR 64 are not applicable to this unit and no further discussion is required.

- i. C-447-27 through '-214, '-224, '-271 through '-294, and '-296 through '-327 – Wine Fermentation and/or Storage Tanks

These wine fermentation and/or storage tanks are not equipped with any add-on control equipment. Therefore, the CAM requirements of 40 CFR 64 are not applicable to these units and no further discussion is required.

- j. C-447-215 through '-223 and '-234 through '-266 – Distilled Spirits Storage Tanks

These distilled spirit storage tanks are not equipped with any add-on control equipment. Therefore, the CAM requirements of 40 CFR 64 are not applicable to these units and no further discussion is required.

- k. C-447-225 – Winery Wastewater Pretreatment and Equalization Operation

This winery wastewater and pretreatment and equalization operation does not contain emission limits for any pollutant. Therefore, the CAM requirements of 40 CFR 64 are not applicable to this unit and no further discussion is required.

- l. C-447-226 – 175,320 Gallon Winery Wastewater Anaerobic Reactor

This wastewater anaerobic reactor has the potential to generate NO_x, CO, VOC, PM₁₀ and SO_x emissions. The permit contains emission limits from the exhaust of the flare serving this operation for NO_x, CO, VOC, PM₁₀ and SO_x. The biogas generated in this wastewater anaerobic reactor is combusted in one of the four boilers operated at this facility. However, if one, or all, of the boilers are not operational, the flare is used as a backup combustion device to prevent biogas (a highly explosive/flammable gas) from being emitted directly to the atmosphere. The biogas can contain small amounts of VOCs. Therefore, as a conservative estimate, it will be assumed that the flare is a control device for VOC emissions. The flare is not considered a control device for NO_x, CO, PM₁₀ or SO_x emissions. Therefore, the CAM requirements of 40 CFR 64 are not applicable for these pollutants and no further discussion is required.

Typically, the District assumes that a flare will achieve 98% control for VOC emissions generated in a wastewater reactor. Therefore, the uncontrolled VOC emission rate from the reactor can be determined using the biogas heating value, the controlled VOC emission factor on the current permit, the control efficiency of the flare, and the biogas production limits on the current permit.

VOC Emissions:

Biogas Heating Value = 691 Btu/scf

Emission Factor = 0.002 lb/MMBtu

Flare Control Efficiency = 98%

Biogas Production Limits: 1st Qtr = 31,670,000 scf; 2nd Qtr = 31,800,300 scf; 3rd and 4th Qtrs = 44,334,800 scf (481,900 scf/day * 92 days)

Annual Uncontrolled PE = $[0.002 \text{ lb-VOC/MMBtu} \times 691 \text{ Btu/scf} \times (31.67 + 31.80 + 44.33 + 44.33) \text{ MMscf/year}] / (1 - 0.98)$

Annual Uncontrolled PE = 10,512 lb/year

As shown above, the uncontrolled PE for VOC emissions is less than the major source threshold. Therefore, this wastewater anaerobic reactor is not subject to the requirements of 40 CFR 64 for this pollutant and no further discussion is required.

m. C-447-227 – 502,100 Gallon Winery Wastewater Anaerobic Reactor

This winery wastewater anaerobic reactor does not contain emission limits for any pollutant. Therefore, the CAM requirements of 40 CFR 64 are not applicable to this unit and no further discussion is required.

n. C-447-230 – Agricultural Waste Composting Operation

This agricultural waste material handling and storage operation only generates PM₁₀ emission and the permit contains a PM₁₀ emission limit. However, the operation is not equipped with any add on control devices. Therefore, the CAM requirements of 40 CFR 64 are not applicable to this unit and no further discussion is required.

o. C-447-233 – Diatomaceous Earth Storage Silo Served by a Bin Vent Filter

This diatomaceous earth storage silo only generates PM₁₀ emissions. The operation is served by a baghouse for PM₁₀ emission control. Typically the District assumes that a baghouse will achieve 99% PM₁₀ emission control. Therefore, the uncontrolled PM₁₀ emission rate from this operation can be determined using the emission factor and annual throughput limit listed on the current permit and the control efficiency of the baghouse.

PM₁₀ Emissions:

Emission Factor = 0.00085 lb/ton
Throughput = 2,500 ton/year
Baghouse Control Efficiency = 99%

Annual Uncontrolled PE = $[0.00085 \text{ lb/ton} \times 2,500 \text{ ton/year}] / (1 - 0.99)$

Annual Uncontrolled PE = 213 lb/year

As shown above, the uncontrolled PE for PM₁₀ emissions is less than the major source threshold. Therefore, this diatomaceous earth storage silo is not subject to the requirements of 40 CFR 64 for this pollutant and no further discussion is required.

p. C-447-267 – 130 bhp Diesel-Fired Emergency IC Engine

This emergency IC engine generates NO_x, CO, VOC, PM₁₀ and SO_x emissions. The permit contains emission limits for all of these pollutants. However, the engine is not equipped with any add on emission control devices. Therefore, the CAM requirements of 40 CFR 64 are not applicable to this unit and no further discussion is required.

q. C-447-268 – Green Waste Organic Material Receiving, Storage and Mixing Operation

The permit for this green waste organic material received, storage and mixing operation contains emission limits for VOC, PM₁₀, and NH₃ emissions. However, this operation is not equipped with any add on control devices. Therefore, the CAM requirements of 40 CFR 64 are not applicable to this unit and no further discussion is required.

r. C-447-269 – Open Windrow Green Waste Composting Operation

The permit for this open windrow green waste composting operation contains emission limits for VOC, PM₁₀, and NH₃ emissions. However, this operation is not equipped with any add on control devices for VOC and NH₃ emissions. Therefore, the CAM requirements of 40 CFR 64 are not applicable for these pollutants and no further discussion is required.

This operation is equipped with an integrated water sprinkler system to help control fugitive dust (PM₁₀) emissions during the receiving, handling, loading, and mixing of the feedstock materials. In accordance with the definition of a control device from 40 CFR 64.1, a control device means equipment, other than inherent process equipment, that is used to destroy or remove air pollutant(s) prior to discharge to the atmosphere. As discussed above, the water sprays associated with this process are in place to reduce fugitive PM₁₀ emissions from dry material handling. The water sprays are not destroying or removing these air pollutants prior to discharge to the atmosphere. Therefore, the water sprays are not considered a control device and the CAM requirements of 40 CFR 64 are not applicable for PM₁₀ emissions. No further discussion is required.

s. C-447-270 – Finished Compost Storage and Loadout Operation

This finished compost storage and loadout operation is not equipped with any add-on control equipment. In addition, the current permit does not contain emission limits for any pollutant. Therefore, the CAM requirements of 40 CFR 64 are not applicable to this unit and no further discussion is required.

t. C-447-295 – 99 MMBtu/hr Natural Gas/Biogas-Fired Boiler (#4)

The permit for this boiler contains emission limits for NO_x, CO, VOC, PM₁₀ and SO_x emissions. However, this boiler is not equipped with any add on control devices for CO, VOC, PM₁₀ or SO_x emissions. Therefore, the CAM requirements of 40 CFR 64 are not applicable for these pollutants and no further discussion is required.

This boiler is equipped with a flue gas recirculation system (FGR) and a selective catalytic reduction system for NO_x emission control. Typically the District assumes that an FGR system in combination with an SCR system will achieve 90% control for the NO_x emissions generated in a natural gas fired boiler. Therefore, the uncontrolled NO_x emission rate from this boiler can be determined using the boiler heat input rate, the controlled NO_x emission factor, the control efficiency of the SCR/FGR system, and a worst case operating scenario of 8,760 hours/year.

NO_x Emissions:

Emission Factor = 0.006 lb/MMBtu
Heat Input Rating = 99.0 MMBtu/hr
FGR+SCR Control Efficiency = 90%

$$\text{Annual Uncontrolled PE} = [0.006 \text{ lb/MMBtu} \times 99 \text{ MMBtu/hour} \times 8,760 \text{ hours/year}] / (1 - 0.90)]$$

$$\text{Annual Uncontrolled PE} = 52,034 \text{ lb/year}$$

As shown above, the uncontrolled PE for NO_x emissions is greater than the major source threshold. Therefore, this boiler is subject to the requirements of 40 CFR 64.

u. C-447-328 – Diatomaceous Earth Storage Silo Served by a Bin Vent Filter

This diatomaceous earth storage silo only generates PM₁₀ emissions. The operation is served by a bin vent filter for PM₁₀ emission control. Typically the District assumes that a bin vent filter will achieve 99% PM₁₀ emission control. Therefore, the uncontrolled PM₁₀ emission rate from this operation can be determined using the emission factor and annual throughput limit listed on the current permit and the control efficiency of the baghouse.

PM₁₀ Emissions:

Emission Factor = 0.00085 lb/ton

Throughput = 25 ton/day => 9,125 ton/year (based on 365 days/year)

Baghouse Control Efficiency = 99%

$$\text{Annual Uncontrolled PE} = [0.00085 \text{ lb/ton} \times 9,125 \text{ ton/year}] / (1 - 0.99)$$

$$\text{Annual Uncontrolled PE} = 776 \text{ lb/year}$$

As shown above, the uncontrolled PE for PM₁₀ emissions is less than the major source threshold. Therefore, this diatomaceous earth storage silo is not subject to the requirements of 40 CFR 64 for this pollutant and no further discussion is required.

v. C-447-329 – 99 MMBtu/hr Biogas/Natural Gas-Fired Boiler (#3)

The permit for this boiler contains emission limits for NO_x, CO, VOC, PM₁₀ and SO_x emissions. However, this boiler is not equipped with any add on control devices for CO, VOC, PM₁₀ or SO_x emissions. Therefore, the CAM requirements of 40 CFR 64 are not applicable for these pollutants and no further discussion is required.

This boiler is equipped with a flue gas recirculation system (FGR) and a selective catalytic reduction system for NO_x emission control. Typically the District assumes that an FGR system in combination with an SCR system will achieve 90% control for the NO_x emissions generated in a natural gas fired boiler. Therefore, the uncontrolled NO_x emission rate from this boiler can be determined using the boiler heat input rate, the controlled NO_x emission factor, the control efficiency of the SCR/FGR system, and a worst case operating scenario of 8,760 hours/year.

NO_x Emissions:

Emission Factor = 0.006 lb/MMBtu
Heat Input Rating = 99 MMBtu/hr
FGR+SCR Control Efficiency = 90%

$$\text{Annual Uncontrolled PE} = [0.006 \text{ lb/MMBtu} \times 99 \text{ MMBtu/hour} \times 8,760 \text{ hours/year}] / (1 - 0.90)$$

$$\text{Annual Uncontrolled PE} = 52,034 \text{ lb/year}$$

As shown above, the uncontrolled PE for NO_x emissions is greater than the major source threshold. Therefore, this boiler is subject to the requirements of 40 CFR 64.

§64.3 thru §64.10 – CAM Monitoring, Design, Operation and Submittal Requirements

As shown above, the 62 MMBtu/hr natural gas/biogas-fired boiler served by a selective catalytic reduction (SCR) system (permit C-447-1-13) and the two 99 MMBtu/hr natural gas/biogas-fired boilers each served by an SCR system (permits C-447-295-2 and '-329-1) are the only units subject to CAM at this facility. SCR systems operate as an external control device where flue gases and a reagent, in this case ammonia, are passed through an appropriate catalyst. Ammonia, will be injected upstream of the catalyst where it reacts and reduces NO_x, over the catalyst bed, to form elemental nitrogen and other by-products.

E & J Gallo Winery previously elected to satisfy CAM requirements for each of these units by installing in-stack NO_x and O₂ analyzers upstream of the stack sampling locations used during source testing. The in-stack analyzers take NO_x and O₂ measurements at least once each day that each boiler operates.

The following conditions on the draft renewed permits are a mechanism to ensure compliance with the requirements of this subpart:

Permit	Condition
C-447-1-13	35 through 42
C-447-295-2	35 through 42
C-447-329-1	34 through 41

M. 40 CFR Part 82, Subpart B – Servicing of Motor Vehicle Air Conditioners

The purpose of 40 CFR Part 82 Subpart B is to implement section 609 of the Clean Air Act, as amended regarding the servicing of motor vehicle air conditioners (MVACs), and to implement section 608 of the Clean Air Act regarding certain servicing, maintenance, repair and disposal of air conditioners in MVACs and MVAC-like appliances.

These regulations apply to any person performing service on a motor vehicle for consideration when this service involves the refrigerant in the motor vehicle air conditioner.

The amendments to this rule do not have any effect on current permit requirements and will therefore not be addressed further in this evaluation.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-447-0-4	28

N. 40 CFR Part 82, Subpart F – Recycling and Emissions Reductions

The purpose of 40 CFR Part 82 Subpart F is to reduce emissions of class I and class II refrigerants and their substitutes to the lowest achievable level by maximizing the recapture and recycling of such refrigerants during the service, maintenance, repair, and disposal of appliances and restricting the sale of refrigerants consisting in whole or in part of a class I and class II ODS in accordance with Title VI of the Clean Air Act.

These regulations apply to any person servicing, maintaining, or repairing appliances. This subpart also applies to persons disposing of appliances, including small appliances and motor vehicle air conditioners. In addition, this subpart applies to refrigerant reclaimers, technician certifying programs, appliance owners and operators, manufacturers of appliances, manufacturers of recycling and recovery equipment, approved recycling and recovery equipment testing organizations, persons selling class I or class II refrigerants or offering class I or class II refrigerants for sale, and persons purchasing class I or class II refrigerants.

The amendments to this rule do not have any effect on current permit requirements and will therefore not be addressed further in this evaluation.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-447-0-4	27

IX. PERMIT SHIELD

A permit shield legally protects a facility from enforcement of the shielded regulations when a source is in compliance with the terms and conditions of the Title V permit. Compliance with the terms and conditions of the Operating Permit is considered compliance with all applicable requirements upon which those conditions are based, including those that have been subsumed.

A. Requirements Addressed by Model General Permit Templates

The applicant is not requesting to use any model general permit templates for this Title V renewal project.

B. Requirements not Addressed by Model General Permit Templates

E & J Gallo Winery is not requesting any new permit shields within this Title V renewal project. In addition, E & J Gallo Winery is not requesting any changes to the existing permit shields already included in their Title V operating permit. Therefore, all of the existing permit shields will be maintained on the revised permit for this renewal project.

X. CALIFORNIA ENVIRONMENTAL QUALITY ACT

The purpose of the Title V permit renewal is to update the permit to ensure that any changes to regulations since the issuance of the initial Title V permit or most recent renewal of the Title V permit are incorporated as permit requirements.

Per the California Environmental Quality Act (CEQA) Statute §21080.24, and CEQA Guidelines §15281, the issuance, modification, amendment, or renewal of any permit by an air pollution control district or air quality management district pursuant to Title V is exempt from CEQA, unless the issuance, modification, amendment, or renewal authorizes a physical or operational change to a source or facility. There will be no physical or operational change to the source or facility nor will the Title V permit renewal authorize a physical or operational change to the source or facility. Therefore, this project, a Title V permit renewal, is subject to a ministerial action that is exempt from CEQA.

XI. PERMIT CONDITIONS

See Attachment A – Draft Renewed Title V Operating Permit

ATTACHMENTS

- A. Draft Renewed Title V Operating Permit
- B. Previous Title V Operating Permit
- C. Detailed Facility List

ATTACHMENT A

Draft Renewed Title V Operating Permit

San Joaquin Valley Air Pollution Control District

FACILITY: C-447-0-4

EXPIRATION DATE: 06/30/2016

FACILITY-WIDE REQUIREMENTS

1. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1 and Fresno County Rule 110] Federally Enforceable Through Title V Permit
2. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0 and Fresno County Rule 110] Federally Enforceable Through Title V Permit
3. {4364} The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (8/18/11). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.13.1] Federally Enforceable Through Title V Permit
6. {4367} A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. {4368} Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. {4369} The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. {4370} The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-0-4 : May 19 2017 9:00AM -- BROWND

10. {4371} The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit
11. {4372} Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
12. {4373} If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
13. {4374} It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
14. {4375} The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
15. {4376} The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
16. {4377} The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
17. {4378} The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
18. {4379} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
19. {4380} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
20. {4381} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
21. {4382} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit
22. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

23. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
24. {4385} All VOC-containing materials subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
25. {4386} The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
26. {4387} With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
27. {4388} If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
28. {4389} If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit
29. {4390} Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8021] Federally Enforceable Through Title V Permit
30. {4391} Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8031] Federally Enforceable Through Title V Permit
31. {4392} An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8041] Federally Enforceable Through Title V Permit
32. {4393} Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8051] Federally Enforceable Through Title V Permit
33. {4394} Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8061] Federally Enforceable Through Title V Permit
34. {4395} Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8071] Federally Enforceable Through Title V Permit
35. {4396} Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

36. {4397} The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
37. {4398} The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
38. {4399} When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
39. {4400} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), Rule 111 (Kern, Tulare, Kings), and Rule 202 (Fresno, Kern, Tulare, Kings, Madera, Stanislaus, Merced, San Joaquin). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. {4401} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601 (12/17/09); 8021 (8/19/2004); 8031 (8/19/2004); 8041 (8/19/2004); 8051 (8/19/2004); 8061 (8/19/2004); and 8071 (9/16/2004). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
42. Should the facility, as defined in 40 CFR section 68.3, become subject to part 68, then the owner or operator shall submit a risk management plan (RMP) by the date specified in 40 CFR section 68.10. The facility shall certify compliance as part of the annual certification as required by 40 CFR part 70. [40 CFR 68] Federally Enforceable Through Title V Permit
43. A Three-Year Compliance Plan that demonstrates compliance with the requirements of Section 5.1 of District Rule 4694 for each year of the applicable compliance period shall be submitted to the District by no later than December 1, 2018, and every three years thereafter on or before December 1. [District Rule 4694]
44. A Three-Year Compliance Plan Verification that demonstrates that the Three-Year Compliance Plan elements are in effect shall be submitted to the District by no later than July 1, 2019, and every three years thereafter on or before July 1. [District Rule 4694]
45. An Annual Compliance Plan Demonstration that shows compliance with the applicable requirements of this rule shall be submitted to the District by no later than March 1, 2018, and every year thereafter on or before March 1. [District Rule 4694]
46. Operators using Certified Emissions Reductions (CER) to mitigate fermentation emissions shall perform all monitoring and recordkeeping, as established in their approved Three-Year Compliance Plan, and shall maintain all records necessary to demonstrate compliance. [District Rule 4694]
47. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report begin January 1 of every year, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit
48. Facilities C-447 and C-3275 are part of the same stationary source for Rule 2201 purposes. [District Rule 2201]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-1-13

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

62.0 MMBTU/HR B & W BIOGAS/NATURAL GAS-FIRED BOILER EQUIPPED WITH A TODD LOW NOX BURNER, FLUE GAS RECIRCULATION, O2 AND CO TRIM CONTROLLERS, A CRI COMPANY SELECTIVE CATALYTIC REDUCTION (SCR) SYSTEM MODEL SHELL DNOX LFR, AND A NOX AND O2 IN-STACK EMISSION MONITORING SYSTEM

PERMIT UNIT REQUIREMENTS

1. All equipment shall be constructed, maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District Rule 2201] Federally Enforceable Through Title V Permit
2. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Particulate matter emissions shall not exceed 0.1 grain/dscf at operating conditions, nor 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
4. The unit shall only be fired on PUC-regulated natural gas and/or on scrubbed biogas from C-447-226. [District Rules 2201, 4301, 4320 and 4801, and Fresno County Rule 406] Federally Enforceable Through Title V Permit
5. The unit shall not burn more than 1,296,000 scf of biogas fuel in any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The H2S content of the scrubbed biogas fuel shall not exceed 50 ppmv. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
7. Except during start-up and shutdown, emissions from this unit shall not exceed any of the following limits: 7 ppmvd NOx @ 3% O2 or 0.008 lb-NOx/MMBtu; 0.0022 lb-PM10/MMBtu; 100 ppmvd CO @ 3% O2 (equivalent to 0.074 lb-CO/MMBtu); or 0.0025 lb-VOC/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
8. During start-up and shutdown, emissions from this unit shall not exceed either of the following limits: 0.68 lb-NOx/hr, or 4.59 lb-CO/hr. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
9. The total duration of start-up time shall not exceed 9.0 hours per day. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. The total duration of startup time shall not exceed 6.0 hours per occurrence. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
11. The total duration of shutdown time shall not exceed 6.0 hours per day. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
12. The total duration of shutdown time shall not exceed 3.0 hours per occurrence. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. The emission control systems shall be in operation and emissions shall be minimized insofar as technologically feasible during start-up and shutdown. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

14. The ammonia (NH₃) emissions shall not exceed 10 ppmvd @ 3% O₂ over a 15 minute averaging period. [District Rule 4102]
15. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
16. Source testing to measure natural gas/biogas combustion NO_x, CO, and NH₃ emissions from this unit shall be conducted at least once every twelve months. After demonstrating compliance on two consecutive annual source tests when unit is fired on natural gas/biogas, the unit shall be tested not less than once every 36 months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve months. [District Rules 2201, 4102, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
17. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
18. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
19. NO_x emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
20. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
21. Stack gas oxygen (O₂) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
22. Source testing for ammonia slip shall be conducted utilizing BAAQMD Method ST-1B. [District Rule 4102]
23. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
24. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
25. The permittee shall monitor and record the stack concentration of NO_x, CO, NH₃, and O₂ at least once during each month in which source testing is not performed. NO_x, CO, and O₂ monitoring shall be conducted utilizing a portable analyzer that meets District specifications or District-approved monitoring equipment. NH₃ monitoring shall be conducted utilizing Draeger tubes or a District approved equivalent method. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless it has been performed within the last month. [District Rules 4102, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
26. If the NO_x, CO or NH₃ concentrations, as measured by the portable analyzer or the District approved ammonia monitoring equipment, exceed the permitted levels, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than one hour of operation after detection. If the portable analyzer or the ammonia monitoring equipment continue to show emission limit violations after one hour of operation following detection, the permittee shall notify the District within the following one hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

27. All NO_x, CO, O₂ and NH₃ emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The NO_x, CO and O₂ analyzer as well as the NH₃ emission monitoring equipment shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
28. NH₃ emission readings shall be conducted at the time the NO_x, CO and O₂ readings are taken. The readings shall be converted to ppmvd @ 3% O₂. [District Rule 4102]
29. The permittee shall maintain records of: (1) the date and time of NO_x, CO, NH₃, and O₂ measurements, (2) the O₂ concentration in percent by volume and the measured NO_x, CO, and NH₃ concentrations corrected to 3% O₂, (3) make and model of the portable analyzer, (4) portable analyzer calibration records, (5) the method of determining the NH₃ emission concentration, and (6) a description of any corrective action taken to maintain the emissions at or below the acceptable levels. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
30. Operator shall maintain copies of fuel invoices and supplier certifications. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
31. Permittee shall determine sulfur content of combusted natural gas annually or shall demonstrate that the combusted natural gas is provided from a PUC or FERC regulated source. [District Rules 1081 and 4320] Federally Enforceable Through Title V Permit
32. The permittee shall monitor the biogas H₂S concentration at the outlet of the biogas scrubber (Permit to Operate C-447-226) on a weekly basis. If the biogas H₂S concentration does not exceed 50 ppmv for four consecutive weeks, monitoring may be conducted on a monthly basis. If the H₂S concentration at the outlet exceeds 50 ppmv, weekly monitoring shall resume. [District Rule 4320] Federally Enforceable Through Title V Permit
33. The permittee shall maintain daily records of start-up and shutdown durations and number of occurrences of each. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
34. The permittee shall maintain records of the daily and cumulative annual natural gas and biogas consumption. [District Rule 2201] Federally Enforceable Through Title V Permit
35. The permittee shall take readings of the NO_x concentration and O₂ percent, by volume, using the in-stack monitoring system at least once per each day that the boiler operates. [District Rule 2201 and 40 CFR Part 64.9] Federally Enforceable Through Title V Permit
36. During times when the in-stack monitoring system is down for maintenance or repairs, the permittee shall use a District approved portable analyzer to record daily NO_x and O₂ concentrations. The permittee shall maintain records of the portable analyzer readings including the date(s) and reason the in-stack monitoring system was not operating. [District Rule 2201 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
37. The permittee shall maintain daily records of the NO_x and O₂ concentration from the in-stack monitoring system. These records shall be made available for District inspection upon request. [District Rule 2201 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
38. The permittee shall compare the NO_x and O₂ concentrations from the in-stack monitoring system with the concentration of NO_x and O₂ readings from calibration gas cylinders for NO_x and O₂ at least once during each month that the boiler operates. The permittee shall maintain these comparison readings and these records shall be available for District inspection upon request. [District Rule 2201 and 40 CFR Part 64] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

39. If the NO_x or O₂ concentrations, as measured by the in-stack monitoring system, exceed the permitted levels the permittee shall return the emissions to compliant levels as soon as possible, but no longer than 1 hour of operation after detection. If the in-stack monitoring system continues to show emission limit violations after 1 hour of operation following detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation that is subject to enforcement action has occurred. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [40 CFR 64] Federally Enforceable Through Title V Permit
40. The permittee shall comply with the compliance assurance monitoring operation and maintenance requirements of 40 CFR part 64.7. [40 CFR Part 64.7] Federally Enforceable Through Title V Permit
41. If the District or EPA determine that a Quality Improvement Plan is required under 40 CFR 64.7(d)(2), the permittee shall develop and implement the Quality Improvement Plan in accordance with 40 CFR Part 64.8. [40 CFR Part 64.8] Federally Enforceable Through Title V Permit
42. The permittee shall comply with the record keeping and reporting requirements of 40 CFR part 64.9. [40 CFR Part 64.9] Federally Enforceable Through Title V Permit
43. All records shall be maintained and retained on-site for a minimum of five years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
44. Compliance with permit conditions in the Title V permit shall be deemed compliance with subsumed requirements of SJVUAPCD Rule 4301. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
45. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements of Fresno County Rule 406 and SJVUAPCD Rule 4801. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
46. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201, 4301, and 4305. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
47. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of SJVUAPCD Rule 1081. A permit shield is granted from this requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
48. The requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source because it is not used to produce electricity for sale and was constructed prior to June 9, 1989 without modifications or reconstruction. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-2-19

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

142.0 MMBTU/HR NEBRASKA MODEL 84 NATURAL GAS-FIRED BOILER WITH A TODD LOW NOX-BURNER, FLUE GAS RECIRCULATION (FGR) SYSTEM, CRI COMPANY SELECTIVE CATALYTIC REDUCTION (SCR) SYSTEM, AND AN ABB MODEL AO2000 CEMS

PERMIT UNIT REQUIREMENTS

1. To ensure the validity of the ERCs issued by Project # 920370, NOx emissions shall not exceed the 0.036 pound per million Btu limitation based on a 24-hour rolling average of the NOx concentration calculated from CEMS. All performance testing shall be done in compliance with District Rules. [District Rules 2201 and 2301 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
2. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Particulate matter emissions shall not exceed 0.1 grain/dscf at operating conditions, nor 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
4. The unit shall only be fired on PUC-regulated natural gas. [District Rules 2201, 4301, 4306, and 4320] Federally Enforceable Through Title V Permit
5. Except during start-up and shutdown, emissions from this unit shall not exceed any of the following limits: 7 ppmvd NOx @ 3% O2 or 0.008 lb-NOx/MMBtu; 0.00285 lb-SOx/MMBtu; 0.0024 lb-PM10/MMBtu; 200 ppmvd CO @ 3% O2 (equivalent to 0.148 lb-CO/MMBtu); or 0.0027 lb-VOC/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
6. During start-up and shutdown, emissions from the exhaust of the SCR system serving this boiler shall not exceed either of the following limits: 1.56 lb-NOx/hr, or 21.0 lb-CO/hr. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. NOx emissions shall not exceed 0.10 lb/MMBtu including periods of startup, shutdown, or malfunction. Compliance with the 0.10 pound per million Btu limitation shall be based on a 30-day rolling average of the NOx concentration calculated from CEMS. All performance testing shall be done in compliance with 40 CFR 60.8. [40 CFR 60.44b (c), (e), (h), and (i) and 40 CFR Part 64] Federally Enforceable Through Title V Permit
8. The total duration of start-up time shall not exceed 9.0 hours per day. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
9. The total duration of startup time shall not exceed 6.0 hours per occurrence. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. The total duration of shutdown time shall not exceed 6.0 hours per day. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
11. The total duration of shutdown time shall not exceed 3.0 hours per occurrence. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. The emission control systems shall be in operation and emissions shall be minimized insofar as technologically feasible during startup and shutdown. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. The ammonia (NH₃) emissions shall not exceed 10 ppmvd @ 3% O₂. [District Rule 4102]
14. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
15. Source testing to measure natural gas-combustion NO_x and CO emissions, and ammonia (NH₃) emissions from this unit shall be conducted at least once every twelve months. After demonstrating compliance on two consecutive annual source tests, the unit shall be tested not less than once 36 months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve months. [District Rules 4102, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
16. The facility shall source test VOC and PM₁₀ emissions from this unit upon request by the District. Emissions shall be calculated using the arithmetic mean, pursuant to District Rule 1081 (Amended December 16, 1993), of 3 thirty minute test runs unless other averaging times are approved in advance. [District Rules 1081 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
18. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
19. NO_x emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
20. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
21. Stack gas oxygen (O₂) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
22. Source testing for ammonia slip shall be conducted utilizing BAAQMD method ST-1B. [District Rule 2201] Federally Enforceable Through Title V Permit
23. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
24. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
25. A Continuous Emissions Monitoring System (CEMS) shall be in place and operating whenever the facility is operating. NO_x emissions in ppmv (as NO₂ corrected to 3% O₂), CO emissions in ppmv (corrected to 3% O₂) and O₂ concentrations must be recorded continuously. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
26. CEMS emission measurements shall be averaged over a period of 15 consecutive minutes to demonstrate compliance with the applicable emission limits. [District Rules 4306 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

27. The facility shall install and maintain equipment, facilities, and systems compatible with the District's CEM data polling software system and shall make CEM data available to the District's automated polling system on a daily basis. [District Rule 1080] Federally Enforceable Through Title V Permit
28. Upon notice by the District that the facility's CEM system is not providing polling data, the facility may continue to operate without providing automated data for a maximum of 30 days per calendar year provided the CEM data is sent to the District by a District-approved alternative method. [District Rule 1080] Federally Enforceable Through Title V Permit
29. The nitrogen oxide emission rates measured by the CEMS shall be expressed in lb/million Btu or in ng/J. The 1-hour average emission rates shall be calculated using the data points required under Section 60.13(b). The records shall also include a daily emission rate consisting of an averaged 24 hour rolling emission rate. [District Rule 2201, 40 CFR 60.48b (d), and 40 CFR Part 64] Federally Enforceable Through Title V Permit
30. The procedures under Section 60.13 shall be followed for evaluation, and operation of the CEMS. [40 CFR 60.48b (e) and 40 CFR Part 64] Federally Enforceable Through Title V Permit
31. Operation and calibration of the Continuous Emissions Monitoring System shall be in accordance with the requirements of 40 CFR, Part 60, Appendix B. [District Rules 1080 and 4001 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
32. The owner/operator shall on a perform a relative accuracy test (RATA) as specified by 40 CFR Part 60, Appendix F, and as specified by 40 CFR Part 60, Appendix B, Spec. 2, Section 7 annually. [District Rule 1080, 40 CFR Part 60.13(c), and 40 CFR Part 64] Federally Enforceable Through Title V Permit
33. In cases of CEMS breakdown, malfunction, repairs, calibration checks, and adjustments, emission data shall be obtained as described in paragraph f of 40 CFR 60.48b. [40 CFR 60.48b (f) and 40 CFR Part 64] Federally Enforceable Through Title V Permit
34. The owner shall submit quarterly excess emission reports for any calendar quarter during which there are excess emissions. The owner shall also submit semiannual reports stating that there have been no excess emissions during periods when there have been no excess emissions. [40 CFR 60.49b (h)] Federally Enforceable Through Title V Permit
35. The permittee shall monitor and record the stack concentration of ammonia (NH₃) at least once during each month in which a source test is not performed. NH₃ monitoring shall be conducted utilizing Draeger tubes or a District approved equivalent method. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within one day of restarting the unit unless monitoring has been performed within the last month. [District Rule 4102]
36. Ammonia (NH₃) emission readings shall be converted to ppmvd @ 3% O₂. [District Rule 4102]
37. The permittee shall maintain records of: (1) the date and time of ammonia (NH₃) measurements, (2) the O₂ concentration in percent by volume and the measured NH₃ concentrations corrected to 3% O₂, (3) the method of determining the NH₃ emission concentration, and (4) a description of any corrective action taken to maintain the emissions at or below the acceptable levels. [District Rule 4102]
38. Operator shall maintain copies of fuel invoices and supplier certifications. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
39. Permittee shall determine sulfur content of combusted gas annually or shall demonstrate that the combusted gas is provided from a PUC or FERC regulated source. [District Rules 1081 and 4320] Federally Enforceable Through Title V Permit
40. Daily summaries of continuous monitoring records for each calendar quarter shall be submitted to the District within 30 days of the end of the calendar quarter. [40 CFR 60.49b (i) and 40 CFR Part 64] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

41. The following records shall be kept for each steam generating unit operating day: (1) Calendar date, (2) Average hourly NO_x emission rate, (3) Average 30-day emission rate for preceding 30 operating days, (4) Identification of daily NO_x limit exceedances including reason for exceedance and the corrective actions taken, (5) Identification of daily CEMS interruptions including reason for interruption and the corrective actions taken, (6) Identification of data exclusions and the reasons for the exclusion, (7) Identification of F factor used for calculations, (8) Identification of times that the pollutant concentration exceeded the full span of the CEMS, (9) Description of modifications to the CEMS, (10) Results of daily CEMS drift tests and other tests required under Appendix B. [40 CFR 60.49b (g) and 40 CFR Part 64] Federally Enforceable Through Title V Permit
42. The permittee shall record the daily startup and shutdown duration times of the boiler. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
43. The owner shall record and maintain records of the amounts of each fuel combusted during each day and calculate the annual capacity factor for each calendar quarter. [40 CFR 60.49b (d)] Federally Enforceable Through Title V Permit
44. All records shall be maintained and retained on-site for a minimum of five years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
45. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed Fresno County APCD Rules: 108.1, 404, 406, and 408. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
46. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: Rule 1081, 4201, 4202, 4301, 4305, and 40 CFR 60 subpart Db. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-5-4

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

STORAGE SILO A FOR DIATOMACEOUS EARTH SERVED BY A SLY PACTECON MODEL #PS3 BAGHOUSE DUST COLLECTOR WITH SHAKER CLEANER

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grain per dry standard cubic foot. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed the hourly rate as calculated in District Rule 4202 using the equation $E = 3.59 \times P^{0.62}$ if P is less than or equal to 30 tons per hour, or $E = 17.31 \times P^{0.16}$ if P is greater than 30 tons per hour. [District Rule 4202] Federally Enforceable Through Title V Permit
3. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 4102]
4. Material removed from dust collectors shall be disposed of in a manner preventing entrainment into the atmosphere. [District Rule 4102]
5. Visible emissions shall be inspected annually during operation. If visible emissions are observed, corrective action shall be taken to eliminate visible emissions. If visible emissions cannot be corrected within 24 hours, a visible emissions test using EPA Method 9 shall be conducted. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. Dust collection system shall be completely inspected annually while in operation for evidence of particulate matter leaks and repaired as needed. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. Dust collector filters shall be thoroughly inspected annually for tears, scuffs, abrasions, holes, or any evidence of particulate matter leaks and shall be replaced as needed. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. Records of dust collector maintenance, inspections, and repair shall be maintained. The records shall include identification of the equipment, date of inspection, corrective action taken, and identification of the individual performing the inspection. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-6-4

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

STORAGE SILO B FOR DIATOMACEOUS EARTH SERVED BY A SLY PACTECON MODEL #PS3 BAGHOUSE DUST COLLECTOR WITH SHAKER CLEANER

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grain per dry standard cubic foot. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed the hourly rate as calculated in District Rule 4202 using the equation $E = 3.59 \times P^{0.62}$ if P is less than or equal to 30 tons per hour, or $E = 17.31 \times P^{0.16}$ if P is greater than 30 tons per hour. [District Rule 4202] Federally Enforceable Through Title V Permit
3. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 4102]
4. Material removed from dust collectors shall be disposed of in a manner preventing entrainment into the atmosphere. [District Rule 4102]
5. Visible emissions shall be inspected annually during operation. If visible emissions are observed, corrective action shall be taken to eliminate visible emissions. If visible emissions cannot be corrected within 24 hours, a visible emissions test using EPA Method 9 shall be conducted. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. Dust collection system shall be completely inspected annually while in operation for evidence of particulate matter leaks and repaired as needed. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. Dust collector filters shall be thoroughly inspected annually for tears, scuffs, abrasions, holes, or any evidence of particulate matter leaks and shall be replaced as needed. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. Records of dust collector maintenance, inspections, and repair shall be maintained. The records shall include identification of the equipment, date of inspection, corrective action taken, and identification of the individual performing the inspection. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-8-4

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

8,190 CUBIC FT SILO C FOR STORAGE OF DIATOMACEOUS EARTH SERVED BY A DYNAMIC AIR PULSE-JET BAGHOUSE FILTER

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grain per dry standard cubic foot. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed the hourly rate as calculated in District Rule 4202 using the equation $E = 3.59 \times P^{0.62}$ if P is less than or equal to 30 tons per hour, or $E = 17.31 \times P^{0.16}$ if P is greater than 30 tons per hour. [District Rule 4202] Federally Enforceable Through Title V Permit
3. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants in the atmosphere. [District Rule 4102]
4. Material removed from dust collectors shall be disposed of in a manner preventing entrainment in the atmosphere. [District Rule 4102]
5. The baghouse shall be equipped with a pressure differential gauge to indicate the pressure drop across the bags. The gauge shall be maintained in good working condition at all times and shall be located in an easily accessible location. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Visible emissions or proper pressure drop shall be inspected annually during operation. If visible emissions or improper pressure drops are observed, corrective action shall be taken to eliminate visible emissions or improper pressure drop. If visible emissions or improper pressure drop cannot be corrected within 24 hours, a visible emissions test using EPA Method 9 shall be conducted. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. Dust collection system shall be completely inspected annually while in operation for evidence of particulate matter leaks and repaired as needed. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. Dust collector filters shall be thoroughly inspected annually for tears, scuffs, abrasions, holes, or any evidence of particulate matter leaks and shall be replaced as needed. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
9. Records of dust collector maintenance, inspections, and repair shall be maintained. The records shall include identification of the equipment, date of inspection, corrective action taken, and identification of the individual performing the inspection. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-9-6

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

GASOLINE DISPENSING OPERATION WITH ONE 500 GALLON CONVAULT ABOVEGROUND STORAGE TANK SERVED BY OPW EVR PHASE I VAPOR RECOVERY SYSTEM (VR-401-B), STANDING LOSS CONTROL (VR-301-D), AND ONE FUELING POINT WITH ONE PHASE II EXEMPT GASOLINE DISPENSING NOZZLE

PERMIT UNIT REQUIREMENTS

1. The Phase I and Standing Loss Control Vapor recovery systems shall be maintained in accordance with the manufacturer specifications and the ARB Executive Orders specified in this permit, including applicable rules and regulations of the Division of Measurement Standards of the Department of Food and Agriculture, the Office of the State Fire Marshal of the Department of Forestry and Fire Protection, the Division of Occupational Safety and Health of the Department of Industrial Relations, and the Division of Water Quality of the State Water Resources Control Board that have been made conditions of the certification. [District Rule 4621 and CH&SC 41950] Federally Enforceable Through Title V Permit
2. This gasoline storage and dispensing equipment shall not be used in retail sales, where gasoline dispensed by the unit is subject to payment of California sales tax on gasoline sales. [District Rule 4621] Federally Enforceable Through Title V Permit
3. The storage container(s) shall be maintained and operated such that they are leak-free. [District Rule 4621] Federally Enforceable Through Title V Permit
4. The Phase I vapor recovery systems and gasoline dispensing equipment shall be maintained without leaks as determined in accordance with the test method specified in this permit. [District Rule 4621] Federally Enforceable Through Title V Permit
5. A leak is defined as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration of total organic compound greater than 10,000 ppmv, as methane, above background when measured in accordance with EPA Test Method 21. [District Rule 4621] Federally Enforceable Through Title V Permit
6. No gasoline delivery vessel shall be operated or be allowed to operate unless valid State of California decals are displayed on the cargo container, which attest to the vapor integrity of the container. [District Rule 4621] Federally Enforceable Through Title V Permit
7. The permittee shall conduct periodic maintenance inspections based on the greatest monthly throughput of gasoline dispensed by the facility in the previous year as follows: A) less than 2,500 gallons - one day per month; B) 2,500 to less than 25,000 gallons - one day per week; or C) 25,000 gallons or greater - five days per week. All inspections shall be documented within the O & M Manual. [District Rule 4621] Federally Enforceable Through Title V Permit
8. Periodic maintenance inspections of the Phase I vapor recovery system shall include, at a minimum, verification that 1) the fill caps and vapor caps are not missing, damaged, or loose; 2) the fill cap gasket and vapor cap gaskets are not missing or damaged; 3) the fill adapter and vapor adapter are securely attached to the risers; 4) where applicable, the spring-loaded submerged fill tube seals properly against the coaxial tubing; 5) the dry break (poppet-valve) is not missing or damaged; and 6) the submerged fill tube is not missing or damaged. [District Rule 4621] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. The permittee shall conduct all periodic vapor recovery system performance tests specified in this permit, no more than 30 days before or after the required compliance testing date, unless otherwise required under the applicable ARB Executive Order. [District Rule 4621] Federally Enforceable Through Title V Permit
10. The permittee shall perform and pass a Static Leak Test "Determination of Static Pressure Performance of Vapor Recovery Systems at Gasoline Dispensing Facilities with Aboveground Tanks" in accordance with the Executive Order specified in this permit for the Phase I Vapor Recovery System at least once every 36 months. [District Rule 4621] Federally Enforceable Through Title V Permit
11. If a rotatable Phase I vapor adaptor is installed, the permittee shall perform and pass a Static Torque of Rotatable Phase I Adaptors test using ARB procedure TP-201.1B at least once every 36 months. [District Rule 4621] Federally Enforceable Through Title V Permit
12. The permittee shall notify the District at least 7 days prior to each performance test. The test results shall be submitted to the District no later than 30 days after the completion of each test. [District Rule 4621] Federally Enforceable Through Title V Permit
13. A person performing installation of, or maintenance on, a certified Phase I vapor recovery system shall be certified by the ICC for Vapor Recovery System Installation and Repair, or work under the direct and personal supervision of an individual physically present at the work site who is certified. The ICC certification shall be renewed every 24 months. [District Rule 4621] Federally Enforceable Through Title V Permit
14. Proof of the ICC certification and all other certifications required by the Executive Order and installation and operation manual shall be made available onsite. [District Rule 4621] Federally Enforceable Through Title V Permit
15. A person conducting testing of, or repairs to, a certified vapor recovery system shall be in compliance with District Rule 1177 (Gasoline Dispensing Facility Tester Certification). [District Rule 4621] Federally Enforceable Through Title V Permit
16. Total gasoline throughput for the facility shall not exceed either of the following: 10,000 gallons in any consecutive 30-day period or 24,000 gallons per calendar year. If throughput exceeds stated limits, the permittee shall submit a complete application for an Authority to Construct (ATC) to the District within 30 days of the loss of exemption and install and test a certified Phase II vapor recovery system within six (6) months from the date the ATC is issued. [District Rule 4622] Federally Enforceable Through Title V Permit
17. The permittee shall maintain monthly and annual gasoline throughput records. The records should allow the gasoline throughput for any 30-day period to be continuously determined. These records shall be maintained on the premises as long as exempt status is claimed. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
18. All records required by this permit shall be retained on-site for a period of at least five years and shall be made available for District inspection upon request. [District Rule 4621] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-10-4

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

CONFINED AND UNCONFINED ABRASIVE BLASTING OPERATION WITH A 6 CU. FT. CAPACITY CLEMCO MODEL 2452 BLASTING POT #1 VENTED TO A BLAST BOOTH (COMMON TO C-447-10 THRU C-447-14) WITH A PAULI MODEL #CT BAGHOUSE DURING CONFINED BLASTING, AND WITH A CLEMCO MODEL AVS-50E ELECTRIC VACUUM

PERMIT UNIT REQUIREMENTS

1. All abrasive blasting shall be conducted within a permanent building unless steel or iron shot/grit is used exclusively, the item to be blasted exceeds 8 feet in any dimension, or the surface being blasted is situated at its permanent location or no further away from its permanent location than is necessary to allow the surface to be blasted. [92500 CCR]
2. Abrasive blasting operations conducted outside a permanent building which do not use steel or iron shot/grit exclusively shall use: wet abrasive blasting, hydroblasting, vacuum blasting, or abrasives certified by CARB for permissible dry outdoor blasting. [92500 CCR]
3. Abrasive blasting operations conducted outside a permanent building shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 2 or equivalent to 40% opacity. [92200 CCR]
4. Abrasive blasting operations conducted within the blast booth shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 1 or equivalent to 20% opacity. [92200 CCR]
5. A used certified abrasive shall not be considered certified for reuse unless the abrasive conforms to its original cut-point fineness. [92530 CCR]
6. All abrasive blasting shall be conducted in accordance with California Code of Regulations Title 17, Subchapter 6, Sections 92000 through 92540. [CCR]
7. When using an IC engine greater than 50 bhp to power an air compressor, the IC engine shall be registered or permitted. [District Rule 2010] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-11-4

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

CONFINED AND UNCONFINED ABRASIVE BLASTING OPERATION WITH A 6 CU. FT. CAPACITY CLEMCO MODEL 2452 BLAST POT #2, VENTED TO A BLAST BOOTH (COMMON TO C-447-10 THRU C-447-14) WITH A PAULI MODEL #CT BAGHOUSE DURING CONFINED BLASTING, AND A CLEMCO MODEL AVS-50E ELECTRIC VACUUM

PERMIT UNIT REQUIREMENTS

1. All abrasive blasting shall be conducted within a permanent building unless steel or iron shot/grit is used exclusively, the item to be blasted exceeds 8 feet in any dimension, or the surface being blasted is situated at its permanent location or no further away from its permanent location than is necessary to allow the surface to be blasted. [92500 CCR]
2. Abrasive blasting operations conducted outside a permanent building which do not use steel or iron shot/grit exclusively shall use: wet abrasive blasting, hydroblasting, vacuum blasting, or abrasives certified by CARB for permissible dry outdoor blasting. [92500 CCR]
3. Abrasive blasting operations conducted outside a permanent building shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 2 or equivalent to 40% opacity. [92200 CCR]
4. Abrasive blasting operations conducted within the blast booth shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 1 or equivalent to 20% opacity. [92200 CCR]
5. A used certified abrasive shall not be considered certified for reuse unless the abrasive conforms to its original cut-point fineness. [92530 CCR]
6. All abrasive blasting shall be conducted in accordance with California Code of Regulations Title 17, Subchapter 6, Sections 92000 through 92540. [CCR]
7. When using an IC engine greater than 50 bhp to power an air compressor, the IC engine shall be registered or permitted. [District Rule 2010] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-12-4

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

CONFINED AND UNCONFINED ABRASIVE BLASTING OPERATION WITH A 100 POUND CLEMCO-MODEL 1440 BLAST POT #3, VENTED TO A BLAST BOOTH (COMMON TO C-447-10 THRU C-447-14) WITH A PAULI MODEL #CT BAGHOUSE DURING CONFINED BLASTING, AND A CLEMCO MODEL AVS-50E ELECTRIC VACUUM

PERMIT UNIT REQUIREMENTS

1. All abrasive blasting shall be conducted within a permanent building unless steel or iron shot/grit is used exclusively, the item to be blasted exceeds 8 feet in any dimension, or the surface being blasted is situated at its permanent location or no further away from its permanent location than is necessary to allow the surface to be blasted. [92500 CCR]
2. Abrasive blasting operations conducted outside a permanent building which do not use steel or iron shot/grit exclusively shall use: wet abrasive blasting, hydroblasting, vacuum blasting, or abrasives certified by CARB for permissible dry outdoor blasting. [92500 CCR]
3. Abrasive blasting operations conducted outside a permanent building shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 2 or equivalent to 40% opacity. [92200 CCR]
4. Abrasive blasting operations conducted within the blast booth shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 1 or equivalent to 20% opacity. [92200 CCR]
5. A used certified abrasive shall not be considered certified for reuse unless the abrasive conforms to its original cut-point fineness. [92530 CCR]
6. All abrasive blasting shall be conducted in accordance with California Code of Regulations Title 17, Subchapter 6, Sections 92000 through 92540. [CCR]
7. When using an IC engine greater than 50 bhp to power an air compressor, the IC engine shall be registered or permitted. [District Rule 2010] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-13-4

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

CONFINED AND UNCONFINED ABRASIVE BLASTING OPERATION WITH A 800 POUND CLEMCO-MODEL L2463 BLASTING POT #4, VENTED TO A BLAST BOOTH (COMMON TO C-447-10 THRU C-447-14) WITH A PAULI MODEL #CT BAGHOUSE DURING CONFINED BLASTING, AND A CLEMCO MODEL AVS-50E ELECTRIC VACUUM

PERMIT UNIT REQUIREMENTS

1. All abrasive blasting shall be conducted within a permanent building unless steel or iron shot/grit is used exclusively, the item to be blasted exceeds 8 feet in any dimension, or the surface being blasted is situated at its permanent location or no further away from its permanent location than is necessary to allow the surface to be blasted. [92500 CCR]
2. Abrasive blasting operations conducted outside a permanent building which do not use steel or iron shot/grit exclusively shall use: wet abrasive blasting, hydroblasting, vacuum blasting, or abrasives certified by CARB for permissible dry outdoor blasting. [92500 CCR]
3. Abrasive blasting operations conducted outside a permanent building shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 2 or equivalent to 40% opacity. [92200 CCR]
4. Abrasive blasting operations conducted within the blast booth shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 1 or equivalent to 20% opacity. [92200 CCR]
5. A used certified abrasive shall not be considered certified for reuse unless the abrasive conforms to its original cut-point fineness. [92530 CCR]
6. All abrasive blasting shall be conducted in accordance with California Code of Regulations Title 17, Subchapter 6, Sections 92000 through 92540. [CCR]
7. When using an IC engine greater than 50 bhp to power an air compressor, the IC engine shall be registered or permitted. [District Rule 2010] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-14-4

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

CONFINED AND UNCONFINED ABRASIVE BLASTING OPERATION WITH A 500 POUND CLEMCO-BLASTING POT #5, VENTED TO A BLAST BOOTH (COMMON TO C-447-10 THRU C-447 14) WITH A PAULI MODEL #CT BAGHOUSE DURING CONFINED BLASTING, AND A CLEMCO MODEL AVS-50E ELECTRIC VACUUM

PERMIT UNIT REQUIREMENTS

1. All abrasive blasting shall be conducted within a permanent building unless steel or iron shot/grit is used exclusively, the item to be blasted exceeds 8 feet in any dimension, or the surface being blasted is situated at its permanent location or no further away from its permanent location than is necessary to allow the surface to be blasted. [92500 CCR]
2. Abrasive blasting operations conducted outside a permanent building which do not use steel or iron shot/grit exclusively shall use: wet abrasive blasting, hydroblasting, vacuum blasting, or abrasives certified by CARB for permissible dry outdoor blasting. [92500 CCR]
3. Abrasive blasting operations conducted outside a permanent building shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 2 or equivalent to 40% opacity. [92200 CCR]
4. Abrasive blasting operations conducted within the blast booth shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 1 or equivalent to 20% opacity. [92200 CCR]
5. A used certified abrasive shall not be considered certified for reuse unless the abrasive conforms to its original cut-point fineness. [92530 CCR]
6. All abrasive blasting shall be conducted in accordance with California Code of Regulations Title 17, Subchapter 6, Sections 92000 through 92540. [CCR]
7. When using an IC engine greater than 50 bhp to power an air compressor, the IC engine shall be registered or permitted. [District Rule 2010] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-16-4

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

METAL PARTS AND PRODUCTS COATING OPERATION WITH HVLP SPRAY GUN(S), PAINT BOOTH WITH DRY EXHAUST FILTERS AND SPRAY GUN CLEANER

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Exhaust fans shall be switched on prior to the start of paint spraying operations. [District Rule 2201] Federally Enforceable Through Title V Permit
3. All filters shall be properly maintained and must be in place during the painting operation. [District Rule 2201] Federally Enforceable Through Title V Permit
4. All coating operations shall be conducted inside the paint spray booth. [District Rule 2201] Federally Enforceable Through Title V Permit
5. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
6. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 360 g/l (3.0 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 360 g/l (3.0 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 360 g/l (3.0 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
7. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 420 g/l (3.5 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
8. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush or continuous coating application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. If an HVLP spray gun is used, the operator must demonstrate that the spray gun operates between 0.1 and 10 pounds per square inch, gauge, (psig) air atomizing pressure, measured dynamically at the center of the air cap and at the air horns. For a gun permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall either be in the form of manufacturer's published technical information or by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. For a gun not permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall be based on manufacturer's published technical material and by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. [District Rule 4603] Federally Enforceable Through Title V Permit
10. An operator of a metal parts products coating operation shall minimize VOC emissions by complying with the following work practice standards: store all VOC-containing coatings, thinners, cleaning materials, and waste materials in closed non-absorbent and non-leaking containers, keeping the containers closed except when specifically in use; close mixing vessels that contain VOC coatings and other materials, except when specifically in use; minimize spill of any VOC-containing materials and clean up spills immediately; and convey VOC-containing materials in closed containers or pipes. [District Rule 4603] Federally Enforceable Through Title V Permit
11. An operator shall store or dispose of fresh or spent, solvents, waste solvent cleaning materials such as cloth, paper, etc, coatings, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers, keeping the containers closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rule 4603] Federally Enforceable Through Title V Permit
12. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
13. Daily emissions from the paint spray booth shall not exceed 73.5 lb-VOC/day or 16.8 lb-PM10/day. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Annual emissions from the paint spray booth shall not exceed 5.5 tons VOC/year or 1.3 tons PM10/year averaged over a rolling 12-month period. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
15. Each container or accompanying data sheet of any coating subject to this rule shall display; the maximum VOC content of the coating, as applied, and after any thinning as recommended by the manufacturer in grams of VOC per liter of coating (less water and exempt compounds), a statement of the manufacturer's recommendation regarding thinning of the coating, the name of the solvent, manufacturer's name, and the VOC content, and density of the solvent, as supplied. [District Rule 4603] Federally Enforceable Through Title V Permit
16. The permittee shall maintain a current list of coatings and solvents in use which contains all of the coating data necessary to evaluate compliance, including the following information: mix ratio of components used, VOC content and specific chemical constituents of coatings as applied, and VOC content and specific chemical constituents of solvents used for surface preparation and cleanup. [District Rule 4603] Federally Enforceable Through Title V Permit
17. Permittee shall maintain daily records which include the following information: volume coating/solvent mix ratio, VOC content (lb/gal or grams/liter) and, for dip coating operations, viscosity (cSt) of coating, volume of each coating used (gallons), and quantity of cleanup solvent used (gallons). [District Rule 4603] Federally Enforceable Through Title V Permit
18. On a monthly basis, the permittee shall calculate and record the annual VOC and PM10 emissions for the rolling 12-month period. The total emissions shall be calculated by summing the emissions from the previous 12 months. [District Rule 2520] Federally Enforceable Through Title V Permit
19. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rule 4603] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-17-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

200 HP CONFINED ABRASIVE BLASTING OPERATION WITH A 100 LB TRINCO BLASTING POT SERVED BY A TRINCO DUST COLLECTOR

PERMIT UNIT REQUIREMENTS

1. {4627} All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 4102]
2. {52} The blasting operations shall be carried out in a manner to prevent any nuisances. [District Rule 4102]
3. {1475} All abrasive blasting shall be conducted in accordance with California Code of Regulations Title 17, Subchapter 6, Sections 92000 through 92540. [92000 through 92540 CCR]
4. {1483} A used certified abrasive shall not be considered certified for reuse unless the abrasive conforms to its original cut-point fineness. [92530 CCR]
5. {1992} Abrasive blasting operations conducted within the blasting cabinet shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 1 or equivalent to 20% opacity. [92200 CCR]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-18-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

200 HP CONFINED ABRASIVE BLASTING OPERATION WITH A 100 LB CYCLONE BLASTING SYSTEMS BLASTING POT SERVED BY CYCLONE BLASTING SYSTEM DUST COLLECTOR

PERMIT UNIT REQUIREMENTS

1. {4627} All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 4102]
2. {52} The blasting operations shall be carried out in a manner to prevent any nuisances. [District Rule 4102]
3. {1475} All abrasive blasting shall be conducted in accordance with California Code of Regulations Title 17, Subchapter 6, Sections 92000 through 92540. [92000 through 92540 CCR]
4. {1483} A used certified abrasive shall not be considered certified for reuse unless the abrasive conforms to its original cut-point fineness. [92530 CCR]
5. {1992} Abrasive blasting operations conducted within the blasting cabinet shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 1 or equivalent to 20% opacity. [92200 CCR]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-19-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

200 HP UNCONFINED ABRASIVE BLASTING OPERATION WITH A 100 LB CLEMCO BLASTING POT #7

PERMIT UNIT REQUIREMENTS

1. {4627} All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 4102]
2. {52} The blasting operations shall be carried out in a manner to prevent any nuisances. [District Rule 4102]
3. {1475} All abrasive blasting shall be conducted in accordance with California Code of Regulations Title 17, Subchapter 6, Sections 92000 through 92540. [92000 through 92540 CCR]
4. {1483} A used certified abrasive shall not be considered certified for reuse unless the abrasive conforms to its original cut-point fineness. [92530 CCR]
5. {1482} Unconfined abrasive blasting operations shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 2 or equivalent to 40% opacity. [92200 CCR]
6. {1990} Abrasive blasting shall be conducted within a permanent building unless steel or iron shot/grit is used. [92500 CCR]
7. {1991} Abrasive blasting of items exceeding 8 feet in any dimension, or of a surface situated at its permanent location, or no further away from its permanent location than is necessary to allow the surface to be blasted, may be performed outside a permanent building only if one of the following is used: steel or iron shot/grit; abrasives certified by CARB for permissible dry outdoor blasting; wet abrasive blasting, hydroblasting; or vacuum blasting. [92500 CCR]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-20-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

200 HP UNCONFINED ABRASIVE BLASTING OPERATION WITH A 200 LB PAULE & GIFFIN BLASTING POT

PERMIT UNIT REQUIREMENTS

1. {4627} All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 4102]
2. {52} The blasting operations shall be carried out in a manner to prevent any nuisances. [District Rule 4102]
3. {1475} All abrasive blasting shall be conducted in accordance with California Code of Regulations Title 17, Subchapter 6, Sections 92000 through 92540. [92000 through 92540 CCR]
4. {1483} A used certified abrasive shall not be considered certified for reuse unless the abrasive conforms to its original cut-point fineness. [92530 CCR]
5. {1482} Unconfined abrasive blasting operations shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 2 or equivalent to 40% opacity. [92200 CCR]
6. {1990} Abrasive blasting shall be conducted within a permanent building unless steel or iron shot/grit is used. [92500 CCR]
7. {1991} Abrasive blasting of items exceeding 8 feet in any dimension, or of a surface situated at its permanent location, or no further away from its permanent location than is necessary to allow the surface to be blasted, may be performed outside a permanent building only if one of the following is used: steel or iron shot/grit; abrasives certified by CARB for permissible dry outdoor blasting; wet abrasive blasting, hydroblasting; or vacuum blasting. [92500 CCR]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-21-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

GASOLINE DISPENSING OPERATION WITH ONE 1,000 GALLON SUPERVAULT FL MODEL ABOVEGROUND STORAGE TANK SERVED BY TWO-POINT OPW EVR PHASE I VAPOR RECOVERY SYSTEM (VR-401-B), ONE FUELING POINT WITH ONE GASOLINE DISPENSING NOZZLE SERVED BY BALANCE PHASE II VAPOR RECOVERY SYSTEM (G-70-132-B), AND STANDING LOSS CONTROL (VR-301-D)

PERMIT UNIT REQUIREMENTS

1. The Phase I, Phase II, and Standing Loss Control Vapor recovery systems shall be maintained in accordance with the manufacturer specifications and the ARB Executive Orders specified in this permit, including applicable rules and regulations of the Division of Measurement Standards of the Department of Food and Agriculture, the Office of the State Fire Marshal of the Department of Forestry and Fire Protection, the Division of Occupational Safety and Health of the Department of Industrial Relations, and the Division of Water Quality of the State Water Resources Control Board that have been made conditions of the certification. [District Rules 4621 and 4622 and CH&SC 41950] Federally Enforceable Through Title V Permit
2. This gasoline storage and dispensing equipment shall not be used in retail sales, where gasoline dispensed by the unit is subject to payment of California sales tax on gasoline sales. [District Rule 4622] Federally Enforceable Through Title V Permit
3. The owner shall prohibit any person from topping off a motor vehicle fuel tank. [District Rule 4622] Federally Enforceable Through Title V Permit
4. The storage container(s) shall be maintained and operated such that they are leak-free. [District Rule 4621] Federally Enforceable Through Title V Permit
5. The Phase I and Phase II vapor recovery systems and gasoline dispensing equipment shall be maintained without leaks as determined in accordance with the test method specified in this permit. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
6. A leak is defined as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration of total organic compound greater than 10,000 ppmv, as methane, above background when measured in accordance with EPA Test Method 21. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
7. No gasoline delivery vessel shall be operated or be allowed to operate unless valid State of California decals are displayed on the cargo container, which attest to the vapor integrity of the container. [District Rule 4621] Federally Enforceable Through Title V Permit
8. No person shall operate any ARB certified Phase II vapor recovery system or any portion thereof that has a major defect or an equipment defect that is identified in any applicable ARB Executive Order until the following conditions have been met: 1) the defect has been repaired, replaced, or adjusted as necessary to correct the defect; 2) the District has been notified, and the District has reinspected the system or authorized the system for use (such authorization shall not include the authority to operate the equipment prior to the correction of the defective components); and 3) all major defects, after repair, are duly entered into the Operations and Maintenance (O&M) manual. [District Rule 4622] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. Upon identification of any major defects, the permittee shall tag "Out-of-Order" all dispensing equipment for which vapor recovery has been impaired. Tagged equipment shall be rendered inoperable and the tag(s) shall not be removed until the defective equipment has been repaired, replaced, or adjusted, as necessary. In the case of defects identified by the District, tagged equipment shall be rendered inoperable, and the tag shall not be removed until the District has been notified of the repairs, and the District has either reinspected the system or authorized the tagged equipment for use. [District Rule 4622] Federally Enforceable Through Title V Permit
10. The permittee shall implement a periodic maintenance inspection program for the certified Phase II vapor recovery system consistent with the requirements of this permit. The program shall be documented in an operation and maintenance (O&M) manual and shall at a minimum contain the following information: 1) copies of all vapor recovery performance tests; 2) all applicable ARB Executive Orders, Approval Letters, and District Permits; 3) the manufacturer's specifications and instructions for installation, operation, repair, and maintenance required pursuant to ARB Certification Procedure CP-201, and any additional instruction provided by the manufacturer; 4) system and/or component testing requirements, including test schedules and passing criteria for each of the standard tests required by this permit (the owner/operator may include any non-ARB required diagnostic and other tests as part of the testing requirements), and 5) additional O&M instructions, if any, that are designed to ensure compliance with the applicable rules, regulations, ARB Executive Orders, and District permit conditions, including replacement schedules for failure or wear prone components. [District Rule 4622] Federally Enforceable Through Title V Permit
11. The permittee shall conduct periodic maintenance inspections based on the greatest monthly throughput of gasoline dispensed by the facility in the previous year as follows: A) less than 2,500 gallons - one day per month; B) 2,500 to less than 25,000 gallons - one day per week; or C) 25,000 gallons or greater - five days per week. All inspections shall be documented within the O & M Manual. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
12. Periodic maintenance inspections of the Phase I vapor recovery system shall include, at a minimum, verification that 1) the fill caps and vapor caps are not missing, damaged, or loose; 2) the fill cap gasket and vapor cap gaskets are not missing or damaged; 3) the fill adapter and vapor adapter are securely attached to the risers; 4) where applicable, the spring-loaded submerged fill tube seals properly against the coaxial tubing; 5) the dry break (poppet-valve) is not missing or damaged; and 6) the submerged fill tube is not missing or damaged. [District Rule 4621] Federally Enforceable Through Title V Permit
13. Periodic maintenance inspections of the Phase II vapor recovery system shall include, at a minimum, verification that 1) the following nozzle components are in place and in good condition as specified in ARB Executive Order as applicable: faceplate/facecone, bellows, latching device spring, vapor check valve, spout (proper diameter/vapor collection holes), insertion interlock mechanism, automatic shut-off mechanism, and hold open latch (unless prohibited by law or the local fire control authority); 2) the hoses are not torn, flattened or crimped; 3) the vapor path of the coaxial hoses associated with bellows equipped nozzles does not contain more than 100 ml of liquid if applicable; and 4) the vapor processing unit is functioning properly, for operations that are required to have or possess such a unit. [District Rule 4622] Federally Enforceable Through Title V Permit
14. In the event of a separation due to a drive off, the permittee shall, unless otherwise specified in the applicable ARB Executive Order, conduct a visual inspection of the affected equipment and either 1) perform qualified repairs on any damaged components and conduct applicable re-verification tests pursuant to the requirements of this permit, or 2) replace the affected nozzles, coaxial hoses, breakaway couplings, and any other damaged components with new or certified rebuilt components that are ARB certified. The activities shall be documented in accordance with the requirements of this permit before placing the affected equipment back in service. [District Rule 4622] Federally Enforceable Through Title V Permit
15. The gasoline throughput for this permit unit shall not exceed 627,000 gallons in any one calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit
16. The permittee shall conduct all periodic vapor recovery system performance tests specified in this permit, no more than 30 days before or after the required compliance testing date, unless otherwise required under the applicable ARB Executive Order. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

17. The permittee shall perform and pass a Static Leak Test "Determination of Static Pressure Performance of Vapor Recovery Systems at Gasoline Dispensing Facilities with Aboveground Tanks" in accordance with the Executive Order specified in this permit for the Phase I Vapor Recovery System at least once every 12 months. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
18. If a rotatable Phase I vapor adaptor is installed, the permittee shall perform and pass a Static Torque of Rotatable Phase I Adaptors test using ARB procedure TP-201.1B at least once every 36 months. [District Rule 4621] Federally Enforceable Through Title V Permit
19. For certified Phase II vapor recovery systems with liquid removal devices, the permittee shall perform and pass an ARB TP-201.6C Liquid Removal Test whenever the liquid in the vapor path exceeds 100 ml of liquid, or as required by the applicable ARB Executive Order. The amount of liquid in the vapor path shall be measured by lowering the gasoline dispensing nozzle into a container until such time that no more liquid drains from the nozzle. The amount of liquid drained into the container shall be measured using a graduated cylinder or graduated beaker. The vapor path shall be inspected according to the monitoring frequency as determined by monthly gasoline throughput. [District Rule 4622] Federally Enforceable Through Title V Permit
20. A person conducting testing of, or repairs to, a certified vapor recovery system shall be in compliance with District Rule 1177 (Gasoline Dispensing Facility Tester Certification). [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
21. A person performing installation of, or maintenance on, a certified Phase I or Phase II vapor recovery system shall be certified by the ICC for Vapor Recovery System Installation and Repair, or work under the direct and personal supervision of an individual physically present at the work site who is certified. The ICC certification shall be renewed every 24 months. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
22. Proof of the ICC certification and all other certifications required by the Executive Order and installation and operation manual shall be made available onsite. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
23. The permittee shall notify the District at least 7 days prior to each performance test. The test results shall be submitted to the District no later than 30 days after the completion of each test. [District Rule 4621] Federally Enforceable Through Title V Permit
24. The permittee shall maintain a copy of all test results. The test results shall be dated and shall contain the name, address, and telephone number of the company responsible for system installation and testing. [District Rule 4622] Federally Enforceable Through Title V Permit
25. The permittee shall maintain on the premises a log of any repairs made to the certified Phase I or Phase II vapor recovery system. The repair log shall include the following: 1) date and time of each repair; 2) the name and applicable certification numbers of the person(s) who performed the repair, and if applicable, the name, address and phone number of the person's employer; 3) description of service performed; 4) each component that was repaired, serviced, or removed; 5) each component that was installed as replacement, if applicable; and 6) receipts or other documents for parts used in the repair and, if applicable, work orders which shall include the name and signature of the person responsible for performing the repairs. [District Rule 4622] Federally Enforceable Through Title V Permit
26. The O&M manual shall be kept at the dispensing operation and made available to any person who operates, inspects, maintains, repairs, or tests the equipment at the operation as well as to District personnel upon request. [District Rule 4622] Federally Enforceable Through Title V Permit
27. Only white paint, listed in the Executive Order specified in this permit for the Standing Loss Control System, shall be applied to the tank. The surface of the tank shall be prepared and the white paint shall be applied per manufacturer's specification. [District Rule 4621] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

28. The permittee shall maintain the following records: 1) receipt of sale that demonstrates the purchase date and amount of white paint purchased, 2) record of the name of personnel applying white paint to include the date of application, surface preparation description (i.e. scraping, sanding, abrasive blasting, primer etc.), method of application (i.e. brush, roller, air/airless sprayer), average ambient temperature (°F) during application, and atmospheric observations during application (i.e. sunny, cloudy, rain, etc.), 3) record of the name of personnel that installed the P/V vent valve, and 4) Technical Data Sheet and/or Material Safety Data Sheet of the white paint that describes the surface preparation, application, and material safety of the white paint. [District Rule 4621] Federally Enforceable Through Title V Permit
29. The permittee shall maintain monthly and annual gasoline throughput records. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
30. All records required by this permit shall be retained on-site for a period of at least five years and shall be made available for District inspection upon request. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-23-7

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

TRANSPORTABLE 138 BHP DEUTZ MODEL TCD 2012L04 2V SERIAL NO. 10603992 TIER 3 CERTIFIED DIESEL-FIRED IC ENGINE POWERING A 100 TON/HOUR POWERSCREEN MODEL TROMMEL 830 ROTARY SCREEN

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Visible emissions from the screen shall not exceed 5% opacity for a period or periods aggregating more than three minutes in any one hour. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
4. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
5. This engine shall be equipped with an operational nonresettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
6. Engine operations shall not exceed 18 hours/day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Operation of this engine, calculated on a rolling 12-month basis, shall not exceed 1,000 hours per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
8. This transportable nonroad engine shall not be operated at one location for more than 12 consecutive months and shall meet all the requirements of a transportable nonroad engine, per CFR Title 40 Part 89. [17 CCR 93116]
9. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801 and 17 CCR 93116] Federally Enforceable Through Title V Permit
10. Emissions from the IC engine shall not exceed any of the following limits: 2.72 g-NOx/bhp-hr, 0.67 g-CO/bhp-hr, or 0.19 g-VOC/bhp-hr. [District Rules 2201 and 4702] Federally Enforceable Through Title V Permit
11. Emissions from the IC engine shall not exceed 0.05 g-PM10/bhp-hr based on USEPA certification using ISO 8178 test procedure. [District Rules 2201 and 4702 and 17 CCR 93116] Federally Enforceable Through Title V Permit
12. PM10 emissions from the Trommel screen shall not exceed 0.0022 lb/ton. [District Rule 2201] Federally Enforceable Through Title V Permit
13. During periods of operation, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
14. The owner/operator shall maintain an engine operating log to demonstrate compliance. The engine operating log shall include, on a monthly basis, the following information: total hours of operation, type of fuel used, maintenance or modifications performed, monitoring data, and any other information necessary to demonstrate compliance. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

15. The permittee shall maintain records of daily and annual, calculated on a rolling 12-month basis, hours of operation. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
16. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-27-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

105,179 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 12 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-28-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

105,043 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 13 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-29-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

105,306 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 14 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-30-4

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

54,680 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION; AND WINE, SPIRITS, HIGH PROOF SPIRITS/ALCOHOL, OR BRANDY STORAGE TANK 509 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-31-4

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

54,668 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION; AND WINE, SPIRITS, HIGH PROOF SPIRITS/ALCOHOL, OR BRANDY STORAGE TANK 510 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-32-4

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

54,672 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION; AND WINE, SPIRITS, HIGH PROOF SPIRITS/ALCOHOL, OR BRANDY STORAGE TANK 511 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-33-4

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

54,668 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION; AND WINE, SPIRITS, HIGH PROOF SPIRITS/ALCOHOL, OR BRANDY STORAGE TANK 512 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-34-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

102,087 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1001 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-35-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

101,870 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1002 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-36-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

102,253 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1003 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-37-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

102,253 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1004 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-38-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

102,175 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1005 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-39-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

102,235 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1006 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-40-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

102,211 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1007 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-41-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

102,968 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1008 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-42-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

102,262 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1009 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-43-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

103,122 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1010 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-44-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

103,146 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1011 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-45-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

103,080 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1012 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-46-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

105,264 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1501 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-47-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

105,259 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1502 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-48-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

105,284 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1503 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-49-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

105,100 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1504 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-50-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

105,215 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1505 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-51-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

105,011 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1506 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-52-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

105,287 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1507 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-53-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

105,054 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1508 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-54-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

105,194 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1509 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-55-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

105,021 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1510 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-56-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

212,026 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2001 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-57-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

212,468 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2002 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-58-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

212,151 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2003 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-59-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

212,120 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2004 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-60-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,917 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2005 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-61-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

212,275 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2006 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-62-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,691 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2007 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-63-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

212,254 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2008 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-64-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

212,766 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2009 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-65-4

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

214,253 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION; AND WINE, SPIRITS, HIGH PROOF SPIRITS/ALCOHOL, OR BRANDY STORAGE TANK 2010 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-66-4

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

213,963 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION; AND WINE, SPIRITS, HIGH PROOF SPIRITS/ALCOHOL, OR BRANDY STORAGE TANK 2011 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-67-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

214,245 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2012 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-68-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

214,528 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2013 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-69-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

214,325 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2014 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-70-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

214,301 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2015 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-71-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

214,236 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2016 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-72-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

213,126 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2501 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-73-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

213,596 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2502 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-74-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

213,687 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2503 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-75-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

213,298 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2504 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-76-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

213,018 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2505 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-77-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

213,471 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2506 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-78-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

213,296 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2507 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-79-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

213,411 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2508 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-80-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,766 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2509 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-81-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,311 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2510 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-82-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,316 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2511 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-83-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,260 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2512 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-84-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,748 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2513 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-85-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,712 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2514 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-86-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,422 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2515 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-87-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,573 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2516 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-88-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,633 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2517 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-89-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,487 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2518 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-90-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,378 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2519 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-91-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,658 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2520 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-92-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,732 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2521 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-93-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,788 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2522 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-94-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,189 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2523 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-95-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,962 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2524 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-96-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

207,390 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2922

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-97-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

207,909 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2923

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-98-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

207,676 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2924

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-99-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

208,185 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2925

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-100-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

207,571 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2926

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-101-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

208,168 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2927

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-102-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

207,821 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2928

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-103-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

207,140 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2929

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-104-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

206,695 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2930

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-105-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

207,451 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2931

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-106-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

206,832 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2932

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-107-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

207,270 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2933

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-108-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

208,117 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2934

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-109-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

208,202 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2935

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-110-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

206,996 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2936

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-111-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

207,039 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2937

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-112-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

206,757 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2938

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-113-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

207,752 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2939

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-114-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

207,369 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2940

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-115-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

208,795 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2941

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-116-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

208,928 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2942

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-117-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

329,824 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3013 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-118-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

329,868 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3014 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-119-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,674 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6013 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-120-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,066 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6014 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-121-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,494 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6015 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-122-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,303 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6016 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-123-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,934 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6017 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-124-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,604 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6018 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-125-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,738 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6019 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-126-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,964 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6020 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-127-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,070 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6021 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-128-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,248 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6022 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-129-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,965 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6023 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-130-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,756 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6024 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-131-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,656 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6025 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-132-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

640,805 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6026 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-133-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,489 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6027 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-134-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,896 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6028 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-135-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,208 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6029 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-136-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,378 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6030 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-137-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,676 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6031 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-138-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,762 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6032 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-139-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,796 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6033 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-140-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

644,594 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6034 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-141-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,126 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6035 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-142-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,874 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6036 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-143-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,803 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6037 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-144-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,307 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6038 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-145-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,509 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6039 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-146-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,199 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6040 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-147-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

644,851 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6041 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-148-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,555 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6042 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-149-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,690 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6043 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-150-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,940 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6044 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-151-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

644,141 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6045 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-152-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,365 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6046 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-153-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,506 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6047 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-154-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,192 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6048 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-155-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,544 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6049 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-156-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,863 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6050 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-157-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

645,153 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6051 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-158-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,894 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6052 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-159-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,374 GALLON STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6053 WITH
PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-160-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,400 GALLON STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6054 WITH
PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-161-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,257 GALLON STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6055 WITH
PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-162-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,277 GALLON STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6056 WITH
PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-163-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,867 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6501 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-164-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,338 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6502 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-165-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,222 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6503 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-166-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,763 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6504 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-167-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,501 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6505 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-168-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,658 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6506 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-169-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,620 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6507 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-170-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,526 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6508 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-171-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,178 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6509 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-172-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,090 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6510 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-173-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,542 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6511 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-174-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,788 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6512 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-175-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

640,725 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6513 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-176-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,118 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6514 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-177-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

640,772 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6515 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-178-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,295 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6516 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-179-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,491 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6517 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-180-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,051 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6518 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-181-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,451 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6519 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-182-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,094 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6520 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-183-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,344 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6521 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-184-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,245 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6522 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-185-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,156 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6523 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-186-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,595 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6524 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-187-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,871 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6526 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-188-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

639,880 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6527 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-189-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,428 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6528 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-190-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,193 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6529 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-191-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,592 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6601 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-192-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,295 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6602 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-193-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

640,961 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6603 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-194-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

640,434 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6604 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-195-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,594 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6609 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-196-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,115 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6610 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-197-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,345 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6611 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-198-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,629 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6612 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-199-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

640,936 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6617 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-200-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,121 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6618 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-201-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,720 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6619 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-202-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,051 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6620 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-203-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

640,612 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6625 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-204-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,491 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6626 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-205-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,974 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6627 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-206-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,792 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6628 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-207-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

640,729 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6633 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-208-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,378 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6634 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-209-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,008 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6641 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-210-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

639,975 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6642 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-211-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

640,530 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6649 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-212-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

640,872 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6650 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-213-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,462 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6657 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-214-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,263 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6658 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-215-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

650,472 GALLON STEEL WINE AND DISTILLED SPIRITS STORAGE TANK 6002 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-216-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

670,445 GALLON STEEL WINE AND DISTILLED SPIRITS STORAGE TANK 6005 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-217-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

661,423 GALLON STEEL WINE AND DISTILLED SPIRITS STORAGE TANK 6006 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-218-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

661,075 GALLON STEEL WINE AND DISTILLED SPIRITS STORAGE TANK 6007 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-219-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

669,320 GALLON STEEL WINE AND DISTILLED SPIRITS STORAGE TANK 6008 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-220-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

661,577 GALLON STEEL WINE AND DISTILLED SPIRITS STORAGE TANK 6009 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-221-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

661,634 GALLON STEEL WINE AND DISTILLED SPIRITS STORAGE TANK 6010 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-222-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

662,596 GALLON STEEL WINE AND DISTILLED SPIRITS STORAGE TANK 6011 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-223-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

669,445 GALLON STEEL WINE AND DISTILLED SPIRITS STORAGE TANK 6012 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-224-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

639,424 GALLON STEEL INSULATED WINE STORAGE TANK #6629 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-225-5

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

WINERY WASTEWATER PRETREATMENT AND EQUALIZATION OPERATION SERVED BY A SIEMENS ZABOCS BIOFILTER SHARED WITH C-447-226 AND -227

PERMIT UNIT REQUIREMENTS

1. The pre-acidification tank shall be enclosed and vented to the biofilter. [District Rules 2201 and 4102] Federally Enforceable Through Title V Permit
2. The recycle tank shall be enclosed and vented to the biofilter and/or sulfide oxidation tank. [District Rules 2201 and 4102] Federally Enforceable Through Title V Permit
3. The concentration of H₂S in the exhaust from the biofilter shall not exceed 5 ppmv. [District Rules 2201 and 4102] Federally Enforceable Through Title V Permit
4. Permittee shall follow the manufacturer's recommended monitoring and maintenance program for the biofilter. [District Rules 2201 and 4102] Federally Enforceable Through Title V Permit
5. Permittee shall maintain monthly records of the inlet and outlet exhaust H₂S concentration. The records shall be retained, maintained on-site for at least five years and made available for District inspection upon request. [District Rule 1070]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-226-13

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

175,320 GALLON WINERY WASTEWATER ANAEROBIC REACTOR SERVED BY A BIOGAS SCRUBBING SYSTEM SHARED WITH C-447-227 AND VENTED TO AN ENCLOSED 39.4 MMBTU/HR VAREC 244EGF FLARE OR BOILERS C-447-1, '2, '3, '295, OR '329, AND 502,000 GALLON WINERY WASTEWATER SULFIDE OXIDATION TANK

PERMIT UNIT REQUIREMENTS

1. The primary chamber of the anaerobic reactor shall be enclosed and vented to the biofilter listed on C-447-225. [District Rule 4102]
2. Oxygen content of the effluent in the sulfide oxidation tank shall be maintained at a level sufficient to prevent nuisance odors. [District Rule 4102]
3. Emission rates from the flare shall not exceed any of the following limits: NO_x (as NO₂) - 0.06 lb/MMBtu; VOC (as methane) - 0.002 lb/MMBtu; CO - 0.3 lb/MMBtu; or PM₁₀ - 0.008 lb/MMBtu. [District Rules 2201 and 4311] Federally Enforceable Through Title V Permit
4. The H₂S scrubber shall be in operation whenever biogas is produced in the anaerobic reactors. [District Rule 2201] Federally Enforceable Through Title V Permit
5. H₂S content of the scrubbed biogas shall not exceed 50 ppmv. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Biogas flow rate to the flare shall not exceed 481,900 scf per day. [District Rules 2201 and 4311] Federally Enforceable Through Title V Permit
7. Biogas production shall not exceed any of the following: 1st quarter - 31,670,000 scf, 2nd quarter - 31,800,300 scf, 3rd quarter - 83,115,800 scf, 4th quarter 83,115,800 scf. [District Rule 2201] Federally Enforceable Through Title V Permit
8. A flame shall be present in the flare at all times when combustible gases are vented through the flare. [District Rule 4311] Federally Enforceable Through Title V Permit
9. The outlet shall be equipped with an automatic ignition system, or, shall be operated with a pilot flame present at all times when combustible gases are vented through the flare, except during purge periods for automatic-ignition equipped flares. [District Rule 4311] Federally Enforceable Through Title V Permit
10. Except for flares equipped with a flow-sensing ignition system, a heat sensing device such as a thermocouple, ultraviolet beam sensor, infrared sensor, or an equivalent device capable of continuously detecting at least one pilot flame or the flare flame is present shall be installed and operated. The flame detection device shall be kept operational at all times except during flare maintenance when the flare is isolated from gas flow. During essential planned power outages when the flare is operating, the pilot monitor is allowed to be non-functional if the flare flame is clearly visible to onsite operators. All pilot monitor downtime shall be reported annually pursuant to Rule 4311, Section 6.2.3.6. [District Rule 4311] Federally Enforceable Through Title V Permit
11. Flaring is prohibited unless it is consistent with an approved flare minimization plan (FMP), pursuant to Section 6.5, and all commitments listed in that plan have been met. This standard does not apply if the APCO determines that the flaring is caused by an emergency as defined by Section 3.7 and is necessary to prevent an accident, hazard or release of vent gas directly to the atmosphere. [District Rule 4311] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. The operator shall monitor and record the vent gas flow to the flare with a flow measuring device or other parameters as specified in the Permit to Operate. [District Rule 4311] Federally Enforceable Through Title V Permit
13. Source testing to measure NO_x and VOC emissions from the flare shall be conducted at least once every twelve (12) months. [District Rule 4311] Federally Enforceable Through Title V Permit
14. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
15. The following test methods shall be used: VOC - EPA Method 25, except when the outlet concentration must be below 50 ppm to meet the standard, in which case Method 25a may be used; exempt compounds - EPA Method 18 or ARB Method 422; NO_x (lb/MMBtu) - EPA Method 19; NO_x and O₂ (concentrations) - EPA Method 3A, EPA Method 7E, or ARB 100. [District Rule 4311] Federally Enforceable Through Title V Permit
16. The results of each source test shall be submitted to the District within 45 days thereafter. [District Rules 1081 and 4311] Federally Enforceable Through Title V Permit
17. H₂S content of the exhaust from the biological reactor serving the scrubber shall not exceed 1 ppmv. [District Rule 2201] Federally Enforceable Through Title V Permit
18. Residual dissolved oxygen level in the sulfide oxidation tank shall not fall below 1 milligram per liter. [District Rules 2201 and 4102] Federally Enforceable Through Title V Permit
19. Permittee shall monitor the H₂S content of the biogas at the inlet and at the outlet of the scrubber on a weekly basis. If the outlet H₂S concentration does not exceed 50 ppmv for four consecutive weeks, monitoring may be conducted on a monthly basis. If the H₂S concentration at the outlet exceeds 50 ppmv, weekly monitoring shall resume. [District Rule 2201] Federally Enforceable Through Title V Permit
20. Permittee shall monitor the residual dissolved oxygen content of the sulfide oxidation tank at least on a weekly basis. If the residual dissolved oxygen content does not fall below 1 mg/liter for four consecutive weeks, monitoring may be conducted on a monthly basis. If the concentration falls below 1 mg/liter, weekly monitoring shall resume. [District Rules 2201 and 4102] Federally Enforceable Through Title V Permit
21. The residual dissolved oxygen content sensor for the sulfide oxidation tank shall be calibrated in accordance with the manufacturer's specifications. A copy of the user's manual or like document from the manufacturer shall be maintained onsite so that the District may verify calibration frequency and procedures. [District Rules 2201 and 4102] Federally Enforceable Through Title V Permit
22. If the residual dissolved oxygen content in the sulfide oxidation tank falls below 1 mg/liter, the permittee shall immediately correct the system. If concentration falls below 1 mg/liter for more than 10 consecutive minutes, the permittee shall notify the District within the following 1 hour. [District Rules 2201 and 4102] Federally Enforceable Through Title V Permit
23. The operator shall notify the APCO of an unplanned flaring event within 24 hours after the start of the next business day or within 24 hours of their discovery, whichever occurs first. The notification shall include the flare source identification, the start date and time, and the end date and time. [District Rule 4311] Federally Enforceable Through Title V Permit
24. The operator of a flare subject to flare minimization plans pursuant to Section 5.8 shall submit an annual report to the APCO that summarizes all Reportable Flaring Events as defined in Section 3.0 that occurred during the previous 12 month period. The report shall be submitted within 30 days following the end of the twelve month period of the previous year. The report shall include, but is not limited to all of the following: the results of an investigation to determine the primary cause and contributing factors of the flaring event; any prevention measures considered or implemented to prevent recurrence together with a justification for rejecting any measures that were considered but not implemented; if appropriate, an explanation of why the flaring was an emergency and necessary to prevent accident, hazard or release of vent gas to the atmosphere, or where, due to a regulatory mandate to vent a flare, it cannot be recovered, treated and used as a fuel gas at the facility; and the date, time, and duration of the flaring event. [District Rule 4311] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

25. The operator of a flare subject to flare monitoring requirements pursuant to Section 5.10 shall submit an annual report to the APCO within 30 days following the end of each 12 month period. The report shall include the following: the total volumetric flow of vent gas in standard cubic feet for each day; if the flow monitor used pursuant to Section 5.10 measures molecular weight, the average molecular weight for each hour of each month; a flow verification report which shall include flow verification testing pursuant to Section 6.3.5. [District Rule 4311] Federally Enforceable Through Title V Permit
26. For purposes of the flow verification report required by Section 6.2.3.8, vent gas flow shall be determined using one or more of the following methods, or by any alternative method approved by the APCO, ARB, and EPA: EPA Methods 1 and 2; a verification method recommended by the manufacturer of the flow monitoring equipment installed pursuant to Section 5.10; tracer gas dilution or velocity; other flow monitors or process monitors that can provide comparison data on a vent stream that is being directed past the ultrasonic flow meter. [District Rule 4311] Federally Enforceable Through Title V Permit
27. Every five years after the initial FMP submittal, the operator shall submit an updated FMP for each flare to the APCO for approval. The current FMP shall remain in effect until the updated FMP is approved by the APCO. If the operator fails to submit an updated FMP as required by this section, the existing FMP shall no longer be considered an approved plan. [District Rule 4311] Federally Enforceable Through Title V Permit
28. An updated FMP shall be submitted by the operator pursuant to Section 6.5 addressing new or modified equipment, prior to installing the equipment. Updated FMP submittals are only required if: (1) The equipment change would require an authority to construct (ATC) and would impact the emissions from the flare, and (2) The ATC is deemed complete after June 18, 2009, and (3) The modification is not solely the removal or decommissioning of equipment that is listed in the FMP, and has no associated increase in flare emissions. [District Rule 4311] Federally Enforceable Through Title V Permit
29. Permittee shall maintain the following records: a copy of the source testing result conducted pursuant to Section 6.4.2; a copy of the approved flare minimization plan pursuant to Section 6.5; a copy of annual reports submitted to the APCO pursuant to Section 6.2. [District Rule 4311] Federally Enforceable Through Title V Permit
30. Permittee shall maintain a log of the residual dissolved oxygen content sensor calibrations, which shall include the date and time of each calibration and any corrective actions. The records shall be retained, maintained on-site for at least five years, and made available for District inspection upon request. [District Rules 2201 and 4102] Federally Enforceable Through Title V Permit
31. Permittee shall maintain records of: (1) daily biogas production, (2) measured H₂S concentration in biogas, (3) date H₂S measurements taken from exhaust of biological reactor serving the scrubber, (4) measured concentration level of residual dissolved oxygen content taken from sulfide oxidation tank, and (5) date measurement of concentration level of residual dissolved oxygen content taken from sulfide oxidation tank. [District Rules 2201 and 4102] Federally Enforceable Through Title V Permit
32. All records shall be maintained and retained on-site for a minimum of five years, and shall be made available for District inspection upon request. [District Rules 2201 and 4311] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-227-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

502,100 GALLON WINERY WASTEWATER ANAEROBIC REACTOR SERVED BY A BIOGAS SCRUBBING SYSTEM
LISTED ON C-447-226

PERMIT UNIT REQUIREMENTS

1. The IC degassing tank of the anaerobic reactor shall be enclosed and vented to the biogas scrubber listed on C-447-226-0. [District Rule 4102]
2. The primary chamber of the anaerobic reactor shall be enclosed and vented to the biofilter listed on C-447-225-0. [District Rule 4102]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-230-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

AGRICULTURAL WASTE COMPOSTING OPERATION INCLUDING MORBARK, MODEL 3800, ELECTRICALLY POWERED HORIZONTAL GRINDER

PERMIT UNIT REQUIREMENTS

1. Maximum amount of material processed by this operation shall not exceed either of the following limits: 204 tons per day or 74,460 tons per year, calculated on a rolling 12-month basis. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Particulate matter (PM10) emissions shall not exceed 0.01 lb/ton of material processed. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The permittee shall maintain daily records of the amount of material processed, in tons. [District Rule 2201] Federally Enforceable Through Title V Permit
4. On a monthly basis, the permittee shall calculate and record the annual throughput for the rolling 12-month period. The annual throughput shall be calculated by summing the throughput from the previous 12 months. [District Rule 2520] Federally Enforceable Through Title V Permit
5. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-233-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

6,000 CUBIC FEET DIATOMACEOUS EARTH STORAGE SILO D SERVED BY A STACLEAN MODEL 9-3.2-BDS BIN VENT FILTER

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed the hourly rate as calculated in District Rule 4202 using the equation $E = 3.59 \times P^{0.62}$ if P is less than or equal to 30 tons per hour, or $E = 17.31 \times P^{0.16}$ if P is greater than 30 tons per hour. [District Rule 4202] Federally Enforceable Through Title V Permit
3. Visible emissions from the bin vent filter serving the storage silo shall not equal or exceed 5% opacity for a period or periods aggregating more than three minutes in one hour. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Visible emissions shall be inspected annually during operation. If visible emissions are observed, corrective action shall be taken to eliminate visible emissions. If visible emissions cannot be corrected within 24 hours, a visible emissions test using EPA Method 9 shall be conducted. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The bin vent filter shall be equipped with a pressure differential gauge to indicate the pressure drop across the filters. The gauge shall be maintained in good working condition at all times and shall be located in an easily accessible location. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The bin vent filter shall operate at all times with a minimum differential pressure of 2.5 inches water column and a maximum differential pressure of 6 inches water column. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Differential operating pressure shall be monitored and recorded on each day that the bin vent filter is in operation. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The bin vent filter shall be maintained and operated according to manufacturer's specifications. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The bin vent filter cleaning frequency and duration shall be adjusted to optimize the control efficiency. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Material removed from the bin vent filter shall be disposed of in a manner preventing entrainment into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
12. A spare set of bags shall be maintained on the premises at all times. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

13. PM10 emissions rate from the storage operation shall not exceed 0.00085 lb/ton of diatomaceous earth loaded into the silo. [District Rule 2201] Federally Enforceable Through Title V Permit
14. The maximum daily throughput of diatomaceous earth loaded into the silo shall not exceed 25 tons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The maximum annual throughput of diatomaceous earth loaded into the silo shall not exceed 2,500 tons, calculated on a rolling 12-month basis. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
16. Dust collection system shall be completely inspected annually while in operation for evidence of particulate matter leaks and repaired as needed. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. Permittee shall maintain records of the daily and calculated rolling 12-month annual quantity (in tons) of diatomaceous earth loaded into the silo. [District Rules 1070, 2201, and 2520] Federally Enforceable Through Title V Permit
18. Records of all maintenance of the bin vent filter, including all change outs of bags or filter media, shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit
19. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rules 1070 and 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-234-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

328,225 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3001 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-235-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

327,544 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3002 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-236-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

328,017 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3003 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-237-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

329,088 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3004 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-238-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

333,405 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3005 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-239-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

336,009 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3006 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-240-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

328,067 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3007 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-241-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

326,941 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3008 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-242-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

328,765 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3009 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-243-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

330,054 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3010 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-244-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

333,641 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3011 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-245-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

333,181 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3012 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-255-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

2,027 GALLON STEEL DISTILLED SPIRITS STORAGE TANK D1 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-256-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

52,788 GALLON STEEL DISTILLED SPIRITS STORAGE TANK P3 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-257-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

16,726 GALLON STEEL DISTILLED SPIRITS STORAGE TANK P4 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-258-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

16,754 GALLON STEEL DISTILLED SPIRITS STORAGE TANK P5 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-259-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

16,711 GALLON STEEL DISTILLED SPIRITS STORAGE TANK P6 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-260-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

16,725 GALLON STEEL DISTILLED SPIRITS STORAGE TANK P7 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-261-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

4,562 GALLON STEEL DISTILLED SPIRITS STORAGE TANK P8 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-262-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

5,333 GALLON STEEL DISTILLED SPIRITS STORAGE TANK P9 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-263-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

49,915 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 501 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-264-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

49,964 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 502 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-265-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

50,146 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 503 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-266-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

50,059 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 504 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-267-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

160 BHP ELECTRONICALLY REGULATED TO 130 BHP CUMMINS MODEL CFP5E-F30 TIER 3 CERTIFIED DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIREWATER PUMP

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. {1898} The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
3. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702 and 17 CCR 93115 and 40 CFR Subpart IIII] Federally Enforceable Through Title V Permit
4. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801, 17 CCR 93115, 40 CFR Part 60 Subpart IIII] Federally Enforceable Through Title V Permit
5. Emissions from this IC engine shall not exceed any of the following limits: 2.70 g-NOx/bhp-hr, 0.67 g-CO/bhp-hr, or 0.14 g-VOC/bhp-hr. [District Rule 2201, 17 CCR 93115, and 40 CFR Part 60 Subpart IIII] Federally Enforceable Through Title V Permit
6. Emissions from this IC engine shall not exceed 0.10 g-PM10/bhp-hr based on USEPA certification using ISO 8178 test procedure. [District Rule 2201, 17 CCR 93115, and 40 CFR Part 60 Subpart IIII] Federally Enforceable Through Title V Permit
7. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702 and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
8. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
9. An emergency situation is an unscheduled event caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
10. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. For testing purposes, the engine shall only be operated the number of hours necessary to comply with the testing requirements of the National Fire Protection Association (NFPA) 25 - "Standard for the Inspection, Testing, and Maintenance of Water-Based Fire Protection Systems", 1998 edition. Total hours of operation for all maintenance, testing, and required regulatory purposes shall not exceed 100 hours in any rolling 12-month period. [District Rules 2520 and 4702, 17 CCR 93115 and 40 CFR Part 60 Subpart IIII] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, and the purpose of the operation (for example: load testing, weekly testing, emergency fire fighting, etc.). For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
12. On a monthly basis, the permittee shall calculate and record the hours of operation for the rolling 12-month period. The hours of operation shall be calculated by summing the hours of operation from the previous 12 months. [District Rule 2520] Federally Enforceable Through Title V Permit
13. The permittee shall maintain monthly records of the type of fuel purchased. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
14. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-268-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

GREEN WASTE ORGANIC MATERIAL RECEIVING, STORAGE, AND MIXING OPERATION

PERMIT UNIT REQUIREMENTS

1. This permit does not authorize the facility to operate without the required permits from other local, state or federal agency and does not authorize the violation of any conditions established for this facility in the Conditional Use Permit (CUP), Special Use Permit (SUP), Site Approval, Site Plan Review (SPR), or other approval documents issued by a local, state or federal agency. [District Rules 2070 and 2080, and Public Resources Code 21000-21177: California Environmental Quality Act] Federally Enforceable Through Title V Permit
2. All materials for processing shall be maintained adequately moist to prevent visible emissions in excess of 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
3. The permittee is allowed to receive the following wastes for the composting operation: green waste, residential food waste, and construction wood waste. Green waste is defined as any organic waste material generated from gardening, agriculture, or landscaping activities including, but not limited to grass clippings, leave, tree and shrub trimmings, and plant remains. Residential food waste is defined as table scraps, vegetable and fruit peelings, meat, bones and fish, egg shells, solid dairy products, coffee grounds, bread and toast, paper waste including, but not limited to, napkins, towels, plates, coffee filters, and tea bags. Construction wood waste is defined as any untreated wood materials, including but not limited to, lumber, paper, and cardboard from construction. [District Rule 2010] Federally Enforceable Through Title V Permit
4. The permittee is prohibited to receive the following wastes for the composting operation: biosolids, animal manure, and poultry litter. Biosolids is defined as organic material resulting from the treatment of sewage sludge or wastewater. Animal manure is defines as non-human animal excretions and waste, including, but not limited to, dried solids and urine from cows, cattle, or swine. Poultry litter is defined as poultry excretions and waste, including, but not limited to dried solids and urine from chickens, turkeys, geese, or ducks. [District Rule 2010] Federally Enforceable Through Title V Permit
5. The quantity of organic material received shall not exceed either of the following limits: 1,325 wet tons/day or 146,853 wet ton/year (equivalent to 378,000 cubic yards/year), calculated on a rolling 12-month basis. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The quantity of organic material stockpiled at this facility for composting shall be less than 100,000 wet tons/year, calculated on a rolling 12-month basis. [District Rules 2201, 2520, and 4566] Federally Enforceable Through Title V Permit
7. Emissions from organic material stockpiling shall not exceed either of the following limits: 1.063 lb-VOC/wet ton/day or 0.318 lb-NH3/wet ton/day. [District Rule 2201] Federally Enforceable Through Title V Permit
8. PM10 emissions from the receiving, handling, and mixing of the organic waste materials shall not exceed 0.00165 lb-PM10/wet ton. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-268-2 : May 19 2017 9:02AM -- BROWND

9. Within 10 days of receipt of the organic material to be composted, the permittee shall perform one of the following: (a). Remove the organic material from the facility; (b). Place the organic material in the active-phase composting windrow and start active phase composting; (c). Cover the organic material with a waterproof cover that have at least a six-feet overlap of adjacent sheets and be securely anchored. [District Rules 2201 and 4566] Federally Enforceable Through Title V Permit
10. A daily operations log shall be maintained and shall include the following: (a) The date, type, and weight (in wet tons) of each organic material received; (b). The date each stockpile was initially formed; (c). The date and action taken on each stockpile to satisfy the stockpile requirements; (d). Total quantity and type of each organic waste material stored for composting (in wet tons); (e). Total quantity and type of each organic waste material mixed for composting (in wet tons); and (f). Any other information necessary to demonstrate compliance with Rule 4566. [District Rules 2201 and 4566] Federally Enforceable Through Title V Permit
11. A cumulative annual log shall be maintained and shall indicate the total quantity and type of each organic waste material received (in wet tons). The records shall be calculated on a rolling 12-month basis and shall be updated at least monthly. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
12. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rules 2201 and 4566] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-269-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

OPEN WINDROW ACTIVE AND CURING PHASE GREEN WASTE COMPOSTING OPERATION WITH AN INTEGRATED WATERING SYSTEM

PERMIT UNIT REQUIREMENTS

1. This permit does not authorize the facility to operate without the required permits from other local, state or federal agency and does not authorize the violation of any conditions established for this facility in the Conditional Use Permit (CUP), Special Use Permit (SUP), Site Approval, Site Plan Review (SPR), or other approval documents issued by a local, state, or federal agency. [District Rules 2070 and 2080, and Public Resources Code 21000-21177: California Environmental Quality Act] Federally Enforceable Through Title V Permit
2. All materials for processing shall be maintained adequately moist to prevent visible emissions in excess of 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
3. PM10 emissions from the organic material composting operation shall not exceed 0.00066 lb-PM10/wet ton. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The total quantity of organic materials composted shall be less than 100,000 wet tons/year, calculated on a rolling 12-month basis. [District Rules 2201, 2520, and 4566] Federally Enforceable Through Title V Permit
5. VOC emissions from the organic material composting operation shall not exceed either of the following limits: 8,808.6 lb/day or 473,335 lb/year, calculated on a rolling 12-month basis. [District Rules 2201 and 4566] Federally Enforceable Through Title V Permit
6. NH3 emissions from the organic material composting operation shall not exceed either of the following limits: 693.2 lb/day or 89,747 lb/year, calculated on a rolling 12-month basis. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall implement at least three turns of each organic material composting windrow during the active-phase of the composting process. [District Rule 4566] Federally Enforceable Through Title V Permit
8. The operator shall install, maintain, and utilize an integrated watering system to apply water to the surface of each active-phase composting windrow. For windrows that will be turned on the same day and will require the same water volume, mechanically turn the first windrow while operating the integrated watering system. Within three hours after turning the first windrow, the operator shall test the windrow for adequate water by taking a sample of the organic material in the windrow and passing a "Ball Test". The "Ball Test" is performed by taking a sample of the compostable material between the vertical midpoint and the peak of the windrow, at least three inches below the outer surface. There should be at least enough water to form a ball when compressed by hand, but the ball may break when tapped. If the ball crumbles during the hand pressure test, apply additional water and mechanically turn the same windrow, then retest until the material passes the ball test. Subsequent windrows shall not be turned until the initial windrow passes the ball test. Utilize the established water volume for the remaining windrows to be turned with the same water volume on the same day. Repeat this method for windrows that will be turned with a different water application rate. If a rain event occurs prior to turning the windrow, application of additional water to the surface of the windrow will not be required if the material passes the ball test as previously described. [District Rule 4566] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. A daily operations log shall be maintained and shall include the following: (a). The date and time the organic material from the windrow was tested for adequate water content using the "Ball Test" and indicate if the material passed the ball test. If the windrow material did not pass the ball test indicate the corrective action taken; (b). The date and time each windrow was turned; (c). Total quantity of organic material transferred from the feedstock piles to the active-phase composting windrows (in wet tons); (d). Total quantity of active phase composting piles utilized onsite (in wet tons); (e). Total quantity of curing phase composting piles utilized onsite (in wet tons); and (f). Any other information necessary to demonstrate compliance with Rule 4566. [District Rules 1070 and 4566] Federally Enforceable Through Title V Permit
10. A cumulative annual log shall be maintained and shall include the following: (a). Total quantity of active-phase composting piles utilized onsite (in wet tons); (b). Total quantity of curing phase composting piles utilized onsite (in wet tons). The records shall be calculated on a rolling 12-month basis and shall be updated at least monthly. [District Rules 1070, 2201, and 2520] Federally Enforceable Through Title V Permit
11. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rules 1070, 2201, and 4566] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-270-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

FINISHED COMPOST STORAGE AND LOADOUT OPERATION

PERMIT UNIT REQUIREMENTS

1. All materials for processing shall be maintained adequately moist to prevent visible emissions in excess of 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
2. No more than 174 vehicles per day shall be used to load out finished compost (based upon the Solid Waste Facility Permit, SWIS #: 10-AA-0182). [District Rule 2010] Federally Enforceable Through Title V Permit
3. A daily log shall be maintained and shall include the following: (a). Total quantity and type of each organic waste material received (in wet tons); (b). Total quantity and type of each organic waste material mixed for composting (in wet tons). [District Rule 1070] Federally Enforceable Through Title V Permit
4. A cumulative annual log shall be maintained and shall include the following: (a). Total quantity and type of each organic waste material received (in wet tons); (b). Total quantity and type of each organic waste material mixed for composting (in wet tons). The records shall be updated at least monthly. [District Rule 1070] Federally Enforceable Through Title V Permit
5. All bulk material transport vehicles shall limit Visible Dust Emissions to 20% opacity by either limiting vehicular speed, maintaining sufficient freeboard on the load, applying water to the top of the load, or covering the load with a tarp or other suitable cover. [District Rules 8011 and 8031] Federally Enforceable Through Title V Permit
6. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 or Rule 8011. [District Rule 8041] Federally Enforceable Through Title V Permit
7. Any open area having 3.0 acres or more of disturbed surface area, that has remained undeveloped, unoccupied, unused or vacant for more than seven days shall comply with the requirements of District Rule 8051 (Open Areas), unless specifically exempted under section 4.0. [District Rule 8051] Federally Enforceable Through Title V Permit
8. Any new or existing public or private paved or unpaved road, road construction project, or road modification project shall implement the control measures and design criteria of, and comply with the requirements of District Rule 8061 (Paved and Unpaved Roads), unless specifically exempted under section 4.0 of Rule 8061. [District Rule 8061] Federally Enforceable Through Title V Permit
9. Water, gravel, roadmix, or chemical/organic dust stabilizers/suppressants, vegetative materials, or other District-approved control measure shall be applied to unpaved vehicle travel areas as required to limit Visible Dust Emissions to 20% opacity and comply with the requirements for a stabilized unpaved road as defined in District Rule 8011. [District Rules 8011 and 8071] Federally Enforceable Through Title V Permit
10. On each day that 50 or more Vehicle Daily Trips or 25 or more Vehicle Daily Trips with 3 axles or more will occur on an unpaved vehicle/equipment traffic area, the permittee shall apply water, gravel, road mix, or chemical/organic dust stabilizers/suppressants, vegetative materials, or other District-approved control measure as required to limit Visible Dust Emissions to 20% opacity and comply with the requirements for a stabilized unpaved road as defined in District Rule 8011. [District Rules 8011 and 8071] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-270-1 : May 19 2017 9:02AM -- BROWN

11. Whenever any portion of the site becomes inactive, the permittee shall restrict access and periodically stabilize any disturbed surface to comply with the conditions for a stabilized surface as defined in District Rule 8011. [District Rules 8011 and 8071] Federally Enforceable Through Title V Permit
12. This permit does not authorize the facility to operate without the required permits from other local, state, or federal agency and does not authorize the violation of any conditions established for this facility in the Conditional Use Permit (CUP), Special Use Permit (SUP), Site Approval, Site Plan Review (SPR), or other approval documents issued by a local, state, or federal agency. [District Rules 2070 and 2080] Federally Enforceable Through Title V Permit
13. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-271-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

609,251 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6635) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,438,235 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a rolling 12-month basis, shall not exceed 3,299 pounds. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; the rolling 12-month wine ethanol content (percentage by volume) and the throughput rate (gallons) for storage operations, calculated monthly; and the rolling 12-month VOC emission rate for fermentation operations, calculated monthly. [District Rules 2201, 2520, and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-272-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

612,539 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6636) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,438,235 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-273-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

612,124 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6637) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,438,235 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a rolling 12-month basis, shall not exceed 3,299 pounds. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; the rolling 12-month wine ethanol content (percentage by volume) and the throughput rate (gallons) for storage operations, calculated monthly; and the rolling 12-month VOC emission rate for fermentation operations, calculated monthly. [District Rules 2201, 2520, and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-274-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

612,972 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6638) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a 12-month rolling basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,438,235 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a rolling 12-month basis, shall not exceed 3,299 pounds. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a rolling 12-month basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; the rolling 12-month wine ethanol content (percentage by volume) and the throughput rate (gallons) for storage operations, calculated monthly; and the rolling 12-month VOC emission rate for fermentation operations, calculated monthly. [District Rules 2201, 2520, and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-275-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

612,770 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6639) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,438,235 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a rolling 12-month basis, shall not exceed 3,299 pounds. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a rolling 12-month basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; the rolling 12-month wine ethanol content (percentage by volume) and the throughput rate (gallons) for storage operations, calculated monthly; and the rolling 12-month VOC emission rate for fermentation operations, calculated monthly. [District Rules 2201, 2520, and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-276-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

611,887 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6640) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,438,235 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a rolling 12-month basis, shall not exceed 3,299 pounds. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; the rolling 12-month wine ethanol content (percentage by volume) and the throughput rate (gallons) for storage operations, calculated monthly; and the rolling 12-month VOC emission rate for fermentation operations, calculated monthly. [District Rules 2201, 2520, and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-277-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

611,101 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6643) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,438,235 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a rolling 12-month basis, shall not exceed 3,299 pounds. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; the rolling 12-month wine ethanol content (percentage by volume) and the throughput rate (gallons) for storage operations, calculated monthly; and the rolling 12-month VOC emission rate for fermentation operations, calculated monthly. [District Rules 2201, 2520, and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-278-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

611,761 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6644) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,438,235 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-279-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

615,034 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6645) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,034 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,438,235 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a rolling 12-month basis, shall not exceed 3,299 pounds. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; the rolling 12-month wine ethanol content (percentage by volume) and the throughput rate (gallons) for storage operations, calculated monthly; and the rolling 12-month VOC emission rate for fermentation operations, calculated monthly. [District Rules 2201, 2520, and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-280-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

613,196 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6646) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,438,235 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a rolling 12-month basis, shall not exceed 3,299 pounds. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; the rolling 12-month wine ethanol content (percentage by volume) and the throughput rate (gallons) for storage operations, calculated monthly; and the rolling 12-month VOC emission rate for fermentation operations, calculated monthly. [District Rules 2201, 2520, and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-281-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

612,106 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6647) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,438,235 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a rolling 12-month basis, shall not exceed 3,299 pounds. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; the rolling 12-month wine ethanol content (percentage by volume) and the throughput rate (gallons) for storage operations, calculated monthly; and the rolling 12-month VOC emission rate for fermentation operations, calculated monthly. [District Rules 2201, 2520, and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-282-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

612,359 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6648) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,438,235 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a rolling 12-month basis, shall not exceed 3,299 pounds. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; the rolling 12-month wine ethanol content (percentage by volume) and the throughput rate (gallons) for storage operations, calculated monthly; and the rolling 12-month VOC emission rate for fermentation operations, calculated monthly. [District Rules 2201, 2520, and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-283-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

611,612 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6651) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,438,235 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a rolling 12-month basis, shall not exceed 3,299 pounds. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; the rolling 12-month wine ethanol content (percentage by volume) and the throughput rate (gallons) for storage operations, calculated monthly; and the rolling 12-month VOC emission rate for fermentation operations, calculated monthly. [District Rules 2201, 2520, and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-284-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

612,592 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6652) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,438,235 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-284-2 : May 19 2017 9:02AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-285-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

613,109 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6653) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,438,235 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a rolling 12-month basis, shall not exceed 3,299 pounds. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; the rolling 12-month wine ethanol content (percentage by volume) and the throughput rate (gallons) for storage operations, calculated monthly; and the rolling 12-month VOC emission rate for fermentation operations, calculated monthly. [District Rules 2201, 2520, and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-286-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

613,536 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6654) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,438,235 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a rolling 12-month basis, shall not exceed 3,299 pounds. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; the rolling 12-month wine ethanol content (percentage by volume) and the throughput rate (gallons) for storage operations, calculated monthly; and the rolling 12-month VOC emission rate for fermentation operations, calculated monthly. [District Rules 2201, 2520, and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-287-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

613,913 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6655) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,438,235 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a rolling 12-month basis, shall not exceed 3,299 pounds. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; the rolling 12-month wine ethanol content (percentage by volume) and the throughput rate (gallons) for storage operations, calculated monthly; and the rolling 12-month VOC emission rate for fermentation operations, calculated monthly. [District Rules 2201, 2520, and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-288-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

615,603 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6656) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,603 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,438,235 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a rolling 12-month basis, shall not exceed 3,299 pounds. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; the rolling 12-month wine ethanol content (percentage by volume) and the throughput rate (gallons) for storage operations, calculated monthly; and the rolling 12-month VOC emission rate for fermentation operations, calculated monthly. [District Rules 2201, 2520, and 4694] Federally Enforceable Through Title V Permit
16. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated rolling 12-month wine ethanol content and throughput rate for storage operations and VOC emission rate for fermentation operations (ethanol percentage by volume, gallons and lb-VOC per rolling 12-month period, calculated monthly). [District Rules 2201, 2520, and 4694] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-289-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

612,570 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6659) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,438,235 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a rolling 12-month basis, shall not exceed 3,299 pounds. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; the rolling 12-month wine ethanol content (percentage by volume) and the throughput rate (gallons) for storage operations, calculated monthly; and the rolling 12-month VOC emission rate for fermentation operations, calculated monthly. [District Rules 2201, 2520, and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-290-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

611,948 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6660) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,438,235 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-291-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

613,637 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6661) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,438,235 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a rolling 12-month basis, shall not exceed 3,299 pounds. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; the rolling 12-month wine ethanol content (percentage by volume) and the throughput rate (gallons) for storage operations, calculated monthly; and the rolling 12-month VOC emission rate for fermentation operations, calculated monthly. [District Rules 2201, 2520, and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-292-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

616,758 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6662) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 616,758 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,438,235 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a rolling 12-month basis, shall not exceed 3,299 pounds. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; the rolling 12-month wine ethanol content (percentage by volume) and the throughput rate (gallons) for storage operations, calculated monthly; and the rolling 12-month VOC emission rate for fermentation operations, calculated monthly. [District Rules 2201, 2520, and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-293-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

615,000 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6663) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,438,235 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a rolling 12-month basis, shall not exceed 3,299 pounds. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; the rolling 12-month wine ethanol content (percentage by volume) and the throughput rate (gallons) for storage operations, calculated monthly; and the rolling 12-month VOC emission rate for fermentation operations, calculated monthly. [District Rules 2201, 2520, and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-294-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

615,446 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6664) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,446 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,438,235 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a rolling 12-month basis, shall not exceed 3,299 pounds. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; the rolling 12-month wine ethanol content (percentage by volume) and the throughput rate (gallons) for storage operations, calculated monthly; and the rolling 12-month VOC emission rate for fermentation operations, calculated monthly. [District Rules 2201, 2520, and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-295-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

99 MMBTU/HR VICTORY ENERGY OPERATIONS NATURAL GAS/BIOGAS-FIRED BOILER EQUIPPED WITH A TODD VERIFLAME MODEL TODD VERIFLAME 99 LOW NOX BURNER, FLUE GAS RECIRCULATION SYSTEM, AND O2 CONTROLLER SERVED BY A NATIONWIDE MODEL CATASTAK SELECTIVE CATALYTIC REDUCTION (SCR) SYSTEM (BOILER #4)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grain/dscf at operating conditions, nor 0.1 grain/dscf calculated to 12% CO₂, nor 10 lb/hr. [District Rules 4201 and 4301] Federally Enforceable Through Title V Permit
2. All equipment shall be constructed, maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District Rule 2201] Federally Enforceable Through Title V Permit
3. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
4. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201 and 40 CFR 60.48 (c)(g)] Federally Enforceable Through Title V Permit
5. The unit shall only be fired on PUC-regulated natural gas and/or on scrubbed biogas from C-447-226. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
6. The H₂S content of the scrubbed biogas fuel shall not exceed 50 ppmv. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
7. Except during start-up and shutdown, emissions from this unit shall not exceed any of the following limits: 5 ppmvd NO_x @ 3% O₂ or 0.006 lb-NO_x/MMBtu; 0.0022 lb-PM₁₀/MMBtu; 200 ppmvd CO @ 3% O₂ (equivalent to 0.147 lb-CO/MMBtu); or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
8. During start-up and shutdown, emissions from this unit shall not exceed any of the following limits: 0.83 lb-NO_x/hr; 0.0022 lb-PM₁₀/MMBtu; 200 ppmvd CO @ 3% O₂ (equivalent to 0.147 lb-CO/MMBtu); or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
9. The total duration of start-up time shall not exceed 5.0 hours per day. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. The total duration of startup time shall not exceed 4.0 hours per occurrence. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
11. The total duration of shutdown time shall not exceed 2.0 hours per day. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
12. The total duration of shutdown time shall not exceed 2.0 hours per occurrence. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

13. The emission control systems shall be in operation and emissions shall be minimized insofar as technologically feasible during startup and shutdown. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
14. The ammonia (NH₃) emissions shall not exceed 10 ppmvd @ 3% O₂ over a 15 minute averaging period. [District Rule 4102]
15. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
16. Source testing to measure natural gas/biogas combustion NO_x, CO, and NH₃ emissions from this unit shall be conducted at least once every twelve months. After demonstrating compliance on two consecutive annual source tests when unit is fired on natural gas, the unit shall be tested not less than once every 36 months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve months. [District Rules 2201, 4102, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
17. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
18. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
19. Nitrogen oxide (NO_x) emission concentrations in ppmv referenced at dry stack emissions shall be corrected to 3% O₂ and lb/MMBtu rates shall be calculated as lb NO₂/MMBtu of heat input (hhv). [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
20. NO_x emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
21. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
22. Stack gas oxygen (O₂) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
23. Source testing for ammonia slip shall be conducted utilizing BAAQMD Method ST-1B. [District Rule 4102]
24. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
25. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
26. The permittee shall monitor and record the stack concentration of NO_x, CO, NH₃, and O₂ at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. NH₃ monitoring shall be conducted utilizing Draeger tubes or a District approved equivalent method. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within five days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4102, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

27. If the NO_x, CO or NH₃ concentrations, as measured by the portable analyzer or the District approved ammonia monitoring equipment, exceed the permitted levels, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than one hour of operation after detection. If the portable analyzer or the ammonia monitoring equipment continue to show emission limit violations after one hour of operation following detection, the permittee shall notify the District within the following one hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
28. All NO_x, CO, O₂ and NH₃ emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The NO_x, CO and O₂ analyzer as well as the NH₃ emission monitoring equipment shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
29. NH₃ emission readings shall be conducted at the time the NO_x, CO and O₂ readings are taken. The readings shall be converted to ppmvd @ 3% O₂. [District Rule 4102]
30. The permittee shall maintain records of: (1) the date and time of NO_x, CO, NH₃, and O₂ measurements, (2) the O₂ concentration in percent by volume and the measured NO_x, CO, and NH₃ concentrations corrected to 3% O₂, (3) make and model of the portable analyzer, (4) portable analyzer calibration records, (5) the method of determining the NH₃ emission concentration, and (6) a description of any corrective action taken to maintain the emissions at or below the acceptable levels. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
31. Permittee shall determine sulfur content of combusted natural gas annually or shall demonstrate that the combusted natural gas is provided from a PUC or FERC regulated source. [District Rules 1081 and 4320] Federally Enforceable Through Title V Permit
32. The permittee shall monitor the biogas H₂S concentration at the outlet of the biogas scrubber (Permit to Operate C-447-226) on a weekly basis. If the biogas H₂S concentration does not exceed 50 ppmv for four consecutive weeks, monitoring may be conducted on a monthly basis. If the H₂S concentration at the outlet exceeds 50 ppmv, weekly monitoring shall resume. [District Rule 4320] Federally Enforceable Through Title V Permit
33. The permittee shall maintain daily records of start-up and shutdown durations and number of occurrences of each. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
34. Permittee shall maintain daily records of the type and quantity of fuel combusted by the boiler. [District Rules 2201 and 40 CFR 60.48 (c)(g)] Federally Enforceable Through Title V Permit
35. The permittee shall take readings of the NO_x concentration and O₂ percent, by volume, using the in-stack monitoring system at least once per each day that the boiler operates. [District Rule 2201 and 40 CFR Part 64.9] Federally Enforceable Through Title V Permit
36. During times when the in-stack monitoring system is down for maintenance or repairs, the permittee shall use a District approved portable analyzer to record daily NO_x and O₂ concentrations. The permittee shall maintain records of the portable analyzer readings including the date(s) and reason the in-stack monitoring system was not operating. [District Rule 2201 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
37. The permittee shall maintain daily records of the NO_x and O₂ concentration from the in-stack monitoring system. These records shall be made available for District inspection upon request. [District Rule 2201 and 40 CFR Part 64] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

38. The permittee shall compare the NO_x and O₂ concentrations from the in-stack monitoring system with the concentration of NO_x and O₂ readings from calibration gas cylinders for NO_x and O₂ at least once during each month that the boiler operates. The permittee shall maintain these comparison readings and these records shall be available for District inspection upon request. [District Rule 2201 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
39. If the NO_x or O₂ concentrations, as measured by the in-stack monitoring system, exceed the permitted levels the permittee shall return the emissions to compliant levels as soon as possible, but no longer than 1 hour of operation after detection. If the in-stack monitoring system continues to show emission limit violations after 1 hour of operation following detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation that is subject to enforcement action has occurred. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [40 CFR Part 64] Federally Enforceable Through Title V Permit
40. The permittee shall comply with the compliance assurance monitoring operation and maintenance requirements of 40 CFR part 64.7. [40 CFR Part 64.7] Federally Enforceable Through Title V Permit
41. If the District or EPA determine that a Quality Improvement Plan is required under 40 CFR 64.7(d)(2), the permittee shall develop and implement the Quality Improvement Plan in accordance with 40 CFR Part 64.8. [40 CFR Part 64.8] Federally Enforceable Through Title V Permit
42. The permittee shall comply with the record keeping and reporting requirements of 40 CFR part 64.9. [40 CFR Part 64.9] Federally Enforceable Through Title V Permit
43. All records shall be maintained and retained on-site for a minimum of five years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-296-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (629,640 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6701)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,450,000 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-297-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (629,689 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6702)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,450,000 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-298-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (629,298 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6705)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,450,000 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-298-2 : May 19 2017 9:02AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-299-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (630,154 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6706)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,450,000 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-299-2 : May 19 2017 9:02AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-300-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (628,456 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6709)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,450,000 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-301-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (628,713 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6710) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,450,000 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-301-2 : May 19 2017 9:02AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-302-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (630,565 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6713)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,450,000 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-303-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (629,783 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6714)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,450,000 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-304-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (628,504 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6717)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,450,000 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-305-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (627,927 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6718)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,450,000 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-305-2 : May 19 2017 9:02AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-306-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (628,545 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6721)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,450,000 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-306-2 : May 19 2017 9:02AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-307-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (627,933 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6722)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,450,000 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-307-2 : May 19 2017 9:02AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-308-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (628,002 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6725)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,450,000 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-309-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (628,728 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6726)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,450,000 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-310-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (630,044 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6729)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,450,000 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-311-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (628,837 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6730)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,450,000 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-312-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (626,556 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6703)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,450,000 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-313-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (627,464 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6704)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,450,000 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-314-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (628,154 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6707)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,450,000 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-315-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (627,892 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6708)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,450,000 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-316-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (632,240 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6711)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,450,000 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-317-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (634,362 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6712)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,450,000 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-318-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (632,359 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6715)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,450,000 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-319-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (632,903 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6716)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,450,000 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-319-2 : May 19 2017 9:02AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-320-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (626,432 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6719)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,450,000 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-321-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (624,782 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6720)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,450,000 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-322-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (626,387 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6723)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,450,000 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-323-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (627,401 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6724)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,450,000 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-324-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (628,736 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6727)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,450,000 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-324-2 : May 19 2017 9:02AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-325-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (628,647 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6728)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,450,000 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-326-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (628,179 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6731)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,450,000 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-326-2 : May 19 2017 9:02AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-327-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (628,120 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6732)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a rolling 12-month basis, shall not exceed 15 percent by volume. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a rolling 12-month basis, shall not exceed 4,450,000 gallons per year. [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated rolling 12-month wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per rolling 12-month period, calculated monthly). [District Rules 2201 and 2520] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

DRAFT

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-328-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

DIATOMACEOUS EARTH RECEIVING AND STORAGE OPERATION WITH A 6,000 CUBIC FEET STORAGE SILO E
SERVED BY A BIN VENT FILTER SYSTEM

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed the hourly rate as calculated in District Rule 4202 using the equation $E = 3.59 \times P^{0.62}$ if P is less than or equal to 30 tons per hour, or $E = 17.31 \times P^{0.16}$ if P is greater than 30 tons per hour. [District Rule 4202] Federally Enforceable Through Title V Permit
3. Visible emissions from the bin vent filter serving the storage silo shall not equal or exceed 5% opacity for a period or periods aggregating more than three minutes in any one hour. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Visible emissions shall be inspected annually during operation. If visible emissions are observed, corrective action shall be taken to eliminate visible emissions. If visible emissions cannot be corrected within 24 hours, a visible emissions test using EPA Method 9 shall be conducted. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. The bin vent filter system shall be equipped with a pressure differential gauge to indicate the pressure drop across the filters. The gauge shall be maintained in good working condition at all times and shall be located in an easily accessible location. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The bin vent filter shall operate at all times with a minimum differential pressure of 2.0 inches water column and a maximum differential pressure of 6 inches water column. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Differential operating pressure shall be monitored and recorded on each day that the bin vent filter system is in operation. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Replacement bags numbering at least 10% of the total number of bags shall be maintained on the premises. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Material removed from the bin vent filter system shall be disposed of in a manner preventing entrainment into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Bin vent filter shall be thoroughly inspected annually for tears, scuffs, abrasions, holes, or any evidence of particulate matter breakthrough and shall be replaced as needed. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
11. PM10 emissions shall not exceed 0.00085 pounds per ton of diatomaceous earth loaded into the silo. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The amount of diatomaceous earth loaded into the silo shall not exceed 25 tons in any one day. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

13. Dust collection system shall be completely inspected annually while in operation for evidence of particulate matter leaks and repaired as needed. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
14. The permittee shall keep records of date and quantity of diatomaceous earth loaded into the silo. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Records of all maintenance of the bin vent filter system, including all change outs of bags or filter media, shall be maintained. These records shall include identification of the equipment, date of inspection, any corrective action taken, and identification of the personnel performing the inspection. [District Rules 2201 and 2520, 9.4.2] Federally Enforceable Through Title V Permit
16. All records shall be retained for a minimum of five years and made available for District inspection upon request. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-329-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

99 MMBTU/HR VICTORY ENERGY OPERATIONS NATURAL GAS/BIOGAS-FIRED BOILER EQUIPPED WITH A COEN VERIFLAME MODEL COEN VERIFLAME 99 LOW NOX BURNER, FLUE GAS RECIRCULATION SYSTEM, AND O2 CONTROLLER SERVED BY A NATIONWIDE MODEL CATASTAK SELECTIVE CATALYTIC REDUCTION (SCR) SYSTEM (BOILER #3)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. All equipment shall be constructed, maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District Rule 2201] Federally Enforceable Through Title V Permit
3. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
4. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201 and 40 CFR 60.48 (c)(g)] Federally Enforceable Through Title V Permit
5. The unit shall only be fired on PUC-regulated natural gas and/or on scrubbed biogas from C-447-226. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
6. The H2S content of the scrubbed biogas fuel shall not exceed 50 ppmv. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
7. Except during start-up and shutdown, emissions from this unit shall not exceed any of the following limits: 5 ppmvd NOx @ 3% O2 or 0.006 lb-NOx/MMBtu; 0.0076 lb-PM10/MMBtu; 200 ppmvd CO @ 3% O2 (equivalent to 0.147 lb-CO/MMBtu); or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
8. During start-up and shutdown, emissions from this unit shall not exceed any of the following limits: 0.83 lb-NOx/hr; 0.0076 lb-PM10/MMBtu; 200 ppmvd CO @ 3% O2 (equivalent to 0.147 lb-CO/MMBtu); or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
9. The total duration of start-up time shall not exceed 5.0 hours per day. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. The total duration of startup time shall not exceed 4.0 hours per occurrence. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
11. The total duration of shutdown time shall not exceed 2.0 hours per day. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
12. The total duration of shutdown time shall not exceed 2.0 hours per occurrence. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

13. The emission control systems shall be in operation and emissions shall be minimized insofar as technologically feasible during startup and shutdown. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
14. The ammonia (NH₃) emissions shall not exceed 10 ppmvd @ 3% O₂ over a 15 minute averaging period. [District Rule 4102]
15. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
16. Source testing to measure natural gas/biogas combustion NO_x, CO, and NH₃ emissions from this unit shall be conducted at least once every twelve months. After demonstrating compliance on two consecutive annual source tests when unit is fired on natural gas, the unit shall be tested not less than once every 36 months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve months. [District Rules 2201, 4102, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
17. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
18. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
19. Nitrogen oxide (NO_x) emission concentrations in ppmv referenced at dry stack emissions shall be corrected to 3% O₂ and lb/MMBtu rates shall be calculated as lb NO₂/MMBtu of heat input (hhv). [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
20. NO_x emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
21. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
22. Stack gas oxygen (O₂) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
23. Source testing for ammonia slip shall be conducted utilizing BAAQMD Method ST-1B. [District Rule 4102]
24. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
25. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
26. The permittee shall monitor and record the stack concentration of NO_x, CO, NH₃, and O₂ at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. NH₃ monitoring shall be conducted utilizing Draeger tubes or a District approved equivalent method. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within five days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4102, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

27. If the NO_x, CO or NH₃ concentrations, as measured by the portable analyzer or the District approved ammonia monitoring equipment, exceed the permitted levels, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than one hour of operation after detection. If the portable analyzer or the ammonia monitoring equipment continue to show emission limit violations after one hour of operation following detection, the permittee shall notify the District within the following one hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
28. All NO_x, CO, O₂ and NH₃ emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The NO_x, CO and O₂ analyzer as well as the NH₃ emission monitoring equipment shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
29. NH₃ emission readings shall be conducted at the time the NO_x, CO and O₂ readings are taken. The readings shall be converted to ppmvd @ 3% O₂. [District Rule 4102]
30. The permittee shall maintain records of: (1) the date and time of NO_x, CO, NH₃, and O₂ measurements, (2) the O₂ concentration in percent by volume and the measured NO_x, CO, and NH₃ concentrations corrected to 3% O₂, (3) make and model of the portable analyzer, (4) portable analyzer calibration records, (5) the method of determining the NH₃ emission concentration, and (6) a description of any corrective action taken to maintain the emissions at or below the acceptable levels. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
31. Permittee shall determine sulfur content of combusted natural gas annually or shall demonstrate that the combusted natural gas is provided from a PUC or FERC regulated source. [District Rules 1081 and 4320] Federally Enforceable Through Title V Permit
32. The permittee shall monitor the biogas H₂S concentration at the outlet of the biogas scrubber (Permit to Operate C-447-226) on a weekly basis. If the biogas H₂S concentration does not exceed 50 ppmv for four consecutive weeks, monitoring may be conducted on a monthly basis. If the H₂S concentration at the outlet exceeds 50 ppmv, weekly monitoring shall resume. [District Rule 4320] Federally Enforceable Through Title V Permit
33. The permittee shall maintain daily records of start-up and shutdown durations and number of occurrences of each. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
34. The permittee shall take readings of the NO_x concentration and O₂ percent, by volume, using the in-stack monitoring system at least once per each day that the boiler operates. [District Rule 2201 and 40 CFR Part 64.9] Federally Enforceable Through Title V Permit
35. During times when the in-stack monitoring system is down for maintenance or repairs, the permittee shall use a District approved portable analyzer to record daily NO_x and O₂ concentrations. The permittee shall maintain records of the portable analyzer readings including the date(s) and reason the in-stack monitoring system was not operating. [District Rule 2201 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
36. The permittee shall maintain daily records of the NO_x and O₂ concentration from the in-stack monitoring system. These records shall be made available for District inspection upon request. [District Rule 2201 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
37. The permittee shall compare the NO_x and O₂ concentrations from the in-stack monitoring system with the concentration of NO_x and O₂ readings from calibration gas cylinders for NO_x and O₂ at least once during each month that the boiler operates. The permittee shall maintain these comparison readings and these records shall be available for District inspection upon request. [District Rule 2201 and 40 CFR Part 64] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

38. If the NO_x or O₂ concentrations, as measured by the in-stack monitoring system, exceed the permitted levels the permittee shall return the emissions to compliant levels as soon as possible, but no longer than 1 hour of operation after detection. If the in-stack monitoring system continues to show emission limit violations after 1 hour of operation following detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation that is subject to enforcement action has occurred. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [40 CFR Part 64] Federally Enforceable Through Title V Permit
39. The permittee shall comply with the compliance assurance monitoring operation and maintenance requirements of 40 CFR part 64.7. [40 CFR Part 64.7] Federally Enforceable Through Title V Permit
40. If the District or EPA determine that a Quality Improvement Plan is required under 40 CFR 64.7(d)(2), the permittee shall develop and implement the Quality Improvement Plan in accordance with 40 CFR Part 64.8. [40 CFR Part 64.8] Federally Enforceable Through Title V Permit
41. The permittee shall comply with the record keeping and reporting requirements of 40 CFR part 64.9. [40 CFR Part 64.9] Federally Enforceable Through Title V Permit
42. Permittee shall maintain daily records of the type and quantity of fuel combusted by the boiler. [District Rules 2201 and 40 CFR 60.48 (c)(g)] Federally Enforceable Through Title V Permit
43. All records shall be maintained and retained on-site for a minimum of five years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

ATTACHMENT B

Previous Title V Operating Permit

Permit to Operate

FACILITY: C-447

EXPIRATION DATE: 06/30/2016

LEGAL OWNER OR OPERATOR: E & J GALLO WINERY
MAILING ADDRESS: 5610 E OLIVE AVE
FRESNO, CA 93727

FACILITY LOCATION: 5610 E OLIVE AVE
FRESNO, CA 93727

FACILITY DESCRIPTION: WINERY

The Facility's Permit to Operate may include Facility-wide Requirements as well as requirements that apply to specific permit units.

This Permit to Operate remains valid through the permit expiration date listed above, subject to payment of annual permit fees and compliance with permit conditions and all applicable local, state, and federal regulations. This permit is valid only at the location specified above, and becomes void upon any transfer of ownership or location. Any modification of the equipment or operation, as defined in District Rule 2201, will require prior District approval. This permit shall be posted as prescribed in District Rule 2010.

Seyed Sadredin
Executive Director / APCO

Arnaud Marjollet
Director of Permit Services

San Joaquin Valley Air Pollution Control District

FACILITY: C-447-0-3

EXPIRATION DATE: 06/30/2016

FACILITY-WIDE REQUIREMENTS

1. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1 and Fresno County Rule 110] Federally Enforceable Through Title V Permit
2. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0 and Fresno County Rule 110] Federally Enforceable Through Title V Permit
3. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.13.1] Federally Enforceable Through Title V Permit
6. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-0-3 : May 19 2017 8:37AM -- BROWN

10. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit
11. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
12. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
13. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
14. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
15. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
16. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
17. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
18. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
19. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
20. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
21. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit
22. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

23. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in the Table of Standards of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
24. All VOC-containing materials subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
25. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
26. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
27. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
28. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit
29. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8021] Federally Enforceable Through Title V Permit
30. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8031] Federally Enforceable Through Title V Permit
31. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8041] Federally Enforceable Through Title V Permit
32. Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8051] Federally Enforceable Through Title V Permit
33. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8061] Federally Enforceable Through Title V Permit
34. Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8071] Federally Enforceable Through Title V Permit
35. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

36. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
37. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
38. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
39. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), Rule 111 (Kern, Tulare, Kings), and Rule 202 (Fresno, Kern, Tulare, Kings, Madera, Stanislaus, Merced, San Joaquin). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601 (12/17/09); 8021 (8/19/2004); 8031 (8/19/2004); 8041 (8/19/2004); 8051 (8/19/2004); 8061 (8/19/2004); and 8071 (9/16/2004). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
42. Should the facility, as defined in 40 CFR section 68.3, become subject to part 68, then the owner or operator shall submit a risk management plan (RMP) by the date specified in 40 CFR section 68.10. The facility shall certify compliance as part of the annual certification as required by 40 CFR part 70. [40 CFR68] Federally Enforceable Through Title V Permit
43. A Three-Year Compliance Plan that demonstrates compliance with the requirements of Section 5.1 of District Rule 4694 for each year of the applicable compliance period shall be submitted to the District by no later than December 1, 2006, and every three years thereafter on or before December 1. [District Rule 4694]
44. A Three-Year Compliance Plan Verification that demonstrates that the Three-Year Compliance Plan elements are in effect shall be submitted to the District by no later than July 1, 2007, and every three years thereafter on or before July 1. [District Rule 4694]
45. An Annual Compliance Plan Demonstration that shows compliance with the applicable requirements of this rule shall be submitted to the District by no later than March 1, 2008, and every year thereafter on or before March 1. [District Rule 4694]
46. Operators using Certified Emissions Reductions (CER) to mitigate fermentation emissions shall perform all monitoring and recordkeeping, as established in their approved Three-Year Compliance Plan, and shall maintain all records necessary to demonstrate compliance. [District Rule 4694]
47. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report begin January 1 of every year, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit
48. Facilities C-447 and C-3275 are part of the same stationary source for Rule 2201 purposes. [District Rule 2201]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-1-12

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

62.0 MMBTU/HR B & W BIOGAS/NATURAL GAS-FIRED BOILER EQUIPPED WITH A TODD LOW-NOX BURNER, FLUE GAS RECIRCULATION, O2 AND CO TRIM CONTROLLERS, A CRI COMPANY SELECTIVE CATALYTIC REDUCTION (SCR) SYSTEM MODEL SHELL DNOX LFR, AND A NOX AND O2 IN-STACK EMISSION MONITORING SYSTEM

PERMIT UNIT REQUIREMENTS

1. All equipment shall be constructed, maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District Rule 2201] Federally Enforceable Through Title V Permit
2. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Particulate matter emissions shall not exceed 0.1 grain/dscf at operating conditions, nor 0.1 grain/dscf calculated to 12% CO2, nor 10 lb/hr. [District Rules 4201, 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
4. The unit shall only be fired on PUC-regulated natural gas and/or on scrubbed biogas from C-447-226. [District Rules 2201, 4301, 4320 and 4801, and Fresno County Rule 406] Federally Enforceable Through Title V Permit
5. The unit shall not burn more than 1,296,000 scf of biogas fuel in any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The H2S content of the scrubbed biogas fuel shall not exceed 50 ppmv. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
7. Except during start-up and shutdown, emissions from this unit shall not exceed any of the following limits: 7 ppmvd NOx @ 3% O2 or 0.008 lb-NOx/MMBtu; 0.0022 lb-PM10/MMBtu; 100 ppmvd CO @ 3% O2 (equivalent to 0.074 lb-CO/MMBtu); or 0.0025 lb-VOC/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
8. During start-up and shutdown, emissions from this unit shall not exceed either of the following limits: 0.68 lb-NOx/hr, or 4.59 lb-CO/hr. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
9. The total duration of start-up time shall not exceed 9.0 hours per day. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. The total duration of startup time shall not exceed 6.0 hours per occurrence. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
11. The total duration of shutdown time shall not exceed 6.0 hours per day. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
12. The total duration of shutdown time shall not exceed 3.0 hours per occurrence. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. The emission control systems shall be in operation and emissions shall be minimized insofar as technologically feasible during start-up and shutdown. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

14. The ammonia (NH₃) emissions shall not exceed 10 ppmvd @ 3% O₂ over a 15 minute averaging period. [District Rule 4102]
15. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
16. Source testing to measure natural gas/biogas combustion NO_x, CO, and NH₃ emissions from this unit shall be conducted at least once every twelve months. After demonstrating compliance on two consecutive annual source tests when unit is fired on natural gas/biogas, the unit shall be tested not less than once every 36 months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve months. [District Rules 2201, 4102, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
17. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
18. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
19. NO_x emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
20. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
21. Stack gas oxygen (O₂) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 4306, 4320 and] Federally Enforceable Through Title V Permit
22. Source testing for ammonia slip shall be conducted utilizing BAAQMD Method ST-1B. [District Rule 4102]
23. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
24. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
25. The permittee shall monitor and record the stack concentration of NO_x, CO, NH₃, and O₂ at least once during each month in which source testing is not performed. NO_x, CO, and O₂ monitoring shall be conducted utilizing a portable analyzer that meets District specifications or District-approved monitoring equipment. NH₃ monitoring shall be conducted utilizing Draeger tubes or a District approved equivalent method. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless it has been performed within the last month. [District Rules 4102, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
26. If the NO_x, CO or NH₃ concentrations, as measured by the portable analyzer or the District approved ammonia monitoring equipment, exceed the permitted levels, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than one hour of operation after detection. If the portable analyzer or the ammonia monitoring equipment continue to show emission limit violations after one hour of operation following detection, the permittee shall notify the District within the following one hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

27. All NO_x, CO, O₂ and NH₃ emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The NO_x, CO and O₂ analyzer as well as the NH₃ emission monitoring equipment shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
28. NH₃ emission readings shall be conducted at the time the NO_x, CO and O₂ readings are taken. The readings shall be converted to ppmvd @ 3% O₂. [District Rule 4102]
29. The permittee shall maintain records of: (1) the date and time of NO_x, CO, NH₃, and O₂ measurements, (2) the O₂ concentration in percent by volume and the measured NO_x, CO, and NH₃ concentrations corrected to 3% O₂, (3) make and model of the portable analyzer, (4) portable analyzer calibration records, (5) the method of determining the NH₃ emission concentration, and (6) a description of any corrective action taken to maintain the emissions at or below the acceptable levels. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
30. Operator shall maintain copies of fuel invoices and supplier certifications. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
31. Operator shall provide that fuel hhv be certified by third party fuel supplier or determined annually by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
32. Permittee shall determine sulfur content of combusted natural gas annually or shall demonstrate that the combusted natural gas is provided from a PUC or FERC regulated source. [District Rules 1081 and 4320] Federally Enforceable Through Title V Permit
33. The permittee shall monitor the biogas H₂S concentration at the outlet of the biogas scrubber (Permit to Operate C-447-226) on a weekly basis. If the biogas H₂S concentration does not exceed 50 ppmv for four consecutive weeks, monitoring may be conducted on a monthly basis. If the H₂S concentration at the outlet exceeds 50 ppmv, weekly monitoring shall resume. [District Rule 4320] Federally Enforceable Through Title V Permit
34. The permittee shall maintain daily records of start-up and shutdown durations and number of occurrences of each. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
35. The permittee shall maintain records of the daily and cumulative annual natural gas and biogas consumption. [District Rule 2201] Federally Enforceable Through Title V Permit
36. The permittee shall take readings of the NO_x concentration and O₂ percent, by volume, using the in-stack monitoring system at least once per each day that the boiler operates. [District Rule 2201 and 40 CFR Part 64.9] Federally Enforceable Through Title V Permit
37. During times when the in-stack monitoring system is down for maintenance or repairs, the permittee shall use a District approved portable analyzer to record daily NO_x and O₂ concentrations. The permittee shall maintain records of the portable analyzer readings including the date(s) and reason the in-stack monitoring system was not operating. [District Rule 2201 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
38. The permittee shall maintain daily records of the NO_x and O₂ concentration from the in-stack monitoring system. These records shall be made available for District inspection upon request. [District Rule 2201 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
39. The permittee shall compare the NO_x and O₂ concentrations from the in-stack monitoring system with the concentration of NO_x and O₂ readings from calibration gas cylinders for NO_x and O₂ at least once during each month that the boiler operates. The permittee shall maintain these comparison readings and these records shall be available for District inspection upon request. [District Rule 2201 and 40 CFR Part 64] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

40. If the NO_x or O₂ concentrations, as measured by the in-stack monitoring system, exceed the permitted levels the permittee shall return the emissions to compliant levels as soon as possible, but no longer than 1 hour of operation after detection. If the in-stack monitoring system continues to show emission limit violations after 1 hour of operation following detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation that is subject to enforcement action has occurred. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4102, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
41. The permittee shall comply with the compliance assurance monitoring operation and maintenance requirements of 40 CFR part 64.7. [40 CFR Part 64.7] Federally Enforceable Through Title V Permit
42. If the District or EPA determine that a Quality Improvement Plan is required under 40 CFR 64.7(d)(2), the permittee shall develop and implement the Quality Improvement Plan in accordance with 40 CFR Part 64.8. [40 CFR Part 64.8] Federally Enforceable Through Title V Permit
43. The permittee shall comply with the record keeping and reporting requirements of 40 CFR part 64.9. [40 CFR Part 64.9] Federally Enforceable Through Title V Permit
44. All records shall be maintained and retained on-site for a minimum of five years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
45. Compliance with permit conditions in the Title V permit shall be deemed compliance with subsumed requirements of SJVUAPCD Rule 4301. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
46. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements of Fresno County Rule 406 and SJVUAPCD Rule 4801. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
47. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: SJVUAPCD Rules 4201, 4301, and 4305. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
48. Compliance with permit conditions in the Title V permit shall be deemed compliance with the requirements of SJVUAPCD Rule 1081. A permit shield is granted from this requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
49. The requirements of 40 CFR 72.6(b) and 40 CFR 60.40c do not apply to this source because it is not used to produce electricity for sale and was constructed prior to June 9, 1989 without modifications or reconstruction. A permit shield is granted from this requirement. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-2-13

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

142.0 MMBTU/HR NEBRASKA MODEL 84 NATURAL GAS-FIRED BOILER WITH A TODD LOW NOX BURNER, FLUE GAS RECIRCULATION (FGR) SYSTEM, CRI COMPANY SELECTIVE CATALYTIC REDUCTION (SCR) SYSTEM, AND AN ABB MODEL AO2000 CEMS

PERMIT UNIT REQUIREMENTS

1. To ensure the validity of the ERCs issued by Project # 920370, NOx emissions shall not exceed the 0.036 pound per million Btu limitation based on a 24-hour rolling average of the NOx concentration calculated from CEMS. All performance testing shall be done in compliance with District Rules. [District NSR Rule and Rule 2301 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
2. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
3. Particulate matter emissions shall not exceed 0.1 grain/dscf at operating conditions, nor 0.1 grain/dscf calculated to 12% CO₂, nor 10 lb/hr. [District Rules 4201 and 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
4. The unit shall only be fired on PUC-regulated natural gas. [District NSR Rule and District Rules 4301, 4306, and 4320] Federally Enforceable Through Title V Permit
5. Except during start-up and shutdown, emissions from this unit shall not exceed any of the following limits: 7 ppmvd NOx @ 3% O₂ or 0.008 lb-NOx/MMBtu; 0.00285 lb-SOx/MMBtu; 0.0024 lb-PM₁₀/MMBtu; 200 ppmvd CO @ 3% O₂ (equivalent to 0.148 lb-CO/MMBtu); or 0.0027 lb-VOC/MMBtu. [District NSR Rule and Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
6. During start-up and shutdown, emissions from the exhaust of the SCR system serving this boiler shall not exceed either of the following limits: 1.56 lb-NOx/hr, or 21.0 lb-CO/hr. [District NSR Rule and District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. NOx emissions shall not exceed 0.10 lb/MMBtu including periods of startup, shutdown, or malfunction. Compliance with the 0.10 pound per million Btu limitation shall be based on a 30-day rolling average of the NOx concentration calculated from CEMS. All performance testing shall be done in compliance with 40 CFR 60.8. [40 CFR 60.44b (c), (e), (h), and (i) and 40 CFR Part 64] Federally Enforceable Through Title V Permit
8. The total duration of start-up time shall not exceed 9.0 hours per day. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
9. The total duration of startup time shall not exceed 6.0 hours per occurrence. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. The total duration of shutdown time shall not exceed 6.0 hours per day. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
11. The total duration of shutdown time shall not exceed 3.0 hours per occurrence. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-2-13 : May 19 2017 8:37AM -- BROWN

12. The emission control systems shall be in operation and emissions shall be minimized insofar as technologically feasible during startup and shutdown. [District NSR Rule and District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. The ammonia (NH₃) emissions shall not exceed 10 ppmvd @ 3% O₂. [District Rule 4102]
14. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
15. Source testing to measure natural gas-combustion NO_x and CO emissions, and ammonia (NH₃) emissions from this unit shall be conducted at least once every twelve months. After demonstrating compliance on two consecutive annual source tests, the unit shall be tested not less than once 36 months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve months. [District Rules 4102, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
16. The facility shall source test VOC and PM₁₀ emissions from this unit upon request by the District. Emissions shall be calculated using the arithmetic mean, pursuant to District Rule 1081 (Amended December 16, 1993), of 3 thirty minute test runs unless other averaging times are approved in advance. [District Rules 1081 and 2520, 9.3.2] Federally Enforceable Through Title V Permit
17. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
18. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
19. NO_x emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
20. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
21. Stack gas oxygen (O₂) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
22. Source testing for ammonia slip shall be conducted utilizing BAAQMD method ST-1B. [District NSR Rule] Federally Enforceable Through Title V Permit
23. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
24. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
25. A Continuous Emissions Monitoring System (CEMS) shall be in place and operating whenever the facility is operating. NO_x emissions in ppmv (as NO₂ corrected to 3% O₂), CO emissions in ppmv (corrected to 3% O₂) and O₂ concentrations must be recorded continuously. [District NSR Rule and District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
26. CEMS emission measurements shall be averaged over a period of 15 consecutive minutes to demonstrate compliance with the applicable emission limits. [District Rules 4306 and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

27. The facility shall install and maintain equipment, facilities, and systems compatible with the District's CEM data polling software system and shall make CEM data available to the District's automated polling system on a daily basis. [District Rule 1080] Federally Enforceable Through Title V Permit
28. Upon notice by the District that the facility's CEM system is not providing polling data, the facility may continue to operate without providing automated data for a maximum of 30 days per calendar year provided the CEM data is sent to the District by a District-approved alternative method. [District Rule 1080] Federally Enforceable Through Title V Permit
29. The nitrogen oxide emission rates measured by the CEMS shall be expressed in lb/million Btu or in ng/J. The 1-hour average emission rates shall be calculated using the data points required under Section 60.13(b). The records shall also include a daily emission rate consisting of an averaged 24 hour rolling emission rate. [District NSR Rule; 40 CFR 60.48b (d) and 40 CFR Part 64] Federally Enforceable Through Title V Permit
30. The procedures under Section 60.13 shall be followed for evaluation, and operation of the CEMS. [40 CFR 60.48b (e) and 40 CFR Part 64] Federally Enforceable Through Title V Permit
31. Operation and calibration of the Continuous Emissions Monitoring System shall be in accordance with the requirements of 40 CFR, Part 60, Appendix B. [District Rules 1080 and 4001 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
32. The owner/operator shall on a perform a relative accuracy test (RATA) as specified by 40 CFR Part 60, Appendix F, and as specified by 40 CFR Part 60, Appendix B, Spec. 2, Section 7 annually. [40 CFR Part 60.13(c), District Rule 1080 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
33. In cases of CEMS breakdown, malfunction, repairs, calibration checks, and adjustments, emission data shall be obtained as described in paragraph f of 40 CFR 60.48b. [40 CFR 60.48b (f) and 40 CFR Part 64] Federally Enforceable Through Title V Permit
34. The owner shall submit quarterly excess emission reports for any calendar quarter during which there are excess emissions. The owner shall also submit semiannual reports stating that there have been no excess emissions during periods when there have been no excess emissions. [40 CFR 60.49b (h)] Federally Enforceable Through Title V Permit
35. The permittee shall monitor and record the stack concentration of ammonia (NH₃) at least once during each month in which a source test is not performed. NH₃ monitoring shall be conducted utilizing Draeger tubes or a District approved equivalent method. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within one day of restarting the unit unless monitoring has been performed within the last month. [District Rule 4102]
36. Ammonia (NH₃) emission readings shall be converted to ppmvd @ 3% O₂. [District Rule 4102]
37. The permittee shall maintain records of: (1) the date and time of ammonia (NH₃) measurements, (2) the O₂ concentration in percent by volume and the measured NH₃ concentrations corrected to 3% O₂, (3) the method of determining the NH₃ emission concentration, and (4) a description of any corrective action taken to maintain the emissions at or below the acceptable levels. [District Rule 4102]
38. Operator shall maintain copies of fuel invoices and supplier certifications. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
39. Operator shall provide that fuel hhv be certified by third party fuel supplier or determined annually by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
40. Permittee shall determine sulfur content of combusted gas annually or shall demonstrate that the combusted gas is provided from a PUC or FERC regulated source. [District Rules 1081 and 4320] Federally Enforceable Through Title V Permit
41. Daily summaries of continuous monitoring records for each calendar quarter shall be submitted to the District within 30 days of the end of the calendar quarter. [40 CFR 60.49b (i) and 40 CFR Part 64] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

42. The following records shall be kept for each steam generating unit operating day: (1) Calendar date, (2) Average hourly NO_x emission rate, (3) Average 30-day emission rate for preceding 30 operating days, (4) Identification of daily NO_x limit exceedances including reason for exceedance and the corrective actions taken, (5) Identification of daily CEMS interruptions including reason for interruption and the corrective actions taken, (6) Identification of data exclusions and the reasons for the exclusion, (7) Identification of F factor used for calculations, (8) Identification of times that the pollutant concentration exceeded the full span of the CEMS, (9) Description of modifications to the CEMS, (10) Results of daily CEMS drift tests and other tests required under Appendix B. [40 CFR 60.49b (g) and 40 CFR Part 64] Federally Enforceable Through Title V Permit
43. The permittee shall record the daily startup and shutdown duration times of the boiler. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
44. The owner shall record and maintain records of the amounts of each fuel combusted during each day and calculate the annual capacity factor for each calendar quarter. [40 CFR 60.49b (d)] Federally Enforceable Through Title V Permit
45. All records shall be maintained and retained on-site for a minimum of five years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
46. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed Fresno County APCD Rules: 108.1, 404, 406, and 408. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
47. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following requirements: Rule 1081, 4201, 4202, 4301, 4305, and 40 CFR 60 subpart Db. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-5-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

STORAGE SILO #1 FOR DIATOMACEOUS EARTH SERVED BY A SLY PACTECON MODEL #PS3 BAGHOUSE DUST COLLECTOR WITH SHAKER CLEANER

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grain per dry standard cubic foot. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
2. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 4102]
3. Material removed from dust collectors shall be disposed of in a manner preventing entrainment into the atmosphere. [District Rule 4102]
4. Visible emissions shall be inspected annually during operation. If visible emissions are observed, corrective action shall be taken to eliminate visible emissions. If visible emissions cannot be corrected within 24 hours, a visible emissions test using EPA Method 9 shall be conducted. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. Dust collection system shall be completely inspected annually while in operation for evidence of particulate matter leaks and repaired as needed. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. Dust collector filters shall be thoroughly inspected annually for tears, scuffs, abrasions, holes, or any evidence of particulate matter leaks and shall be replaced as needed. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. Particulate matter emissions shall not exceed the hourly rate as calculated in District Rule 4202 using the equation $E = 3.59 \times P^{0.62}$ if P is less than or equal to 30 tons per hour, or $E = 17.31 \times P^{0.16}$ if P is greater than 30 tons per hour. [District Rule 4202] Federally Enforceable Through Title V Permit
8. Records of dust collector maintenance, inspections, and repair shall be maintained. The records shall include identification of the equipment, date of inspection, corrective action taken, and identification of the individual performing the inspection. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-6-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

STORAGE SILO #2 FOR DIATOMACEOUS EARTH SERVED BY A SLY PACTECON MODEL #PS3 BAGHOUSE DUST COLLECTOR WITH SHAKER CLEANER

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grain per dry standard cubic foot. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
2. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 4102]
3. Material removed from dust collectors shall be disposed of in a manner preventing entrainment into the atmosphere. [District Rule 4102]
4. Visible emissions shall be inspected annually during operation. If visible emissions are observed, corrective action shall be taken to eliminate visible emissions. If visible emissions cannot be corrected within 24 hours, a visible emissions test using EPA Method 9 shall be conducted. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
5. Dust collection system shall be completely inspected annually while in operation for evidence of particulate matter leaks and repaired as needed. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. Dust collector filters shall be thoroughly inspected annually for tears, scuffs, abrasions, holes, or any evidence of particulate matter leaks and shall be replaced as needed. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. Particulate matter emissions shall not exceed the hourly rate as calculated in District Rule 4202 using the equation $E = 3.59 \times P^{0.62}$ if P is less than or equal to 30 tons per hour, or $E = 17.31 \times P^{0.16}$ if P is greater than 30 tons per hour. [District Rule 4202] Federally Enforceable Through Title V Permit
8. Records of dust collector maintenance, inspections, and repair shall be maintained. The records shall include identification of the equipment, date of inspection, corrective action taken, and identification of the individual performing the inspection. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-8-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

8190 CUBIC FT SILO #3 FOR STORAGE OF DIATOMACEOUS EARTH SERVED BY A DYNAMIC AIR PULSE-JET BAGHOUSE FILTER

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grain per dry standard cubic foot. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
2. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants in the atmosphere. [District Rule 4102]
3. Material removed from dust collectors shall be disposed of in a manner preventing entrainment in the atmosphere. [District Rule 4102]
4. The baghouse shall be equipped with a pressure differential gauge to indicate the pressure drop across the bags. The gauge shall be maintained in good working condition at all times and shall be located in an easily accessible location. [District NSR Rule] Federally Enforceable Through Title V Permit
5. Visible emissions or proper pressure drop shall be inspected annually during operation. If visible emissions or improper pressure drops are observed, corrective action shall be taken to eliminate visible emissions or improper pressure drop. If visible emissions or improper pressure drop cannot be corrected within 24 hours, a visible emissions test using EPA Method 9 shall be conducted. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
6. Dust collection system shall be completely inspected annually while in operation for evidence of particulate matter leaks and repaired as needed. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. Dust collector filters shall be thoroughly inspected annually for tears, scuffs, abrasions, holes, or any evidence of particulate matter leaks and shall be replaced as needed. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. Particulate matter emissions shall not exceed the hourly rate as calculated in District Rule 4202 using the equation $E = 3.59 \times P^{0.62}$ if P is less than or equal to 30 tons per hour, or $E = 17.31 \times P^{0.16}$ if P is greater than 30 tons per hour. [District Rule 4202] Federally Enforceable Through Title V Permit
9. Records of dust collector maintenance, inspections, and repair shall be maintained. The records shall include identification of the equipment, date of inspection, corrective action taken, and identification of the individual performing the inspection. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-9-5

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

GASOLINE DISPENSING OPERATION WITH ONE 500 GALLON CONVAULT ABOVEGROUND STORAGE TANK SERVED BY OPW EVR PHASE I VAPOR RECOVERY SYSTEM (VR-401-B), STANDING LOSS CONTROL (VR-301-D), AND ONE FUELING POINT WITH ONE PHASE II EXEMPT GASOLINE DISPENSING NOZZLE

PERMIT UNIT REQUIREMENTS

1. The Phase I vapor recovery system shall be installed and maintained in accordance with the manufacturer specifications and the ARB Executive Order specified in this permit, including applicable rules and regulations of the Division of Measurement Standards of the Department of Food and Agriculture, the Office of the State Fire Marshal of the Department of Forestry and Fire Protection, the Division of Occupational Safety and Health of the Department of Industrial Relations, and the Division of Water Quality of the State Water Resources Control Board that have been made conditions of the certification. [District Rule 4621] Federally Enforceable Through Title V Permit
2. This gasoline storage and dispensing equipment shall not be used in retail sales, where gasoline dispensed by the unit is subject to payment of California sales tax on gasoline sales. [District Rule 4621] Federally Enforceable Through Title V Permit
3. Total gasoline throughput for the facility shall not exceed either of the following: 10,000 gallons in any consecutive 30-day period or 24,000 gallons per calendar year. If throughput exceeds stated limits, the permittee shall submit a complete application for an Authority to Construct (ATC) to the District within 30 days of the loss of exemption and install and test a certified Phase II vapor recovery system within six (6) months from the date the ATC is issued. [District Rule 4622] Federally Enforceable Through Title V Permit
4. The storage container(s) shall be installed, maintained, and operated such that they are leak-free. [District Rule 4621] Federally Enforceable Through Title V Permit
5. The Phase I vapor recovery systems and gasoline dispensing equipment shall be maintained without leaks as determined in accordance with the test method specified in this permit. [District Rule 4621] Federally Enforceable Through Title V Permit
6. A leak is defined as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration of total organic compound greater than 10,000 ppmv, as methane, above background when measured in accordance with EPA Test Method 21. [District Rule 4621] Federally Enforceable Through Title V Permit
7. No gasoline delivery vessel shall be operated or be allowed to operate unless valid State of California decals are displayed on the cargo container, which attest to the vapor integrity of the container. [District Rule 4621] Federally Enforceable Through Title V Permit
8. The permittee shall conduct periodic maintenance inspections based on the greatest monthly throughput of gasoline dispensed by the facility in the previous year as follows: A) less than 2,500 gallons - one day per month; B) 2,500 to less than 25,000 gallons - one day per week; or C) 25,000 gallons or greater - five days per week. All inspections shall be documented within the O & M Manual. [District Rule 4621] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. Periodic maintenance inspections of the Phase I vapor recovery system shall include, at a minimum, verification that 1) the fill caps and vapor caps are not missing, damaged, or loose; 2) the fill cap gasket and vapor cap gaskets are not missing or damaged; 3) the fill adapter and vapor adapter are securely attached to the risers; 4) where applicable, the spring-loaded submerged fill tube seals properly against the coaxial tubing; 5) the dry break (poppet-valve) is not missing or damaged; and 6) the submerged fill tube is not missing or damaged. [District Rule 4621] Federally Enforceable Through Title V Permit
10. The permittee shall conduct all periodic vapor recovery system performance tests specified in this permit, no more than 30 days before or after the required compliance testing date, unless otherwise required under the applicable ARB Executive Order. [District Rule 4621] Federally Enforceable Through Title V Permit
11. The permittee shall perform and pass a Static Leak Test "Determination of Static Pressure Performance of Vapor Recovery Systems at Gasoline Dispensing Facilities with Aboveground Tanks" in accordance with the Executive Order specified in this permit for the Phase I Vapor Recovery System at least once every 36 months. [District Rule 4621] Federally Enforceable Through Title V Permit
12. A person conducting testing of, or repairs to, a certified vapor recovery system shall be in compliance with District Rule 1177 (Gasoline Dispensing Facility Tester Certification). [District Rule 4621] Federally Enforceable Through Title V Permit
13. A person performing installation of, or maintenance on, a certified Phase I vapor recovery system shall be certified by the ICC for Vapor Recovery System Installation and Repair, or work under the direct and personal supervision of an individual physically present at the work site who is certified. The ICC certification shall be renewed every 24 months. [District Rule 4621] Federally Enforceable Through Title V Permit
14. Proof of the ICC certification and all other certifications required by the Executive Order and installation and operation manual shall be made available onsite. [District Rule 4621] Federally Enforceable Through Title V Permit
15. The permittee shall notify the District at least 7 days prior to each performance test. The test results shall be submitted to the District no later than 30 days after the completion of each test. [District Rule 4621] Federally Enforceable Through Title V Permit
16. The permittee shall maintain monthly and annual gasoline throughput records. The records should allow the gasoline throughput for any 30-day period to be continuously determined. These records shall be maintained on the premises as long as exempt status is claimed. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
17. All records required by this permit shall be retained on-site for a period of at least five years and shall be made available for District inspection upon request. [District Rule 4621] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-10-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

CONFINED AND UNCONFINED ABRASIVE BLASTING OPERATION WITH A 6 CU. FT. CAPACITY CLEMCO MODEL 2452 BLASTING POT #1 VENTED TO A BLAST BOOTH (COMMON TO C- 447-10 THRU C-447-14) WITH A PAULI MODEL #CT BAGHOUSE DURING CONFINED BLASTING, AND WITH A CLEMCO MODEL AVS-50E ELECTRIC VACUUM

PERMIT UNIT REQUIREMENTS

1. All abrasive blasting shall be conducted within a permanent building unless steel or iron shot/grit is used exclusively, the item to be blasted exceeds 8 feet in any dimension, or the surface being blasted is situated at its permanent location or no further away from its permanent location than is necessary to allow the surface to be blasted. [92500 CCR]
2. Abrasive blasting operations conducted outside a permanent building which do not use steel or iron shot/grit exclusively shall use: wet abrasive blasting, hydroblasting, vacuum blasting, or abrasives certified by CARB for permissible dry outdoor blasting. [92500 CCR]
3. Abrasive blasting operations conducted outside a permanent building shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 2 or equivalent to 40% opacity. [92200 CCR]
4. Abrasive blasting operations conducted within the blast booth shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 1 or equivalent to 20% opacity. [92200 CCR]
5. A used certified abrasive shall not be considered certified for reuse unless the abrasive conforms to its original cut-point fineness. [92530 CCR]
6. All abrasive blasting shall be conducted in accordance with California Code of Regulations Title 17, Subchapter 6, Sections 92000 through 92540. [CCR]
7. When using an IC engine greater than 50 bhp to power an air compressor, the IC engine shall be registered or permitted. [District Rule 2010] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-11-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

CONFINED AND UNCONFINED ABRASIVE BLASTING OPERATION WITH A 6 CU. FT. CAPACITY CLEMCO MODEL 2452 BLAST POT #2, VENTED TO A BLAST BOOTH (COMMON TO C-447-10 THRU C-447-14) WITH A PAULI MODEL #CT BAGHOUSE DURING CONFINED BLASTING, AND A CLEMCO MODEL AVS-50E ELECTRIC VACUUM

PERMIT UNIT REQUIREMENTS

1. All abrasive blasting shall be conducted within a permanent building unless steel or iron shot/grit is used exclusively, the item to be blasted exceeds 8 feet in any dimension, or the surface being blasted is situated at its permanent location or no further away from its permanent location than is necessary to allow the surface to be blasted. [92500 CCR]
2. Abrasive blasting operations conducted outside a permanent building which do not use steel or iron shot/grit exclusively shall use: wet abrasive blasting, hydroblasting, vacuum blasting, or abrasives certified by CARB for permissible dry outdoor blasting. [92500 CCR]
3. Abrasive blasting operations conducted outside a permanent building shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 2 or equivalent to 40% opacity. [92200 CCR]
4. Abrasive blasting operations conducted within the blast booth shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 1 or equivalent to 20% opacity. [92200 CCR]
5. A used certified abrasive shall not be considered certified for reuse unless the abrasive conforms to its original cut-point fineness. [92530 CCR]
6. All abrasive blasting shall be conducted in accordance with California Code of Regulations Title 17, Subchapter 6, Sections 92000 through 92540. [CCR]
7. When using an IC engine greater than 50 bhp to power an air compressor, the IC engine shall be registered or permitted. [District Rule 2010] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-12-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

CONFINED AND UNCONFINED ABRASIVE BLASTING OPERATION WITH A 100 POUND CLEMCO MODEL 1440 BLAST POT #3, VENTED TO A BLAST BOOTH (COMMON TO C-447-10 THRU C-447-14) WITH A PAULI MODEL #CT BAGHOUSE DURING CONFINED BLASTING, AND A CLEMCO MODEL AVS-50E ELECTRIC VACUUM

PERMIT UNIT REQUIREMENTS

1. All abrasive blasting shall be conducted within a permanent building unless steel or iron shot/grit is used exclusively, the item to be blasted exceeds 8 feet in any dimension, or the surface being blasted is situated at its permanent location or no further away from its permanent location than is necessary to allow the surface to be blasted. [92500 CCR]
2. Abrasive blasting operations conducted outside a permanent building which do not use steel or iron shot/grit exclusively shall use: wet abrasive blasting, hydroblasting, vacuum blasting, or abrasives certified by CARB for permissible dry outdoor blasting. [92500 CCR]
3. Abrasive blasting operations conducted outside a permanent building shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 2 or equivalent to 40% opacity. [92200 CCR]
4. Abrasive blasting operations conducted within the blast booth shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 1 or equivalent to 20% opacity. [92200 CCR]
5. A used certified abrasive shall not be considered certified for reuse unless the abrasive conforms to its original cut-point fineness. [92530 CCR]
6. All abrasive blasting shall be conducted in accordance with California Code of Regulations Title 17, Subchapter 6, Sections 92000 through 92540. [CCR]
7. When using an IC engine greater than 50 bhp to power an air compressor, the IC engine shall be registered or permitted. [District Rule 2010] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-13-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

CONFINED AND UNCONFINED ABRASIVE BLASTING OPERATION WITH A 800 POUND CLEMCO MODEL L2463 BLASTING POT #4, VENTED TO A BLAST BOOTH (COMMON TO C-447-10 THRU C-447-14) WITH A PAULI MODEL #CT BAGHOUSE DURING CONFINED BLASTING, AND A CLEMCO MODEL AVS-50E ELECTRIC VACUUM

PERMIT UNIT REQUIREMENTS

1. All abrasive blasting shall be conducted within a permanent building unless steel or iron shot/grit is used exclusively, the item to be blasted exceeds 8 feet in any dimension, or the surface being blasted is situated at its permanent location or no further away from its permanent location than is necessary to allow the surface to be blasted. [92500 CCR]
2. Abrasive blasting operations conducted outside a permanent building which do not use steel or iron shot/grit exclusively shall use: wet abrasive blasting, hydroblasting, vacuum blasting, or abrasives certified by CARB for permissible dry outdoor blasting. [92500 CCR]
3. Abrasive blasting operations conducted outside a permanent building shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 2 or equivalent to 40% opacity. [92200 CCR]
4. Abrasive blasting operations conducted within the blast booth shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 1 or equivalent to 20% opacity. [92200 CCR]
5. A used certified abrasive shall not be considered certified for reuse unless the abrasive conforms to its original cut-point fineness. [92530 CCR]
6. All abrasive blasting shall be conducted in accordance with California Code of Regulations Title 17, Subchapter 6, Sections 92000 through 92540. [CCR]
7. When using an IC engine greater than 50 bhp to power an air compressor, the IC engine shall be registered or permitted. [District Rule 2010] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-14-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

CONFINED AND UNCONFINED ABRASIVE BLASTING OPERATION WITH A 500 POUND CLEMCO BLASTING POT #5, VENTED TO A BLAST BOOTH (COMMON TO C-447-10 THRU C-447 14) WITH A PAULI MODEL #CT BAGHOUSE DURING CONFINED BLASTING, AND A CLEMCO MODEL AVS-50E ELECTRIC VACUUM

PERMIT UNIT REQUIREMENTS

1. All abrasive blasting shall be conducted within a permanent building unless steel or iron shot/grit is used exclusively, the item to be blasted exceeds 8 feet in any dimension, or the surface being blasted is situated at its permanent location or no further away from its permanent location than is necessary to allow the surface to be blasted. [92500 CCR]
2. Abrasive blasting operations conducted outside a permanent building which do not use steel or iron shot/grit exclusively shall use: wet abrasive blasting, hydroblasting, vacuum blasting, or abrasives certified by CARB for permissible dry outdoor blasting. [92500 CCR]
3. Abrasive blasting operations conducted outside a permanent building shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 2 or equivalent to 40% opacity. [92200 CCR]
4. Abrasive blasting operations conducted within the blast booth shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 1 or equivalent to 20% opacity. [92200 CCR]
5. A used certified abrasive shall not be considered certified for reuse unless the abrasive conforms to its original cut-point fineness. [92530 CCR]
6. All abrasive blasting shall be conducted in accordance with California Code of Regulations Title 17, Subchapter 6, Sections 92000 through 92540. [CCR]
7. When using an IC engine greater than 50 bhp to power an air compressor, the IC engine shall be registered or permitted. [District Rule 2010] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-16-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

METAL PARTS AND PRODUCTS COATING OPERATION WITH HVLP SPRAY GUN(S), PAINT BOOTH WITH DRY EXHAUST FILTERS AND SPRAY GUN CLEANER

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Exhaust fans shall be switched on prior to the start of paint spraying operations. [District NSR Rule] Federally Enforceable Through Title V Permit
3. All filters shall be properly maintained and must be in place during the painting operation. [District NSR Rule] Federally Enforceable Through Title V Permit
4. All coating operations shall be conducted inside the paint spray booth. [District NSR Rule] Federally Enforceable Through Title V Permit
5. VOC content of any coatings as applied, excluding water and exempt compounds, used for any metal parts or product shall not exceed any of the following limits, except as allowed elsewhere in this permit: baked coating 275 g/l (2.3 lb/gal), air-dried coating: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of more than 45.6 centistokes at 78 °F or an average dry-film thickness of greater than 2.0 millimeters: 340 g/l (2.8 lb/gal), air-dried dip coating of steel joists with coating viscosity, as applied, of less than or equal to 45.6 centistokes at 78 °F or an average dry-film thickness of less than or equal to 2.0 millimeters: 400 g/l (3.32 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
6. VOC content of baked specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 360 g/l (3.0 lb/gal), extreme performance: 360 g/l (3.0 lb/gal), heat resistant: 360 g/l (3.0 lb/gal), high gloss: 360 g/l (3.0 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 360 g/l (3.0 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 360 g/l (3.0 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 360 g/l (3.0 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
7. VOC content of air-dried specialty coatings as applied, excluding water and exempt compounds, used for metal parts or product shall not exceed any of the following limits: camouflage 420 g/l (3.5 lb/gal), extreme performance: 420 g/l (3.5 lb/gal), heat resistant: 420 g/l (3.5 lb/gal), high gloss: 420 g/l (3.5 lb/gal), high performance architectural: 420 g/l (3.5 lb/gal), high temperature: 420 g/l (3.5 lb/gal), metallic coating: 420 g/l (3.5 lb/gal), pretreatment coating: 420 g/l (3.5 lb/gal), touch up and repair coating: 420 g/l (3.5 lb/gal), silicone release: 420 g/l (3.5 lb/gal), solar absorbent: 420 g/l (3.5 lb/gal), and solid film lubricant: 880 g/l (7.3 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
8. Only HVLP, electrostatic, electrodeposition, flow, roll, dip, brush or continuous coating application equipment shall be used, and the application equipment shall be operated in accordance with the manufacturer's recommendations [District Rule 4603] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-16-3 : May 19 2017 8:37AM -- BROWND

9. If an HVLP spray gun is used, the operator must demonstrate that the spray gun operates between 0.1 and 10 pounds per square inch, gauge, (psig) air atomizing pressure, measured dynamically at the center of the air cap and at the air horns. For a gun permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall either be in the form of manufacturer's published technical information or by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. For a gun not permanently labeled HVLP by the manufacturer, a satisfactory demonstration shall be based on manufacturer's published technical material and by a demonstration of the operation of the gun using an air pressure tip gauge from the manufacturer of the gun. [District Rule 4603] Federally Enforceable Through Title V Permit
10. An operator of a metal parts products coating operation shall minimize VOC emissions by complying with the following work practice standards: store all VOC-containing coatings, thinners, cleaning materials, and waste materials in closed non-absorbent and non-leaking containers, keeping the containers closed except when specifically in use; close mixing vessels that contain VOC coatings and other materials, except when specifically in use; minimize spill of any VOC-containing materials and clean up spills immediately; and convey VOC-containing materials in closed containers or pipes. [District Rule 4603] Federally Enforceable Through Title V Permit
11. An operator shall store or dispose of fresh or spent, solvents, waste solvent cleaning materials such as cloth, paper, etc, coatings, adhesives, catalysts, and thinners in closed, non-absorbent and non-leaking containers, keeping the containers closed at all times except when depositing or removing the contents of the containers or when the container is empty. [District Rule 4603] Federally Enforceable Through Title V Permit
12. VOC content of solvents used shall not exceed any of the following limits: product cleaning during manufacturing process or surface preparation for coating application: 25 g/l (0.21 lb/gal), repair and maintenance cleaning 25 g/l (0.21 lb/gal), and cleaning of coating application equipment: 25 g/l (0.21 lb/gal). [District Rule 4603] Federally Enforceable Through Title V Permit
13. Daily emissions from the paint spray booth shall not exceed 73.5 lb VOC/day or 16.8 lb PM10/day. [District NSR Rule] Federally Enforceable Through Title V Permit
14. Annual emissions from the paint spray booth shall not exceed 5.5 tons VOC/year or 1.3 tons PM10/year averaged over a 12 month rolling period. [District NSR Rule] Federally Enforceable Through Title V Permit
15. Each container or accompanying data sheet of any coating subject to this rule shall display; the maximum VOC content of the coating, as applied, and after any thinning as recommended by the manufacturer in grams of VOC per liter of coating (less water and exempt compounds), a statement of the manufacturer's recommendation regarding thinning of the coating, the name of the solvent, manufacturer's name, and the VOC content, and density of the solvent, as supplied. [District Rule 4603] Federally Enforceable Through Title V Permit
16. The permittee shall maintain a current list of coatings and solvents in use which contains all of the coating data necessary to evaluate compliance, including the following information: mix ratio of components used, VOC content and specific chemical constituents of coatings as applied, and VOC content and specific chemical constituents of solvents used for surface preparation and cleanup. [District Rule 4603] Federally Enforceable Through Title V Permit
17. Permittee shall maintain daily records which include the following information: volume coating/solvent mix ratio, VOC content (lb/gal or grams/liter) and, for dip coating operations, viscosity (cSt) of coating, volume of each coating used (gallons), and quantity of cleanup solvent used (gallons). [District Rule 4603] Federally Enforceable Through Title V Permit
18. Records shall be retained on-site for a minimum of five years and made available for District inspection upon request. [District Rule 4603] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-17-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

200 HP CONFINED ABRASIVE BLASTING OPERATION WITH A 100 LB TRINCO BLASTING POT SERVED BY A TRINCO DUST COLLECTOR

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 4102]
2. The blasting operations shall be carried out in a manner to prevent any nuisances. [District Rule 4102]
3. All abrasive blasting shall be conducted in accordance with California Code of Regulations Title 17, Subchapter 6, Sections 92000 through 92540. [92000 through 92540 CCR]
4. A used certified abrasive shall not be considered certified for reuse unless the abrasive conforms to its original cut-point fineness. [92530 CCR]
5. Abrasive blasting operations conducted within the blasting cabinet shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 1 or equivalent to 20% opacity. [92200 CCR]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-18-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

200 HP CONFINED ABRASIVE BLASTING OPERATION WITH A 100 LB CYCLONE BLASTING SYSTEMS BLASTING POT SERVED BY CYCLONE BLASTING SYSTEM DUST COLLECTOR

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 4102]
2. The blasting operations shall be carried out in a manner to prevent any nuisances. [District Rule 4102]
3. All abrasive blasting shall be conducted in accordance with California Code of Regulations Title 17, Subchapter 6, Sections 92000 through 92540. [92000 through 92540 CCR]
4. A used certified abrasive shall not be considered certified for reuse unless the abrasive conforms to its original cut-point fineness. [92530 CCR]
5. Abrasive blasting operations conducted within the blasting cabinet shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 1 or equivalent to 20% opacity. [92200 CCR]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-19-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

200 HP UNCONFINED ABRASIVE BLASTING OPERATION WITH A 100 LB CLEMCO BLASTING POT #7

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 4102]
2. The blasting operations shall be carried out in a manner to prevent any nuisances. [District Rule 4102]
3. All abrasive blasting shall be conducted in accordance with California Code of Regulations Title 17, Subchapter 6, Sections 92000 through 92540. [92000 through 92540 CCR]
4. A used certified abrasive shall not be considered certified for reuse unless the abrasive conforms to its original cut-point fineness. [92530 CCR]
5. Unconfined abrasive blasting operations shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 2 or equivalent to 40% opacity. [92200 CCR]
6. Abrasive blasting shall be conducted within a permanent building unless steel or iron shot/grit is used. [92500 CCR]
7. Abrasive blasting of items exceeding 8 feet in any dimension, or of a surface situated at its permanent location, or no further away from its permanent location than is necessary to allow the surface to be blasted, may be performed outside a permanent building only if one of the following is used: steel or iron shot/grit; abrasives certified by CARB for permissible dry outdoor blasting; wet abrasive blasting, hydroblasting; or vacuum blasting. [92500 CCR]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-20-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

200 HP UNCONFINED ABRASIVE BLASTING OPERATION WITH A 200 LB PAULE & GIFFIN BLASTING POT

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 4102]
2. The blasting operations shall be carried out in a manner to prevent any nuisances. [District Rule 4102]
3. All abrasive blasting shall be conducted in accordance with California Code of Regulations Title 17, Subchapter 6, Sections 92000 through 92540. [92000 through 92540 CCR]
4. A used certified abrasive shall not be considered certified for reuse unless the abrasive conforms to its original cut-point fineness. [92530 CCR]
5. Unconfined abrasive blasting operations shall not discharge air contaminants into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark or darker than Ringelmann 2 or equivalent to 40% opacity. [92200 CCR]
6. Abrasive blasting shall be conducted within a permanent building unless steel or iron shot/grit is used. [92500 CCR]
7. Abrasive blasting of items exceeding 8 feet in any dimension, or of a surface situated at its permanent location, or no further away from its permanent location than is necessary to allow the surface to be blasted, may be performed outside a permanent building only if one of the following is used: steel or iron shot/grit; abrasives certified by CARB for permissible dry outdoor blasting; wet abrasive blasting, hydroblasting; or vacuum blasting. [92500 CCR]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-21-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

GASOLINE DISPENSING OPERATION WITH ONE 1,000 GALLON SUPERVAULT FL MODEL ABOVEGROUND STORAGE TANK SERVED BY TWO-POINT OPW EVR PHASE I VAPOR RECOVERY SYSTEM (VR-401-B), ONE FUELING POINT WITH ONE GASOLINE DISPENSING NOZZLE SERVED BY BALANCE PHASE II VAPOR RECOVERY SYSTEM (G-70-132-B), AND STANDING LOSS CONTROL (VR-301-D)

PERMIT UNIT REQUIREMENTS

1. The Phase I, Phase II, and Standing Loss Control Vapor recovery systems shall be installed and maintained in accordance with the manufacturer specifications and the ARB Executive Orders specified in this permit, including applicable rules and regulations of the Division of Measurement Standards of the Department of Food and Agriculture, the Office of the State Fire Marshal of the Department of Forestry and Fire Protection, the Division of Occupational Safety and Health of the Department of Industrial Relations, and the Division of Water Quality of the State Water Resources Control Board that have been made conditions of the certification. [District Rules 4621 and 4622 and CH&SC 41950] Federally Enforceable Through Title V Permit
2. This gasoline storage and dispensing equipment shall not be used in retail sales, where gasoline dispensed by the unit is subject to payment of California sales tax on gasoline sales. [District Rule 4622] Federally Enforceable Through Title V Permit
3. The storage container(s) shall be installed, maintained, and operated such that they are leak-free. [District Rule 4621] Federally Enforceable Through Title V Permit
4. The Phase I and Phase II vapor recovery systems and gasoline dispensing equipment shall be maintained without leaks as determined in accordance with the test method specified in this permit. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
5. A leak is defined as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration of total organic compound greater than 10,000 ppmv, as methane, above background when measured in accordance with EPA Test Method 21. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
6. No gasoline delivery vessel shall be operated or be allowed to operate unless valid State of California decals are displayed on the cargo container, which attest to the vapor integrity of the container. [District Rule 4621] Federally Enforceable Through Title V Permit
7. No person shall operate any ARB certified Phase II vapor recovery system or any portion thereof that has a major defect or an equipment defect that is identified in any applicable ARB Executive Order until the following conditions have been met: 1) the defect has been repaired, replaced, or adjusted as necessary to correct the defect; 2) the District has been notified, and the District has reinspected the system or authorized the system for use (such authorization shall not include the authority to operate the equipment prior to the correction of the defective components); and 3) all major defects, after repair, are duly entered into the Operations and Maintenance (O&M) manual. [District Rule 4622] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-21-2 : May 19 2017 8:37AM -- BROWN

8. Upon identification of any major defects, the permittee shall tag "Out-of-Order" all dispensing equipment for which vapor recovery has been impaired. Tagged equipment shall be rendered inoperable and the tag(s) shall not be removed until the defective equipment has been repaired, replaced, or adjusted, as necessary. In the case of defects identified by the District, tagged equipment shall be rendered inoperable, and the tag shall not be removed until the District has been notified of the repairs, and the District has either reinspected the system or authorized the tagged equipment for use. [District Rule 4622] Federally Enforceable Through Title V Permit
9. The permittee shall implement a periodic maintenance inspection program for the certified Phase II vapor recovery system consistent with the requirements of this permit. The program shall be documented in an operation and maintenance (O&M) manual and shall at a minimum contain the following information: 1) copies of all vapor recovery performance tests; 2) all applicable ARB Executive Orders, Approval Letters, and District Permits; 3) the manufacturer's specifications and instructions for installation, operation, repair, and maintenance required pursuant to ARB Certification Procedure CP-201, and any additional instruction provided by the manufacturer; 4) system and/or component testing requirements, including test schedules and passing criteria for each of the standard tests required by this permit (the owner/operator may include any non-ARB required diagnostic and other tests as part of the testing requirements), and 5) additional O&M instructions, if any, that are designed to ensure compliance with the applicable rules, regulations, ARB Executive Orders, and District permit conditions, including replacement schedules for failure or wear prone components. [District Rule 4622] Federally Enforceable Through Title V Permit
10. The permittee shall conduct periodic maintenance inspections based on the greatest monthly throughput of gasoline dispensed by the facility in the previous year as follows: A) less than 2,500 gallons - one day per month; B) 2,500 to less than 25,000 gallons - one day per week; or C) 25,000 gallons or greater - five days per week. All inspections shall be documented within the O & M Manual. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
11. Periodic maintenance inspections of the Phase I vapor recovery system shall include, at a minimum, verification that 1) the fill caps and vapor caps are not missing, damaged, or loose; 2) the fill cap gasket and vapor cap gaskets are not missing or damaged; 3) the fill adapter and vapor adapter are securely attached to the risers; 4) where applicable, the spring-loaded submerged fill tube seals properly against the coaxial tubing; 5) the dry break (poppet-valve) is not missing or damaged; and 6) the submerged fill tube is not missing or damaged. [District Rule 4621] Federally Enforceable Through Title V Permit
12. Periodic maintenance inspections of the Phase II vapor recovery system shall include, at a minimum, verification that 1) the following nozzle components are in place and in good condition as specified in ARB Executive Order as applicable: faceplate/facecone, bellows, latching device spring, vapor check valve, spout (proper diameter/vapor collection holes), insertion interlock mechanism, automatic shut-off mechanism, and hold open latch (unless prohibited by law or the local fire control authority); 2) the hoses are not torn, flattened or crimped; 3) the vapor path of the coaxial hoses associated with bellows equipped nozzles does not contain more than 100 ml of liquid if applicable; and 4) the vapor processing unit is functioning properly, for operations that are required to have or possess such a unit. [District Rule 4622] Federally Enforceable Through Title V Permit
13. In the event of a separation due to a drive off, the permittee shall, unless otherwise specified in the applicable ARB Executive Order, conduct a visual inspection of the affected equipment and either 1) perform qualified repairs on any damaged components and conduct applicable re-verification tests pursuant to the requirements of this permit, or 2) replace the affected nozzles, coaxial hoses, breakaway couplings, and any other damaged components with new or certified rebuilt components that are ARB certified. The activities shall be documented in accordance with the requirements of this permit before placing the affected equipment back in service. [District Rule 4622] Federally Enforceable Through Title V Permit
14. The gasoline throughput for this permit unit shall not exceed 657,000 gallons in any one calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit
15. The permittee shall conduct all periodic vapor recovery system performance tests specified in this permit, no more than 30 days before or after the required compliance testing date, unless otherwise required under the applicable ARB Executive Order. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

16. The permittee shall perform and pass a Static Leak Test "Determination of Static Pressure Performance of Vapor Recovery Systems at Gasoline Dispensing Facilities with Aboveground Tanks" in accordance with the Executive Order specified in this permit for the Phase I Vapor Recovery System at least once every 12 months. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
17. If a rotatable Phase I vapor adaptor is installed, the permittee shall perform and pass a Static Torque of Rotatable Phase I Adaptors test using ARB procedure TP-201.1B at least once every 36 months. [District Rule 4621] Federally Enforceable Through Title V Permit
18. For certified Phase II vapor recovery systems with liquid removal devices, the permittee shall perform and pass an ARB TP-201.6C Liquid Removal Test whenever the liquid in the vapor path exceeds 100 ml of liquid, or as required by the applicable ARB Executive Order. The amount of liquid in the vapor path shall be measured by lowering the gasoline dispensing nozzle into a container until such time that no more liquid drains from the nozzle. The amount of liquid drained into the container shall be measured using a graduated cylinder or graduated beaker. The vapor path shall be inspected according to the monitoring frequency as determined by monthly gasoline throughput. [District Rule 4622] Federally Enforceable Through Title V Permit
19. A person conducting testing of, or repairs to, a certified vapor recovery system shall be in compliance with District Rule 1177 (Gasoline Dispensing Facility Tester Certification). [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
20. A person performing installation of, or maintenance on, a certified Phase I or Phase II vapor recovery system shall be certified by the ICC for Vapor Recovery System Installation and Repair, or work under the direct and personal supervision of an individual physically present at the work site who is certified. The ICC certification shall be renewed every 24 months. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
21. Proof of the ICC certification and all other certifications required by the Executive Order and installation and operation manual shall be made available onsite. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
22. The permittee shall notify the District at least 7 days prior to each performance test. The test results shall be submitted to the District no later than 30 days after the completion of each test. [District Rule 4621] Federally Enforceable Through Title V Permit
23. The permittee shall maintain a copy of all test results. The test results shall be dated and shall contain the name, address, and telephone number of the company responsible for system installation and testing. [District Rule 4622] Federally Enforceable Through Title V Permit
24. The permittee shall maintain on the premises a log of any repairs made to the certified Phase I or Phase II vapor recovery system. The repair log shall include the following: 1) date and time of each repair; 2) the name and applicable certification numbers of the person(s) who performed the repair, and if applicable, the name, address and phone number of the person's employer; 3) description of service performed; 4) each component that was repaired, serviced, or removed; 5) each component that was installed as replacement, if applicable; and 6) receipts or other documents for parts used in the repair and, if applicable, work orders which shall include the name and signature of the person responsible for performing the repairs. [District Rule 4622] Federally Enforceable Through Title V Permit
25. The O&M manual shall be kept at the dispensing operation and made available to any person who operates, inspects, maintains, repairs, or tests the equipment at the operation as well as to District personnel upon request. [District Rule 4622] Federally Enforceable Through Title V Permit
26. Only white paint, listed in the Executive Order specified in this permit for the Standing Loss Control System, shall be applied to the tank. The surface of the tank shall be prepared and the white paint shall be applied per manufacturer's specification. [District Rule 4621] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

27. The permittee shall maintain the following records: 1) receipt of sale that demonstrates the purchase date and amount of white paint purchased, 2) record of the name of personnel applying white paint to include the date of application, surface preparation description (i.e. scraping, sanding, abrasive blasting, primer etc.), method of application (i.e. brush, roller, air/airless sprayer), average ambient temperature (øF) during application, and atmospheric observations during application (i.e. sunny, cloudy, rain, etc.), 3) record of the name of personnel that installed the P/V vent valve, and 4) Technical Data Sheet and/or Material Safety Data Sheet of the white paint that describes the surface preparation, application, and material safety of the white paint. [District Rule 4621] Federally Enforceable Through Title V Permit
28. The permittee shall maintain monthly and annual gasoline throughput records. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
29. All records required by this permit shall be retained on-site for a period of at least five years and shall be made available for District inspection upon request. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-23-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

TRANSPORTABLE 138 BHP DEUTZ MODEL TCD 2012L04 2V SERIAL NO. 10603992 TIER 3 CERTIFIED DIESEL-FIRED IC ENGINE POWERING A 100 TON/HOUR POWERSCREEN MODEL TROMMEL 830 ROTARY SCREEN

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Visible emissions from the screen shall not exceed 5% opacity for a period or periods aggregating more than three minutes in any one hour. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
4. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
5. This engine shall be equipped with an operational nonresettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
6. Engine operations shall not exceed 18 hours/day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Operation of this engine shall not exceed 1,000 hours per year. [District Rule 2201] Federally Enforceable Through Title V Permit
8. This transportable nonroad engine shall not be operated at one location for more than 12 consecutive months and shall meet all the requirements of a transportable nonroad engine, per CFR Title 40 Part 89. [17 CCR 93116]
9. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801 and 17 CCR 93116] Federally Enforceable Through Title V Permit
10. Emissions from the IC engine shall not exceed any of the following limits: 2.72 g-NOx/bhp-hr, 0.67 g-CO/bhp-hr, or 0.19 g-VOC/bhp-hr. [District Rules 2201 and 4702] Federally Enforceable Through Title V Permit
11. Emissions from the IC engine shall not exceed 0.05 g-PM10/bhp-hr based on USEPA certification using ISO 8178 test procedure. [District Rules 2201 and 4702 and 17 CCR 93116] Federally Enforceable Through Title V Permit
12. PM10 emissions from the Trommel screen shall not exceed 0.0022 lb/ton. [District Rule 2201] Federally Enforceable Through Title V Permit
13. During periods of operation, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
14. The owner/operator shall maintain an engine operating log to demonstrate compliance. The engine operating log shall include, on a monthly basis, the following information: total hours of operation, type of fuel used, maintenance or modifications performed, monitoring data, and any other information necessary to demonstrate compliance. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

15. The permittee shall maintain records of daily and annual hours of operation. [District Rule 2201] Federally Enforceable Through Title V Permit
16. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-23-1 : May 19 2017 8:37AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-27-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

105,179 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 12 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-28-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

105,043 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 13 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-29-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

105,306 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 14 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-30-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

54,680 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION; AND WINE, SPIRITS, HIGH PROOF SPIRITS/ALCOHOL, OR BRANDY STORAGE TANK 509 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-31-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

54,668 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION; AND WINE, SPIRITS, HIGH PROOF SPIRITS/ALCOHOL, OR BRANDY STORAGE TANK 510 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-32-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

54,672 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION; AND WINE, SPIRITS, HIGH PROOF SPIRITS/ALCOHOL, OR BRANDY STORAGE TANK 511 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-33-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

54,668 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION; AND WINE, SPIRITS, HIGH PROOF SPIRITS/ALCOHOL, OR BRANDY STORAGE TANK 512 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-34-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

102,087 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1001 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-35-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

101,870 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1002 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-36-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

102,253 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1003 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-37-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

102,253 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1004 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-38-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

102,175 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1005 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-39-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

102,235 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1006 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-40-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

102,211 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1007 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-41-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

102,968 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1008 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-42-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

102,262 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1009 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-43-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

103,122 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1010 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-44-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

103,146 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1011 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-45-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

103,080 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1012 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-46-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

105,264 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1501 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-47-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

105,259 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1502 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-48-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

105,284 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1503 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-49-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

105,100 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1504 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-50-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

105,215 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1505 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-51-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

105,011 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1506 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-52-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

105,287 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1507 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-53-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

105,054 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1508 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-54-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

105,194 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1509 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-55-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

105,021 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1510 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-56-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

212,026 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2001 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-57-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

212,468 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2002 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-58-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

212,151 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2003 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-59-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

212,120 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2004 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-60-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,917 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2005 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-61-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

212,275 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2006 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-62-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,691 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2007 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-63-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

212,254 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2008 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-64-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

212,766 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2009 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-65-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

214,253 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION; AND WINE, SPIRITS, HIGH PROOF SPIRITS/ALCOHOL, OR BRANDY STORAGE TANK 2010 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-66-3

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

213,963 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION; AND WINE, SPIRITS, HIGH PROOF SPIRITS/ALCOHOL, OR BRANDY STORAGE TANK 2011 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-67-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

214,245 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2012 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-68-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

214,528 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2013 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-69-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

214,325 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2014 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-70-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

214,301 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2015 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-71-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

214,236 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2016 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-72-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

213,126 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2501 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-73-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

213,596 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2502 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-74-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

213,687 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2503 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-75-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

213,298 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2504 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-76-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

213,018 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2505 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-77-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

213,471 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2506 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-78-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

213,296 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2507 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-79-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

213,411 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2508 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-80-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,766 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2509 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-81-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,311 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2510 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-82-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,316 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2511 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-83-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,260 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2512 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-84-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,748 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2513 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-85-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,712 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2514 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-86-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,422 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2515 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-87-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,573 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2516 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-88-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,633 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2517 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-89-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,487 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2518 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-90-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,378 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2519 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-91-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,658 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2520 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-92-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,732 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2521 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-93-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,788 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2522 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-94-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,189 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2523 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-95-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

211,962 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2524 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-96-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

207,390 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2922

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-96-2 : May 19 2017 8:38AM -- BROWN

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-97-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

207,909 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2923

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-97-2 : May 19 2017 8:38AM -- BROWN

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-98-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

207,676 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2924

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-98-2 : May 19 2017 8:38AM -- BROWN

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-99-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

208,185 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2925

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-99-2 : May 19 2017 8:38AM -- BROWN

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-100-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

207,571 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2926

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-100-2 : May 19 2017 8:38AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-101-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

208,168 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2927

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-101-2 : May 19 2017 8:38AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-102-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

207,821 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2928

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-102-2 : May 19 2017 8:38AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-103-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

207,140 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2929

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-103-2 : May 19 2017 8:38AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-104-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

206,695 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2930

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-104-2 : May 19 2017 8:38AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-105-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

207,451 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2931

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-105-2 : May 19 2017 8:38AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-106-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

206,832 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2932

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-106-2 : May 19 2017 8:38AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-107-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

207,270 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2933

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-107-2 : May 19 2017 8:38AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-108-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

208,117 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2934

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-108-2 : May 19 2017 8:38AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-109-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

208,202 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2935

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-109-2 : May 19 2017 8:38AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-110-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

206,996 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2936

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-110-2 : May 19 2017 8:38AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-111-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

207,039 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2937

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-111-2 : May 19 2017 8:38AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-112-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

206,757 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2938

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-112-2 : May 19 2017 8:38AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-113-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

207,752 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2939

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-113-2 : May 19 2017 8:38AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-114-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

207,369 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2940

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-114-2 : May 19 2017 8:38AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-115-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

208,795 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2941

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-115-2 : May 19 2017 8:38AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-116-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

208,928 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2942

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-116-2 : May 19 2017 8:38AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-117-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

329,824 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3013 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-118-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

329,868 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3014 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-119-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,674 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6013 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-120-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,066 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6014 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-121-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,494 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6015 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-122-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,303 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6016 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-123-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,934 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6017 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-124-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,604 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6018 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-125-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,738 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6019 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-126-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,964 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6020 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-127-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,070 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6021 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-128-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,248 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6022 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-129-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,965 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6023 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-130-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,756 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6024 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-131-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,656 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6025 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-132-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

640,805 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6026 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-133-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,489 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6027 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-134-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,896 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6028 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-135-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,208 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6029 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-136-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,378 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6030 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-137-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,676 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6031 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-138-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,762 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6032 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-139-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,796 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6033 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-140-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

644,594 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6034 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-141-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,126 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6035 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-142-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,874 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6036 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-143-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,803 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6037 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-144-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,307 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6038 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-145-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,509 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6039 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-146-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,199 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6040 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-147-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

644,851 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6041 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-148-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,555 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6042 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-149-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,690 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6043 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-150-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,940 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6044 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-151-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

644,141 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6045 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-152-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,365 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6046 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-153-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,506 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6047 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-154-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,192 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6048 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-155-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,544 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6049 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-156-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,863 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6050 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-157-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

645,153 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6051 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-158-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,894 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6052 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-159-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,374 GALLON STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6053 WITH
PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-160-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,400 GALLON STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6054 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-161-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,257 GALLON STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6055 WITH
PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-162-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,277 GALLON STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6056 WITH
PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-163-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,867 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6501 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-164-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,338 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6502 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-165-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,222 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6503 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-166-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,763 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6504 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-167-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,501 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6505 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-168-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,658 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6506 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-169-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,620 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6507 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-170-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,526 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6508 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-171-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,178 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6509 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-172-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,090 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6510 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-173-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,542 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6511 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-174-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,788 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6512 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-175-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

640,725 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6513 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-176-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,118 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6514 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-177-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

640,772 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6515 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-178-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,295 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6516 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-179-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,491 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6517 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-180-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,051 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6518 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-181-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,451 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6519 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-182-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,094 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6520 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-183-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,344 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6521 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-184-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,245 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6522 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-185-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,156 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6523 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-186-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,595 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6524 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-187-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,871 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6526 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-188-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

639,880 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6527 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-189-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,428 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6528 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-190-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,193 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6529 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-191-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,592 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6601 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-192-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

643,295 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6602 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-193-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

640,961 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6603 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-194-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

640,434 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6604 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-195-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,594 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6609 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-196-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,115 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6610 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-197-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,345 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6611 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-198-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,629 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6612 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-199-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

640,936 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6617 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-200-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,121 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6618 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-201-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,720 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6619 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-202-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,051 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6620 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-203-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

640,612 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6625 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-204-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,491 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6626 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-205-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,974 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6627 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-206-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

642,792 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6628 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-207-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

640,729 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6633 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-208-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,378 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6634 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-209-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,008 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6641 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-210-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

639,975 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6642 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-211-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

640,530 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6649 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-212-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

640,872 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6650 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-213-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,462 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6657 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-214-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

641,263 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6658 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, and uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-215-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

650,472 GALLON STEEL WINE AND DISTILLED SPIRITS STORAGE TANK 6002 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-216-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

670,445 GALLON STEEL WINE AND DISTILLED SPIRITS STORAGE TANK 6005 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-217-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

661,423 GALLON STEEL WINE AND DISTILLED SPIRITS STORAGE TANK 6006 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-218-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

661,075 GALLON STEEL WINE AND DISTILLED SPIRITS STORAGE TANK 6007 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-219-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

669,320 GALLON STEEL WINE AND DISTILLED SPIRITS STORAGE TANK 6008 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-220-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

661,577 GALLON STEEL WINE AND DISTILLED SPIRITS STORAGE TANK 6009 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-221-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

661,634 GALLON STEEL WINE AND DISTILLED SPIRITS STORAGE TANK 6010 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-222-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

662,596 GALLON STEEL WINE AND DISTILLED SPIRITS STORAGE TANK 6011 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-223-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

669,445 GALLON STEEL WINE AND DISTILLED SPIRITS STORAGE TANK 6012 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-224-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

639,424 GALLON STEEL INSULATED WINE STORAGE TANK #6629 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
5. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-225-4

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

WINERY WASTEWATER PRETREATMENT AND EQUALIZATION OPERATION SERVED BY A SIEMENS ZABOCS BIOFILTER SHARED WITH C-447-226 AND -227

PERMIT UNIT REQUIREMENTS

1. The pre-acidification tank shall be enclosed and vented to the biofilter. [District Rules 2201 and 4102] Federally Enforceable Through Title V Permit
2. The recycle tank shall be enclosed and vented to the biofilter and/or sulfide oxidation tank. [District Rules 2201 and 4102] Federally Enforceable Through Title V Permit
3. The concentration of H₂S in the exhaust from the biofilter shall not exceed 5 ppmv. [District Rules 2201 and 4102] Federally Enforceable Through Title V Permit
4. Permittee shall follow the manufacturer's recommended monitoring and maintenance program for the biofilter. [District Rules 2201 and 4102] Federally Enforceable Through Title V Permit
5. Permittee shall maintain monthly records of the inlet and outlet exhaust H₂S concentration. The records shall be retained, maintained on-site for at least five years and made available for District inspection upon request. [District Rule 1070]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-226-12

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

175,320 GALLON WINERY WASTEWATER ANAEROBIC REACTOR SERVED BY A BIOGAS SCRUBBING SYSTEM SHARED WITH C-447-227 AND VENTED TO AN ENCLOSED 39.4 MMBTU/HR VAREC 244EGF FLARE OR BOILERS C-447-1, '2, '3, '295, OR '329, AND 502,000 GALLON WINERY WASTEWATER SULFIDE OXIDATION TANK

PERMIT UNIT REQUIREMENTS

1. The primary chamber of the anaerobic reactor shall be enclosed and vented to the biofilter listed on C-447-225. [District Rule 4102]
2. Oxygen content of the effluent in the sulfide oxidation tank shall be maintained at a level sufficient to prevent nuisance odors. [District Rule 4102]
3. Emission rates from the flare shall not exceed any of the following limits: NO_x (as NO₂) - 0.06 lb/MMBtu; VOC (as methane) - 0.002 lb/MMBtu; CO - 0.3 lb/MMBtu; or PM₁₀ - 0.008 lb/MMBtu. [District Rules 2201 and 4311] Federally Enforceable Through Title V Permit
4. The H₂S scrubber shall be in operation whenever biogas is produced in the anaerobic reactors. [District Rule 2201] Federally Enforceable Through Title V Permit
5. H₂S content of the scrubbed biogas shall not exceed 50 ppmv. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Biogas flow rate to the flare shall not exceed 481,900 scf per day. [District Rules 2201 and 4311] Federally Enforceable Through Title V Permit
7. Biogas production shall not exceed any of the following: 1st quarter - 31,670,000 scf, 2nd quarter - 31,800,300 scf, 3rd quarter - 83,115,800 scf, 4th quarter 83,115,800 scf. [District Rule 2201] Federally Enforceable Through Title V Permit
8. A flame shall be present in the flare at all times when combustible gases are vented through the flare. [District Rule 4311] Federally Enforceable Through Title V Permit
9. The outlet shall be equipped with an automatic ignition system, or, shall be operated with a pilot flame present at all times when combustible gases are vented through the flare, except during purge periods for automatic-ignition equipped flares. [District Rule 4311] Federally Enforceable Through Title V Permit
10. Except for flares equipped with a flow-sensing ignition system, a heat sensing device such as a thermocouple, ultraviolet beam sensor, infrared sensor, or an equivalent device capable of continuously detecting at least one pilot flame or the flare flame is present shall be installed and operated. The flame detection device shall be kept operational at all times except during flare maintenance when the flare is isolated from gas flow. During essential planned power outages when the flare is operating, the pilot monitor is allowed to be non-functional if the flare flame is clearly visible to onsite operators. All pilot monitor downtime shall be reported annually pursuant to Rule 4311, Section 6.2.3.6. [District Rule 4311] Federally Enforceable Through Title V Permit
11. Flaring is prohibited unless it is consistent with an approved flare minimization plan (FMP), pursuant to Section 6.5, and all commitments listed in that plan have been met. This standard does not apply if the APCO determines that the flaring is caused by an emergency as defined by Section 3.7 and is necessary to prevent an accident, hazard or release of vent gas directly to the atmosphere. [District Rule 4311] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. The operator shall monitor and record the vent gas flow to the flare with a flow measuring device or other parameters as specified in the Permit to Operate. [District Rule 4311] Federally Enforceable Through Title V Permit
13. Source testing to measure NO_x and VOC emissions from the flare shall be conducted at least once every twelve (12) months. [District Rule 4311] Federally Enforceable Through Title V Permit
14. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
15. The following test methods shall be used: VOC - EPA Method 25, except when the outlet concentration must be below 50 ppm to meet the standard, in which case Method 25a may be used; exempt compounds - EPA Method 18 or ARB Method 422; NO_x (lb/MMBtu) - EPA Method 19; NO_x and O₂ (concentrations) - EPA Method 3A, EPA Method 7E, or ARB 100. [District Rule 4311] Federally Enforceable Through Title V Permit
16. The results of each source test shall be submitted to the District within 45 days thereafter. [District Rules 1081 and 4311] Federally Enforceable Through Title V Permit
17. H₂S content of the exhaust from the biological reactor serving the scrubber shall not exceed 1 ppmv. [District Rule 2201] Federally Enforceable Through Title V Permit
18. Residual dissolved oxygen level in the sulfide oxidation tank shall not fall below 1 milligram per liter. [District Rules 2201 and 4102] Federally Enforceable Through Title V Permit
19. Permittee shall monitor the H₂S content of the biogas at the inlet and at the outlet of the scrubber on a weekly basis. If the outlet H₂S concentration does not exceed 50 ppmv for four consecutive weeks, monitoring may be conducted on a monthly basis. If the H₂S concentration at the outlet exceeds 50 ppmv, weekly monitoring shall resume. [District Rule 2201] Federally Enforceable Through Title V Permit
20. Permittee shall monitor the residual dissolved oxygen content of the sulfide oxidation tank at least on a weekly basis. If the residual dissolved oxygen content does not fall below 1 mg/liter for four consecutive weeks, monitoring may be conducted on a monthly basis. If the concentration falls below 1 mg/liter, weekly monitoring shall resume. [District Rules 2201 and 4102] Federally Enforceable Through Title V Permit
21. The residual dissolved oxygen content sensor for the sulfide oxidation tank shall be calibrated in accordance with the manufacturer's specifications. A copy of the user's manual or like document from the manufacturer shall be maintained onsite so that the District may verify calibration frequency and procedures. [District Rules 2201 and 4102] Federally Enforceable Through Title V Permit
22. If the residual dissolved oxygen content in the sulfide oxidation tank falls below 1 mg/liter, the permittee shall immediately correct the system. If concentration falls below 1 mg/liter for more than 10 consecutive minutes, the permittee shall notify the District within the following 1 hour. [District Rules 2201 and 4102] Federally Enforceable Through Title V Permit
23. The operator shall notify the APCO of an unplanned flaring event within 24 hours after the start of the next business day or within 24 hours of their discovery, whichever occurs first. The notification shall include the flare source identification, the start date and time, and the end date and time. [District Rule 4311] Federally Enforceable Through Title V Permit
24. The operator of a flare subject to flare minimization plans pursuant to Section 5.8 shall submit an annual report to the APCO that summarizes all Reportable Flaring Events as defined in Section 3.0 that occurred during the previous 12 month period. The report shall be submitted within 30 days following the end of the twelve month period of the previous year. The report shall include, but is not limited to all of the following: the results of an investigation to determine the primary cause and contributing factors of the flaring event; any prevention measures considered or implemented to prevent recurrence together with a justification for rejecting any measures that were considered but not implemented; if appropriate, an explanation of why the flaring was an emergency and necessary to prevent accident, hazard or release of vent gas to the atmosphere, or where, due to a regulatory mandate to vent a flare, it cannot be recovered, treated and used as a fuel gas at the facility; and the date, time, and duration of the flaring event. [District Rule 4311] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

25. The operator of a flare subject to flare monitoring requirements pursuant to Section 5.10 shall submit an annual report to the APCO within 30 days following the end of each 12 month period. The report shall include the following: the total volumetric flow of vent gas in standard cubic feet for each day; if the flow monitor used pursuant to Section 5.10 measures molecular weight, the average molecular weight for each hour of each month; a flow verification report which shall include flow verification testing pursuant to Section 6.3.5. [District Rule 4311] Federally Enforceable Through Title V Permit
26. For purposes of the flow verification report required by Section 6.2.3.8, vent gas flow shall be determined using one or more of the following methods, or by any alternative method approved by the APCO, ARB, and EPA: EPA Methods 1 and 2; a verification method recommended by the manufacturer of the flow monitoring equipment installed pursuant to Section 5.10; tracer gas dilution or velocity; other flow monitors or process monitors that can provide comparison data on a vent stream that is being directed past the ultrasonic flow meter. [District Rule 4311] Federally Enforceable Through Title V Permit
27. Every five years after the initial FMP submittal, the operator shall submit an updated FMP for each flare to the APCO for approval. The current FMP shall remain in effect until the updated FMP is approved by the APCO. If the operator fails to submit an updated FMP as required by this section, the existing FMP shall no longer be considered an approved plan. [District Rule 4311] Federally Enforceable Through Title V Permit
28. An updated FMP shall be submitted by the operator pursuant to Section 6.5 addressing new or modified equipment, prior to installing the equipment. Updated FMP submittals are only required if: (1) The equipment change would require an authority to construct (ATC) and would impact the emissions from the flare, and (2) The ATC is deemed complete after June 18, 2009, and (3) The modification is not solely the removal or decommissioning of equipment that is listed in the FMP, and has no associated increase in flare emissions. [District Rule 4311] Federally Enforceable Through Title V Permit
29. Permittee shall maintain the following records: a copy of the source testing result conducted pursuant to Section 6.4.2; a copy of the approved flare minimization plan pursuant to Section 6.5; a copy of annual reports submitted to the APCO pursuant to Section 6.2. [District Rule 4311] Federally Enforceable Through Title V Permit
30. Permittee shall maintain a log of the residual dissolved oxygen content sensor calibrations, which shall include the date and time of each calibration and any corrective actions. The records shall be retained, maintained on-site for at least five years, and made available for District inspection upon request. [District Rules 2201 and 4102] Federally Enforceable Through Title V Permit
31. Permittee shall maintain records of: (1) daily biogas production, (2) measured H₂S concentration in biogas, (3) date H₂S measurements taken from exhaust of biological reactor serving the scrubber, (4) measured concentration level of residual dissolved oxygen content taken from sulfide oxidation tank, and (5) date measurement of concentration level of residual dissolved oxygen content taken from sulfide oxidation tank. [District Rules 2201 and 4102] Federally Enforceable Through Title V Permit
32. All records shall be maintained and retained on-site for a minimum of five years, and shall be made available for District inspection upon request. [District Rules 2201 and 4311] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-227-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

502,100 GALLON WINERY WASTEWATER ANAEROBIC REACTOR SERVED BY A BIOGAS SCRUBBING SYSTEM
LISTED ON C-447-226

PERMIT UNIT REQUIREMENTS

1. The IC degassing tank of the anaerobic reactor shall be enclosed and vented to the biogas scrubber listed on C-447-226-0. [District Rule 4102]
2. The primary chamber of the anaerobic reactor shall be enclosed and vented to the biofilter listed on C-447-225-0. [District Rule 4102]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-230-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

AGRICULTURAL WASTE COMPOSTING OPERATION INCLUDING MORBARK, MODEL 3800, ELECTRICALLY POWERED HORIZONTAL GRINDER

PERMIT UNIT REQUIREMENTS

1. Maximum amount of material processed by this operation shall not exceed either of the following limits: 204 tons per day or 74,460 tons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Particulate matter (PM10) emissions shall not exceed 0.01 lb/ton of material processed. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The permittee shall maintain daily records of the amount of material processed, in tons. [District Rule 2201] Federally Enforceable Through Title V Permit
4. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070]

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-230-2 : May 19 2017 8:38AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-233-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

6,000 CUBIC FEET DIATOMACEOUS EARTH STORAGE SILO SERVED BY A STACLEAN MODEL 9-3.2-BDS BIN VENT FILTER

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Visible emissions from the bin vent filter serving the storage silo shall not equal or exceed 5% opacity for a period or periods aggregating more than three minutes in one hour. [District NSR Rule] Federally Enforceable Through Title V Permit
3. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
4. The bin vent filter shall be equipped with a pressure differential gauge to indicate the pressure drop across the filters. The gauge shall be maintained in good working condition at all times and shall be located in an easily accessible location. [District NSR Rule] Federally Enforceable Through Title V Permit
5. The bin vent filter shall operate at all times with a minimum differential pressure of 2.5 inches water column and a maximum differential pressure of 6 inches water column. [District NSR Rule] Federally Enforceable Through Title V Permit
6. Differential operating pressure shall be monitored and recorded on each day that the bin vent filter is in operation. [District NSR Rule] Federally Enforceable Through Title V Permit
7. The bin vent filter shall be maintained and operated according to manufacturer's specifications. [District NSR Rule] Federally Enforceable Through Title V Permit
8. The bin vent filter cleaning frequency and duration shall be adjusted to optimize the control efficiency. [District NSR Rule] Federally Enforceable Through Title V Permit
9. Material removed from the bin vent filter shall be disposed of in a manner preventing entrainment into the atmosphere. [District NSR Rule] Federally Enforceable Through Title V Permit
10. A spare set of bags shall be maintained on the premises at all times. [District NSR Rule] Federally Enforceable Through Title V Permit
11. PM10 emissions rate from the storage operation shall not exceed 0.00085 lb/ton of diatomaceous earth loaded into the silo. [District NSR Rule] Federally Enforceable Through Title V Permit
12. The maximum daily throughput of diatomaceous earth loaded into the silo shall not exceed 25 tons per day. [District NSR Rule] Federally Enforceable Through Title V Permit
13. The maximum annual throughput of diatomaceous earth loaded into the silo shall not exceed 2,500 tons per calendar year. [District NSR Rule] Federally Enforceable Through Title V Permit
14. Permittee shall maintain records of the daily and annual quantity (in tons) of diatomaceous earth loaded into the silo. [District NSR Rule and 1070] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-233-2 : May 19 2017 8:38AM -- BROWND

15. Records of all maintenance of the bin vent filter, including all change outs of bags or filter media, shall be maintained. [District NSR Rule] Federally Enforceable Through Title V Permit
16. Particulate matter emissions shall not exceed the hourly rate as calculated in District Rule 4202 using the equation $E = 3.59 \times P^{0.62}$ if P is less than or equal to 30 tons per hour, or $E = 17.31 \times P^{0.16}$ if P is greater than 30 tons per hour. [District Rule 4202] Federally Enforceable Through Title V Permit
17. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070 and 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

**San Joaquin Valley
Air Pollution Control District**

PERMIT UNIT: C-447-234-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

328,225 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3001 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-234-1 : May 19 2017 8:38AM -- BROWND

**San Joaquin Valley
Air Pollution Control District**

PERMIT UNIT: C-447-235-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

327,544 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3002 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-235-1 : May 19 2017 8:38AM -- BROWND

**San Joaquin Valley
Air Pollution Control District**

PERMIT UNIT: C-447-236-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

328,017 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3003 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-236-1 : May 19 2017 8:38AM -- BROWND

**San Joaquin Valley
Air Pollution Control District**

PERMIT UNIT: C-447-237-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

329,088 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3004 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-237-1 : May 19 2017 8:38AM -- BROWND

**San Joaquin Valley
Air Pollution Control District**

PERMIT UNIT: C-447-238-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

333,405 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3005 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-238-1 : May 19 2017 8:38AM -- BROWND

**San Joaquin Valley
Air Pollution Control District**

PERMIT UNIT: C-447-239-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

336,009 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3006 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-239-1 : May 19 2017 8:38AM -- BROWND

**San Joaquin Valley
Air Pollution Control District**

PERMIT UNIT: C-447-240-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

328,067 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3007 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-240-1 : May 19 2017 8:38AM -- BROWND

**San Joaquin Valley
Air Pollution Control District**

PERMIT UNIT: C-447-241-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

326,941 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3008 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-241-1 : May 19 2017 8:38AM -- BROWND

**San Joaquin Valley
Air Pollution Control District**

PERMIT UNIT: C-447-242-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

328,765 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3009 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-242-1 : May 19 2017 8:39AM -- BROWND

**San Joaquin Valley
Air Pollution Control District**

PERMIT UNIT: C-447-243-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

330,054 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3010 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-243-1 : May 19 2017 8:39AM -- BROWND

**San Joaquin Valley
Air Pollution Control District**

PERMIT UNIT: C-447-244-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

333,641 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3011 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-244-1 : May 19 2017 8:39AM -- BROWND

**San Joaquin Valley
Air Pollution Control District**

PERMIT UNIT: C-447-245-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

333,181 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3012 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-245-1 : May 19 2017 8:39AM -- BROWND

**San Joaquin Valley
Air Pollution Control District**

PERMIT UNIT: C-447-255-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

2,027 GALLON STEEL DISTILLED SPIRITS STORAGE TANK D1 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-255-1 : May 19 2017 8:39AM -- BROWND

**San Joaquin Valley
Air Pollution Control District**

PERMIT UNIT: C-447-256-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

52,788 GALLON STEEL DISTILLED SPIRITS STORAGE TANK P3 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-256-1 : May 19 2017 8:39AM -- BROWND

**San Joaquin Valley
Air Pollution Control District**

PERMIT UNIT: C-447-257-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

16,726 GALLON STEEL DISTILLED SPIRITS STORAGE TANK P4 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-257-1 : May 19 2017 8:39AM -- BROWND

**San Joaquin Valley
Air Pollution Control District**

PERMIT UNIT: C-447-258-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

16,754 GALLON STEEL DISTILLED SPIRITS STORAGE TANK P5 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-258-1 : May 19 2017 8:39AM -- BROWND

**San Joaquin Valley
Air Pollution Control District**

PERMIT UNIT: C-447-259-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

16,711 GALLON STEEL DISTILLED SPIRITS STORAGE TANK P6 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-259-1 : May 19 2017 8:39AM -- BROWND

**San Joaquin Valley
Air Pollution Control District**

PERMIT UNIT: C-447-260-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

16,725 GALLON STEEL DISTILLED SPIRITS STORAGE TANK P7 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-260-1 : May 19 2017 8:39AM -- BROWND

**San Joaquin Valley
Air Pollution Control District**

PERMIT UNIT: C-447-261-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

4,562 GALLON STEEL DISTILLED SPIRITS STORAGE TANK P8 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-261-1 : May 19 2017 8:39AM -- BROWND

**San Joaquin Valley
Air Pollution Control District**

PERMIT UNIT: C-447-262-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

5,333 GALLON STEEL DISTILLED SPIRITS STORAGE TANK P9 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-262-1 : May 19 2017 8:39AM -- BROWND

**San Joaquin Valley
Air Pollution Control District**

PERMIT UNIT: C-447-263-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

49,915 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 501 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-263-1 : May 19 2017 8:39AM -- BROWND

**San Joaquin Valley
Air Pollution Control District**

PERMIT UNIT: C-447-264-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

49,964 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 502 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-264-1 : May 19 2017 8:39AM -- BROWND

**San Joaquin Valley
Air Pollution Control District**

PERMIT UNIT: C-447-265-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

50,146 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 503 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-265-1 : May 19 2017 8:39AM -- BROWND

**San Joaquin Valley
Air Pollution Control District**

PERMIT UNIT: C-447-266-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

50,059 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 504 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

See facility-wide requirements for permit conditions applicable to this permit unit.

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-266-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-267-2

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

160 BHP ELECTRONICALLY REGULATED TO 130 BHP CUMMINS MODEL CFP5E-F30 TIER 3 CERTIFIED DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING A FIREWATER PUMP

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
5. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702 and 17 CCR 93115 and 40 CFR Subpart IIII] Federally Enforceable Through Title V Permit
6. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801, 17 CCR 93115, 40 CFR Part 60 Subpart IIII] Federally Enforceable Through Title V Permit
7. Emissions from this IC engine shall not exceed any of the following limits: 2.70 g-NOx/bhp-hr, 0.67 g-CO/bhp-hr, or 0.14 g-VOC/bhp-hr. [District Rule 2201, 17 CCR 93115, and 40 CFR Part 60 Subpart IIII] Federally Enforceable Through Title V Permit
8. Emissions from this IC engine shall not exceed 0.10 g-PM10/bhp-hr based on USEPA certification using ISO 8178 test procedure. [District Rule 2201, 17 CCR 93115, and 40 CFR Part 60 Subpart IIII] Federally Enforceable Through Title V Permit
9. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702 and 40 CFR 60 Subpart IIII] Federally Enforceable Through Title V Permit
10. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
11. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
13. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. For testing purposes, the engine shall only be operated the number of hours necessary to comply with the testing requirements of the National Fire Protection Association (NFPA) 25 - "Standard for the Inspection, Testing, and Maintenance of Water-Based Fire Protection Systems", 1998 edition. Total hours of operation for all maintenance, testing, and required regulatory purposes shall not exceed 100 hours per calendar year. [District Rule 4702, 17 CCR 93115 and 40 CFR Part 60 Subpart IIII] Federally Enforceable Through Title V Permit
14. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 17 CCR 93115]
15. The permittee shall maintain monthly records of the type of fuel purchased. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
16. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-268-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

GREEN WASTE ORGANIC MATERIAL RECEIVING, STORAGE, AND MIXING OPERATION

PERMIT UNIT REQUIREMENTS

1. This permit does not authorize the facility to operate without the required permits from other local, state or federal agency and does not authorize the violation of any conditions established for this facility in the Conditional Use Permit (CUP), Special Use Permit (SUP), Site Approval, Site Plan Review (SPR), or other approval documents issued by a local, state or federal agency. [District Rules 2070 & 2080, and Public Resources Code 21000-21177: California Environmental Quality Act]
2. All materials for processing shall be maintained adequately moist to prevent visible emissions in excess of 20% opacity [District Rule 4101]
3. The permittee is allowed to receive the following wastes for the composting operation: green waste, residential food waste, and construction wood waste. Green waste is defined as any organic waste material generated from gardening, agriculture, or landscaping activities including, but not limited to grass clippings, leave, tree and shrub trimmings, and plant remains. Residential food waste is defined as table scraps, vegetable and fruit peelings, meat, bones and fish, egg shells, solid dairy products, coffee grounds, bread and toast, paper waste including, but not limited to, napkins, towels, plates, coffee filters, and tea bags. Construction wood waste is defined as any untreated wood materials, including but not limited to, lumber, paper, and cardboard from construction. [District Rule 2010]
4. The permittee is prohibited to receive the following wastes for the composting operation: biosolids, animal manure, and poultry litter. Biosolids is defined as organic material resulting from the treatment of sewage sludge or wastewater. Animal manure is defines as non-human animal excretions and waste, including, but not limited to, dried solids and urine from cows, cattle, or swine. Poultry litter is defined as poultry excretions and waste, including, but not limited to dried solids and urine from chickens, turkeys, geese, or ducks. [District Rule 2010]
5. The quantity of organic material received shall not exceed either of the following limits: 1,325 wet tons/day or 146,853 wet ton/year (equivalent to 378,000 cubic yards/year). [District Rule 2201]
6. The quantity of organic material stockpiled at this facility for composting shall be less than 100,000 wet tons/year. [District Rules 2201 and 4566]
7. Emissions from organic material stockpiling shall not exceed either of the following limits: 1.063 lb-VOC/wet ton/day or 0.318 lb-NH3/wet ton/day. [District Rule]
8. PM10 emissions from the receiving, handling, and mixing of the organic waste materials shall not exceed 0.00165 lb-PM10/wet ton. [District Rule 2201]
9. Within 10 days of receipt of the organic material to be composted, the permittee shall perform one of the following: (a). Remove the organic material from the facility; (b). Place the organic material in the active-phase composting windrow and start active phase composting; (c). Cover the organic material with a waterproof cover that have at least a six-feet overlap of adjacent sheets and be securely anchored. [District Rules 2201 and 4566]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-268-1 : May 19 2017 8:39AM -- BROWND

10. A daily operations log shall be maintained and shall include the following: (a) The date, type, and weight (in wet tons) of each organic material received; (b). The date each stockpile was initially formed; (c). The date and action taken on each stockpile to satisfy the stockpile requirements; (d). Total quantity and type of each organic waste material stored for composting (in wet tons); (e). Total quantity and type of each organic waste material mixed for composting (in wet tons); and (f). Any other information necessary to demonstrate compliance with Rule 4566. [District Rules 2201 and 4566]
11. A cumulative annual log shall be maintained and shall indicate the total quantity and type of each organic waste material received (in wet tons). The records shall be updated at least monthly. [District Rule 2201]
12. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rules 2201 and 4566]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-269-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

OPEN WINDROW ACTIVE AND CURING PHASE GREEN WASTE COMPOSTING OPERATION WITH AN INTEGRATED WATERING SYSTEM

PERMIT UNIT REQUIREMENTS

1. This permit does not authorize the facility to operate without the required permits from other local, state or federal agency and does not authorize the violation of any conditions established for this facility in the Conditional Use Permit (CUP), Special Use Permit (SUP), Site Approval, Site Plan Review (SPR), or other approval documents issued by a local, state, or federal agency. [District Rules 2070 and 2080, and Public Resources Code 21000-21177: California Environmental Quality Act]
2. All materials for processing shall be maintained adequately moist to prevent visible emissions in excess of 20% opacity. [District Rule 4101]
3. PM10 emissions from the organic material composting operation shall not exceed 0.00066 lb-PM10/wet ton. [District Rule 2201]
4. The total quantity of organic materials composted shall be less than 100,000 wet tons/year. [District Rules 2201 and 4566]
5. VOC emissions from the organic material composting operation shall not exceed either of the following limits: 8,808.6 lb/day or 473,335 lb/year. [District Rules 2201 and 4566]
6. NH3 emissions from the organic material composting operation shall not exceed either of the following limits: 693.2 lb/day or 89,747 lb/year. [District Rule 2201]
7. The operator shall install, maintain, and utilize an integrated watering system to apply water to the surface of each active-phase composting windrow. For windrows that will be turned on the same day and will require the same water volume, mechanically turn the first windrow while operating the integrated watering system. Within three hours after turning the first windrow, the operator shall test the windrow for adequate water by taking a sample of the organic material in the windrow and passing a "Ball Test". The "Ball Test" is performed by taking a sample of the compostable material between the vertical midpoint and the peak of the windrow, at least three inches below the outer surface. There should be at least enough water to form a ball when compressed by hand, but the ball may break when tapped. If the ball crumbles during the hand pressure test, apply additional water and mechanically turn the same windrow, then retest until the material passes the ball test. Subsequent windrows shall not be turned until the initial windrow passes the ball test. Utilize the established water volume for the remaining windrows to be turned with the same water volume on the same day. Repeat this method for windrows that will be turned with a different water application rate. If a rain event occurs prior to turning the windrow, application of additional water to the surface of the windrow will not be required if the material passes the ball test as previously described. [District Rule 4566]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-269-1: May 19 2017 8:39AM -- BROWND

8. A daily operations log shall be maintained and shall include the following: (a). The date and time the organic material from the windrow was tested for adequate water content using the "Ball Test" and indicate if the material passed the ball test. If the windrow material did not pass the ball test indicate the corrective action taken; (b). The date and time each windrow was turned; (c). Total quantity of organic material transferred from the feedstock piles to the active-phase composting windrows (in wet tons); (d). Total quantity of active phase composting piles utilized onsite (in wet tons); (e). Total quantity of curing phase composting piles utilized onsite (in wet tons); and (f). Any other information necessary to demonstrate compliance with Rule 4566. [District Rules 4566 and 1070]
9. A cumulative annual log shall be maintained and shall include the following: (a). Total quantity of active-phase composting piles utilized onsite (in wet tons); (b). Total quantity of curing phase composting piles utilized onsite (in wet tons). The records shall be updated at least monthly. [District Rules 2201 and 1070]
10. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rules 2201, 4566, and 1070]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-270-0

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

FINISHED COMPOST STORAGE AND LOADOUT OPERATION

PERMIT UNIT REQUIREMENTS

1. All materials for processing shall be maintained adequately moist to prevent visible emissions in excess of 20% opacity. [District Rule 4101]
2. No more than 174 vehicles per day shall be used to load out finished compost (based upon the Solid Waste Facility Permit, SWIS #: 10-AA-0182). [District Rule 2010]
3. A daily log shall be maintained and shall include the following: (a). Total quantity and type of each organic waste material received (in wet tons); (b). Total quantity and type of each organic waste material mixed for composting (in wet tons). [District Rule 1070]
4. A cumulative annual log shall be maintained and shall include the following: (a). Total quantity and type of each organic waste material received (in wet tons); (b). Total quantity and type of each organic waste material mixed for composting (in wet tons). The records shall be updated at least monthly. [District Rule 1070]
5. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070]
6. All bulk material transport vehicles shall limit Visible Dust Emissions to 20% opacity by either limiting vehicular speed, maintaining sufficient freeboard on the load, applying water to the top of the load, or covering the load with a tarp or other suitable cover. [District Rules 8011 and 8031]
7. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 or Rule 8011. [District Rule 8041]
8. Any open area having 3.0 acres or more of disturbed surface area, that has remained undeveloped, unoccupied, unused or vacant for more than seven days shall comply with the requirements of District Rule 8051 (Open Areas), unless specifically exempted under section 4.0. [District Rule 8051]
9. Any new or existing public or private paved or unpaved road, road construction project, or road modification project shall implement the control measures and design criteria of, and comply with the requirements of District Rule 8061 (Paved and Unpaved Roads), unless specifically exempted under section 4.0 of Rule 8061. [District Rule 8061]
10. Water, gravel, roadmix, or chemical/organic dust stabilizers/suppressants, vegetative materials, or other District-approved control measure shall be applied to unpaved vehicle travel areas as required to limit Visible Dust Emissions to 20% opacity and comply with the requirements for a stabilized unpaved road as defined in District Rule 8011. [District Rules 8071 and 8011]
11. On each day that 50 or more Vehicle Daily Trips or 25 or more Vehicle Daily Trips with 3 axles or more will occur on an unpaved vehicle/equipment traffic area, the permittee shall apply water, gravel, road mix, or chemical/organic dust stabilizers/suppressants, vegetative materials, or other District-approved control measure as required to limit Visible Dust Emissions to 20% opacity and comply with the requirements for a stabilized unpaved road as defined in District Rule 8011. [District Rules 8071 and 8011]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-270-0 : May 19 2017 8:39AM -- BROWND

12. Whenever any portion of the site becomes inactive, the permittee shall restrict access and periodically stabilize any disturbed surface to comply with the conditions for a stabilized surface as defined in District Rule 8011. [District Rules 8071 and 8011]
13. This permit does not authorize the facility to operate without the required permits from other local, state, or federal agency and does not authorize the violation of any conditions established for this facility in the Conditional Use Permit (CUP), Special Use Permit (SUP), Site Approval, Site Plan Review (SPR), or other approval documents issued by a local, state, or federal agency. [District Rules 2070 and 2080]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-271-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

609,251 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6635) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,438,235 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a 12 month rolling basis, shall not exceed 3,299 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-271-1 : May 19 2017 8:39AM -- BROWND

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine ethanol content and throughput rate for storage operations and VOC emission rate for fermentation operations (ethanol percentage by volume, gallons and lb-VOC per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-272-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

612,539 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6636) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,438,235 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-272-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-273-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

612,124 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6637) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,438,235 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a 12 month rolling basis, shall not exceed 3,299 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-273-1 : May 19 2017 8:39AM -- BROWND

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine ethanol content and throughput rate for storage operations and VOC emission rate for fermentation operations (ethanol percentage by volume, gallons and lb-VOC per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-274-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

612,972 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6638) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,438,235 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a 12 month rolling basis, shall not exceed 3,299 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-274-1 : May 19 2017 8:39AM -- BROWND

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine ethanol content and throughput rate for storage operations and VOC emission rate for fermentation operations (ethanol percentage by volume, gallons and lb-VOC per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-275-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

612,770 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6639) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,438,235 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a 12 month rolling basis, shall not exceed 3,299 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-275-1 : May 19 2017 8:39AM -- BROWND

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine ethanol content and throughput rate for storage operations and VOC emission rate for fermentation operations (ethanol percentage by volume, gallons and lb-VOC per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-276-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

611,887 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6640) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,438,235 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a 12 month rolling basis, shall not exceed 3,299 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-276-1 : May 19 2017 8:39AM -- BROWND

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine ethanol content and throughput rate for storage operations and VOC emission rate for fermentation operations (ethanol percentage by volume, gallons and lb-VOC per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-277-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

611,101 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6643) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,438,235 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a 12 month rolling basis, shall not exceed 3,299 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-277-1: May 19 2017 8:39AM -- BROWND

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine ethanol content and throughput rate for storage operations and VOC emission rate for fermentation operations (ethanol percentage by volume, gallons and lb-VOC per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-278-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

611,761 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6644) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,438,235 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-278-1 : May 19 2017 8:39AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-278-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-279-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

615,034 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6645) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,034 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,438,235 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a 12 month rolling basis, shall not exceed 3,299 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-279-1 : May 19 2017 8:39AM -- BROWND

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine ethanol content and throughput rate for storage operations and VOC emission rate for fermentation operations (ethanol percentage by volume, gallons and lb-VOC per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-280-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

613,196 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6646) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,438,235 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a 12 month rolling basis, shall not exceed 3,299 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-280-1 : May 19 2017 8:39AM -- BROWND

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine ethanol content and throughput rate for storage operations and VOC emission rate for fermentation operations (ethanol percentage by volume, gallons and lb-VOC per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-281-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

612,106 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6647) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,438,235 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a 12 month rolling basis, shall not exceed 3,299 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-281-1 : May 19 2017 8:39AM -- BROWND

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine ethanol content and throughput rate for storage operations and VOC emission rate for fermentation operations (ethanol percentage by volume, gallons and lb-VOC per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-282-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

612,359 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6648) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,438,235 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a 12 month rolling basis, shall not exceed 3,299 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine ethanol content and throughput rate for storage operations and VOC emission rate for fermentation operations (ethanol percentage by volume, gallons and lb-VOC per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-283-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

611,612 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6651) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,438,235 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a 12 month rolling basis, shall not exceed 3,299 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-283-1 : May 19 2017 8:39AM -- BROWND

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine ethanol content and throughput rate for storage operations and VOC emission rate for fermentation operations (ethanol percentage by volume, gallons and lb-VOC per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-284-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

612,592 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6652) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,438,235 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-284-1 : May 19 2017 8:39AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-284-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-285-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

613,109 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6653) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,438,235 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a 12 month rolling basis, shall not exceed 3,299 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-285-1 : May 19 2017 8:39AM -- BROWND

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine ethanol content and throughput rate for storage operations and VOC emission rate for fermentation operations (ethanol percentage by volume, gallons and lb-VOC per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-286-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

613,536 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6654) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,438,235 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a 12 month rolling basis, shall not exceed 3,299 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-286-1 : May 19 2017 8:39AM -- BROWND

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine ethanol content and throughput rate for storage operations and VOC emission rate for fermentation operations (ethanol percentage by volume, gallons and lb-VOC per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-287-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

613,913 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6655) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,438,235 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a 12 month rolling basis, shall not exceed 3,299 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine ethanol content and throughput rate for storage operations and VOC emission rate for fermentation operations (ethanol percentage by volume, gallons and lb-VOC per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-288-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

615,603 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6656) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,603 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,438,235 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a 12 month rolling basis, shall not exceed 3,299 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-288-1 : May 19 2017 8:39AM -- BROWND

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine ethanol content and throughput rate for storage operations and VOC emission rate for fermentation operations (ethanol percentage by volume, gallons and lb-VOC per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-289-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

612,570 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6659) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,438,235 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a 12 month rolling basis, shall not exceed 3,299 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine ethanol content and throughput rate for storage operations and VOC emission rate for fermentation operations (ethanol percentage by volume, gallons and lb-VOC per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-290-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

611,948 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6660) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,438,235 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-290-1 : May 19 2017 8:39AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-291-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

613,637 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6661) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,438,235 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a 12 month rolling basis, shall not exceed 3,299 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine ethanol content and throughput rate for storage operations and VOC emission rate for fermentation operations (ethanol percentage by volume, gallons and lb-VOC per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-292-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

616,758 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6662) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 616,758 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,438,235 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a 12 month rolling basis, shall not exceed 3,299 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-292-1 : May 19 2017 8:39AM -- BROWND

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine ethanol content and throughput rate for storage operations and VOC emission rate for fermentation operations (ethanol percentage by volume, gallons and lb-VOC per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-293-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

615,000 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6663) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,438,235 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a 12 month rolling basis, shall not exceed 3,299 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-293-1 : May 19 2017 8:39AM -- BROWND

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine ethanol content and throughput rate for storage operations and VOC emission rate for fermentation operations (ethanol percentage by volume, gallons and lb-VOC per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-294-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

615,446 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6664) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The average fermentation temperature of each batch of must fermented in this tank shall not exceed 95 degrees Fahrenheit, calculated as the average of all temperature measurements for the batch taken at least every 12 hours over the course of the fermentation. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank shall not exceed 615,446 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,438,235 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
8. The annual VOC emissions from both wine fermentation and wine storage in this tank, calculated on a 12 month rolling basis, shall not exceed 3,299 pounds. [District Rule 2201] Federally Enforceable Through Title V Permit
9. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
10. When this tank is used for wine storage, daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. The daily VOC emissions for fermentation operations in this tank shall not exceed 3.46 lb/day per 1000 gallons of tank capacity. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Annual VOC emissions from wine fermentation in this tank, calculated on a twelve month rolling basis, shall be determined by the following equation: $E = 4.0 \text{ lb per 1000 gallons} \times \text{annual red wine production (in gallons)} + 1.6 \text{ lb per 1000 gallons} \times \text{annual white wine production (in gallons)}$. [District Rule 2201] Federally Enforceable Through Title V Permit
13. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
14. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
15. The permittee shall maintain the following records: red wine and white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury; the volume of each wine movement; and the calculated 12 month rolling wine ethanol content and throughput rate for storage operations and VOC emission rate for fermentation operations (ethanol percentage by volume, gallons and lb-VOC per 12 month rolling period, calculated monthly). [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
16. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201] Federally Enforceable Through Title V Permit
18. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-295-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

99 MMBTU/HR VICTORY ENERGY OPERATIONS NATURAL GAS/BIOGAS-FIRED BOILER EQUIPPED WITH A TODD VERIFLAME MODEL TODD VERIFLAME 99 LOW NOX BURNER, FLUE GAS RECIRCULATION SYSTEM, AND O2 CONTROLLER SERVED BY A NATIONWIDE MODEL CATASTAK SELECTIVE CATALYTIC REDUCTION (SCR) SYSTEM (BOILER #4)

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101] Federally Enforceable Through Title V Permit
3. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
4. All equipment shall be constructed, maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District Rule 2201] Federally Enforceable Through Title V Permit
5. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
6. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201 and 40 CFR 60.48 (c)(g)] Federally Enforceable Through Title V Permit
7. The unit shall only be fired on PUC-regulated natural gas and/or on scrubbed biogas from C-447-226. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
8. The H2S content of the scrubbed biogas fuel shall not exceed 50 ppmv. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
9. Except during start-up and shutdown, emissions from this unit shall not exceed any of the following limits: 5 ppmvd NOx @ 3% O2 or 0.006 lb-NOx/MMBtu; 0.0022 lb-PM10/MMBtu; 200 ppmvd CO @ 3% O2 (equivalent to 0.147 lb-CO/MMBtu); or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. During start-up and shutdown, emissions from this unit shall not exceed any of the following limits: 0.83 lb-NOx/hr; 0.0022 lb-PM10/MMBtu; 200 ppmvd CO @ 3% O2 (equivalent to 0.147 lb-CO/MMBtu); or 0.0055 lb-VOC/MMBtu.. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
11. The total duration of start-up time shall not exceed 5.0 hours per day. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
12. The total duration of startup time shall not exceed 4.0 hours per occurrence. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-295-1 : May 19 2017 8:39AM -- BROWND

13. The total duration of shutdown time shall not exceed 2.0 hours per day. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
14. The total duration of shutdown time shall not exceed 2.0 hours per occurrence. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
15. The permittee shall maintain daily records of start-up and shutdown durations and number of occurrences of each. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
16. The ammonia (NH₃) emissions shall not exceed 10 ppmvd @ 3% O₂ over a 15 minute averaging period. [District Rule 4102]
17. Source testing to measure natural gas combustion NO_x, CO, and NH₃ emissions from this unit shall be conducted at least once every twelve months. After demonstrating compliance on two consecutive annual source tests when unit is fired on natural gas, the unit shall be tested not less than once every 36 months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve months. [District Rules 2201, 4102, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
18. Nitrogen oxide (NO_x) emission concentrations in ppmv referenced at dry stack emissions shall be corrected to 3% O₂ and lb/MMBtu rates shall be calculated as lb NO₂/MMBtu of heat input (hhv). [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
19. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
20. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
21. NO_x emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
22. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
23. Stack gas oxygen (O₂) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
24. Source testing for ammonia slip shall be conducted utilizing BAAQMD Method ST-1B. [District Rule 4102]
25. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
26. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
27. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
28. The permittee shall monitor and record the stack concentration of NO_x, CO, NH₃, and O₂ at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. NH₃ monitoring shall be conducted utilizing Draeger tubes or a District approved equivalent method. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within five days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4102, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

29. If the NO_x, CO or NH₃ concentrations, as measured by the portable analyzer or the District approved ammonia monitoring equipment, exceed the permitted levels, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than one hour of operation after detection. If the portable analyzer or the ammonia monitoring equipment continue to show emission limit violations after one hour of operation following detection, the permittee shall notify the District within the following one hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
30. All NO_x, CO, O₂ and NH₃ emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The NO_x, CO and O₂ analyzer as well as the NH₃ emission monitoring equipment shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
31. NH₃ emission readings shall be conducted at the time the NO_x, CO and O₂ readings are taken. The readings shall be converted to ppmvd @ 3% O₂. [District Rule 4102]
32. The permittee shall maintain records of: (1) the date and time of NO_x, CO, NH₃, and O₂ measurements, (2) the O₂ concentration in percent by volume and the measured NO_x, CO, and NH₃ concentrations corrected to 3% O₂, (3) make and model of the portable analyzer, (4) portable analyzer calibration records, (5) the method of determining the NH₃ emission concentration, and (6) a description of any corrective action taken to maintain the emissions at or below the acceptable levels. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
33. Operator shall provide that fuel hhv be certified by third party fuel supplier or determined annually by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
34. Permittee shall determine sulfur content of combusted natural gas annually or shall demonstrate that the combusted natural gas is provided from a PUC or FERC regulated source. [District Rules 1081 and 4320] Federally Enforceable Through Title V Permit
35. The permittee shall monitor the biogas H₂S concentration at the outlet of the biogas scrubber (Permit to Operate C-447-226) on a weekly basis. If the biogas H₂S concentration does not exceed 50 ppmv for four consecutive weeks, monitoring may be conducted on a monthly basis. If the H₂S concentration at the outlet exceeds 50 ppmv, weekly monitoring shall resume. [District Rule 4320] Federally Enforceable Through Title V Permit
36. The permittee shall take readings of the NO_x concentration and O₂ percent, by volume, using the in-stack monitoring system at least once per each day that the boiler operates. [District Rule 2201 and 40 CFR Part 64.9] Federally Enforceable Through Title V Permit
37. During times when the in-stack monitoring system is down for maintenance or repairs, the permittee shall use a District approved portable analyzer to record daily NO_x and O₂ concentrations. The permittee shall maintain records of the portable analyzer readings including the date(s) and reason the in-stack monitoring system was not operating. [District Rule 2201 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
38. The permittee shall maintain daily records of the NO_x and O₂ concentration from the in-stack monitoring system. These records shall be made available for District inspection upon request. [District Rule 2201 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
39. The permittee shall compare the NO_x and O₂ concentrations from the in-stack monitoring system with the concentration of NO_x and O₂ readings from calibration gas cylinders for NO_x and O₂ at least once during each month that the boiler operates. The permittee shall maintain these comparison readings and these records shall be available for District inspection upon request. [District Rule 2201 and 40 CFR Part 64] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

40. If the NO_x or O₂ concentrations, as measured by the in-stack monitoring system, exceed the permitted levels the permittee shall return the emissions to compliant levels as soon as possible, but no longer than 1 hour of operation after detection. If the in-stack monitoring system continues to show emission limit violations after 1 hour of operation following detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation that is subject to enforcement action has occurred. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4102, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
41. The permittee shall comply with the compliance assurance monitoring operation and maintenance requirements of 40 CFR part 64.7. [40 CFR Part 64.7] Federally Enforceable Through Title V Permit
42. If the District or EPA determine that a Quality Improvement Plan is required under 40 CFR 64.7(d)(2), the permittee shall develop and implement the Quality Improvement Plan in accordance with 40 CFR Part 64.8. [40 CFR Part 64.8] Federally Enforceable Through Title V Permit
43. The permittee shall comply with the record keeping and reporting requirements of 40 CFR part 64.9. [40 CFR Part 64.9] Federally Enforceable Through Title V Permit
44. Permittee shall maintain daily records of the type and quantity of fuel combusted by the boiler. [District Rules 2201 and 40 CFR 60.48 (c)(g)] Federally Enforceable Through Title V Permit
45. All records shall be maintained and retained on-site for a minimum of five years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-296-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (629,640 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6701)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-296-1 : May 19 2017 8:39AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-296-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-297-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (629,689 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6702)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-297-1: May 19 2017 8:39AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-297-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-298-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (629,298 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6705)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-298-1 : May 19 2017 8:39AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-298-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-299-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (630,154 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6706)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-299-1 : May 19 2017 8:39AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-299-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-300-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (628,456 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6709)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-300-1 : May 19 2017 8:39AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-300-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-301-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (628,713 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6710)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-301-1 : May 19 2017 8:39AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-301-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-302-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (630,565 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6713)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-302-1: May 19 2017 8:39AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-302-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-303-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (629,783 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6714)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-303-1 : May 19 2017 8:39AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-303-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-304-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (628,504 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6717)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-304-1 : May 19 2017 8:39AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-304-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-305-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (627,927 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6718)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-305-1 : May 19 2017 8:39AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-305-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-306-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (628,545 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6721)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-306-1 : May 19 2017 8:39AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-306-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-307-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (627,933 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6722)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-307-1: May 19 2017 8:39AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-307-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-308-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (628,002 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6725)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-308-1 : May 19 2017 8:39AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-308-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-309-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (628,728 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6726)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-309-1 : May 19 2017 8:39AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-309-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-310-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (630,044 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6729)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-310-1 : May 19 2017 8:39AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-310-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-311-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (628,837 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6730)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-311-1 : May 19 2017 8:39AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-311-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-312-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (626,556 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6703)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-312-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-313-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (627,464 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6704)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-313-1 : May 19 2017 8:39AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-313-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-314-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (628,154 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6707)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-314-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-315-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (627,892 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6708)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-315-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-316-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (632,240 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6711)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-316-1 : May 19 2017 8:39AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-316-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-317-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (634,362 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6712)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-317-1: May 19 2017 8:39AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-317-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-318-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (632,359 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6715)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-318-1 : May 19 2017 8:39AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-318-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-319-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (632,903 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6716)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-319-1 : May 19 2017 8:39AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-319-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-320-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (626,432 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6719)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-320-1 : May 19 2017 8:39AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-320-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-321-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (624,782 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6720)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-321-1 : May 19 2017 8:39AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-321-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-322-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (626,387 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6723)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-322-1: May 19 2017 8:39AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-322-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-323-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (627,401 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6724)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-323-1: May 19 2017 8:39AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-323-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-324-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (628,736 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6727)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-324-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-325-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (628,647 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6728)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-325-1 : May 19 2017 8:39AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-325-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-326-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (628,179 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6731)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-326-1 : May 19 2017 8:39AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-326-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-327-1

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

629,000 GALLON NOMINAL (628,120 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6732)
WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. This tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
2. The pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rules 2201 and 4694, 5.2.1] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rules 2201 and 4694, 5.2.2] Federally Enforceable Through Title V Permit
4. The weighted annual average ethanol content of wine stored in this tank, calculated on a twelve month rolling basis, shall not exceed 15 percent by volume. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The maximum wine storage throughput in this tank shall not exceed 629,000 gallons per day. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The maximum wine storage throughput in this tank, calculated on a twelve month rolling basis, shall not exceed 4,450,000 gallons per year. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694, 6.4.2] Federally Enforceable Through Title V Permit
8. Daily throughput records, including records of filling and emptying operations, the dates of such operations, a unique identifier for each batch, the volume percent ethanol in the batch, and the volume of wine transferred, shall be maintained. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
9. The operator shall maintain records of the calculated 12 month rolling wine ethanol content and storage throughput rate (ethanol percentage by volume and gallons per 12 month rolling period, calculated monthly). [District Rule 2201] Federally Enforceable Through Title V Permit
10. If the throughput or ethanol content calculated for any rolling 12-month period exceeds the annual throughput or ethanol content limitations of this permit, in a crush season in which the start of the crush season (defined as the day on which the facility's seasonal crushing/fermentation operations commence) occurs less than 365 days after the start of the previous crush season, then no violation of the throughput or ethanol content limits for that rolling 12-month period will be deemed to have occurred so long as the calendar year throughput and ethanol content are below the annual throughput and ethanol content limitations. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-327-1: May 19 2017 8:39AM -- BROWND

11. Records shall be maintained that demonstrate the date of each year's start of crush season. [District Rule 2201]
Federally Enforceable Through Title V Permit
12. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rules 1070, 2201 and 4694] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-327-1 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-328-0

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

DIATOMACEOUS EARTH RECEIVING AND STORAGE OPERATION WITH A 6,000 CUBIC FEET STORAGE SILO E
SERVED BY A BIN VENT FILTER SYSTEM

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Visible emissions from the bin vent filter serving the storage silo shall not equal or exceed 5% opacity for a period or periods aggregating more than three minutes in any one hour. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The bin vent filter system shall be equipped with a pressure differential gauge to indicate the pressure drop across the filters. The gauge shall be maintained in good working condition at all times and shall be located in an easily accessible location. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The differential pressure gauge reading range is 2"-6" water column per manufacturer. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Replacement bags numbering at least 10% of the total number of bags shall be maintained on the premises. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Material removed from the bin vent filter system shall be disposed of in a manner preventing entrainment into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Bin vent filter shall be thoroughly inspected annually for tears, scuffs, abrasions, holes, or any evidence of particulate matter breakthrough and shall be replaced as needed. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. PM10 emissions shall not exceed 0.00085 pounds per ton of diatomaceous earth loaded into the silo. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The amount of diatomaceous earth loaded into the silo shall not exceed 25 tons in any one day. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The permittee shall keep records of date and quantity of diatomaceous earth loaded into the silo. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Differential operating pressure shall be monitored and recorded on each day that the bin vent filter system is in operation. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Records of all maintenance of the bin vent filter system, including all change outs of bags or filter media, shall be maintained. These records shall include identification of the equipment, date of inspection, any corrective action taken, and identification of the personnel performing the inspection. [District Rules 2201 and 2520, 9.4.2] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

13. Visible emissions shall be inspected annually during operation. If visible emissions are observed, corrective action shall be taken to eliminate visible emissions. If visible emissions cannot be corrected within 24 hours, a visible emissions test using EPA Method 9 shall be conducted. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
14. All records shall be retained for a minimum of five years and made available for District inspection upon request. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: E & J GALLO WINERY

Location: 5610 E OLIVE AVE, FRESNO, CA 93727

C-447-328-0 : May 19 2017 8:39AM -- BROWND

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: C-447-329-0

EXPIRATION DATE: 06/30/2016

EQUIPMENT DESCRIPTION:

99 MMBTU/HR VICTORY ENERGY OPERATIONS NATURAL GAS/BIOGAS-FIRED BOILER EQUIPPED WITH A COEN VERIFLAME MODEL COEN VERIFLAME 99 LOW NOX BURNER, FLUE GAS RECIRCULATION SYSTEM, AND O2 CONTROLLER SERVED BY A NATIONWIDE MODEL CATASTAK SELECTIVE CATALYTIC REDUCTION (SCR) SYSTEM (BOILER #3)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. All equipment shall be constructed, maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District Rule 2201] Federally Enforceable Through Title V Permit
3. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
4. A non-resettable, totalizing mass or volumetric fuel flow meter to measure the amount of fuel combusted in the unit shall be installed, utilized and maintained. [District Rule 2201 and 40 CFR 60.48 (c)(g)] Federally Enforceable Through Title V Permit
5. The unit shall only be fired on PUC-regulated natural gas and/or on scrubbed biogas from C-447-226. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
6. The H2S content of the scrubbed biogas fuel shall not exceed 50 ppmv. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
7. Except during start-up and shutdown, emissions from this unit shall not exceed any of the following limits: 5 ppmvd NOx @ 3% O2 or 0.006 lb-NOx/MMBtu; 0.0076 lb-PM10/MMBtu; 200 ppmvd CO @ 3% O2 (equivalent to 0.147 lb-CO/MMBtu); or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
8. During start-up and shutdown, emissions from this unit shall not exceed any of the following limits: 0.83 lb-NOx/hr; 0.0076 lb-PM10/MMBtu; 200 ppmvd CO @ 3% O2 (equivalent to 0.147 lb-CO/MMBtu); or 0.0055 lb-VOC/MMBtu.. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
9. The total duration of start-up time shall not exceed 5.0 hours per day. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. The total duration of startup time shall not exceed 4.0 hours per occurrence. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
11. The total duration of shutdown time shall not exceed 2.0 hours per day. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
12. The total duration of shutdown time shall not exceed 2.0 hours per occurrence. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

13. The permittee shall maintain daily records of start-up and shutdown durations and number of occurrences of each. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
14. The ammonia (NH₃) emissions shall not exceed 10 ppmvd @ 3% O₂ over a 15 minute averaging period. [District Rule 4102]
15. Source testing to measure NO_x and CO emissions from this unit while fired on natural gas shall be conducted within 60 days of initial start-up. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
16. Source testing to measure natural gas combustion NO_x, CO, and NH₃ emissions from this unit shall be conducted at least once every twelve months. After demonstrating compliance on two consecutive annual source tests when unit is fired on natural gas, the unit shall be tested not less than once every 36 months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve months. [District Rules 2201, 4102, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
17. Nitrogen oxide (NO_x) emission concentrations in ppmv referenced at dry stack emissions shall be corrected to 3% O₂ and lb/MMBtu rates shall be calculated as lb NO₂/MMBtu of heat input (hhv). [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
18. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit
19. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
20. NO_x emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
21. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
22. Stack gas oxygen (O₂) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
23. Source testing for ammonia slip shall be conducted utilizing BAAQMD Method ST-1B. [District Rule 4102]
24. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
25. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
26. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
27. The permittee shall monitor and record the stack concentration of NO_x, CO, NH₃, and O₂ at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. NH₃ monitoring shall be conducted utilizing Draeger tubes or a District approved equivalent method. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within five days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4102, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

28. If the NO_x, CO or NH₃ concentrations, as measured by the portable analyzer or the District approved ammonia monitoring equipment, exceed the permitted levels, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than one hour of operation after detection. If the portable analyzer or the ammonia monitoring equipment continue to show emission limit violations after one hour of operation following detection, the permittee shall notify the District within the following one hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
29. All NO_x, CO, O₂ and NH₃ emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The NO_x, CO and O₂ analyzer as well as the NH₃ emission monitoring equipment shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
30. NH₃ emission readings shall be conducted at the time the NO_x, CO and O₂ readings are taken. The readings shall be converted to ppmvd @ 3% O₂. [District Rule 4102]
31. The permittee shall maintain records of: (1) the date and time of NO_x, CO, NH₃, and O₂ measurements, (2) the O₂ concentration in percent by volume and the measured NO_x, CO, and NH₃ concentrations corrected to 3% O₂, (3) make and model of the portable analyzer, (4) portable analyzer calibration records, (5) the method of determining the NH₃ emission concentration, and (6) a description of any corrective action taken to maintain the emissions at or below the acceptable levels. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
32. Operator shall provide that fuel hhv be certified by third party fuel supplier or determined annually by ASTM D 1826 or D 1945 in conjunction with ASTM D 3588. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
33. Permittee shall determine sulfur content of combusted natural gas annually or shall demonstrate that the combusted natural gas is provided from a PUC or FERC regulated source. [District Rules 1081 and 4320] Federally Enforceable Through Title V Permit
34. The permittee shall monitor the biogas H₂S concentration at the outlet of the biogas scrubber (Permit to Operate C-447-226) on a weekly basis. If the biogas H₂S concentration does not exceed 50 ppmv for four consecutive weeks, monitoring may be conducted on a monthly basis. If the H₂S concentration at the outlet exceeds 50 ppmv, weekly monitoring shall resume. [District Rule 4320] Federally Enforceable Through Title V Permit
35. The permittee shall take readings of the NO_x concentration and O₂ percent, by volume, using the in-stack monitoring system at least once per each day that the boiler operates. [District Rule 2201 and 40 CFR Part 64.9] Federally Enforceable Through Title V Permit
36. During times when the in-stack monitoring system is down for maintenance or repairs, the permittee shall use a District approved portable analyzer to record daily NO_x and O₂ concentrations. The permittee shall maintain records of the portable analyzer readings including the date(s) and reason the in-stack monitoring system was not operating. [District Rule 2201 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
37. The permittee shall maintain daily records of the NO_x and O₂ concentration from the in-stack monitoring system. These records shall be made available for District inspection upon request. [District Rule 2201 and 40 CFR Part 64] Federally Enforceable Through Title V Permit
38. The permittee shall compare the NO_x and O₂ concentrations from the in-stack monitoring system with the concentration of NO_x and O₂ readings from calibration gas cylinders for NO_x and O₂ at least once during each month that the boiler operates. The permittee shall maintain these comparison readings and these records shall be available for District inspection upon request. [District Rule 2201 and 40 CFR Part 64] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

39. If the NO_x or O₂ concentrations, as measured by the in-stack monitoring system, exceed the permitted levels the permittee shall return the emissions to compliant levels as soon as possible, but no longer than 1 hour of operation after detection. If the in-stack monitoring system continues to show emission limit violations after 1 hour of operation following detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation that is subject to enforcement action has occurred. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4102, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
40. The permittee shall comply with the compliance assurance monitoring operation and maintenance requirements of 40 CFR part 64.7. [40 CFR Part 64.7] Federally Enforceable Through Title V Permit
41. If the District or EPA determine that a Quality Improvement Plan is required under 40 CFR 64.7(d)(2), the permittee shall develop and implement the Quality Improvement Plan in accordance with 40 CFR Part 64.8. [40 CFR Part 64.8] Federally Enforceable Through Title V Permit
42. The permittee shall comply with the record keeping and reporting requirements of 40 CFR part 64.9. [40 CFR Part 64.9] Federally Enforceable Through Title V Permit
43. Permittee shall maintain daily records of the type and quantity of fuel combusted by the boiler. [District Rules 2201 and 40 CFR 60.48 (c)(g)] Federally Enforceable Through Title V Permit
44. All records shall be maintained and retained on-site for a minimum of five years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

ATTACHMENT C

Detailed Facility List

Detailed Facility Report
For Facility=447 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

E & J GALLO WINERY 5610 E OLIVE AVE FRESNO, CA 93727	FAC # STATUS: TELEPHONE:	C 447 A 5594582480	TYPE: TOXIC ID:	TitleV 40095	EXPIRE ON: AREA: INSP. DATE:	06/30/2016 6 / 312 05/17

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-447-1-12	62.0 MMBtu/hr burner	3020-02 H	1	1,128.00	1,128.00	A	62.0 MMBTU/HR B & W BIOGAS/NATURAL GAS-FIRED BOILER EQUIPPED WITH A TODD LOW-NOX BURNER, FLUE GAS RECIRCULATION, O2 AND CO TRIM CONTROLLERS, A CRI COMPANY SELECTIVE CATALYTIC REDUCTION (SCR) SYSTEM MODEL SHELL DNOX LFR, AND A NOX AND O2 IN-STACK EMISSION MONITORING SYSTEM
C-447-2-13	142,000 kBTU/HR	3020-02 H	1	1,128.00	1,128.00	A	142.0 MMBTU/HR NEBRASKA MODEL 84 NATURAL GAS-FIRED BOILER WITH A TODD LOW NOX BURNER, FLUE GAS RECIRCULATION (FGR) SYSTEM, CRI COMPANY SELECTIVE CATALYTIC REDUCTION (SCR) SYSTEM, AND AN ABB MODEL AO2000 CEMS
C-447-5-3	47,892 gallon storage silo (7,450 cubic feet)	3020-05 C	1	149.00	149.00	A	STORAGE SILO #1 FOR DIATOMACEOUS EARTH SERVED BY A SLY PACTECON MODEL #PS3 BAGHOUSE DUST COLLECTOR WITH SHAKER CLEANER
C-447-6-3	47,892 gallon storage silo (7,450 cubic feet)	3020-05 C	1	149.00	149.00	A	STORAGE SILO #2 FOR DIATOMACEOUS EARTH SERVED BY A SLY PACTECON MODEL #PS3 BAGHOUSE DUST COLLECTOR WITH SHAKER CLEANER
C-447-8-3	52,650 gallon storage silo (8190 cubic feet)	3020-05 D	1	203.00	203.00	A	8190 CUBIC FT SILO #3 FOR STORAGE OF DIATOMACEOUS EARTH SERVED BY A DYNAMIC AIR PULSE-JET BAGHOUSE FILTER
C-447-9-5	1 nozzle	3020-11 A	1	38.00	38.00	A	GASOLINE DISPENSING OPERATION WITH ONE 500 GALLON CONVAULT ABOVEGROUND STORAGE TANK SERVED BY OPW EVR PHASE I VAPOR RECOVERY SYSTEM (VR-401-B), STANDING LOSS CONTROL (VR-301-D), AND ONE FUELING POINT WITH ONE PHASE II EXEMPT GASOLINE DISPENSING NOZZLE
C-447-10-3	60 HP ABRASIVE BLASTER	3020-01 C	1	217.00	217.00	A	CONFINED AND UNCONFINED ABRASIVE BLASTING OPERATION WITH A 6 CU. FT. CAPACITY CLEMCO MODEL 2452 BLASTING POT #1 VENTED TO A BLAST BOOTH (COMMON TO C- 447-10 THRU C-447-14) WITH A PAULI MODEL #CT BAGHOUSE DURING CONFINED BLASTING, AND WITH A CLEMCO MODEL AVS-50E ELECTRIC VACUUM
C-447-11-3	60 HP ABRASIVE BLASTER	3020-01 C	1	217.00	217.00	A	CONFINED AND UNCONFINED ABRASIVE BLASTING OPERATION WITH A 6 CU. FT. CAPACITY CLEMCO MODEL 2452 BLAST POT #2, VENTED TO A BLAST BOOTH (COMMON TO C-447-10 THRU C-447-14) WITH A PAULI MODEL #CT BAGHOUSE DURING CONFINED BLASTING, AND A CLEMCO MODEL AVS-50E ELECTRIC VACUUM
C-447-12-3	60 HP ABRASIVE BLASTER	3020-01 C	1	217.00	217.00	A	CONFINED AND UNCONFINED ABRASIVE BLASTING OPERATION WITH A 100 POUND CLEMCO MODEL 1440 BLAST POT #3, VENTED TO A BLAST BOOTH (COMMON TO C-447-10 THRU C-447-14) WITH A PAULI MODEL #CT BAGHOUSE DURING CONFINED BLASTING, AND A CLEMCO MODEL AVS-50E ELECTRIC VACUUM

Detailed Facility Report
For Facility=447 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-447-13-3	60 HP ABRASIVE BLASTER	3020-01 C	1	217.00	217.00	A	CONFINED AND UNCONFINED ABRASIVE BLASTING OPERATION WITH A 800 POUND CLEMCO MODEL L2463 BLASTING POT #4, VENTED TO A BLAST BOOTH (COMMON TO C-447-10 THRU C-447-14) WITH A PAULI MODEL #CT BAGHOUSE DURING CONFINED BLASTING, AND A CLEMCO MODEL AVS-50E ELECTRIC VACUUM
C-447-14-3	60 HP ABRASIVE BLASTER	3020-01 C	1	217.00	217.00	A	CONFINED AND UNCONFINED ABRASIVE BLASTING OPERATION WITH A 500 POUND CLEMCO BLASTING POT #5, VENTED TO A BLAST BOOTH (COMMON TO C-447-10 THRU C-447 14) WITH A PAULI MODEL #CT BAGHOUSE DURING CONFINED BLASTING, AND A CLEMCO MODEL AVS-50E ELECTRIC VACUUM
C-447-16-3	5 Hp Paint Spray Booth	3020-01 A	1	97.00	97.00	A	METAL PARTS AND PRODUCTS COATING OPERATION WITH HVLP SPRAY GUN(S), PAINT BOOTH WITH DRY EXHAUST FILTERS AND SPRAY GUN CLEANER
C-447-17-1	200 hp electric air compressor	3020-01 D	1	345.00	345.00	A	200 HP CONFINED ABRASIVE BLASTING OPERATION WITH A 100 LB TRINCO BLASTING POT SERVED BY A TRINCO DUST COLLECTOR
C-447-18-1	200 hp electric air compressor	999-99	1	0.00	0.00	A	200 HP CONFINED ABRASIVE BLASTING OPERATION WITH A 100 LB CYCLONE BLASTING SYSTEMS BLASTING POT SERVED BY CYCLONE BLASTING SYSTEM DUST COLLECTOR
C-447-19-1	200 hp electric air compressor	999-99	1	0.00	0.00	A	200 HP UNCONFINED ABRASIVE BLASTING OPERATION WITH A 100 LB CLEMCO BLASTING POT #7
C-447-20-1	200 hp electric air compressor	999-99	1	0.00	0.00	A	200 HP UNCONFINED ABRASIVE BLASTING OPERATION WITH A 200 LB PAULE & GFIFFIN BLASTING POT
C-447-21-2	1 nozzle	3020-11 A	1	38.00	38.00	A	GASOLINE DISPENSING OPERATION WITH ONE 1,000 GALLON SUPERVAULT FL MODEL ABOVEGROUND STORAGE TANK SERVED BY TWO-POINT OPW EVR PHASE I VAPOR RECOVERY SYSTEM (VR-401-B), ONE FUELING POINT WITH ONE GASOLINE DISPENSING NOZZLE SERVED BY BALANCE PHASE II VAPOR RECOVERY SYSTEM (G-70-132-B), AND STANDING LOSS CONTROL (VR-301-D)
C-447-23-1	138 bhp IC engine	3020-10 B	1	129.00	129.00	A	TRANSPORTABLE 138 BHP DEUTZ MODEL TCD 2012L04 2V SERIAL NO. 10603992 TIER 3 CERTIFIED DIESEL-FIRED IC ENGINE POWERING A 100 TON/HOUR POWERSCREEN MODEL TROMMEL 830 ROTARY SCREEN
C-447-27-2	105,179 GALLON	3020-05 E	1	270.00	270.00	A	105,179 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 12 WITH PRESSURE/VACUUM VALVE
C-447-28-2	105,179 GALLON	3020-05 E	1	270.00	270.00	A	105,043 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 13 WITH PRESSURE/VACUUM VALVE
C-447-29-2	105,306 GALLON	3020-05 E	1	270.00	270.00	A	105,306 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 14 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report
For Facility=447 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-447-30-3	54,680 GALLON	3020-05 D	1	203.00	203.00	A	54,680 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION; AND WINE, SPIRITS, HIGH PROOF SPIRITS/ALCOHOL, OR BRANDY STORAGE TANK 509 WITH PRESSURE/VACUUM VALVE
C-447-31-3	54,668 GALLON	3020-05 D	1	203.00	203.00	A	54,668 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION; AND WINE, SPIRITS, HIGH PROOF SPIRITS/ALCOHOL, OR BRANDY STORAGE TANK 510 WITH PRESSURE/VACUUM VALVE
C-447-32-3	54,672 GALLON	3020-05 D	1	203.00	203.00	A	54,672 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION; AND WINE, SPIRITS, HIGH PROOF SPIRITS/ALCOHOL, OR BRANDY STORAGE TANK 511 WITH PRESSURE/VACUUM VALVE
C-447-33-3	54,668 GALLON	3020-05 D	1	203.00	203.00	A	54,668 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION; AND WINE, SPIRITS, HIGH PROOF SPIRITS/ALCOHOL, OR BRANDY STORAGE TANK 512 WITH PRESSURE/VACUUM VALVE
C-447-34-2	102,087 GALLON	3020-05 E	1	270.00	270.00	A	102,087 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1001 WITH PRESSURE/VACUUM VALVE
C-447-35-2	101,870 GALLON	3020-05 E	1	270.00	270.00	A	101,870 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1002 WITH PRESSURE/VACUUM VALVE
C-447-36-2	102,253 GALLON	3020-05 E	1	270.00	270.00	A	102,253 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1003 WITH PRESSURE/VACUUM VALVE
C-447-37-2	102,253 GALLON	3020-05 E	1	270.00	270.00	A	102,253 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1004 WITH PRESSURE/VACUUM VALVE
C-447-38-2	102,175 GALLON	3020-05 E	1	270.00	270.00	A	102,175 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1005 WITH PRESSURE/VACUUM VALVE
C-447-39-2	102,235 GALLON	3020-05 E	1	270.00	270.00	A	102,235 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1006 WITH PRESSURE/VACUUM VALVE
C-447-40-2	102,211 GALLON	3020-05 E	1	270.00	270.00	A	102,211 GALLON STEEL ENCLOSED TOP WHITE WINE FERMENTATION AND STORAGE TANK 1007 WITH PRESSURE/VACUUM VALVE
C-447-41-2	102,968 GALLON	3020-05 E	1	270.00	270.00	A	102,968 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1008 WITH PRESSURE/VACUUM VALVE
C-447-42-2	102,262 GALLON	3020-05 E	1	270.00	270.00	A	102,262 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1009 WITH PRESSURE/VACUUM VALVE
C-447-43-2	103,122 GALLON	3020-05 E	1	270.00	270.00	A	103,122 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1010 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report
For Facility=447 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-447-44-2	103,146 GALLON	3020-05 E	1	270.00	270.00	A	103,146 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1011 WITH PRESSURE/VACUUM VALVE
C-447-45-2	103,080 GALLON	3020-05 E	1	270.00	270.00	A	103,080 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1012 WITH PRESSURE/VACUUM VALVE
C-447-46-2	105,264 GALLON	3020-05 E	1	270.00	270.00	A	105,264 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1501 WITH PRESSURE/VACUUM VALVE
C-447-47-2	105,259 GALLON	3020-05 E	1	270.00	270.00	A	105,259 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1502 WITH PRESSURE/VACUUM VALVE
C-447-48-2	105,284 GALLON	3020-05 E	1	270.00	270.00	A	105,284 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1503 WITH PRESSURE/VACUUM VALVE
C-447-49-2	105,100 GALLON	3020-05 E	1	270.00	270.00	A	105,100 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1504 WITH PRESSURE/VACUUM VALVE
C-447-50-2	105,215 GALLON	3020-05 E	1	270.00	270.00	A	105,215 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1505 WITH PRESSURE/VACUUM VALVE
C-447-51-2	105,011 GALLON	3020-05 E	1	270.00	270.00	A	105,011 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1506 WITH PRESSURE/VACUUM VALVE
C-447-52-2	105,287 GALLON	3020-05 E	1	270.00	270.00	A	105,287 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1507 WITH PRESSURE/VACUUM VALVE
C-447-53-2	105,054 GALLON	3020-05 E	1	270.00	270.00	A	105,054 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1508 WITH PRESSURE/VACUUM VALVE
C-447-54-2	105,194 GALLON	3020-05 E	1	270.00	270.00	A	105,194 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1509 WITH PRESSURE/VACUUM VALVE
C-447-55-2	105,021 GALLON	3020-05 E	1	270.00	270.00	A	105,021 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 1510 WITH PRESSURE/VACUUM VALVE
C-447-56-2	212,026 GALLON	3020-05 E	1	270.00	270.00	A	212,026 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2001 WITH PRESSURE/VACUUM VALVE
C-447-57-2	212,468 GALLON	3020-05 E	1	270.00	270.00	A	212,468 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2002 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report
For Facility=447 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-447-58-2	212,151 GALLON	3020-05 E	1	270.00	270.00	A	212,151 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2003 WITH PRESSURE/VACUUM VALVE
C-447-59-2	212,120 GALLON	3020-05 E	1	270.00	270.00	A	212,120 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2004 WITH PRESSURE/VACUUM VALVE
C-447-60-2	211,917 GALLON	3020-05 E	1	270.00	270.00	A	211,917 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2005 WITH PRESSURE/VACUUM VALVE
C-447-61-2	212,275 GALLON	3020-05 E	1	270.00	270.00	A	212,275 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2006 WITH PRESSURE/VACUUM VALVE
C-447-62-2	211,691 GALLON	3020-05 E	1	270.00	270.00	A	211,691 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2007 WITH PRESSURE/VACUUM VALVE
C-447-63-2	212,254 GALLON	3020-05 E	1	270.00	270.00	A	212,254 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2008 WITH PRESSURE/VACUUM VALVE
C-447-64-2	212,766 GALLON	3020-05 E	1	270.00	270.00	A	212,766 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2009 WITH PRESSURE/VACUUM VALVE
C-447-65-3	214,253 GALLON	3020-05 E	1	270.00	270.00	A	214,253 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION; AND WINE, SPIRITS, HIGH PROOF SPIRITS/ALCOHOL, OR BRANDY STORAGE TANK 2010 WITH PRESSURE/VACUUM VALVE
C-447-66-3	213,963 GALLON	3020-05 E	1	270.00	270.00	A	213,963 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION; AND WINE, SPIRITS, HIGH PROOF SPIRITS/ALCOHOL, OR BRANDY STORAGE TANK 2011 WITH PRESSURE/VACUUM VALVE
C-447-67-2	214,245 GALLON	3020-05 E	1	270.00	270.00	A	214,245 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2012 WITH PRESSURE/VACUUM VALVE
C-447-68-2	214,528 GALLON	3020-05 E	1	270.00	270.00	A	214,528 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2013 WITH PRESSURE/VACUUM VALVE
C-447-69-2	214,325 GALLON	3020-05 E	1	270.00	270.00	A	214,325 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2014 WITH PRESSURE/VACUUM VALVE
C-447-70-2	214,301 GALLON	3020-05 E	1	270.00	270.00	A	214,301 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2015 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report
For Facility=447 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-447-71-2	214,236 GALLON	3020-05 E	1	270.00	270.00	A	214,236 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2016 WITH PRESSURE/VACUUM VALVE
C-447-72-2	213,126 GALLON	3020-05 E	1	270.00	270.00	A	213,126 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2501 WITH PRESSURE/VACUUM VALVE
C-447-73-2	213,596 GALLON	3020-05 E	1	270.00	270.00	A	213,596 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2502 WITH PRESSURE/VACUUM VALVE
C-447-74-2	213,687 GALLON	3020-05 E	1	270.00	270.00	A	213,687 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2503 WITH PRESSURE/VACUUM VALVE
C-447-75-2	213,298 GALLON	3020-05 E	1	270.00	270.00	A	213,298 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2504 WITH PRESSURE/VACUUM VALVE
C-447-76-2	213,018 GALLON	3020-05 E	1	270.00	270.00	A	213,018 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2505 WITH PRESSURE/VACUUM VALVE
C-447-77-2	213,471 GALLON	3020-05 E	1	270.00	270.00	A	213,471 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2506 WITH PRESSURE/VACUUM VALVE
C-447-78-2	213,296 GALLON	3020-05 E	1	270.00	270.00	A	213,296 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2507 WITH PRESSURE/VACUUM VALVE
C-447-79-2	213,411 GALLON	3020-05 E	1	270.00	270.00	A	213,411 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2508 WITH PRESSURE/VACUUM VALVE
C-447-80-2	211,766 GALLON	3020-05 E	1	270.00	270.00	A	211,766 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2509 WITH PRESSURE/VACUUM VALVE
C-447-81-2	211,311 GALLON	3020-05 E	1	270.00	270.00	A	211,311 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2510 WITH PRESSURE/VACUUM VALVE
C-447-82-2	211,316 GALLON	3020-05 E	1	270.00	270.00	A	211,316 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2511 WITH PRESSURE/VACUUM VALVE
C-447-83-2	211,260 GALLON	3020-05 E	1	270.00	270.00	A	211,260 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2512 WITH PRESSURE/VACUUM VALVE
C-447-84-2	211,748 GALLON	3020-05 E	1	270.00	270.00	A	211,748 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2513 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report
For Facility=447 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-447-85-2	211,712 GALLON	3020-05 E	1	270.00	270.00	A	211,712 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2514 WITH PRESSURE/VACUUM VALVE
C-447-86-2	211,422 GALLON	3020-05 E	1	270.00	270.00	A	211,422 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2515 WITH PRESSURE/VACUUM VALVE
C-447-87-2	211,573 GALLON	3020-05 E	1	270.00	270.00	A	211,573 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2516 WITH PRESSURE/VACUUM VALVE
C-447-88-2	211,633 GALLON	3020-05 E	1	270.00	270.00	A	211,633 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2517 WITH PRESSURE/VACUUM VALVE
C-447-89-2	211,487 GALLON	3020-05 E	1	270.00	270.00	A	211,487 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2518 WITH PRESSURE/VACUUM VALVE
C-447-90-2	211,378 GALLON	3020-05 E	1	270.00	270.00	A	211,378 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2519 WITH PRESSURE/VACUUM VALVE
C-447-91-2	211,658 GALLON	3020-05 E	1	270.00	270.00	A	211,658 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2520 WITH PRESSURE/VACUUM VALVE
C-447-92-2	211,732 GALLON	3020-05 E	1	270.00	270.00	A	211,732 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2521 WITH PRESSURE/VACUUM VALVE
C-447-93-2	211,788 GALLON	3020-05 E	1	270.00	270.00	A	211,788 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2522 WITH PRESSURE/VACUUM VALVE
C-447-94-2	211,189 GALLON	3020-05 E	1	270.00	270.00	A	211,189 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2523 WITH PRESSURE/VACUUM VALVE
C-447-95-2	211,962 GALLON	3020-05 E	1	270.00	270.00	A	211,962 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 2524 WITH PRESSURE/VACUUM VALVE
C-447-96-2	207,390 GALLON	3020-05 E	1	270.00	270.00	A	207,390 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2922
C-447-97-2	207,909 GALLON	3020-05 E	1	270.00	270.00	A	207,909 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2923
C-447-98-2	207,676 GALLON	3020-05 E	1	270.00	270.00	A	207,676 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2924
C-447-99-2	208,185 GALLON	3020-05 E	1	270.00	270.00	A	208,185 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2925

Detailed Facility Report
For Facility=447 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-447-100-2	207,571 GALLON	3020-05 E	1	270.00	270.00	A	207,571 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2926
C-447-101-2	208,168 GALLON	3020-05 E	1	270.00	270.00	A	208,168 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2927
C-447-102-2	207,821 GALLON	3020-05 E	1	270.00	270.00	A	207,821 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2928
C-447-103-2	207,140 GALLON	3020-05 E	1	270.00	270.00	A	207,140 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2929
C-447-104-2	206,695 GALLON	3020-05 E	1	270.00	270.00	A	206,695 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2930
C-447-105-2	207,451 GALLON	3020-05 E	1	270.00	270.00	A	207,451 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2931
C-447-106-2	206,832 GALLON	3020-05 E	1	270.00	270.00	A	206,832 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2932
C-447-107-2	207,270 GALLON	3020-05 E	1	270.00	270.00	A	207,270 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2933
C-447-108-2	208,117 GALLON	3020-05 E	1	270.00	270.00	A	208,117 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2934
C-447-109-2	208,202 GALLON	3020-05 E	1	270.00	270.00	A	208,202 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2935
C-447-110-2	206,996 GALLON	3020-05 E	1	270.00	270.00	A	206,996 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2936
C-447-111-2	207,039 GALLON	3020-05 E	1	270.00	270.00	A	207,039 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2937
C-447-112-2	206,757 GALLON	3020-05 E	1	270.00	270.00	A	206,757 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2938
C-447-113-2	207,752 GALLON	3020-05 E	1	270.00	270.00	A	207,752 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2939
C-447-114-2	207,369 GALLON	3020-05 E	1	270.00	270.00	A	207,369 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2940
C-447-115-2	208,795 GALLON	3020-05 E	1	270.00	270.00	A	208,795 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2941
C-447-116-2	208,928 GALLON	3020-05 E	1	270.00	270.00	A	208,928 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION TANK 2942
C-447-117-2	329,824 GALLON	3020-05 E	1	270.00	270.00	A	329,824 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3013 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report
For Facility=447 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-447-118-2	329,868 GALLON	3020-05 E	1	270.00	270.00	A	329,868 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 3014 WITH PRESSURE/VACUUM VALVE
C-447-119-2	642,674 GALLON	3020-05 F	1	330.00	330.00	A	642,674 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6013 WITH PRESSURE/VACUUM VALVE
C-447-120-2	642,066 GALLON	3020-05 F	1	330.00	330.00	A	642,066 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6014 WITH PRESSURE/VACUUM VALVE
C-447-121-2	642,494 GALLON	3020-05 F	1	330.00	330.00	A	642,494 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6015 WITH PRESSURE/VACUUM VALVE
C-447-122-2	643,303 GALLON	3020-05 F	1	330.00	330.00	A	643,303 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6016 WITH PRESSURE/VACUUM VALVE
C-447-123-2	643,934 GALLON	3020-05 F	1	330.00	330.00	A	643,934 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6017 WITH PRESSURE/VACUUM VALVE
C-447-124-2	642,604 GALLON	3020-05 F	1	330.00	330.00	A	642,604 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6018 WITH PRESSURE/VACUUM VALVE
C-447-125-2	642,738 GALLON	3020-05 F	1	330.00	330.00	A	642,738 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6019 WITH PRESSURE/VACUUM VALVE
C-447-126-2	643,964 GALLON	3020-05 F	1	330.00	330.00	A	643,964 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6020 WITH PRESSURE/VACUUM VALVE
C-447-127-2	641,070 GALLON	3020-05 F	1	330.00	330.00	A	641,070 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6021 WITH PRESSURE/VACUUM VALVE
C-447-128-2	641,248 GALLON	3020-05 F	1	330.00	330.00	A	641,248 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6022 WITH PRESSURE/VACUUM VALVE
C-447-129-2	641,965 GALLON	3020-05 F	1	330.00	330.00	A	641,965 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6023 WITH PRESSURE/VACUUM VALVE
C-447-130-2	641,756 GALLON	3020-05 F	1	330.00	330.00	A	641,756 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6024 WITH PRESSURE/VACUUM VALVE
C-447-131-2	642,656 GALLON	3020-05 F	1	330.00	330.00	A	642,656 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6025 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report
For Facility=447 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-447-132-2	640,805 GALLON	3020-05 F	1	330.00	330.00	A	640,805 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6026 WITH PRESSURE/VACUUM VALVE
C-447-133-2	641,489 GALLON	3020-05 F	1	330.00	330.00	A	641,489 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6027 WITH PRESSURE/VACUUM VALVE
C-447-134-2	641,896 GALLON	3020-05 F	1	330.00	330.00	A	641,896 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6028 WITH PRESSURE/VACUUM VALVE
C-447-135-2	643,208 GALLON	3020-05 F	1	330.00	330.00	A	643,208 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6029 WITH PRESSURE/VACUUM VALVE
C-447-136-2	643,378 GALLON	3020-05 F	1	330.00	330.00	A	643,378 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6030 WITH PRESSURE/VACUUM VALVE
C-447-137-2	643,676 GALLON	3020-05 F	1	330.00	330.00	A	643,676 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6031 WITH PRESSURE/VACUUM VALVE
C-447-138-2	642,762 GALLON	3020-05 F	1	330.00	330.00	A	642,762 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6032 WITH PRESSURE/VACUUM VALVE
C-447-139-2	642,796 GALLON	3020-05 F	1	330.00	330.00	A	642,796 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6033 WITH PRESSURE/VACUUM VALVE
C-447-140-2	644,594 GALLON	3020-05 F	1	330.00	330.00	A	644,594 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6034 WITH PRESSURE/VACUUM VALVE
C-447-141-2	642,126 GALLON	3020-05 F	1	330.00	330.00	A	642,126 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6035 WITH PRESSURE/VACUUM VALVE
C-447-142-2	642,874 GALLON	3020-05 F	1	330.00	330.00	A	642,874 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6036 WITH PRESSURE/VACUUM VALVE
C-447-143-2	643,803 GALLON	3020-05 F	1	330.00	330.00	A	643,803 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6037 WITH PRESSURE/VACUUM VALVE
C-447-144-2	641,307 GALLON	3020-05 F	1	330.00	330.00	A	641,307 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6038 WITH PRESSURE/VACUUM VALVE
C-447-145-2	643,509 GALLON	3020-05 F	1	330.00	330.00	A	643,509 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6039 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report
For Facility=447 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-447-146-2	643,199 GALLON	3020-05 F	1	330.00	330.00	A	643,199 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6040 WITH PRESSURE/VACUUM VALVE
C-447-147-2	644,851 GALLON	3020-05 F	1	330.00	330.00	A	644,851 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6041 WITH PRESSURE/VACUUM VALVE
C-447-148-2	642,555 GALLON	3020-05 F	1	330.00	330.00	A	642,555 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6042 WITH PRESSURE/VACUUM VALVE
C-447-149-2	642,690 GALLON	3020-05 F	1	330.00	330.00	A	642,690 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6043 WITH PRESSURE/VACUUM VALVE
C-447-150-2	642,940 GALLON	3020-05 F	1	330.00	330.00	A	642,940 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6044 WITH PRESSURE/VACUUM VALVE
C-447-151-2	644,141 GALLON	3020-05 F	1	330.00	330.00	A	644,141 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6045 WITH PRESSURE/VACUUM VALVE
C-447-152-2	643,365 GALLON	3020-05 F	1	330.00	330.00	A	643,365 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6046 WITH PRESSURE/VACUUM VALVE
C-447-153-2	642,506 GALLON	3020-05 F	1	330.00	330.00	A	642,506 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6047 WITH PRESSURE/VACUUM VALVE
C-447-154-2	643,192 GALLON	3020-05 F	1	330.00	330.00	A	643,192 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6048 WITH PRESSURE/VACUUM VALVE
C-447-155-2	643,544 GALLON	3020-05 F	1	330.00	330.00	A	643,544 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6049 WITH PRESSURE/VACUUM VALVE
C-447-156-2	642,863 GALLON	3020-05 F	1	330.00	330.00	A	642,863 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6050 WITH PRESSURE/VACUUM VALVE
C-447-157-2	645,153 GALLON	3020-05 F	1	330.00	330.00	A	645,153 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6051 WITH PRESSURE/VACUUM VALVE
C-447-158-2	643,894 GALLON	3020-05 F	1	330.00	330.00	A	643,894 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6052 WITH PRESSURE/VACUUM VALVE
C-447-159-2	642,374 GALLON	3020-05 F	1	330.00	330.00	A	642,374 GALLON STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6053 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report
For Facility=447 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-447-160-2	641,400 GALLON	3020-05 F	1	330.00	330.00	A	641,400 GALLON STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6054 WITH PRESSURE/VACUUM VALVE
C-447-161-2	642,257 GALLON	3020-05 F	1	330.00	330.00	A	642,257 GALLON STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6055 WITH PRESSURE/VACUUM VALVE
C-447-162-2	643,277 GALLON	3020-05 F	1	330.00	330.00	A	643,277 GALLON STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6056 WITH PRESSURE/VACUUM VALVE
C-447-163-2	641,867 GALLON	3020-05 F	1	330.00	330.00	A	641,867 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6501 WITH PRESSURE/VACUUM VALVE
C-447-164-2	642,338 GALLON	3020-05 F	1	330.00	330.00	A	642,338 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6502 WITH PRESSURE/VACUUM VALVE
C-447-165-2	641,222 GALLON	3020-05 F	1	330.00	330.00	A	641,222 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6503 WITH PRESSURE/VACUUM VALVE
C-447-166-2	641,763 GALLON	3020-05 F	1	330.00	330.00	A	641,763 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6504 WITH PRESSURE/VACUUM VALVE
C-447-167-2	642,501 GALLON	3020-05 F	1	330.00	330.00	A	642,501 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6505 WITH PRESSURE/VACUUM VALVE
C-447-168-2	642,658 GALLON	3020-05 F	1	330.00	330.00	A	642,658 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6506 WITH PRESSURE/VACUUM VALVE
C-447-169-2	643,620 GALLON	3020-05 F	1	330.00	330.00	A	643,620 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6507 WITH PRESSURE/VACUUM VALVE
C-447-170-2	642,526 GALLON	3020-05 F	1	330.00	330.00	A	642,526 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6508 WITH PRESSURE/VACUUM VALVE
C-447-171-2	643,178 GALLON	3020-05 F	1	330.00	330.00	A	643,178 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6509 WITH PRESSURE/VACUUM VALVE
C-447-172-2	642,090 GALLON	3020-05 F	1	330.00	330.00	A	642,090 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6510 WITH PRESSURE/VACUUM VALVE
C-447-173-2	642,542 GALLON	3020-05 F	1	330.00	330.00	A	642,542 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6511 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report
For Facility=447 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-447-174-2	642,788 GALLON	3020-05 F	1	330.00	330.00	A	642,788 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6512 WITH PRESSURE/VACUUM VALVE
C-447-175-2	640,725 GALLON	3020-05 F	1	330.00	330.00	A	640,725 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6513 WITH PRESSURE/VACUUM VALVE
C-447-176-2	643,118 GALLON	3020-05 F	1	330.00	330.00	A	643,118 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6514 WITH PRESSURE/VACUUM VALVE
C-447-177-2	640,772 GALLON	3020-05 F	1	330.00	330.00	A	640,772 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6515 WITH PRESSURE/VACUUM VALVE
C-447-178-2	643,295 GALLON	3020-05 F	1	330.00	330.00	A	643,295 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6516 WITH PRESSURE/VACUUM VALVE
C-447-179-2	642,491 GALLON	3020-05 F	1	330.00	330.00	A	642,491 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6517 WITH PRESSURE/VACUUM VALVE
C-447-180-2	643,051 GALLON	3020-05 F	1	330.00	330.00	A	643,051 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6518 WITH PRESSURE/VACUUM VALVE
C-447-181-2	642,451 GALLON	3020-05 F	1	330.00	330.00	A	642,451 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6519 WITH PRESSURE/VACUUM VALVE
C-447-182-2	642,094 GALLON	3020-05 F	1	330.00	330.00	A	642,094 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6520 WITH PRESSURE/VACUUM VALVE
C-447-183-2	642,344 GALLON	3020-05 F	1	330.00	330.00	A	642,344 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6521 WITH PRESSURE/VACUUM VALVE
C-447-184-2	642,245 GALLON	3020-05 F	1	330.00	330.00	A	642,245 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6522 WITH PRESSURE/VACUUM VALVE
C-447-185-2	643,156 GALLON	3020-05 F	1	330.00	330.00	A	643,156 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6523 WITH PRESSURE/VACUUM VALVE
C-447-186-2	641,595 GALLON	3020-05 F	1	330.00	330.00	A	641,595 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6524 WITH PRESSURE/VACUUM VALVE
C-447-187-2	642,871 GALLON	3020-05 F	1	330.00	330.00	A	642,871 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6526 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report
For Facility=447 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-447-188-2	639,880 GALLON	3020-05 F	1	330.00	330.00	A	639,880 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6527 WITH PRESSURE/VACUUM VALVE
C-447-189-2	641,428 GALLON	3020-05 F	1	330.00	330.00	A	641,428 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6528 WITH PRESSURE/VACUUM VALVE
C-447-190-2	642,193 GALLON	3020-05 F	1	330.00	330.00	A	642,193 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6529 WITH PRESSURE/VACUUM VALVE
C-447-191-2	642,592 GALLON	3020-05 F	1	330.00	330.00	A	642,592 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6601 WITH PRESSURE/VACUUM VALVE
C-447-192-2	643,295 GALLON	3020-05 F	1	330.00	330.00	A	643,295 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6602 WITH PRESSURE/VACUUM VALVE
C-447-193-2	640,961 GALLON	3020-05 F	1	330.00	330.00	A	640,961 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6603 WITH PRESSURE/VACUUM VALVE
C-447-194-2	640,434 GALLON	3020-05 F	1	330.00	330.00	A	640,434 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6604 WITH PRESSURE/VACUUM VALVE
C-447-195-2	642,594 GALLON	3020-05 F	1	330.00	330.00	A	642,594 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6609 WITH PRESSURE/VACUUM VALVE
C-447-196-2	641,115 GALLON	3020-05 F	1	330.00	330.00	A	641,115 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6610 WITH PRESSURE/VACUUM VALVE
C-447-197-2	641,345 GALLON	3020-05 F	1	330.00	330.00	A	641,345 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6611 WITH PRESSURE/VACUUM VALVE
C-447-198-2	641,629 GALLON	3020-05 F	1	330.00	330.00	A	641,629 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6612 WITH PRESSURE/VACUUM VALVE
C-447-199-2	640,936 GALLON	3020-05 F	1	330.00	330.00	A	640,936 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6617 WITH PRESSURE/VACUUM VALVE
C-447-200-2	642,121 GALLON	3020-05 F	1	330.00	330.00	A	642,121 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6618 WITH PRESSURE/VACUUM VALVE
C-447-201-2	641,720 GALLON	3020-05 F	1	330.00	330.00	A	641,720 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6619 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report
For Facility=447 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-447-202-2	642,051 GALLON	3020-05 F	1	330.00	330.00	A	642,051 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6620 WITH PRESSURE/VACUUM VALVE
C-447-203-2	640,612 GALLON	3020-05 F	1	330.00	330.00	A	640,612 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6625 WITH PRESSURE/VACUUM VALVE
C-447-204-2	642,491 GALLON	3020-05 F	1	330.00	330.00	A	642,491 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6626 WITH PRESSURE/VACUUM VALVE
C-447-205-2	642,974 GALLON	3020-05 F	1	330.00	330.00	A	642,974 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6627 WITH PRESSURE/VACUUM VALVE
C-447-206-2	642,792 GALLON	3020-05 F	1	330.00	330.00	A	642,792 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6628 WITH PRESSURE/VACUUM VALVE
C-447-207-2	640,729 GALLON	3020-05 F	1	330.00	330.00	A	640,729 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6633 WITH PRESSURE/VACUUM VALVE
C-447-208-2	641,378 GALLON	3020-05 F	1	330.00	330.00	A	641,378 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6634 WITH PRESSURE/VACUUM VALVE
C-447-209-2	641,008 GALLON	3020-05 F	1	330.00	330.00	A	641,008 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6641 WITH PRESSURE/VACUUM VALVE
C-447-210-2	639,975 GALLON	3020-05 F	1	330.00	330.00	A	639,975 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6642 WITH PRESSURE/VACUUM VALVE
C-447-211-2	640,530 GALLON	3020-05 F	1	330.00	330.00	A	640,530 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6649 WITH PRESSURE/VACUUM VALVE
C-447-212-2	640,872 GALLON	3020-05 F	1	330.00	330.00	A	640,872 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6650 WITH PRESSURE/VACUUM VALVE
C-447-213-2	641,462 GALLON	3020-05 F	1	330.00	330.00	A	641,462 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6657 WITH PRESSURE/VACUUM VALVE
C-447-214-2	641,263 GALLON	3020-05 F	1	330.00	330.00	A	641,263 GALLON STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND STORAGE TANK 6658 WITH PRESSURE/VACUUM VALVE
C-447-215-1	650,472 GALLONS	3020-05 F	1	330.00	330.00	A	650,472 GALLON STEEL WINE AND DISTILLED SPIRITS STORAGE TANK 6002 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report
For Facility=447 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-447-216-1	670,445 GALLONS	3020-05 F	1	330.00	330.00	A	670,445 GALLON STEEL WINE AND DISTILLED SPIRITS STORAGE TANK 6005 WITH PRESSURE/VACUUM VALVE
C-447-217-1	661,423 GALLONS	3020-05 F	1	330.00	330.00	A	661,423 GALLON STEEL WINE AND DISTILLED SPIRITS STORAGE TANK 6006 WITH PRESSURE/VACUUM VALVE
C-447-218-1	661,075 GALLONS	3020-05 F	1	330.00	330.00	A	661,075 GALLON STEEL WINE AND DISTILLED SPIRITS STORAGE TANK 6007 WITH PRESSURE/VACUUM VALVE
C-447-219-1	669,320 GALLONS	3020-05 F	1	330.00	330.00	A	669,320 GALLON STEEL WINE AND DISTILLED SPIRITS STORAGE TANK 6008 WITH PRESSURE/VACUUM VALVE
C-447-220-1	661,577 GALLONS	3020-05 F	1	330.00	330.00	A	661,577 GALLON STEEL WINE AND DISTILLED SPIRITS STORAGE TANK 6009 WITH PRESSURE/VACUUM VALVE
C-447-221-1	661,634 GALLONS	3020-05 F	1	330.00	330.00	A	661,634 GALLON STEEL WINE AND DISTILLED SPIRITS STORAGE TANK 6010 WITH PRESSURE/VACUUM VALVE
C-447-222-1	662,596 GALLONS	3020-05 F	1	330.00	330.00	A	662,596 GALLON STEEL WINE AND DISTILLED SPIRITS STORAGE TANK 6011 WITH PRESSURE/VACUUM VALVE
C-447-223-1	669,445 GALLONS	3020-05 F	1	330.00	330.00	A	669,445 GALLON STEEL WINE AND DISTILLED SPIRITS STORAGE TANK 6012 WITH PRESSURE/VACUUM VALVE
C-447-224-1	639,424 GALLONS	3020-05 F	1	330.00	330.00	A	639,424 GALLON STEEL INSULATED WINE STORAGE TANK #6629 WITH PRESSURE/VACUUM VALVE
C-447-225-4	7.5 hp electric motors	3020-01 A	1	97.00	97.00	A	WINERY WASTEWATER PRETREATMENT AND EQUALIZATION OPERATION SERVED BY A SIEMENS ZABOCS BIOFILTER SHARED WITH C-447-226 AND -227
C-447-226-12	39,400 kBtu/hr	3020-02 H	1	1,128.00	1,128.00	A	175,320 GALLON WINERY WASTEWATER ANAEROBIC REACTOR SERVED BY A BIOGAS SCRUBBING SYSTEM SHARED WITH C-447-227 AND VENTED TO AN ENCLOSED 39.4 MMBTU/HR VAREC 244EGF FLARE OR BOILERS C-447-1, '2, '3, '295, OR '329, AND 502,000 GALLON WINERY WASTEWATER SULFIDE OXIDATION TANK
C-447-227-2	502,100 gallon	3020-05 F	1	330.00	330.00	A	502,100 GALLON WINERY WASTEWATER ANAEROBIC REACTOR SERVED BY A BIOGAS SCRUBBING SYSTEM LISTED ON C-447-226
C-447-230-2	600 HP ELECTRIC MOTOR RATING	3020-01 F	1	666.00	666.00	A	AGRICULTURAL WASTE COMPOSTING OPERATION INCLUDING MORBARK, MODEL 3800, ELECTRICALLY POWERED HORIZONTAL GRINDER
C-447-233-2	38,571 gallon storage silo (6,000 cubic feet)	3020-05 C	1	149.00	149.00	A	6,000 CUBIC FEET DIATOMACEOUS EARTH STORAGE SILO SERVED BY A STACLEAN MODEL 9-3.2-BDS BIN VENT FILTER
C-447-234-1	328,225 gallons	3020-05 E	1	270.00	270.00	A	328,225 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3001 WITH PRESSURE/VACUUM VALVE
C-447-235-1	327,544 gallons	3020-05 E	1	270.00	270.00	A	327,544 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3002 WITH PRESSURE/VACUUM VALVE
C-447-236-1	328,017 gallons	3020-05 E	1	270.00	270.00	A	328,017 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3003 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report
For Facility=447 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-447-237-1	329,088 gallons	3020-05 E	1	270.00	270.00	A	329,088 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3004 WITH PRESSURE/VACUUM VALVE
C-447-238-1	333,405 gallons	3020-05 E	1	270.00	270.00	A	333,405 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3005 WITH PRESSURE/VACUUM VALVE
C-447-239-1	336,009 gallons	3020-05 E	1	270.00	270.00	A	336,009 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3006 WITH PRESSURE/VACUUM VALVE
C-447-240-1	328,067 gallons	3020-05 E	1	270.00	270.00	A	328,067 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3007 WITH PRESSURE/VACUUM VALVE
C-447-241-1	326,941 gallons	3020-05 E	1	270.00	270.00	A	326,941 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3008 WITH PRESSURE/VACUUM VALVE
C-447-242-1	328,765 gallons	3020-05 E	1	270.00	270.00	A	328,765 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3009 WITH PRESSURE/VACUUM VALVE
C-447-243-1	330,054 gallons	3020-05 E	1	270.00	270.00	A	330,054 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3010 WITH PRESSURE/VACUUM VALVE
C-447-244-1	333,641 gallons	3020-05 E	1	270.00	270.00	A	333,641 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3011 WITH PRESSURE/VACUUM VALVE
C-447-245-1	333,181 gallons	3020-05 E	1	270.00	270.00	A	333,181 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 3012 WITH PRESSURE/VACUUM VALVE
C-447-255-1	2,027 gallons	3020-05 A	1	83.00	83.00	A	2,027 GALLON STEEL DISTILLED SPIRITS STORAGE TANK D1 WITH PRESSURE/VACUUM VALVE
C-447-256-1	52,788 gallons	3020-05 D	1	203.00	203.00	A	52,788 GALLON STEEL DISTILLED SPIRITS STORAGE TANK P3 WITH PRESSURE/VACUUM VALVE
C-447-257-1	16,726 gallons	3020-05 B	1	103.00	103.00	A	16,726 GALLON STEEL DISTILLED SPIRITS STORAGE TANK P4 WITH PRESSURE/VACUUM VALVE
C-447-258-1	16,754 gallons	3020-05 B	1	103.00	103.00	A	16,754 GALLON STEEL DISTILLED SPIRITS STORAGE TANK P5 WITH PRESSURE/VACUUM VALVE
C-447-259-1	16,711 gallons	3020-05 B	1	103.00	103.00	A	16,711 GALLON STEEL DISTILLED SPIRITS STORAGE TANK P6 WITH PRESSURE/VACUUM VALVE
C-447-260-1	16,725 gallons	3020-05 B	1	103.00	103.00	A	16,725 GALLON STEEL DISTILLED SPIRITS STORAGE TANK P7 WITH PRESSURE/VACUUM VALVE
C-447-261-1	4,562 gallons	3020-05 A	1	83.00	83.00	A	4,562 GALLON STEEL DISTILLED SPIRITS STORAGE TANK P8 WITH PRESSURE/VACUUM VALVE
C-447-262-1	5,333 gallons	3020-05 B	1	103.00	103.00	A	5,333 GALLON STEEL DISTILLED SPIRITS STORAGE TANK P9 WITH PRESSURE/VACUUM VALVE
C-447-263-1	49,915 gallons	3020-05 C	1	149.00	149.00	A	49,915 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 501 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report
For Facility=447 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-447-264-1	49,964 gallons	3020-05 C	1	149.00	149.00	A	49,964 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 502 WITH PRESSURE/VACUUM VALVE
C-447-265-1	50,146 gallons	3020-05 D	1	203.00	203.00	A	50,146 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 503 WITH PRESSURE/VACUUM VALVE
C-447-266-1	50,059 gallons	3020-05 D	1	203.00	203.00	A	50,059 GALLON STEEL DISTILLED SPIRITS STORAGE TANK 504 WITH PRESSURE/VACUUM VALVE
C-447-267-2	130 bhp	3020-10 B	1	129.00	129.00	A	160 BHP ELECTRONICALLY REGULATED TO 130 BHP CUMMINS MODEL CFP5E-F30 TIER 3 CERTIFIED DIESEL-FIRED EMERGENCY STANDBY IC ENGINE POWERING A FIREWATER PUMP
C-447-268-1	misc.	3020-06	1	116.00	116.00	A	GREEN WASTE ORGANIC MATERIAL RECEIVING, STORAGE, AND MIXING OPERATION
C-447-269-1	misc.	3020-06	1	116.00	116.00	A	OPEN WINDROW ACTIVE AND CURING PHASE GREEN WASTE COMPOSTING OPERATION WITH AN INTEGRATED WATERING SYSTEM
C-447-270-0	Miscellaneous	3020-06	1	116.00	116.00	A	FINISHED COMPOST STORAGE AND LOADOUT OPERATION
C-447-271-1	609,251 gallons	3020-05 F	1	330.00	330.00	A	609,251 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6635) WITH PRESSURE/VACUUM VALVE
C-447-272-1	612,539 gallons	3020-05 F	1	330.00	330.00	A	612,539 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6636) WITH PRESSURE/VACUUM VALVE
C-447-273-1	612,124 gallons	3020-05 F	1	330.00	330.00	A	612,124 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6637) WITH PRESSURE/VACUUM VALVE
C-447-274-1	612,972 gallons	3020-05 F	1	330.00	330.00	A	612,972 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6638) WITH PRESSURE/VACUUM VALVE
C-447-275-1	611,101 gallons	3020-05 F	1	330.00	330.00	A	612,770 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6639) WITH PRESSURE/VACUUM VALVE
C-447-276-1	611,761 gallons	3020-05 F	1	330.00	330.00	A	611,887 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6640) WITH PRESSURE/VACUUM VALVE
C-447-277-1	615,034 gallons	3020-05 F	1	330.00	330.00	A	611,101 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6643) WITH PRESSURE/VACUUM VALVE
C-447-278-1	613,196 gallons	3020-05 F	1	330.00	330.00	A	611,761 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6644) WITH PRESSURE/VACUUM VALVE
C-447-279-1	611,612 gallons	3020-05 F	1	330.00	330.00	A	615,034 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6645) WITH PRESSURE/VACUUM VALVE

Detailed Facility Report
For Facility=447 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-447-280-1	612,592 gallons	3020-05 F	1	330.00	330.00	A	613,196 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6646) WITH PRESSURE/VACUUM VALVE
C-447-281-1	613,109 gallons	3020-05 F	1	330.00	330.00	A	612,106 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6647) WITH PRESSURE/VACUUM VALVE
C-447-282-1	613,536 gallons	3020-05 F	1	330.00	330.00	A	612,359 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6648) WITH PRESSURE/VACUUM VALVE
C-447-283-1	612,570 gallons	3020-05 F	1	330.00	330.00	A	611,612 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6651) WITH PRESSURE/VACUUM VALVE
C-447-284-1	611,948 gallons	3020-05 F	1	330.00	330.00	A	612,592 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6652) WITH PRESSURE/VACUUM VALVE
C-447-285-1	613,637 gallons	3020-05 F	1	330.00	330.00	A	613,109 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6653) WITH PRESSURE/VACUUM VALVE
C-447-286-1	616,758 gallons	3020-05 F	1	330.00	330.00	A	613,536 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6654) WITH PRESSURE/VACUUM VALVE
C-447-287-1	612,770 gallons	3020-05 F	1	330.00	330.00	A	613,913 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6655) WITH PRESSURE/VACUUM VALVE
C-447-288-1	611,887 gallons	3020-05 F	1	330.00	330.00	A	615,603 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6656) WITH PRESSURE/VACUUM VALVE
C-447-289-1	612,106 gallons	3020-05 F	1	330.00	330.00	A	612,570 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6659) WITH PRESSURE/VACUUM VALVE
C-447-290-1	612,359 gallons	3020-05 F	1	330.00	330.00	A	611,948 GALLON INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6660) WITH PRESSURE/VACUUM VALVE
C-447-291-1	613,913 gallons	3020-05 F	1	330.00	330.00	A	613,637 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6661) WITH PRESSURE/VACUUM VALVE
C-447-292-1	615,603 gallons	3020-05 F	1	330.00	330.00	A	616,758 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6662) WITH PRESSURE/VACUUM VALVE
C-447-293-1	615,000 gallons	3020-05 F	1	330.00	330.00	A	615,000 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6663) WITH PRESSURE/VACUUM VALVE

Detailed Facility Report
For Facility=447 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-447-294-1	615,446 gallons	3020-05 F	1	330.00	330.00	A	615,446 GALLON INSULATED STAINLESS STEEL RED AND WHITE WINE FERMENTATION AND STORAGE TANK (TANK 6664) WITH PRESSURE/VACUUM VALVE
C-447-295-1	99 MMBtu/hr	3020-02 H	1	1,128.00	1,128.00	A	99 MMBTU/HR VICTORY ENERGY OPERATIONS NATURAL GAS/BIOGAS-FIRED BOILER EQUIPPED WITH A TODD VERIFLAME MODEL TODD VERIFLAME 99 LOW NOX BURNER, FLUE GAS RECIRCULATION SYSTEM, AND O2 CONTROLLER SERVED BY A NATIONWIDE MODEL CATASTAK SELECTIVE CATALYTIC REDUCTION (SCR) SYSTEM (BOILER #4)
C-447-296-1	629,000 gallons	3020-05 F	1	330.00	330.00	A	629,000 GALLON NOMINAL (629,640 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6701) WITH PRESSURE/VACUUM VALVE
C-447-297-1	629,000 gallons	3020-05 F	1	330.00	330.00	A	629,000 GALLON NOMINAL (629,689 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6702) WITH PRESSURE/VACUUM VALVE
C-447-298-1	629,000 gallons	3020-05 F	1	330.00	330.00	A	629,000 GALLON NOMINAL (629,298 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6705) WITH PRESSURE/VACUUM VALVE
C-447-299-1	629,000 gallons	3020-05 F	1	330.00	330.00	A	629,000 GALLON NOMINAL (630,154 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6706) WITH PRESSURE/VACUUM VALVE
C-447-300-1	629,000 gallons	3020-05 F	1	330.00	330.00	A	629,000 GALLON NOMINAL (628,456 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6709) WITH PRESSURE/VACUUM VALVE
C-447-301-1	629,000 gallons	3020-05 F	1	330.00	330.00	A	629,000 GALLON NOMINAL (628,713 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6710) WITH PRESSURE/VACUUM VALVE
C-447-302-1	629,000 gallons	3020-05 F	1	330.00	330.00	A	629,000 GALLON NOMINAL (630,565 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6713) WITH PRESSURE/VACUUM VALVE
C-447-303-1	629,000 gallons	3020-05 F	1	330.00	330.00	A	629,000 GALLON NOMINAL (629,783 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6714) WITH PRESSURE/VACUUM VALVE
C-447-304-1	629,000 gallons	3020-05 F	1	330.00	330.00	A	629,000 GALLON NOMINAL (628,504 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6717) WITH PRESSURE/VACUUM VALVE
C-447-305-1	629,000 gallons	3020-05 F	1	330.00	330.00	A	629,000 GALLON NOMINAL (627,927 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6718) WITH PRESSURE/VACUUM VALVE
C-447-306-1	629,000 gallons	3020-05 F	1	330.00	330.00	A	629,000 GALLON NOMINAL (628,545 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6721) WITH PRESSURE/VACUUM VALVE

Detailed Facility Report
For Facility=447 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-447-307-1	629,000 gallons	3020-05 F	1	330.00	330.00	A	629,000 GALLON NOMINAL (627,933 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6722) WITH PRESSURE/VACUUM VALVE
C-447-308-1	629,000 gallons	3020-05 F	1	330.00	330.00	A	629,000 GALLON NOMINAL (628,002 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6725) WITH PRESSURE/VACUUM VALVE
C-447-309-1	629,000 gallons	3020-05 F	1	330.00	330.00	A	629,000 GALLON NOMINAL (628,728 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6726) WITH PRESSURE/VACUUM VALVE
C-447-310-1	629,000 gallons	3020-05 F	1	330.00	330.00	A	629,000 GALLON NOMINAL (630,044 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6729) WITH PRESSURE/VACUUM VALVE
C-447-311-1	629,000 gallons	3020-05 F	1	330.00	330.00	A	629,000 GALLON NOMINAL (628,837 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6730) WITH PRESSURE/VACUUM VALVE
C-447-312-1	629,000 gallons	3020-05 F	1	330.00	330.00	A	629,000 GALLON NOMINAL (626,556 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6703) WITH PRESSURE/VACUUM VALVE
C-447-313-1	629,000 gallons	3020-05 F	1	330.00	330.00	A	629,000 GALLON NOMINAL (627,464 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6704) WITH PRESSURE/VACUUM VALVE
C-447-314-1	629,000 gallons	3020-05 F	1	330.00	330.00	A	629,000 GALLON NOMINAL (628,154 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6707) WITH PRESSURE/VACUUM VALVE
C-447-315-1	629,000 gallons	3020-05 F	1	330.00	330.00	A	629,000 GALLON NOMINAL (627,892 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6708) WITH PRESSURE/VACUUM VALVE
C-447-316-1	629,000 gallons	3020-05 F	1	330.00	330.00	A	629,000 GALLON NOMINAL (632,240 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6711) WITH PRESSURE/VACUUM VALVE
C-447-317-1	629,000 gallons	3020-05 F	1	330.00	330.00	A	629,000 GALLON NOMINAL (634,362 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6712) WITH PRESSURE/VACUUM VALVE
C-447-318-1	629,000 gallons	3020-05 F	1	330.00	330.00	A	629,000 GALLON NOMINAL (632,359 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6715) WITH PRESSURE/VACUUM VALVE
C-447-319-1	629,000 gallons	3020-05 F	1	330.00	330.00	A	629,000 GALLON NOMINAL (632,903 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6716) WITH PRESSURE/VACUUM VALVE
C-447-320-1	629,000 gallons	3020-05 F	1	330.00	330.00	A	629,000 GALLON NOMINAL (626,432 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6719) WITH PRESSURE/VACUUM VALVE

Detailed Facility Report
For Facility=447 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-447-321-1	629,000 gallons	3020-05 F	1	330.00	330.00	A	629,000 GALLON NOMINAL (624,782 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6720) WITH PRESSURE/VACUUM VALVE
C-447-322-1	629,000 gallons	3020-05 F	1	330.00	330.00	A	629,000 GALLON NOMINAL (626,387 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6723) WITH PRESSURE/VACUUM VALVE
C-447-323-1	629,000 gallons	3020-05 F	1	330.00	330.00	A	629,000 GALLON NOMINAL (627,401 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6724) WITH PRESSURE/VACUUM VALVE
C-447-324-1	629,000 gallons	3020-05 F	1	330.00	330.00	A	629,000 GALLON NOMINAL (628,736 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6727) WITH PRESSURE/VACUUM VALVE
C-447-325-1	629,000 gallons	3020-05 F	1	330.00	330.00	A	629,000 GALLON NOMINAL (628,647 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6728) WITH PRESSURE/VACUUM VALVE
C-447-326-1	629,000 gallons	3020-05 F	1	330.00	330.00	A	629,000 GALLON NOMINAL (628,179 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6731) WITH PRESSURE/VACUUM VALVE
C-447-327-1	629,000 gallons	3020-05 F	1	330.00	330.00	A	629,000 GALLON NOMINAL (628,120 GAUGE) INSULATED STAINLESS STEEL WINE STORAGE TANK (TANK 6732) WITH PRESSURE/VACUUM VALVE
C-447-328-0	44,880 Gallons	3020-05 C	1	149.00	149.00	A	DIATOMACEOUS EARTH RECEIVING AND STORAGE OPERATION WITH A 6,000 CUBIC FEET STORAGE SILO E SERVED BY A BIN VENT FILTER SYSTEM
C-447-329-0	99 MMBtu/hr	3020-02 H	1	1,128.00	1,128.00	A	99 MMBTU/HR VICTORY ENERGY OPERATIONS NATURAL GAS/BIOGAS-FIRED BOILER EQUIPPED WITH A COEN VERIFLAME MODEL COEN VERIFLAME 99 LOW NOX BURNER, FLUE GAS RECIRCULATION SYSTEM, AND O2 CONTROLLER SERVED BY A NATIONWIDE MODEL CATASTAK SELECTIVE CATALYTIC REDUCTION (SCR) SYSTEM (BOILER #3)

Number of Facilities Reported: 1