San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

OCT 17 2017

Mr. Guy Ruhland
Heck Cellars
15401 Bear Mountain Winery Road
Di Giorgio, CA 93203

Re: Notice of Preliminary Decision – Title V Permit Renewal
District Facility # S-381
Project # 1162605

Dear Mr. Ruhland:

Enclosed for your review and comment is the District's analysis of the application to renew the Federally Mandated Operating Permit for Heck Cellars at 15401 Bear Mountain Winery Road, Di Giorgio, California.

The notice of preliminary decision for this project will be published approximately three days from the date of this letter. After addressing all comments made during the 30-day public notice and the 45-day EPA comment periods, the District intends to issue the renewed Federally Mandated Operating Permit. Please submit your written comments on this project within the 30-day public comment period, as specified in the enclosed public notice.

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Leonard Scandura, Permit Services Manager, at (661) 392-5500.

Sincerely,

Arnaud Marjollet
Director of Permit Services

Enclosures

cc: Tung Le, CARB (w/enclosure) via email
cc: Gerardo C. Rios, EPA (w/enclosure) via email

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

www.valleyair.org www.healthyairliving.com

Printed on recycled paper.

SAN JOAQUIN VALLEY
AIR POLLUTION CONTROL DISTRICT

Proposed Title V Permit Renewal Evaluation
Heck Cellars
S-381

TABLE OF CONTENTS

I. PROPOSAL 2
II. FACILITY LOCATION 2
III. EQUIPMENT LISTING 2
IV. GENERAL PERMIT TEMPLATE USAGE 2
V. SCOPE OF EPA AND PUBLIC REVIEW 2
VI. FEDERALLY ENFORCEABLE REQUIREMENTS 3
VII. REQUIREMENTS NOT FEDERALLY ENFORCEABLE 5
VIII. PERMIT REQUIREMENTS 5
IX. PERMIT SHIELD 8
X. CALIFORNIA ENVIRONMENTAL QUALITY ACT 8
XI. PERMIT CONDITIONS 9

ATTACHMENTS 9

A. DRAFT RENEWED TITLE V OPERATING PERMIT
B. PREVIOUS TITLE V OPERATING PERMIT
C. DETAILED SUMMARY LIST OF FACILITY PERMITS

TITLE V PERMIT RENEWAL EVALUATION

Winery

Engineer: David Torii
Date: 10/5/17

Facility Number: S-381
Facility Name: Heck Cellars
Mailing Address: 15401 Bear Mountain Winery Road
Di Giorgio, CA 93203

Contact Name: Guy Ruhland
Phone: 661-854-6120

Responsible Official: Guy Ruhland
Title: Winery Manager

Project # : 1162605
Deemed Complete: 7/26/17

I. PROPOSAL

Heck Cellars was issued a Title V permit on 10/11/12. As required by District Rule 2520, the applicant is requesting a permit renewal. The existing Title V permit shall be reviewed and modified to reflect all applicable District and federal rules updated, removed, or added since the issuance of the initial Title V permit.

The purpose of this evaluation is to provide the legal and factual basis for all updated applicable requirements and to determine if the facility will comply with these updated requirements. It also specifically identifies all additions, deletions, and/or changes made to permit conditions or equipment descriptions.

II. FACILITY LOCATION

Heck Cellars is located at 15401 Bear Mountain Winery Road in Di Giorgio.

III. EQUIPMENT LISTING

A detailed facility printout listing all permitted equipment at the facility is included as Attachment C.

IV. GENERAL PERMIT TEMPLATE USAGE

The applicant does not propose to use any model general permit templates.

V. SCOPE OF EPA AND PUBLIC REVIEW

Certain segments of the proposed Renewed Operating Permit are based on model general permit templates that have been previously subject to EPA and public review. The terms and conditions from the model general permit templates are included in the proposed permit and are not subject to further EPA and public review.

For permit applications utilizing model general permit templates, public and agency comments on the District's proposed actions are limited to the applicant's eligibility for model general permit template, applicable requirements not covered by the model general permit template, and the applicable procedural requirements for issuance of Title V Operating Permits.

The applicant is not requesting any model general permit templates. Therefore, all federally enforceable conditions in this current Title V permit will be subject to EPA and public review.

VI. FEDERALLY ENFORCEABLE REQUIREMENTS

A. Rules Updated

- District Rule 2020, Exemptions (amended December 20, 2007 ⇒ amended December 18, 2014)
- District Rule 2201, New and Modified Stationary Source Review Rule (amended December 18, 2008 ⇒ amended February 18, 2016)
- District Rule 4702 Internal Combustion Engines — Phase 2 (amended November 14, 2013)
- 40 CFR Part 60 Subpart Dc—Standards of Performance for Small Industrial-Commercial-Institutional Steam Generating Units (2/16/2012)
- 40 CFR Part 60, Subpart IIII, Standards of Performance for Stationary
- Compression Ignition Internal Combustion Engines (2/27/14)
- 40 CFR Part 63, Subpart ZZZZ, National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines (amended 2/27/2014)
- 40 CFR Part 82, Subpart B Stratospheric Ozone (amended June 25, 2013)
- 40 CFR Part 82, Subpart F Stratospheric Ozone (amended June 25, 2013)
- 40 CFR Part 82, Subpart B, Servicing of Motor Vehicle Air Conditioners
- (amended June 18, 2008 ⇒ amended June 25, 2013)
- 40 CFR Part 82, Subpart F, Recycling and Emission Reduction (amended June 18, 2008 ⇒ amended April 10, 2015)

B. Rules Removed

There are no applicable rules that were removed since the last Title V renewal.

C. Rules Added

None.

D. Rules Not Updated

- District Rule 1070 Inspections (amended December 17, 1992)
- District Rule 1080, Stack Monitoring (amended December 17, 1992)
- District Rule 1081, Source Sampling (amended December 16, 1993)
- District Rule 1100, Equipment Breakdown (amended December 17, 1992)
- District Rule 1160, Emission Statements (adopted November 18, 1992)
- District Rule 2010, Permits Required (amended December 17, 1992)
- District Rule 2031, Transfer of Permits (amended December 17, 1992)
- District Rule 2040, Applications (amended December 17, 1992)
- District Rule 2070, Standards for Granting Applications (amended December 17, 1992)
- District Rule 2080, Conditional Approval (amended December 17, 1992)
- District Rule 2410, Prevention of Significant Deterioration (adopted June 16, 2011, effective November 26, 2012)
- District Rule 2520, Federally Mandated Operating Permits (amended June
- 21, 2001)
- District Rule 4001 New Source Performance Standards (amended January
- 19, 1995; amended September 17, 1997; amended April 14, 1999)
- District Rule 4101, Visible Emissions (amended February 17, 2005)
- District Rule 4102, Nuisance (amended December 17, 1992)
- District Rule 4201, Particulate Matter Concentration (amended December 17, 1992)
- District Rule 4202, Particulate Matter - Emission Rate (amended December
- 17, 1992)
- District Rule 4301, Fuel Burning Equipment (amended December 17,
- 1992)
- District Rule 4305, Boilers, Steam Generators and Process Heaters - Phase 2 (amended August 21, 2003)
- District Rule 4306, Boilers, Steam Generators and Process Heaters - Phase 3 (amended October 16, 2008)
- District Rule 4601 Architectural Coatings (amended December 17, 2009)
- Rule 4701 Internal Combustion Engines – Phase 1 (amended 8/21/03)
- District Rule 8021, Construction, Demolition, Excavation, Extraction, and Other Earthmoving Activities (amended August 19, 2004)
- District Rule 8021 Construction, Demolition, Excavation, Extraction, And
- Other Earthmoving Activities (November 15, 2001; amended August 19, 2004)
- District Rule 8011 General Requirements (amended August 19, 2004)
- District Rule 8031, Bulk Materials (amended August 19, 2004)
- District Rule 8041, Carryout and Trackout (amended August 19, 2004)
- District Rule 8051, Open Areas (amended August 19, 2004)
- District Rule 8061, Paved and Unpaved Roads (amended August 19, 2004)
- District Rule 8071, Unpaved Vehicle/Equipment Traffic Areas (amended September 16, 2004)
- 40 CFR Part 60 Appendix F (7/1/91)
- 40 CFR Part 61, Subpart M, National Emission Standard for Asbestos (7/20/04)
- 40 CFR Part 64, Compliance Assurance Monitoring (CAM)

VII. REQUIREMENTS NOT FEDERALLY ENFORCEABLE

For each Title V source, the District issues a single permit that contains the Federally Enforceable requirements, as well as the District-only requirements. The District-only requirements are not a part of the Title V Operating Permits. The terms and conditions that are part of the facility's Title V permit are designated as "Federally Enforceable Through Title V Permit".

For this facility, the following are not federally enforceable and will not be discussed in further detail:

A. Rules Added/Updated

None.

B. Rules Not Updated

District Rule 4102, Nuisance (as amended December 17, 1992)

VIII. PERMIT REQUIREMENTS

The purpose of this evaluation is to review changes to federally enforceable requirements; therefore, this compliance section will only address rules that have been amended or added since the issuance of the initial Title V permit or most recent renewal of the Title V permit.

A. District Rule 2020 - Exemptions

District Rule 2020 lists equipment which is specifically exempt from obtaining permits and specifies recordkeeping requirements to verify such exemptions. The amendments to this rule do not have any effect on current permit requirements and will therefore not be addressed in this evaluation.

B. District Rule 2201 - New and Modified Stationary Source Review Rule (NSR)

District Rule 2201 has been amended since this facility's initial Title V permit was issued. However, the requirements of this rule are only triggered at the time the source undergoes a modification. All applicable requirements from any NSR permit actions have already been incorporated into the current Title V permit.

C. District Rule 2410 – Prevention of Significant Deterioration (PSD)

District Rule 2410 has been newly adopted since this Title V permit was last renewed. However the requirements of this rule are only triggered at the time the source undergoes a modification. All applicable requirements from any PSD permit actions have already been incorporated into the current Title V permit. (OR …, except for the terms from project # xxx, which are being included as part of this Title V permit renewal (see Section XXX for more information.) OR This source has never been subject to this rule, therefore

there are no PSD permit applicable requirements to include in the Title V permit.

District Rule 2410 has been newly adopted since this Title V permit was last renewed. However the requirements of this rule are only triggered at the time the source undergoes a modification. All applicable requirements from any PSD permit actions have already been incorporated into the current Title V permit.

D. District Rule 2520 - Federally Mandated Operating Permits

No changes to this Rule have occurred since issuance of the previous TV permit; however, greenhouse gas emissions will be addressed under Rule 2520 during this renewal.

Greenhouse Gas Discussion

There are no federally applicable Greenhouse Gas (GHG) requirements for this source. It should be noted that the Mandatory Greenhouse Gas Reporting rule (40 CFR Part 98) is not included in the definition of an applicable requirement within Title V (per 40 CFR 71.2). Therefore, there will be no further discussion of GHG in this evaluation.

E. District Rule 4702 - Internal Combustion Engines – Phase II

The facility's IC engines are emergency standby units and are only subject to the administrative requirements of Rule 4702 which weren't revised in the 11/14/13 amendment. No change to the permits is required as a result of the amendment; ttherefore, continued compliance with this regulation is expected

F. 40 CFR Part 60 Subpart Dc Standards of Performance for Small Industrial-Commercial-Institutional Steam Generating Units

This rule incorporates NSPS from Part 60, Chapter 1, Title 40, Code of Federal Regulations (CFR); and applies to all new sources of air pollution and modifications of existing sources of air pollution listed in 40 CFR Part 60. 40 CFR Part 60, Subpart Dc applies to Small Industrial-Commercial-Industrial Steam Generators between 10 MMBtu/hr and 100 MMBtu/hr (post-6/9/89 construction, modification or, reconstruction). Subpart Dc has standards for SO_X and PM_{10}. Boiler S-381-9 is subject to Subpart Dc requirements.

This subpart was amended on 2/16/12.

The 2/16/12 amendment revided PM emission monitoring requirements. Boiler S-381-9 is gas-fired and; therefore, is not subject to the PM testing and monitoring requirements. No change to the permit is required as a result of the amendments; ttherefore, continued compliance with this regulation is expected

G. 40 CFR Part 60, Subpart IIII--Standards of Performance for Stationary Compression Ignition Internal Combustion Engines

Pursuant to section 60.4200(3) this subpart applies to owners and operators of any stationary compression ignited IC engine that were

modified or reconstructed after July 11, 2005 and any person that modifies or reconstructs any stationary CI ICE after July 11, 2005. Engine S-381-11 is subject to this subpart.

This subpart was amended on 2/27/14 to revise test methods for compression ignited IC engines. Testing is not required for engine S-381-11; therefore, the amendment does not affect IC engine S-381-11. No further discussion is required.

H. 40 CFR 63 Subpart ZZZZ – National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Emissions (RICE)

The requirements of 40 CFR Part 63, Subpart ZZZZ, National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines, are applicable to owners and operators of a stationary RICE installed prior to 6/12/06 and located at a major or area source of HAP emissions. This facility is not a major source of HAP emissions and is therefore, by definition, and area source of HAP emissions.

Engine S-381-6 was installed before 2006; therefore, as defined by Section 63.65.90(iii), this engine can be classified as existing stationary RICE. Engine is therefore subject to this subpart.

Engine S-381-11 was installed after 2006 and is therefore not subject to this subpart.

This subpart was amended on 1/30/13 and 2/27/14. The 1/30/13 amendment included alternative testing options for certain large spark ignition (generally natural gas-fueled) stationary reciprocating internal combustion engines, management practices for a subset of existing spark ignition stationary reciprocating internal combustion engines in sparsely populated areas and alternative monitoring and compliance options for the same engines in populated areas.

The 2/27/14 amendment included revisions to clarify that a heated probe is not necessary when using ASTM D6522 to measure oxygen or carbon dioxide concentrations. The requirement to use Method 1 or 1A for sampling site and sampling point selection in testing gaseous emissions from engines with smaller ducts is deleted, and single- or three-point sampling, depending on duct size, is added.

These amendments do not affect IC engine S-381-6. No further discussion is required.

H. 40 CFR Part 64 - <u>Compliance Assurance Monitoring(CAM)</u>

40 CFR Part 64 requires Compliance Assurance Monitoring for units that meet the following three criteria:

1) the unit must have an emission limit for the pollutant;

2) the unit must have add-on controls for the pollutant; these are devices such as flue gas recirculation (FGR), baghouses, and catalytic oxidizers; and
3) the unit must have a pre-control potential to emit of greater than the major source thresholds.

Pollutant	Major Source Threshold (lb/year)
NO_X	20,000
SO_X	140,000
PM_{10}	140,000
CO	200,000
VOC	20,000

This regulation was last amended on 10/22/97; however, the Rule 2201 Major Source thresholds for NOx and VOC were lowered from 50,000 to 20,000 lb/year via the 12/18/08 amendment to Rule 2201 (the amended rule was not effective till 6/10/10). The initial Title V (finalized on 10/11/12) evaluated the permits at the 20,000 lb/year NOx and VOC thresholds; consequently, a CAM discussion is not required for this renewal.

I. 40 CFR Part 82, Subparts B and F, Stratospheric Ozone

These regulations apply to servicing motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC). Sections of this regulation were amended in 2013, and conditions 27 and 28 of S-381-0-2 assure compliance with the requirements.

IX. PERMIT SHIELD

A permit shield legally protects a facility from enforcement of the shielded regulations when a source is in compliance with the terms and conditions of the Title V permit. Compliance with the terms and conditions of the Operating Permit is considered compliance with all applicable requirements upon which those conditions are based, including those that have been subsumed.

A. Requirements Addressed by Model General Permit Templates

The applicant does not propose to use any model general permit templates.

X. CALIFORNIA ENVIRONMENTAL QUALITY ACT

The purpose of the Title V permit renewal is to update the permit to ensure that any changes to regulations since the issuance of the initial Title V permit or most recent renewal of the Title V permit are incorporated as permit requirements.

Per the California Environmental Quality Act (CEQA) Statute §21080.24, and CEQA Guidelines §15281, the issuance, modification, amendment, or renewal of any permit by an air pollution control district or air quality management district pursuant to Title V is exempt from CEQA, unless the issuance, modification, amendment, or renewal authorizes a physical or operational change to a source or facility. There will be no physical or operational change to the source or facility

nor will the Title V permit renewal authorize a physical or operational change to the source or facility. Therefore, this project, a Title V permit renewal, is subject to a ministerial action that is exempt from CEQA.

XI. PERMIT CONDITIONS

See Attachment A - Draft Renewed Title V Operating Permit.

ATTACHMENTS

A. Draft Renewed Title V Operating Permit
B. Previous Title V Operating Permit
C. Detailed Summary List of Facility Permits

ATTACHMENT A

Draft Renewed Title V Operating Permit

ATTACHMENT B

Previous Title V Operating Permit

ATTACHMENT C

Detailed Summary List of Facility Permits

Facility # S-381
HECK CELLARS
15401 BEAR MOUNTAIN WINERY RD
DIGIORGIO, CA 93203-9743

Notice of Permit Issuance

The enclosed permit unit requirements authorize the operation of the equipment as described. These permit unit requirements supersede any and all previous permits for the specified equipment.* Please insert these documents into the Facility Permit to Operate, and post copies on or near the equipment as required by District Rule 2010.

Please contact any of our Small Business Assistance (SBA) staff at the numbers below if you have any questions:

Modesto:	(209) 557-6446
Fresno:	(559) 230-5888
Bakersfield:	(661) 392-5665

*Failure to comply with the permit unit requirements may result in enforcement action.

Permit to Operate

FACILITY: S-381 **EXPIRATION DATE:** 12/31/2016

LEGAL OWNER OR OPERATOR: HECK CELLARS
MAILING ADDRESS: 15401 BEAR MOUNTAIN WINERY RD
DIGIORGIO, CA 93203-9743

FACILITY LOCATION: 15401 BEAR MOUNTAIN WINERY RD
DIGIORGIO, CA 93203-9743

FACILITY DESCRIPTION: WINERY

The Facility's Permit to Operate may include Facility-wide Requirements as well as requirements that apply to specific permit units.

This Permit to Operate remains valid through the permit expiration date listed above, subject to payment of annual permit fees and compliance with permit conditions and all applicable local, state, and federal regulations. This permit is valid only at the location specified above, and becomes void upon any transfer of ownership or location. Any modification of the equipment or operation, as defined in District Rule 2201, will require prior District approval. This permit shall be posted as prescribed in District Rule 2010.

Seyed Sadredin
Executive Director / APCO

Arnaud Marjollet
Director of Permit Services

Southern Regional Office • 34946 Flyover Court • Bakersfield, CA 93308 • (661) 392-5500 • Fax (661) 392-5585

San Joaquin Valley
Air Pollution Control District

FACILITY: S-381-0-1 **EXPIRATION DATE:** 12/31/2016

FACILITY-WIDE REQUIREMENTS

1. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1 and Kern County Rule 111] Federally Enforceable Through Title V Permit
2. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0 and Kern County Rule 111] Federally Enforceable Through Title V Permit
3. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.13.1] Federally Enforceable Through Title V Permit
6. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

10. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

11. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

12. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

13. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

14. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

15. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

16. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

17. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

18. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

19. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

20. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

21. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

22. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

23. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in Table of Standards 1 effective until 12/30/10 or Table of Standards 2 effective on and after 1/1/11 of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

24. All VOC-containing materials subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

25. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

26. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

27. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

28. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit

29. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8021] Federally Enforceable Through Title V Permit

30. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8031] Federally Enforceable Through Title V Permit

31. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8041] Federally Enforceable Through Title V Permit

32. Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8051] Federally Enforceable Through Title V Permit

33. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8061] Federally Enforceable Through Title V Permit

34. Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8071] Federally Enforceable Through Title V Permit

35. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

36. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

37. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

38. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

39. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

40. This facility shall annually achieve the Required Annual Emission Reductions (RAER) as specified in the facility's APCO-approved Three-Year Compliance Plan for District Rule 4694. [District Rule 4694]

41. A Three-Year Compliance Plan that demonstrates compliance with the requirements of Section 5.1 of District Rule 4694 for each year of the applicable compliance period shall be submitted to the District every three years on or before December 1. [District Rule 4694]

42. A Three-Year Compliance Plan Verification that demonstrates that the Three-Year Compliance Plan elements are in effect shall be submitted to the District every three years on or before July 1. [District Rule 4694]

43. An Annual Compliance Plan Demonstration that shows compliance with the applicable requirements of this rule shall be submitted to the District every year on or before March 1. [District Rule 4694]

44. Operators using CER to mitigate fermentation emissions shall perform all monitoring and recordkeeping, as established in their approved Three-Year Compliance Plan, and shall maintain all records necessary to demonstrate compliance. [District Rule 4694]

45. On October 31, 2012, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-6-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
235 BHP DETROIT MODEL DDFP-04ATRH DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIRE WATER PUMP

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Engine shall be equipped with a turbocharger. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 40 CFR 63.6625(f), and 17 CCR 93115] Federally Enforceable Through Title V Permit
4. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
5. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
6. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
7. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
8. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
9. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
10. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 20 hours per calendar year. [District Rule 4702, 40 CFR 63.6640(f)(ii), and 17 CCR 93115] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. The permittee shall maintain monthly records of the type of fuel purchased, the amount of fuel purchased, date when the fuel was purchased, signature of the permittee who received the fuel, and signature of the fuel supplier indicating that the fuel was delivered. [2520, 9.3.2 and 17 CCR 93115] Federally Enforceable Through Title V Permit
12. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702, 40 CFR 63.6660, and 17 CCR 93115] Federally Enforceable Through Title V Permit
13. On and after May 3, 2013, the permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes. [40 CFR 63.6625(h)] Federally Enforceable Through Title V Permit
14. On and after May 3, 2013, the engine shall be in full compliance with 40 CFR Part 63, Subpart ZZZZ (National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines). [40 CFR 63.6585/63.6595(a)] Federally Enforceable Through Title V Permit
15. On and after May 3, 2013, the engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63.6603/63.6640 Table 2d, Row 4.a] Federally Enforceable Through Title V Permit
16. On and after May 3, 2013, the engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63.6603/63.6640 Table 2d, Row 4.b] Federally Enforceable Through Title V Permit
17. On and after May 3, 2013, the engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63.6603/63.6640 Table 2d, Row 4.c] Federally Enforceable Through Title V Permit
18. On and after May 3, 2013, the permittee shall maintain monthly records of all performance tests, opacity and visible emissions observations and required maintenance performed on the air pollution control and monitoring equipment. [40 CFR 63.6655(a)(3)/§63.10(b)(2)(viii) and §63.6655(a)(4)] Federally Enforceable Through Title V Permit
19. 10. On and after May 3, 2013, the permittee shall maintain monthly records of the occurrence and duration of each malfunction of operation (i.e., process equipment) or the air pollution control and monitoring equipment. The permittee shall also maintain monthly records of action taken during periods of malfunction to minimize emissions in accordance with §63.6605(b), including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation. [40 CFR 63.6655(a)(2) and (a)(5)] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-9-2 **EXPIRATION DATE:** 12/31/2016

SECTION: 02 **TOWNSHIP:** 31S **RANGE:** 29E

EQUIPMENT DESCRIPTION:
26 MMBTU/HR NATURAL GAS-FIRED BOILER WITH FGR, ZINC RAPID MIX FRMB 19-G-600 LOW NOX BURNER

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The unit shall only be fired on PUC-regulated natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Emissions rates from the natural gas-fired unit shall not exceed any of the following limits: 7 ppmv NOx @ 3% O2 or 0.008 lb-NOx/MMBtu, 0.00285 lb-SOx/MMBtu, 0.0075 lb-PM10/MMBtu, or 100 ppmv CO @ 3% O2. [District Rules 2201, 4305, 4306, 4320] Federally Enforceable Through Title V Permit
5. The permittee shall monitor and record the stack concentration of NOX, CO, and O2 at least once every month (in which a source test is not performed) using a portable analyzer that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
6. If either the NOX or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

8. The permittee shall maintain records of: (1) the date and time of NOX, CO, and O2 measurements, (2) the O2 concentration in percent by volume and the measured NOX and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

9. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

10. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

11. This unit shall be tested for compliance with the NOx and CO emissions limits at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

12. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

13. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

14. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

15. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100. [[District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. The owner or operator shall record and maintain records of the amount of fuel combusted during each operating day. [40 CFR 60.48c(g)(1)] Federally Enforceable Through Title V Permit

18. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-10-3 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
33,310 BARREL CAPACITY BRANDY STORAGE AND AGING OPERATION (BUILDINGS K & L) SERVED BY A 0.289 MMBTU/HR ADWEST TECHNOLOGIES MODEL RETOX 1.0 RTO95 PRIMARY REGENERATIVE THERMAL OXIDIZER (SMALL RTO) AND 1.156 MMBTU/HR ADWEST TECHNOLOGIES MODEL RETOX 4.0 RTO95 SECONDARY RTO (LARGE RTO)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. All brandy storage and aging operations at this facility shall only be performed in Buildings K and L. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. Only PUC-regulated natural gas shall be used as supplemental fuel for the regenerative thermal oxidizers. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The brandy storage enclosures and regenerative thermal oxidation system shall be maintained in proper operating condition at all times. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The facility shall notify the District of any occurrence which constitutes a breakdown condition of the VOC control system pursuant to District Rule 1100. [District Rule 2201 and District Rule 1100] Federally Enforceable Through Title V Permit
6. Manway access doors are defined as doors with a maximum opening of 21 square feet, intended solely for occasional personnel access to the warehouse for maintenance or monitoring activities. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Non-manway access doors are defined as openings equipped with roll-up doors which are required to allow routine movement of brandy into and out of the warehouse or for warehouse access with wheeled and motorized maintenance equipment. [District Rule 2201] Federally Enforceable Through Title V Permit
8. All openings in the warehouse enclosures which may be opened during "normal operation" of the VOC control system and which do not qualify as manway access doors or non-manway access doors shall be considered to be Natural Draft Openings (NDO) for purposes of certification of the enclosure as a Permanent Total Enclosure pursuant to U.S. EPA Method 204. [District Rule 2201] Federally Enforceable Through Title V Permit
9. "Normal operation" is defined for each warehouse building enclosure as operation with the enclosure meeting the minimum requirements for a permanent total enclosure pursuant to EPA Method 204 (with the fan inlet pressure operating with a vacuum at or higher than the minimum allowed vacuum and all non-manway access doors closed) and the regenerative thermal oxidizer system fully operational with the combustion chamber temperature at or above 1400 degrees F. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The facility shall be equipped with a continuous monitoring system to monitor, at a minimum, the status of the fan inlet pressure control, all non-manway access doors and the combustion chamber temperature of each in-service RTO. Actual hours of "normal operation" shall be continuously and automatically monitored and recorded for each warehouse building enclosure. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Buildings K and L shall be certified and maintained as Permanent Total Enclosures (PTE) pursuant to U.S. EPA Method 204. [District Rule 2201] Federally Enforceable Through Title V Permit

12. Certification of Buildings K and L as Permanent Total Enclosures shall be performed by a District-approved independent certifying entity. [District Rule 2201] Federally Enforceable Through Title V Permit

13. Each manway access door shall be equipped with an automatic closure device to minimize the time that the door is open. Manway access doors shall be opened only as required for access to or exit from the enclosure, minimizing the duration of the opening, and shall not be propped open. [District Rule 2201] Federally Enforceable Through Title V Permit

14. Each non-manway access opening shall be equipped with a motor-actuated door and controls which will minimize the time the door remains open during access and exit and shall be integrated with the continuous monitoring system to record the time periods that the door is open. [District Rules 1080 and 2201] Federally Enforceable Through Title V Permit

15. The fan inlet pressure control point shall be equipped with a continuous pressure monitor integrated with the facility's continuous monitoring system to continuously record the actual fan inlet vacuum. [District Rules 1080 and 2201] Federally Enforceable Through Title V Permit

16. The measured vacuum at the fan inlet pressure control point shall not be less than the established minimum allowable vacuum during "normal operation." [District Rule 2201] Federally Enforceable Through Title V Permit

17. Each month the facility shall demonstrate that control of the ID fan inlet pressure at or above the established minimum allowable vacuum is adequate to simultaneously maintain the qualification of all enclosures (Buildings K and L) as Permanent Total Enclosures pursuant to EPA Method 204 by manually measuring and recording facial velocity at the test port opening on each warehouse building enclosure and confirming a minimum facial velocity of 200 feet per minute at each port. If a velocity less than 200 feet per minute is determined, operating adjustments shall be made as required to increase the measured facial velocity to 200 feet per minute within 24 hours of the initial measurement. If the permittee is unable to demonstrate a minimum facial velocity of 200 feet per minute within 48 hours after initial measurement, permittee shall notify the APCO within 72 hours of the initial measurement. After 12 consecutive months of demonstrating the adequacy of the established minimum allowable vacuum, the monitoring frequency can be reduced to once per quarter per warehouse building enclosure. [District Rule 2201] Federally Enforceable Through Title V Permit

18. The induced draft fan and RTO serving the warehouse building enclosures shall be adequately sized to simultaneously maintain "normal operation" for all warehouse building enclosures during periods of maximum brandy loss from the storage and aging operation. [District Rule 2201] Federally Enforceable Through Title V Permit

19. At least one regenerative thermal oxidizer shall operate at all times. [District Rule 2201] Federally Enforceable Through Title V Permit

20. The minimum allowable vacuum at the fan inlet pressure control point, adequate to ensure maintenance of a continuous negative pressure on all warehouse storage enclosures as required to simultaneously qualify all enclosures as Permanent Total Enclosures pursuant to EPA Method 204, shall be demonstrated and recorded annually. [District Rules 1080 and 2201] Federally Enforceable Through Title V Permit

21. Each regenerative thermal oxidizer shall be equipped with a dedicated isolation damper to isolate it from the brandy warehouse when not in operation. The isolation damper shall not be opened unless the regenerative thermal oxidizer it serves is fully operational with a combustion chamber temperature not less than 1400 F. [District Rule 2201] Federally Enforceable Through Title V Permit

22. Each regenerative thermal oxidizer shall be equipped with an operational temperature gauge to indicate the temperature of the combustion chamber. A continuously recording device integrated with the facility's continuous monitoring system shall be utilized to indicate the combustion chamber temperature during operation. [District Rules 1080 and 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. Each regenerative thermal oxidizer shall operate with a combustion chamber temperature of not less than 1400 F when its isolation damper is open to the warehouse. Upon detecting any temperature excursion less than 1400F, the permittee shall investigate the excursion and take corrective action to minimize excessive emissions and prevent recurrence of the excursion as expeditiously as practicable. [District Rule 2201 and 40 CFR part 64] Federally Enforceable Through Title V Permit
24. The VOC destruction efficiency of each regenerative thermal oxidizer shall not be less than 98%. [District Rule 2201] Federally Enforceable Through Title V Permit
25. Routine scheduled maintenance which requires shutdown of the primary (larger) regenerative thermal oxidizer shall not be performed during the months of July, August, or September. [District Rule 2201] Federally Enforceable Through Title V Permit
26. Total evaporative emissions from brandy shall not exceed 46,108 lb-VOC/year based on a 12-month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit
27. The total evaporative brandy VOC emissions shall be quantified by the sum of the evaporative brandy VOC emissions emitted to the atmosphere from each warehouse building enclosure based on a 12-month rolling basis. Evaporative losses from each warehouse building enclosure shall be calculated by the following formula: Evaporative Brandy VOC Emissions (tons/year-enclosure) = Uncontrolled Emissions (tons/year-enclosure) x Control Factor. Uncontrolled Emissions = the average enclosure inventory for the year (bbls/enclosure) x the measured brandy loss per barrel for the year in the enclosure (PG/bbl-year) x 3.31 lb-VOC/PG. The Control Factor for the year = (8,760-0.98xH)/8,760, where H is hours of "normal operation" for the enclosure (as defined in this permit) recorded based on a 12-month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit
28. Combined VOC emissions from the exhaust of the regenerative thermal oxidizers shall not exceed 81.0 lb/day during "normal operation." [District Rule 2201] Federally Enforceable Through Title V Permit
29. The emissions from the combustion of natural gas or LPG shall not exceed any of the following limits: 0.494 lb-NOx/MMBtu, 0.084 lb-CO/MMBtu, 0.0076 lb-PM10/MMBtu, 0.0055 lb-VOC/MMBtu, or 0.00285 lb-SOx/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
30. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 2201] Federally Enforceable Through Title V Permit
31. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
32. Each regenerative thermal oxidizer (RTO) shall be tested for compliance with VOC emissions limits and to demonstrate the destruction efficiency of the RTO at least once every 12 months. After an RTO has demonstrated compliance on two consecutive annual source tests, it shall be tested not less than once every thirty-six months. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit
33. VOC emissions for source test purposes shall be determined using US EPA Method 25 or Method 18 or BAAQMD ST-32, except when the outlet concentration must be below 50 ppmv in order to meet the standard, in which case US EPA Method 25a may be used. VOC emissions during the source test shall be calculated as the arithmetic average of three 30-consecutive-minute test runs. [District Rule 2201] Federally Enforceable Through Title V Permit
34. Daily and annual records of the hours of operation shall be kept, indicating the time and duration of all periods of outage for the VOC control system including maintenance. [District Rule 2201] Federally Enforceable Through Title V Permit
35. Records shall be kept of all maintenance activities requiring a shutdown of a regenerative thermal oxidizer, including the maintenance activity, time and date of shutdown of the regenerative thermal oxidizer, and the duration of the shutdown. [District Rule 2201] Federally Enforceable Through Title V Permit
36. Records of all required monitoring including facial velocity measurements and annual evaporative VOC emissions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

37. Daily and annual records of the number of barrels in each warehouse storage enclosure shall be kept. [District Rule 2201] Federally Enforceable Through Title V Permit

38. Records of all barrel filling and dumping operations shall be kept, recording the proof gallons placed into storage, the proof gallons removed from storage, the proof gallons lost while in storage and the date of each action. Annual summaries of all filling and dumping operations shall be maintained to allow annual determination of total proof-gallons lost from each warehouse building enclosure. All gauging of distilled spirits shall be in accordance with the methods and procedures of the Gauging Manual of the Alcohol and Tobacco Tax and Trade Bureau, Department of the Treasury (27 CFR 30). [District Rule 2201] Federally Enforceable Through Title V Permit

39. All records shall be retained for a minimum of five years, and shall be made available for District inspection upon request. [District Rule 2201 and 40 CFR part 64] Federally Enforceable Through Title V Permit

40. Each regenerative thermal oxidizer temperature monitoring device shall be calibrated, maintained, and operated according to the manufacturer's specifications. [40 CFR part 64] Federally Enforceable Through Title V Permit

41. Each regenerative thermal oxidizer and its associated components shall be inspected on an annual basis. The records of inspection shall at least contain date and time of inspection, identification of the person performing an inspection, parts replacement and repairs, and all maintenance actions taken. The records shall be kept and maintained for compliance inspection upon request. [40 CFR part 64] Federally Enforceable Through Title V Permit

42. The permittee shall comply with the compliance assurance monitoring operation and maintenance requirements of 40 CFR part 64.7. [40 CFR part 64] Federally Enforceable Through Title V Permit

43. If the District or EPA determine that a Quality Improvement Plan is required under 40 CFR 64.7(d)(2), the permittee shall develop and implement the Quality Improvement Plan in accordance with 40 CFR part 64.8. [40 CFR part 64] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-11-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
240 BHP CLARKE MODEL JU6H-UF60 TIER 2 CERTIFIED DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIRE WATER PUMP

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201, 4801, 40 CFR 60.4207 (b), and 17 CCR 93115] Federally Enforceable Through Title V Permit
3. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
4. This engine shall be operated only for maintenance, testing, required regulatory purposes, and during emergency situations. For testing purposes, the engine shall only be operated the number of hours necessary to comply with the testing requirements of the National Fire Protection Association (NFPA) 25 - "Standard for the Inspection, Testing, and Maintenance of Water-Based Fire Protection Systems", 1998 edition. Total hours of operation for all maintenance, testing, and required regulatory purposes shall not exceed 100 hours per calendar year. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
5. Emissions from this IC engine shall not exceed any of the following limits: 4.5 g-NOx/bhp-hr, 0.59 g-CO/bhp-hr, or 1.4 g-VOC/bhp-hr. [District Rule 2201, 40 CFR 60.4205(c), 13 CCR 2423, and 17 CCR 93115] Federally Enforceable Through Title V Permit
6. Emissions from this IC engine shall not exceed 0.14 g-PM10/bhp-hr based on USEPA certification using ISO 8178 test procedure. [District Rules 2201, 4102, 40 CFR 60.4205(c), 13 CCR 2423, and 17 CCR 93115] Federally Enforceable Through Title V Permit
7. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
8. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, and the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.). For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
9. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702 and 40 CFR 60.4211(a)] Federally Enforceable Through Title V Permit
10. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-12-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
17,369 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #BB-1) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-13-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
17,369 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #BB-2) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-14-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
182,523 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #DM51) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-15-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
182,523 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #DM52) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-16-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
182,523 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #DM53) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-17-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
182,523 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #DM54) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-18-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
27,480 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-20) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-19-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
27,480 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-21) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-20-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
27,480 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-22) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-21-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
27,480 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-23) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-22-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
27,480 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-24) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-23-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
27,480 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-25) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-24-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
27,480 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-26) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-25-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
27,480 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-27) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-26-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
27,480 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-28) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-27-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
27,480 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-29) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-28-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
10,449 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-30) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-29-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
10,449 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-31) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-30-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
10,449 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-32) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-31-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
10,449 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-33) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-32-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
10,449 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-34) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-33-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
10,449 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-35) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-34-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
10,449 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-36) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-35-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
10,449 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-37) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-36-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
10,449 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-38) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-37-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
2,331 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-39) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-38-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
2,331 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-40) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-39-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
3,455 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-41) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-40-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
3,455 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-42) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-41-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-3) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-42-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-4) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-43-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-5) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-44-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-6) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-45-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-7) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-46-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-8) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-47-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-9) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-48-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-10) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-49-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-11) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-50-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-12) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-51-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-13) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-52-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-14) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-53-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-15) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-54-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-16) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-55-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-17) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-56-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-18) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-57-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-19) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-58-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-20) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-59-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-21) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-60-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-22) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-61-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-23) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-62-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-24) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-63-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-25) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-64-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-26) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-65-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-27) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-66-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
7,163 GALLON PLASTIC WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-28) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-67-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
7,163 GALLON PLASTIC WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-29) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-68-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
7,163 GALLON PLASTIC WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-30) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-69-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-32) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-70-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-33) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-71-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-34) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-72-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-35) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-74-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-37) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-75-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-38) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-76-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-40) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-78-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-44) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-79-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-45) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-80-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-46) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-81-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-47) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-82-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-48) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-83-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
3,965 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-49) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-84-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
3,965 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-50) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-85-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
5,139 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-51) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-86-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
5,139 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-52) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-87-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
5,139 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-53) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-88-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
5,139 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-54) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-89-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
5,139 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-55) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-90-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
10,449 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-56) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-91-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
2,331 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-57) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-92-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
2,331 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-58) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-93-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
64,579 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #101)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-94-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
64,579 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #102)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-95-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
64,579 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #103)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-96-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
64,579 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #104)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-97-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
64,579 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #105)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-98-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
265,366 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #238)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-99-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
263,525 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #245)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-104-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
51,739 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #300) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-105-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
51,739 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #301) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-106-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
111,404 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #302) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-107-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
198,762 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #303) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-108-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
198,103 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #304) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-109-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
198,762 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #305) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-110-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
198,762 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #306) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-111-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
198,762 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #307) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-112-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
111,104 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #308) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-113-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
111,104 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #309) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-114-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
111,104 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #310) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-115-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
111,404 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #311) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-116-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
111,404 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #312) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-117-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
111,404 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #313) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-118-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
111,404 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #314) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-119-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,060 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #315) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-120-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
218,755 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #316) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-121-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
218,755 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #317) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-122-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
198,762 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #318) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-123-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
198,762 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #319) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-124-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
198,762 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #320) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-125-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
198,762 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #321) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-126-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
198,762 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #322) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-127-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
655,230 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #326) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-128-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
646,257 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #327) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-129-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
639,742 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #328) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-130-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
651,057 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #329) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-131-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
648,162 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #330) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-132-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
648,162 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #331) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-133-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
648,162 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #333) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-134-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
648,162 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #334) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-135-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
650,156 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #337) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-136-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
655,703 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #338) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-137-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
651,940 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #339) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-138-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
653,237 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #340) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-139-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
27,621 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #341) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-140-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
27,621 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #342) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-141-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
27,621 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #343) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-142-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
27,621 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #344) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-143-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
27,621 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #345) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-144-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
27,621 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #346) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-145-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
305,902 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #347) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-146-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
307,251 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #348) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-147-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
307,251 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #349) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-148-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
307,251 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #350) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-149-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #351) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-150-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #352) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-151-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #353) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-152-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #354) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-153-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #355) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-154-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #356) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-155-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #357) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-156-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #358) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-157-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #359) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-158-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #360) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-159-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #361) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-160-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
281,563 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #362) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-161-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #363) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-162-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #364) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-163-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #365) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-164-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #366) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-165-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #367) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-166-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #368) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-167-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #369) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-168-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #370) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-169-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #371) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-170-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #372) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-171-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #373) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-172-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #374) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-173-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #411) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-174-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #412) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-175-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #413) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-176-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #414) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-177-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #415) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-178-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #421) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-179-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #422) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-180-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #423) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-181-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #424) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-182-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #425) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-183-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #431) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-184-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #432) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-185-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #433) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-186-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
294,359 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #441) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-187-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
294,693 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #442) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-188-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
294,693 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #443) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-189-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #451) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-190-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #452) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-191-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #453) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-192-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #463) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-193-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #471) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-194-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #472) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-195-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #473) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-196-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #474) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-197-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #475) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-198-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #481) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-199-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #482) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-200-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #483) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-201-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #484) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-202-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #485) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-203-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
26,729 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #491) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-204-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
28,285 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #492) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-205-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
27,528 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #493) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-206-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
27,528 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #494) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-207-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
27,528 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #495) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-208-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
28,285 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #4101) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-209-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
27,528 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #4102) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-210-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
27,528 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #4103) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-211-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
27,528 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #4104) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-212-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
27,528 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #4105) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-213-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
64,579 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #106)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-214-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
64,579 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #107)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-215-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
64,579 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #108)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-216-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
64,579 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #109)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-217-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
64,579 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #110)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-280-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
29,744 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #259)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-281-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
15,229 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #260)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-308-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
15,239 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #287)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-309-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
29,942 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #288)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-313-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
648,162 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #325) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-314-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
648,162 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #332) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-315-1

EXPIRATION DATE: 12/31/2016

EQUIPMENT DESCRIPTION:
648,162 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #335) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-316-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
648,162 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #336) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-317-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-31) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-320-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-42) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-324-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
15,281 GALLON STEEL SPIRIT STORAGE TANK (TANK #SING. 4) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-325-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
15,281 GALLON STEEL SPIRIT STORAGE TANK (TANK #SING. 5) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-326-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
20,958 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 1)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-330-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
23,057 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 5) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-331-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
23,050 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 6) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-332-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
23,076 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 7) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-333-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
23,014 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 8) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-334-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
23,050 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 9) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-335-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
23,076 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 10) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-338-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
58,439 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 13) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-339-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
58,439 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 14) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-340-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
58,439 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 15) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-341-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
17,369 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 20) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-342-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
17,369 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 21) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-343-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
3,965 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 100) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-344-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
15,845 GALLON STEEL SPIRIT STORAGE TANK (TANK #WT-30) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-345-1 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
3,704 GALLON STEEL SPIRIT STORAGE TANK (TANK #WB-24) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

FACILITY: S-381-0-2

EXPIRATION DATE: 12/31/2016

DRAFT

FACILITY-WIDE REQUIREMENTS

1. {4362} The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
2. {4363} The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
3. {4364} The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. {4365} Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. {4366} The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.13.1] Federally Enforceable Through Title V Permit
6. {4367} A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. {4368} Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. {4369} The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

DRAFT

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

9. {4370} The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

10. {4371} The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

11. {4372} Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

12. {4373} If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

13. {4374} It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

14. {4375} The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

15. {4376} The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

16. {4377} The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

17. {4378} The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

18. {4379} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

19. {4380} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

20. {4381} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

21. {4382} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

DRAFT

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

22. {4383} No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

23. {4384} No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in Table of Standards 1 effective until 12/30/10 or Table of Standards 2 effective on and after 1/1/11 of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

24. {4385} All VOC-containing materials subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

25. {4386} The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

26. {4387} With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

27. {4388} If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

28. {4389} If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit

29. {4390} Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8021] Federally Enforceable Through Title V Permit

30. {4391} Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8031] Federally Enforceable Through Title V Permit

31. {4392} An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8041] Federally Enforceable Through Title V Permit

32. {4393} Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8051] Federally Enforceable Through Title V Permit

33. {4394} Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8061] Federally Enforceable Through Title V Permit

DRAFT

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

34. {4395} Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8071] Federally Enforceable Through Title V Permit

35. {4396} Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

36. {4397} The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

37. {4398} The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

38. {4399} When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

39. {4400} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), Rule 111 (Kern, Tulare, Kings), and Rule 202 (Fresno, Kern, Tulare, Kings, Madera, Stanislaus, Merced, San Joaquin). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

40. {4401} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601 (12/17/09); 8021 (8/19/2004); 8031 (8/19/2004); 8041 (8/19/2004); 8051 (8/19/2004); 8061 (8/19/2004); and 8071 (9/16/2004). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

41. This facility shall annually achieve the Required Annual Emission Reductions (RAER) as specified in the facility's APCO-approved Three-Year Compliance Plan for District Rule 4694. [District Rule 4694]

42. A Three-Year Compliance Plan that demonstrates compliance with the requirements of Section 5.1 of District Rule 4694 for each year of the applicable compliance period shall be submitted to the District every three years on or before December 1. [District Rule 4694]

43. A Three-Year Compliance Plan Verification that demonstrates that the Three-Year Compliance Plan elements are in effect shall be submitted to the District every three years on or before July 1. [District Rule 4694]

44. An Annual Compliance Plan Demonstration that shows compliance with the applicable requirements of this rule shall be submitted to the District every year on or before March 1. [District Rule 4694]

DRAFT

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

45. Operators using CER to mitigate fermentation emissions shall perform all monitoring and recordkeeping, as established in their approved Three-Year Compliance Plan, and shall maintain all records necessary to demonstrate compliance. [District Rule 4694]

46. On October 31, 2012, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-6-2 **EXPIRATION DATE:** 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
235 BHP DETROIT MODEL DDFP-04ATRH DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIRE WATER PUMP

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Engine shall be equipped with a turbocharger. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 40 CFR 63.6625(f), and 17 CCR 93115] Federally Enforceable Through Title V Permit
4. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
5. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201 and 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
6. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
7. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.) and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
8. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
9. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit
10. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 20 hours per calendar year. [District Rule 4702, 40 CFR 63.6640(f)(ii), and 17 CCR 93115] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. The permittee shall maintain monthly records of the type of fuel purchased, the amount of fuel purchased, date when the fuel was purchased, signature of the permittee who received the fuel, and signature of the fuel supplier indicating that the fuel was delivered. [2520, 9.3.2 and 17 CCR 93115] Federally Enforceable Through Title V Permit
12. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702, 40 CFR 63.6660, and 17 CCR 93115] Federally Enforceable Through Title V Permit
13. On and after May 3, 2013, the permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes. [40 CFR 63.6625(h)] Federally Enforceable Through Title V Permit
14. On and after May 3, 2013, the engine shall be in full compliance with 40 CFR Part 63, Subpart ZZZZ (National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines). [40 CFR 63.6585/63.6595(a)] Federally Enforceable Through Title V Permit
15. On and after May 3, 2013, the engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63.6603/63.6640 Table 2d, Row 4.a] Federally Enforceable Through Title V Permit
16. On and after May 3, 2013, the engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63.6603/63.6640 Table 2d, Row 4.b] Federally Enforceable Through Title V Permit
17. On and after May 3, 2013, the engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63.6603/63.6640 Table 2d, Row 4.c] Federally Enforceable Through Title V Permit
18. On and after May 3, 2013, the permittee shall maintain monthly records of all performance tests, opacity and visible emissions observations and required maintenance performed on the air pollution control and monitoring equipment. [40 CFR 63.6655(a)(3)/§63.10(b)(2)(viii) and §63.6655(a)(4)] Federally Enforceable Through Title V Permit
19. 10. On and after May 3, 2013, the permittee shall maintain monthly records of the occurrence and duration of each malfunction of operation (i.e., process equipment) or the air pollution control and monitoring equipment. The permittee shall also maintain monthly records of action taken during periods of malfunction to minimize emissions in accordance with §63.6605(b), including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation. [40 CFR 63.6655(a)(2) and (a)(5)] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-9-3

EXPIRATION DATE: 12/31/2016

DRAFT

SECTION: 02 **TOWNSHIP:** 31S **RANGE:** 29E

EQUIPMENT DESCRIPTION:
26 MMBTU/HR NATURAL GAS-FIRED BOILER WITH FGR, ZINC RAPID MIX FRMB 19-G-600 LOW NOX BURNER

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The unit shall only be fired on PUC-regulated natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Emissions rates from the natural gas-fired unit shall not exceed any of the following limits: 7 ppmv NOx @ 3% O2 or 0.008 lb-NOx/MMBtu, 0.00285 lb-SOx/MMBtu, 0.0075 lb-PM10/MMBtu, or 100 ppmv CO @ 3% O2. [District Rules 2201, 4305, 4306, 4320] Federally Enforceable Through Title V Permit
5. The permittee shall monitor and record the stack concentration of NOX, CO, and O2 at least once every month (in which a source test is not performed) using a portable analyzer that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
6. If either the NOX or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

8. The permittee shall maintain records of: (1) the date and time of NOX, CO, and O2 measurements, (2) the O2 concentration in percent by volume and the measured NOX and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

9. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4306. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

10. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

11. This unit shall be tested for compliance with the NOx and CO emissions limits at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306 and 4320] Federally Enforceable Through Title V Permit

12. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

13. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit

14. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit

15. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, NOx (lb/MMBtu) - EPA Method 19, CO (ppmv) - EPA Method 10 or ARB Method 100, stack gas oxygen - EPA Method 3 or 3A or ARB Method 100. [[District Rules 1081, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

16. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. The owner or operator shall record and maintain records of the amount of fuel combusted during each operating day. [40 CFR 60.48c(g)(1)] Federally Enforceable Through Title V Permit

18. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-10-4

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
33,310 BARREL CAPACITY BRANDY STORAGE AND AGING OPERATION (BUILDINGS K & L) SERVED BY A 0.289 MMBTU/HR ADWEST TECHNOLOGIES MODEL RETOX 1.0 RTO95 PRIMARY REGENERATIVE THERMAL OXIDIZER (SMALL RTO) AND 1.156 MMBTU/HR ADWEST TECHNOLOGIES MODEL RETOX 4.0 RTO95 SECONDARY RTO (LARGE RTO)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. All brandy storage and aging operations at this facility shall only be performed in Buildings K and L. [District Rules 2201 and 4694] Federally Enforceable Through Title V Permit
3. Only PUC-regulated natural gas shall be used as supplemental fuel for the regenerative thermal oxidizers. [District Rule 2201] Federally Enforceable Through Title V Permit
4. The brandy storage enclosures and regenerative thermal oxidation system shall be maintained in proper operating condition at all times. [District Rule 2201] Federally Enforceable Through Title V Permit
5. The facility shall notify the District of any occurrence which constitutes a breakdown condition of the VOC control system pursuant to District Rule 1100. [District Rule 2201 and District Rule 1100] Federally Enforceable Through Title V Permit
6. Manway access doors are defined as doors with a maximum opening of 21 square feet, intended solely for occasional personnel access to the warehouse for maintenance or monitoring activities. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Non-manway access doors are defined as openings equipped with roll-up doors which are required to allow routine movement of brandy into and out of the warehouse or for warehouse access with wheeled and motorized maintenance equipment. [District Rule 2201] Federally Enforceable Through Title V Permit
8. All openings in the warehouse enclosures which may be opened during "normal operation" of the VOC control system and which do not qualify as manway access doors or non-manway access doors shall be considered to be Natural Draft Openings (NDO) for purposes of certification of the enclosure as a Permanent Total Enclosure pursuant to U.S. EPA Method 204. [District Rule 2201] Federally Enforceable Through Title V Permit
9. "Normal operation" is defined for each warehouse building enclosure as operation with the enclosure meeting the minimum requirements for a permanent total enclosure pursuant to EPA Method 204 (with the fan inlet pressure operating with a vacuum at or higher than the minimum allowed vacuum and all non-manway access doors closed) and the regenerative thermal oxidizer system fully operational with the combustion chamber temperature at or above 1400 degrees F. [District Rule 2201] Federally Enforceable Through Title V Permit
10. The facility shall be equipped with a continuous monitoring system to monitor, at a minimum, the status of the fan inlet pressure control, all non-manway access doors and the combustion chamber temperature of each in-service RTO. Actual hours of "normal operation" shall be continuously and automatically monitored and recorded for each warehouse building enclosure. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. Buildings K and L shall be certified and maintained as Permanent Total Enclosures (PTE) pursuant to U.S. EPA Method 204. [District Rule 2201] Federally Enforceable Through Title V Permit
12. Certification of Buildings K and L as Permanent Total Enclosures shall be performed by a District-approved independent certifying entity. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Each manway access door shall be equipped with an automatic closure device to minimize the time that the door is open. Manway access doors shall be opened only as required for access to or exit from the enclosure, minimizing the duration of the opening, and shall not be propped open. [District Rule 2201] Federally Enforceable Through Title V Permit
14. Each non-manway access opening shall be equipped with a motor-actuated door and controls which will minimize the time the door remains open during access and exit and shall be integrated with the continuous monitoring system to record the time periods that the door is open. [District Rules 1080 and 2201] Federally Enforceable Through Title V Permit
15. The fan inlet pressure control point shall be equipped with a continuous pressure monitor integrated with the facility's continuous monitoring system to continuously record the actual fan inlet vacuum. [District Rules 1080 and 2201] Federally Enforceable Through Title V Permit
16. The measured vacuum at the fan inlet pressure control point shall not be less than the established minimum allowable vacuum during "normal operation." [District Rule 2201] Federally Enforceable Through Title V Permit
17. Each month the facility shall demonstrate that control of the ID fan inlet pressure at or above the established minimum allowable vacuum is adequate to simultaneously maintain the qualification of all enclosures (Buildings K and L) as Permanent Total Enclosures pursuant to EPA Method 204 by manually measuring and recording facial velocity at the test port opening on each warehouse building enclosure and confirming a minimum facial velocity of 200 feet per minute at each port. If a velocity less than 200 feet per minute is determined, operating adjustments shall be made as required to increase the measured facial velocity to 200 feet per minute within 24 hours of the initial measurement. If the permittee is unable to demonstrate a minimum facial velocity of 200 feet per minute within 48 hours after initial measurement, permittee shall notify the APCO within 72 hours of the initial measurement. After 12 consecutive months of demonstrating the adequacy of the established minimum allowable vacuum, the monitoring frequency can be reduced to once per quarter per warehouse building enclosure. [District Rule 2201] Federally Enforceable Through Title V Permit
18. The induced draft fan and RTO serving the warehouse building enclosures shall be adequately sized to simultaneously maintain "normal operation" for all warehouse building enclosures during periods of maximum brandy loss from the storage and aging operation. [District Rule 2201] Federally Enforceable Through Title V Permit
19. At least one regenerative thermal oxidizer shall operate at all times. [District Rule 2201] Federally Enforceable Through Title V Permit
20. The minimum allowable vacuum at the fan inlet pressure control point, adequate to ensure maintenance of a continuous negative pressure on all warehouse storage enclosures as required to simultaneously qualify all enclosures as Permanent Total Enclosures pursuant to EPA Method 204, shall be demonstrated and recorded annually. [District Rules 1080 and 2201] Federally Enforceable Through Title V Permit
21. Each regenerative thermal oxidizer shall be equipped with a dedicated isolation damper to isolate it from the brandy warehouse when not in operation. The isolation damper shall not be opened unless the regenerative thermal oxidizer it serves is fully operational with a combustion chamber temperature not less than 1400 F. [District Rule 2201] Federally Enforceable Through Title V Permit
22. Each regenerative thermal oxidizer shall be equipped with an operational temperature gauge to indicate the temperature of the combustion chamber. A continuously recording device integrated with the facility's continuous monitoring system shall be utilized to indicate the combustion chamber temperature during operation. [District Rules 1080 and 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

23. Each regenerative thermal oxidizer shall operate with a combustion chamber temperature of not less than 1400 F when its isolation damper is open to the warehouse. Upon detecting any temperature excursion less than 1400F, the permittee shall investigate the excursion and take corrective action to minimize excessive emissions and prevent recurrence of the excursion as expeditiously as practicable. [District Rule 2201 and 40 CFR part 64] Federally Enforceable Through Title V Permit
24. The VOC destruction efficiency of each regenerative thermal oxidizer shall not be less than 98%. [District Rule 2201] Federally Enforceable Through Title V Permit
25. Routine scheduled maintenance which requires shutdown of the primary (larger) regenerative thermal oxidizer shall not be performed during the months of July, August, or September. [District Rule 2201] Federally Enforceable Through Title V Permit
26. Total evaporative emissions from brandy shall not exceed 46,108 lb-VOC/year based on a 12-month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit
27. The total evaporative brandy VOC emissions shall be quantified by the sum of the evaporative brandy VOC emissions emitted to the atmosphere from each warehouse building enclosure based on a 12-month rolling basis. Evaporative losses from each warehouse building enclosure shall be calculated by the following formula: Evaporative Brandy VOC Emissions (tons/year-enclosure) = Uncontrolled Emissions (tons/year-enclosure) x Control Factor. Uncontrolled Emissions = the average enclosure inventory for the year (bbls/enclosure) x the measured brandy loss per barrel for the year in the enclosure (PG/bbl-year) x 3.31 lb-VOC/PG. The Control Factor for the year = (8,760-0.98xH)/8,760, where H is hours of "normal operation" for the enclosure (as defined in this permit) recorded based on a 12-month rolling basis. [District Rule 2201] Federally Enforceable Through Title V Permit
28. Combined VOC emissions from the exhaust of the regenerative thermal oxidizers shall not exceed 81.0 lb/day during "normal operation." [District Rule 2201] Federally Enforceable Through Title V Permit
29. The emissions from the combustion of natural gas or LPG shall not exceed any of the following limits: 0.494 lb-NOx/MMBtu, 0.084 lb-CO/MMBtu, 0.0076 lb-PM10/MMBtu, 0.0055 lb-VOC/MMBtu, or 0.00285 lb-SOx/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
30. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 2201] Federally Enforceable Through Title V Permit
31. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
32. Each regenerative thermal oxidizer (RTO) shall be tested for compliance with VOC emissions limits and to demonstrate the destruction efficiency of the RTO at least once every 12 months. After an RTO has demonstrated compliance on two consecutive annual source tests, it shall be tested not less than once every thirty-six months. [District Rules 1081 and 2201] Federally Enforceable Through Title V Permit
33. VOC emissions for source test purposes shall be determined using US EPA Method 25 or Method 18 or BAAQMD ST-32, except when the outlet concentration must be below 50 ppmv in order to meet the standard, in which case US EPA Method 25a may be used. VOC emissions during the source test shall be calculated as the arithmetic average of three 30-consecutive-minute test runs. [District Rule 2201] Federally Enforceable Through Title V Permit
34. Daily and annual records of the hours of operation shall be kept, indicating the time and duration of all periods of outage for the VOC control system including maintenance. [District Rule 2201] Federally Enforceable Through Title V Permit
35. Records shall be kept of all maintenance activities requiring a shutdown of a regenerative thermal oxidizer, including the maintenance activity, time and date of shutdown of the regenerative thermal oxidizer, and the duration of the shutdown. [District Rule 2201] Federally Enforceable Through Title V Permit
36. Records of all required monitoring including facial velocity measurements and annual evaporative VOC emissions shall be maintained. [District Rule 2201] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

37. Daily and annual records of the number of barrels in each warehouse storage enclosure shall be kept. [District Rule 2201] Federally Enforceable Through Title V Permit

38. Records of all barrel filling and dumping operations shall be kept, recording the proof gallons placed into storage, the proof gallons removed from storage, the proof gallons lost while in storage and the date of each action. Annual summaries of all filling and dumping operations shall be maintained to allow annual determination of total proof-gallons lost from each warehouse building enclosure. All gauging of distilled spirits shall be in accordance with the methods and procedures of the Gauging Manual of the Alcohol and Tobacco Tax and Trade Bureau, Department of the Treasury (27 CFR 30). [District Rule 2201] Federally Enforceable Through Title V Permit

39. All records shall be retained for a minimum of five years, and shall be made available for District inspection upon request. [District Rule 2201 and 40 CFR part 64] Federally Enforceable Through Title V Permit

40. Each regenerative thermal oxidizer temperature monitoring device shall be calibrated, maintained, and operated according to the manufacturer's specifications. [40 CFR part 64] Federally Enforceable Through Title V Permit

41. Each regenerative thermal oxidizer and its associated components shall be inspected on an annual basis. The records of inspection shall at least contain date and time of inspection, identification of the person performing an inspection, parts replacement and repairs, and all maintenance actions taken. The records shall be kept and maintained for compliance inspection upon request. [40 CFR part 64] Federally Enforceable Through Title V Permit

42. The permittee shall comply with the compliance assurance monitoring operation and maintenance requirements of 40 CFR part 64.7. [40 CFR part 64] Federally Enforceable Through Title V Permit

43. If the District or EPA determine that a Quality Improvement Plan is required under 40 CFR 64.7(d)(2), the permittee shall develop and implement the Quality Improvement Plan in accordance with 40 CFR part 64.8. [40 CFR part 64] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-11-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
240 BHP CLARKE MODEL JU6H-UF60 TIER 2 CERTIFIED DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIRE WATER PUMP

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rules 2201, 4801, 40 CFR 60.4207 (b), and 17 CCR 93115] Federally Enforceable Through Title V Permit
3. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
4. This engine shall be operated only for maintenance, testing, required regulatory purposes, and during emergency situations. For testing purposes, the engine shall only be operated the number of hours necessary to comply with the testing requirements of the National Fire Protection Association (NFPA) 25 - "Standard for the Inspection, Testing, and Maintenance of Water-Based Fire Protection Systems", 1998 edition. Total hours of operation for all maintenance, testing, and required regulatory purposes shall not exceed 100 hours per calendar year. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
5. Emissions from this IC engine shall not exceed any of the following limits: 4.5 g-NOx/bhp-hr, 0.59 g-CO/bhp-hr, or 1.4 g-VOC/bhp-hr. [District Rule 2201, 40 CFR 60.4205(c), 13 CCR 2423, and 17 CCR 93115] Federally Enforceable Through Title V Permit
6. Emissions from this IC engine shall not exceed 0.14 g-PM10/bhp-hr based on USEPA certification using ISO 8178 test procedure. [District Rules 2201, 4102, 40 CFR 60.4205(c), 13 CCR 2423, and 17 CCR 93115] Federally Enforceable Through Title V Permit
7. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
8. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, and the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.). For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
9. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702 and 40 CFR 60.4211(a)] Federally Enforceable Through Title V Permit
10. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-12-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
17,369 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #BB-1) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-381-13-2 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
17,369 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #BB-2) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-14-2 **EXPIRATION DATE:** 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
182,523 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #DM51) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-15-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
182,523 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #DM52) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-16-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
182,523 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #DM53) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-17-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
182,523 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #DM54) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-18-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
27,480 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-20) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-19-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
27,480 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-21) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-20-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
27,480 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-22) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-21-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
27,480 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-23) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-22-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
27,480 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-24) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-23-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
27,480 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-25) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-381-24-2

EXPIRATION DATE: 12/31/2016

EQUIPMENT DESCRIPTION:
27,480 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-26) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-25-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
27,480 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-27) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-26-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
27,480 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-28) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-27-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
27,480 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-29) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-381-28-2

EXPIRATION DATE: 12/31/2016

EQUIPMENT DESCRIPTION:
10,449 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-30) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-381-29-2

EXPIRATION DATE: 12/31/2016

EQUIPMENT DESCRIPTION:
10,449 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-31) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-30-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,449 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-32) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-31-2 **EXPIRATION DATE:** 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,449 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-33) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-32-2 **EXPIRATION DATE:** 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,449 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-34) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-33-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,449 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-35) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-34-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,449 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-36) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-35-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,449 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-37) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-36-2 **EXPIRATION DATE:** 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,449 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-38) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-381-37-2

EXPIRATION DATE: 12/31/2016

EQUIPMENT DESCRIPTION:
2,331 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-39) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-38-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
2,331 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-40) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-39-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
3,455 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-41) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-40-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
3,455 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-42) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-41-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-3) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-42-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-4) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-43-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-5) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-44-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-6) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-45-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-7) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-46-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-8) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-47-2 **EXPIRATION DATE:** 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-9) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-48-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-10) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-49-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-11) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-50-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-12) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-51-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-13) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-52-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-14) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-53-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-15) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-54-2 **EXPIRATION DATE:** 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-16) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-55-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-17) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-56-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-18) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-57-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-19) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-58-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-20) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-59-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-21) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-60-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-22) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-381-61-2

EXPIRATION DATE: 12/31/2016

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-23) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-62-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-24) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-63-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-25) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-64-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-26) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-65-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-27) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-66-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
7,163 GALLON PLASTIC WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-28) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-67-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
7,163 GALLON PLASTIC WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-29) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-68-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
7,163 GALLON PLASTIC WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-30) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-69-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-32) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-70-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-33) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-71-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-34) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-72-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-35) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-74-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-37) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-75-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-38) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-381-76-2

EXPIRATION DATE: 12/31/2016

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-40) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-78-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-44) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-79-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-45) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-80-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-46) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-81-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-47) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-82-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-48) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-83-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
3,965 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-49) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-84-2 **EXPIRATION DATE:** 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
3,965 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-50) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-85-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
5,139 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-51) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-86-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
5,139 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-52) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-87-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
5,139 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-53) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-381-88-2

EXPIRATION DATE: 12/31/2016

EQUIPMENT DESCRIPTION:
5,139 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-54) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-89-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
5,139 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-55) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-90-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,449 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-56) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-381-91-2

EXPIRATION DATE: 12/31/2016

EQUIPMENT DESCRIPTION:
2,331 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-57) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-92-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
2,331 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-58) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-93-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
64,579 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #101)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-94-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
64,579 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #102)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-95-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
64,579 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #103)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-96-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
64,579 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #104)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-97-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
64,579 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #105)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-98-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
265,366 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #238)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-99-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
263,525 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #245)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-104-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
51,739 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #300) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-105-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
51,739 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #301) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-106-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
111,404 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #302) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-107-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
198,762 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #303) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-108-2 **EXPIRATION DATE:** 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
198,103 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #304) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-109-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
198,762 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #305) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-110-2 **EXPIRATION DATE:** 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
198,762 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #306) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-381-111-2

EXPIRATION DATE: 12/31/2016

EQUIPMENT DESCRIPTION:
198,762 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #307) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-381-112-2

EXPIRATION DATE: 12/31/2016

EQUIPMENT DESCRIPTION:
111,104 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #308) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-113-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
111,104 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #309) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-114-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
111,104 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #310) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-381-115-2

EXPIRATION DATE: 12/31/2016

EQUIPMENT DESCRIPTION:
111,404 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #311) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-116-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
111,404 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #312) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-117-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
111,404 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #313) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-118-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
111,404 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #314) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-119-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
106,060 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #315) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-120-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
218,755 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #316) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-121-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
218,755 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #317) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-381-122-2

EXPIRATION DATE: 12/31/2016

EQUIPMENT DESCRIPTION:
198,762 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #318) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-123-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
198,762 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #319) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-124-2 **EXPIRATION DATE:** 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
198,762 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #320) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-125-2 **EXPIRATION DATE:** 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
198,762 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #321) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-381-126-2

EXPIRATION DATE: 12/31/2016

EQUIPMENT DESCRIPTION:
198,762 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #322) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-127-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
655,230 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #326) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-128-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
646,257 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #327) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-129-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
639,742 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #328) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-130-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
651,057 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #329) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-131-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
648,162 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #330) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-132-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
648,162 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #331) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-133-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
648,162 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #333) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-134-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
648,162 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #334) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-135-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
650,156 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #337) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-136-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
655,703 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #338) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-137-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
651,940 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #339) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-381-138-2

EXPIRATION DATE: 12/31/2016

EQUIPMENT DESCRIPTION:
653,237 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #340) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-139-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
27,621 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #341) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-140-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
27,621 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #342) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-381-141-2

EXPIRATION DATE: 12/31/2016

EQUIPMENT DESCRIPTION:
27,621 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #343) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-142-2 **EXPIRATION DATE:** 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
27,621 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #344) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-143-2 **EXPIRATION DATE:** 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
27,621 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #345) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-144-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
27,621 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #346) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-145-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
305,902 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #347) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-146-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
307,251 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #348) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-381-147-2

EXPIRATION DATE: 12/31/2016

EQUIPMENT DESCRIPTION:
307,251 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #349) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-148-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
307,251 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #350) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-149-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #351) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-150-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #352) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-151-2 **EXPIRATION DATE:** 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #353) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-152-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #354) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-381-153-2 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #355) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-154-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #356) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-155-2 **EXPIRATION DATE:** 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #357) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-156-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #358) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-157-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #359) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-158-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #360) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-159-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #361) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-160-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
281,563 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #362) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-161-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #363) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-162-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #364) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-381-163-2

EXPIRATION DATE: 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #365) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-164-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #366) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-165-2 **EXPIRATION DATE:** 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #367) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-166-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #368) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-167-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #369) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-168-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #370) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-169-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #371) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-170-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #372) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-381-171-2

EXPIRATION DATE: 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #373) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-172-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #374) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-173-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #411) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-174-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #412) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-175-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #413) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-176-2 **EXPIRATION DATE:** 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #414) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-177-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #415) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-381-178-2 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #421) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-179-2 **EXPIRATION DATE:** 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #422) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-180-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #423) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-181-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #424) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-182-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #425) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-183-2 **EXPIRATION DATE:** 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #431) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-381-184-2

EXPIRATION DATE: 12/31/2016

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #432) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-185-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #433) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-186-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
294,359 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #441) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-187-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
294,693 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #442) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-381-188-2

EXPIRATION DATE: 12/31/2016

EQUIPMENT DESCRIPTION:
294,693 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #443) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-189-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #451) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-190-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #452) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-191-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #453) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-192-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #463) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-193-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #471) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-381-194-2 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #472) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-195-2 **EXPIRATION DATE:** 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #473) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-196-2 **EXPIRATION DATE:** 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #474) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-197-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #475) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-198-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #481) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-199-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #482) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-200-2 **EXPIRATION DATE:** 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #483) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-201-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #484) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-202-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #485) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-203-2 **EXPIRATION DATE:** 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
26,729 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #491) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-204-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
28,285 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #492) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-381-205-2 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
27,528 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #493) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-206-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
27,528 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #494) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-381-207-2

EXPIRATION DATE: 12/31/2016

EQUIPMENT DESCRIPTION:
27,528 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #495) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-208-2 **EXPIRATION DATE:** 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
28,285 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #4101) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-209-2 **EXPIRATION DATE:** 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
27,528 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #4102) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-210-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
27,528 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #4103) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-211-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
27,528 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #4104) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-381-212-2

EXPIRATION DATE: 12/31/2016

EQUIPMENT DESCRIPTION:
27,528 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #4105) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-213-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
64,579 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #106)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-214-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
64,579 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #107)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-215-2 **EXPIRATION DATE:** 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
64,579 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #108)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-216-2 **EXPIRATION DATE:** 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
64,579 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #109)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-217-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
64,579 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #110)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-280-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
29,744 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #259)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-281-2 **EXPIRATION DATE:** 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
15,229 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #260)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-308-2 **EXPIRATION DATE:** 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
15,239 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #287)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-309-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
29,942 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #288)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-313-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
648,162 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #325) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-314-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
648,162 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #332) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-315-2 **EXPIRATION DATE:** 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
648,162 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #335) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-316-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
648,162 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #336) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-317-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-31) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: S-381-320-2

EXPIRATION DATE: 12/31/2016

EQUIPMENT DESCRIPTION:
10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-42) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. Except when used for fermentation of wine, the wine storage tank shall be equipped and operated with a pressure-vacuum relief valve, set to operate within 10% of the maximum allowable working pressure of the tank and permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. Except when used for fermentation of wine, the pressure-vacuum relief valve shall be installed and operated in accordance with the manufacturer's instructions. [District Rule 4694] Federally Enforceable Through Title V Permit
3. Except when used for fermentation of wine, the pressure-vacuum relief valve and wine storage tank shall remain in a gas-tight condition except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
4. The temperature of each batch of wine placed, stored, or held in the tank shall not exceed 75 degrees F after 60 days following completion of fermentation. [District Rule 4694] Federally Enforceable Through Title V Permit
5. Except when used for fermentation of wine, the maximum temperature of each batch of wine placed, stored, or held in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
6. Except when used for fermentation of wine, records of filling and emptying operations shall be kept for this tank including the date of the operation, a unique identifier for each batch and the volume of wine transferred. [District Rule 4694] Federally Enforceable Through Title V Permit
7. Except when used for fermentation of wine, the wine batch identifier and volume stored in the tank shall be recorded weekly. [District Rule 4694] Federally Enforceable Through Title V Permit
8. The following information shall be recorded for each fermentation batch processed in this tank: 1) wine type stated as either red or white wine, 2) total gallons of must fermented, 3) the uncontrolled fermentation emissions from the batch (calculated per the emission factors given in District Rule 4694). [District Rule 4694]
9. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-324-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
15,281 GALLON STEEL SPIRIT STORAGE TANK (TANK #SING. 4) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-325-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
15,281 GALLON STEEL SPIRIT STORAGE TANK (TANK #SING. 5) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-326-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
20,958 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 1)

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-330-2 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
23,057 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 5) WITH PRESSURE/VACUUM VALVE

DRAFT

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-331-2 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
23,050 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 6) WITH PRESSURE/VACUUM VALVE

DRAFT

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-332-2 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
23,076 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 7) WITH PRESSURE/VACUUM VALVE

DRAFT

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-333-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
23,014 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 8) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-334-2

EXPIRATION DATE: 12/31/2016

EQUIPMENT DESCRIPTION:
23,050 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 9) WITH PRESSURE/VACUUM VALVE

DRAFT

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-335-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
23,076 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 10) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-338-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
58,439 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 13) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-339-2 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
58,439 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 14) WITH PRESSURE/VACUUM VALVE

DRAFT

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-340-2 **EXPIRATION DATE:** 12/31/2016

EQUIPMENT DESCRIPTION:
58,439 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 15) WITH PRESSURE/VACUUM VALVE

DRAFT

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-341-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
17,369 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 20) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-342-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
17,369 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 21) WITH PRESSURE/VACUUM VALVE AND INSULATION

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-343-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
3,965 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 100) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-344-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
15,845 GALLON STEEL SPIRIT STORAGE TANK (TANK #WT-30) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: S-381-345-2

EXPIRATION DATE: 12/31/2016

DRAFT

EQUIPMENT DESCRIPTION:
3,704 GALLON STEEL SPIRIT STORAGE TANK (TANK #WB-24) WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. See Facility-wide requirements for conditions applicable to this permit unit. [District Rule 2080] Federally Enforceable Through Title V Permit

DRAFT

Detailed Facility Report

For Facility=381 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

HECK CELLARS
15401 BEAR MOUNTAIN WINERY RD
DIGIORGIO, CA 93203-9743

FAC # **S 381**
STATUS: **A**
TELEPHONE: **6618546120**

TYPE: **TitleV**
TOXIC ID: **60251**

EXPIRE ON: 12/31/2016
AREA: 9 /
INSP. DATE: 05/18

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-381-6-1	235 BHP IC ENGINE	3020-10 C	1	264.00	264.00	A	235 BHP DETROIT MODEL DDFP-04ATRH DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIRE WATER PUMP
S-381-9-2	26 MMBtu/hr	3020-02 H	1	1,128.00	1,128.00	A	26 MMBTU/HR NATURAL GAS-FIRED BOILER WITH FGR, ZINC RAPID MIX FRMB 19-G-600 LOW NOX BURNER
S-381-10-3	1.67 million gallons	3020-05 G	1	419.00	419.00	A	33,310 BARREL CAPACITY BRANDY STORAGE AND AGING OPERATION (BUILDINGS K & L) SERVED BY A 0.289 MMBTU/HR ADWEST TECHNOLOGIES MODEL RETOX 1.0 RTO95 PRIMARY REGENERATIVE THERMAL OXIDIZER (SMALL RTO) AND 1.156 MMBTU/HR ADWEST TECHNOLOGIES MODEL RETOX 4.0 RTO95 SECONDARY RTO (LARGE RTO)
S-381-11-1	240 bhp IC engine	3020-10 C	1	264.00	264.00	A	240 BHP CLARKE MODEL JU6H-UF60 TIER 2 CERTIFIED DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIRE WATER PUMP
S-381-12-1	17,369 gallons	3020-05 B	1	103.00	103.00	A	17,369 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #BB-1) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-13-1	17,369 gallons	3020-05 B	1	103.00	103.00	A	17,369 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #BB-2) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-14-1	182,523 gallons	3020-05 E	1	270.00	270.00	A	182,523 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #DM51) WITH PRESSURE/VACUUM VALVE
S-381-15-1	182,523 gallons	3020-05 E	1	270.00	270.00	A	182,523 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #DM52) WITH PRESSURE/VACUUM VALVE
S-381-16-1	182,523 gallons	3020-05 E	1	270.00	270.00	A	182,523 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #DM53) WITH PRESSURE/VACUUM VALVE
S-381-17-1	182,523 gallons	3020-05 E	1	270.00	270.00	A	182,523 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #DM54) WITH PRESSURE/VACUUM VALVE
S-381-18-1	27,480 gallons	3020-05 C	1	149.00	149.00	A	27,480 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-20) WITH PRESSURE/VACUUM VALVE
S-381-19-1	27,480 gallons	3020-05 C	1	149.00	149.00	A	27,480 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-21) WITH PRESSURE/VACUUM VALVE
S-381-20-1	27,480 gallons	3020-05 C	1	149.00	149.00	A	27,480 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-22) WITH PRESSURE/VACUUM VALVE

Detailed Facility Report

For Facility=381 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-381-21-1	27,480 gallons	3020-05 C	1	149.00	149.00	A	27,480 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-23) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-22-1	27,480 gallons	3020-05 C	1	149.00	149.00	A	27,480 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-24) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-23-1	27,480 gallons	3020-05 C	1	149.00	149.00	A	27,480 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-25) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-24-1	27,480 GALLON	3020-05 C	1	149.00	149.00	A	27,480 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-26) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-25-1	27,480 gallons	3020-05 C	1	149.00	149.00	A	27,480 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-27) WITH PRESSURE/VACUUM VALVE
S-381-26-1	27,480 gallons	3020-05 C	1	149.00	149.00	A	27,480 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-28) WITH PRESSURE/VACUUM VALVE
S-381-27-1	27,480 gallons	3020-05 C	1	149.00	149.00	A	27,480 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-29) WITH PRESSURE/VACUUM VALVE
S-381-28-1	10,449 gallons	3020-05 B	1	103.00	103.00	A	10,449 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-30) WITH PRESSURE/VACUUM VALVE
S-381-29-1	10,449 gallons	3020-05 B	1	103.00	103.00	A	10,449 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-31) WITH PRESSURE/VACUUM VALVE
S-381-30-1	10,449 gallons	3020-05 B	1	103.00	103.00	A	10,449 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-32) WITH PRESSURE/VACUUM VALVE
S-381-31-1	10,449 gallons	3020-05 B	1	103.00	103.00	A	10,449 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-33) WITH PRESSURE/VACUUM VALVE
S-381-32-1	10,449 GALLON	3020-05 B	1	103.00	103.00	A	10,449 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-34) WITH PRESSURE/VACUUM VALVE
S-381-33-1	10,449 gallons	3020-05 B	1	103.00	103.00	A	10,449 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-35) WITH PRESSURE/VACUUM VALVE
S-381-34-1	10,449 gallons	3020-05 B	1	103.00	103.00	A	10,449 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-36) WITH PRESSURE/VACUUM VALVE
S-381-35-1	10,449 gallons	3020-05 B	1	103.00	103.00	A	10,449 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-37) WITH PRESSURE/VACUUM VALVE
S-381-36-1	10,449 gallons	3020-05 B	1	103.00	103.00	A	10,449 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-38) WITH PRESSURE/VACUUM VALVE
S-381-37-1	2,331 gallons	3020-05 A	1	83.00	83.00	A	2,331 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-39) WITH PRESSURE/VACUUM VALVE

Detailed Facility Report

For Facility=381 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-381-38-1	2,331 gallons	3020-05 A	1	83.00	83.00	A	2,331 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-40) WITH PRESSURE/VACUUM VALVE
S-381-39-1	3,455 gallons	3020-05 A	1	83.00	83.00	A	3,455 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-41) WITH PRESSURE/VACUUM VALVE
S-381-40-1	3,455 gallons	3020-05 A	1	83.00	83.00	A	3,455 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #B-42) WITH PRESSURE/VACUUM VALVE
S-381-41-1	12,773 gallons	3020-05 B	1	103.00	103.00	A	12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-3) WITH PRESSURE/VACUUM VALVE
S-381-42-1	10,277 gallons	3020-05 B	1	103.00	103.00	A	10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-4) WITH PRESSURE/VACUUM VALVE
S-381-43-1	10,277 gallons	3020-05 B	1	103.00	103.00	A	10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-5) WITH PRESSURE/VACUUM VALVE
S-381-44-1	10,277 gallons	3020-05 B	1	103.00	103.00	A	10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-6) WITH PRESSURE/VACUUM VALVE
S-381-45-1	12,773 gallons	3020-05 B	1	103.00	103.00	A	12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-7) WITH PRESSURE/VACUUM VALVE
S-381-46-1	12,773 gallons	3020-05 B	1	103.00	103.00	A	12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-8) WITH PRESSURE/VACUUM VALVE
S-381-47-1	12,773 gallons	3020-05 B	1	103.00	103.00	A	12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-9) WITH PRESSURE/VACUUM VALVE
S-381-48-1	12,773 gallons	3020-05 B	1	103.00	103.00	A	12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-10) WITH PRESSURE/VACUUM VALVE
S-381-49-1	12,773 gallons	3020-05 B	1	103.00	103.00	A	12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-11) WITH PRESSURE/VACUUM VALVE
S-381-50-1	12,773 gallons	3020-05 B	1	103.00	103.00	A	12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-12) WITH PRESSURE/VACUUM VALVE
S-381-51-1	12,773 gallons	3020-05 B	1	103.00	103.00	A	12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-13) WITH PRESSURE/VACUUM VALVE
S-381-52-1	12,773 gallons	3020-05 B	1	103.00	103.00	A	12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-14) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-53-1	12,773 gallons	3020-05 B	1	103.00	103.00	A	12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-15) WITH PRESSURE/VACUUM VALVE AND INSULATION

Detailed Facility Report

For Facility=381 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-381-54-1	12,773 gallons	3020-05 B	1	103.00	103.00	A	12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-16) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-55-1	12,773 gallons	3020-05 B	1	103.00	103.00	A	12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-17) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-56-1	12,773 gallons	3020-05 B	1	103.00	103.00	A	12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-18) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-57-1	12,773 gallons	3020-05 B	1	103.00	103.00	A	12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-19) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-58-1	12,773 gallons	3020-05 B	1	103.00	103.00	A	12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-20) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-59-1	12,773 gallons	3020-05 B	1	103.00	103.00	A	12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-21) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-60-1	12,773 gallons	3020-05 B	1	103.00	103.00	A	12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-22) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-61-1	12,773 gallons	3020-05 B	1	103.00	103.00	A	12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-23) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-62-1	12,773 gallons	3020-05 B	1	103.00	103.00	A	12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-24) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-63-1	12,773 gallons	3020-05 B	1	103.00	103.00	A	12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-25) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-64-1	12,773 gallons	3020-05 B	1	103.00	103.00	A	12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-26) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-65-1	12,773 gallons	3020-05 B	1	103.00	103.00	A	12,773 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-27) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-66-1	7,163 gallons	3020-05 B	1	103.00	103.00	A	7,163 GALLON PLASTIC WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-28) WITH PRESSURE/VACUUM VALVE
S-381-67-1	7,163 gallons	3020-05 B	1	103.00	103.00	A	7,163 GALLON PLASTIC WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-29) WITH PRESSURE/VACUUM VALVE

Detailed Facility Report

For Facility=381 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-381-68-1	7,163 gallons	3020-05 B	1	103.00	103.00	A	7,163 GALLON PLASTIC WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-30) WITH PRESSURE/VACUUM VALVE
S-381-69-1	10,277 gallons	3020-05 B	1	103.00	103.00	A	10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-32) WITH PRESSURE/VACUUM VALVE
S-381-70-1	10,277 gallons	3020-05 B	1	103.00	103.00	A	10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-33) WITH PRESSURE/VACUUM VALVE
S-381-71-1	10,277 gallons	3020-05 B	1	103.00	103.00	A	10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-34) WITH PRESSURE/VACUUM VALVE
S-381-72-1	10,277 gallons	3020-05 B	1	103.00	103.00	A	10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-35) WITH PRESSURE/VACUUM VALVE
S-381-74-1	10,277 gallons	3020-05 B	1	103.00	103.00	A	10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-37) WITH PRESSURE/VACUUM VALVE
S-381-75-1	10,277 gallons	3020-05 B	1	103.00	103.00	A	10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-38) WITH PRESSURE/VACUUM VALVE
S-381-76-1	10,277 gallons	3020-05 B	1	103.00	103.00	A	10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-40) WITH PRESSURE/VACUUM VALVE
S-381-78-1	10,277 gallons	3020-05 B	1	103.00	103.00	A	10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-44) WITH PRESSURE/VACUUM VALVE
S-381-79-1	10,277 gallons	3020-05 B	1	103.00	103.00	A	10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-45) WITH PRESSURE/VACUUM VALVE
S-381-80-1	10,277 gallons	3020-05 B	1	103.00	103.00	A	10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-46) WITH PRESSURE/VACUUM VALVE
S-381-81-1	10,277 gallons	3020-05 B	1	103.00	103.00	A	10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-47) WITH PRESSURE/VACUUM VALVE
S-381-82-1	10,277 gallons	3020-05 B	1	103.00	103.00	A	10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-48) WITH PRESSURE/VACUUM VALVE
S-381-83-1	3,965 gallons	3020-05 A	1	83.00	83.00	A	3,965 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-49) WITH PRESSURE/VACUUM VALVE

Detailed Facility Report

For Facility=381 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-381-84-1	3,965 gallons	3020-05 A	1	83.00	83.00	A	3,965 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-50) WITH PRESSURE/VACUUM VALVE
S-381-85-1	5,139 gallons	3020-05 B	1	103.00	103.00	A	5,139 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-51) WITH PRESSURE/VACUUM VALVE
S-381-86-1	5,139 gallons	3020-05 B	1	103.00	103.00	A	5,139 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-52) WITH PRESSURE/VACUUM VALVE
S-381-87-1	5,139 gallons	3020-05 B	1	103.00	103.00	A	5,139 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-53) WITH PRESSURE/VACUUM VALVE
S-381-88-1	5,139 gallons	3020-05 B	1	103.00	103.00	A	5,139 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-54) WITH PRESSURE/VACUUM VALVE
S-381-89-1	5,139 gallons	3020-05 B	1	103.00	103.00	A	5,139 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-55) WITH PRESSURE/VACUUM VALVE
S-381-90-1	10,449 gallons	3020-05 B	1	103.00	103.00	A	10,449 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-56) WITH PRESSURE/VACUUM VALVE
S-381-91-1	2,331 gallons	3020-05 A	1	83.00	83.00	A	2,331 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-57) WITH PRESSURE/VACUUM VALVE
S-381-92-1	2,331 gallons	3020-05 A	1	83.00	83.00	A	2,331 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-58) WITH PRESSURE/VACUUM VALVE
S-381-93-1	64,579 gallons	3020-05 D	1	203.00	203.00	A	64,579 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #101)
S-381-94-1	64,579 gallons	3020-05 D	1	203.00	203.00	A	64,579 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #102)
S-381-95-1	64,579 gallons	3020-05 D	1	203.00	203.00	A	64,579 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #103)
S-381-96-1	64,579 gallons	3020-05 D	1	203.00	203.00	A	64,579 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #104)
S-381-97-1	64,579 gallons	3020-05 D	1	203.00	203.00	A	64,579 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #105)
S-381-98-1	265,366 gallons	3020-05 E	1	270.00	270.00	A	265,366 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #238)

Detailed Facility Report

For Facility=381 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-381-99-1	263,525 gallons	3020-05 E	1	270.00	270.00	A	263,525 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #245)
S-381-104-1	51,739 gallons	3020-05 D	1	203.00	203.00	A	51,739 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #300) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-105-1	51,739 gallons	3020-05 D	1	203.00	203.00	A	51,739 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #301) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-106-1	111,404 gallons	3020-05 E	1	270.00	270.00	A	111,404 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #302) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-107-1	198,762 gallons	3020-05 E	1	270.00	270.00	A	198,762 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #303) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-108-1	198,103 gallons	3020-05 E	1	270.00	270.00	A	198,103 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #304) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-109-1	198,762 gallons	3020-05 E	1	270.00	270.00	A	198,762 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #305) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-110-1	198,762 gallons	3020-05 E	1	270.00	270.00	A	198,762 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #306) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-111-1	198,762 gallons	3020-05 E	1	270.00	270.00	A	198,762 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #307) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-112-1	111,104 gallons	3020-05 E	1	270.00	270.00	A	111,104 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #308) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-113-1	111,104 gallons	3020-05 E	1	270.00	270.00	A	111,104 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #309) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-114-1	111,104 gallons	3020-05 E	1	270.00	270.00	A	111,104 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #310) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-115-1	111,104 gallons	3020-05 E	1	270.00	270.00	A	111,404 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #311) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-116-1	111,104 gallons	3020-05 E	1	270.00	270.00	A	111,404 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #312) WITH PRESSURE/VACUUM VALVE AND INSULATION

Detailed Facility Report

For Facility=381 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-381-117-1	111,104 gallons	3020-05 E	1	270.00	270.00	A	111,404 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #313) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-118-1	111,104 gallons	3020-05 E	1	270.00	270.00	A	111,404 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #314) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-119-1	106,060 gallons	3020-05 E	1	270.00	270.00	A	106,060 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #315) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-120-1	218,755 gallons	3020-05 E	1	270.00	270.00	A	218,755 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #316) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-121-1	218,755 gallons	3020-05 E	1	270.00	270.00	A	218,755 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #317) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-122-1	198,762 gallons	3020-05 E	1	270.00	270.00	A	198,762 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #318) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-123-1	198,762 gallons	3020-05 E	1	270.00	270.00	A	198,762 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #319) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-124-1	198,762 gallons	3020-05 E	1	270.00	270.00	A	198,762 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #320) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-125-1	198,762 gallons	3020-05 E	1	270.00	270.00	A	198,762 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #321) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-126-1	198,762 gallons	3020-05 E	1	270.00	270.00	A	198,762 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #322) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-127-1	655,230 gallons	3020-05 F	1	330.00	330.00	A	655,230 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #326) WITH PRESSURE/VACUUM VALVE
S-381-128-1	646,257 gallons	3020-05 F	1	330.00	330.00	A	646,257 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #327) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-129-1	639,742 gallons	3020-05 F	1	330.00	330.00	A	639,742 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #328) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-130-1	651,057 gallons	3020-05 F	1	330.00	330.00	A	651,057 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #329) WITH PRESSURE/VACUUM VALVE AND INSULATION

Detailed Facility Report

For Facility=381 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-381-131-1	648,162 gallons	3020-05 F	1	330.00	330.00	A	648,162 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #330) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-132-1	648,162 gallons	3020-05 F	1	330.00	330.00	A	648,162 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #331) WITH PRESSURE/VACUUM VALVE
S-381-133-1	648,162 gallons	3020-05 F	1	330.00	330.00	A	648,162 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #333) WITH PRESSURE/VACUUM VALVE
S-381-134-1	648,162 gallons	3020-05 F	1	330.00	330.00	A	648,162 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #334) WITH PRESSURE/VACUUM VALVE
S-381-135-1	650,156 gallons	3020-05 F	1	330.00	330.00	A	650,156 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #337) WITH PRESSURE/VACUUM VALVE
S-381-136-1	655,703 gallons	3020-05 F	1	330.00	330.00	A	655,703 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #338) WITH PRESSURE/VACUUM VALVE
S-381-137-1	651,940 gallons	3020-05 F	1	330.00	330.00	A	651,940 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #339) WITH PRESSURE/VACUUM VALVE
S-381-138-1	653,237 gallons	3020-05 F	1	330.00	330.00	A	653,237 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #340) WITH PRESSURE/VACUUM VALVE
S-381-139-1	27,621 gallons	3020-05 C	1	149.00	149.00	A	27,621 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #341) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-140-1	27,621 gallons	3020-05 C	1	149.00	149.00	A	27,621 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #342) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-141-1	27,621 gallons	3020-05 C	1	149.00	149.00	A	27,621 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #343) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-142-1	27,621 gallons	3020-05 C	1	149.00	149.00	A	27,621 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #344) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-143-1	27,621 gallons	3020-05 C	1	149.00	149.00	A	27,621 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #345) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-144-1	27,621 gallons	3020-05 C	1	149.00	149.00	A	27,621 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #346) WITH PRESSURE/VACUUM VALVE AND INSULATION

Detailed Facility Report

For Facility=381 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-381-145-1	305,902 gallons	3020-05 E	1	270.00	270.00	A	305,902 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #347) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-146-1	307,251 gallons	3020-05 E	1	270.00	270.00	A	307,251 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #348) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-147-1	307,251 gallons	3020-05 E	1	270.00	270.00	A	307,251 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #349) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-148-1	307,251 gallons	3020-05 E	1	270.00	270.00	A	307,251 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #350) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-149-1	218,185 gallons	3020-05 E	1	270.00	270.00	A	218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #351) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-150-1	218,185 gallons	3020-05 E	1	270.00	270.00	A	218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #352) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-151-1	218,185 gallons	3020-05 E	1	270.00	270.00	A	218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #353) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-152-1	218,185 gallons	3020-05 E	1	270.00	270.00	A	218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #354) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-153-1	218,185 gallons	3020-05 E	1	270.00	270.00	A	218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #355) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-154-1	218,185 gallons	3020-05 E	1	270.00	270.00	A	218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #356) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-155-1	218,185 gallons	3020-05 E	1	270.00	270.00	A	218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #357) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-156-1	218,185 gallons	3020-05 E	1	270.00	270.00	A	218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #358) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-157-1	218,185 gallons	3020-05 E	1	270.00	270.00	A	218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #359) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-158-1	218,185 gallons	3020-05 E	1	270.00	270.00	A	218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #360) WITH PRESSURE/VACUUM VALVE AND INSULATION

Detailed Facility Report

For Facility=381 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-381-159-1	218,185 gallons	3020-05 E	1	270.00	270.00	A	218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #361) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-160-1	281,563 gallons	3020-05 E	1	270.00	270.00	A	281,563 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #362) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-161-1	106,878 gallons	3020-05 E	1	270.00	270.00	A	106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #363) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-162-1	106,878 gallons	3020-05 E	1	270.00	270.00	A	106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #364) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-163-1	106,878 gallons	3020-05 E	1	270.00	270.00	A	106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #365) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-164-1	106,878 gallons	3020-05 E	1	270.00	270.00	A	106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #366) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-165-1	106,878 gallons	3020-05 E	1	270.00	270.00	A	106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #367) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-166-1	106,878 gallons	3020-05 E	1	270.00	270.00	A	106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #368) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-167-1	106,878 gallons	3020-05 E	1	270.00	270.00	A	106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #369) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-168-1	106,878 gallons	3020-05 E	1	270.00	270.00	A	106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #370) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-169-1	106,878 gallons	3020-05 E	1	270.00	270.00	A	106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #371) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-170-1	106,878 gallons	3020-05 E	1	270.00	270.00	A	106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #372) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-171-1	106,878 gallons	3020-05 E	1	270.00	270.00	A	106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #373) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-172-1	106,878 gallons	3020-05 E	1	270.00	270.00	A	106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #374) WITH PRESSURE/VACUUM VALVE AND INSULATION

Detailed Facility Report

For Facility=381 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-381-173-1	106,878 gallons	3020-05 E	1	270.00	270.00	A	106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #411) WITH PRESSURE/VACUUM VALVE
S-381-174-1	106,878 gallons	3020-05 E	1	270.00	270.00	A	106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #412) WITH PRESSURE/VACUUM VALVE
S-381-175-1	106,878 gallons	3020-05 E	1	270.00	270.00	A	106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #413) WITH PRESSURE/VACUUM VALVE
S-381-176-1	106,878 gallons	3020-05 E	1	270.00	270.00	A	106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #414) WITH PRESSURE/VACUUM VALVE
S-381-177-1	106,878 gallons	3020-05 E	1	270.00	270.00	A	106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #415) WITH PRESSURE/VACUUM VALVE
S-381-178-1	106,878 gallons	3020-05 E	1	270.00	270.00	A	106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #421) WITH PRESSURE/VACUUM VALVE
S-381-179-1	106,878 gallons	3020-05 E	1	270.00	270.00	A	106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #422) WITH PRESSURE/VACUUM VALVE
S-381-180-1	106,878 gallons	3020-05 E	1	270.00	270.00	A	106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #423) WITH PRESSURE/VACUUM VALVE
S-381-181-1	106,878 gallons	3020-05 E	1	270.00	270.00	A	106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #424) WITH PRESSURE/VACUUM VALVE
S-381-182-1	106,878 gallons	3020-05 E	1	270.00	270.00	A	106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #425) WITH PRESSURE/VACUUM VALVE
S-381-183-1	218,185 gallons	3020-05 E	1	270.00	270.00	A	218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #431) WITH PRESSURE/VACUUM VALVE
S-381-184-1	218,185 gallons	3020-05 E	1	270.00	270.00	A	218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #432) WITH PRESSURE/VACUUM VALVE
S-381-185-1	218,185 gallons	3020-05 E	1	270.00	270.00	A	218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #433) WITH PRESSURE/VACUUM VALVE
S-381-186-1	294,395 gallons	3020-05 E	1	270.00	270.00	A	294,359 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #441) WITH PRESSURE/VACUUM VALVE

Detailed Facility Report

For Facility=381 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-381-187-1	294,693 gallons	3020-05 E	1	270.00	270.00	A	294,693 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #442) WITH PRESSURE/VACUUM VALVE
S-381-188-1	294,693 gallons	3020-05 E	1	270.00	270.00	A	294,693 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #443) WITH PRESSURE/VACUUM VALVE
S-381-189-1	218,185 gallons	3020-05 E	1	270.00	270.00	A	218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #451) WITH PRESSURE/VACUUM VALVE
S-381-190-1	218,185 gallons	3020-05 E	1	270.00	270.00	A	218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #452) WITH PRESSURE/VACUUM VALVE
S-381-191-1	218,185 gallons	3020-05 E	1	270.00	270.00	A	218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #453) WITH PRESSURE/VACUUM VALVE
S-381-192-1	218,185 gallons	3020-05 E	1	270.00	270.00	A	218,185 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #463) WITH PRESSURE/VACUUM VALVE
S-381-193-1	106,878 gallons	3020-05 E	1	270.00	270.00	A	106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #471) WITH PRESSURE/VACUUM VALVE
S-381-194-1	106,878 gallons	3020-05 E	1	270.00	270.00	A	106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #472) WITH PRESSURE/VACUUM VALVE
S-381-195-1	106,878 gallons	3020-05 E	1	270.00	270.00	A	106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #473) WITH PRESSURE/VACUUM VALVE
S-381-196-1	106,878 gallons	3020-05 E	1	270.00	270.00	A	106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #474) WITH PRESSURE/VACUUM VALVE
S-381-197-1	106,878 gallons	3020-05 E	1	270.00	270.00	A	106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #475) WITH PRESSURE/VACUUM VALVE
S-381-198-1	106,878 gallons	3020-05 E	1	270.00	270.00	A	106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #481) WITH PRESSURE/VACUUM VALVE
S-381-199-1	106,878 gallons	3020-05 E	1	270.00	270.00	A	106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #482) WITH PRESSURE/VACUUM VALVE
S-381-200-1	106,878 gallons	3020-05 E	1	270.00	270.00	A	106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #483) WITH PRESSURE/VACUUM VALVE

Detailed Facility Report

For Facility=381 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-381-201-1	106,878 gallons	3020-05 E	1	270.00	270.00	A	106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #484) WITH PRESSURE/VACUUM VALVE
S-381-202-1	106,878 gallons	3020-05 E	1	270.00	270.00	A	106,878 GALLON STEEL WINE AND SPIRIT STORAGE AND RED AND WHITE WINE FERMENTATION TANK (TANK #485) WITH PRESSURE/VACUUM VALVE
S-381-203-1	26,729 gallons	3020-05 C	1	149.00	149.00	A	26,729 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #491) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-204-1	28,285 gallons	3020-05 C	1	149.00	149.00	A	28,285 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #492) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-205-1	27,528 gallons	3020-05 C	1	149.00	149.00	A	27,528 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #493) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-206-1	27,528 gallons	3020-05 C	1	149.00	149.00	A	27,528 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #494) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-207-1	27,528 gallons	3020-05 C	1	149.00	149.00	A	27,528 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #495) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-208-1	28,285 gallons	3020-05 C	1	149.00	149.00	A	28,285 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #4101) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-209-1	27,528 gallons	3020-05 C	1	149.00	149.00	A	27,528 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #4102) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-210-1	27,528 gallons	3020-05 C	1	149.00	149.00	A	27,528 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #4103) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-211-1	27,528 gallons	3020-05 C	1	149.00	149.00	A	27,528 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #4104) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-212-1	27,528 gallons	3020-05 C	1	149.00	149.00	A	27,528 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #4105) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-213-1	64,579 gallons	3020-05 D	1	203.00	203.00	A	64,579 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #106)
S-381-214-1	64,579 gallons	3020-05 D	1	203.00	203.00	A	64,579 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #107)

Detailed Facility Report

For Facility=381 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-381-215-1	64,579 gallons	3020-05 D	1	203.00	203.00	A	64,579 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #108)
S-381-216-1	64,579 gallons	3020-05 D	1	203.00	203.00	A	64,579 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #109)
S-381-217-1	64,579 gallons	3020-05 D	1	203.00	203.00	A	64,579 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #110)
S-381-280-1	29,744 gallons	3020-05 C	1	149.00	149.00	A	29,744 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #259)
S-381-281-1	15,229 gallons	3020-05 B	1	103.00	103.00	A	15,229 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #260)
S-381-308-1	15,239 gallons	3020-05 B	1	103.00	103.00	A	15,239 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #287)
S-381-309-1	29,942 gallons	3020-05 C	1	149.00	149.00	A	29,942 GALLON CONCRETE WINE STORAGE AND WHITE WINE FERMENTATION TANK (TANK #288)
S-381-313-1	648,162 gallons	3020-05 F	1	330.00	330.00	A	648,162 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #325) WITH PRESSURE/VACUUM VALVE
S-381-314-1	648,162 gallons	3020-05 F	1	330.00	330.00	A	648,162 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #332) WITH PRESSURE/VACUUM VALVE
S-381-315-1	648,162 gallons	3020-05 F	1	330.00	330.00	A	648,162 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #335) WITH PRESSURE/VACUUM VALVE
S-381-316-1	648,162 gallons	3020-05 F	1	330.00	330.00	A	648,162 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #336) WITH PRESSURE/VACUUM VALVE
S-381-317-1	10,277 gallons	3020-05 B	1	103.00	103.00	A	10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-31) WITH PRESSURE/VACUUM VALVE
S-381-320-1	10,277 gallons	3020-05 B	1	103.00	103.00	A	10,277 GALLON STEEL WINE AND SPIRIT STORAGE AND WHITE WINE FERMENTATION TANK (TANK #SS-42) WITH PRESSURE/VACUUM VALVE
S-381-324-1	15,281 gallons	3020-05 B	1	103.00	103.00	A	15,281 GALLON STEEL SPIRIT STORAGE TANK (TANK #SING. 4) WITH PRESSURE/VACUUM VALVE
S-381-325-1	15,281 gallons	3020-05 B	1	103.00	103.00	A	15,281 GALLON STEEL SPIRIT STORAGE TANK (TANK #SING. 5) WITH PRESSURE/VACUUM VALVE
S-381-326-1	20,958 gallons	3020-05 C	1	149.00	149.00	A	20,958 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 1)
S-381-330-1	23,057 gallons	3020-05 C	1	149.00	149.00	A	23,057 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 5) WITH PRESSURE/VACUUM VALVE

Detailed Facility Report

For Facility=381 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-381-331-1	23,050 gallons	3020-05 C	1	149.00	149.00	A	23,050 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 6) WITH PRESSURE/VACUUM VALVE
S-381-332-1	23,076 gallons	3020-05 C	1	149.00	149.00	A	23,076 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 7) WITH PRESSURE/VACUUM VALVE
S-381-333-1	23,014 gallons	3020-05 C	1	149.00	149.00	A	23,014 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 8) WITH PRESSURE/VACUUM VALVE
S-381-334-1	23,050 gallons	3020-05 C	1	149.00	149.00	A	23,050 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 9) WITH PRESSURE/VACUUM VALVE
S-381-335-1	23,076 gallons	3020-05 C	1	149.00	149.00	A	23,076 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 10) WITH PRESSURE/VACUUM VALVE
S-381-338-1	58,439 gallons	3020-05 D	1	203.00	203.00	A	58,439 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 13) WITH PRESSURE/VACUUM VALVE
S-381-339-1	58,439 gallons	3020-05 D	1	203.00	203.00	A	58,439 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 14) WITH PRESSURE/VACUUM VALVE
S-381-340-1	58,439 gallons	3020-05 D	1	203.00	203.00	A	58,439 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 15) WITH PRESSURE/VACUUM VALVE
S-381-341-1	17,369 gallons	3020-05 B	1	103.00	103.00	A	17,369 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 20) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-342-1	17,369 gallons	3020-05 B	1	103.00	103.00	A	17,369 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 21) WITH PRESSURE/VACUUM VALVE AND INSULATION
S-381-343-1	3,965 gallons	3020-05 A	1	83.00	83.00	A	3,965 GALLON STEEL SPIRIT STORAGE TANK (TANK #PSP 100) WITH PRESSURE/VACUUM VALVE
S-381-344-1	15,845 gallons	3020-05 B	1	103.00	103.00	A	15,845 GALLON STEEL SPIRIT STORAGE TANK (TANK #WT-30) WITH PRESSURE/VACUUM VALVE
S-381-345-1	3,704 gallons	3020-05 A	1	83.00	83.00	A	3,704 GALLON STEEL SPIRIT STORAGE TANK (TANK #WB-24) WITH PRESSURE/VACUUM VALVE

Number of Facilities Reported: 1