San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

OCT 19 2017

Mr. Erik Martella
CBUS Ops dba Mission Bell Winery
12667 Road 24
Madera, CA 93637

Re: Notice of Preliminary Decision – Title V Permit Renewal
District Facility # C-628
Project # C-1161173

Dear Mr. Martella:

Enclosed for your review and comment is the District's analysis of the application to renew the Federally Mandated Operating Permit for CBUS Ops dba Mission Bell Winery located at 12667 Road 24, Madera, California.

The notice of preliminary decision for this project will be published approximately three days from the date of this letter. After addressing all comments made during the 30-day public notice and the 45-day EPA comment periods, the District intends to issue the renewed Federally Mandated Operating Permit. Please submit your written comments on this project within the 30-day public comment period, as specified in the enclosed public notice.

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Errol Villegas, Permit Services Manager, at (559) 230-5900.

Sincerely,

Arnaud Marjollet
Director of Permit Services

Enclosures

cc: Tung Le, CARB (w/enclosure) via email
cc: Gerardo C. Rios, EPA (w/enclosure) via email

Seyed Sadredin
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

www.valleyair.org www.healthyairliving.com

Printed on recycled paper.

SAN JOAQUIN VALLEY
AIR POLLUTION CONTROL DISTRICT

Proposed Title V Permit Renewal Evaluation
CBUS Ops dba Mission Bell Winery
C-628

TABLE OF CONTENTS

I. PROPOSAL 2
II. FACILITY LOCATION 2
III. EQUIPMENT LISTING 2
IV. GENERAL PERMIT TEMPLATE USAGE 3
V. SCOPE OF EPA AND PUBLIC REVIEW 3
VI. FEDERALLY ENFORCEABLE REQUIREMENTS 3
VII. REQUIREMENTS NOT FEDERALLY ENFORCEABLE 6
VIII. PERMIT REQUIREMENTS 7
IX. PERMIT SHIELD 41
X. CALIFORNIA ENVIRONMENTAL QUALITY ACT 42
XI. PERMIT CONDITIONS 42

ATTACHMENTS 42

A. DRAFT RENEWED TITLE V OPERATING PERMIT
B. PREVIOUS TITLE V OPERATING PERMIT
C. DETAILED SUMMARY LIST OF FACILITY PERMITS

TITLE V PERMIT RENEWAL EVALUATION

Winery

Engineer: Dustin Brown
Date: October 19, 2017

Facility Number: C-628
Facility Name: CBUS Ops dba Mission Bell Winery
Mailing Address: 12667 Road 24
Madera, CA 93637

Contact Name: Erik Martella
Phone: (559) 661-5640

Responsible Official: Mr. Erik Martella
Title: VP, General Manager

Project #: C-1161173
Deemed Complete: June 13, 2016

I. PROPOSAL

CBUS Ops dba Mission Bell Winery was issued their last renewed Title V permit on December 22, 2011. As required by District Rule 2520, the applicant is requesting a permit renewal. The existing Title V permit will be reviewed and modified to reflect all applicable District and federal rules that have been updated, removed, or added since the issuance of the facility's last renewed Title V permit.

The purpose of this evaluation is to provide the legal and factual basis for all updated applicable requirements and to determine if the facility will comply with these updated requirements. It also specifically identifies all additions, deletions, and/or changes made to permit conditions or equipment descriptions.

II. FACILITY LOCATION

CBUS Ops dba Mission Bell Winery is located at 12667 Road 24 in Fresno, CA.

III. EQUIPMENT LISTING

A detailed facility printout listing all permitted equipment at the facility is included as Attachment C.

IV. GENERAL PERMIT TEMPLATE USAGE

The applicant is not proposing to use any model general permit templates as a part of this Title V renewal project.

V. SCOPE OF EPA AND PUBLIC REVIEW

The applicant is not requesting any model general permit templates. Therefore, all Federally Enforceable conditions in this current Title V permit will be subject to EPA and public review.

VI. FEDERALLY ENFORCEABLE REQUIREMENTS

A. Rules Updated or Evaluated

- District Rule 2020, Exemptions
  (amended August 18, 2011 ⇒ amended December 18, 2014)

- District Rule 2201, New and Modified Stationary Source Review Rule
  (amended December 18, 2008 ⇒ amended February 18, 2016)

- District Rule 2520, Federally Mandated Operating Permits
  (amended June 21, 2001)

  District Rule 4621, Gasoline Transfer Into Stationary Storage Containers, Delivery Vessels, and Bulk Plants
  (amended December 20, 2007 ⇒ amended December 19, 2013)

- District Rule 4622, Gasoline Transfer Into Motor Vehicle Fuel Tanks
  (amended December 20, 2007 ⇒ amended December 19, 2013)

- District Rule 4702, Internal Combustion Engines
  (amended August 18, 2011 ⇒ amended November 14, 2013)

- 40 CFR Part 60, Subpart Dc, Standards of Performance for Small Industrial-Commercial-Institutional Steam Generating Units
  (amended February 16, 2012)

- 40 CFR Part 63, Subpart ZZZZ, National Emissions Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines
  (amended February 27, 2014)

- 40 CFR Part 64, Compliance Assurance Monitoring
  (adopted October 22, 1997)

- 40 CFR Part 82, Subpart B, Servicing of Motor Vechicle Air Conditioners
  (amended June 25, 2013)

- 40 CFR Part 82, Subpart F, Recycling and Emissions Reductions
  (amended December 1, 2016)

B. Rules Removed

There have been no rules removed since the last renewed Title V permit was issued.

C. Rules Added

- District Rule 2410, Prevention of Significant Deterioration
  (adopted June 16, 2011)

D. Rules Not Updated

- District Rule 1070, Inspections
  (amended December 17, 1992)

- District Rule 1080, Stack Monitoring
  (amended December 17, 1992)

- District Rule 1081, Source Sampling
  (amended December 16, 1993)

- District Rule 1100, Equipment Breakdown (Non-SIP replacement for Fresno County Rule 110)
  (amended December 17, 1992)

- District Rule 1160, Emission Statements
  (amended November 18, 1992)

- District Rule 2010, Permits Required
  (amended December 17, 1992)

- District Rule 2031, Transfer of Permits
  (amended December 17, 1992)

- District Rule 2040, Applications
  (amended December 17, 1992)

- District Rule 2070, Standards for Granting Applications
  (amended December 17, 1992)

- District Rule 2080, Conditional Approval
  (amended December 17, 1992)

- District Rule 4101, Visible Emissions
  (amended February 17, 2005)

- District Rule 4201, Particulate Matter Concentration
  (amended December 17, 1992)

- District Rule 4202, Particulate Matter Emission Rate
  (amended December 17, 1992)

- District Rule 4301, Fuel Burning Equipment
  (amended December 17, 1992)

- District Rule 4305, Boilers, Steam Generators and Process Heaters – Phase 2
  (amended August 21, 2003)

- District Rule 4306, Boilers, Steam Generators and Process Heaters – Phase 3
  (amended October 16, 2008)

- District Rule 4320, Advanced Emission Reduction Options for Boilers, Steam Generators and Process Heaters Greater Than 5.0 MMBtu/hr
  (adopted October 16, 2008)

- District Rule 4601, Architectural Coatings
  (amended December 17, 2009)

- District Rule 4694, Wine Fermentation and Storage Tanks
  (amended December 15, 2005)

- District Rule 4801, Sulfur Compounds (Non-SIP replacement for Fresno County Rule 106)
  (amended December 17, 1992)

- District Rule 8011, Fugitive Dust General Requirements
  (amended August 19, 2004)

- District Rule 8021, Fugitive Dust Requirements for Control of Fine Particulate Matter (PM10) from Construction, Demolition, Excavation, and Extraction Activities
  (amended August 19, 2004)

- District Rule 8031, Fugitive Dust Requirements for Control of Fine Particulate Matter (PM10) from Handling and Storage of Bulk Materials
  (amended August 19, 2004)

- District Rule 8041, Fugitive Dust Requirements for Control of Fine Particulate Matter (PM10) from Carryout and Trackout
  (amended August 19, 2004)

- District Rule 8051, Fugitive Dust Requirements for Control of Fine Particulate Matter (PM10) from Open Areas
  (amended August 19, 2004)

- District Rule 8061, Fugitive Dust Requirements for Control of Fine Particulate Matter (PM10) from Paved and Unpaved Roads
  (amended August 19, 2004)

- District Rule 8071, Fugitive Dust Requirements for Control of Fine Particulate Matter (PM10) from Unpaved Vehicle/Equipment Areas
  (amended September 16, 2004)

- 40 CFR Part 61, Subpart M, National Emissions Standards for Asbestos
  (amended July 20, 2004)

VII. REQUIREMENTS NOT FEDERALLY ENFORCEABLE

For each Title V source, the District issues a single permit that contains the Federally Enforceable requirements, as well as the District-only requirements. The District-only requirements are not a part of the Title V Operating Permits. The terms and conditions that are part of the facility's Title V permit are designated as "Federally Enforceable Through Title V Permit."

For this facility, the following rules are not Federally Enforceable:

A. Rules Updated or Evaluated

- District Rule 4694, Wine Fermentation and Storage Tanks *(adopted December 15, 2005)*

B. Rules Added

No rules were added.

C. Rules Not Updated

- District Rule 4102, Nuisance *(amended December 17, 1992)*
- 17 CCR 93115, Airborne Toxic Control Measure (ATCM) for Stationary Compression-Ignition Engines *(adopted May 19, 2011)*

VIII. PERMIT REQUIREMENTS

The purpose of this evaluation is to review changes to Federally Enforceable requirements; therefore, this compliance section will only address rules that have been amended or added since the issuance of the last Title V permit renewal in 2011.

A. District Rule 2020 – Exemptions

District Rule 2020 lists equipment which is specifically exempt from obtaining permits and specifies recordkeeping requirements to verify such exemptions. The amendments to this rule do not have any effect on current permit requirements and will therefore not be addressed in this evaluation.

B. District Rule 2201– New and Modified Stationary Source Review Rule

District Rule 2201 has been amended since this Title V permit was last renewed. However, the requirements of this rule are only triggered at the time the source undergoes a modification. All applicable requirements from any NSR permit actions have already been incorporated into the current Title V permit. Therefore, the updated requirements of this rule are not applicable at this time.

C. District Rule 2410 – Prevention of Significant Deterioration

District Rule 2410 has been newly adopted since this Title V permit was last renewed. However, the requirements of this rule are only triggered at the time the source undergoes a modification. The requirements of this rule cannot be triggered by the renewal of a Title V permit, since permit renewal does not involve any construction or modification of the stationary source. Therefore, the newly adopted requirements of this rule are not applicable at this time.

D. District Rule 2520 – Federally Mandated Operating Permits

District Rule 2520 has not been amended since this Title V permit was last renewed. However, EPA has provided the District with comments on other Title V permits and indicated that the District was issuing permits without appropriate and practical recordkeeping requirements for annual emissions limitations. According to EPA policy, annual emission limits must be practically enforceable, which also goes on to say that to be practically enforceable, annual limits must be enforced on a short-term basis.

The District had previously committed to 12-month rolling recordkeeping to enforce annual limits in all Title V permits. In accordance with that committal, the District has developed conditions to address EPA's concerns regarding practically enforceable annual emission and throughput limits. Therefore, the following conditions have been modified and/or added to the permits at this facility.

Permits	Conditions
C-628-6-4	4 and 8
C-628-749-2	9 and 13
C-628-751-2	17 and 30
C-628-752-2	6 and 8

Greenhouse Gas Discussion

There are no federally applicable Greenhouse Gas (GHG) requirements for this source. It should be noted that the Mandatory Greenhouse Gas Reporting rule (40 CFR Part 98) is not included in the definition of an applicable requirement within Title V (per 40 CFR 71.2). Therefore, there will be no further discussion of GHG in this evaluation.

E. District Rule 4621 – Gasoline Transfer Into Stationary Storage Containers, Delivery Vessels, and Bulk Plants

The purpose of this rule is to limit VOC emissions from stationary storage containers, delivery vessels and bulk plants and to provide the administrative requirements for determining compliance with this rule. Therefore, the requirements of this rule apply to the gasoline dispensing operation under permit C-628-751-2.

Section 5.1 states that loading equipment and vapor collection equipment shall be installed, maintained, and operated such that it is leak-free, with no excess organic liquid drainage at disconnect.

Section 3.19.2 defines a leak as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration or total organic compound greater than 10,000 ppmv, as methane, above background when measured in accordance with the test method in Section 6.4.3. Any liquid or gas coming from a component undergoing repair or replacement, or during sampling of process fluid from a component or equipment into a container is not considered sampling of a leak provided such activities are accomplished as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere.

The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of these sections:

Permit	Conditions
C-628-751-2	5 and 6

Section 5.2.1 states that no person shall transfer, or permit the transfer, of gasoline from any delivery vessel into any stationary storage container subject to the requirements of this rule unless such container is equipped with an ARB certified permanent submerged fill pipe and utilizes an ARB certified Phase I vapor recovery system that is maintained and operated according to manufacturer specifications and the applicable ARB Executive Order.

In addition, ARB has the additional certification requirements, including applicable rules and regulations of the Division of Measurement Standards, the Department of Food and Agriculture, the Office of the State Fire Marshal, the Department of Forestry and Fire Protection, the Division of Occupational Safety and Health, the Department of Industrial Relations, and the Division of Water Quality of the State Water Resources Control Board that have been made conditions of the certification.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-628-751-2	1

Section 5.4.1 states that all aboveground storage containers shall be constructed and maintained in a leak-free condition.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-628-751-2	4

Section 5.4.3 specifies requirements for aboveground storage containers that contain aviation gasoline. This facility does not handle aviation gasoline. Therefore, the requirements of this section are not applicable.

Section 5.4.4 states that operators of an aboveground storage container not located at a bulk plant shall conduct and pass a "Static Leak Test" (reference Section 6.4.8) performance test to determine compliance at least once every 36 months, (no more than 30 days before or after the required performance test date) unless otherwise required under ARB Executive Order.

The following condition on the draft renewed permits is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-628-751-2	21

Section 5.5 states that all Phase I vapor recovery systems shall be inspected according to the frequency specified in Table 1. The person conducting the inspections shall, at a minimum, verify that the fill caps and vapor caps are not missing, damaged, or loose, that the fill cap gasket and vapor cap gaskets are not missing or damaged, that the fill adapter and vapor adapter are securely attached to the risers, that, where applicable, the spring-loaded submerged fill tube seals properly against the coaxial tubing, and the dry break (poppet-valve) is not missing or damaged and that the submerged fill tube is not missing or damaged.

The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of this section:

Permit	Conditions
C-628-751-2	11 and 12

Section 5.6 specifies requirements for bulk plants. This facility is not a bulk plant. Therefore, the requirements of this section are not applicable.

Section 5.7.2 states that no person shall operate, or allow the operation of a delivery vessel unless valid State of California decals which attest to the vapor integrity of the container are displayed.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-628-751-2	7

Section 6.1.4 states that all records required to demonstrate compliance with the requirements of this rule shall be retained on the premises for a minimum of five years and made available on site during normal business hours to the APCO, ARB, or EPA, and submitted to the APCO, ARB, or EPA upon request.

The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of this section:

Permit	Conditions
C-628-751-2	29 and 30

Section 6.2.3 states "Operators shall notify the District at least seven days prior to any performance testing."

Section 6.2.4 states "Operators shall submit all performance test results to the District within 30 days of test completion."

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-628-751-2	25

Section 6.3.1 states that installation and maintenance contractors shall be certified by the ICC for Vapor Recovery System Installation and Repair (VI) and make available onsite proof of ICC certification for VI, and have and make available on site proof of any and all certifications required by the Executive Order and installation and operation manual in order to install or maintain specific systems, or work under the direct and personal supervision of an individual physically present at the work site who possesses and makes available onsite a current certificate from the ICC, indicating he or she has passed the VI exam and all certifications required by the applicable Executive Order.

Section 6.3.2 states that All ICC certifications shall be renewed every 24 months by passing the appropriate exam specific to the certification being sought.

The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of these sections:

Permit	Conditions
C-628-751-2	23 and 24

Section 6.3.3 states that Gasoline Dispensing Facility Testers wishing to conduct vapor recovery system testing and repair at facilities located within the District, shall be in full compliance with District Rule 1177 (Gasoline Dispensing Facility Tester Certification).

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-628-751-2	22

F. District Rule 4622 – Gasoline Transfer Into Motor Vehicle Fuel Tanks

The purpose of this rule is to limit emissions of gasoline vapors from the transfer of gasoline into motor vehicle fuel tanks. This rule applies to any gasoline storage and dispensing operation or mobile fueler from which gasoline is transferred into motor vehicle fuel tanks. Therefore, the requirements of this rule apply to the gasoline dispensing operation under permit C-628-751-2.

Section 3.28 defines a retail gasoline outlet as an establishment at which gasoline is sold or offered for sale to the general public for use in motor vehicles. This facility does not sell gasoline to the general public.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-628-751-2	2

Section 5.1 states that a person shall not transfer or permit the transfer of gasoline from any stationary storage container, or from any mobile fueler with a capacity greater than 120 gallons, into a motor vehicle fuel tank with a capacity greater than 5 gallons, unless the gasoline dispensing unit used to transfer the gasoline is equipped with and has in operation an ARB certified Phase II vapor recovery system.

Section 5.1.1 states that all ARB certified Phase II vapor recovery systems shall be maintained according to ARB certifications and the manufacturer specifications applicable to the system. Since the facility operates this tank with an ARB certified Phase II vapor recovery system, requirements of this section are satisfied and compliance is expected.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-628-751-2	1

Section 5.1.2 states that all ARB certified Phase II vapor recovery systems and gasoline dispensing equipment shall be maintained without leaks as determined by EPA Test Method 21 (reference Section 6.5.4).

Section 3.17 defines a leak as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration or total organic compound greater than 10,000 ppmv, as methane, above background when measured in accordance with EPA Test Method 21. Any liquid or gas coming from a component undergoing repair or replacement, or during sampling of process fluid from a component or equipment into a container is not considered sampling of a leak provided such activities are accomplished as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere.

The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of these sections:

Permit	Conditions
C-628-751-2	5 and 6

Section 5.2.1 states that any gasoline dispensing system subject to this rule shall comply with the provisions of this rule at the time of installation. As shown in this evaluation, this gasoline dispensing operation is not being installed as a part of this project and is in compliance with the requirements of this rule. Therefore, the requirements of this section have been satisfied.

Section 5.2.2 states that operators shall have all underground storage container installations and all underground piping configurations inspected by the APCO prior to backfilling. This tank is an aboveground storage tank. Therefore, the requirements of this section are not applicable.

Section 5.2.3 states that installation and maintenance contractors shall, be certified by the ICC for Vapor Recovery System Installation and Repair by June 20, 2008, renew the ICC certification for Vapor Recovery System Installation and Repair every 24 months, make available onsite proof of ICC certification, and have and make available on site proof of any and all certifications required by the Executive Order and installation and operation manual in order to install or maintain specific systems.

Section 5.2.4 states "in lieu of complying with Sections 5.2.3.1 through 5.2.3.4, installation and maintenance contractors may work under the direct and personal supervision of an individual physically present at the work site who possesses and makes available on site current certifications from the ICC, indicating he or she has passed the ICC Vapor Recovery System Installation and Repair exam and all other certifications required by the applicable Executive Order."

The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of these sections:

Permit	Conditions
C-628-751-2	23 and 24

Section 5.2.5 states that notwithstanding any provisions of this rule, any gasoline dispensing operation which has installed and obtained a permit to operate an ARB certified Phase II vapor recovery system shall continue to use such system and shall maintain the system and all of its components in good-repair in order that such system can continue to comply with the certification recovery efficiency.

The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of this section:

Permit	Conditions
C-628-751-2	1 and 8

Section 5.2.6 states that any ARB certified Phase II vapor recovery system that has been installed shall not be removed regardless of the amount of gasoline dispensed or how the gasoline is delivered to the operation. Permit C-628-751 requires the above ground tank to be equipped with a Phase II vapor recovery system. In order to remove the system, Mission Bell Winery would be required to submit an Authority to Construct application to request that change to this operation and the District would fully evaluate their request under that application. Therefore, the requirements of this section have been satisfied.

Section 5.3.1 states that the owner or operator of an ARB certified Phase II vapor recovery system shall conduct periodic maintenance inspections to ensure that components of the vapor recovery system are in proper operating condition.

Section 5.3.2 states that the frequency of inspections shall be based on the operation's largest monthly gasoline throughput from the previous calendar year as indicated in Table 1.

Section 5.3.3 states that the frequency of vapor path inspections shall be based on the amount of gasoline dispensed by the operation in a calendar month as indicated in Table 1.

Section 5.3.4 states that the person conducting the inspections shall at a minimum, verify that the fueling instructions required by Section 5.5 are clearly displayed with the appropriate toll-free complaint phone number and toxic warning signs, that the following nozzle components are in place and in good condition as specified in ARB Executive Orders: faceplate/facecone, bellows, latching device spring, vapor check valve, spout (proper diameter/vapor collection holes), insertion interlock mechanism, automatic shut-off mechanism, hold open latch, that the hoses are not torn, flattened or crimped, that the vapor path of coaxial hoses associated with bellows equipped nozzles does not contain more than 100 ml of liquid and that the vapor processing unit is functioning properly, for operations that are required to have or possess such a unit.

The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of these sections:

Permit	Conditions
C-628-751-2	11 and 13

Section 5.4.1 states that no person shall operate any ARB certified Phase II vapor recovery system or any portion thereof that has a major defect or an equipment defect that is identified in any applicable ARB Executive Order, until: the defect has been repaired, replaced, or adjusted as necessary to correct the defect; the District has been notified, and the District has reinspected the system or authorized the system for use. Such authorization shall not include the authority to operate the equipment prior to the correction of the defective components; and all major defects, after repair, are duly entered into the Operations and Maintenance (O&M) manual.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-628-751-2	8

Section 5.4.2 states that upon identification of any major defects, the owner or operator shall tag "Out-of-Order" all dispensing equipment for which vapor recovery has been impaired.

Section 5.4.2.1 states that tagged equipment shall be rendered inoperable and the tag(s) shall not be removed until the defective equipment has been repaired, replaced, or adjusted, as necessary.

Section 5.4.2.2 states that in the case of defects identified by the District, tagged equipment shall be rendered inoperable, and the tag shall not be removed until the District has been notified of the repairs, and the District has either reinspected the system or authorized the tagged equipment for use.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of these sections:

Permit	Condition
C-628-751-2	9

Section 5.4.4 states that in the event of a separation due to a drive off, the owner or operator shall complete one of the following, unless otherwise specified in the applicable ARB Executive Order, and document the activities in accordance with Section 6.2, before placing the affected equipment back in service:

1) Conduct a visual inspection of the affected equipment, perform qualified repairs on any damaged components, and conduct applicable re-verification tests pursuant to Sections 6.5.1.1 and 6.5.1.4, or

2) Conduct a visual inspection of the affected equipment and replace the affected nozzles, coaxial hoses, breakaway couplings, and any other damaged components with new or certified rebuilt components that are ARB certified, before placing affected equipment back in service.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-628-751-2	14

Section 5.5 is applicable to retail gasoline outlets. The tank operated at this facility is not used as a retail gasoline outlet. Therefore, the requirements of this section are not applicable.

Section 5.6 states that no person shall top off a motor vehicle fuel tank.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-628-751-2	3

Sections 5.7 and 5.8 establish requirements for hold-open gasoline dispensing nozzle latches utilized for retail gasoline outlets. The tank operated at this facility is not used as a retail gasoline outlet. Therefore, the requirements of these sections are not applicable.

Section 5.9 states that no owner or operator shall tamper with, or permit tampering with, the system in a manner that would impair the operation of effectiveness of the system.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-628-751-2	1

Section 5.10 states that all liquid removal devices required by ARB Executive Order shall be maintained to achieve a minimum liquid removal rate of five milliliters per gallon. This standard shall apply at dispensing rates exceeding five gallons per minute, unless a higher removal rate is specified in the applicable Executive Order.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-628-751-2	20

Section 5.11 establishes requirements for mobile fuelers. The tank operated at this facility is not used as part of a mobile fueler. Therefore, the requirements of this section are not applicable.

Section 5.12 requires that vapor condensate traps shall be used, if necessary, to keep the vapor return piping clear of any liquid blockage from the remote dispenser to the aboveground storage tank or when it is not possible to achieve the necessary slope from the dispenser to the underground storage tank. The aboveground storage tank is not equipped with a liquid condensate trap. Therefore, the requirements of this section are not applicable.

Section 5.13 establishes requirements for in-station diagnostics (ISD) systems. ISD systems are not required for aboveground gasoline storage tanks. Therefore, the requirements of this section do not apply.

Section 6.1 specifies recordkeeping and reporting requirements for gasoline dispensing systems that are exempt from installing a Phase II vapor recovery system. This gasoline dispensing system is equipped with a Phase II vapor recovery system. Therefore, the requirements of this section do not apply.

Section 6.2.1 requires that operators shall retain the test result verification that each ARB certified Phase II vapor recovery system meets or exceeds the requirements of the tests specified in Section 6.5. These verifications shall be maintained for at least five years. These test results shall be dated and shall contain the names, addresses, and telephone numbers of the companies responsible for system installation and testing.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-628-751-2	26

Section 6.2.2 requires a person who performs repairs on any ARB certified Phase I or Phase II vapor recovery system shall provide to the owner or operator a repair log, which the owner or operator shall maintain on the premises for at least five years and which shall include all of the following:

1) Date and time of each repair;

2) The name and applicable certification numbers of the person(s) who performed the repair, and, if applicable, the name, address and phone number of the person's employer;

3) Description of service performed;

4) Each component that was repaired, serviced, or removed;

5) Each component that was installed as replacement, if applicable;

6) Receipts or other documents for parts used in the repair and, if applicable, work orders which shall include the name and signature of the person responsible for performing the repairs.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-628-751-2	27

Section 6.2.3 requires each operator who is required to perform periodic maintenance inspections under Section 5.3 shall maintain monthly gasoline throughput records on the premises for a minimum of five years, make them available on site during normal business hours to the APCO, ARB, or EPA, and submit them to the APCO, ARB, or EPA upon request.

The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of this section:

Permit	Conditions
C-628-751-2	29 and 30

Section 6.3.1 requires that the owner or operator of a gasoline dispensing operation shall maintain an O&M Manual in accordance with Section 6.3.

Section 6.3.2 requires that the O&M manual shall be kept at the dispensing operation and made available to any person who operates, inspects, maintains, repairs, or tests the equipment at the operation as well as to District personnel upon request.

Section 6.3.3 requires that the O&M manual shall, at a minimum, include the following current information:

1) copies of all vapor recovery performance tests,

2) all applicable ARB Executive Orders, Approval Letters, and District Permits,

3) manufacturer's specifications and instructions for installation, operation, repair, and maintenance required pursuant to ARB Certification Procedure CP-201, and any additional instruction provided by the manufacturer,

4) system and/or component testing requirements, including test schedules and passing criteria for each of the standard tests listed in Section 6.0. The owner/operator may include any non-ARB required diagnostic and other tests as part of the testing requirements, and

5) additional O&M instructions, if any, that are designed to ensure compliance with the applicable rules, regulations, ARB Executive Orders, and District permit conditions, including replacement schedules for failure or wear prone components.

Section 6.3.4 requires owners or operators of gasoline dispensing operations shall document the periodic maintenance inspection program in the O&M manual.

The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of these sections:

Permit	Conditions
C-628-751-2	10 and 28

Section 6.4.1 requires that operators shall comply with the ARB certified Phase II vapor recovery system performance tests specified in Sections 6.4.1.1 through 6.4.1.4 and shall conduct all applicable performance tests at start up and thereafter (no more than 30 days before or after the required compliance testing date) as required by ARB Executive Order and installation and operation manuals.

Section 6.4.1.1 requires that an operator shall conduct and pass a Static Leak Test of the ARB certified Phase II vapor recovery system at least once every twelve months.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-628-751-2	22

Section 6.4.1.2 requires that an operator shall conduct and pass a Dynamic Back-Pressure Test of the ARB certified Phase II vapor recovery system at least once every twelve months except for those aboveground storage tanks that have integral dispensers (non-remote), unless otherwise required under ARB Executive Order. All balance Phase II systems require integral dispensers (top or side mounted). The only balance system that allows a non-integral dispenser is Petro Vault (G-70-130-A) and the maximum distance of the dispenser from the base of the tank is 2 feet which is not considered a remote dispenser. Therefore, balance Phase II systems cannot have a remote dispenser and thus no Dynamic Back-Pressure Test is required for balance Phase II systems.

Section 6.4.1.3 requires that for ARB certified Phase II vapor recovery systems with bellows-less nozzles, conduct and pass, as applicable, an Air-to-Liquid Volume Ratio Test or a Vapor-to-Liquid Ratio Test at least once every six months. This gasoline dispensing system is not equipped with bellows-less nozzles. Therefore, the requirements of this section are not applicable.

Section 6.4.1.4 requires that for ARB certified Phase II vapor recovery systems with a liquid removal device required by ARB Executive Orders, conduct and pass a Liquid Removal Test whenever the liquid in the vapor path exceeds 100 ml of liquid. The amount of liquid in the vapor path shall be determined in accordance with the procedure specified in Section 5.3.5.4. This gasoline dispensing system is not equipped with a liquid removal device. Therefore, the requirements of this section are not applicable.

Section 6.4.2 requires that the person responsible for conducting the tests specified in Section 6.4 shall use calibrated equipment meeting the calibration range and calibration intervals specified by the manufacturer, ARB Executive Order, or ARB test procedure.

Section 6.4.3 requires that each person responsible for conducting tests specified in Section 6.5 shall be in full compliance with all provisions of Rule 1177 (Gasoline Dispensing Facility Tester Certification).

Section 6.4.4 requires that each gasoline dispensing operation shall notify the District at least seven days prior to any performance testing.

Section 6.4.5 requires that each ARB certified Phase II vapor recovery system shall be tested within 60 days of completion of installation or modification.

The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of these sections:

Permit	Conditions
C-628-751-2	19, 24 and 25

Section 6.5.1 requires that tests shall be conducted in accordance with the latest version of the following ARB and EPA approved test methods, or their equivalents as approved by the EPA, and the APCO.

Section 6.5.1.2 requires that Dynamic Back-Pressure Test be conducted using ARB method TP-201.4.

Section 6.5.1.3 requires that Air-to-Liquid Volume Ratio Test be conducted using ARB method TP-201.5.
Section 6.5.1.4 requires that Liquid Removal Test be conducted using ARB method TP-201.6C.

Section 6.5.1.5 requires that Static Leak Test for Aboveground Tanks be conducted using ARB method TP-206.3 or TP-201.3B, as applicable.

The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of these sections:

Permit	Conditions
C-628-751-2	20 and 21

G. District Rule 4694 – Wine Fermentation and Storage Tanks

The purpose of this rule is to reduce emissions of volatile organic compounds (VOC) from the fermentation and bulk storage of wine, or achieve equivalent reductions from alternative emission sources.

This rule applies to any winery fermenting wine and/or storing wine in bulk containers. Therefore, the requirements of this rule apply to all of the wine fermentation and/or storage tanks permitted at this facility.

The requirements of Rule 4694 have not been amended since the last time the Title V permit for this facility was renewed. However, during the review of the permit requirements, the following changes were made to the permits for tanks constructed solely of concrete and tanks with a capacity of less than 5,000 gallons.

Concrete Tanks:

In accordance with the exemption requirements of Section 4.2, Section 5.2 shall not apply to storage tanks constructed primarily of concrete. Therefore, the wine storage tank requirements of Section 5.2 do not apply to the concrete tanks under permits C-628-71-3, '-72-3, and '-136-3 through '-171-3 at this facility. Since these tanks are constructed of concrete, there are no recordkeeping requirements that the facility needs to maintain to verify they are complying with the exemption of Section 4.2.

Therefore, the following recordkeeping condition was removed from each of the permits for the concrete tanks at this facility and will not be included as a part of the draft renewed permits.

- *Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694] N*

Tanks with a Capacity of Less Than 5,000 Gallons:

All of the tanks permitted at this facility are authorized for wine fermentation and wine storage. In accordance with Section 5.2, the storage tank requirements of Rule 4694 do not apply to tanks that have an internal volume equal to or less than 5,000 gallons. However, the fermentation requirements of Section 5.1 still apply to these tanks.

The fermentation requirements of Section 5.1 were not included on the permits for the tanks rated at less than 5,000 gallons at this facility. Therefore, the following condition on the draft renewed permits was added and included as a mechanism to ensure compliance with the requirements of this section:

- *For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694] N*

H. District Rule 4702 – Internal Combustion Engines

The purpose of this rule is to limit the emissions of nitrogen oxides (NOx), carbon monoxide (CO), volatile organic compounds (VOC), and sulfur oxides (SOx) from internal combustion engines.

This rule applies to any internal combustion engine rated at 25 brake horsepower or greater. Therefore, the requirements of this rule apply to the 465 bhp natural gas-fired IC engine operating under permit C-628-3-8, the 186 bhp diesel-fired emergency IC engine operating under permit C-628-6-4, and the 225 bhp (re-rated to 121.7 bhp) LPG/propane-fired emergency IC engine operating under permit C-628-749-2.

C-628-3-8 (465 bhp natural gas-fired IC engine powering an electrical generator – currently in compliant dormant emission unit status):

Section 5.1 establishes requirements for engines rated between 25 bhp and 50 bhp. This IC engine operated is rated at 465 bhp. Therefore, the requirements of this section are not applicable to this engine.

Section 5.2 establishes emission requirements for engines rated at greater than 50 bhp. Section 5.2.1 establishes the emission limits for spark ignited engines used in non-Agricultural Operations (AO).

Emission Limits/Standards for a Spark-Ignited Internal Combustion Engine rated at >50 bhp Used Exclusively in Non-AO (All ppmv limits are corrected to 15% oxygen on a dry basis.)			
Engine Type	NOx	CO	VOC
Rich-Burn			
c. All other engines	25 ppmv or 96% reduction	2000 ppmv	250 ppmv

This engine is a rich-burn spark-ignited IC engine. The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of this section:

Permit	Conditions
C-628-3-8	7 and 11

Section 5.3 specifies requirements for units equipped with continuous emission monitoring systems (CEMS). This engine is not equipped with a CEMS. Therefore, the requirements of this section are not applicable.

Sections 5.4 and 5.5 specify requirements for engines that utilize the percent emission reduction option to comply with the NO_x emission requirements of Section 5.2. This engine does not utilize the percent emission reduction option to comply with the NO_x emission requirements of Section 5.2. Therefore, the requirements of these sections are not applicable.

Section 5.6 specifies requirements for operators that elect to pay an annual fee in lieu of complying with the NO_x emission limits specified in this rule. This engine complies with the NO_x emission limits specified in the rule. Therefore, the annual fee payment requirements of this section are not applicable.

Section 5.7 specifies emission control requirements for sulfur oxides (SOx). Operators of non-agricultural operation (AO) spark-ignited engines and non-AO compression ignited engines shall comply with one of the following:

5.7.1 Operate the engine exclusively on PUC-quality natural gas, commercial propane, butane, or liquefied petroleum gas, or a combination of such gases; or
5.7.2 Limit gaseous fuel sulfur content to no more than five (5) grains of total sulfur per one hundred (100) standard cubic feet; or
5.7.3 Use California Reformulated Gasoline for gasoline-fired spark-ignited engines; or
5.7.4. Use California Reformulated Diesel for compression-ignited engines; or
5.7.5 Operate the engine on liquid fuel that contains no more than 15 ppm sulfur, as determined by the test method specified in Section 6.4.6; or
5.7.6 Install and properly operate an emission control system that reduces SOx emissions by at least 95% by weight, as determined by the test method specified in Section 6.4.6.

This engine is operated only on PUC regulated natural gas. The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirement of this section:

Permit	Condition
C-628-3-8	7

Section 5.8 specifies monitoring requirements for non-AO spark-ignited engines and any engine subject to the alternative emission control plan (AECP) requirements of Section 8.0. This engine is a spark-ignited engine that is not used as part of an AO. Therefore, the requirements of this section are applicable to this engine.

Section 5.8.1 requires the operator with an engine equipped with an external control device to either install, operate, and maintain continuous monitoring equipment (CEMs) for NOx, CO, and oxygen, as identified in Rule 1080 (Stack Monitoring), or install, operate, and maintain APCO-approved alternate monitoring consisting of one or more of the following:

- Periodic NO_x and CO emission concentrations,
- Engine exhaust oxygen concentration,
- Air-to-fuel ratio,
- Flow rate of reducing agents added to engine exhaust,
- Catalyst inlet and exhaust temperature,
- Catalyst inlet and exhaust oxygen concentration,
- Other operational characteristics.

While in operation, this engine is required to periodically measure NO_x and CO emissions concentrations at least once per month. The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirement of this section:

Permit	Conditions
C-628-3-8	22, 23, and 24

Section 5.8.2 establishes monitoring requirements for all other engines that are not subject to Section 5.8.1 above. As shown above, this engine is subject to the monitoring requirements of Section 5.8.1 above; therefore, the requirements of Section 5.8.2 are not applicable.

Section 5.8.3 requires that for each engine with an alternative monitoring system, submit to, and receive approval from the APCO, adequate verification of the alternative monitoring system's acceptability. This engine utilizes a pre-approved alternate emissions monitoring plan that specifies that the permittee perform periodic NO_x, CO, and O_2 emissions concentrations as specified in District Policy SSP-1810. Therefore, the requirements of this section are satisfied.

Section 5.8.4 specifies requirements for engines equipped with an APCO approved CEMS. This engine is not equipped with a CEMS, therefore, the requirements of this section are not applicable.

Section 5.8.5 requires that the APCO approve the data gathering and retrieval capabilities of an installed monitoring system. This engine is not using an installed monitoring system with a data gathering system. Therefore, the requirements of this section are not applicable.

Section 5.8.6 requires an engine operator to install and operate a nonresettable elapsed time meter. In lieu of installing a nonresettable time meter, the owner or operator may use an alternative device, method, or technique in determining operating time provided that the alternative is approved by the APCO and is allowed by Permit-to-Operate or Stationary Equipment Registration condition. The owner of the engine shall properly maintain and operate the time meter or alternative device in accordance with the manufacturer's instructions.

The following condition on the draft renewed permit are a mechanism to ensure compliance with the requirements of these sections:

Permit	Condition
C-628-3-8	8

Section 5.8.7 requires that for each engine, the permittee implement the Inspection and Monitoring (I&M) plan, if any, submitted to and approved by the APCO pursuant to Section 6.5.

The following condition on the draft renewed permit are a mechanism to ensure compliance with the requirements of these sections:

Permit	Condition
C-628-3-8	9

Section 5.8.8 requires that for each engine, collect data through the I & M plan in a form approved by the APCO. This facility is required to maintain records of their alternate monitoring and source test results. In addition, they are also required to track and maintenance or modifications performed on the engine. The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of these sections:

Permit	Conditions
C-628-3-8	25 and 27

Section 5.8.9 requires that a portable NO_x analyzer be used to take NO_x emission readings to verify compliance with the emission requirements of Section 5.2 during each calendar quarter in which a source test is not performed and the engine is operated.

The following condition on the draft renewed permit are a mechanism to ensure compliance with the requirements of these sections:

Permit	Condition
C-628-3-8	22

Section 5.8.10 requires that the APCO shall not approve an alternative monitoring system unless it is documented that continued operation within ranges of specified emissions-related performance indicators or operational characteristics provides a reasonable assurance of compliance with applicable emission limits. The operator shall source test over the proposed range of surrogate operating parameters to demonstrate compliance with the applicable emission standards. This engine follows a pre-approved alternate monitoring scheme where the NO_X, CO and O_2 levels are directly measured using a District approved portable analyzer at least once per month the engine operates. This alternate monitoring scheme does not require a range to be established for specific emissions-related performance indicators to be established. Therefore, the requirements of this section are not applicable.

Section 5.8.11 specifies requirements for engines that are subject to Section 8.0 (compliance for engine groupings). This facility only operates one full time engine and not subject to the requirements of Section 8.0. Therefore, the requirements of this section are not applicable.

Section 5.9 establishes monitoring requirements for all other engines that are not subject to Section 5.8 above. As shown above, this engine is subject to the monitoring requirements of Section 5.8 above; therefore, the requirements of Section 5.9 are not applicable.

Section 6.1 establishes requirements for emission control plans for each engine. The engine in this project is already subject to, and complying with, the requirements of this rule. Therefore, the emission control plan requirements are not applicable at this time.

Section 6.2 requires that the owner of an engine subject to the requirements of Section 5.2 shall maintain an engine operating log to demonstrate compliance with this rule. This information shall be retained for a period of at least five years, shall be readily available, and be made available to the APCO upon request. The engine-operating log shall include, on a monthly basis, the following information:

- Total hours of operation,
- Type of fuel used,
- Maintenance or modifications performed,
- Monitoring data,
- Compliance source test results, and
- Any other information necessary to demonstrate compliance with this rule.

The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of this section:

Permit	Conditions
C-628-3-8	25, 27, and 43

Section 6.3 establishes the source testing requirements. Engines retrofitted with exhaust control devices must comply with Sections 6.3.2 through 6.3.4

6.3.2 requires that engines demonstrate compliance with the applicable limits, ppmv or percent reduction, in accordance with the test methods in Section 6.4, as specified below:

6.3.2.1 At least once every 24 months, except for an engine subject to Section 6.3.2.2.
6.3.2.2 At least once every 60 months, for an AO spark-ignited engine that has been retro-fitted with a catalytic emission control device.
6.3.2.3 A portable NO_x analyzer may be used to show initial compliance with the applicable limits/standards in Section 5.2 for AO spark-ignited engines, provided the criteria specified in Sections 6.3.2.3.1 to 6.3.2.3.5 are met, and a source test is conducted in accordance with Section 6.3.2 within 12 months from the required compliance date.

This engine is spark-ignited and is not used as a part of an AO operation. The following condition on the draft renewed permit are a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-628-3-8	13

Section 6.3.3 requires that emissions source testing be conducted with the engine operating either at conditions representative of normal operations or conditions specified in the permit. For emissions source testing performed pursuant to Section 6.3.2 for the purpose of determining compliance with an applicable standard or numerical limitation, the arithmetic average of three (3) 30-consecutive-minute test runs shall apply. If two (2) of three (3) runs are above an applicable limit, the test cannot be used to demonstrate compliance with an applicable limit. VOC shall be reported as methane. VOC, NO_x, and CO concentrations shall be reported in ppm, corrected to 15 percent oxygen. For engines that comply with a percent reduction limit, the percent reduction of NO_x emissions shall also be reported.

The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of this section:

Permit	Conditions
C-628-3-8	14 and 15

Section 6.3.4 requires that in addition to other information, the source test protocol shall describe what critical parameters will be measured and how the appropriate range of these parameters shall be established. The range for these parameters shall be incorporated into the I & M plan. As discussed above, this engine is not following an alternate monitoring scheme which requires parameters to be established during the source test. Therefore, the requirements of this section are not applicable.

Section 6.3.5 states that engines that are limited by permit condition to be fueled exclusively with PUC quality natural gas shall not be subject to the reoccurring source test requirements of Section 6.3.2 for VOC emissions. This engine is required to fired solely on PUC regulated natural gas. Therefore, the engine is not subject to the reoccurring source test requirements for VOC emissions. The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of this section:

Permit	Conditions
C-628-3-8	7 and 13

Section 6.3.6 specifies requirements for representative source testing of groups of identical engines. This facility only operates one engine. Therefore, the requirements of this section are not applicable.

Section 6.4 requires that the compliance with the requirements of Section 5.2 shall be determined in accordance with the following test procedures or any other method approved by EPA and the APCO:

- Oxides of nitrogen - EPA Method 7E, or ARB Method 100.
- Carbon monoxide - EPA Method 10, or ARB Method 100.
- Stack gas oxygen - EPA Method 3 or 3A, or ARB Method 100.
- Volatile organic compounds - EPA Method 25A or 25B, or ARB Method 100. Methane and ethane, which are exempt compounds, shall be excluded from the result of the test.
- Operating horsepower determination - any method approved by EPA and the APCO.
- Oxides of sulfur – EPA Method 6C or 8, or ARB Method 100.

The following condition on the draft renewed permit are a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-628-3-8	16

Section 6.5 requires that the operator of an engine subject to the requirements of Section 5.2 or the requirements of Section 8.0 shall submit to the APCO for approval an I&M plan that specifies all actions to be taken to satisfy the following requirements and the requirements of Section 5.8. This engine has an existing I & M plan that was approved by the District. The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of these sections:

Permit	Conditions
C-628-3-8	9 and 10

C-628-6-4 (emergency IC engine powering a firewater pump):

Pursuant to Section 4.3, except for the requirements of Section 6.2.3, the requirements of this rule shall not apply to an internal combustion engine that meets the following conditions:

1) The engine is operated exclusively to preserve or protect property, human life, or public health during a disaster or state of emergency, such as a fire or flood, and

2) Except for operations associated with Section 4.3.1.1, the engine is limited to operate no more than 100 hours per calendar year as determined by an operational nonresettable elapsed operating time meter, for periodic maintenance, periodic readiness testing, and readiness testing during and after repair work of the engine, and

3) The engine is operated with a nonresettable elapsed operating time meter. In lieu of installing a nonresettable time meter, the owner of an engine may use an alternative device, method, or technique, in determining operating time provided that the alternative is approved by the APCO. The owner of the engine shall properly maintain and operate the time meter or alternative device in accordance with the manufacturer's instructions.

Section 6.2.3 requires that an owner claiming an exemption under Section 4.2 or Section 4.3 shall maintain annual operating records. This information shall be retained for at least five years, shall be readily available, and submitted to the APCO upon request and at the end of each calendar year in a manner and form approved by the APCO. The records shall include, but are not limited to, the following:

- Total hours of operation,
- The type of fuel used,
- The purpose for operating the engine,
- For emergency standby engines, all hours of non-emergency and emergency operation shall be reported, and
- Other support documentation necessary to demonstrate claim to the exemption.

The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of these sections.

Permit	Conditions
C-628-6-4	3, 4, 5, 6, 7, and 16

C-628-749-2 (emergency standby IC engine powering an electrical generator):

Pursuant to Section 4.2, except for the requirements of Sections 5.9 and 6.2.3, the requirements of this rule shall not apply to an emergency standby engine or a low-use engine, provided that the engine is operated with an operating nonresettable elapsed time meter.

Section 5.9 requires the owner to:

- Properly operate and maintain each engine as recommended by the engine manufacturer or emission control system supplier.

- Monitor the operational characteristics of each engine as recommended by the engine manufacturer or emission control system supplier.
- Install and operate a nonresettable elapsed operating time meter. In lieu of installing a nonresettable time meter, the owner of an engine may use an alternative device, method, or technique, in determining operating time provided that the alternative is approved by the APCO and is allowed by Permit-to-Operate or Permit-Exempt Equipment Registration condition. The owner of the engine shall properly maintain and operate the time meter or alternative device in accordance with the manufacturer's instructions.

Section 6.2.3 requires that an owner claiming an exemption under Section 4.2 or Section 4.3 shall maintain annual operating records. This information shall be retained for at least five years, shall be readily available, and submitted to the APCO upon request and at the end of each calendar year in a manner and form approved by the APCO. The records shall include, but are not limited to, the following:

- Total hours of operation,
- The type of fuel used,
- The purpose for operating the engine,
- For emergency standby engines, all hours of non-emergency and emergency operation shall be reported, and
- Other support documentation necessary to demonstrate claim to the exemption.

The following conditions on the draft renewed permit are a mechanism to ensure compliance with the requirements of these sections.

Permit	Conditions
C-628-749-2	3, 5, 8, 9, 10, 11, 12, and 14

I. 40 CFR Part 60, Subpart Dc– Standards of Performance for Small Industrial-Commercial-Institutional Steam Generating Units

This subpart establishes requirements for steam generating units that have a heat input capacity of less than 100 MMBtu/hr and that commenced construction, modification, or reconstruction after June 9, 1989. The facility has two 97 MMBtu/hr boilers operating under permits C-628-4-10 and '-5-10 and one 44.0 MMBtu/hr boiler operating under permit C-628-13-7. All three of these boilers were constructed and/or modified after June 9, 1989. Therefore, the requirements of this subpart apply to these three boilers. Since the time that these permits were last modified, some sections of this subpart have been amended. However, the sections which were amended do not affect any of the conditions on these permits. Therefore, a full breakdown of the requirements of this subpart will not be included in this evaluation.

The following conditions were taken from the current permits for these boilers and will be included on the renewed permits as a mechanism to ensure continued compliance with the requirements of this subpart.

Permit	Conditions
C-628-4-11 and '-5-11	20 and 21
C-628-13-8	20 and 21

J. 40 CFR Part 60, Subpart ZZZZ – National Emissions Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines

This subpart establishes national emission limitations and operating limitations for hazardous air pollutants (HAP) emitted from stationary reciprocating internal combustion engines (RICE) located at major and area sources of HAP emissions. This subpart also establishes requirements to demonstrate initial and continuous compliance with the emission limitations and operating limitations. The 465 bhp natural gas-fired emergency engine powering an electrical generator operating under permit C-628-3-8 and the 186 bhp diesel-fired emergency IC engine powering a firewater pump are the only units subject to the requirements of this subpart at this facility. Since the time that the permit was last modified, some sections of this subpart have been amended. However, the sections which were amended do not affect any of the conditions on these two permits. Therefore, a full breakdown of the requirements of this subpart will not be included in this evaluation.

The following conditions were taken from the current permits for these two IC engines and have been included on the draft renewed permits as a mechanism to ensure continued compliance with the requirements of this subpart.

Permit	Conditions
C-628-3-8	35 through 43
C-628-6-4	3, 4, and 11 through 16

K. 40 CFR Part 64 - CAM

§64.2 – Applicability

This section requires Compliance Assurance Monitoring (CAM) for units that meet the following three criteria:

1) the unit must have an emission limit for the pollutant;
2) the unit must have add-on controls for the pollutant; these are devices such as flue gas recirculation (FGR), baghouses, and catalytic oxidizers; and
3) the unit must have a pre-control potential to emit of greater than the major source thresholds.

Pollutant	Major Source Threshold (lb/year)
VOC	20,000
NO_X	20,000
CO	200,000
PM_{10}	140,000
SO_X	140,000

a. C-628-3 – 465 bhp Natural Gas-Fired IC Engine

During the last Title V permit renewal performed for this facility under project C-1092630, it was determined that this engine was subject to CAM requirements for NO_X and VOC emissions. The engine has not been modified since the previous Title V renewal project was finalized on December 22, 2011. Therefore, this unit will continue to be subject to the CAM requirements of 40 CFR 64 for NO_X and VOC emissions. The following conditions were taken from the current permit for this IC engine and will be included on the draft renewed permit as a mechanism to ensure continued compliance with the requirements of this subpart.

Permit	Conditions
C-628-3-8	31 through 35

b. C-628-4 and '-5 – 97 MMBtu/hr Natural Gas-Fired Boilers

The permits for these boilers contains emission limits for NO_X, CO, VOC, PM_{10} and SO_X emissions. However, each of these boilers are only equipped with a low NO_X burner and are not equipped with any add on control devices for NO_X, CO, VOC, PM_{10} or SO_X emissions. Therefore, the CAM requirements of 40 CFR 64 are not applicable and no further discussion is required.

c. C-628-6 – 186 bhp Diesel-Fired Emergency IC Engine

This emergency IC engine generates NO_X, CO, VOC, PM_{10} and SO_X emissions. The permit contains emission limits for all of these pollutants. However, the engine is not equipped with any add on emission control devices. Therefore, the CAM requirements of 40 CFR 64 are not applicable to this unit and no further discussion is required.

d. C-628-12 – Diatomaceous Earth Storage Silo and Four Mixing Tanks all Served by Dust Collectors

The permit for this storage silo does not contain emission limitations for any pollutant. Therefore, the CAM requirements of 40 CFR 64 are not applicable and no further discussion is required.

e. C-628-4 – 44 MMBtu/hr Natural Gas-Fired Boiler

The permit for this boiler contains emission limits for NO_X, CO, VOC, PM_{10} and SO_X emissions. However, this boiler is only equipped with a low NO_X burner and is not equipped with any add on control devices for NO_X, CO, VOC, PM_{10} or SO_X emissions. Therefore, the CAM requirements of 40 CFR 64 are not applicable and no further discussion is required.

f. C-628-15 through '-478 – Wine Fermentation and Storage Tanks

These wine fermentation and/or storage tanks are not equipped with any add-on control equipment. Therefore, the CAM requirements of 40 CFR 64 are not applicable to these units and no further discussion is required.

g. C-628-749 – 225 bhp LPG/Propane-Fired Emergency Standby IC Engine

The permit for this emergency IC engine contains emission limits for NO_X, CO, VOC, and PM_{10} emissions. However, this engine is not equipped with any add on control devices for PM_{10} emissions. Therefore, the CAM requirements of 40 CFR 64 are not applicable for PM_{10} and no further discussion is required.

This engine is equipped with a non-selective catalytic reduction (NSCR) system for NO_X, CO, and VOC emission control. Typically, the District assumes that an NSCR system will achieve 90% control for the NO_X emissions, 80% control for CO emissions, and 50% control for VOC emissions. Therefore, the uncontrolled emission rates from this emergency IC engine can be determined using the horsepower rating, the controlled emission factors listed on the permit, the control efficiency of the NSCR system, and a worst case non-emergency operating scenario of 100 hours/year.

NO_X Emissions:

Emission Factor = 0.52 g/bhp-hr
Heat Input Rating = 121.7 bhp
NSCR Control Efficiency = 90%

Annual Uncontrolled PE = [0.52 g/bhp-hr x 121.7 bhp x 100 hours/year x 1 lb/453.6 g] / (1 – 0.90)]

Annual Uncontrolled NO_X PE = 140 lb/year

CO Emissions:

Emission Factor = 3.14 g/bhp-hr
Heat Input Rating = 121.7 bhp
NSCR Control Efficiency = 80%

Annual Uncontrolled PE = [3.14 g/bhp-hr x 121.7 bhp x 100 hours/year x 1 lb/453.6 g] / (1 – 0.80)]

Annual Uncontrolled CO PE = 421 lb/year

VOC Emissions:

Emission Factor = 0.032 g/bhp-hr
Heat Input Rating = 121.7 bhp

Annual Uncontrolled PE = [0.032 g/bhp-hr x 121.7 bhp x 100 hours/year x 1 lb/453.6 g] / (1 – 0.50)]

Annual Uncontrolled VOC PE = 2 lb/year

As shown above, the uncontrolled PE for NO_X, CO, and VOC emissions is less than the major source threshold for each pollutant. Therefore, the CAM requirements of 40 CFR 64 are not applicable for these pollutants and no further discussion is required.

h. C-628-751 – Gasoline Dispensing Operation with 500 Gallon Aboveground Storage Tank

The permit for this gasoline dispensing operation contains an emission limit for VOC emissions. This gasoline dispensing operation is equipped with a phase I and phase II vapor recovery system for VOC emission control. Typically the District assumes that phase I and phase II vapor recovery systems can achieve up to 95% control for the VOC emissions, Therefore, the uncontrolled emission rates from this gasoline dispensing operation can be determined using the controlled emission limit factors listed on the permit, the control efficiency of the phase I and phase II vapor recovery systems, and the annual throughput limit specified in the permit.

VOC Emissions:

Total Emission Factor = 1.366 lb-VOC/1,000 gallons
Throughput = 18,000 gallons/year
Control Efficiency = 95%

Annual Uncontrolled PE = [1.366 lb-VOC/1,000 gallons x 18,000 gallons/yr / (1 – 0.95)]

Annual Uncontrolled VOC PE = 492 lb-VOC/year

As shown above, the uncontrolled PE for VOC emissions is less than the major source threshold. Therefore, the CAM requirements of 40 CFR 64 are not applicable for these pollutants and no further discussion is required.

i. C-628-752 – Grape Seed Drying Operation with 7.3 MMBtu/hr Burner System

The permits for this grape seed dryer contains emission limits for NO_X, CO, VOC, PM_{10} and SO_X emissions. However, this grape seed dryer is not equipped with any add on control devices for NO_X, CO, VOC, PM_{10} or SO_X emissions. Therefore, the CAM requirements of 40 CFR 64 are not applicable and no further discussion is required.

L. 40 CFR Part 82, Subpart B – Servicing of Motor Vehicle Air Conditioners

The purpose of 40 CFR Part 82 Subpart B is to implement section 609 of the Clean Air Act, as amended regarding the servicing of motor vehicle air conditioners (MVACs), and to implement section 608 of the Clean Air Act regarding certain servicing, maintenance, repair and disposal of air conditioners in MVACs and MVAC-like appliances.

These regulations apply to any person performing service on a motor vehicle for consideration when this service involves the refrigerant in the motor vehicle air conditioner.

The amendments to this rule do not have any effect on current permit requirements and will therefore not be addressed further in this evaluation.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-628-0-3	28

M. 40 CFR Part 82, Subpart F – Recycling and Emissions Reductions

The purpose of 40 CFR Part 82 Subpart F is to reduce emissions of class I and class II refrigerants and their substitutes to the lowest achievable level by maximizing the recapture and recycling of such refrigerants during the service, maintenance, repair, and disposal of appliances and restricting the sale of refrigerants consisting in whole or in part of a class I and class II ODS in accordance with Title VI of the Clean Air Act.

These regulations apply to any person servicing, maintaining, or repairing appliances. This subpart also applies to persons disposing of appliances, including small appliances and motor vehicle air conditioners. In addition, this subpart applies to refrigerant reclaimers, technician certifying programs, appliance owners and operators, manufacturers of appliances, manufacturers of recycling and recovery equipment, approved recycling and recovery equipment testing organizations, persons selling class I or class II refrigerants or offering class I or class II refrigerants for sale, and persons purchasing class I or class II refrigerants.

The amendments to this rule do not have any effect on current permit requirements and will therefore not be addressed further in this evaluation.

The following condition on the draft renewed permit is a mechanism to ensure compliance with the requirements of this section:

Permit	Condition
C-628-0-3	27

IX. PERMIT SHIELD

A permit shield legally protects a facility from enforcement of the shielded regulations when a source is in compliance with the terms and conditions of the Title V permit. Compliance with the terms and conditions of the Operating Permit is considered compliance with all applicable requirements upon which those conditions are based, including those that have been subsumed.

A. Requirements Addressed by Model General Permit Templates

The applicant is not requesting to use any model general permit templates for this Title V renewal project.

B. Requirements not Addressed by Model General Permit Templates

CBUS Ops dba Mission Bell Winery is not requesting any new permit shields within this Title V renewal project. In addition, CBUS Ops dba Mission Bell Winery is not requesting any changes to the existing permit shields already included in their Title V operating permit. Therefore, all of the existing permit shields will be maintained on the revised permit for this renewal project.

X. CALIFORNIA ENVIRONMENTAL QUALITY ACT

The purpose of the Title V permit renewal is to update the permit to ensure that any changes to regulations since the issuance of the initial Title V permit or most recent renewal of the Title V permit are incorporated as permit requirements.

Per the California Environmental Quality Act (CEQA) Statute §21080.24, and CEQA Guidelines §15281, the issuance, modification, amendment, or renewal of any permit by an air pollution control district or air quality management district pursuant to Title V is exempt from CEQA, unless the issuance, modification, amendment, or renewal authorizes a physical or operational change to a source or facility. There will be no physical or operational change to the source or facility nor will the Title V permit renewal authorize a physical or operational change to the source or facility. Therefore, this project, a Title V permit renewal, is subject to a ministerial action that is exempt from CEQA.

XI. PERMIT CONDITIONS

See Attachment A – Draft Renewed Title V Operating Permit

ATTACHMENTS

A. Draft Renewed Title V Operating Permit
B. Previous Title V Operating Permit
C. Detailed Summary List of Facility Permits

ATTACHMENT A

Draft Renewed Title V Operating Permit

San Joaquin Valley
Air Pollution Control District

FACILITY: C-628-0-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

FACILITY-WIDE REQUIREMENTS

1. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1 and Madera County Rule 113] Federally Enforceable Through Title V Permit
2. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0 and Madera County Rule 113] Federally Enforceable Through Title V Permit
3. {4364} The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (8/18/11). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. {4366} The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.13.1] Federally Enforceable Through Title V Permit
6. {4367} A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. {4368} Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. {4369} The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. {4370} The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

10. {4371} The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

11. {4372} Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

12. {4373} If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

13. {4374} It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

14. {4375} The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

15. {4376} The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

16. {4377} The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

17. {4378} The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

18. {4379} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

19. {4380} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

20. {4381} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

21. {4382} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

22. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

23. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in Table of Standards of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

24. {4385} All VOC-containing materials subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

25. {4386} The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

26. {4387} With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

27. {4388} If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

28. {4389} If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit

29. {4390} Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8021] Federally Enforceable Through Title V Permit

30. {4391} Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8031] Federally Enforceable Through Title V Permit

31. {4392} An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8041] Federally Enforceable Through Title V Permit

32. {4393} Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8051] Federally Enforceable Through Title V Permit

33. {4394} Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8061] Federally Enforceable Through Title V Permit

34. {4395} Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8071] Federally Enforceable Through Title V Permit

35. {4396} Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

DRAFT

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

36. {4397} The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

37. {4398} The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

38. {4399} When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

39. {4400} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), Rule 111 (Kern, Tulare, Kings), and Rule 202 (Fresno, Kern, Tulare, Kings, Madera, Stanislaus, Merced, San Joaquin). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

40. {4401} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601 (12/17/09); 8021 (8/19/2004); 8031 (8/19/2004); 8041 (8/19/2004); 8051 (8/19/2004); 8061 (8/19/2004); and 8071 (9/16/2004). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

41. {98} No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

42. A Three-Year Compliance Plan that demonstrates compliance with the requirements of Section 5.1 of District Rule 4694 for each year of the applicable compliance period shall be submitted to the District by no later than December 1, 2018, and every three years thereafter on or before December 1. [District Rule 4694]

43. A Three-Year Compliance Plan Verification that demonstrates that the Three-Year Compliance Plan elements are in effect shall be submitted to the District by no later than July 1, 2019, and every three years thereafter on or before July 1. [District Rule 4694]

44. An Annual Compliance Plan Demonstration that shows compliance with the applicable requirements of this rule shall be submitted to the District by no later than March 1, 2018, and every year thereafter on or before March 1. [District Rule 4694]

45. Operators using Certified Emissions Reductions (CER) to mitigate fermentation emissions shall perform all monitoring and recordkeeping, as established in their approved Three-Year Compliance Plan, and shall maintain all records necessary to demonstrate compliance. [District Rule 4694]

46. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report begin January 1 of every year, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-3-8 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
465 BHP CATERPILLAR MODEL G379 NATURAL GAS-FIRED IC ENGINE WITH NON-SELECTIVE CATALYTIC REDUCTION (NSCR) POWERING AN ELECTRICAL GENERATOR WITH A HEAT RECOVERY CO-GENERATION SYSTEM (COMPLIANT DORMANT EMISSIONS UNIT)

PERMIT UNIT REQUIREMENTS

1. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2080] Federally Enforceable Through Title V Permit
2. The fuel supply line shall be physically disconnected from this unit. [District Rule 2080] Federally Enforceable Through Title V Permit
3. The hour-meter shall not exceed a reading of 97,570.25 hours. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Operators shall notify the District at least seven (7) calendar days prior to recommencing operation of this dormant emissions unit (DEU), at which time this permit will be administratively modified to remove DEU references. [District Rules 1070 and 4702] Federally Enforceable Through Title V Permit
5. If this unit becomes out of compliance with District Rules while it is dormant, operation of the unit is not authorized until an Authority to Construct permit is issued approving all necessary retrofits and permit changes required to comply with the respective District Rules. [District Rule 2010] Federally Enforceable Through Title V Permit
6. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
7. Upon recommencing operation, this unit shall be fired only on PUC-regulated natural gas with a sulfur content of less than or equal to 0.017% by weight. [District Rules 2201, 4702, and 4801] Federally Enforceable Through Title V Permit
8. This engine shall be equipped with a nonresettable elapsed operating time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
9. Upon recommencing operation, this engine shall be operated and maintained in proper operating condition per the manufacturer's requirements as specified on the Inspection and Monitoring (I&M) plan submitted to the District. [District Rule 4702] Federally Enforceable Through Title V Permit
10. Upon recommencing operation, the permittee shall update the I&M plan for this engine prior to any planned change in operation. The permittee must notify the District no later than seven days after changing the I&M plan and must submit an updated I&M plan to the APCO for approval no later than 14 days after the change. The date and time of the change to the I&M plan shall be recorded in the engine's operating log. For modifications, the revised I&M plan shall be submitted to and approved by the APCO prior to issuance of the Permit to Operate. The permittee may request a change to the I&M plan at any time. [District Rule 4702] Federally Enforceable Through Title V Permit
11. Upon recommencing operation, emissions from this IC engine shall not exceed any of the following limits: 25 ppmvd NOx @ 15% O2 (equivalent to 0.349 g-NOx/hp-hr), 0.055 g-SOx/hp-hr, 0.073 g-PM10/hp-hr, 500 ppmvd CO @ 15% O2 (equivalent to 4.245 g-CO/hp-hr), or 250 ppmvd VOC @ 15% O2 (equivalent to 1.213 g-VOC/hp-hr). [District Rules 2201, 4701, and 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

12. A source test to demonstrate compliance with the indicated emissions limits shall be performed within 60 days of recommencing operation of this unit. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Upon recommencing operation, source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be measured not less than once every 24 months. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
14. Emissions source testing shall be conducted with the engine operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
15. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit, the test cannot be used to demonstrate compliance with an applicable limit. NOx and CO concentrations shall be reported in ppmv, corrected to 15% oxygen. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
16. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, CO (ppmv) - EPA Method 10 or ARB Method 100, and stack gas oxygen - EPA Method 3 or 3A or ARB Method 100. [District Rules 1081, 4701, and 4702] Federally Enforceable Through Title V Permit
17. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
18. The results of each source test shall be submitted to the District within 60 days thereafter. Source tests must be submitted for all District authorized compliance source tests regardless of pass, fail or reschedule because of failure status. A District authorized compliance source test shall not be discontinued solely due to the failure of one or more runs to meet applicable standards. [District Rule 1081] Federally Enforceable Through Title V Permit
19. A scheduled source test may not be discontinued solely due to the failure of one or more runs to meet applicable standards. [District Rule 1081] Federally Enforceable Through Title V Permit
20. In the event that a sample is accidentally lost or conditions occur in which one of three runs must be discontinued because of forced shutdown, failure of an irreplaceable portion of the sampling train, extreme meteorological conditions presenting a hazard to the sampling team, or other circumstances beyond the owner or operators control, upon the APCO's approval, compliance may be determined using the arithmetic mean of the other two runs. [District Rule 1081] Federally Enforceable Through Title V Permit
21. Source sampling to determine the compliance status of an emissions source shall be witnessed or authorized by District personnel. [District Rule 1081] Federally Enforceable Through Title V Permit
22. Upon recommencing operation, the permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the engine is not in operation, i.e. the engine need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the engine unless monitoring has been performed within the last month. Records must be maintained of the dates of non-operation to validate extended monitoring frequencies. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit
23. Upon recommencing operation, all alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. Upon recommencing operation, if either the NOx or CO concentrations corrected to 15% O2, as measured by the portable analyzer, exceed the allowable emission concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 8 hours after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 8 hours, the permittee shall notify the District within the following 1 hour, and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

25. The permittee shall maintain records of: (1) the date and time of O2 and NOx measurements, (2) the O2 concentration in percent and the measured NOx concentration corrected to 15% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

26. The permittee shall maintain on file copies of all natural gas bills or fuel throughput records for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

27. Upon recommencing operation, the permittee shall maintain an engine operating log to demonstrate compliance. The engine operating log shall include, on a monthly basis, the following information: total hours of operation, type of fuel used, maintenance or modifications performed, monitoring data, compliance source test results, and any other information necessary to demonstrate compliance. [District Rules 4701 and 4702] Federally Enforceable Through Title V Permit

28. {2437} The requirements of SJVAPCD District Rule 1080 (Amended December 17, 1992), do not apply to this source because this unit is subject to alternate monitoring in lieu of any continuous emission monitoring requirements. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

29. {2421} Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: Rules 404 (Madera), 406 (Fresno), and 407 (Kings, Merced, San Joaquin, Tulare, Kern, and Stanislaus). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

30. Upon recommencing operation, the operator shall establish an O2 sensor output voltage range that indicates that the control device(s) on this engine are operating properly at all times. [40 CFR 64] Federally Enforceable Through Title V Permit

31. Within twelve months of recommencing operation, the operator shall submit a Title V minor modification application to incorporate the O2 sensor output voltage range established for this engine. [40 CFR 64] Federally Enforceable Through Title V Permit

32. Upon recommencing operation, the permittee shall comply with the compliance assurance monitoring operation and maintenance requirements of 40 CFR Part 64.7. [40 CFR 64] Federally Enforceable Through Title V Permit

33. Upon recommencing operation, the permittee shall comply with the recordkeeping and reporting requirements of 40 CFR Part 64.9. [40 CFR 64] Federally Enforceable Through Title V Permit

34. Upon recommencing operation, if the District or EPA determine that a Quality Improvement Plan is required under 40 CFR 64.7(d)(2), the permittee shall develop and implement the Quality Improvement Plan in accordance with 40 CFR Part 64.8. [40 CFR 64] Federally Enforceable Through Title V Permit

35. Upon recommencing operation, the engine shall be in full compliance with 40 CFR Part 63, Subpart ZZZZ (National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines). [40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit

36. Upon recommencing operation, the permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes. [40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

DRAFT

37. Upon recommencing operation, the engine's oil and filter shall be changed every 1,440 hours of operation or every 12 months, whichever comes first. [40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit

38. Upon recommencing operation, the engine's spark plugs shall be inspected every 1,440 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit

39. Upon recommencing operation, the engine's hoses and belts shall be inspected every 1,440 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit

40. Upon recommencing operation, the permittee shall maintain monthly records that include any information necessary to demonstrate compliance with 40 CFR 63, ZZZZ. [40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit

41. Upon recommencing operation, the permittee shall maintain monthly records of all performance tests, opacity and visible emissions observations and required maintenance performed on the air pollution control and monitoring equipment. [40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit

42. Upon recommencing operation, the permittee shall maintain monthly records of the occurrence and duration of each malfunction of the operation (i.e., process equipment) or the air pollution control and monitoring equipment. The permittee shall also maintain monthly records of the action(s) taken during periods of malfunction to minimize emissions in accordance with §63.6605(b), including corrective actions to restore malfunctioning operation and air pollution control and monitoring equipment to its normal or usual manner of operation. [40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit

43. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 4701 and 4702, and 40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-4-11 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
97 MMBTU/HR NEBRASKA MODEL NS-F-81 NATURAL GAS-FIRED BOILER (WEST) WITH AN ALZETA MODEL CSB-1210 ULTRA LOW NOX BURNER

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. This unit shall be fired exclusively on PUC-regulated natural gas. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
4. Emissions rates from this unit shall not exceed any of the following limits: 7 ppmvd NOx @ 3% O2 or 0.008 lb-NOx/MMBtu, 0.00285 lb-SOx/MMBtu, 0.0076 lb-PM10/MMBtu, 100 ppmvd CO @ 3% O2 or 0.074 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
5. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
6. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
8. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
9. NOx emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
11. Stack gas oxygen (O2) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Fuel hhv for source test purposes shall be certified by a third party fuel supplier or determined using ASTM D 1826 or D1945 in conjunction with ASTM D 3588 for gaseous fuels or ASTM D 240 or D 2382 for liquid hydrocarbon fuels. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
14. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
15. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
16. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
17. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
18. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
19. The permittee shall submit an analysis showing the fuel's sulfur content at least once every year. Valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy this requirement, provided they establish the fuel parameters mentioned above. [District Rule 4320] Federally Enforceable Through Title V Permit
20. Permittee shall record the monthly fuel consumption. [District Rules 1070 and 2520, and 40 CFR 60.48(c)(g)(2)] Federally Enforceable Through Title V Permit
21. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320, and 40 CFR 60.48(c)(i)] Federally Enforceable Through Title V Permit
22. The requirements of 40 CFR 72.6(b) are not applicable because this is not an affected unit under the acid rain provisions. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-5-11 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
97 MMBTU/HR NEBRASKA MODEL NS-F-81 NATURAL GAS-FIRED BOILER (EAST) WITH AN ALZETA MODEL CSB-1210 ULTRA LOW NOX BURNER

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. This unit shall be fired exclusively on PUC-regulated natural gas. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
4. Emissions rates from this unit shall not exceed any of the following limits: 7 ppmvd NOx @ 3% O2 or 0.008 lb-NOx/MMBtu, 0.00285 lb-SOx/MMBtu, 0.0076 lb-PM10/MMBtu, 100 ppmvd CO @ 3% O2 or 0.074 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
5. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
6. Source testing to measure NOx and CO emissions from this unit while fired on natural gas shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
8. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
9. NOx emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
11. Stack gas oxygen (O2) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Fuel hhv for source test purposes shall be certified by a third party fuel supplier or determined using ASTM D 1826 or D1945 in conjunction with ASTM D 3588 for gaseous fuels or ASTM D 240 or D 2382 for liquid hydrocarbon fuels. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
14. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
15. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
16. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
17. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
18. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
19. The permittee shall submit an analysis showing the fuel's sulfur content at least once every year. Valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy this requirement, provided they establish the fuel parameters mentioned above. [District Rule 4320] Federally Enforceable Through Title V Permit
20. Permittee shall record the monthly fuel consumption. [District Rules 1070 and 2520, and 40 CFR 60.48(c)(g)(2)] Federally Enforceable Through Title V Permit
21. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320, and 40 CFR 60.48(c)(i)] Federally Enforceable Through Title V Permit
22. The requirements of 40 CFR 72.6(b) are not applicable because this is not an affected unit under the acid rain provisions. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-6-4

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
186 BHP DETROIT DIESEL MODEL 6061AZ DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIREWATER PUMP

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rule 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
3. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 17 CCR 93115, and 40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit
4. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. For testing purposes, the engine shall only be operated the number of hours necessary to comply with the testing requirements of the National Fire Protection Association (NFPA) 25 - "Standard for the Inspection, Testing, and Maintenance of Water-Based Fire Protection Systems", 1998 edition. Total hours of operation for all maintenance, testing, and required regulatory purposes shall not exceed 100 hours in any rolling 12-month period. [District Rule 4702, 17 CCR 93115, and 40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit
5. An emergency situation is preserving or protecting property, human life, or public health during a disaster or other event such as a fire or flood. [District Rule 4702] Federally Enforceable Through Title V Permit
6. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, and the purpose of the operation (for example: load testing, weekly testing, fire protection, etc.). For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
7. The permittee shall maintain monthly records of the type of fuel purchased, the amount of fuel purchased, date when the fuel was purchased, signature of the permittee who received the fuel, and signature of the fuel supplier indicating that the fuel was delivered. [District Rules 2520, 9.3.2 and 4702, and 17 CCR 93115] Federally Enforceable Through Title V Permit
8. On a monthly basis, the permittee shall calculate and record the hours of operation for the rolling 12-month period. The hours of operation shall be calculated by summing the hours of operation from the previous 12 months. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
9. The engine shall be in full compliance with 40 CFR Part 63, Subpart ZZZZ (National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines. [40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit
10. The permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes. [40 CFR 63, ZZZZ)] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. The engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit
12. The engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit
13. The engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit
14. The permittee shall maintain monthly records of all performance tests, opacity and visible emissions observations and required maintenance performed on the air pollution control and monitoring equipment. [District Rule 1070 and 40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit
15. The permittee shall maintain monthly records of the occurrence and duration of each malfunction of operation (i.e., process equipment) or the air pollution control and monitoring equipment. The permittee shall also maintain monthly records of action taken during periods of malfunction to minimize emissions in accordance with §63.6605(b), including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation. [District Rule 1070 and 40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit
16. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702, 17 CCR 93115, and 40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: C-628-12-3 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
PNEUMATICALLY LOADED DIATOMACEOUS EARTH FILTER POWDER STORAGE SILO WITH PNEUMATIC TRANSFER CAPABILITY TO FOUR MIXING TANKS, ALL SERVED INDIVIDUALLY BY DUST COLLECTORS

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grain per dry standard cubic foot. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed the hourly rate as calculated in District Rule 4202 using the equation E = 3.59xP^0.62 if P is less than or equal to 30 tons per hour, or E = 17.31xP^0.16 if P is greater than 30 tons per hour. [District Rule 4202] Federally Enforceable Through Title V Permit
3. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants in the atmosphere. [District Rule 4102]
4. Material removed from dust collectors shall be disposed of in a manner preventing entrainment in the atmosphere. [District Rule 4102]
5. Records of daily and annual throughput of filter powder shall be maintained, retained for at least five years, and made available to the District upon request. [District Rules 1070 and 2520, 9.4.2] Federally Enforceable Through Title V Permit
6. Visible emissions shall be inspected annually during operation. If visible emissions are observed, corrective action shall be taken to eliminate visible emissions prior to further loading. Corrective action shall eliminate visible emissions before next loading event. The results of inspection shall be kept in a record and shall be made available to the District upon request. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
7. Permittee shall perform a complete vent filter inspection on an annual basis. Dust collector filters shall be inspected thoroughly for tears, scuffs, abrasions, holes, or any evidence of particulate matter leaks and shall be replaced as needed. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. Records of dust collector inspection, maintenance, and repair shall be maintained. These records shall include identification of the dust collector, date of inspection, any corrective action taken as a result of inspection, and initials of the personnel performing the inspection. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-13-8 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
44 MMBTU/HR NEBRASKA MODEL NS-C-42-ECON NATURAL GAS-FIRED BOILER, EQUIPPED WITH AN ALZETA ULTRA-LOW NOX BURNER WITH A VARIABLE FREQUENCY DRIVE FOR AIR INTAKE FAN MOTOR AND OXYGEN TRIM EQUIPMENT IN EXHAUST STACK

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. This unit shall be fired exclusively on PUC-regulated natural gas. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
4. Emissions rates from this unit shall not exceed any of the following limits: 7 ppmvd NOx @ 3% O2 or 0.008 lb-NOx/MMBtu, 0.00285 lb-SOx/MMBtu, 0.0076 lb-PM10/MMBtu, 100 ppmvd CO @ 3% O2 or 0.074 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
5. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
6. Source testing to measure NOx and CO emissions from this unit while fired on natural gas shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
8. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
9. NOx emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
10. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
11. Stack gas oxygen (O2) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Fuel hhv for source test purposes shall be certified by a third party fuel supplier or determined using ASTM D 1826 or D1945 in conjunction with ASTM D 3588 for gaseous fuels or ASTM D 240 or D 2382 for liquid hydrocarbon fuels. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
14. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
15. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
16. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
17. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
18. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
19. The permittee shall submit an analysis showing the fuel's sulfur content at least once every year. Valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy this requirement, provided they establish the fuel parameters mentioned above. [District Rule 4320] Federally Enforceable Through Title V Permit
20. Permittee shall record the monthly fuel consumption. [District Rules 1070 and 2520, and 40 CFR 60.48(c)(g)(2)] Federally Enforceable Through Title V Permit
21. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320, and 40 CFR 60.48(c)(i)] Federally Enforceable Through Title V Permit
22. The requirements of 40 CFR 72.6(b) are not applicable because this is not an affected unit under the acid rain provisions. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-15-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
126,766 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-16-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
126,766 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-17-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
126,766 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 3 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-18-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
126,766 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 4 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-19-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
126,766 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 5 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-20-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
126,766 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 6 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-21-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
126,019 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 7 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-22-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
126,077 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 8 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-23-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
25,068 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 17 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-24-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
25,068 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 18 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-27-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
266,111 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 31 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-28-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
265,911 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 32 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-29-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
252,795 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 39 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-30-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
252,795 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 40 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-31-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
252,795 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 41 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-32-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
252,795 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 42 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-33-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
252,795 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 43 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-34-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
252,795 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 44 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-35-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
350,282 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 45 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-36-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
350,282 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 46 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-37-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
350,282 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 47 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-38-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
660,328 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 49 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-39-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
660,101 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 50 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-40-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
658,995 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 51 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-41-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
659,353 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 52 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-42-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
659,353 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 53 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-43-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
659,285 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 54 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-44-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
659,353 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 55 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-45-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
659,174 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 56 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-46-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
647,141 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 57 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-47-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
647,149 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 58 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-48-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
647,149 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 59 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-49-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
647,149 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 60 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-50-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
647,149 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 61 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-51-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
647,149 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 62 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-52-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
647,149 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 63 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-53-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
647,141 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 64 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-54-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
127,615 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 65 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-55-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
127,615 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 66 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-56-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
127,615 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 67 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-57-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
127,615 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 68 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-58-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
324,512 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 71 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-59-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
323,316 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 72 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-60-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
322,446 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 73 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-61-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
322,446 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 74 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-62-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
265,052 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 81 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-63-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
265,552 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 82 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-64-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
265,162 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 83 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-65-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
252,500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 84 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-66-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
127,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 85 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-67-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
128,100 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 86 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-68-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
128,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 87 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-69-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
128,300 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 88 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-70-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
127,615 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 89 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-71-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
172,945 GALLON CONCRETE OPEN RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 101

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-72-3 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
172,941 GALLON CONCRETE OPEN RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 102

DRAFT

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-73-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
17,170 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 110 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-74-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
17,170 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 111 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-75-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
17,170 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 112 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-76-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
17,170 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 113 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-77-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
17,170 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 114 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-78-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
17,170 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 115 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-79-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 121 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-80-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 122 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-81-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 123 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-82-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 124 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-83-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 125 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-84-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 126 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-85-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 127 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-86-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 128 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-87-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 129 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-88-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 130 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-89-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 131 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-90-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 132 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-91-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 133 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-92-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 134 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-93-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 135 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-94-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 136 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-95-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 137 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-96-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 138 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-97-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 139 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-98-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 140 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-99-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 141 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-100-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 142 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-101-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 143 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-102-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 144 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-103-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 145 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-104-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 146 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-105-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
5,834 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 150 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-106-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
5,832 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 151 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-107-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
4,489 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 152 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-108-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
4,489 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 153 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-133-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
11,186 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 224 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-134-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
11,186 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 225 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-135-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,428 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 226 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: C-628-136-3

EXPIRATION DATE: 11/30/2016

EQUIPMENT DESCRIPTION:
63,543 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 401

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-137-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,269 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 402

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-138-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,461 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 403

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-139-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
62,977 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 404

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-140-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
62,913 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 405

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-141-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,174 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 406

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-142-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,654 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 407

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-143-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,403 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 408

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-144-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,284 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 409

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-145-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
62,919 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 410

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-146-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
62,999 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 411

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-147-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,000 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 412

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-148-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,114 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 413

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-149-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,172 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 414

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-150-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
62,996 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 415

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-151-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,020 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 416

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-152-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,022 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 417

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-153-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,323 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 418

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-154-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,037 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 419

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: C-628-155-3

EXPIRATION DATE: 11/30/2016

EQUIPMENT DESCRIPTION:
62,966 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 420

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-156-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,174 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 421

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-157-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,018 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 422

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: C-628-158-3

EXPIRATION DATE: 11/30/2016

EQUIPMENT DESCRIPTION:
62,945 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 423

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-159-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,439 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 424

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-160-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,970 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 425

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-161-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,153 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 426

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-162-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
62,908 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 427

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-163-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
62,803 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 428

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-164-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
62,885 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 429

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-165-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,096 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 430

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-166-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,181 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 431

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-167-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
62,834 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 432

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-168-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
62,908 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 433

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-169-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
62,786 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 434

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-170-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,456 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 435

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: C-628-171-3

EXPIRATION DATE: 11/30/2016

EQUIPMENT DESCRIPTION:
62,994 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 436

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-172-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 500 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-173-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 501 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-174-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 502 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-175-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 503 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-176-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 504 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-177-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 505 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-178-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
307,100 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 506 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-179-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,524 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 507 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-180-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 508 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-181-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 509 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-182-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 510 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-183-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 511 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-184-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
307,105 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 512 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-185-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 513 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-186-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 514 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-187-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 515 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-188-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 516 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-189-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 517 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-190-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 518 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-191-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 519 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-192-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,627 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 520 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-193-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,682 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 521 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-194-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
307,160 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 522 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-195-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 523 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-196-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 524 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-197-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 525 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-198-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 526 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-199-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 527 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-200-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 528 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-201-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 529 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-202-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 530 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-203-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 531 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-204-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 532 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-206-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,924 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 534 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-208-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 536 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-210-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 538 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-211-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 550 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-212-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 551 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-213-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 552 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-215-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 554 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-216-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 555 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-217-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 556 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-219-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 558 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-220-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 559 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-221-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 560 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-223-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 562 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-224-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 563 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-225-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 564 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-227-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 566 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-229-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 568 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-231-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 570 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-233-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 572 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-237-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 576 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-238-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
64,452 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 600 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-239-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
64,452 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 601 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-240-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
64,452 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 602 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-241-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
64,452 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 603 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-242-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
64,452 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 604 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-243-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
64,452 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 605 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-244-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,816 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 606 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-245-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,816 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 607 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-246-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,816 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 608 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-247-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,816 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 609 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-248-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,816 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 610 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-249-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,816 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 611 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-250-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
20,947 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 612 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-251-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
20,947 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 613 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-254-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
3,175 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 793 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-255-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
3,175 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 794 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: C-628-256-3 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
3,175 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 795 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-257-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
13,536 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 797 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-258-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
13,536 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 798 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-259-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
13,536 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 799 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-260-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 800 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-261-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 801 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-262-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 802 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-263-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 803 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-264-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 804 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-265-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 805 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-266-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 806 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-267-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 807 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-268-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 808 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-269-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 809 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-270-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 810 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-271-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 811 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-272-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
6,933 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 812 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-273-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
6,933 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 813 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-274-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
6,933 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 814 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-275-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
6,933 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 815 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-276-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
260,516 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 850 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-277-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
260,500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 851 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-278-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
260,500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 852 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-279-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
260,500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 853 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-280-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
260,516 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 854 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-281-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
122,975 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 855 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-282-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
122,975 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 856 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-283-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
122,975 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 857 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-284-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
122,975 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 858 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-285-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
122,975 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 859 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-286-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
122,975 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 860 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-287-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
122,975 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 861 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-288-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
122,975 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 862 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-289-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
122,975 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 863 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-290-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
122,975 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 864 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-291-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 866 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-292-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 867 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-293-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 868 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-294-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 869 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-295-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 870 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-296-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 871 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-297-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 872 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-298-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 873 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-299-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 874 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-300-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 875 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-301-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 876 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-302-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 877 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-303-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 878 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-304-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 879 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-305-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 880 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-306-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 881 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-307-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 882 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-308-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 883 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-309-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 884 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-310-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 885 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-311-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
20,740 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 886 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-312-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
20,740 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 887 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-313-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
20,740 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 888 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-314-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
20,740 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 889 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-315-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
20,740 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 890 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-316-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
20,740 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 891 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-317-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
20,740 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 892 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-318-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
20,740 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 893 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-319-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
20,740 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 894 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-320-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
20,740 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 895 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-321-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
62,390 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 900 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-322-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 901 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-323-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 902 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-324-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
8,114 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 903 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-325-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 904 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-326-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
8,114 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 905 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-327-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 906 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-328-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
8,114 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 907 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-329-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 908 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: C-628-330-3

EXPIRATION DATE: 11/30/2016

EQUIPMENT DESCRIPTION:
128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 909 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-331-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
8,114 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 910 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-332-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 911 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-333-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
8,114 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 912 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-334-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 913 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-335-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
8,114 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 914 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-336-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 915 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-337-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
8,114 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 916 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-338-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 917 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-339-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
19,980 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 918 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-340-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
19,980 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 919 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-341-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 920 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-342-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
8,114 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 921 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-343-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 922 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-344-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
8,114 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 923 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-345-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 924 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-346-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
8,114 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 925 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-347-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 926 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-348-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
19,980 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 927 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

DRAFT

PERMIT UNIT: C-628-349-3

EXPIRATION DATE: 11/30/2016

EQUIPMENT DESCRIPTION:
19,980 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 928 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-350-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
62,390 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 929 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-351-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
62,390 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 930 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-352-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
62,390 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 931 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-353-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
62,390 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 932 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-354-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
62,390 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 933 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-355-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
62,390 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 934 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-356-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
62,390 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 935 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-357-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
62,390 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 936 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-358-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 937 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-359-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 938 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-360-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 939 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-361-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 940 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-362-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 941 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-363-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 942 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-364-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 943 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-365-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 944 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-366-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 945 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-367-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 946 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-368-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 947 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-369-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 948 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-370-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 949 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-371-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 950 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-372-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 951 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-373-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 952 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-374-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 953 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-375-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 954 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-376-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 955 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-377-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 956 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-378-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 957 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-379-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 958 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-380-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 959 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-381-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 960 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-382-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 961 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-383-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 962 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-384-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 963 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-385-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 964 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-386-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 965 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-387-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 966 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-388-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 967 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-389-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 968 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-390-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 969 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-391-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 970 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-392-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 971 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-393-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 972 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-394-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 973 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-395-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 974 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-396-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 975 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-397-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 976 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-398-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 977 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-399-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 978 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-400-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 979 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-401-3 **EXPIRATION DATE:** 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 980 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-402-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 981 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-403-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 982 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-404-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 983 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-405-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 984 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-406-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 985 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-407-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 986 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-408-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 987 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-409-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 988 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-410-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 989 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-411-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 990 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-412-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 991 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-413-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,643 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 992 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-414-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
4,527 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 993 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-415-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,643 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 994 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-416-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,643 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 995 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-417-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,643 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 996 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-418-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
10,643 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 997 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-419-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
5,714 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 998 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-420-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
24,955 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P1 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-421-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
24,955 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P2 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-422-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
24,955 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P3 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-423-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
24,955 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P4 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-424-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
24,955 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P5 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-425-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
24,955 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P6 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-427-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
12,425 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P8 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-428-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
12,425 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P9 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-429-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
12,425 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P10 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-431-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
1,173 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P12 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-432-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
155,321 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1013 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-433-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
1,173 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P14 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-434-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
61,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P21 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-435-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
61,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P22 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-476-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
1,957 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 897 WITH PRESSURE VALVE

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-477-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
1,242 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 898 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-478-3

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
1,242 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 899 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature, the uncontrolled fermentation emissions, and any fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
3. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-749-2

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
225 BHP, LIMITED TO 121.7 BHP @ 1800 RPM, FORD MODEL WSG-1068 RICH-BURN LPG/PROPANE-FIRED EMERGENCY-STANDBY IC ENGINE WITH NON-SELECTIVE CATALYTIC REDUCTION (NSCR) POWERING AN ELECTRICAL GENERATOR (CATERPILLAR G60F3 GENERATOR SET)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. This IC engine shall be equipped with a three-way catalyst. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
4. {1898} The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
5. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
6. Emissions from this IC engine shall not exceed any of the following limits: 0.52 g-NOx/bhp-hr, 0.175 g-PM10/bhp-hr, 3.14 g-CO/bhp-hr, or 0.032 g-VOC/bhp-hr. [District Rule 2201] Federally Enforceable Through Title V Permit
7. This IC engine shall be fired on LPG/propane gas only. [District Rule 2201] Federally Enforceable Through Title V Permit
8. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
9. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 100 hours in any rolling 12-month period. [District Rule 4702] Federally Enforceable Through Title V Permit
10. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
11. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.), the type of fuel used, and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702] Federally Enforceable Through Title V Permit

13. On a monthly basis, the permittee shall calculate and record the hours of operation for the rolling 12-month period. The hours of operation shall be calculated by summing the hours of operation from the previous 12 months. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

14. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-751-2

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
GASOLINE DISPENSING OPERATION WITH ONE 500 GALLON TRUSCO SUPERVAULT ABOVEGROUND STORAGE TANK SERVED BY STANDING LOSS CONTROL (VR-301-X), AND 1 FUELING POINT WITH 1 GASOLINE DISPENSING NOZZLE SERVED BY BALANCE PHASE II VAPOR RECOVERY SYSTEM (G-70-132-A)

PERMIT UNIT REQUIREMENTS

1. The Phase I and Phase II vapor recovery systems shall be maintained in accordance with the manufacturer specifications and the ARB Executive Orders specified in this permit, including applicable rules and regulations of the Division of Measurement Standards of the Department of Food and Agriculture, the Office of the State Fire Marshal of the Department of Forestry and Fire Protection, the Division of Occupational Safety and Health of the Department of Industrial Relations, and the Division of Water Quality of the State Water Resources Control Board that have been made conditions of the certification. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
2. This gasoline storage and dispensing equipment shall not be used in retail sales, where gasoline dispensed by the unit is subject to payment of California sales tax on gasoline sales. [District Rule 4622] Federally Enforceable Through Title V Permit
3. The owner shall prohibit any person from topping off a motor vehicle fuel tank. [District Rule 4622] Federally Enforceable Through Title V Permit
4. The storage container(s) shall be maintained and operated such that they are leak-free. [District Rule 4621] Federally Enforceable Through Title V Permit
5. The Phase I and Phase II vapor recovery systems and gasoline dispensing equipment shall be maintained without leaks as determined in accordance with the test method specified in this permit. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
6. A leak is defined as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration of total organic compound greater than 10,000 ppmv, as methane, above background when measured in accordance with EPA Test Method 21. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
7. No gasoline delivery vessel shall be operated or be allowed to operate unless valid State of California decals are displayed on the cargo container, which attest to the vapor integrity of the container. [District Rule 4621] Federally Enforceable Through Title V Permit
8. No person shall operate any ARB certified Phase II vapor recovery system or any portion thereof that has a major defect or an equipment defect that is identified in any applicable ARB Executive Order until the following conditions have been met: 1) the defect has been repaired, replaced, or adjusted as necessary to correct the defect; 2) the District has been notified, and the District has reinspected the system or authorized the system for use (such authorization shall not include the authority to operate the equipment prior to the correction of the defective components); and 3) all major defects, after repair, are duly entered into the Operations and Maintenance (O&M) manual. [District Rule 4622] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Upon identification of any major defects, the permittee shall tag "Out-of-Order" all dispensing equipment for which vapor recovery has been impaired. Tagged equipment shall be rendered inoperable and the tag(s) shall not be removed until the defective equipment has been repaired, replaced, or adjusted, as necessary. In the case of defects identified by the District, tagged equipment shall be rendered inoperable, and the tag shall not be removed until the District has been notified of the repairs, and the District has either reinspected the system or authorized the tagged equipment for use. [District Rule 4622] Federally Enforceable Through Title V Permit

10. The permittee shall implement a periodic maintenance inspection program for the certified Phase II vapor recovery system consistent with the requirements of this permit. The program shall be documented in an operation and maintenance (O&M) manual and shall at a minimum contain the following information: 1) copies of all vapor recovery performance tests; 2) all applicable ARB Executive Orders, Approval Letters, and District Permits; 3) the manufacturer's specifications and instructions for installation, operation, repair, and maintenance required pursuant to ARB Certification Procedure CP-201, and any additional instruction provided by the manufacturer; 4) system and/or component testing requirements, including test schedules and passing criteria for each of the standard tests required by this permit (the owner/operator may include any non-ARB required diagnostic and other tests as part of the testing requirements), and 5) additional O&M instructions, if any, that are designed to ensure compliance with the applicable rules, regulations, ARB Executive Orders, and District permit conditions, including replacement schedules for failure or wear prone components. [District Rule 4622] Federally Enforceable Through Title V Permit

11. The permittee shall conduct periodic maintenance inspections based on the greatest monthly throughput of gasoline dispensed by the facility in the previous year as follows: A) less than 2,500 gallons - one day per month; B) 2,500 to less than 25,000 gallons - one day per week; or C) 25,000 gallons or greater - five days per week. All inspections shall be documented within the O & M Manual. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

12. Periodic maintenance inspections of the Phase I vapor recovery system shall include, at a minimum, verification that 1) the fill caps and vapor caps are not missing, damaged, or loose; 2) the fill cap gasket and vapor cap gaskets are not missing or damaged; 3) the fill adapter and vapor adapter are securely attached to the risers; 4) where applicable, the spring-loaded submerged fill tube seals properly against the coaxial tubing; 5) the dry break (poppet-valve) is not missing or damaged; and 6) the submerged fill tube is not missing or damaged. [District Rule 4621] Federally Enforceable Through Title V Permit

13. Periodic maintenance inspections of the Phase II vapor recovery system shall include, at a minimum, verification that 1) the following nozzle components are in place and in good condition as specified in ARB Executive Order as applicable: faceplate/facecone, bellows, latching device spring, vapor check valve, spout (proper diameter/vapor collection holes), insertion interlock mechanism, automatic shut-off mechanism, and hold open latch (unless prohibited by law or the local fire control authority); 2) the hoses are not torn, flattened or crimped; 3) the vapor path of the coaxial hoses associated with bellows equipped nozzles does not contain more than 100 ml of liquid if applicable; and 4) the vapor processing unit is functioning properly, for operations that are required to have or possess such a unit. [District Rule 4622] Federally Enforceable Through Title V Permit

14. In the event of a separation due to a drive off, the permittee shall, unless otherwise specified in the applicable ARB Executive Order, conduct a visual inspection of the affected equipment and either 1) perform qualified repairs on any damaged components and conduct applicable re-verification tests pursuant to the requirements of this permit, or 2) replace the affected nozzles, coaxial hoses, breakaway couplings, and any other damaged components with new or certified rebuilt components that are ARB certified. The activities shall be documented in accordance with the requirements of this permit before placing the affected equipment back in service. [District Rule 4622] Federally Enforceable Through Title V Permit

15. Only white paint, listed in the Executive Order specified in this permit for the Standing Loss Control System, shall be applied to the tank. The surface of the tank shall be prepared and the white paint shall be applied per manufacturer's specification. [District Rule 4621] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

16. The permittee shall maintain the following records: 1) receipt of sale that demonstrates the purchase date and amount of white paint purchased, 2) record of the name of personnel applying white paint to include the date of application, surface preparation description (i.e. scraping, sanding, abrasive blasting, primer etc.), method of application (i.e. brush, roller, air/airless sprayer), average ambient temperature (øF) during application, and atmospheric observations during application (i.e. sunny, cloudy, rain, etc.), 3) record of the name of personnel that installed the P/V vent valve, and 4) Technical Data Sheet and/or Material Safety Data Sheet of the white paint that describes the surface preparation, application, and material safety of the white paint. [District Rule 4621] Federally Enforceable Through Title V Permit
17. The gasoline throughput for this permit unit shall not exceed 18,000 gallons in any rolling 12-month period [District Rule 2201] Federally Enforceable Through Title V Permit
18. Emissions from this operation shall not exceed 0.5 lb-VOC/day. Emissions may be calculated as follows: [(# gallons delivered/day x 0.473 lb-VOC/1000gallons) + (# gallons dispensed/day x 0.893 lb-VOC/1000 gallons)]. [District Rule 2201] Federally Enforceable Through Title V Permit
19. The permittee shall conduct all periodic vapor recovery system performance tests specified in this permit, no more than 30 days before or after the required compliance testing date, unless otherwise required under the applicable ARB Executive Order. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
20. For certified Phase II vapor recovery systems with liquid removal devices, the permittee shall perform and pass an ARB TP-201.6C Liquid Removal Test whenever the liquid in the vapor path exceeds 100 ml of liquid, or as required by the applicable ARB Executive Order. The amount of liquid in the vapor path shall be measured by lowering the gasoline dispensing nozzle into a container until such time that no more liquid drains from the nozzle. The amount of liquid drained into the container shall be measured using a graduated cylinder or graduated beaker. The vapor path shall be inspected according to the monitoring frequency as determined by monthly gasoline throughput. [District Rule 4622] Federally Enforceable Through Title V Permit
21. The permittee shall perform and pass a Static Leak Test for Aboveground Tanks using ARB TP-201.3B or TP-206.3 at least once every 12 months thereafter. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
22. A person conducting testing of, or repairs to, a certified vapor recovery system shall be in compliance with District Rule 1177 (Gasoline Dispensing Facility Tester Certification). [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
23. A person performing installation of, or maintenance on, a certified Phase I or Phase II vapor recovery system shall be certified by the ICC for Vapor Recovery System Installation and Repair, or work under the direct and personal supervision of an individual physically present at the work site who is certified. The ICC certification shall be renewed every 24 months. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
24. Proof of the ICC certification and all other certifications required by the Executive Order and installation and operation manual shall be made available onsite. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
25. The permittee shall notify the District at least 7 days prior to each performance test. The test results shall be submitted to the District no later than 30 days after the completion of each test. [District Rule 4621] Federally Enforceable Through Title V Permit
26. The permittee shall maintain a copy of all test results. The test results shall be dated and shall contain the name, address, and telephone number of the company responsible for system installation and testing. [District Rule 4622] Federally Enforceable Through Title V Permit
27. The permittee shall maintain on the premises a log of any repairs made to the certified Phase I or Phase II vapor recovery system. The repair log shall include the following: 1) date and time of each repair; 2) the name and applicable certification numbers of the person(s) who performed the repair, and if applicable, the name, address and phone number of the person's employer; 3) description of service performed; 4) each component that was repaired, serviced, or removed; 5) each component that was installed as replacement, if applicable; and 6) receipts or other documents for parts used in the repair and, if applicable, work orders which shall include the name and signature of the person responsible for performing the repairs. [District Rule 4622] Federally Enforceable Through Title V Permit

DRAFT

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

28. The O&M manual shall be kept at the dispensing operation and made available to any person who operates, inspects, maintains, repairs, or tests the equipment at the operation as well as to District personnel upon request. [District Rule 4622] Federally Enforceable Through Title V Permit

29. The permittee shall maintain daily, monthly and annual gasoline throughput records. [District Rules 2201, 4621 and 4622] Federally Enforceable Through Title V Permit

30. On a monthly basis, the permittee shall calculate and record the gasoline throughput for the rolling 12-month period. The gasoline throughput shall be calculated by summing the gallons of gasoline dispensed from the previous 12 months. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

31. All records required by this permit shall be retained on-site for a period of at least five years and shall be made available for District inspection upon request. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

DRAFT

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-752-2

EXPIRATION DATE: 11/30/2016

DRAFT

EQUIPMENT DESCRIPTION:
GRAPE SEED DRYING OPERATION CONSISTING OF DELUX MFG CO NATURAL GAS-FIRED TOWER GRAIN DRYER WITH A 7.3 MMBTU/HR DELUX MFG CO MODEL 24 ½" NOVA BURNER SYSTEM

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The unit shall only be fired on PUC regulated natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
3. A non-resettable, totalizing mass or volumetric fuel flow meter shall be installed on the fuel line to the dryer burners. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [District Rule 4801 and Merced County Rule 407] Federally Enforceable Through Title V Permit
5. Emissions from the natural gas-fired unit shall not exceed any of the following limits: 0.05 lb-NOx/MMBtu, 0.00285 lb-SOx/MMBtu, 0.0076 lb-PM10/MMBtu, 0.051 lb-CO/MMBtu, or 0.0141 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The total heat input shall not exceed 3,660 MMBtu/yr during any rolling 12-month period. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Visible emissions shall be observed once per calendar quarter during operation. Any indication of potential visible emissions in excess of the limits of Rule 4101 shall be corrected within 24 hours. If visible emissions cannot be corrected within 24 hours, a visible emissions test using EPA Method 9 shall be conducted. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. Permittee shall keep a record of the rolling 12-month heat input of the unit. This record shall be updated on a monthly basis. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Permittee shall maintain records which demonstrate the unit is fired exclusively on PUC regulated natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Operator shall maintain copies of all fuel invoices and supplier certifications. [District Rule 2201] Federally Enforceable Through Title V Permit
11. All records shall be maintained for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

DRAFT

ATTACHMENT B

Previous Title V Operating Permit

San Joaquin Valley
AIR POLLUTION CONTROL DISTRICT

HEALTHY AIR LIVING™

Permit to Operate

FACILITY: C-628

EXPIRATION DATE: 11/30/2016

LEGAL OWNER OR OPERATOR: CBUS OPS DBA MISSION BELL WINERY
MAILING ADDRESS: 12667 ROAD 24
MADERA, CA 93637

FACILITY LOCATION: 12667 ROAD 24
MADERA, CA 93637

FACILITY DESCRIPTION: WINERY

The Facility's Permit to Operate may include Facility-wide Requirements as well as requirements that apply to specific permit units.

This Permit to Operate remains valid through the permit expiration date listed above, subject to payment of annual permit fees and compliance with permit conditions and all applicable local, state, and federal regulations. This permit is valid only at the location specified above, and becomes void upon any transfer of ownership or location. Any modification of the equipment or operation, as defined in District Rule 2201, will require prior District approval. This permit shall be posted as prescribed in District Rule 2010.

Seyed Sadredin
Executive Director / APCO

Arnaud Marjollet
Director of Permit Services

Oct 19 2017 9:27AM – BROWND

San Joaquin Valley
Air Pollution Control District

FACILITY: C-628-0-2 **EXPIRATION DATE:** 11/30/2016

FACILITY-WIDE REQUIREMENTS

1. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
2. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
3. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.13.1] Federally Enforceable Through Title V Permit
6. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

10. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit

11. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit

12. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit

13. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit

14. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit

15. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit

16. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit

17. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit

18. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit

19. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit

20. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit

21. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

22. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

23. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in Table of Standards 1 effective until 12/30/10 or Table of Standards 2 effective on and after 1/1/11 of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit

24. All VOC-containing materials subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit

25. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit

26. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit

27. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit

28. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit

29. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8021] Federally Enforceable Through Title V Permit

30. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8031] Federally Enforceable Through Title V Permit

31. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8041] Federally Enforceable Through Title V Permit

32. Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8051] Federally Enforceable Through Title V Permit

33. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8061] Federally Enforceable Through Title V Permit

34. Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8071] Federally Enforceable Through Title V Permit

35. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

36. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit

37. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit

38. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit

39. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), Rule 111 (Kern, Tulare, Kings), and Rule 202 (Fresno, Kern, Tulare, Kings, Madera, Stanislaus, Merced, San Joaquin). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

40. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601 (12/17/09); 8021 (8/19/2004); 8031 (8/19/2004); 8041 (8/19/2004); 8051 (8/19/2004); 8061 (8/19/2004); and 8071 (9/16/2004). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit

41. On December 31, 2004, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report begin January 1 of every year, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit

42. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]

43. A Three-Year Compliance Plan that demonstrates compliance with the requirements of Section 5.1 of District Rule 4694 for each year of the applicable compliance period shall be submitted to the District by no later than December 1, 2006, and every three years thereafter on or before December 1. [District Rule 4694]

44. A Three-Year Compliance Plan Verification that demonstrates that the Three-Year Compliance Plan elements are in effect shall be submitted to the District by no later than July 1, 2007, and every three years thereafter on or before July 1. [District Rule 4694]

45. An Annual Compliance Plan Demonstration that shows compliance with the applicable requirements of this rule shall be submitted to the District by no later than March 1, 2008, and every year thereafter on or before March 1. [District Rule 4694]

46. Operators using Certified Emissions Reductions (CER) to mitigate fermentation emissions shall perform all monitoring and recordkeeping, as established in their approved Three-Year Compliance Plan, and shall maintain all records necessary to demonstrate compliance. [District Rule 4694]

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-3-7 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
465 BHP CATERPILLAR MODEL G379 NATURAL GAS-FIRED IC ENGINE WITH NON-SELECTIVE CATALYTIC REDUCTION (NSCR) POWERING AN ELECTRICAL GENERATOR WITH A HEAT RECOVERY CO-GENERATION SYSTEM (COMPLIANT DORMANT EMISSIONS UNIT)

PERMIT UNIT REQUIREMENTS

1. No modification to this unit shall be performed without an Authority to Construct for such modification(s), except for changes specified in conditions below. [District Rule 2080] Federally Enforceable Through Title V Permit
2. The fuel supply line shall be physically disconnected from this unit. [District Rule 2080] Federally Enforceable Through Title V Permit
3. The hour-meter shall not exceed a reading of 97,570.25 hours. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Operators shall notify the District at least seven (7) calendar days prior to recommencing operation of this dormant emissions unit (DEU), at which time this permit will be administratively modified to remove DEU references. [District Rules 1070 and 4702] Federally Enforceable Through Title V Permit
5. If this unit becomes out of compliance with District Rules while it is dormant, operation of the unit is not authorized until an Authority to Construct permit is issued approving all necessary retrofits and permit changes required to comply with the respective District Rules. [District Rule 2010] Federally Enforceable Through Title V Permit
6. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
7. Upon recommencing operation, this unit shall be fired only on PUC-regulated natural gas with a sulfur content of less than or equal to 0.017% by weight. [District Rules 2201 and 4801] Federally Enforceable Through Title V Permit
8. This engine shall be equipped with a nonresettable elapsed operating time meter or other APCO approved alternative. [District Rule 4702, 5.6.6] Federally Enforceable Through Title V Permit
9. Upon recommencing operation, this engine shall be operated and maintained in proper operating condition per the manufacturer's requirements as specified on the Inspection and Monitoring (I&M) plan submitted to the District. [District Rule 4702, 6.5.6] Federally Enforceable Through Title V Permit
10. Upon recommencing operation, the permittee shall update the I&M plan for this engine prior to any planned change in operation. The permittee must notify the District no later than seven days after changing the I&M plan and must submit an updated I&M plan to the APCO for approval no later than 14 days after the change. The date and time of the change to the I&M plan shall be recorded in the engine's operating log. For modifications, the revised I&M plan shall be submitted to and approved by the APCO prior to issuance of the Permit to Operate. The permittee may request a change to the I&M plan at any time. [District Rule 4702, 6.5.9] Federally Enforceable Through Title V Permit
11. Upon recommencing operation, emissions from this IC engine shall not exceed any of the following limits: 25 ppmvd NOx @ 15% O2 (equivalent to 0.349 g-NOx/hp-hr), 0.055 g-SOx/hp-hr, 0.073 g-PM10/hp-hr, 500 ppmvd CO @ 15% O2 (equivalent to 4.245 g-CO/hp-hr), or 250 ppmvd VOC @ 15% O2 (equivalent to 1.213 g-VOC/hp-hr). [District Rules 2201, 4701, 5.1, and 4702, 5.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. A source test to demonstrate compliance with the indicated emissions limits shall be performed within 60 days of recommencing operation of this unit. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Upon recommencing operation, source testing to measure natural gas-combustion NOx and CO emissions from this unit shall be measured not less than once every 24 months. [District Rules 4701, 6.3.1 and 4702, 6.3.1] Federally Enforceable Through Title V Permit
14. Emissions source testing shall be conducted with the engine operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. [District Rules 4701, 6.3.2 and 4702, 6.3.2] Federally Enforceable Through Title V Permit
15. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit, the test cannot be used to demonstrate compliance with an applicable limit. NOx and CO concentrations shall be reported in ppmv, corrected to 15% oxygen. [District Rules 4701, 6.3.2 and 4702, 6.3.2] Federally Enforceable Through Title V Permit
16. The following test methods shall be used: NOx (ppmv) - EPA Method 7E or ARB Method 100, CO (ppmv) - EPA Method 10 or ARB Method 100, and stack gas oxygen - EPA Method 3 or 3A or ARB Method 100. [District Rules 1081, 4701, 6.4, and 4702, 6.4] Federally Enforceable Through Title V Permit
17. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
18. The results of each source test shall be submitted to the District within 60 days thereafter. Source tests must be submitted for all District authorized compliance source tests regardless of pass, fail or reschedule because of failure status. A District authorized compliance source test shall not be discontinued solely due to the failure of one or more runs to meet applicable standards. [District Rule 1081] Federally Enforceable Through Title V Permit
19. A scheduled source test may not be discontinued solely due to the failure of one or more runs to meet applicable standards. [District Rule 1081] Federally Enforceable Through Title V Permit
20. In the event that a sample is accidentally lost or conditions occur in which one of three runs must be discontinued because of forced shutdown, failure of an irreplaceable portion of the sampling train, extreme meteorological conditions presenting a hazard to the sampling team, or other circumstances beyond the owner or operators control, upon the APCO's approval, compliance may be determined using the arithmetic mean of the other two runs. [District Rule 1081] Federally Enforceable Through Title V Permit
21. Source sampling to determine the compliance status of an emissions source shall be witnessed or authorized by District personnel. [District Rule 1081] Federally Enforceable Through Title V Permit
22. Upon recommencing operation, the permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the engine is not in operation, i.e. the engine need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the engine unless monitoring has been performed within the last month. Records must be maintained of the dates of non-operation to validate extended monitoring frequencies. [District Rules 4701, 5.4.1 and 4702, 5.6 and 6.5.2] Federally Enforceable Through Title V Permit
23. Upon recommencing operation, all alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the permit-to-operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4701, 5.4.3 and 4702, 5.6.9 and 6.5.7] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

24. Upon recommencing operation, if either the NOx or CO concentrations corrected to 15% O2, as measured by the portable analyzer, exceed the allowable emission concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 8 hours after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 8 hours, the permittee shall notify the District within the following 1 hour, and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of the performing the notification and testing required by this condition. [District Rules 4701, 5.4.1 and 4702, 5.6 and 6.5.4] Federally Enforceable Through Title V Permit
25. The permittee shall maintain records of: (1) the date and time of O2 and NOx measurements, (2) the O2 concentration in percent and the measured NOx concentration corrected to 15% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4701, 6.2.1 and 4702, 6.2.1 and 6.5.8] Federally Enforceable Through Title V Permit
26. The permittee shall maintain on file copies of all natural gas bills or fuel throughput records for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
27. Upon recommencing operation, the permittee shall maintain an engine operating log to demonstrate compliance. The engine operating log shall include, on a monthly basis, the following information: total hours of operation, type of fuel used, maintenance or modifications performed, monitoring data, compliance source test results, and any other information necessary to demonstrate compliance. [District Rules 4701, 6.2.1 and 4702, 6.2.1] Federally Enforceable Through Title V Permit
28. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 4701, 6.2.3 and 4702, 6.2.2, and 40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit
29. The requirements of SJVAPCD District Rule 1080 (Amended December 17, 1992), do not apply to this source because this unit is subject to alternate monitoring in lieu of any continuous emission monitoring requirements. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
30. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following subsumed requirements: Rules 404 (Madera), 406 (Fresno), and 407 (Kings, Merced, San Joaquin, Tulare, Kern, and Stanislaus). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
31. Upon recommencing operation, the operator shall establish an O2 sensor output voltage range that indicates that the control device(s) on this engine are operating properly at all times. [40 CFR 64] Federally Enforceable Through Title V Permit
32. Within twelve months of recommencing operation, the operator shall submit a Title V minor modification application to incorporate the O2 sensor output voltage range established for this engine. [40 CFR 64] Federally Enforceable Through Title V Permit
33. Upon recommencing operation, the permittee shall comply with the compliance assurance monitoring operation and maintenance requirements of 40 CFR Part 64.7. [40 CFR 64] Federally Enforceable Through Title V Permit
34. Upon recommencing operation, the permittee shall comply with the recordkeeping and reporting requirements of 40 CFR Part 64.9. [40 CFR 64] Federally Enforceable Through Title V Permit
35. Upon recommencing operation, if the District or EPA determine that a Quality Improvement Plan is required under 40 CFR 64.7(d)(2), the permittee shall develop and implement the Quality Improvement Plan in accordance with 40 CFR Part 64.8. [40 CFR 64] Federally Enforceable Through Title V Permit
36. Upon recommencing operation, on and after October 19, 2013, the permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes. [40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

37. Upon recommencing operation, on and after October 19, 2013, the engine shall be in full compliance with 40 CFR Part 63, Subpart ZZZZ (National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines). [40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit
38. Upon recommencing operation, on and after October 19, 2013, the engine's oil and filter shall be changed every 1,440 hours of operation or every 12 months, whichever comes first. [40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit
39. Upon recommencing operation, on and after October 19, 2013, the engine's spark plugs shall be inspected every 1,440 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit
40. Upon recommencing operation, on and after October 19, 2013, the engine's hoses and belts shall be inspected every 1,440 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit
41. Upon recommencing operation, on and after October 19, 2013, the permittee shall maintain monthly records that include any information necessary to demonstrate compliance with 40 CFR 63, ZZZZ. [40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit
42. Upon recommencing operation, on and after October 19, 2013, the permittee shall maintain monthly records of all performance tests, opacity and visible emissions observations and required maintenance performed on the air pollution control and monitoring equipment. [40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit
43. Upon recommencing operation, on and after October 19, 2013, the permittee shall maintain monthly records of the occurrence and duration of each malfunction of the operation (i.e., process equipment) or the air pollution control and monitoring equipment. The permittee shall also maintain monthly records of the action(s) taken during periods of malfunction to minimize emissions in accordance with §63.6605(b), including corrective actions to restore malfunctioning operation and air pollution control and monitoring equipment to its normal or usual manner of operation. [40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-4-10 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
97 MMBTU/HR NEBRASKA MODEL NS-F-81 NATURAL GAS-FIRED BOILER (WEST) WITH AN ALZETA MODEL CSB-1210 ULTRA LOW NOX BURNER

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. This unit shall be fired exclusively on PUC-regulated natural gas. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
4. Emissions rates from this unit shall not exceed any of the following limits: 7 ppmvd NOx @ 3% O2 or 0.008 lb-NOx/MMBtu, 0.00285 lb-SOx/MMBtu, 0.0076 lb-PM10/MMBtu, 100 ppmvd CO @ 3% O2 or 0.074 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
5. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
6. Source testing to measure NOx and CO emissions from this unit shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
8. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
9. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
10. NOx emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
11. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Stack gas oxygen (O2) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

13. Fuel hhv for source test purposes shall be certified by a third party fuel supplier or determined using ASTM D 1826 or D1945 in conjunction with ASTM D 3588 for gaseous fuels or ASTM D 240 or D 2382 for liquid hydrocarbon fuels. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

14. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

15. The requirements of 40 CFR 72.6(b) are not applicable because this is not an affected unit under the acid rain provisions. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

16. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

18. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

19. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

20. The permittee shall submit an analysis showing the fuel's sulfur content at least once every year. Valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy this requirement, provided they establish the fuel parameters mentioned above. [District Rule 4320] Federally Enforceable Through Title V Permit

21. Permittee shall record the monthly fuel consumption. [District Rules 1070 and 2520, and 40 CFR 60.48(c)(g)(2)] Federally Enforceable Through Title V Permit

22. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320, and 40 CFR 60.48(c)(i)] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-5-10 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
97 MMBTU/HR NEBRASKA MODEL NS-F-81 NATURAL GAS-FIRED BOILER (EAST) WITH AN ALZETA MODEL CSB-1210 ULTRA LOW NOX BURNER

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. This unit shall be fired exclusively on PUC-regulated natural gas. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
4. Emissions rates from this unit shall not exceed any of the following limits: 7 ppmvd NOx @ 3% O2 or 0.008 lb-NOx/MMBtu, 0.00285 lb-SOx/MMBtu, 0.0076 lb-PM10/MMBtu, 100 ppmvd CO @ 3% O2 or 0.074 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
5. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
6. Source testing to measure NOx and CO emissions from this unit while fired on natural gas shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
8. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
9. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
10. NOx emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
11. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Stack gas oxygen (O2) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

13. Fuel hhv for source test purposes shall be certified by a third party fuel supplier or determined using ASTM D 1826 or D1945 in conjunction with ASTM D 3588 for gaseous fuels or ASTM D 240 or D 2382 for liquid hydrocarbon fuels. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

14. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

15. The requirements of 40 CFR 72.6(b) are not applicable because this is not an affected unit under the acid rain provisions. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit

16. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

17. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

18. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

19. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

20. The permittee shall submit an analysis showing the fuel's sulfur content at least once every year. Valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy this requirement, provided they establish the fuel parameters mentioned above. [District Rule 4320] Federally Enforceable Through Title V Permit

21. Permittee shall record the monthly fuel consumption. [District Rules 1070 and 2520, and 40 CFR 60.48(c)(g)(2)] Federally Enforceable Through Title V Permit

22. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320, and 40 CFR 60.48(c)(i)] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-6-3 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
186 BHP DETROIT DIESEL MODEL 6061AZ DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIREWATER PUMP

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. Only CARB certified diesel fuel containing not more than 0.0015% sulfur by weight is to be used. [District Rule 4801 and 17 CCR 93115] Federally Enforceable Through Title V Permit
3. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702, 17 CCR 93115, and 40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit
4. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. For testing purposes, the engine shall only be operated the number of hours necessary to comply with the testing requirements of the National Fire Protection Association (NFPA) 25 - "Standard for the Inspection, Testing, and Maintenance of Water-Based Fire Protection Systems", 1998 edition. Total hours of operation for all maintenance, testing, and required regulatory purposes shall not exceed 100 hours per calendar year. [District Rule 4702, 17 CCR 93115, and 40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit
5. An emergency situation is preserving or protecting property, human life, or public health during a disaster or other event such as a fire or flood. [District Rule 4702] Federally Enforceable Through Title V Permit
6. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, and the purpose of the operation (for example: load testing, weekly testing, fire protection, etc.). For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702 and 17 CCR 93115] Federally Enforceable Through Title V Permit
7. The permittee shall maintain monthly records of the type of fuel purchased, the amount of fuel purchased, date when the fuel was purchased, signature of the permittee who received the fuel, and signature of the fuel supplier indicating that the fuel was delivered. [District Rules 2520, 9.3.2 and 4702, and 17 CCR 93115] Federally Enforceable Through Title V Permit
8. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702, 17 CCR 93115, and 40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit
9. On and after May 3, 2013, the permittee must minimize the engine's time spent at idle during startup and minimize the engine's startup time to a period needed for appropriate and safe loading of the engine, not to exceed 30 minutes. [40 CFR 63, ZZZZ)] Federally Enforceable Through Title V Permit
10. On and after May 3, 2013, the engine shall be in full compliance with 40 CFR Part 63, Subpart ZZZZ (National Emission Standards for Hazardous Air Pollutants for Stationary Reciprocating Internal Combustion Engines. [40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

11. On and after May 3, 2013, the engine's oil and filter shall be changed every 500 hours of operation or every 12 months, whichever comes first. [40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit
12. On and after May 3, 2013, the engine's air filter shall be inspected every 1,000 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit
13. On and after May 3, 2013, the engine's hoses and belts shall be inspected every 500 hours of operation or every 12 months, whichever comes first, and replaced as necessary. [40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit
14. On and after May 3, 2013, the permittee shall maintain monthly records of all performance tests, opacity and visible emissions observations and required maintenance performed on the air pollution control and monitoring equipment. [District Rule 1070 and 40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit
15. On and after May 3, 2013, the permittee shall maintain monthly records of the occurrence and duration of each malfunction of operation (i.e., process equipment) or the air pollution control and monitoring equipment. The permittee shall also maintain monthly records of action taken during periods of malfunction to minimize emissions in accordance with §63.6605(b), including corrective actions to restore malfunctioning process and air pollution control and monitoring equipment to its normal or usual manner of operation. [District Rule 1070 and 40 CFR 63, ZZZZ] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-12-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
PNEUMATICALLY LOADED DIATOMACEOUS EARTH FILTER POWDER STORAGE SILO WITH PNEUMATIC TRANSFER CAPABILITY TO FOUR MIXING TANKS, ALL SERVED INDIVIDUALLY BY DUST COLLECTORS

PERMIT UNIT REQUIREMENTS

1. Records of daily and annual throughput of filter powder shall be maintained, retained for at least five years, and made available to the District upon request. [District Rules 1070 and 2520, 9.4.2] Federally Enforceable Through Title V Permit
2. Visible emissions shall be inspected annually during operation. If visible emissions are observed, corrective action shall be taken to eliminate visible emissions prior to further loading. Corrective action shall eliminate visible emissions before next loading event. The results of inspection shall be kept in a record and shall be made available to the District upon request. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
3. Permittee shall perform a complete vent filter inspection on an annual basis. Dust collector filters shall be inspected thoroughly for tears, scuffs, abrasions, holes, or any evidence of particulate matter leaks and shall be replaced as needed. [District Rule 2520, 9.3.2]
4. Records of dust collector inspection, maintenance, and repair shall be maintained. These records shall include identification of the dust collector, date of inspection, any corrective action taken as a result of inspection, and initials of the personnel performing the inspection. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-13-7 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
44 MMBTU/HR NEBRASKA MODEL NS-C-42-ECON NATURAL GAS-FIRED BOILER, EQUIPPED WITH AN ALZETA ULTRA-LOW NOX BURNER WITH A VARIABLE FREQUENCY DRIVE FOR AIR INTAKE FAN MOTOR AND OXYGEN TRIM EQUIPMENT IN EXHAUST STACK

PERMIT UNIT REQUIREMENTS

1. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
3. This unit shall be fired exclusively on PUC-regulated natural gas. [District Rules 2201 and 4320] Federally Enforceable Through Title V Permit
4. Emissions rates from this unit shall not exceed any of the following limits: 7 ppmvd NOx @ 3% O2 or 0.008 lb-NOx/MMBtu, 0.00285 lb-SOx/MMBtu, 0.0076 lb-PM10/MMBtu, 100 ppmvd CO @ 3% O2 or 0.074 lb-CO/MMBtu, or 0.0055 lb-VOC/MMBtu. [District Rules 2201, 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
5. All emissions measurements shall be made with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. No determination of compliance shall be established within two hours after a continuous period in which fuel flow to the unit is shut off for 30 minutes or longer, or within 30 minutes after a re-ignition as defined in Section 3.0 of District Rule 4320. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
6. Source testing to measure NOx and CO emissions from this unit while fired on natural gas shall be conducted at least once every twelve (12) months. After demonstrating compliance on two (2) consecutive annual source tests, the unit shall be tested not less than once every thirty-six (36) months. If the result of the 36-month source test demonstrates that the unit does not meet the applicable emission limits, the source testing frequency shall revert to at least once every twelve (12) months. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
7. The source test plan shall identify which basis (ppmv or lb/MMBtu) will be used to demonstrate compliance. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
8. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081] Federally Enforceable Through Title V Permit
9. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081] Federally Enforceable Through Title V Permit
10. NOx emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
11. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. Stack gas oxygen (O2) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
13. Fuel hhv for source test purposes shall be certified by a third party fuel supplier or determined using ASTM D 1826 or D1945 in conjunction with ASTM D 3588 for gaseous fuels or ASTM D 240 or D 2382 for liquid hydrocarbon fuels. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
14. For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit the test cannot be used to demonstrate compliance with an applicable limit. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
15. The requirements of 40 CFR 72.6(b) are not applicable because this is not an affected unit under the acid rain provisions. A permit shield is granted from these requirements. [District Rule 2520] Federally Enforceable Through Title V Permit
16. The permittee shall monitor and record the stack concentration of NOx, CO, and O2 at least once every month (in which a source test is not performed) using a portable emission monitor that meets District specifications. Monitoring shall not be required if the unit is not in operation, i.e. the unit need not be started solely to perform monitoring. Monitoring shall be performed within 5 days of restarting the unit unless monitoring has been performed within the last month. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
17. If either the NOx or CO concentrations corrected to 3% O2, as measured by the portable analyzer, exceed the allowable emissions concentration, the permittee shall return the emissions to within the acceptable range as soon as possible, but no longer than 1 hour of operation after detection. If the portable analyzer readings continue to exceed the allowable emissions concentration after 1 hour of operation after detection, the permittee shall notify the District within the following 1 hour and conduct a certified source test within 60 days of the first exceedance. In lieu of conducting a source test, the permittee may stipulate a violation has occurred, subject to enforcement action. The permittee must then correct the violation, show compliance has been re-established, and resume monitoring procedures. If the deviations are the result of a qualifying breakdown condition pursuant to Rule 1100, the permittee may fully comply with Rule 1100 in lieu of performing the notification and testing required by this condition. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
18. All alternate monitoring parameter emission readings shall be taken with the unit operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. The analyzer shall be calibrated, maintained, and operated in accordance with the manufacturer's specifications and recommendations or a protocol approved by the APCO. Emission readings taken shall be averaged over a 15 consecutive-minute period by either taking a cumulative 15 consecutive-minute sample reading or by taking at least five (5) readings, evenly spaced out over the 15 consecutive-minute period. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
19. The permittee shall maintain records of: (1) the date and time of NOx, CO, and O2 measurements, (2) the O2 concentration in percent and the measured NOx and CO concentrations corrected to 3% O2, (3) make and model of exhaust gas analyzer, (4) exhaust gas analyzer calibration records, and (5) a description of any corrective action taken to maintain the emissions within the acceptable range. [District Rules 4305, 4306, and 4320] Federally Enforceable Through Title V Permit
20. The permittee shall submit an analysis showing the fuel's sulfur content at least once every year. Valid purchase contracts, supplier certifications, tariff sheets, or transportation contracts may be used to satisfy this requirement, provided they establish the fuel parameters mentioned above. [District Rule 4320] Federally Enforceable Through Title V Permit
21. Permittee shall record the monthly fuel consumption. [District Rules 1070 and 2520, and 40 CFR 60.48(c)(g)(2)] Federally Enforceable Through Title V Permit
22. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070, 4305, 4306, and 4320, and 40 CFR 60.48(c)(i)] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-15-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
126,766 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-16-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
126,766 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-17-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
126,766 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 3 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-18-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
126,766 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 4 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-19-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
126,766 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 5 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-20-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
126,766 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 6 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-21-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
126,019 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 7 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-22-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
126,077 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 8 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-23-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
25,068 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 17 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-24-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
25,068 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 18 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-27-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
266,111 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 31 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-28-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
265,911 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 32 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-29-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
252,795 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 39 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-30-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
252,795 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 40 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-31-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
252,795 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 41 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-32-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
252,795 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 42 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-33-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
252,795 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 43 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-34-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
252,795 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 44 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-35-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
350,282 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 45 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-36-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
350,282 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 46 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-37-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
350,282 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 47 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-38-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
660,328 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 49 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-39-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
660,101 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 50 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-40-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
658,995 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 51 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-41-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
659,353 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 52 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-42-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
659,353 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 53 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-43-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
659,285 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 54 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-44-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
659,353 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 55 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-45-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
659,174 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 56 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-46-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
647,141 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 57 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-47-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
647,149 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 58 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-48-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
647,149 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 59 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-49-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
647,149 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 60 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-50-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
647,149 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 61 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-51-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
647,149 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 62 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-52-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
647,149 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 63 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-53-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
647,141 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 64 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-54-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
127,615 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 65 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-55-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
127,615 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 66 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-56-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
127,615 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 67 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-57-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
127,615 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 68 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-58-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
324,512 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 71 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-59-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
323,316 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 72 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-60-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
322,446 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 73 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-61-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
322,446 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 74 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-62-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
265,052 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 81 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-63-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
265,552 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 82 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-64-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
265,162 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 83 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-65-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
252,500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 84 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-66-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
127,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 85 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-67-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
128,100 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 86 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-68-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
128,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 87 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-69-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
128,300 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 88 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-70-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
127,615 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 89 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-71-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
172,945 GALLON CONCRETE OPEN RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 101

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-72-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
172,941 GALLON CONCRETE OPEN RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 102

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-73-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
17,170 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 110 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-74-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
17,170 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 111 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-75-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
17,170 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 112 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-76-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
17,170 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 113 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-77-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
17,170 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 114 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-78-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
17,170 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 115 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-79-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 121 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-80-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 122 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-81-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 123 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-82-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 124 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-83-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 125 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-84-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 126 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-85-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 127 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-86-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 128 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-87-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 129 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-88-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 130 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-89-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 131 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-90-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 132 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-91-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 133 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-92-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 134 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-93-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 135 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-94-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 136 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-95-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 137 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-96-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 138 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-97-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 139 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-98-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 140 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-99-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 141 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-100-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 142 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-101-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 143 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-102-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 144 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-103-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 145 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-104-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 146 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-105-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
5,834 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 150 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-106-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
5,832 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 151 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-107-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
4,489 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 152 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-108-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
4,489 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 153 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-133-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
11,186 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 224 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-134-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
11,186 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 225 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-135-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
10,428 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 226 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-136-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,543 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 401

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-137-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,269 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 402

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-138-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,461 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 403

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-139-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
62,977 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 404

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-140-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
62,913 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 405

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-141-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,174 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 406

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-142-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,654 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 407

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-143-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,403 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 408

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-144-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,284 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 409

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-145-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
62,919 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 410

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-146-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
62,999 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 411

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-147-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,000 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 412

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-148-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,114 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 413

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-149-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,172 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 414

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-150-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
62,996 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 415

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-151-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,020 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 416

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-152-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,022 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 417

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-153-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,323 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 418

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-154-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,037 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 419

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-155-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
62,966 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 420

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-156-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,174 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 421

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-157-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,018 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 422

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-158-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
62,945 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 423

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-159-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,439 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 424

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-160-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,970 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 425

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-161-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,153 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 426

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-162-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
62,908 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 427

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-163-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
62,803 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 428

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-164-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
62,885 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 429

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-165-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,096 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 430

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-166-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,181 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 431

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-167-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
62,834 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 432

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-168-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
62,908 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 433

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-169-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
62,786 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 434

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-170-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,456 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 435

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-171-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
62,994 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 436

PERMIT UNIT REQUIREMENTS

1. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
2. Separate annual records each of total red wine and total white wine produced by fermentation at this facility, based on values reported to the Alcohol and Tobacco Tax and Trade Bureau (TTB), U.S. Department of the Treasury, shall be kept. [District Rule 4694]
3. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
4. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-172-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 500 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-173-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 501 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-174-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 502 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-175-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 503 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-176-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 504 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-177-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 505 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-178-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
307,100 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 506 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-179-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,524 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 507 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-180-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 508 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-181-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 509 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-182-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 510 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-183-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 511 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-184-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
307,105 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 512 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-185-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 513 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-186-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 514 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-187-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 515 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-188-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 516 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-189-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 517 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-190-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 518 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-191-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 519 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-192-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,627 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 520 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-193-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,682 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 521 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-194-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
307,160 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 522 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-195-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 523 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-196-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 524 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-197-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 525 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-198-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 526 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-199-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 527 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-200-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 528 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-201-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 529 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-202-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 530 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-203-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 531 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-204-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 532 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-206-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,924 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 534 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-208-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 536 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-210-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 538 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-211-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 550 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-212-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 551 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-213-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 552 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-215-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 554 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-216-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 555 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-217-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 556 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-219-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 558 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-220-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 559 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-221-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 560 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-223-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 562 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-224-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 563 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-225-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 564 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-227-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 566 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-229-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 568 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-231-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 570 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-233-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 572 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-237-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 576 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-238-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
64,452 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 600 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-239-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
64,452 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 601 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-240-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
64,452 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 602 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-241-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
64,452 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 603 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-242-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
64,452 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 604 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-243-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
64,452 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 605 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-244-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,816 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 606 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-245-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,816 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 607 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-246-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,816 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 608 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-247-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,816 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 609 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-248-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,816 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 610 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-249-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,816 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 611 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-250-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
20,947 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 612 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-251-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
20,947 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 613 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-254-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
3,175 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 793 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-255-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
3,175 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 794 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-256-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
3,175 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 795 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-257-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
13,536 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 797 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-258-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
13,536 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 798 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-259-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
13,536 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 799 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-260-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 800 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-261-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 801 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-262-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 802 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-263-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 803 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-264-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 804 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-265-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 805 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-266-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 806 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-267-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 807 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-268-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 808 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-269-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 809 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-270-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 810 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-271-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 811 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-272-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
6,933 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 812 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-273-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
6,933 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 813 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-274-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
6,933 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 814 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-275-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
6,933 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 815 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-276-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
260,516 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 850 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-277-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
260,500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 851 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-278-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
260,500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 852 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-279-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
260,500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 853 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-280-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
260,516 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 854 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-281-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
122,975 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 855 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-282-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
122,975 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 856 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-283-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
122,975 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 857 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-284-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
122,975 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 858 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-285-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
122,975 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 859 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-286-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
122,975 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 860 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-287-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
122,975 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 861 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-288-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
122,975 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 862 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-289-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
122,975 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 863 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-290-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
122,975 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 864 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-291-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 866 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-292-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 867 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-293-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 868 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-294-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 869 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-295-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 870 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-296-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 871 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-297-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 872 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-298-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 873 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-299-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 874 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-300-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 875 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-301-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 876 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-302-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 877 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-303-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 878 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-304-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 879 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-305-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 880 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-306-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 881 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-307-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 882 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-308-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 883 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-309-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 884 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-310-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 885 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-311-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
20,740 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 886 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-312-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
20,740 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 887 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-313-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
20,740 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 888 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-314-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
20,740 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 889 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-315-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
20,740 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 890 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-316-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
20,740 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 891 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-317-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
20,740 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 892 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-318-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
20,740 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 893 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-319-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
20,740 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 894 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-320-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
20,740 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 895 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-321-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
62,390 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 900 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-322-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 901 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-323-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 902 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-324-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
8,114 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 903 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-325-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 904 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-326-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
8,114 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 905 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-327-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 906 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-328-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
8,114 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 907 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-329-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 908 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-330-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 909 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-331-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
8,114 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 910 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-332-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 911 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-333-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
8,114 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 912 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-334-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 913 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-335-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
8,114 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 914 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-336-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 915 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-337-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
8,114 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 916 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-338-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 917 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-339-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
19,980 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 918 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-340-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
19,980 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 919 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-341-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 920 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-342-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
8,114 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 921 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-343-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 922 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-344-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
8,114 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 923 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-345-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 924 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-346-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
8,114 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 925 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-347-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 926 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-348-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
19,980 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 927 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-349-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
19,980 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 928 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-350-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
62,390 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 929 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-351-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
62,390 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 930 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-352-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
62,390 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 931 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-353-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
62,390 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 932 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-354-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
62,390 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 933 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-355-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
62,390 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 934 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-356-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
62,390 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 935 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-357-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
62,390 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 936 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-358-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 937 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-359-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 938 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-360-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 939 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-361-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 940 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-362-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 941 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-363-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 942 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-364-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 943 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-365-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 944 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-366-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 945 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-367-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 946 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-368-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 947 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-369-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 948 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-370-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 949 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-371-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 950 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-372-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 951 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-373-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 952 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-374-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 953 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-375-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 954 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-376-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 955 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-377-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 956 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-378-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 957 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-379-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 958 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-380-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 959 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-381-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 960 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-382-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 961 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-383-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 962 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-384-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 963 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-385-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 964 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-386-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 965 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-387-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 966 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-388-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 967 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-389-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 968 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-390-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 969 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-391-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 970 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-392-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 971 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-393-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 972 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-394-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 973 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-395-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 974 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-396-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 975 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-397-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 976 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-398-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 977 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-399-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 978 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-400-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 979 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-401-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 980 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-402-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 981 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-403-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 982 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-404-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 983 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-405-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 984 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-406-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 985 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-407-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 986 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-408-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 987 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-409-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 988 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-410-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 989 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-411-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 990 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-412-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 991 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-413-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
10,643 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 992 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-414-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
4,527 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 993 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-415-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
10,643 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 994 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-416-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
10,643 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 995 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-417-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
10,643 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 996 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-418-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
10,643 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 997 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-419-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
5,714 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 998 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-420-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
24,955 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P1 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-421-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
24,955 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P2 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-422-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
24,955 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P3 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-423-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
24,955 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P4 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-424-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
24,955 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P5 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-425-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
24,955 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P6 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-427-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
12,425 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P8 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-428-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
12,425 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P9 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-429-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
12,425 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P10 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-431-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
1,173 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P12 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-432-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
155,321 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1013 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-433-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
1,173 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P14 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-434-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
61,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P21 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-435-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
61,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P22 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When used for wine storage, this tank shall be equipped with and operated with a pressure-vacuum relief valve, which shall operate within 10% of the maximum allowable working pressure of the tank, operate in accordance with the manufacturer's instructions, and be permanently labeled with the operating pressure settings. [District Rule 4694] Federally Enforceable Through Title V Permit
2. When this tank is used for wine storage, the pressure-vacuum relief valve and storage tank shall remain in a gas-tight condition, except when the operating pressure of the tank exceeds the valve set pressure. A gas-tight condition shall be determined by measuring the gas leak in accordance with the procedures in EPA Method 21. [District Rule 4694] Federally Enforceable Through Title V Permit
3. The temperature of the wine stored in this tank shall be maintained at or below 75 degrees Fahrenheit. The temperature of the stored wine shall be determined and recorded at least once per week. For each batch of wine, the operator shall achieve the storage temperature of 75 degrees Fahrenheit or less within 60 days after completing fermentation, and shall maintain records to show when the required storage temperature of 75 degrees Fahrenheit or less was achieved. [District Rule 4694] Federally Enforceable Through Title V Permit
4. For each batch of must fermented in this tank, the operator shall record the fermentation completion date, the total gallons of must fermented, the average fermentation temperature and the uncontrolled fermentation emissions and fermentation emission reductions (calculated per the emission factors given in District Rule 4694). The information shall be recorded by the tank Permit to Operate number and by wine type, stated as either red wine or white wine. [District Rule 4694]
5. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
6. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-476-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
1,957 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 897 WITH PRESSURE VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-477-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
1,242 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 898 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-478-2 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
1,242 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 899 WITH PRESSURE/VACUUM VALVE

PERMIT UNIT REQUIREMENTS

1. When this tank is used for wine storage, the operator shall record, on a weekly basis, the total gallons of wine contained in the tank and the maximum temperature of the stored wine. [District Rule 4694] Federally Enforceable Through Title V Permit
2. All records shall be retained on-site for a period of at least five years and made available for District inspection upon request. [District Rule 4694] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-749-1 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
225 BHP, LIMITED TO 121.7 BHP @ 1800 RPM, FORD MODEL WSG-1068 RICH-BURN LPG/PROPANE-FIRED EMERGENCY-STANDBY IC ENGINE WITH NON-SELECTIVE CATALYTIC REDUCTION (NSCR) POWERING AN ELECTRICAL GENERATOR (CATERPILLAR G60F3 GENERATOR SET)

PERMIT UNIT REQUIREMENTS

1. This IC engine shall be equipped with a three-way catalyst. [District Rule 2201] Federally Enforceable Through Title V Permit
2. This engine shall be equipped with an operational non-resettable elapsed time meter or other APCO approved alternative. [District Rule 4702] Federally Enforceable Through Title V Permit
3. The exhaust stack shall vent vertically upward. The vertical exhaust flow shall not be impeded by a rain cap (flapper ok), roof overhang, or any other obstruction. [District Rule 4102]
4. This engine shall be operated and maintained in proper operating condition as recommended by the engine manufacturer or emissions control system supplier. [District Rule 4702] Federally Enforceable Through Title V Permit
5. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
6. Emissions from this IC engine shall not exceed any of the following limits: 0.52 g-NOx/bhp-hr, 0.175 g-PM10/bhp-hr, 3.14 g-CO/bhp-hr, or 0.032 g-VOC/bhp-hr. [District Rule 2201] Federally Enforceable Through Title V Permit
7. This IC engine shall be fired on LPG/propane gas only. [District Rule 2201] Federally Enforceable Through Title V Permit
8. During periods of operation for maintenance, testing, and required regulatory purposes, the permittee shall monitor the operational characteristics of the engine as recommended by the manufacturer or emission control system supplier (for example: check engine fluid levels, battery, cables and connections; change engine oil and filters; replace engine coolant; and/or other operational characteristics as recommended by the manufacturer or supplier). [District Rule 4702] Federally Enforceable Through Title V Permit
9. This engine shall be operated only for testing and maintenance of the engine, required regulatory purposes, and during emergency situations. Operation of the engine for maintenance, testing, and required regulatory purposes shall not exceed 100 hours per calendar year. [District Rule 4702] Federally Enforceable Through Title V Permit
10. An emergency situation is an unscheduled electrical power outage caused by sudden and reasonably unforeseen natural disasters or sudden and reasonably unforeseen events beyond the control of the permittee. [District Rule 4702] Federally Enforceable Through Title V Permit
11. This engine shall not be used to produce power for the electrical distribution system, as part of a voluntary utility demand reduction program, or for an interruptible power contract. [District Rule 4702] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

12. The permittee shall maintain monthly records of emergency and non-emergency operation. Records shall include the number of hours of emergency operation, the date and number of hours of all testing and maintenance operations, the purpose of the operation (for example: load testing, weekly testing, rolling blackout, general area power outage, etc.), the type of fuel used, and records of operational characteristics monitoring. For units with automated testing systems, the operator may, as an alternative to keeping records of actual operation for testing purposes, maintain a readily accessible written record of the automated testing schedule. [District Rule 4702] Federally Enforceable Through Title V Permit

13. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 4702] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-751-0 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
GASOLINE DISPENSING OPERATION WITH ONE 500 GALLON TRUSCO SUPERVAULT ABOVEGROUND STORAGE TANK SERVED BY STANDING LOSS CONTROL (VR-301-X), AND 1 FUELING POINT WITH 1 GASOLINE DISPENSING NOZZLE SERVED BY BALANCE PHASE II VAPOR RECOVERY SYSTEM (G-70-132-A)

PERMIT UNIT REQUIREMENTS

1. The Phase I and Phase II vapor recovery systems shall be installed and maintained in accordance with the manufacturer specifications and the ARB Executive Orders specified in this permit, including applicable rules and regulations of the Division of Measurement Standards of the Department of Food and Agriculture, the Office of the State Fire Marshal of the Department of Forestry and Fire Protection, the Division of Occupational Safety and Health of the Department of Industrial Relations, and the Division of Water Quality of the State Water Resources Control Board that have been made conditions of the certification. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
2. This gasoline storage and dispensing equipment shall not be used in retail sales, where gasoline dispensed by the unit is subject to payment of California sales tax on gasoline sales. [District Rule 4622] Federally Enforceable Through Title V Permit
3. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
4. The storage container(s) shall be installed, maintained, and operated such that they are leak-free. [District Rule 4621] Federally Enforceable Through Title V Permit
5. The Phase I and Phase II vapor recovery systems and gasoline dispensing equipment shall be maintained without leaks as determined in accordance with the test method specified in this permit. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
6. A leak is defined as the dripping of VOC-containing liquid at a rate of more than three (3) drops per minute, or the detection of any gaseous or vapor emissions with a concentration of total organic compound greater than 10,000 ppmv, as methane, above background when measured in accordance with EPA Test Method 21. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
7. No gasoline delivery vessel shall be operated or be allowed to operate unless valid State of California decals are displayed on the cargo container, which attest to the vapor integrity of the container. [District Rule 4621] Federally Enforceable Through Title V Permit
8. No person shall operate any ARB certified Phase II vapor recovery system or any portion thereof that has a major defect or an equipment defect that is identified in any applicable ARB Executive Order until the following conditions have been met: 1) the defect has been repaired, replaced, or adjusted as necessary to correct the defect; 2) the District has been notified, and the District has reinspected the system or authorized the system for use (such authorization shall not include the authority to operate the equipment prior to the correction of the defective components); and 3) all major defects, after repair, are duly entered into the Operations and Maintenance (O&M) manual. [District Rule 4622] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

9. Upon identification of any major defects, the permittee shall tag "Out-of-Order" all dispensing equipment for which vapor recovery has been impaired. Tagged equipment shall be rendered inoperable and the tag(s) shall not be removed until the defective equipment has been repaired, replaced, or adjusted, as necessary. In the case of defects identified by the District, tagged equipment shall be rendered inoperable, and the tag shall not be removed until the District has been notified of the repairs, and the District has either reinspected the system or authorized the tagged equipment for use. [District Rule 4622] Federally Enforceable Through Title V Permit

10. The permittee shall implement a periodic maintenance inspection program for the certified Phase II vapor recovery system consistent with the requirements of this permit. The program shall be documented in an operation and maintenance (O&M) manual and shall at a minimum contain the following information: 1) copies of all vapor recovery performance tests; 2) all applicable ARB Executive Orders, Approval Letters, and District Permits; 3) the manufacturer's specifications and instructions for installation, operation, repair, and maintenance required pursuant to ARB Certification Procedure CP-201, and any additional instruction provided by the manufacturer; 4) system and/or component testing requirements, including test schedules and passing criteria for each of the standard tests required by this permit (the owner/operator may include any non-ARB required diagnostic and other tests as part of the testing requirements), and 5) additional O&M instructions, if any, that are designed to ensure compliance with the applicable rules, regulations, ARB Executive Orders, and District permit conditions, including replacement schedules for failure or wear prone components. [District Rule 4622] Federally Enforceable Through Title V Permit

11. The permittee shall conduct periodic maintenance inspections based on the greatest monthly throughput of gasoline dispensed by the facility in the previous year as follows: A) less than 2,500 gallons - one day per month; B) 2,500 to less than 25,000 gallons - one day per week; or C) 25,000 gallons or greater - five days per week. All inspections shall be documented within the O & M Manual. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

12. Periodic maintenance inspections of the Phase I vapor recovery system shall include, at a minimum, verification that 1) the fill caps and vapor caps are not missing, damaged, or loose; 2) the fill cap gasket and vapor cap gaskets are not missing or damaged; 3) the fill adapter and vapor adapter are securely attached to the risers; 4) where applicable, the spring-loaded submerged fill tube seals properly against the coaxial tubing; 5) the dry break (poppet-valve) is not missing or damaged; and 6) the submerged fill tube is not missing or damaged. [District Rule 4621] Federally Enforceable Through Title V Permit

13. Periodic maintenance inspections of the Phase II vapor recovery system shall include, at a minimum, verification that 1) the following nozzle components are in place and in good condition as specified in ARB Executive Order as applicable: faceplate/facecone, bellows, latching device spring, vapor check valve, spout (proper diameter/vapor collection holes), insertion interlock mechanism, automatic shut-off mechanism, and hold open latch (unless prohibited by law or the local fire control authority); 2) the hoses are not torn, flattened or crimped; 3) the vapor path of the coaxial hoses associated with bellows equipped nozzles does not contain more than 100 ml of liquid if applicable; and 4) the vapor processing unit is functioning properly, for operations that are required to have or possess such a unit. [District Rule 4622] Federally Enforceable Through Title V Permit

14. In the event of a separation due to a drive off, the permittee shall, unless otherwise specified in the applicable ARB Executive Order, conduct a visual inspection of the affected equipment and either 1) perform qualified repairs on any damaged components and conduct applicable re-verification tests pursuant to the requirements of this permit, or 2) replace the affected nozzles, coaxial hoses, breakaway couplings, and any other damaged components with new or certified rebuilt components that are ARB certified. The activities shall be documented in accordance with the requirements of this permit before placing the affected equipment back in service. [District Rule 4622] Federally Enforceable Through Title V Permit

15. Only white paint, listed in the Executive Order specified in this permit for the Standing Loss Control System, shall be applied to the tank. The surface of the tank shall be prepared and the white paint shall be applied per manufacturer's specification. [District Rule 4621] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

16. The permittee shall maintain the following records: 1) receipt of sale that demonstrates the purchase date and amount of white paint purchased, 2) record of the name of personnel applying white paint to include the date of application, surface preparation description (i.e. scraping, sanding, abrasive blasting, primer etc.), method of application (i.e. brush, roller, air/airless sprayer), average ambient temperature (øF) during application, and atmospheric observations during application (i.e. sunny, cloudy, rain, etc.), 3) record of the name of personnel that installed the P/V vent valve, and 4) Technical Data Sheet and/or Material Safety Data Sheet of the white paint that describes the surface preparation, application, and material safety of the white paint. [District Rule 4621] Federally Enforceable Through Title V Permit
17. The gasoline throughput for this permit unit shall not exceed 18,000 gallons in any one calendar year. [District Rule 2201] Federally Enforceable Through Title V Permit
18. Emissions from this operation shall not exceed 0.5 lb-VOC/day. Emissions may be calculated as follows: [(# gallons delivered/day x 0.473 lb-VOC/1000gallons) + (# gallons dispensed/day x 0.893 lb-VOC/1000 gallons)] [District Rule 2201] Federally Enforceable Through Title V Permit
19. The permittee shall conduct all periodic vapor recovery system performance tests specified in this permit, no more than 30 days before or after the required compliance testing date, unless otherwise required under the applicable ARB Executive Order. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
20. For certified Phase II vapor recovery systems with liquid removal devices, the permittee shall perform and pass an ARB TP-201.6C Liquid Removal Test whenever the liquid in the vapor path exceeds 100 ml of liquid, or as required by the applicable ARB Executive Order. The amount of liquid in the vapor path shall be measured by lowering the gasoline dispensing nozzle into a container until such time that no more liquid drains from the nozzle. The amount of liquid drained into the container shall be measured using a graduated cylinder or graduated beaker. The vapor path shall be inspected according to the monitoring frequency as determined by monthly gasoline throughput. [District Rule 4622] Federally Enforceable Through Title V Permit
21. The permittee shall perform and pass a Static Leak Test for Aboveground Tanks using ARB TP-201.3B or TP-206.3 at least once every 12 months thereafter. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
22. A person conducting testing of, or repairs to, a certified vapor recovery system shall be in compliance with District Rule 1177 (Gasoline Dispensing Facility Tester Certification). [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
23. A person performing installation of, or maintenance on, a certified Phase I or Phase II vapor recovery system shall be certified by the ICC for Vapor Recovery System Installation and Repair, or work under the direct and personal supervision of an individual physically present at the work site who is certified. The ICC certification shall be renewed every 24 months. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
24. Proof of the ICC certification and all other certifications required by the Executive Order and installation and operation manual shall be made available onsite. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit
25. The permittee shall notify the District at least 7 days prior to each performance test. The test results shall be submitted to the District no later than 30 days after the completion of each test. [District Rule 4621] Federally Enforceable Through Title V Permit
26. The permittee shall maintain a copy of all test results. The test results shall be dated and shall contain the name, address, and telephone number of the company responsible for system installation and testing. [District Rule 4622] Federally Enforceable Through Title V Permit
27. The permittee shall maintain on the premises a log of any repairs made to the certified Phase I or Phase II vapor recovery system. The repair log shall include the following: 1) date and time of each repair; 2) the name and applicable certification numbers of the person(s) who performed the repair, and if applicable, the name, address and phone number of the person's employer; 3) description of service performed; 4) each component that was repaired, serviced, or removed; 5) each component that was installed as replacement, if applicable; and 6) receipts or other documents for parts used in the repair and, if applicable, work orders which shall include the name and signature of the person responsible for performing the repairs. [District Rule 4622] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

28. The O&M manual shall be kept at the dispensing operation and made available to any person who operates, inspects, maintains, repairs, or tests the equipment at the operation as well as to District personnel upon request. [District Rule 4622] Federally Enforceable Through Title V Permit

29. The permittee shall maintain daily, monthly and annual gasoline throughput records. [District Rules 2201, 4621 and 4622] Federally Enforceable Through Title V Permit

30. All records required by this permit shall be retained on-site for a period of at least five years and shall be made available for District inspection upon request. [District Rules 4621 and 4622] Federally Enforceable Through Title V Permit

San Joaquin Valley
Air Pollution Control District

PERMIT UNIT: C-628-752-4 **EXPIRATION DATE:** 11/30/2016

EQUIPMENT DESCRIPTION:
GRAPE SEED DRYING OPERATION CONSISTING OF DELUX MFG CO NATURAL GAS-FIRED TOWER GRAIN DRYER WITH A 7.3 MMBTU/HR DELUX MFG CO MODEL 24 ½" NOVA BURNER SYSTEM

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
2. The unit shall only be fired on PUC regulated natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
3. A non-resettable, totalizing mass or volumetric fuel flow meter shall be installed on the fuel line to the dryer burners. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [District Rule 4801 and Merced County Rule 407] Federally Enforceable Through Title V Permit
5. Emissions from the natural gas-fired unit shall not exceed any of the following limits: 0.05 lb-NOx/MMBtu, 0.00285 lb-SOx/MMBtu, 0.0076 lb-PM10/MMBtu, 0.051 lb-CO/MMBtu, or 0.0141 lb-VOC/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The total heat input shall not exceed 3,660 MMBtu/yr during any rolling 12-month period. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Visible emissions shall be observed once per calendar quarter during operation. Any indication of potential visible emissions in excess of the limits of Rule 4101 shall be corrected within 24 hours. If visible emissions cannot be corrected within 24 hours, a visible emissions test using EPA Method 9 shall be conducted. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
8. Permittee shall keep a record of the rolling 12-month heat input of the unit. This record shall be updated on a monthly basis. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Permittee shall maintain records which demonstrate the unit is fired exclusively on PUC regulated natural gas. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Operator shall maintain copies of all fuel invoices and supplier certifications. [District Rule 2201] Federally Enforceable Through Title V Permit
11. All records shall be maintained for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

ATTACHMENT C

Detailed Summary List of Facility Permits

Detailed Facility Report

For Facility=628 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

CBUS OPS DBA MISSION BELL WINERY
12667 ROAD 24
MADERA, CA 93637

FAC # C 628
STATUS: A
TELEPHONE:

TYPE: TitleV
TOXIC ID: 51902
EXPIRE ON: 11/30/2016
AREA: 2 / 308
INSP. DATE: 03/18

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-628-3-7	465 bhp IC engine	3020-10 D	1	525.00	525.00	A	465 BHP CATERPILLAR MODEL G379 NATURAL GAS-FIRED IC ENGINE WITH NON-SELECTIVE CATALYTIC REDUCTION (NSCR) POWERING AN ELECTRICAL GENERATOR WITH A HEAT RECOVERY CO-GENERATION SYSTEM (COMPLIANT DORMANT EMISSIONS UNIT)
C-628-4-10	97 MMBtu/hr	3020-02 H	1	1,128.00	1,128.00	A	97 MMBTU/HR NEBRASKA MODEL NS-F-81 NATURAL GAS-FIRED BOILER (WEST) WITH AN ALZETA MODEL CSB-1210 ULTRA LOW NOX BURNER
C-628-5-10	97 MMBtu/hr	3020-02 H	1	1,128.00	1,128.00	A	97 MMBTU/HR NEBRASKA MODEL NS-F-81 NATURAL GAS-FIRED BOILER (EAST) WITH AN ALZETA MODEL CSB-1210 ULTRA LOW NOX BURNER
C-628-6-3	186 Bhp IC engine	3020-10 B	1	129.00	129.00	A	186 BHP DETROIT DIESEL MODEL 6061AZ DIESEL-FIRED EMERGENCY IC ENGINE POWERING A FIREWATER PUMP
C-628-12-2	115 Hp	3020-01 D	1	345.00	345.00	A	PNEUMATICALLY LOADED DIATOMACEOUS EARTH FILTER POWDER STORAGE SILO WITH PNEUMATIC TRANSFER CAPABILITY TO FOUR MIXING TANKS, ALL SERVED INDIVIDUALLY BY DUST COLLECTORS
C-628-13-7	44 MMBtu/hr	3020-02 H	1	1,128.00	1,128.00	A	44 MMBTU/HR NEBRASKA MODEL NS-C-42-ECON NATURAL GAS-FIRED BOILER, EQUIPPED WITH AN ALZETA ULTRA-LOW NOX BURNER WITH A VARIABLE FREQUENCY DRIVE FOR AIR INTAKE FAN MOTOR AND OXYGEN TRIM EQUIPMENT IN EXHAUST STACK
C-628-15-2	126,766 Gallons	3020-05 E	1	270.00	270.00	A	126,766 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1 WITH PRESSURE/VACUUM VALVE
C-628-16-2	126,766 Gallons	3020-05 E	1	270.00	270.00	A	126,766 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 2 WITH PRESSURE/VACUUM VALVE
C-628-17-2	126,766 Gallons	3020-05 E	1	270.00	270.00	A	126,766 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 3 WITH PRESSURE/VACUUM VALVE
C-628-18-2	126,766 Gallons	3020-05 E	1	270.00	270.00	A	126,766 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 4 WITH PRESSURE/VACUUM VALVE
C-628-19-2	126,766 Gallons	3020-05 E	1	270.00	270.00	A	126,766 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 5 WITH PRESSURE/VACUUM VALVE
C-628-20-2	126,766 Gallons	3020-05 E	1	270.00	270.00	A	126,766 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 6 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report

For Facility=628 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-628-21-2	126,019 Gallons	3020-05 E	1	270.00	270.00	A	126,019 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 7 WITH PRESSURE/VACUUM VALVE
C-628-22-2	126,077 Gallons	3020-05 E	1	270.00	270.00	A	126,077 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 8 WITH PRESSURE/VACUUM VALVE
C-628-23-2	25,068 Gallons	3020-05 C	1	149.00	149.00	A	25,068 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 17 WITH PRESSURE/VACUUM VALVE
C-628-24-2	25,068 Gallons	3020-05 C	1	149.00	149.00	A	25,068 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 18 WITH PRESSURE/VACUUM VALVE
C-628-27-2	266,111 Gallons	3020-05 E	1	270.00	270.00	A	266,111 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 31 WITH PRESSURE/VACUUM VALVE
C-628-28-2	265,911 Gallons	3020-05 E	1	270.00	270.00	A	265,911 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 32 WITH PRESSURE/VACUUM VALVE
C-628-29-2	252,795 Gallons	3020-05 E	1	270.00	270.00	A	252,795 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 39 WITH PRESSURE/VACUUM VALVE
C-628-30-2	252,795 Gallons	3020-05 E	1	270.00	270.00	A	252,795 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 40 WITH PRESSURE/VACUUM VALVE
C-628-31-2	252,795 Gallons	3020-05 E	1	270.00	270.00	A	252,795 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 41 WITH PRESSURE/VACUUM VALVE
C-628-32-2	252,795 Gallons	3020-05 E	1	270.00	270.00	A	252,795 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 42 WITH PRESSURE/VACUUM VALVE
C-628-33-2	252,795 Gallons	3020-05 E	1	270.00	270.00	A	252,795 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 43 WITH PRESSURE/VACUUM VALVE
C-628-34-2	252,795 Gallons	3020-05 E	1	270.00	270.00	A	252,795 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 44 WITH PRESSURE/VACUUM VALVE
C-628-35-2	350,282 Gallons	3020-05 E	1	270.00	270.00	A	350,282 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 45 WITH PRESSURE/VACUUM VALVE
C-628-36-2	350,282 Gallons	3020-05 E	1	270.00	270.00	A	350,282 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 46 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report

For Facility=628 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-628-37-2	350,282 Gallons	3020-05 E	1	270.00	270.00	A	350,282 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 47 WITH PRESSURE/VACUUM VALVE
C-628-38-2	660,328 Gallons	3020-05 F	1	330.00	330.00	A	660,328 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 49 WITH PRESSURE/VACUUM VALVE
C-628-39-2	660,101 Gallons	3020-05 F	1	330.00	330.00	A	660,101 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 50 WITH PRESSURE/VACUUM VALVE
C-628-40-2	658,995 Gallons	3020-05 F	1	330.00	330.00	A	658,995 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 51 WITH PRESSURE/VACUUM VALVE
C-628-41-2	659,353 Gallons	3020-05 F	1	330.00	330.00	A	659,353 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 52 WITH PRESSURE/VACUUM VALVE
C-628-42-2	659,353 Gallons	3020-05 F	1	330.00	330.00	A	659,353 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 53 WITH PRESSURE/VACUUM VALVE
C-628-43-2	659,285 Gallons	3020-05 F	1	330.00	330.00	A	659,285 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 54 WITH PRESSURE/VACUUM VALVE
C-628-44-2	659,353 Gallons	3020-05 F	1	330.00	330.00	A	659,353 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 55 WITH PRESSURE/VACUUM VALVE
C-628-45-2	659,174 Gallons	3020-05 F	1	330.00	330.00	A	659,174 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 56 WITH PRESSURE/VACUUM VALVE
C-628-46-2	647,141 Gallons	3020-05 F	1	330.00	330.00	A	647,141 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 57 WITH PRESSURE/VACUUM VALVE
C-628-47-2	647,149 Gallons	3020-05 F	1	330.00	330.00	A	647,149 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 58 WITH PRESSURE/VACUUM VALVE
C-628-48-2	647,149 Gallons	3020-05 F	1	330.00	330.00	A	647,149 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 59 WITH PRESSURE/VACUUM VALVE
C-628-49-2	647,149 Gallons	3020-05 F	1	330.00	330.00	A	647,149 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 60 WITH PRESSURE/VACUUM VALVE
C-628-50-2	647,149 Gallons	3020-05 F	1	330.00	330.00	A	647,149 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 61 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report

For Facility=628 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-628-51-2	647,149 Gallons	3020-05 F	1	330.00	330.00	A	647,149 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 62 WITH PRESSURE/VACUUM VALVE
C-628-52-2	647,149 Gallons	3020-05 F	1	330.00	330.00	A	647,149 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 63 WITH PRESSURE/VACUUM VALVE
C-628-53-2	647,141 Gallons	3020-05 F	1	330.00	330.00	A	647,141 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 64 WITH PRESSURE/VACUUM VALVE
C-628-54-2	127,615 Gallons	3020-05 E	1	270.00	270.00	A	127,615 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 65 WITH PRESSURE/VACUUM VALVE
C-628-55-2	127,615 Gallons	3020-05 E	1	270.00	270.00	A	127,615 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 66 WITH PRESSURE/VACUUM VALVE
C-628-56-2	127,615 Gallons	3020-05 E	1	270.00	270.00	A	127,615 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 67 WITH PRESSURE/VACUUM VALVE
C-628-57-2	127,615 Gallons	3020-05 E	1	270.00	270.00	A	127,615 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 68 WITH PRESSURE/VACUUM VALVE
C-628-58-2	324,512 Gallons	3020-05 E	1	270.00	270.00	A	324,512 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 71 WITH PRESSURE/VACUUM VALVE
C-628-59-2	323,316 Gallons	3020-05 E	1	270.00	270.00	A	323,316 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 72 WITH PRESSURE/VACUUM VALVE
C-628-60-2	322,446 Gallons	3020-05 E	1	270.00	270.00	A	322,446 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 73 WITH PRESSURE/VACUUM VALVE
C-628-61-2	322,446 Gallons	3020-05 E	1	270.00	270.00	A	322,446 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 74 WITH PRESSURE/VACUUM VALVE
C-628-62-2	265,052 Gallons	3020-05 E	1	270.00	270.00	A	265,052 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 81 WITH PRESSURE/VACUUM VALVE
C-628-63-2	265,552 Gallons	3020-05 E	1	270.00	270.00	A	265,552 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 82 WITH PRESSURE/VACUUM VALVE
C-628-64-2	265,162 Gallons	3020-05 E	1	270.00	270.00	A	265,162 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 83 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report

For Facility=628 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-628-65-2	252,500 Gallons	3020-05 E	1	270.00	270.00	A	252,500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 84 WITH PRESSURE/VACUUM VALVE
C-628-66-2	127,600 Gallons	3020-05 E	1	270.00	270.00	A	127,600 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 85 WITH PRESSURE/VACUUM VALVE
C-628-67-2	128,100 Gallons	3020-05 E	1	270.00	270.00	A	128,100 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 86 WITH PRESSURE/VACUUM VALVE
C-628-68-2	128,000 Gallons	3020-05 E	1	270.00	270.00	A	128,000 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 87 WITH PRESSURE/VACUUM VALVE
C-628-69-2	128,300 Gallons	3020-05 E	1	270.00	270.00	A	128,300 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 88 WITH PRESSURE/VACUUM VALVE
C-628-70-2	127,615 Gallons	3020-05 E	1	270.00	270.00	A	127,615 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 89 WITH PRESSURE/VACUUM VALVE
C-628-71-2	172,945 Gallons	3020-05 E	1	270.00	270.00	A	172,945 GALLON CONCRETE OPEN RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 101
C-628-72-2	172,941 Gallons	3020-05 E	1	270.00	270.00	A	172,941 GALLON CONCRETE OPEN RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 102
C-628-73-2	17,170 Gallons	3020-05 B	1	103.00	103.00	A	17,170 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 110 WITH PRESSURE/VACUUM VALVE
C-628-74-2	17,170 Gallons	3020-05 B	1	103.00	103.00	A	17,170 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 111 WITH PRESSURE/VACUUM VALVE
C-628-75-2	17,170 Gallons	3020-05 B	1	103.00	103.00	A	17,170 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 112 WITH PRESSURE/VACUUM VALVE
C-628-76-2	17,170 Gallons	3020-05 B	1	103.00	103.00	A	17,170 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 113 WITH PRESSURE/VACUUM VALVE
C-628-77-2	17,170 Gallons	3020-05 B	1	103.00	103.00	A	17,170 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 114 WITH PRESSURE/VACUUM VALVE
C-628-78-2	17,170 Gallons	3020-05 B	1	103.00	103.00	A	17,170 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 115 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report

For Facility=628 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-628-79-2	122,247 Gallons	3020-05 E	1	270.00	270.00	A	122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 121 WITH PRESSURE/VACUUM VALVE
C-628-80-2	122,247 Gallons	3020-05 E	1	270.00	270.00	A	122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 122 WITH PRESSURE/VACUUM VALVE
C-628-81-2	122,247 Gallons	3020-05 E	1	270.00	270.00	A	122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 123 WITH PRESSURE/VACUUM VALVE
C-628-82-2	122,247 Gallons	3020-05 E	1	270.00	270.00	A	122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 124 WITH PRESSURE/VACUUM VALVE
C-628-83-2	122,247 Gallons	3020-05 E	1	270.00	270.00	A	122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 125 WITH PRESSURE/VACUUM VALVE
C-628-84-2	122,247 Gallons	3020-05 E	1	270.00	270.00	A	122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 126 WITH PRESSURE/VACUUM VALVE
C-628-85-2	122,247 Gallons	3020-05 E	1	270.00	270.00	A	122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 127 WITH PRESSURE/VACUUM VALVE
C-628-86-2	122,247 Gallons	3020-05 E	1	270.00	270.00	A	122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 128 WITH PRESSURE/VACUUM VALVE
C-628-87-2	122,247 Gallons	3020-05 E	1	270.00	270.00	A	122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 129 WITH PRESSURE/VACUUM VALVE
C-628-88-2	122,247 Gallons	3020-05 E	1	270.00	270.00	A	122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 130 WITH PRESSURE/VACUUM VALVE
C-628-89-2	122,247 Gallons	3020-05 E	1	270.00	270.00	A	122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 131 WITH PRESSURE/VACUUM VALVE
C-628-90-2	122,247 Gallons	3020-05 E	1	270.00	270.00	A	122,247 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 132 WITH PRESSURE/VACUUM VALVE
C-628-91-2	51,842 Gallons	3020-05 D	1	203.00	203.00	A	51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 133 WITH PRESSURE/VACUUM VALVE
C-628-92-2	51,842 Gallons	3020-05 D	1	203.00	203.00	A	51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 134 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report

For Facility=628 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-628-93-2	51,842 Gallons	3020-05 D	1	203.00	203.00	A	51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 135 WITH PRESSURE/VACUUM VALVE
C-628-94-2	51,842 Gallons	3020-05 D	1	203.00	203.00	A	51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 136 WITH PRESSURE/VACUUM VALVE
C-628-95-2	51,842 Gallons	3020-05 D	1	203.00	203.00	A	51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 137 WITH PRESSURE/VACUUM VALVE
C-628-96-2	51,842 Gallons	3020-05 D	1	203.00	203.00	A	51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 138 WITH PRESSURE/VACUUM VALVE
C-628-97-2	51,842 Gallons	3020-05 D	1	203.00	203.00	A	51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 139 WITH PRESSURE/VACUUM VALVE
C-628-98-2	51,842 Gallons	3020-05 D	1	203.00	203.00	A	51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 140 WITH PRESSURE/VACUUM VALVE
C-628-99-2	51,842 Gallons	3020-05 D	1	203.00	203.00	A	51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 141 WITH PRESSURE/VACUUM VALVE
C-628-100-2	51,842 Gallons	3020-05 D	1	203.00	203.00	A	51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 142 WITH PRESSURE/VACUUM VALVE
C-628-101-2	51,842 Gallons	3020-05 D	1	203.00	203.00	A	51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 143 WITH PRESSURE/VACUUM VALVE
C-628-102-2	51,842 Gallons	3020-05 D	1	203.00	203.00	A	51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 144 WITH PRESSURE/VACUUM VALVE
C-628-103-2	51,842 Gallons	3020-05 D	1	203.00	203.00	A	51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 145 WITH PRESSURE/VACUUM VALVE
C-628-104-2	51,842 Gallons	3020-05 D	1	203.00	203.00	A	51,842 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 146 WITH PRESSURE/VACUUM VALVE
C-628-105-2	5,837 Gallons	3020-05 B	1	103.00	103.00	A	5,834 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 150 WITH PRESSURE/VACUUM VALVE
C-628-106-2	5,832 Gallons	3020-05 B	1	103.00	103.00	A	5,832 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 151 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report

For Facility=628 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-628-107-2	4,489 Gallons	3020-05 A	1	83.00	83.00	A	4,489 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 152 WITH PRESSURE/VACUUM VALVE
C-628-108-2	4,489 Gallons	3020-05 A	1	83.00	83.00	A	4,489 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 153 WITH PRESSURE/VACUUM VALVE
C-628-133-2	11,186 Gallons	3020-05 B	1	103.00	103.00	A	11,186 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 224 WITH PRESSURE/VACUUM VALVE
C-628-134-2	11,186 Gallons	3020-05 B	1	103.00	103.00	A	11,186 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 225 WITH PRESSURE/VACUUM VALVE
C-628-135-2	10,428 Gallons	3020-05 B	1	103.00	103.00	A	10,428 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 226 WITH PRESSURE/VACUUM VALVE
C-628-136-2	63,543 Gallons	3020-05 D	1	203.00	203.00	A	63,543 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 401
C-628-137-2	63,269 Gallons	3020-05 D	1	203.00	203.00	A	63,269 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 402
C-628-138-2	63,461 Gallons	3020-05 D	1	203.00	203.00	A	63,461 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 403
C-628-139-2	62,977 Gallons	3020-05 D	1	203.00	203.00	A	62,977 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 404
C-628-140-2	62,913 Gallons	3020-05 D	1	203.00	203.00	A	62,913 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 405
C-628-141-2	63,174 Gallons	3020-05 D	1	203.00	203.00	A	63,174 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 406
C-628-142-2	63,654 Gallons	3020-05 D	1	203.00	203.00	A	63,654 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 407
C-628-143-2	63,403 Gallons	3020-05 D	1	203.00	203.00	A	63,403 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 408
C-628-144-2	63,284 Gallons	3020-05 D	1	203.00	203.00	A	63,284 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 409
C-628-145-2	62,919 Gallons	3020-05 D	1	203.00	203.00	A	62,919 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 410
C-628-146-2	62,999 Gallons	3020-05 D	1	203.00	203.00	A	62,999 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 411
C-628-147-2	63,000 Gallons	3020-05 D	1	203.00	203.00	A	63,000 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 412

Detailed Facility Report

For Facility=628 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-628-148-2	63,114 Gallons	3020-05 D	1	203.00	203.00	A	63,114 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 413
C-628-149-2	63,172 Gallons	3020-05 D	1	203.00	203.00	A	63,172 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 414
C-628-150-2	62,996 Gallons	3020-05 D	1	203.00	203.00	A	62,996 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 415
C-628-151-2	63,020 Gallons	3020-05 D	1	203.00	203.00	A	63,020 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 416
C-628-152-2	63,022 Gallons	3020-05 D	1	203.00	203.00	A	63,022 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 417
C-628-153-2	63,323 Gallons	3020-05 D	1	203.00	203.00	A	63,323 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 418
C-628-154-2	63,037 Gallons	3020-05 D	1	203.00	203.00	A	63,037 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 419
C-628-155-2	62.966 Gallons	3020-05 D	1	203.00	203.00	A	62,966 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 420
C-628-156-2	63,174 Gallons	3020-05 D	1	203.00	203.00	A	63,174 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 421
C-628-157-2	63,018 Gallons	3020-05 D	1	203.00	203.00	A	63,018 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 422
C-628-158-2	62,945 Gallons	3020-05 D	1	203.00	203.00	A	62,945 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 423
C-628-159-2	63,439 Gallons	3020-05 D	1	203.00	203.00	A	63,439 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 424
C-628-160-2	63,970 Gallons	3020-05 D	1	203.00	203.00	A	63,970 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 425
C-628-161-2	63,153 Gallons	3020-05 D	1	203.00	203.00	A	63,153 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 426
C-628-162-2	62,908 Gallons	3020-05 D	1	203.00	203.00	A	62,908 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 427
C-628-163-2	62,803 Gallons	3020-05 D	1	203.00	203.00	A	62,803 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 428
C-628-164-2	62,885 Gallons	3020-05 D	1	203.00	203.00	A	62,885 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 429
C-628-165-2	63,096 Gallons	3020-05 D	1	203.00	203.00	A	63,096 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 430

Detailed Facility Report

For Facility=628 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-628-166-2	63,181 Gallons	3020-05 D	1	203.00	203.00	A	63,181 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 431
C-628-167-2	62,834 Gallons	3020-05 D	1	203.00	203.00	A	62,834 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 432
C-628-168-2	62,908 Gallons	3020-05 D	1	203.00	203.00	A	62,908 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 433
C-628-169-2	62,786 Gallons	3020-05 D	1	203.00	203.00	A	62,786 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 434
C-628-170-2	63,456 Gallons	3020-05 D	1	203.00	203.00	A	63,456 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 435
C-628-171-2	62,994 Gallons	3020-05 D	1	203.00	203.00	A	62,994 GALLON CONCRETE ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 436
C-628-172-2	306,473 Gallons	3020-05 E	1	270.00	270.00	A	306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 500 WITH PRESSURE/VACUUM VALVE
C-628-173-2	306,473 Gallons	3020-05 E	1	270.00	270.00	A	306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 501 WITH PRESSURE/VACUUM VALVE
C-628-174-2	306,473 Gallons	3020-05 E	1	270.00	270.00	A	306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 502 WITH PRESSURE/VACUUM VALVE
C-628-175-2	306,473 Gallons	3020-05 E	1	270.00	270.00	A	306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 503 WITH PRESSURE/VACUUM VALVE
C-628-176-2	306,473 Gallons	3020-05 E	1	270.00	270.00	A	306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 504 WITH PRESSURE/VACUUM VALVE
C-628-177-2	306,473 Gallons	3020-05 E	1	270.00	270.00	A	306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 505 WITH PRESSURE/VACUUM VALVE
C-628-178-2	307,100 Gallons	3020-05 E	1	270.00	270.00	A	307,100 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 506 WITH PRESSURE/VACUUM VALVE
C-628-179-2	306,524 Gallons	3020-05 E	1	270.00	270.00	A	306,524 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 507 WITH PRESSURE/VACUUM VALVE
C-628-180-2	306,473 Gallons	3020-05 E	1	270.00	270.00	A	306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 508 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report

For Facility=628 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-628-181-2	306,473 Gallons	3020-05 E	1	270.00	270.00	A	306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 509 WITH PRESSURE/VACUUM VALVE
C-628-182-2	306,473 Gallons	3020-05 E	1	270.00	270.00	A	306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 510 WITH PRESSURE/VACUUM VALVE
C-628-183-2	306,473 Gallons	3020-05 E	1	270.00	270.00	A	306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 511 WITH PRESSURE/VACUUM VALVE
C-628-184-2	307,105 Gallons	3020-05 E	1	270.00	270.00	A	307,105 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 512 WITH PRESSURE/VACUUM VALVE
C-628-185-2	306,473 Gallons	3020-05 E	1	270.00	270.00	A	306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 513 WITH PRESSURE/VACUUM VALVE
C-628-186-2	306,473 Gallons	3020-05 E	1	270.00	270.00	A	306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 514 WITH PRESSURE/VACUUM VALVE
C-628-187-2	306,473 Gallons	3020-05 E	1	270.00	270.00	A	306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 515 WITH PRESSURE/VACUUM VALVE
C-628-188-2	306,473 Gallons	3020-05 E	1	270.00	270.00	A	306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 516 WITH PRESSURE/VACUUM VALVE
C-628-189-2	306,473 Gallons	3020-05 E	1	270.00	270.00	A	306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 517 WITH PRESSURE/VACUUM VALVE
C-628-190-2	306,473 Gallons	3020-05 E	1	270.00	270.00	A	306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 518 WITH PRESSURE/VACUUM VALVE
C-628-191-2	306,473 Gallons	3020-05 E	1	270.00	270.00	A	306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 519 WITH PRESSURE/VACUUM VALVE
C-628-192-2	306,627 Gallons	3020-05 E	1	270.00	270.00	A	306,627 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 520 WITH PRESSURE/VACUUM VALVE
C-628-193-2	306,682 Gallons	3020-05 E	1	270.00	270.00	A	306,682 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 521 WITH PRESSURE/VACUUM VALVE
C-628-194-2	307,160 Gallons	3020-05 E	1	270.00	270.00	A	307,160 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 522 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report

For Facility=628 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-628-195-2	306,473 Gallons	3020-05 E	1	270.00	270.00	A	306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 523 WITH PRESSURE/VACUUM VALVE
C-628-196-2	306,473 Gallons	3020-05 E	1	270.00	270.00	A	306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 524 WITH PRESSURE/VACUUM VALVE
C-628-197-2	306,473 Gallons	3020-05 E	1	270.00	270.00	A	306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 525 WITH PRESSURE/VACUUM VALVE
C-628-198-2	306,473 Gallons	3020-05 E	1	270.00	270.00	A	306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 526 WITH PRESSURE/VACUUM VALVE
C-628-199-2	306,473 Gallons	3020-05 E	1	270.00	270.00	A	306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 527 WITH PRESSURE/VACUUM VALVE
C-628-200-2	306,473 Gallons	3020-05 E	1	270.00	270.00	A	306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 528 WITH PRESSURE/VACUUM VALVE
C-628-201-2	306,473 Gallons	3020-05 E	1	270.00	270.00	A	306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 529 WITH PRESSURE/VACUUM VALVE
C-628-202-2	306,473 Gallons	3020-05 E	1	270.00	270.00	A	306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 530 WITH PRESSURE/VACUUM VALVE
C-628-203-2	306,473 Gallons	3020-05 E	1	270.00	270.00	A	306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 531 WITH PRESSURE/VACUUM VALVE
C-628-204-2	306,473 Gallons	3020-05 E	1	270.00	270.00	A	306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 532 WITH PRESSURE/VACUUM VALVE
C-628-206-2	306,924 Gallons	3020-05 E	1	270.00	270.00	A	306,924 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 534 WITH PRESSURE/VACUUM VALVE
C-628-208-2	306,473 Gallons	3020-05 E	1	270.00	270.00	A	306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 536 WITH PRESSURE/VACUUM VALVE
C-628-210-2	306,473 Gallons	3020-05 E	1	270.00	270.00	A	306,473 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 538 WITH PRESSURE/VACUUM VALVE
C-628-211-2	350,136 Gallons	3020-05 E	1	270.00	270.00	A	350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 550 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report

For Facility=628 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-628-212-2	350,136 Gallons	3020-05 E	1	270.00	270.00	A	350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 551 WITH PRESSURE/VACUUM VALVE
C-628-213-2	350,136 Gallons	3020-05 E	1	270.00	270.00	A	350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 552 WITH PRESSURE/VACUUM VALVE
C-628-215-2	350,136 Gallons	3020-05 E	1	270.00	270.00	A	350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 554 WITH PRESSURE/VACUUM VALVE
C-628-216-2	350,136 Gallons	3020-05 E	1	270.00	270.00	A	350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 555 WITH PRESSURE/VACUUM VALVE
C-628-217-2	350,136 Gallons	3020-05 E	1	270.00	270.00	A	350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 556 WITH PRESSURE/VACUUM VALVE
C-628-219-2	350,136 Gallons	3020-05 E	1	270.00	270.00	A	350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 558 WITH PRESSURE/VACUUM VALVE
C-628-220-2	350,136 Gallons	3020-05 E	1	270.00	270.00	A	350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 559 WITH PRESSURE/VACUUM VALVE
C-628-221-2	350,136 Gallons	3020-05 E	1	270.00	270.00	A	350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 560 WITH PRESSURE/VACUUM VALVE
C-628-223-2	350,136 Gallons	3020-05 E	1	270.00	270.00	A	350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 562 WITH PRESSURE/VACUUM VALVE
C-628-224-2	350,136 Gallons	3020-05 E	1	270.00	270.00	A	350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 563 WITH PRESSURE/VACUUM VALVE
C-628-225-2	350,136 Gallons	3020-05 E	1	270.00	270.00	A	350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 564 WITH PRESSURE/VACUUM VALVE
C-628-227-2	350,136 Gallons	3020-05 E	1	270.00	270.00	A	350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 566 WITH PRESSURE/VACUUM VALVE
C-628-229-2	350,136 Gallons	3020-05 E	1	270.00	270.00	A	350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 568 WITH PRESSURE/VACUUM VALVE
C-628-231-2	350,136 Gallons	3020-05 E	1	270.00	270.00	A	350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 570 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report

For Facility=628 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-628-233-2	350,136 Gallons	3020-05 E	1	270.00	270.00	A	350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 572 WITH PRESSURE/VACUUM VALVE
C-628-237-2	350,136 Gallons	3020-05 E	1	270.00	270.00	A	350,136 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 576 WITH PRESSURE/VACUUM VALVE
C-628-238-2	64,452 Gallons	3020-05 D	1	203.00	203.00	A	64,452 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 600 WITH PRESSURE/VACUUM VALVE
C-628-239-2	64,452 Gallons	3020-05 D	1	203.00	203.00	A	64;452 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 601 WITH PRESSURE/VACUUM VALVE
C-628-240-2	64,452 Gallons	3020-05 D	1	203.00	203.00	A	64,452 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 602 WITH PRESSURE/VACUUM VALVE
C-628-241-2	64,452 Gallons	3020-05 D	1	203.00	203.00	A	64,452 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 603 WITH PRESSURE/VACUUM VALVE
C-628-242-2	64,452 Gallons	3020-05 D	1	203.00	203.00	A	64,452 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 604 WITH PRESSURE/VACUUM VALVE
C-628-243-2	64,452 Gallons	3020-05 D	1	203.00	203.00	A	64,452 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 605 WITH PRESSURE/VACUUM VALVE
C-628-244-2	32,816 Gallons	3020-05 C	1	149.00	149.00	A	32,816 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 606 WITH PRESSURE/VACUUM VALVE
C-628-245-2	32,816 Gallons	3020-05 C	1	149.00	149.00	A	32,816 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 607 WITH PRESSURE/VACUUM VALVE
C-628-246-2	32,816 Gallons	3020-05 C	1	149.00	149.00	A	32,816 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 608 WITH PRESSURE/VACUUM VALVE
C-628-247-2	32,816 Gallons	3020-05 C	1	149.00	149.00	A	32,816 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 609 WITH PRESSURE/VACUUM VALVE
C-628-248-2	32,816 Gallons	3020-05 C	1	149.00	149.00	A	32,816 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 610 WITH PRESSURE/VACUUM VALVE
C-628-249-2	32,816 Gallons	3020-05 C	1	149.00	149.00	A	32,816 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 611 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report

For Facility=628 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-628-250-2	20,947 Gallons	3020-05 C	1	149.00	149.00	A	20,947 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 612 WITH PRESSURE/VACUUM VALVE
C-628-251-2	20,947 Gallons	3020-05 C	1	149.00	149.00	A	20,947 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 613 WITH PRESSURE/VACUUM VALVE
C-628-254-2	3,175 Gallons	3020-05 A	1	83.00	83.00	A	3,175 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 793 WITH PRESSURE/VACUUM VALVE
C-628-255-2	3,175 Gallons	3020-05 A	1	83.00	83.00	A	3,175 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 794 WITH PRESSURE/VACUUM VALVE
C-628-256-2	3,175 Gallons	3020-05 A	1	83.00	83.00	A	3,175 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 795 WITH PRESSURE/VACUUM VALVE
C-628-257-2	13,536 Gallons	3020-05 B	1	103.00	103.00	A	13,536 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 797 WITH PRESSURE/VACUUM VALVE
C-628-258-2	13,536 Gallons	3020-05 B	1	103.00	103.00	A	13,536 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 798 WITH PRESSURE/VACUUM VALVE
C-628-259-2	13,536 Gallons	3020-05 B	1	103.00	103.00	A	13,536 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 799 WITH PRESSURE/VACUUM VALVE
C-628-260-2	63,666 Gallons	3020-05 D	1	203.00	203.00	A	63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 800 WITH PRESSURE/VACUUM VALVE
C-628-261-2	63,666 Gallons	3020-05 D	1	203.00	203.00	A	63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 801 WITH PRESSURE/VACUUM VALVE
C-628-262-2	63,666 Gallons	3020-05 D	1	203.00	203.00	A	63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 802 WITH PRESSURE/VACUUM VALVE
C-628-263-2	63,666 Gallons	3020-05 D	1	203.00	203.00	A	63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 803 WITH PRESSURE/VACUUM VALVE
C-628-264-2	63,666 Gallons	3020-05 D	1	203.00	203.00	A	63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 804 WITH PRESSURE/VACUUM VALVE
C-628-265-2	63,666 Gallons	3020-05 D	1	203.00	203.00	A	63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 805 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report

For Facility=628 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-628-266-2	63,666 Gallons	3020-05 D	1	203.00	203.00	A	63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 806 WITH PRESSURE/VACUUM VALVE
C-628-267-2	63,666 Gallons	3020-05 D	1	203.00	203.00	A	63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 807 WITH PRESSURE/VACUUM VALVE
C-628-268-2	63,666 Gallons	3020-05 D	1	203.00	203.00	A	63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 808 WITH PRESSURE/VACUUM VALVE
C-628-269-2	63,666 Gallons	3020-05 D	1	203.00	203.00	A	63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 809 WITH PRESSURE/VACUUM VALVE
C-628-270-2	63,666 Gallons	3020-05 D	1	203.00	203.00	A	63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 810 WITH PRESSURE/VACUUM VALVE
C-628-271-2	63,666 Gallons	3020-05 D	1	203.00	203.00	A	63,666 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 811 WITH PRESSURE/VACUUM VALVE
C-628-272-2	6,933 Gallons	3020-05 B	1	103.00	103.00	A	6,933 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 812 WITH PRESSURE/VACUUM VALVE
C-628-273-2	6,933 Gallons	3020-05 B	1	103.00	103.00	A	6,933 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 813 WITH PRESSURE/VACUUM VALVE
C-628-274-2	6,933 Gallons	3020-05 B	1	103.00	103.00	A	6,933 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 814 WITH PRESSURE/VACUUM VALVE
C-628-275-2	6,933 Gallons	3020-05 B	1	103.00	103.00	A	6,933 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 815 WITH PRESSURE/VACUUM VALVE
C-628-276-2	260,516 Gallons	3020-05 E	1	270.00	270.00	A	260,516 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 850 WITH PRESSURE/VACUUM VALVE
C-628-277-2	260,500 Gallons	3020-05 E	1	270.00	270.00	A	260,500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 851 WITH PRESSURE/VACUUM VALVE
C-628-278-2	260,500 Gallons	3020-05 E	1	270.00	270.00	A	260,500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 852 WITH PRESSURE/VACUUM VALVE
C-628-279-2	260,500 Gallons	3020-05 E	1	270.00	270.00	A	260,500 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 853 WITH PRESSURE/VACUUM VALVE

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-628-280-2	260,516 Gallons	3020-05 E	1	270.00	270.00	A	260,516 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 854 WITH PRESSURE/VACUUM VALVE
C-628-281-2	122,975 Gallons	3020-05 E	1	270.00	270.00	A	122,975 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 855 WITH PRESSURE/VACUUM VALVE
C-628-282-2	122,975 Gallons	3020-05 E	1	270.00	270.00	A	122,975 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 856 WITH PRESSURE/VACUUM VALVE
C-628-283-2	122,975 Gallons	3020-05 E	1	270.00	270.00	A	122,975 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 857 WITH PRESSURE/VACUUM VALVE
C-628-284-2	122,975 Gallons	3020-05 E	1	270.00	270.00	A	122,975 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 858 WITH PRESSURE/VACUUM VALVE
C-628-285-2	122,975 Gallons	3020-05 E	1	270.00	270.00	A	122,975 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 859 WITH PRESSURE/VACUUM VALVE
C-628-286-2	122,975 Gallons	3020-05 E	1	270.00	270.00	A	122,975 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 860 WITH PRESSURE/VACUUM VALVE
C-628-287-2	122,975 Gallons	3020-05 E	1	270.00	270.00	A	122,975 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 861 WITH PRESSURE/VACUUM VALVE
C-628-288-2	122,975 Gallons	3020-05 E	1	270.00	270.00	A	122,975 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 862 WITH PRESSURE/VACUUM VALVE
C-628-289-2	122,975 Gallons	3020-05 E	1	270.00	270.00	A	122,975 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 863 WITH PRESSURE/VACUUM VALVE
C-628-290-2	122,975 Gallons	3020-05 E	1	270.00	270.00	A	122,975 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 864 WITH PRESSURE/VACUUM VALVE
C-628-291-2	10,409 Gallons	3020-05 B	1	103.00	103.00	A	10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 866 WITH PRESSURE/VACUUM VALVE
C-628-292-2	10,409 Gallons	3020-05 B	1	103.00	103.00	A	10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 867 WITH PRESSURE/VACUUM VALVE
C-628-293-2	10,409 Gallons	3020-05 B	1	103.00	103.00	A	10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 868 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report

For Facility=628 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-628-294-2	10,409 Gallons	3020-05 B	1	103.00	103.00	A	10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 869 WITH PRESSURE/VACUUM VALVE
C-628-295-2	10,409 Gallons	3020-05 B	1	103.00	103.00	A	10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 870 WITH PRESSURE/VACUUM VALVE
C-628-296-2	10,409 Gallons	3020-05 B	1	103.00	103.00	A	10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 871 WITH PRESSURE/VACUUM VALVE
C-628-297-2	10,409 Gallons	3020-05 B	1	103.00	103.00	A	10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 872 WITH PRESSURE/VACUUM VALVE
C-628-298-2	10,409 Gallons	3020-05 B	1	103.00	103.00	A	10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 873 WITH PRESSURE/VACUUM VALVE
C-628-299-2	10,409 Gallons	3020-05 B	1	103.00	103.00	A	10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 874 WITH PRESSURE/VACUUM VALVE
C-628-300-2	10,409 Gallons	3020-05 B	1	103.00	103.00	A	10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 875 WITH PRESSURE/VACUUM VALVE
C-628-301-2	10,409 Gallons	3020-05 B	1	103.00	103.00	A	10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 876 WITH PRESSURE/VACUUM VALVE
C-628-302-2	10,409 Gallons	3020-05 B	1	103.00	103.00	A	10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 877 WITH PRESSURE/VACUUM VALVE
C-628-303-2	10,409 Gallons	3020-05 B	1	103.00	103.00	A	10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 878 WITH PRESSURE/VACUUM VALVE
C-628-304-2	10,409 Gallons	3020-05 B	1	103.00	103.00	A	10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 879 WITH PRESSURE/VACUUM VALVE
C-628-305-2	10,409 Gallons	3020-05 B	1	103.00	103.00	A	10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 880 WITH PRESSURE/VACUUM VALVE
C-628-306-2	10,409 Gallons	3020-05 B	1	103.00	103.00	A	10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 881 WITH PRESSURE/VACUUM VALVE
C-628-307-2	10,409 Gallons	3020-05 B	1	103.00	103.00	A	10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 882 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report

For Facility=628 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-628-308-2	10,409 Gallons	3020-05 B	1	103.00	103.00	A	10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 883 WITH PRESSURE/VACUUM VALVE
C-628-309-2	10,409 Gallons	3020-05 B	1	103.00	103.00	A	10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 884 WITH PRESSURE/VACUUM VALVE
C-628-310-2	10,409 Gallons	3020-05 B	1	103.00	103.00	A	10,409 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 885 WITH PRESSURE/VACUUM VALVE
C-628-311-2	20,740 Gallons	3020-05 C	1	149.00	149.00	A	20,740 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 886 WITH PRESSURE/VACUUM VALVE
C-628-312-2	20,740 Gallons	3020-05 C	1	149.00	149.00	A	20,740 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 887 WITH PRESSURE/VACUUM VALVE
C-628-313-2	20,740 Gallons	3020-05 C	1	149.00	149.00	A	20,740 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 888 WITH PRESSURE/VACUUM VALVE
C-628-314-2	20,740 Gallons	3020-05 C	1	149.00	149.00	A	20,740 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 889 WITH PRESSURE/VACUUM VALVE
C-628-315-2	20,740 Gallons	3020-05 C	1	149.00	149.00	A	20,740 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 890 WITH PRESSURE/VACUUM VALVE
C-628-316-2	20,740 Gallons	3020-05 C	1	149.00	149.00	A	20,740 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 891 WITH PRESSURE/VACUUM VALVE
C-628-317-2	20,740 Gallons	3020-05 C	1	149.00	149.00	A	20,740 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 892 WITH PRESSURE/VACUUM VALVE
C-628-318-2	20,740 Gallons	3020-05 C	1	149.00	149.00	A	20,740 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 893 WITH PRESSURE/VACUUM VALVE
C-628-319-2	20,740 Gallons	3020-05 C	1	149.00	149.00	A	20,740 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 894 WITH PRESSURE/VACUUM VALVE
C-628-320-2	20,740 Gallons	3020-05 C	1	149.00	149.00	A	20,740 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 895 WITH PRESSURE/VACUUM VALVE
C-628-321-2	62,390 Gallons	3020-05 D	1	203.00	203.00	A	62,390 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 900 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report

For Facility=628 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-628-322-2	128,200 Gallons	3020-05 E	1	270.00	270.00	A	128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 901 WITH PRESSURE/VACUUM VALVE
C-628-323-2	128,200 Gallons	3020-05 E	1	270.00	270.00	A	128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 902 WITH PRESSURE/VACUUM VALVE
C-628-324-2	8,114 Gallons	3020-05 B	1	103.00	103.00	A	8,114 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 903 WITH PRESSURE/VACUUM VALVE
C-628-325-2	128,200 Gallons	3020-05 E	1	270.00	270.00	A	128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 904 WITH PRESSURE/VACUUM VALVE
C-628-326-2	8,114 Gallons	3020-05 B	1	103.00	103.00	A	8,114 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 905 WITH PRESSURE/VACUUM VALVE
C-628-327-2	128,200 Gallons	3020-05 E	1	270.00	270.00	A	128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 906 WITH PRESSURE/VACUUM VALVE
C-628-328-2	8,114 Gallons	3020-05 B	1	103.00	103.00	A	8,114 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 907 WITH PRESSURE/VACUUM VALVE
C-628-329-2	128,200 Gallons	3020-05 E	1	270.00	270.00	A	128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 908 WITH PRESSURE/VACUUM VALVE
C-628-330-2	128,200 Gallons	3020-05 E	1	270.00	270.00	A	128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 909 WITH PRESSURE/VACUUM VALVE
C-628-331-2	8,114 Gallons	3020-05 B	1	103.00	103.00	A	8,114 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 910 WITH PRESSURE/VACUUM VALVE
C-628-332-2	128,200 Gallons	3020-05 E	1	270.00	270.00	A	128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 911 WITH PRESSURE/VACUUM VALVE
C-628-333-2	8,114 Gallons	3020-05 B	1	103.00	103.00	A	8,114 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 912 WITH PRESSURE/VACUUM VALVE
C-628-334-2	128,200 Gallons	3020-05 E	1	270.00	270.00	A	128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 913 WITH PRESSURE/VACUUM VALVE
C-628-335-2	8,114 Gallons	3020-05 B	1	103.00	103.00	A	8,114 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 914 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report

For Facility=628 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-628-336-2	128,200 Gallons	3020-05 E	1	270.00	270.00	A	128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 915 WITH PRESSURE/VACUUM VALVE
C-628-337-2	8,114 Gallons	3020-05 B	1	103.00	103.00	A	8,114 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 916 WITH PRESSURE/VACUUM VALVE
C-628-338-2	128,200 Gallons	3020-05 E	1	270.00	270.00	A	128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 917 WITH PRESSURE/VACUUM VALVE
C-628-339-2	19,980 Gallons	3020-05 C	1	149.00	149.00	A	19,980 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 918 WITH PRESSURE/VACUUM VALVE
C-628-340-2	19,980 Gallons	3020-05 C	1	149.00	149.00	A	19,980 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 919 WITH PRESSURE/VACUUM VALVE
C-628-341-2	128,200 Gallons	3020-05 E	1	270.00	270.00	A	128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 920 WITH PRESSURE/VACUUM VALVE
C-628-342-2	8,114 Gallons	3020-05 B	1	103.00	103.00	A	8,114 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 921 WITH PRESSURE/VACUUM VALVE
C-628-343-2	128,200 Gallons	3020-05 E	1	270.00	270.00	A	128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 922 WITH PRESSURE/VACUUM VALVE
C-628-344-2	8,114 Gallons	3020-05 B	1	103.00	103.00	A	8,114 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 923 WITH PRESSURE/VACUUM VALVE
C-628-345-2	128,200 Gallons	3020-05 E	1	270.00	270.00	A	128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 924 WITH PRESSURE/VACUUM VALVE
C-628-346-2	8,114 Gallons	3020-05 B	1	103.00	103.00	A	8,114 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 925 WITH PRESSURE/VACUUM VALVE
C-628-347-2	128,200 Gallons	3020-05 E	1	270.00	270.00	A	128,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 926 WITH PRESSURE/VACUUM VALVE
C-628-348-2	19,980 Gallons	3020-05 B	1	103.00	103.00	A	19,980 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 927 WITH PRESSURE/VACUUM VALVE
C-628-349-2	19,980 Gallons	3020-05 B	1	103.00	103.00	A	19,980 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 928 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report

For Facility=628 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-628-350-2	62,390 Gallons	3020-05 D	1	203.00	203.00	A	62,390 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 929 WITH PRESSURE/VACUUM VALVE
C-628-351-2	62,390 Gallons	3020-05 D	1	203.00	203.00	A	62,390 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 930 WITH PRESSURE/VACUUM VALVE
C-628-352-2	62,390 Gallons	3020-05 D	1	203.00	203.00	A	62,390 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 931 WITH PRESSURE/VACUUM VALVE
C-628-353-2	62,390 Gallons	3020-05 D	1	203.00	203.00	A	62,390 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 932 WITH PRESSURE/VACUUM VALVE
C-628-354-2	62,390 Gallons	3020-05 D	1	203.00	203.00	A	62,390 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 933 WITH PRESSURE/VACUUM VALVE
C-628-355-2	62,390 Gallons	3020-05 D	1	203.00	203.00	A	62,390 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 934 WITH PRESSURE/VACUUM VALVE
C-628-356-2	62,390 Gallons	3020-05 D	1	203.00	203.00	A	62,390 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 935 WITH PRESSURE/VACUUM VALVE
C-628-357-2	62,390 Gallons	3020-05 D	1	203.00	203.00	A	62,390 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 936 WITH PRESSURE/VACUUM VALVE
C-628-358-2	263,616 Gallons	3020-05 E	1	270.00	270.00	A	263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 937 WITH PRESSURE/VACUUM VALVE
C-628-359-2	263,616 Gallons	3020-05 E	1	270.00	270.00	A	263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 938 WITH PRESSURE/VACUUM VALVE
C-628-360-2	263,616 Gallons	3020-05 E	1	270.00	270.00	A	263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 939 WITH PRESSURE/VACUUM VALVE
C-628-361-2	263,616 Gallons	3020-05 E	1	270.00	270.00	A	263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 940 WITH PRESSURE/VACUUM VALVE
C-628-362-2	263,616 Gallons	3020-05 E	1	270.00	270.00	A	263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 941 WITH PRESSURE/VACUUM VALVE
C-628-363-2	263,616 Gallons	3020-05 E	1	270.00	270.00	A	263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 942 WITH PRESSURE/VACUUM VALVE

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-628-364-2	263,616 Gallons	3020-05 E	1	270.00	270.00	A	263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 943 WITH PRESSURE/VACUUM VALVE
C-628-365-2	263,616 Gallons	3020-05 E	1	270.00	270.00	A	263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 944 WITH PRESSURE/VACUUM VALVE
C-628-366-2	263,616 Gallons	3020-05 E	1	270.00	270.00	A	263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 945 WITH PRESSURE/VACUUM VALVE
C-628-367-2	263,616 Gallons	3020-05 E	1	270.00	270.00	A	263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 946 WITH PRESSURE/VACUUM VALVE
C-628-368-2	263,616 Gallons	3020-05 E	1	270.00	270.00	A	263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 947 WITH PRESSURE/VACUUM VALVE
C-628-369-2	263,616 Gallons	3020-05 E	1	270.00	270.00	A	263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 948 WITH PRESSURE/VACUUM VALVE
C-628-370-2	263,616 Gallons	3020-05 E	1	270.00	270.00	A	263,616 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 949 WITH PRESSURE/VACUUM VALVE
C-628-371-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 950 WITH PRESSURE/VACUUM VALVE
C-628-372-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 951 WITH PRESSURE/VACUUM VALVE
C-628-373-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 952 WITH PRESSURE/VACUUM VALVE
C-628-374-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 953 WITH PRESSURE/VACUUM VALVE
C-628-375-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 954 WITH PRESSURE/VACUUM VALVE
C-628-376-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 955 WITH PRESSURE/VACUUM VALVE
C-628-377-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 956 WITH PRESSURE/VACUUM VALVE

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-628-378-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 957 WITH PRESSURE/VACUUM VALVE
C-628-379-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 958 WITH PRESSURE/VACUUM VALVE
C-628-380-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 959 WITH PRESSURE/VACUUM VALVE
C-628-381-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 960 WITH PRESSURE/VACUUM VALVE
C-628-382-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 961 WITH PRESSURE/VACUUM VALVE
C-628-383-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 962 WITH PRESSURE/VACUUM VALVE
C-628-384-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 963 WITH PRESSURE/VACUUM VALVE
C-628-385-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 964 WITH PRESSURE/VACUUM VALVE
C-628-386-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 965 WITH PRESSURE/VACUUM VALVE
C-628-387-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 966 WITH PRESSURE/VACUUM VALVE
C-628-388-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 967 WITH PRESSURE/VACUUM VALVE
C-628-389-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 968 WITH PRESSURE/VACUUM VALVE
C-628-390-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 969 WITH PRESSURE/VACUUM VALVE
C-628-391-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 970 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report

For Facility=628 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-628-392-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 971 WITH PRESSURE/VACUUM VALVE
C-628-393-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 972 WITH PRESSURE/VACUUM VALVE
C-628-394-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 973 WITH PRESSURE/VACUUM VALVE
C-628-395-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 974 WITH PRESSURE/VACUUM VALVE
C-628-396-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 975 WITH PRESSURE/VACUUM VALVE
C-628-397-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 976 WITH PRESSURE/VACUUM VALVE
C-628-398-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 977 WITH PRESSURE/VACUUM VALVE
C-628-399-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 978 WITH PRESSURE/VACUUM VALVE
C-628-400-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 979 WITH PRESSURE/VACUUM VALVE
C-628-401-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 980 WITH PRESSURE/VACUUM VALVE
C-628-402-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 981 WITH PRESSURE/VACUUM VALVE
C-628-403-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 982 WITH PRESSURE/VACUUM VALVE
C-628-404-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 983 WITH PRESSURE/VACUUM VALVE
C-628-405-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 984 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report

For Facility=628 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-628-406-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 985 WITH PRESSURE/VACUUM VALVE
C-628-407-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 986 WITH PRESSURE/VACUUM VALVE
C-628-408-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 987 WITH PRESSURE/VACUUM VALVE
C-628-409-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 988 WITH PRESSURE/VACUUM VALVE
C-628-410-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 989 WITH PRESSURE/VACUUM VALVE
C-628-411-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 990 WITH PRESSURE/VACUUM VALVE
C-628-412-2	32,112 Gallons	3020-05 C	1	149.00	149.00	A	32,112 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 991 WITH PRESSURE/VACUUM VALVE
C-628-413-2	10,643 Gallons	3020-05 B	1	103.00	103.00	A	10,643 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 992 WITH PRESSURE/VACUUM VALVE
C-628-414-2	4,527 Gallons	3020-05 A	1	83.00	83.00	A	4,527 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 993 WITH PRESSURE/VACUUM VALVE
C-628-415-2	10,643 Gallons	3020-05 B	1	103.00	103.00	A	10,643 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 994 WITH PRESSURE/VACUUM VALVE
C-628-416-2	10,643 Gallons	3020-05 B	1	103.00	103.00	A	10,643 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 995 WITH PRESSURE/VACUUM VALVE
C-628-417-2	10,643 Gallons	3020-05 B	1	103.00	103.00	A	10,643 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 996 WITH PRESSURE/VACUUM VALVE
C-628-418-2	10,643 Gallons	3020-05 B	1	103.00	103.00	A	10,643 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 997 WITH PRESSURE/VACUUM VALVE
C-628-419-2	5,714 Gallons	3020-05 B	1	103.00	103.00	A	5,714 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 998 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report

For Facility=628 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-628-420-2	24,955 Gallons	3020-05 C	1	149.00	149.00	A	24,955 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P1 WITH PRESSURE/VACUUM VALVE
C-628-421-2	24,955 Gallons	3020-05 C	1	149.00	149.00	A	24,955 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P2 WITH PRESSURE/VACUUM VALVE
C-628-422-2	24,955 Gallons	3020-05 C	1	149.00	149.00	A	24,955 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P3 WITH PRESSURE/VACUUM VALVE
C-628-423-2	24,955 Gallons	3020-05 C	1	149.00	149.00	A	24,955 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P4 WITH PRESSURE/VACUUM VALVE
C-628-424-2	24,955 Gallons	3020-05 C	1	149.00	149.00	A	24,955 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P5 WITH PRESSURE/VACUUM VALVE
C-628-425-2	24,955 Gallons	3020-05 C	1	149.00	149.00	A	24,955 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P6 WITH PRESSURE/VACUUM VALVE
C-628-427-2	12,425 Gallons	3020-05 B	1	103.00	103.00	A	12,425 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P8 WITH PRESSURE/VACUUM VALVE
C-628-428-2	12,425 Gallons	3020-05 B	1	103.00	103.00	A	12,425 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P9 WITH PRESSURE/VACUUM VALVE
C-628-429-2	12,425 Gallons	3020-05 B	1	103.00	103.00	A	12,425 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P10 WITH PRESSURE/VACUUM VALVE
C-628-431-2	1,173 Gallons	3020-05 A	1	83.00	83.00	A	1,173 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P12 WITH PRESSURE/VACUUM VALVE
C-628-432-2	155,321 Gallons	3020-05 E	1	270.00	270.00	A	155,321 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 1013 WITH PRESSURE/VACUUM VALVE
C-628-433-2	1,173 Gallons	3020-05 A	1	83.00	83.00	A	1,173 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P14 WITH PRESSURE/VACUUM VALVE
C-628-434-2	61,200 Gallons	3020-05 D	1	203.00	203.00	A	61,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P21 WITH PRESSURE/VACUUM VALVE
C-628-435-2	61,200 Gallons	3020-05 D	1	203.00	203.00	A	61,200 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK P22 WITH PRESSURE/VACUUM VALVE

Detailed Facility Report

For Facility=628 and excluding Deleted Permits
Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
C-628-476-2	1,957 gallon	3020-05 A	1	83.00	83.00	A	1,957 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 897 WITH PRESSURE VALVE
C-628-477-2	1,242 gallon	3020-05 A	1	83.00	83.00	A	1,242 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 898 WITH PRESSURE/VACUUM VALVE
C-628-478-2	1,242 gallon	3020-05 A	1	83.00	83.00	A	1,242 GALLON STAINLESS STEEL ENCLOSED TOP RED AND WHITE WINE FERMENTATION AND WINE STORAGE TANK 899 WITH PRESSURE/VACUUM VALVE
C-628-749-1	121.7 BHP	3020-10 B	1	129.00	129.00	A	225 BHP, LIMITED TO 121.7 BHP @ 1800 RPM, FORD MODEL WSG-1068 RICH-BURN LPG/PROPANE-FIRED EMERGENCY-STANDBY IC ENGINE WITH NON-SELECTIVE CATALYTIC REDUCTION (NSCR) POWERING AN ELECTRICAL GENERATOR (CATERPILLAR G60F3 GENERATOR SET)
C-628-751-0	1 nozzle	3020-11 A	1	38.00	38.00	A	GASOLINE DISPENSING OPERATION WITH ONE 500 GALLON TRUSCO SUPERVAULT ABOVEGROUND STORAGE TANK SERVED BY STANDING LOSS CONTROL (VR-301-X), AND 1 FUELING POINT WITH 1 GASOLINE DISPENSING NOZZLE SERVED BY BALANCE PHASE II VAPOR RECOVERY SYSTEM (G-70-132-A)
C-628-752-4	7.3 MMBtu/hour	3020-02 G	1	893.00	893.00	A	GRAPE SEED DRYING OPERATION CONSISTING OF DELUX MFG CO NATURAL GAS-FIRED TOWER GRAIN DRYER WITH A 7.3 MMBTU/HR DELUX MFG CO MODEL 24 ½" NOVA BURNER SYSTEM

Number of Facilities Reported: 1