



San Joaquin Valley

AIR POLLUTION CONTROL DISTRICT



OCT - 5 2018

Mr. William Shaffer
California Resources Production Corporation
11109 River Run Blvd
Bakersfield, CA 93311

Re: Notice of Preliminary Decision – Title V Permit Renewal
Facility Number: S-1737
Project Number: S-1173088

Dear Mr. Shaffer:

Enclosed for your review and comment is the District's analysis of the application to renew the Federally Mandated Operating Permit for California Resources Production Corporation in central Kern County, California.

The notice of preliminary decision for this project will be published approximately three days from the date of this letter. After addressing all comments made during the 30-day public notice and the 45-day EPA comment periods, the District intends to issue the renewed Federally Mandated Operating Permit. Please submit your written comments on this project within the 30-day public comment period, as specified in the enclosed public notice.

Thank you for your cooperation in this matter. If you have any questions, please contact Mr. Leonard Scandura, Permit Services Manager, at (661) 392-5500.

Sincerely,

Arnaud Marjollet
Director of Permit Services

Enclosures

cc: Tung Le, CARB (w/enclosure) via email
cc: Gerardo C. Rios, EPA (w/enclosure) via email

Samir Sheikh
Executive Director/Air Pollution Control Officer

Northern Region
4800 Enterprise Way
Modesto, CA 95356-8718
Tel: (209) 557-6400 FAX: (209) 557-6475

Central Region (Main Office)
1990 E. Gettysburg Avenue
Fresno, CA 93726-0244
Tel: (559) 230-6000 FAX: (559) 230-6061

Southern Region
34946 Flyover Court
Bakersfield, CA 93308-9725
Tel: 661-392-5500 FAX: 661-392-5585

SAN JOAQUIN VALLEY AIR POLLUTION CONTROL DISTRICT

Proposed Title V Permit Renewal Evaluation California Resources Production Corporation S-1738

TABLE OF CONTENTS

I.	PROPOSAL	2
II.	FACILITY LOCATION	2
III.	EQUIPMENT LISTING	3
IV.	GENERAL PERMIT TEMPLATE USAGE	3
V.	SCOPE OF EPA AND PUBLIC REVIEW	3
VI.	FEDERALLY ENFORCEABLE REQUIREMENTS	3
VII.	REQUIREMENTS NOT FEDERALLY ENFORCEABLE	5
VIII.	PERMIT REQUIREMENTS	5
IX.	PERMIT SHIELD	12
X.	CALIFORNIA ENVIRONMENTAL QUALITY ACT	13
XI.	PERMIT CONDITIONS	13
ATTACHMENTS		13
A.	DRAFT RENEWED TITLE V OPERATING PERMIT	
B.	PREVIOUS TITLE V OPERATING PERMIT	
C.	DETAILED SUMMARY LIST OF FACILITY PERMITS	

TITLE V PERMIT RENEWAL EVALUATION

Engineer: David Torii
Date: 7/19/18

Facility Number: S-1738
Facility Name: California Resources Production Corp
Mailing Address: 11109 River Run Blvd.
Bakersfield, CA 93311

Contact Name: Doug Shaffer
Phone: (661) 529-4366

Responsible Official: Raymond Rodriguez
Title: North Operations Environmental Manager

Project # : 1173087
Deemed Complete: 8/29/17

I. PROPOSAL

California Resources Production Corporation was issued a Title V permit on 9/23/99. As required by District Rule 2520, the applicant is requesting a permit renewal. The existing Title V permit shall be reviewed and modified to reflect all applicable District and federal rules updated, removed, or added since the issuance of the previously renewed Title V permit on 1/14/14.

The purpose of this evaluation is to provide the legal and factual basis for all updated applicable requirements and to determine if the facility will comply with these updated requirements. It also specifically identifies all additions, deletions, and/or changes made to permit conditions or equipment descriptions.

II. FACILITY LOCATION

California Resources Production Corporation's S-1738 facility is located in the Light Oil Central Stationary Source in Kern County, CA.

III. EQUIPMENT LISTING

A detailed facility printout listing all permitted equipment at the facility is included as Attachment C.

IV. GENERAL PERMIT TEMPLATE USAGE

The applicant is requesting to use the following model general permit Templates:

A. Template SJV-UM-0-3 Facility Wide Umbrella

The applicant does not propose to use any model general permit templates.

V. SCOPE OF EPA AND PUBLIC REVIEW

The applicant is not requesting any model general permit templates. Therefore, all federally enforceable conditions in this current Title V permit will be subject to EPA and public review.

VI. FEDERALLY ENFORCEABLE REQUIREMENTS

A. Rules Updated or Evaluated

- District Rule 2020, Exemptions (amended December 18, 2014)
- District Rule 2201, New and Modified Stationary Source Review Rule (amended February 18, 2016)
- 40 CFR Part 60, Subpart JJJJ—Standards of Performance for Stationary Spark Ignition Internal Combustion Engines (6/28/11, 1/30/13, 2/27/14, 8/30/16)
- 40 CFR Part 60, Subpart OOOO Standards of Performance for Crude Oil and Natural Gas Production, Transmission and Distribution (12/31/14, 8/12/15 and 6/3/16)
- 40 CFR Part 64, Compliance Assurance Monitoring (10/22/97)

B. Rules Removed

There are no applicable rules that were removed since the last Title V renewal.

C. Rules Added

There are no applicable rules that were added since the last Title V renewal.

D. Rules Not Updated

- District Rule 1070 Inspections (Amended December 17, 1992)
- District Rule 1080, Stack Monitoring (Amended December 17, 1992)
- District Rule 1081, Source Sampling (Amended December 16, 1993)
- District Rule 1100, Equipment Breakdown (amended December 17, 1992)
- District Rule 1160, Emission Statements (adopted November 18, 1992)
- District Rule 2010, Permits Required (amended December 17, 1992)

- District Rule 2031, Transfer of Permits (amended December 17, 1992)
- District Rule 2040, Applications (amended December 17, 1992)
- District Rule 2070, Standards for Granting Applications (amended December 17, 1992)
- District Rule 2080, Conditional Approval (amended December 17, 1992)
- District Rule 2520, Federally Mandated Operating Permits (amended June 21, 2001)
- District Rule 4001 New Source Performance Standards (Amended January 19, 1995; Amended September 17, 1997; Amended April 14, 1999)
- District Rule 4101, Visible Emissions (amended February 17, 2005)
- District Rule 4102, Nuisance (amended December 17, 1992)
- District Rule 4201, Particulate Matter Concentration (amended December 17, 1992)
- District Rule 4202, Particulate Matter - Emission Rate (amended December 17, 1992)
- District Rule 4301, Fuel Burning Equipment (amended December 17, 1992)
- District Rule 4305, Boilers, Steam Generators and Process Heaters - Phase 2 (amended August 21, 2003)
- District Rule 4306, Boilers, Steam Generators and Process Heaters - Phase 3 (amended October 16, 2008)
- District Rule 4320, Advanced Emission Reduction Options for Boilers, Steam Generators and Process Heaters greater than 5.0 MMBtu/hr (adopted October 16, 2008)
- District Rule 4311 Flares (amended 6/18/2009)
- District Rule 4409 Components At Light Crude Oil Production Facilities, Natural Gas Production Facilities, And Natural Gas Processing Facilities (amended 4/20/2005)
- Rule 4701 Internal Combustion Engines – Phase 1 (Amended 8/21/03)
- District Rule 4601 Architectural Coatings (Amended December 17, 2009)
- District Rule 4624, Transfer of Organic Liquid (Amended December 20, 2007)
- District Rule 4801, Sulfur Compounds (amended December 17, 1992)
- District Rule 8021, Construction, Demolition, Excavation, Extraction, and Other Earthmoving Activities (amended August 19, 2004)
- District Rule 8021 Construction, Demolition, Excavation, Extraction, And Other Earthmoving Activities (November 15, 2001; Amended August 19, 2004)
- District Rule 8011 General Requirements (Amended August 19, 2004)
- District Rule 8031, Bulk Materials (amended August 19, 2004)
- District Rule 8041, Carryout and Trackout (amended August 19, 2004)
- District Rule 8051, Open Areas (amended August 19, 2004)
- District Rule 8061, Paved and Unpaved Roads (amended August 19, 2004)
- District Rule 8071, Unpaved Vehicle/Equipment Traffic Areas (amended September 16, 2004)
- 40 CFR Part 60 Subpart Dc—Standards of Performance for Small Industrial-Commercial-Institutional Steam Generating Units (1/20/11 and 2/16/2012)
- 40 CFR Part 60 Appendix F (7/1/91)
- 40 CFR Part 61, Subpart M, National Emission Standard for Asbestos (7/20/04)
- 40 CFR Part 64, Compliance Assurance Monitoring (CAM)

VII. REQUIREMENTS NOT FEDERALLY ENFORCEABLE

For each Title V source, the District issues a single permit that contains the Federally Enforceable requirements, as well as the District-only requirements. The District-only requirements are not a part of the Title V Operating Permits. The terms and conditions that are part of the facility's Title V permit are designated as "Federally Enforceable Through Title V Permit".

For this facility, the following are not federally enforceable and will not be discussed in further detail:

A. Rules Added/Updated

None

B. Rules Not Updated

District Rule 4102, Nuisance (as amended December 17, 1992)

Condition 42 of permit unit '0-5 is based on District Rule 4102 and will therefore not be discussed any further.

VIII. PERMIT REQUIREMENTS

The purpose of this evaluation is to review changes to federally enforceable requirements; therefore, this compliance section will only address rules that have been amended or added since the issuance of most recent renewal of the Title V permit.

A. District Rule 2020 - Exemptions

District Rule 2020 lists equipment which is specifically exempt from obtaining permits and specifies recordkeeping requirements to verify such exemptions. The amendments to this rule do not have any effect on current permit requirements and will therefore not be addressed in this evaluation.

B. District Rule 2201 - New and Modified Stationary Source Review Rule (NSR)

District Rule 2201 has been amended since this facility's initial Title V permit was issued. However, the requirements of this rule are only triggered at the time the source undergoes a modification. All applicable requirements from any NSR permit actions have already been incorporated into the current Title V permit.

C. District Rule 2520 - Federally Mandated Operating Permits

No changes to this Rule have occurred since issuance of the previous TV permit; however, greenhouse gas emissions will be addressed under Rule 2520 during this renewal.

There are no federally applicable Greenhouse Gas (GHG) requirements for this source. It should be noted that the Mandatory Greenhouse Gas Reporting rule (40 CFR Part 98) is not included in the definition of an applicable requirement within Title V (per 40 CFR 71.2). Therefore, there will be no further discussion of GHG in this evaluation.

D. 40 CFR Part 60, Subpart JJJJ—Standards of Performance for Stationary Spark Ignition Internal Combustion Engines (2/27/14)

This subpart applies to owners and operators of stationary spark (SI) ignited IC engines.

Section 60.423(a)(4)(iv) states that the provisions of this subpart are applicable to manufacturers, owners, and operators of emergency stationary spark ignition (SI) internal combustion engines greater than 25 HP that commence construction after June 12, 2006, where the stationary SI ICE are manufactured on or after January 1, 2009.

Emergency IC engines S-1738-77 and '408 are rated greater than 25 HP; however, they commenced construction prior to 6/12/2006; therefore, they are not subject to this subpart.

Section 60.4233(f)(4)(i) states that the provisions of this subpart are applicable to manufacturers, owners, and operators of stationary spark ignition (SI) internal combustion engines (ICE) that are modified or reconstructed after June 12, 2006 where the stationary ICE are manufactured prior to July 1, 2007 for engines with a maximum engine power greater than 500 hp.

615 bhp IC engine S-1738-345 was manufactured prior to July 1, 2007 but has not been modified or reconstructed after June 12, 2006; therefore, S-1738-345 is not subject to this subpart.

Section 60.4230(a)(4)(iii) states that the provisions of this subpart are applicable to manufacturers, owners, and operators of stationary spark ignition (SI) internal combustion engines (ICE) that commence construction after June 12, 2006 where the stationary ICE are manufactured on or after July 1, 2008 for engines with a maximum engine power less than 500 hp.

The applicant states that IC engines S-1738-470 through '483 fall into this time frame. These units are natural gas/LPG-fired rich burn spark ignited IC engines, that are rated less than 500 hp, and were manufactured on or after 7/1/08. These engines are subject to this subpart.

The following conditions will be included of the above permits to ensure compliance with Section 60.4230(a)(4)(iii).

	The following conditions will be added to permits S-1738-470 through '483 to ensure compliance:
Per Section 60.4233(d), owners must comply with the emission standards for field testing in 40 CFR 1048.101(c) for their non-emergency stationary SI ICE. 40 CFR 1048.101(c)(2) lists the HC + NOx standard as 3.8 g/kW-hr (equivalent to 2.8 g/bhp-hr) and the CO standard as 6.5 g/kW-hr (equivalent to 4.8 g/bhp-hr).	<i>Emissions rates shall not exceed any of the following: PM10: 0.01 g/bhp-hr; NOx (as NO2): 5 ppmvd @15% O2; VOC (as CH4): 25 ppmvd @15% O2; CO: 50 ppmvd @15% O2; or SOx (as SO2): 0.0438 g/bhp-hr. Emission limits are on a 15 minute average. [District Rules 2201, 4701, and 4702 and 40 CFR 60 Subpart JJJJ]</i> Note that the sum of the VOC and NOx emission limits equals 0.167 g/bhp-hr which is less than 2.8 g-(HC+NOx)/bhp-hr. 50 ppmv CO = 0.106 g-CO/bhp-hr. Therefore, the requirements of this section are satisfied.
Section 60.4234 states owners and operators of stationary SI ICE must operate and maintain stationary SI ICE that achieve the emission standards as required in Section 60.4233 over the entire life of the engine	District Rule 4702 requires periodic monitoring to ensure that the applicable emission limits contained in the permit are met. Additionally, the emissions rates for the engines will be listed as a permit condition for the life of the permit. Therefore, the requirements of this section are satisfied.
Section 60.4236(a) states that after July 1, 2010, owners and operators may not install stationary SI ICE with a maximum engine power of less than 500 hp that do not meet the applicable requirements of Section 60.4233.	The above listed engines meet the applicable requirements of Section 60.4233. Therefore, the requirements of Section 60.4236 are satisfied.

Section 60.4243(b)(2)(i) states that owner must keep a maintenance plan and records of conducted maintenance and must, to the extent practicable, maintain and operate the engine in a manner consistent with good air pollution control practice for minimizing emissions. In addition, an initial performance test to demonstrate compliance is required.	The following conditions will be added to the permits to ensure compliance: <i>Permittee shall maintain an engine operating log, on a monthly basis, which includes the following information; total hours of operation, type and quantity of fuel used, maintenance or modifications performed, monitoring data, compliance source test results, and any other information necessary to demonstrate compliance with Rule 4702. [District Rule 4702 and 40 CFR 60 Subpart JJJJ]</i> <i>Source testing to measure natural gas-combustion NOx, CO, and VOC emissions from this unit shall be measured not less than once every 24 months.[District Rule 4702 and 40 CFR 60 Subpart JJJJ]</i> <i>This engine shall be operated and maintained in proper operating condition per the manufacturer's requirements as specified on the Inspection and Monitoring (I&M) plan submitted to the District. [District Rule 4702 and 40 CFR 60 Subpart JJJJ]</i>
Section 60.4243(g) states that it is expected that air-to-fuel ratio controllers will be used with the operation of three-way catalysts/non-selective catalytic reduction. The controller must be maintained and operated appropriately in order to ensure proper operation of the engine and control device to minimize emissions at all times.	The following condition will be added to the permits to ensure compliance: <i>Air-to-fuel ratio controller(s) shall be maintained and operated appropriately in order to ensure proper operation of the engine and control device to minimize emissions at all times. [District Rule 2201 and 40 CFR 60 Subpart JJJJ]</i> <i>Air-to-fuel ratio controller(s) shall be maintained and operated appropriately in order to ensure proper operation of the engine and control device to minimize emissions at all times. [District Rule 2201 and 40 CFR 60 Subpart JJJJ] Y</i>

Section 60.4244 lists test methods and other procedures for owners and operators of stationary SI ICE who conduct performance tests. Three separate test runs are required for each performance test, and each performance test must be conducted within 10 percent of 100 percent peak (or the highest achievable) load. Additionally, performance tests may not be conducted during periods of startup, shutdown, or malfunction.	The following condition will be added to the permits to ensure compliance: <i>For emissions source testing, the arithmetic average of three 30-consecutive-minute test runs shall apply. If two of three runs are above an applicable limit, the test cannot be used to demonstrate compliance with an applicable limit. VOC emissions shall be reported as methane. VOC, NOx, and CO concentrations shall be reported in ppmv, corrected to 15% oxygen. [District Rule 4702 and 40 CFR 60 Subpart JJJJ]</i> <i>Emissions source testing shall be conducted with the engine operating either at conditions representative of normal operations or conditions specified in the Permit to Operate. [District Rule 4702 and 40 CFR 60 Subpart JJJJ]</i>
Section 60.4245(a) states that owners and operators of all stationary SI ICE must keep records	The following condition will be added to the permits to ensure compliance: <i>Permittee shall maintain an engine operating log, on a monthly basis, which includes the following information; total hours of operation, type and quantity of fuel used, maintenance or modifications performed, monitoring data, compliance source test results, and any other information necessary to demonstrate compliance with Rule 4702. [District Rule 4702 and 40 CFR 60 Subpart JJJJ]</i>
Section 60.4245(d) states owners and operators of stationary SI ICE that are subject to performance testing must submit a copy of each performance test within 60 days after the test has been completed.	The following condition will be added to the permits to ensure compliance: <i>The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 1081 and 40 CFR 60 Subpart JJJJ]</i>

Therefore, compliance with the requirements of this subpart is expected.

E. 40 CFR Part 60, Subpart OOOO

Subpart OOOO could potentially apply to this facility's tanks. However, pursuant to 40 CFR 60.5395, this subpart does not apply since the emissions from each of the tanks are estimated to be less than 6 tons per year. Therefore, the requirements of this subpart is not applicable to this facility

F. 40 CFR Part 64 - Compliance Assurance Monitoring(CAM)

40 CFR Part 64 requires Compliance Assurance Monitoring for units that meet the following three criteria:

- 1) the unit must have an emission limit for the pollutant;
- 2) the unit must have add-on controls for the pollutant; these are devices such as flue gas recirculation (FGR), baghouses, and catalytic oxidizers; and
- 3) the unit must have a pre-control potential to emit of greater than the major source thresholds.

Pollutant	Major Source Threshold (lb/year)
NO _x	20,000
SO _x	140,000
PM ₁₀	140,000
CO	200,000
VOC	20,000

Tanks:

Facility S-1738 has several storage/process tanks with emissions limits. These units are equipped with vapor recovery system.

§64.1 defines a control device as equipment, other than inherent process equipment, that is used to destroy or remove air pollutants prior to discharge to the atmosphere.

These permit units for tanks with vapor recovery are not subject to CAM since the vapor recovery system does not meet CAM's definition of a control device. The vapor recovery system consists of a vapor return or condensation system that connects to a gas pipeline distribution system which does not destroy or remove air pollutants prior to discharge to the atmosphere.

IC Engines:

All of the facility's IC engines with add-on controls are rich burn with three-way catalysts. They may be subject to CAM for NOX, CO, and VOC as they have NOX, CO and VOC emissions limit.

Per AP-42 Table 3.2-3 (7/00) the uncontrolled emission factors for NOX, CO and VOC for a rich burn engine are 2.27 lb-NOx/MMBtu, 3.72 lb-CO/MMBtu, and 0.0296 lb-VOC/MMBtu. Horsepower ratings triggering Major Source thresholds are calculated as follows:

$$\frac{20,000 \text{ lb} - \text{NO}_x}{\text{year}} \times \frac{\text{MMBtu}}{2.27 \text{ lb} - \text{NO}_x} \times \frac{\text{bhp} - \text{hr}}{2542.5 \text{ Btu}} \times \frac{1,000,000 \text{ Btu}}{1 \text{ MMBtu}} \times \frac{\text{year}}{8760 \text{ hr}} = 395.6 \text{ bhp}$$

$$\frac{200,000 \text{ lb} - \text{CO}}{\text{year}} \times \frac{\text{MMBtu}}{3.72 \text{ lb} - \text{CO}} \times \frac{\text{bhp} - \text{hr}}{2542.5 \text{ Btu}} \times \frac{1,000,000 \text{ Btu}}{1 \text{ MMBtu}} \times \frac{\text{year}}{8760 \text{ hr}} = 2,413.9 \text{ bhp}$$

$$\frac{20,000 \text{ lb} - \text{VOC}}{\text{year}} \times \frac{\text{MMBtu}}{0.0296 \text{ lb} - \text{VOC}} \times \frac{\text{bhp} - \text{hr}}{2542.5 \text{ Btu}} \times \frac{1,000,000 \text{ Btu}}{1 \text{ MMBtu}} \times \frac{\text{year}}{8760 \text{ hr}} = 30,337.0 \text{ bhp}$$

As shown above, an engine would need to have a bhp rating greater than 395 to trigger the above CAM emission threshold for NOx, and a greater bhp to trigger CAM for CO and VOC.

Of the facility's IC engines only IC engine S-1738-345 has a bhp rating greater than 395 . Therefore, since S-1738-345' uncontrolled NOx emissions are greater than 20,000 lb-NOx/year it is subject to CAM.

IC engine S-1738-345:

In order to determine if a 15-minute monitoring interval is required, we will determine if post-control emissions also exceed the Major Source threshold for NOx emissions:

$$\frac{0.134 \text{ g} - \text{NOx}}{\text{bhp} - \text{hr}} \times \frac{\text{lb}}{453.6 \text{ g}} \times \frac{8760 \text{ hr}}{\text{year}} \times 615 \text{ bhp} = 1,592 \text{ lb} - \text{NOx}/\text{year}$$

Since the post-control annual emissions do not exceed the Major Source threshold for NOx of 20,000 lb/year, a once-daily monitoring interval is sufficient to determine S-1738-345's compliance with CAM.

S-1738-345 is a full time spark-ignited IC engines served by an add-on control (NSCR) which controls NOX, CO and VOC emissions by using a precious metal catalyst to promote the chemical reduction of NOX to N2, CO2 and H2O and the oxidation of CO and VOC to CO2 and H2O.

S-1738-345's uncontrolled PE is above major source threshold for NOx but not CO or VOC. Therefore, the engine is subject to the requirements of 40 CFR 64 for NOx only.

The facility will comply with CAM by establishing the output voltage range of the O2 sensor in the 3-way catalyst controlled exhaust stream device, then monitoring/recording the O2 sensor reading. Once-daily monitoring of the exhaust O2 sensor is required to satisfy CAM for NOX. However, since previously established CAM monitoring conditions established by the District for large catalyst controlled gas-fired engines were not included on the current Permit Unit Requirements for engine S-1738-345, the following conditions will be added to the Permit Unit Requirements during this renewal:

- The operator shall establish an O2 sensor output voltage range that indicates that the control device(s) on this engine are operating properly at all times. [40 CFR 64]
- The operator shall submit a Title V minor modification application to incorporate the O2 sensor output voltage range established for this engine within twelve months from the date in which the renewed Title V permit is issued. [District Rule 2520, 9.3.2 and 40 CFR 64]

- The permittee shall record the O2 sensor reading (in millivolts) on a daily basis. [District Rule 2520, 9.4.2 and 40 CFR 64]
- The permittee shall comply with the compliance assurance monitoring operation and maintenance requirements of 40 CFR Part 64.7. [40 CFR 64]
- The permittee shall comply with the recordkeeping and reporting requirements of 40 CFR part 64.9. [40 CFR 64]
- If the District or EPA determine that a Quality Improvement Plan is required under 40 CFR 64.7(d)(2), the permittee shall develop and implement the Quality Improvement Plan in accordance with 40 CFR part 64.8. [40 CFR 64]

Conditions 33 through 38 incorporate the CAM requirements on draft PTO S-1738-345-8

Organic Liquid Loading Rack

Facility S-1738 has two class 1 organic liquid loading racks.

§64.1 defines a control device as equipment, other than inherent process equipment, that is used to destroy or remove air pollutants prior to discharge to the atmosphere.

These permit units are not subject to CAM since the vapor recovery system does not meet CAM's definition of a control device. The vapor recovery system consists of a vapor return or condensation system that connects to a gas pipeline distribution system which does not destroy or remove air pollutants prior to discharge to the atmosphere.

Flares/Thermal Oxidizers:

Facility S-1738 has several flares and thermal oxidizers with emissions limits. However this units are not equipped with an add on control device. Therefore, they do not trigger CAM.

IX. PERMIT SHIELD

A permit shield legally protects a facility from enforcement of the shielded regulations when a source is in compliance with the terms and conditions of the Title V permit. Compliance with the terms and conditions of the Operating Permit is considered compliance with all applicable requirements upon which those conditions are based, including those that have been subsumed.

A. Requirements Addressed by Model General Permit Templates

The applicant does not propose to use any model general permit templates.

B. Obsolete Permit Shields From Existing Permit Requirements

S-1738-118-17: 195 bhp Waukesha Natural Gas-Fired IC Engine

Permit shield condition #27 from the current permit was deleted since it was obsolete.

X. CALIFORNIA ENVIRONMENTAL QUALITY ACT

The purpose of the Title V permit renewal is to update the permit to ensure that any changes to regulations since the issuance of the initial Title V permit or most recent renewal of the Title V permit are incorporated as permit requirements.

Per the California Environmental Quality Act (CEQA) Statute §21080.24, and CEQA Guidelines §15281, the issuance, modification, amendment, or renewal of any permit by an air pollution control district or air quality management district pursuant to Title V is exempt from CEQA, unless the issuance, modification, amendment, or renewal authorizes a physical or operational change to a source or facility. There will be no physical or operational change to the source or facility nor will the Title V permit renewal authorize a physical or operational change to the source or facility. Therefore, this project, a Title V permit renewal, is subject to a ministerial action that is exempt from CEQA.

XI. PERMIT CONDITIONS

See Attachment A - Draft Renewed Title V Operating Permit.

ATTACHMENTS

- A. Draft Renewed Title V Operating Permit
- B. Previous Title V Operating Permit
- C. Detailed Summary List of Facility Permits

ATTACHMENT A

Draft Renewed Title V Operating Permit

San Joaquin Valley Air Pollution Control District

FACILITY: S-1737-0-5

EXPIRATION DATE: 02/28/2018

FACILITY-WIDE REQUIREMENTS

1. {4362} The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
2. {4363} The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
3. {4364} The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. {4365} Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. {4366} The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.13.1] Federally Enforceable Through Title V Permit
6. {4367} A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. {4368} Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. {4369} The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: CALIFORNIA RESOURCES PRODUCTION CORP

Location: LIGHT OIL CENTRAL, KERN COUNTY, CA

S-1737-0-5 Oct 5 2018 11:50AM - OROZCOA

9. {4370} The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit
10. {4371} The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit
11. {4372} Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
12. {4373} If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
13. {4374} It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
14. {4375} The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
15. {4376} The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
16. {4377} The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
17. {4378} The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
18. {4379} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
19. {4380} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
20. {4381} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
21. {4382} Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

22. {4383} No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit
23. {4384} No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in Table of Standards 1 effective until 12/30/10 or Table of Standards 2 effective on and after 1/1/11 of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
24. {4385} All VOC-containing materials subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
25. {4386} The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
26. {4387} With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
27. {4388} If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
28. {4389} If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit
29. {4390} Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8021] Federally Enforceable Through Title V Permit
30. {4391} Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8031] Federally Enforceable Through Title V Permit
31. {4392} An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8041] Federally Enforceable Through Title V Permit
32. {4393} Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8051] Federally Enforceable Through Title V Permit
33. {4394} Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8061] Federally Enforceable Through Title V Permit

DRAFT

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

34. {4395} Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8071] Federally Enforceable Through Title V Permit
35. {4396} Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit
36. {4397} The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
37. {4398} The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
38. {4399} When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
39. {4400} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), Rule 111 (Kern, Tulare, Kings), and Rule 202 (Fresno, Kern, Tulare, Kings, Madera, Stanislaus, Merced, San Joaquin). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. {4401} Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601 (12/17/09); 8021 (8/19/2004); 8031 (8/19/2004); 8041 (8/19/2004); 8051 (8/19/2004); 8061 (8/19/2004); and 8071 (9/16/2004). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report begin January 1 of every year, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit
42. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
43. Operator shall maintain accurate monthly records of Gas-to-oil ratio (GOR) and API gravity of liquids produced showing that facility exclusively processes, stores, or transfers black oil (as defined in 40 CFR 63.761). [40 CFR 63.760(e)] Federally Enforceable Through Title V Permit
44. {3321} The permittee shall not use any components that leak in excess of the applicable leak standards as specified in this permit. Components that have been found leaking in excess of the applicable leak standards of this rule may be used provided such leaking components have been identified with a tag for repair, are repaired, or are awaiting re-inspection after being repaired, within the applicable time period specified in this permit. [District Rule 4409, 5.1.1] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

45. {3506} For valves, threaded connections, flanges, pipes, pumps, compressors, and other components subject to the requirements of Rule 4409, but not specified in this permit; a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 1,000 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 2,000 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4409, 5.1.1] Federally Enforceable Through Title V Permit
46. {3323} For pressure relief devices (PRDs); a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 200 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 400 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4409, 5.1.1] Federally Enforceable Through Title V Permit
47. {3324} For polished rod stuffing boxes (PRSBs); a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 1,000 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 1,000 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4409, 5.1.1] Federally Enforceable Through Title V Permit
48. {3325} Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4409, 5.1.2] Federally Enforceable Through Title V Permit
49. {3326} Minor gas leaks from PRSBs detected during any District inspection shall not be counted toward determination of compliance with this rule provided the permittee repairs, replaces, or removes leaking PRSBs from VOC service as soon as practicable but not later than seven calendar days. [District Rule 4409, 5.1.3.1.2] Federally Enforceable Through Title V Permit
50. {3327} Leaks detected during quarterly operator inspections shall not be counted towards determination of compliance with the provisions of Rule 4409 provided the leaking components are repaired as soon as practicable but not later than the time frame specified in this permit. Leaks detected during quarterly operator inspections that are not repaired, replaced, or removed from operation as soon as practicable but not later than the time frame specified in this rule shall be counted toward determination of compliance with the provisions of Rule 4409. [District Rule 4409, 5.1.3.2.1 and 5.1.3.2.2] Federally Enforceable Through Title V Permit
51. {3328} Leaking components at this facility detected during annual operator inspections, as required by Rule 4409 for a specific component type, that exceed the leak standards specified in this permit, shall constitute a violation of this rule. This violation is regardless of whether or not the leaking components are repaired, replaced, or removed from operation within the allowable repair time frame specified in this permit. [District Rule 4409, 5.1.3.2.3] Federally Enforceable Through Title V Permit
52. {3329} An open-ended line, or a valve located at the end of the line, that is not sealed with either a blind flange, a plug, a cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended line is a leak. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4409, 5.1.4.1] Federally Enforceable Through Title V Permit
53. {3330} A leak from a component is when there is a major liquid leak from the component. A major liquid leak from a component is when a visible mist or a continuous flow of liquid, that is not seal lubricant, leaks from the component. [District Rule 4409, 5.1.4.2] Federally Enforceable Through Title V Permit
54. {3331} A leak from a component is when gas emissions greater than 50,000 ppmv, as methane, leaks from the component. [District Rule 4409, 5.1.4.3] Federally Enforceable Through Title V Permit
55. {3332} A minor liquid leak from a component is when more than three drops of liquid per minute, that is not seal lubricant and is not a major liquid leak, leaks from the component. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

56. {3333} When 200 or fewer valves are inspected, a leak from a valve is when more than one valve has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 valves are inspected, a leak from a valve is when more than 0.5 % (rounded up to the nearest whole number) of the valves have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit
57. {3334} When 200 or fewer threaded connections are inspected, a leak from a threaded connection is when more than one threaded connection has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 threaded connections are inspected, a leak from a threaded connection is when more than 0.5 % (rounded up to the nearest whole number) of the threaded connections have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit
58. {3335} When 200 or fewer flanges are inspected, a leak from a flange is when more than one flange has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 flanges are inspected, a leak from a flange is when more than 0.5 % (rounded up to the nearest whole number) of the flanges have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit
59. {3336} When 200 or fewer pumps are inspected, a leak from a pump is when more than two pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. When greater than 200 pumps are inspected, a leak from a pump is when more than 1.0 % (rounded up to the nearest whole number) of the pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit
60. {3337} When compressors, PRDs, or other components not specified in this permit are inspected, a leak from these components is when more than one component has a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit
61. {3338} When 200 or fewer PRSBs are inspected, a leak is when more than four have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 PRSBs are inspected, a leak is when more than 2.0 % (rounded up to the nearest whole number) of the PRSBs have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit
62. {3339} When 200 or fewer wells at light crude oil or gas production facilities are inspected, a leak from a pipe is when more than two or more pipes have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 wells at light crude oil or gas production facilities are inspected, a leak from a pipe is when more than 1.0 % (rounded up to the nearest whole number) of the pipes have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit
63. {3340} When pipes at natural gas processing facilities are inspected, a leak from a pipe is when more than two have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit
64. {3341} For manned facilities all accessible operating pumps, compressors, and PRDs, in service, shall be audio-visually inspected for leaks at least once every 24 hours except when operators do not report to the facility during a 24 hour period. [District Rule 4409, 5.2.1] Federally Enforceable Through Title V Permit
65. {3342} For unmanned facilities all accessible operating pumps, compressors, and PRDs, in service, shall be audio-visually inspected for leaks at least once per calendar week. [District Rule 4409, 5.2.2] Federally Enforceable Through Title V Permit
66. {3343} All accessible operating pumps, compressors, and PRDs, in service, that are found to be leaking by audio-visual inspection shall be attempted to be repaired immediately. The leaking component shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4409, 5.2.3] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

67. {3344} Except for inaccessible components, unsafe-to-monitor components, or pipes, all components, in service, shall be tested for leaks at least once every calendar quarter. [District Rule 4409, 5.2.4] Federally Enforceable Through Title V Permit
68. {3345} All new, replaced, or repaired fittings, flanges, and threaded connections shall be tested for leaks immediately after being placed into service. [District Rule 4409, 5.2.5] Federally Enforceable Through Title V Permit
69. {3346} All inaccessible components shall be tested for leaks at least once every 12 months. [District Rule 4409, 5.2.6] Federally Enforceable Through Title V Permit
70. {3347} All unsafe-to-monitor components shall be tested for leaks during each turnaround. [District Rule 4409, 5.2.7] Federally Enforceable Through Title V Permit
71. {3348} All pipes shall be visually inspected for leaks at least once every 12 months. [District Rule 4409, 5.2.8] Federally Enforceable Through Title V Permit
72. {3349} All pipes, in service, that are found to be leaking by visual inspection shall be attempted to be repaired immediately. The leaking pipe shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4409, 5.2.8.1] Federally Enforceable Through Title V Permit
73. {3350} The annual pipe inspection required by either the Department of Oil, Gas, and Geothermal Resources (DOGGR) pursuant to California Code of Regulation Title 14, Division 2, Subchapter 2, Section 1774 (Oilfield Facilities and Equipment Maintenance), or by the Spill Prevention Control and Countermeasure Plan (SPCC) pursuant to 40 Code of Federal Regulation Part 112 (Oil Prevention and Response: Non- Transportation-Related Onshore and Offshore Facilities) can be used as the annual pipe inspection required by District Rule 4409. [District Rule 4409, 5.2.8.2] Federally Enforceable Through Title V Permit
74. {3351} Except for pumps, compressors, and PRDs, the permittee may apply for written approval from the District to change the inspection frequency of accessible components from quarterly to annually for a specific component type provided the following two qualifying requirements are met. During the previous five consecutive quarterly inspections, for the specific component type, there shall be no more leaks than as allowed by this permit. The permittee also shall not have received a Notice of Violation (NOV) from the District during the previous 12 months for violating any provisions of District Rule 4409 for the specific component type. If these two qualifying requirements have not been met, then the inspection frequency shall revert back to quarterly. The written request shall include pertinent documentation to demonstrate that the operator has successfully met the two qualifying requirements. [District Rule 4409, 5.2.9 and 5.2.10] Federally Enforceable Through Title V Permit
75. {3352} The permittee shall notify the District in writing within five calendar days after changing the inspection frequency for a specific component type. The written notification shall include the reason(s) and date of change to a quarterly inspection frequency. [District Rule 4409, 5.2.11] Federally Enforceable Through Title V Permit
76. {3353} A PRD that releases to the atmosphere shall be inspected by the permittee for leaks as soon as practicable but not later than 24 hours after the time of the release. The permittee shall reinspect the PRD for leaks not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the date of the initial release. If the PRD is found by the permittee to be leaking during either inspection, the PRD leak shall be treated as if the leak was found during the required quarterly operator inspections. [District Rule 4409, 5.2.12] Federally Enforceable Through Title V Permit
77. {3354} Except for PRDs, a component shall be inspected for leaks not later than 15 calendar days after repairing the leak or replacing the component. [District Rule 4409, 5.2.13] Federally Enforceable Through Title V Permit
78. {3355} District inspections shall not be counted as an operator inspection required by District Rule 4409. Any attempt by an operator to count such District inspections as part of the operator's mandatory inspections is considered a willful circumvention of the rule and is a violation of this rule. [District Rule 4409, 5.2.14] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

79. {3356} The operator, upon detection of a leaking component, shall affix to that component a weatherproof, readily visible tag, bearing the date and time when the leak was detected and the date and time of the leak measurement. For gaseous leaks, the tag shall indicate the leak concentration in ppmv. For liquid leaks, the tag shall indicate whether it is a major liquid leak or a minor liquid leak. The tag shall indicate, when applicable, whether the component is an essential component, an unsafe-to-monitor component, or a critical component. The tag shall remain in place until the leaking component is repaired or replaced and reinspected and found to be in compliance with the requirements of this rule. [District Rule 4409, 5.3.1] Federally Enforceable Through Title V Permit
80. {3357} The operator shall minimize all component leaks immediately, to the extent possible, but not later than one hour after detection of the leak in order to stop or reduce leakage to the atmosphere. If the leak has been minimized but the leak still exceeds the applicable leak standards specified in this permit, the operator shall do one of the following within the timeframes specified within this permit: 1) repair or replace the leaking component; 2) vent the leaking component to a closed vent system; 3) or remove the leaking component from operation. A closed vent system is a District approved system that is not open to the atmosphere. It is composed of hard-piping, ductwork connections and, if necessary, flow inducing devices that transport gas or vapor from a piece or pieces of equipment to a District approved control device that has a overall VOC collection and destruction or removal efficiency of at least 95%, or that transports gases or vapors back to a process system. [District Rule 4409, 5.3.4 and 5.3.5] Federally Enforceable Through Title V Permit
81. {3358} The operator shall repair minor gas leaks within seven days. The operator shall repair major gas leaks, which are $> 10,000$ ppmv but $\leq 50,000$ ppmv, within three days. The operator shall repair major gas leaks, which are $> 50,000$ ppmv, within two days. The operator shall repair minor liquid leaks within three days. The operator shall repair major liquid leaks within two days. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period. The start of the repair period shall be the time of the initial leak detection. [District Rule 4409, 5.3.4 and 5.3.5] Federally Enforceable Through Title V Permit
82. {3359} For each calendar quarter, the operator may extend the repair period for a total number of leaking components, not to exceed 0.05 % of the number of components inspected, by type, rounded upward to the nearest whole number. The repair period for minor gas leaks can be extended by seven additional days. The repair period for major gas leaks, which are $> 10,000$ ppmv but $\leq 50,000$ ppmv, can be extended by two additional days. [District Rule 4409, 5.3.5] Federally Enforceable Through Title V Permit
83. {3360} If a leaking component is an essential component or a critical component and which cannot be shut down immediately for repairs, the operator shall do the following: 1) minimize the leak within one hour after detection of the leak; 2) and if the leak has been minimized, but the leak still exceeds the applicable leak standards of Rule 4409 as specified in this permit, the essential component or critical component shall be repaired or replaced to eliminate the leak during the next process unit turnaround. The repair shall occur no later than one year from the date of the original leak detection. [District Rule 4409, 5.3.6] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

84. {3361} For any component that has incurred five repair actions for major gas leaks or major liquid leaks, or a combination of major gas leaks and major liquid leaks within a continuous 12-month period, the operator shall do one of the following four options. Options 1a through 1f require written notification to the District, option 2 requires written notification to the District and written District approval, options 3 and 4 do not require written notification to the District: 1a) For compressors replace the existing seal with either a dual mechanical seal, an oil film seal, a gas seal, or a face-type seal; 1b) for pumps replace the pump with a seal-less pump or replace the seal with a dual mechanical seal; 1c) for PRDs replace the PRD and install a rupture disc in the line which precedes the PRD such that the PRD is in series with and follows the rupture disc; 1d) for valves replace the valve with a sealed bellows valve, or for seal rings install graphite or Teflon chevron seal rings in a live-loaded packing gland; 1e) for threaded connections weld the connections or replace threaded connections with flanges; 1f) for sampling connections replace the sampling connection with a closed-loop sampling system; 2) Replace the component with Achieved-in-Practice Best Available Control Technology (BACT) equipment; 3) Vent the component to a District approved closed-vent system; 4) Remove the component from operation. For any component that is accessible, is not unsafe-to-monitor, is not an essential component, or is not a critical component, the operator shall comply with these requirements as soon as practicable but not later than twelve months after the date of detection of the fifth major leak within a continuous 12-month period. For any component that is inaccessible, is unsafe-to-monitor, is essential, or is a critical component, the operator shall comply with these requirements as soon as practicable but not later than the next turnaround or not later than two years after the date of detection of the fifth major leak within a continuous 12-month period, whichever comes first. [District Rule 4409, 5.3.7] Federally Enforceable Through Title V Permit
85. {3362} All major components and critical components shall be physically identified clearly and visibly for inspection, repair, and recordkeeping purposes. The physical identification shall consist of labels, tags, manufacturer's nameplate identifier, serial number, or model number, or other system approved by the District that enables an operator or the District to locate each individual component. The operator shall replace physical identifications that become missing or unreadable as soon as practicable but not later than 24 hours after discovery. [District Rule 4409, 5.4.1] Federally Enforceable Through Title V Permit
86. {3363} The operator shall keep a copy of the District approved Operator Management Plan (OMP) at the facility and make it available to the District, ARB, and EPA upon request. [District Rule 4409, 6.1.2] Federally Enforceable Through Title V Permit
87. {3364} By January 30th of each year the operator shall submit to the District for approval, in writing, an annual report indicating any changes to the existing OMP on file at the District. [District Rule 4409, 6.1.4] Federally Enforceable Through Title V Permit
88. {3365} The operator shall maintain an inspection log that has been signed and dated by the facility operator responsible for the inspection, certifying the accuracy of the information recorded in the log. The inspection log shall contain, at a minimum, all of the following information: 1) The total number of components inspected, and the total number and percentage of leaking components found by component types; 2) The location, type, name or description of each leaking component and the description of any unit where the leaking component is found; 3) Date of the leak detection and method of the leak detection; 4) For gaseous leaks, record the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak; 5) The date of repair, replacement, or removal from operation of the leaking component(s); 6) The identification and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes first; 7) The method(s) used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 8) The date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced; 9) The inspector's name, business mailing address, and business telephone number. [District Rule 4409, 6.2.1] Federally Enforceable Through Title V Permit
89. {3366} Records of leaks detected during quarterly or annual operator inspections, and each subsequent repair and re-inspection, shall be submitted to the District, ARB, and EPA upon request. [District Rule 4409, 6.2.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

90. {3367} Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components. The records shall include a copy of the current calibration gas certification from the vendor of the calibration gas cylinder, the date of calibration, the concentration of calibration gas, the instrument reading of calibration gas before adjustment, the instrument reading of calibration gas after adjustment, the calibration gas expiration date, and the calibration gas cylinder pressure at the time of calibration. [District Rule 4409, 6.2.3] Federally Enforceable Through Title V Permit
91. {3368} All records required by this permit shall be retained on-site for a minimum of five years and made available for District, ARB, and EPA inspection upon request. [District Rule 4409, 6.2.4] Federally Enforceable Through Title V Permit
92. {3369} All measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instructions not more than 30 days prior to its use. [District Rule 4409, 6.3.1] Federally Enforceable Through Title V Permit
93. {3370} The VOC content by weight percent shall be determined using ASTM D-1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 for liquids. [District Rule 4409, 6.3.2] Federally Enforceable Through Title V Permit
94. {3371} The percent by volume liquid evaporated at 302 °F (150 °C) shall be determined using ASTM D-86. [District Rule 4409, 6.3.3] Federally Enforceable Through Title V Permit
95. {3372} The TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D-323, and converting the RVP to TVP at the maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures specified in Appendix A of District Rule 4409. [District Rule 4409, 6.3.4] Federally Enforceable Through Title V Permit
96. {3373} The API gravity of crude oil or petroleum distillate shall be determined by using ASTM D-287 or ASTM 1298. Sampling for API gravity shall be performed in accordance with ASTM D-4057. [District Rule 4409, 6.3.5] Federally Enforceable Through Title V Permit
97. {3374} The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4409, 6.3.6] Federally Enforceable Through Title V Permit
98. {3375} Halogenated exempt compounds shall be analyzed by EPA Method 18 or ARB Method 422. [District Rule 4409, 6.3.7] Federally Enforceable Through Title V Permit

DRAFT

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-159-3

EXPIRATION DATE: 02/28/2018

SECTION: NW03 **TOWNSHIP:** 28S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

42,000 GALLON (1,000 BBL) FIXED ROOF WASH TANK (T-03) SERVED BY SHARED VAPOR CONTROL SYSTEM LISTED ON S-1737-157

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor loss prevention system capable of collecting all VOC emissions and preventing their emissions to the atmosphere at an efficiency of at least 95% by weight. [District Rule 4623] Federally Enforceable Through Title V Permit
2. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Fugitive VOC emissions shall be less than 0.5 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. All piping, valves, and fittings shall be constructed and maintained in a Leak-Free condition. [District Rules 2201 and 4623, 5.6.3] Federally Enforceable Through Title V Permit
6. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated to methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
7. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2201] Federally Enforceable Through Title V Permit
8. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information. [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
11. Formerly S-1132-84-2
12. Formerly S-4241-27-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-158-3

EXPIRATION DATE: 02/28/2018

SECTION: NW03 **TOWNSHIP:** 28S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

42,000 GALLON (1,000 BBL) SHIPPING TANK (T-02) SERVED BY SHARED VAPOR CONTROL SYSTEM LISTED ON S-1737-157

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor loss prevention system capable of collecting all VOC emissions and preventing their emissions to the atmosphere at an efficiency of at least 95% by weight. [District Rule 4623] Federally Enforceable Through Title V Permit
2. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Fugitive VOC emissions shall be less than 0.5 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. All tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. All piping, valves, and fittings shall be constructed and maintained in a Leak-Free condition. [District Rules 2201 and 4623, 5.6.3] Federally Enforceable Through Title V Permit
6. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated to methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
7. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2201] Federally Enforceable Through Title V Permit
8. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information. [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
11. Formerly S-1132-83-0
12. Formerly S-4241-26-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-157-10

EXPIRATION DATE: 02/28/2018

SECTION: NW03 **TOWNSHIP:** 28S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

63,000 GALLON FIXED ROOF WASH TANK (T-01) WITH VAPOR CONTROL SHARED WITH S-1737-158, '-159, '-160, '-161, AND OPTIONAL PORTABLE TANKS S-1737-181, '-182, '-183, AND/OR '-184 VENTING TO GAS SALES LINE, 41.7 MMBTU/HR COANDA TIP FLARE, FLARES S-1737-167 AND '-180 AND/OR 2.0 MMBTU/HR PRODUCTION HEATER (S-1737-160)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device that reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
3. VOC fugitive emissions from the components in gas service on tank and tank vapor collection system) shall not exceed 0.5 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rules 4623] Federally Enforceable Through Title V Permit
5. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Permittee shall maintain accurate component count for tank according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors < 10,000 ppmv. Permittee shall update such records when new components are approved and installed. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2201] Federally Enforceable Through Title V Permit
8. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
9. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 2201 and 4623] Federally Enforceable Through Title V Permit
11. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
12. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
13. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
14. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
15. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
16. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
17. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rules 4623 and 2080] Federally Enforceable Through Title V Permit
18. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rules 4623 and 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

19. This tank shall be degassed before commencing interior cleaning by 1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less 2) by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia, or 3) by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623] Federally Enforceable Through Title V Permit
20. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623] Federally Enforceable Through Title V Permit
21. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rules 4623] Federally Enforceable Through Title V Permit
22. This tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid having a TVP of 0.5 psia or greater. [District Rule 4623] Federally Enforceable Through Title V Permit
23. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit
24. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit
25. The permittee shall keep accurate records of the dates of inspection and monitoring and the components inspected and monitored. [District Rule 2201] Federally Enforceable Through Title V Permit
26. Gas rate to the production heater shall not exceed 40,000 scf per day. [District Rule 2201] Federally Enforceable Through Title V Permit
27. The 41.7 MMBtu/hr flare shall be equipped with flared gas flow meter. [District Rules 2201 and 4311] Federally Enforceable Through Title V Permit
28. Gas rate to the 41.7 MMBtu/hr flare shall not exceed 4.0 MMscf per day nor 438.0 MMscf per year. [District Rule 2201] Federally Enforceable Through Title V Permit
29. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
30. Emission rates for the 41.7 MMBtu/hr flare shall not exceed any of the following: PM10: 20 lb/MMscf, NOx (as NO2): 68 lb/MMscf, VOC: 33 lb/MMscf, or CO: 38 lb/MMscf. [District Rule 2201] Federally Enforceable Through Title V Permit
31. Sulfur content of gas burned in the 41.7 MMBtu/hr flare or the heater shall not exceed 0.3 gr/100 scf as sulfur. [District Rules 2201 and 4801] Federally Enforceable Through Title V Permit
32. The sulfur content of the gas being incinerated in the 41.7 MMBtu/hr flare shall be determined using ASTM Test Methods D3246, D4084, D4810, double GC for H2S and mercaptans, or other method approved by the APCO. [District Rule 2201] Federally Enforceable Through Title V Permit
33. Permittee shall measure sulfur content of gas incinerated at least once per year. [District Rules 2201 and 4801] Federally Enforceable Through Title V Permit
34. The outlet shall be equipped with an automatic ignition system, or, shall operate with a pilot flame present at all times when combustible gases are vented through the 41.7 MMBtu/hr flare, except during purge periods for automatic-ignition equipped flares. [District Rule 4311, 5.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

35. Except for flares equipped with a flow-sensing ignition system, a heat sensing device such as a thermocouple, ultraviolet beam sensor, infrared sensor, or an equivalent device, capable of continuously detecting at least one pilot flame or the flare flame is present, shall be installed and operated. [District Rule 4311, 5.4] Federally Enforceable Through Title V Permit
36. Flares that use flow-sensing automatic ignition systems and which do not use a continuous flame pilot shall use purge gas for purging. [District Rule 4311, 5.5] Federally Enforceable Through Title V Permit
37. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
38. Permittee shall maintain accurate records of the daily amounts and annual vapor H₂S concentration of the gas burned in the 41.7 MMBtu/hr flare and production heater. [District Rules 2201 and 4311] Federally Enforceable Through Title V Permit
39. The permittee shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2201 and 4623] Federally Enforceable Through Title V Permit
40. Formerly S-1132-82-0
41. Formerly S-4241-25-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-155-3

EXPIRATION DATE: 02/28/2018

SECTION: SW34 **TOWNSHIP:** 28S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

8,820 GALLON (210 BBL) FIXED ROOF PRODUCED WATER STORAGE TANK WITH PRESSURE/VACUUM RELIEF VALVE AND VENT LINE TO OIL SHIPPING TANKS (TULARE 34-1, NORTH SHAFTER FIELD)

PERMIT UNIT REQUIREMENTS

1. Only produced water shall be stored in this tank with no visible oil pad. [District Rule 2201] Federally Enforceable Through Title V Permit
2. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 11 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
3. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in leak-free condition except when the operating pressure exceeds the valve's set pressure. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
5. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Formerly S-1132-61-0
7. Formerly S-4241-23-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-148-3

EXPIRATION DATE: 02/28/2018

SECTION: 03 **TOWNSHIP:** 28S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

8,820 GALLON SHIPPING TANK (TULARE 3-1 SHIPPING TANK #2)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 11 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Volatile organic compound (VOC) emission rate shall not exceed 1.98 lb/ day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in leak-free condition except when the operating pressure exceeds the valve's set pressure. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
5. TVP shall be calculated using CARB approved correlation from most recent Reid Vapor Pressure (RVP). Testing for RVP shall be conducted annually. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Permittee shall maintain accurate daily records of throughput, true vapor pressure, temperature of liquids stored and VOC emissions, and shall make such records available for District inspection for a period of five years. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
7. Formerly S-1132-28-0
8. Formerly S-4241-12-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-146-3

EXPIRATION DATE: 02/28/2018

SECTION: NW03 **TOWNSHIP:** 28S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

4.2 MMBTU/HR COANDA EFFECT SMOKELESS FLARE INCINERATING PRODUCED GAS FROM PRIMARY PRODUCTION WELL (TULARE 3-1, NORTH SHAFTER FIELD)

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is dark or darker than Ringelmann 1/4 or equivalent to 5% opacity. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Flare shall be equipped with a gas flow meter measuring total fuel flow to the flare. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Waste gas flow rate to flare shall not exceed 50 MSCFD. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Emission rates shall not exceed the following: PM10: 0.020 lb/MMBTU, SO_x (as SO₂): 0.001 lb/MMBTU, NO_x (as NO₂): 0.068 lb/MMBTU, VOC: 0.088 lb/MMBTU and CO: 0.37 lb/MMBTU. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Sulfur content of gases burned in flare shall not exceed 0.3 gr/100 SCF as H₂S. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The sulfur content of the gas being flared shall be determined using ASTM D1072, D3031, D4084, D3246, or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit
7. The gas being flared shall be tested for sulfur content and higher heating value semi-annually. If a semi-annual sulfur content test fails to show compliance, then the compliance testing frequency shall be weekly. If compliance with fuel sulfur content limit has been demonstrated for 8 consecutive weeks, the frequency of testing shall resume to semi-annually. [District Rules 2080 and 4801] Federally Enforceable Through Title V Permit
8. The flame shall be present at all times when combustible gases are vented through the flare. [District Rule 4311, 5.2] Federally Enforceable Through Title V Permit
9. The outlet shall be equipped with an automatic ignition system, or, shall operate with a pilot flame present at all times when combustible gases are vented through the flare, except during purge periods for automatic-ignition equipped flares. [District Rule 4311, 5.3] Federally Enforceable Through Title V Permit
10. Except for flares equipped with a flow-sensing ignition system, a heat sensing device such as a thermocouple, ultraviolet beam sensor, infrared sensor, or an equivalent device, capable of continuously detecting at least one pilot flame or the flare flame is present, shall be installed and operated. [District Rule 4311, 5.4] Federally Enforceable Through Title V Permit
11. Flares that use flow-sensing automatic ignition systems and which do not use a continuous flame pilot shall use purge gas for purging. [District Rule 4311, 5.5] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. The permittee shall keep accurate records of date, time, amount and sulfur content of gas flared. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
13. Formerly S-1132-26-1
14. Formerly S-4241-10-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-145-3

EXPIRATION DATE: 02/28/2018

SECTION: NW03 **TOWNSHIP:** 28S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

8,820 GALLON FIXED ROOF CRUDE OIL STORAGE TANK WITH PV VENT (WW#3)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 11 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Volatile organic compound (VOC) emission rate shall not exceed 1.98 lb/ day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in leak-free condition except when the operating pressure exceeds the valve's set pressure. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
5. TVP shall be calculated using CARB approved correlation from most recent Reid Vapor Pressure (RVP). Testing for RVP shall be conducted annually. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Permittee shall maintain accurate daily records of throughput, true vapor pressure, temperature of liquids stored and VOC emissions, and shall make such records available for District inspection for a period of five years. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
7. Formerly S-1132-25-1
8. Formerly S-4241-9-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-144-3

EXPIRATION DATE: 02/28/2018

SECTION: 34 **TOWNSHIP:** 27S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

8,820 GALLON SHIPPING TANK (TULARE 34-3 SHIPPING TANK #5)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 11 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Volatile organic compound (VOC) emission rate shall not exceed 1.98 lb/ day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in leak-free condition except when the operating pressure exceeds the valve's set pressure. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
5. TVP shall be calculated using CARB approved correlation from most recent Reid Vapor Pressure (RVP). Testing for RVP shall be conducted annually. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Permittee shall maintain accurate daily records of throughput, true vapor pressure, temperature of liquids stored and VOC emissions, and shall make such records available for District inspection for a period of five years. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
7. Formerly S-1132-24-0
8. Formerly S-4241-8-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-143-3

EXPIRATION DATE: 02/28/2018

SECTION: 34 **TOWNSHIP:** 27S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

8,820 GALLON SHIPPING TANK (TULARE 34-3 SHIPPING TANK #4)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 11 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Volatile organic compound (VOC) emission rate shall not exceed 1.98 lb/ day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in leak-free condition except when the operating pressure exceeds the valve's set pressure. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
5. TVP shall be calculated using CARB approved correlation from most recent Reid Vapor Pressure (RVP). Testing for RVP shall be conducted annually. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Permittee shall maintain accurate daily records of throughput, true vapor pressure, temperature of liquids stored and VOC emissions, and shall make such records available for District inspection for a period of five years. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
7. Formerly S-1132-23-0
8. Formerly S-4241-7-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-142-3

EXPIRATION DATE: 02/28/2018

SECTION: NW03 **TOWNSHIP:** 28S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

8,820 GALLON FIXED ROOF CRUDE OIL STORAGE TANK WITH PV VENT (TANK ID WW#2)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 11 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Volatile organic compound (VOC) emission rate shall not exceed 1.99 lb/ day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in leak-free condition except when the operating pressure exceeds the valve's set pressure. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
5. TVP shall be calculated using CARB approved correlation from most recent Reid Vapor Pressure (RVP). Testing for RVP shall be conducted annually. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Permittee shall maintain accurate daily records of throughput, true vapor pressure, temperature of liquids stored and VOC emissions, and shall make such records available for District inspection for a period of five years. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
7. Formerly S-1132-22-1
8. Formerly S-4241-6-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-141-3

EXPIRATION DATE: 02/28/2018

SECTION: NW34 **TOWNSHIP:** 27S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

8,820 GALLON FIXED ROOF PETROLEUM SHIPPING TANK WITH PV VENT (ID: TULARE 34-2 SHIPPING TANK #2)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 11 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Volatile organic compound (VOC) emission rate shall not exceed 1.99 lb/ day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in leak-free condition except when the operating pressure exceeds the valve's set pressure. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Permittee shall maintain accurate daily records of throughput, true vapor pressure, temperature of liquids stored and VOC emissions, and shall make such records available for District inspection for a period of five years. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
6. Formerly S-1132-21-0
7. Formerly S-4241-5-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-140-3

EXPIRATION DATE: 02/28/2018

SECTION: NW34 **TOWNSHIP:** 27S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

8,820 GALLON FIXED ROOF PETROLEUM SHIPPING TANK WITH PV VENT (ID: TULARE 34-2 SHIPPING TANK #1)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 11 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Volatile organic compound (VOC) emission rate shall not exceed 1.99 lb/ day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in leak-free condition except when the operating pressure exceeds the valve's set pressure. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Permittee shall maintain accurate daily records of throughput, true vapor pressure, temperature of liquids stored and VOC emissions, and shall make such records available for District inspection for a period of five years. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
6. Formerly S-1132-20-0
7. Formerly S-4241-4-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-139-3

EXPIRATION DATE: 02/28/2018

SECTION: SE34 **TOWNSHIP:** 27S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

8,820 GALLON FIXED ROOF PETROLEUM SHIPPING TANK WITH PV VENT (ID: TULARE 34-1 SHIPPING TANK #3)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 11 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Volatile organic compound (VOC) emission rate shall not exceed 1.99 lb/ day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in leak-free condition except when the operating pressure exceeds the valve's set pressure. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Permittee shall maintain accurate daily records of throughput, true vapor pressure, temperature of liquids stored and VOC emissions, and shall make such records available for District inspection for a period of five years. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
6. Formerly S-1132-18-0
7. Formerly S-4241-3-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-138-3

EXPIRATION DATE: 02/28/2018

SECTION: SE34 **TOWNSHIP:** 27S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

8,820 GALLON FIXED ROOF PETROLEUM SHIPPING TANK WITH PV VENT (ID: TULARE 34-1 SHIPPING TANK #2)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 11 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Volatile organic compound (VOC) emission rate shall not exceed 1.99 lb/ day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in leak-free condition except when the operating pressure exceeds the valve's set pressure. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Permittee shall maintain accurate daily records of throughput, true vapor pressure, temperature of liquids stored and VOC emissions, and shall make such records available for District inspection for a period of five years. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
6. Formerly S-1132-17-0
7. Formerly S-4241-2-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-137-3

EXPIRATION DATE: 02/28/2018

SECTION: SE34 **TOWNSHIP:** T27 **RANGE:** R25

EQUIPMENT DESCRIPTION:

8,820 GALLON FIXED ROOF PETROLEUM SHIPPING TANK WITH PV VENT (ID: TULARE 34-1 SHIPPING TANK #1)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 11 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Volatile organic compound (VOC) emission rate shall not exceed 1.99 lb/ day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in leak-free condition except when the operating pressure exceeds the valve's set pressure. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Permittee shall maintain accurate daily records of throughput, true vapor pressure, temperature of liquids stored and VOC emissions, and shall make such records available for District inspection for a period of five years. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
6. Formerly S-1132-16-0
7. Formerly S-4241-1-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-120-6

EXPIRATION DATE: 02/28/2018

SECTION: 34 **TOWNSHIP:** 11N **RANGE:** 19W

EQUIPMENT DESCRIPTION:

42,000 GALLON FIXED ROOF PETROLEUM STORAGE TANK (TEJON)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct True Vapor Pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. In lieu of testing each uncontrolled fixed roof tank, an operator may conduct a TVP testing of a representative tank provided the following requirements are met. The selection of representative, uncontrolled fixed roof tanks is submitted in writing to the APCO, and written approval is granted by the APCO prior to conducting the test. One uncontrolled fixed roof tank represents some or all of the tanks in a tank battery. For crude oil production facilities, the representative uncontrolled fixed roof tank shall be the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. The stored organic liquid in each of the represented tanks is the same and came from the same source. The TVP and storage temperature of the stored organic liquid of the representative tank to be tested are the same or higher than those of the tanks it is to represent. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. If the tank stores crude oil or petroleum distillates, the operator shall also conduct an API gravity testing. [District Rule 4623, 6.2.1.2] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit
6. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit
7. For other organic liquids, the true vapor pressure (TVP) shall be measured using Reid vapor pressure ASTM Method D323, and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance of the oil and gas section of "California Air Resources Boards (ARB) Technical Guidance Document to the Criteria and Guidelines Regulations for AB 2588", dated August 1989. As an alternative to using ASTM D 323, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

8. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
9. This tank shall be subject to the requirements of Rule 4623 if the tank loses its exemption under section 4.0 on the date the exemption status is lost. [Rule 4623, 7.2] Federally Enforceable Through Title V Permit
10. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
11. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
12. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-115-7

EXPIRATION DATE: 02/28/2018

SECTION: 34 **TOWNSHIP:** 11N **RANGE:** 19W

EQUIPMENT DESCRIPTION:

31,500 GALLON FIXED ROOF PETROLEUM STORAGE TANK (TEJON)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct True Vapor Pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. In lieu of testing each uncontrolled fixed roof tank, an operator may conduct a TVP testing of a representative tank provided the following requirements are met. The selection of representative, uncontrolled fixed roof tanks is submitted in writing to the APCO, and written approval is granted by the APCO prior to conducting the test. One uncontrolled fixed roof tank represents some or all of the tanks in a tank battery. For crude oil production facilities, the representative uncontrolled fixed roof tank shall be the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. The stored organic liquid in each of the represented tanks is the same and came from the same source. The TVP and storage temperature of the stored organic liquid of the representative tank to be tested are the same or higher than those of the tanks it is to represent. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. If the tank stores crude oil or petroleum distillates, the operator shall also conduct an API gravity testing. [District Rule 4623, 6.2.1.2] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit
6. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit
7. For other organic liquids, the true vapor pressure (TVP) shall be measured using Reid vapor pressure ASTM Method D323, and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance of the oil and gas section of "California Air Resources Boards (ARB) Technical Guidance Document to the Criteria and Guidelines Regulations for AB 2588", dated August 1989. As an alternative to using ASTM D 323, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

8. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
9. This tank shall be subject to the requirements of Rule 4623 if the tank loses its exemption under section 4.0 on the date the exemption status is lost. [Rule 4623, 7.2] Federally Enforceable Through Title V Permit
10. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
11. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
12. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-113-7

EXPIRATION DATE: 02/28/2018

SECTION: 34 **TOWNSHIP:** 11N **RANGE:** 19W

EQUIPMENT DESCRIPTION:

42,000 GALLON FIXED ROOF PETROLEUM STORAGE TANK #1171 (TEJON)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct True Vapor Pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. In lieu of testing each uncontrolled fixed roof tank, an operator may conduct a TVP testing of a representative tank provided the following requirements are met. The selection of representative, uncontrolled fixed roof tanks is submitted in writing to the APCO, and written approval is granted by the APCO prior to conducting the test. One uncontrolled fixed roof tank represents some or all of the tanks in a tank battery. For crude oil production facilities, the representative uncontrolled fixed roof tank shall be the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. The stored organic liquid in each of the represented tanks is the same and came from the same source. The TVP and storage temperature of the stored organic liquid of the representative tank to be tested are the same or higher than those of the tanks it is to represent. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. If the tank stores crude oil or petroleum distillates, the operator shall also conduct an API gravity testing. [District Rule 4623, 6.2.1.2] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method)". Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit
6. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit
7. For other organic liquids, the true vapor pressure (TVP) shall be measured using Reid vapor pressure ASTM Method D323, and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance of the oil and gas section of "California Air Resources Boards (ARB) Technical Guidance Document to the Criteria and Guidelines Regulations for AB 2588", dated August 1989. As an alternative to using ASTM D 323, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

8. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
9. This tank shall be subject to the requirements of Rule 4623 if the tank loses its exemption under section 4.0 on the date the exemption status is lost. [Rule 4623, 7.2] Federally Enforceable Through Title V Permit
10. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
11. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
12. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-112-7

EXPIRATION DATE: 02/28/2018

SECTION: 34 **TOWNSHIP:** 11N **RANGE:** 19W

EQUIPMENT DESCRIPTION:

42,000 GALLON FIXED ROOF PETROLEUM STORAGE TANK #1172

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct True Vapor Pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. In lieu of testing each uncontrolled fixed roof tank, an operator may conduct a TVP testing of a representative tank provided the following requirements are met. The selection of representative, uncontrolled fixed roof tanks is submitted in writing to the APCO, and written approval is granted by the APCO prior to conducting the test. One uncontrolled fixed roof tank represents some or all of the tanks in a tank battery. For crude oil production facilities, the representative uncontrolled fixed roof tank shall be the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. The stored organic liquid in each of the represented tanks is the same and came from the same source. The TVP and storage temperature of the stored organic liquid of the representative tank to be tested are the same or higher than those of the tanks it is to represent. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. If the tank stores crude oil or petroleum distillates, the operator shall also conduct an API gravity testing. [District Rule 4623, 6.2.1.2] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit
6. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit
7. For other organic liquids, the true vapor pressure (TVP) shall be measured using Reid vapor pressure ASTM Method D323, and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance of the oil and gas section of "California Air Resources Boards (ARB) Technical Guidance Document to the Criteria and Guidelines Regulations for AB 2588", dated August 1989. As an alternative to using ASTM D 323, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

8. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
9. This tank shall be subject to the requirements of Rule 4623 if the tank loses its exemption under section 4.0 on the date the exemption status is lost. [Rule 4623, 7.2] Federally Enforceable Through Title V Permit
10. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
11. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
12. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-111-6

EXPIRATION DATE: 02/28/2018

SECTION: 34 **TOWNSHIP:** 11N **RANGE:** 19W

EQUIPMENT DESCRIPTION:

42,000 GALLON FIXED ROOF PETROLEUM STORAGE TANK #12176 (TEJON)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct True Vapor Pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. In lieu of testing each uncontrolled fixed roof tank, an operator may conduct a TVP testing of a representative tank provided the following requirements are met. The selection of representative, uncontrolled fixed roof tanks is submitted in writing to the APCO, and written approval is granted by the APCO prior to conducting the test. One uncontrolled fixed roof tank represents some or all of the tanks in a tank battery. For crude oil production facilities, the representative uncontrolled fixed roof tank shall be the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. The stored organic liquid in each of the represented tanks is the same and came from the same source. The TVP and storage temperature of the stored organic liquid of the representative tank to be tested are the same or higher than those of the tanks it is to represent. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. If the tank stores crude oil or petroleum distillates, the operator shall also conduct an API gravity testing. [District Rule 4623, 6.2.1.2] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit
6. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit
7. For other organic liquids, the true vapor pressure (TVP) shall be measured using Reid vapor pressure ASTM Method D323, and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance of the oil and gas section of "California Air Resources Boards (ARB) Technical Guidance Document to the Criteria and Guidelines Regulations for AB 2588", dated August 1989. As an alternative to using ASTM D 323, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

8. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
9. This tank shall be subject to the requirements of Rule 4623 if the tank loses its exemption under section 4.0 on the date the exemption status is lost. [Rule 4623, 7.2] Federally Enforceable Through Title V Permit
10. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
11. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
12. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-110-6

EXPIRATION DATE: 02/28/2018

SECTION: 34 **TOWNSHIP:** 11N **RANGE:** 19W

EQUIPMENT DESCRIPTION:

42,000 GALLON FIXED ROOF PETROLEUM STORAGE TANK #12177 (TEJON)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct True Vapor Pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. In lieu of testing each uncontrolled fixed roof tank, an operator may conduct a TVP testing of a representative tank provided the following requirements are met. The selection of representative, uncontrolled fixed roof tanks is submitted in writing to the APCO, and written approval is granted by the APCO prior to conducting the test. One uncontrolled fixed roof tank represents some or all of the tanks in a tank battery. For crude oil production facilities, the representative uncontrolled fixed roof tank shall be the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. The stored organic liquid in each of the represented tanks is the same and came from the same source. The TVP and storage temperature of the stored organic liquid of the representative tank to be tested are the same or higher than those of the tanks it is to represent. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. If the tank stores crude oil or petroleum distillates, the operator shall also conduct an API gravity testing. [District Rule 4623, 6.2.1.2] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method)". Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit
6. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit
7. For other organic liquids, the true vapor pressure (TVP) shall be measured using Reid vapor pressure ASTM Method D323, and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance of the oil and gas section of "California Air Resources Boards (ARB) Technical Guidance Document to the Criteria and Guidelines Regulations for AB 2588", dated August 1989. As an alternative to using ASTM D 323, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

8. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
9. This tank shall be subject to the requirements of Rule 4623 if the tank loses its exemption under section 4.0 on the date the exemption status is lost. [Rule 4623, 7.2] Federally Enforceable Through Title V Permit
10. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
11. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
12. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

DRAFT

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-200-2

EXPIRATION DATE: 02/28/2018

SECTION: SW 23 **TOWNSHIP:** 27S **RANGE:** 24E

EQUIPMENT DESCRIPTION:

500 BBL FIXED ROOF CRUDE OIL TANK VENTED TO VAPOR CONTROL SYSTEM LISTED ON TANK S-1737-172

PERMIT UNIT REQUIREMENTS

1. The tank and all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
2. All tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
3. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated to methane in accordance with the procedures specified in EPA Test Method 21. A gas leak is a violation of Rule 2201. [District Rule 2201] Federally Enforceable Through Title V Permit
4. VOC fugitive emissions from the components in gas service on the tank up to the vapor control system trunk line shall not exceed 0.2 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall maintain accurate component count for tank according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors < 10,000 ppmv. Permittee shall update such records when new components are approved and installed. [District Rule 2201] Federally Enforceable Through Title V Permit
6. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
7. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: CALIFORNIA RESOURCES PRODUCTION CORP

Location: LIGHT OIL CENTRAL, KERN COUNTY, CA

S-1737-200-2 Oct 5 2018 11:50AM -- OROZCOA

8. This tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623] Federally Enforceable Through Title V Permit
9. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623] Federally Enforceable Through Title V Permit
10. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623] Federally Enforceable Through Title V Permit
11. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623] Federally Enforceable Through Title V Permit
12. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623] Federally Enforceable Through Title V Permit
13. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
14. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623 shall constitute a violation of this rule. [District Rule 4623] Federally Enforceable Through Title V Permit
15. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623] Federally Enforceable Through Title V Permit
16. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 2201] Federally Enforceable Through Title V Permit
17. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

18. Operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 1070] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-193-2

EXPIRATION DATE: 02/28/2018

SECTION: SW 36 **TOWNSHIP:** 26S **RANGE:** 24E

EQUIPMENT DESCRIPTION:

3,000 BBL FIXED ROOF CRUDE OIL TANK VENTED TO VAPOR CONTROL SYSTEM LISTED ON TANK S-1737-168

PERMIT UNIT REQUIREMENTS

1. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
2. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
3. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
4. VOC fugitive emissions from the components in gas/light oil service on tank and from tank to vapor control, system trunk line shall not exceed 0.1 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall maintain accurate component count for tank according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors < 10,000 ppmv. Permittee shall update such records when new components are approved and installed. [District Rule 2201] Federally Enforceable Through Title V Permit
6. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
7. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
8. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 2201 and 4623] Federally Enforceable Through Title V Permit
9. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
11. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
12. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
13. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
14. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rules 4623 and 2080] Federally Enforceable Through Title V Permit
15. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rules 4623 and 2080] Federally Enforceable Through Title V Permit
16. This tank shall be degassed before commencing interior cleaning by 1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less 2) by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia. or 3) by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623] Federally Enforceable Through Title V Permit
17. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623] Federally Enforceable Through Title V Permit
18. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rules 4623] Federally Enforceable Through Title V Permit
19. This tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid having a TVP of 0.5 psia or greater. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

20. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit
21. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit
22. The permittee shall keep accurate records of the dates of inspection and monitoring and the components inspected and monitored. [District Rule 2201] Federally Enforceable Through Title V Permit
23. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
24. The permittee shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2201 and 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-186-1

EXPIRATION DATE: 02/28/2018

SECTION: SE 36 **TOWNSHIP:** 26S **RANGE:** 24E

EQUIPMENT DESCRIPTION:

500 BBL CRUDE OIL STORAGE TANK CONNECTED TO THE VAPOR CONTROL SYSTEM LISTED ON PERMIT S-1737-168

PERMIT UNIT REQUIREMENTS

1. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
2. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
3. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
4. VOC fugitive emissions from the components in gas/light oil service on tank and from tank to vapor control, system trunk line shall not exceed 0.3 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall maintain accurate component count for tank according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors < 10,000 ppmv. Permittee shall update such records when new components are approved and installed. [District Rule 2201] Federally Enforceable Through Title V Permit
6. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
7. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
8. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 2201 and 4623] Federally Enforceable Through Title V Permit
9. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
11. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
12. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
13. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rules 2201 and 4623]
14. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rules 4623 and 2080] Federally Enforceable Through Title V Permit
15. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rules 4623 and 2080] Federally Enforceable Through Title V Permit
16. This tank shall be degassed before commencing interior cleaning by 1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less 2) by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia. or 3) by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623] Federally Enforceable Through Title V Permit
17. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623] Federally Enforceable Through Title V Permit
18. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rules 4623] Federally Enforceable Through Title V Permit
19. This tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid having a TVP of 0.5 psia or greater. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

20. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit
21. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit
22. The permittee shall keep accurate records of the dates of inspection and monitoring and the components inspected and monitored. [District Rule 2201] Federally Enforceable Through Title V Permit
23. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
24. The permittee shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2201 and 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-185-1

EXPIRATION DATE: 02/28/2018

SECTION: SE 36 **TOWNSHIP:** 26S **RANGE:** 24E

EQUIPMENT DESCRIPTION:

500 BBL CRUDE OIL STORAGE TANK CONNECTED TO THE VAPOR CONTROL SYSTEM LISTED ON PERMIT S-1737-168

PERMIT UNIT REQUIREMENTS

1. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
2. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
3. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
4. VOC fugitive emissions from the components in gas/light oil service on tank and from tank to vapor control, system trunk line shall not exceed 0.3 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall maintain accurate component count for tank according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors < 10,000 ppmv. Permittee shall update such records when new components are approved and installed. [District Rule 2201] Federally Enforceable Through Title V Permit
6. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
7. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
8. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 2201 and 4623] Federally Enforceable Through Title V Permit
9. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
11. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
12. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
13. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
14. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rules 4623 and 2080] Federally Enforceable Through Title V Permit
15. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rules 4623 and 2080] Federally Enforceable Through Title V Permit
16. This tank shall be degassed before commencing interior cleaning by 1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less 2) by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia, or 3) by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623] Federally Enforceable Through Title V Permit
17. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623] Federally Enforceable Through Title V Permit
18. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rules 4623] Federally Enforceable Through Title V Permit
19. This tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid having a TVP of 0.5 psia or greater. [District Rule 4623] Federally Enforceable Through Title V Permit

DRAFT
PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

20. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit
21. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit
22. The permittee shall keep accurate records of the dates of inspection and monitoring and the components inspected and monitored. [District Rule 2201] Federally Enforceable Through Title V Permit
23. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
24. The permittee shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2201 and 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-180-4

EXPIRATION DATE: 02/28/2018

EQUIPMENT DESCRIPTION:

49 MMBTU/HR FLARE APPROVED FOR USE IN WELL TESTING, TANK AND WELL VENT CONTROL, EQUIPMENT SHUTDOWN, EMERGENCIES AND OTHER SITUATIONS REQUIRING A SAFETY FLARE AT VARIOUS UNSPECIFIED LOCATIONS

PERMIT UNIT REQUIREMENTS

1. Flare shall not be located within 1000 feet of any K-12 school. [CH&SC 42301.6]
2. The flare must not operate within 100 meter from the facility boundary. [District Rule 4102]
3. Permittee shall notify the District Compliance Division of each location at which the flare is located in excess of 24 hours. Such notification shall be made no later than 48 hours after starting operation at the location. [District Rule 1070] Federally Enforceable Through Title V Permit
4. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
5. Flare shall operate in a smokeless manner (0% opacity) except for three minutes in any one hour. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Flare gas inlet line shall be equipped with operational volumetric totalizing flowrate indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Gas flowrate to flare (not including pilot gas) shall not exceed 1.4 MMscf per day nor 255.5 MMscf/yr of gas. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Emission rates from this unit shall not exceed any of the following limits: NO_x (as NO₂) - 0.068 lb/Mscf; VOC (as methane) - 0.063 lb/Mscf; CO - 0.37 lb/Mscf or PM₁₀ - 0.008 lb/Mscf. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Gas sulfur content shall not exceed 0.25 gr/100 scf. [District Rules 2201 and 4801] Federally Enforceable Through Title V Permit
10. Gas shall be tested quarterly for sulfur content. Upon transfer of location or change in the method of operation of the flare (excluding emergencies), gas shall be tested weekly for sulfur content. If compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks then the fuel testing frequency shall be quarterly. If a quarterly fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The sulfur content of the gas being flared shall be determined using ASTM D1072, D3031, D4084, D3246, or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit
12. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by: ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

13. A trained observer, as defined in EPA Method 22, shall check visible emissions at least once every two weeks for a period of 15 minutes. If visible emissions are detected at any time during this period, the observation period shall be extended to two hours. A record containing the results of these observations shall be maintained, which also includes company name, process unit, observer's name and affiliation, date, estimated wind speed and direction, sky condition, and the observer's location relative to the source and sun. [District Rules 2080 and 4101] Federally Enforceable Through Title V Permit
14. The outlet shall be equipped with an automatic ignition system, or, shall operate with a pilot flame present at all times when combustible gases are vented through the flare, except during purge periods for automatic-ignition equipped flares. [District Rule 4311] Federally Enforceable Through Title V Permit
15. Permittee shall obtain an ATC to modify any permit unit which authorizes this flare as a control device prior to this flare operating as a control device for that permit unit. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Except for flares equipped with a flow-sensing ignition system, a heat sensing device such as a thermocouple, ultraviolet beam sensor, infrared sensor, or an equivalent device, capable of continuously detecting at least one pilot flame or the flare flame is present, shall be installed and operated. [District Rule 4311] Federally Enforceable Through Title V Permit
17. Flares that use flow-sensing automatic ignition systems and which do not use a continuous flame pilot shall use purge gas for purging. [District Rule 4311] Federally Enforceable Through Title V Permit
18. Open flares (air-assisted, steam assisted or non-assisted) in which the flare gas pressure is less than 5 psig shall be operated in such a manner that meets the provisions of 40 CFR 60.18. [District Rule 4311] Federally Enforceable Through Title V Permit
19. The flare shall be inspected every two weeks while in operation for visible emissions. If visible emissions are observed, corrective action shall be taken. If visible emissions continue, an EPA method 9 test shall be conducted within 72 hours. [District Rule 2201] Federally Enforceable Through Title V Permit
20. The flare shall be operated according to the manufacturer's specifications, a copy of which shall be maintained on site. [District Rule 2080] Federally Enforceable Through Title V Permit
21. Permittee shall maintain accurate daily records of volume, type, higher heating value, and sulfur content of gas flared [District Rule 2201 & 1070] Federally Enforceable Through Title V Permit
22. Permittee shall maintain accurate records of location and duration of operation at each stationary source. [District Rule 2201, 4311 & 4409] Federally Enforceable Through Title V Permit
23. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 2201, 4311 & 4409] Federally Enforceable Through Title V Permit

DRAFT

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-178-2

EXPIRATION DATE: 02/28/2018

SECTION: SW23 **TOWNSHIP:** 27S **RANGE:** 23E

EQUIPMENT DESCRIPTION:

25 FOOT TALL MACTRONIC AIR-ASSISTED PROCESS GAS FLARE SERVING VAPOR CONTROL SYSTEM LISTED ON S-1737-172, WITH 2 INCH DIAMETER FLARE GAS LINE, 6 INCH DIAMETER FLARE STACK, ELECTRONIC IGNITOR, AND FLAME ARRESTOR SERVED BY 20 BBL GAS-LIQUID SEPARATOR; 3 EACH, 3 BBL KNOCKOUT VESSELS; AND AN H2S SCAVENGER

PERMIT UNIT REQUIREMENTS

1. Gas shall be processed in the H2S scrubber as needed to meet 50 ppmv sulfur (as H2S) content limit. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Flare air-assist blower shall be maintained and operated for smokeless combustion, i.e. no visible emissions in excess of 5% opacity or 1/4 Ringelmann. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Flare shall be equipped with waste gas volume flow meter. [District Rule 2201] Federally Enforceable Through Title V Permit
4. This permit does not authorize the utilization of any IC engine, or other combustion device requiring a separate permit, for powering the air assist to the flare. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Flare shall operate in a smokeless manner (no greater than 5% opacity) except for three minutes in any one hour. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Operator shall immediately utilize air assist if flare exhibits smoke greater than 0% opacity. [District Rule 2201 and 4101] Federally Enforceable Through Title V Permit
7. Total sulfur (as H2S) concentration of gas incinerated in flare shall not exceed 50 ppmv. [District Rules 2201 and 4801] Federally Enforceable Through Title V Permit
8. The amount of gas combusted shall not exceed 100,000 scf/day. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Emissions from the flare shall not exceed any of the following (based on total gas combusted): NOx (as NO2): 0.068 lb/MMBtu; PM10: 0.008 lb/MMBtu; CO: 0.37 lb/MMBtu; or VOC: 0.063 lb/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Fugitive VOC emissions rate, calculated using CAPCOA California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities Table IV-2c less than or equal to 10,000 ppmv (Feb 1999), from the total number of tank components, including vapor control system components from the tank to the vapor control system trunk line shall not exceed 1.1 pounds per day. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Permittee shall comply with all applicable requirements of Rule 4311. [District Rule 4311] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. All piping, valves and fittings shall be constructed and maintained in a gas-tight condition. Gas-tight shall be defined as emitting no more than 10,000 ppmv of methane measured at the potential source with an instrument calibrated with methane in accordance with EPA Method 21. Emissions in excess of this limit shall be considered a leak. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Permittee shall measure sulfur content of gas incinerated in flare at least once every year. Such data shall be submitted to the District within 60 days of sample collection. [District Rules 2201 and 4801] Federally Enforceable Through Title V Permit
14. Permittee shall determine sulfur content of gas flared using ASTM method D3246 or double GC for H₂S and mercaptans. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Permittee shall keep accurate records of daily, quarterly, and annual quantity of gas combusted, and such records shall be retained for a period of five years and made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: CALIFORNIA RESOURCES PRODUCTION CORP

Location: LIGHT OIL CENTRAL, KERN COUNTY, CA

S-1737-178-2 Oct 5 2018 11:50AM - OROZCOA

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-177-2

EXPIRATION DATE: 02/28/2018

SECTION: SW 23 **TOWNSHIP:** 27S **RANGE:** 23E

EQUIPMENT DESCRIPTION:

0.5 MMBTU/HR FIELD GAS-FIRED HEATER (SEMITROPIC TANK BATTERY)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grain/dscf at operating conditions, nor 0.1 grain/dscf calculated to 12% CO₂, nor 10 lb/hr. [District Rule 4201 and District Rule 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
2. Emissions of sulfur compounds from this unit shall not exceed 200 lb per hour, calculated as SO₂. [District Rules 4301, 5.2.1] Federally Enforceable Through Title V Permit
3. Emissions of nitrogen oxides from this unit shall not exceed 140 lb per hour, calculated as NO₂. [District Rule 4301, 5.2.1] Federally Enforceable Through Title V Permit
4. Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [District Rule 4801]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-176-2

EXPIRATION DATE: 02/28/2018

SECTION: SW 23 **TOWNSHIP:** 27S **RANGE:** 23E

EQUIPMENT DESCRIPTION:

4200 GALLON FIXED ROOF SLOP TANK VENTED TO VAPOR CONTROL SYSTEM LISTED ON S-1737-172
(SEMITROPIC TANK BATTERY)

PERMIT UNIT REQUIREMENTS

1. Combined VOC emissions rate from the components associated with the tank in gas, light liquid and light crude oil service shall not exceed 0.1 pounds per day. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Any tank gauging or sampling device on this tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
3. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Leak-free shall be a condition without a gas leak or a liquid leak. Gas Leak shall be defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the EPA Method 21. Liquid leak is shall be defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Permittee shall maintain a log indicating component type, number of components, appropriate emission factors from CAPCOA 's document "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities" Table IV-2c (Feb 1999) - Screening Range Emissions Factors, and resultant emissions to demonstrate on-going compliance with the daily emission limit. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Hatch, tank seals and seams, cable seals, piping components directly affixed to the tank including but not limited to valves, flanges, connectors etc. shall be inspected and monitored at least once every quarter by the operator using portable hydrocarbon detection instrument in accordance with EPA Method 21. If a component type found to leak during the quarterly inspection, then conduct monthly inspections of that component type for two consecutive months. If a component type is found to have no leak after two consecutive months, then revert to quarterly inspections. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall keep records of the dates on which components are inspected and monitored, and number of components inspected corresponding to each component type. For leaking components, the operator shall immediately affix a tag and maintain records of liquid leak and gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
8. All records shall be retained for a minimum of five years, and shall be made available for District inspection upon request. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-175-2

EXPIRATION DATE: 02/28/2018

SECTION: SW 23 **TOWNSHIP:** 27S **RANGE:** 23E

EQUIPMENT DESCRIPTION:

21,000 GALLON FIXED ROOF SKIM TANK VENTED TO VAPOR CONTROL SYSTEM LISTED ON S-1737-172
(SEMITROPIC TANK BATTERY)

PERMIT UNIT REQUIREMENTS

1. Combined VOC emissions rate from the components associated with the tank in gas, light liquid and light crude oil service shall not exceed 0.2 pounds per day. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Any tank gauging or sampling device on this tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
3. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Leak-free shall be a condition without a gas leak or a liquid leak. Gas Leak shall be defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the EPA Method 21. Liquid leak is shall be defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Permittee shall maintain a log indicating component type, number of components, appropriate emission factors from CAPCOA 's document "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities" Table IV-2c (Feb 1999) - Screening Range Emissions Factors, and resultant emissions to demonstrate on-going compliance with the daily emission limit. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall keep records of the dates on which components are inspected and monitored, and number of components inspected corresponding to each component type. For leaking components, the operator shall immediately affix a tag and maintain records of liquid leak and gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Hatch, tank seals and seams, cable seals, piping components directly affixed to the tank including but not limited to valves, flanges, connectors etc. shall be inspected and monitored at least once every quarter by the operator using portable hydrocarbon detection instrument in accordance with EPA Method 21. If a component type found to leak during the quarterly inspection, then conduct monthly inspections of that component type for two consecutive months. If a component type is found to have no leak after two consecutive months, then revert to quarterly inspections. [District Rule 2201] Federally Enforceable Through Title V Permit
8. All records shall be retained for a minimum of five years, and shall be made available for District inspection upon request. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-174-2

EXPIRATION DATE: 02/28/2018

SECTION: SW 23 **TOWNSHIP:** 27S **RANGE:** 23E

EQUIPMENT DESCRIPTION:

21,000 GALLON FIXED ROOF STOCK TANK VENTED TO VAPOR CONTROL SYSTEM LISTED ON S-1737-172
(SEMITROPIC TANK BATTERY)

PERMIT UNIT REQUIREMENTS

1. Combined VOC emissions rate from the components associated with the tank in gas, light liquid and light crude oil service shall not exceed 0.2 pounds per day. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Any tank gauging or sampling device on this tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
3. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Leak-free shall be a condition without a gas leak or a liquid leak. Gas Leak shall be defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the EPA Method 21. Liquid leak is shall be defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Permittee shall maintain a log indicating component type, number of components, appropriate emission factors from CAPCOA 's document "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities" Table IV-2c (Feb 1999) - Screening Range Emissions Factors, and resultant emissions to demonstrate on-going compliance with the daily emission limit. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Hatch, tank seals and seams, cable seals, piping components directly affixed to the tank including but not limited to valves, flanges, connectors etc. shall be inspected and monitored at least once every quarter by the operator using portable hydrocarbon detection instrument in accordance with EPA Method 21. If a component type found to leak during the quarterly inspection, then conduct monthly inspections of that component type for two consecutive months. If a component type is found to have no leak after two consecutive months, then revert to quarterly inspections. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall keep records of the dates on which components are inspected and monitored, and number of components inspected corresponding to each component type. For leaking components, the operator shall immediately affix a tag and maintain records of liquid leak and gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
8. All records shall be retained for a minimum of five years, and shall be made available for District inspection upon request. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-173-2

EXPIRATION DATE: 02/28/2018

SECTION: SW 23 **TOWNSHIP:** 27S **RANGE:** 23E

EQUIPMENT DESCRIPTION:

21,000 GALLON FIXED ROOF STOCK TANK VENTED TO VAPOR CONTROL SYSTEM LISTED ON S-1737-172
(SEMITROPIC TANK BATTERY)

PERMIT UNIT REQUIREMENTS

1. Combined VOC emissions rate from the components associated with the tank in gas, light liquid and light crude oil service shall not exceed 0.2 pounds per day. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Any tank gauging or sampling device on this tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
3. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Leak-free shall be a condition without a gas leak or a liquid leak. Gas Leak shall be defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the EPA Method 21. Liquid leak is shall be defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Permittee shall maintain a log indicating component type, number of components, appropriate emission factors from CAPCOA 's document "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities" Table IV-2c (Feb 1999) - Screening Range Emissions Factors, and resultant emissions to demonstrate on-going compliance with the daily emission limit. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Hatch, tank seals and seams, cable seals, piping components directly affixed to the tank including but not limited to valves, flanges, connectors etc. shall be inspected and monitored at least once every quarter by the operator using portable hydrocarbon detection instrument in accordance with EPA Method 21. If a component type found to leak during the quarterly inspection, then conduct monthly inspections of that component type for two consecutive months. If a component type is found to have no leak after two consecutive months, then revert to quarterly inspections. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall keep records of the dates on which components are inspected and monitored, and number of components inspected corresponding to each component type. For leaking components, the operator shall immediately affix a tag and maintain records of liquid leak and gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
8. All records shall be retained for a minimum of five years, and shall be made available for District inspection upon request. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-172-9

EXPIRATION DATE: 02/28/2018

SECTION: SW 23 **TOWNSHIP:** 27S **RANGE:** 23E

EQUIPMENT DESCRIPTION:

12,600 GALLON CRUDE OIL WASH TANK WITH VAPOR CONTROL SYSTEM INCLUDING COMPRESSOR, SERVED BY FLARE AND HYDROGEN SULFIDE SCAVENGER SYSTEM LISTED ON S-1737-178, SHARED WITH S-1737-173, -174, -175, -176, AND '200 (SEMITROPIC TANK BATTERY)

PERMIT UNIT REQUIREMENTS

1. Combined VOC emissions rate from the components associated with the tank and the vapor recovery system in gas, light liquid and light crude oil service shall not exceed 0.4 pounds per day. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Vapor recovery system shall be maintained in leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
3. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device that reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on this tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
5. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Leak-free shall be a condition without a gas leak or a liquid leak. Gas Leak shall be defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the EPA Method 21. Liquid leak is shall be defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Permittee shall maintain a log indicating component type, number of components, appropriate emission factors from CAPCOA 's document "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities" Table IV-2c (Feb 1999) - Screening Range Emissions Factors, and resultant emissions to demonstrate on-going compliance with the daily emission limit. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

8. Hatch, tank seals and seams, cable seals, piping components directly affixed to the tank, components for vapor recovery system including but not limited to valves, flanges, connectors etc. shall be inspected and monitored at least once every quarter by the operator using portable hydrocarbon detection instrument in accordance with EPA Method 21. If a component type found to leak during the quarterly inspection, then conduct monthly inspections of that component type for two consecutive months. If a component type is found to have no leak after two consecutive months, then revert to quarterly inspections. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The operator shall keep records of the dates on which components are inspected and monitored, and number of components inspected corresponding to each component type. For leaking components, the operator shall immediately affix a tag and maintain records of liquid leak and gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records shall be retained for a minimum of five years, and shall be made available for District inspection upon request. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

DRAFT

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-171-3

EXPIRATION DATE: 02/28/2018

SECTION: SE 36 **TOWNSHIP:** 26S **RANGE:** 24E

EQUIPMENT DESCRIPTION:

21,000 GALLON FIXED ROOF CRUDE OIL GAUGE STORAGE TANK SERVED BY VAPOR RECOVERY SYSTEM
SHARED WITH S-1737-168

PERMIT UNIT REQUIREMENTS

1. The API gravity of any organic liquid stored or processed in this tank shall be less than 30°. [District Rule 2201] Federally Enforceable Through Title V Permit
2. VOC fugitive emissions from the components in gas service on tank (if permit includes the vapor control system Insert: and tank vapor collection system) shall not exceed 0.1 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The tank shall be vented to a vapor control system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor control system shall be APCO-approved and maintained in leak-free condition. Vapors shall be discharged to approved control devices having a destruction efficiency of at least 99% by weight. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
4. Permittee shall maintain accurate component count for tank according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors < 10,000 ppmv. Permittee shall update such records when new components are approved and installed. [District Rule 2201] Federally Enforceable Through Title V Permit
5. All piping, valves, and fittings shall be constructed and maintained in a Leak-Free condition. [District Rules 2201 and 4623, 5.6.3] Federally Enforceable Through Title V Permit
6. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated to methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate more than 3 drops per minute. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
7. Any tank gauging or sampling device on a tank vented to the vapor control system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
8. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
9. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
11. The permittee shall keep accurate records of each organic liquid stored in the tank, including its type and API gravity. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-170-3

EXPIRATION DATE: 02/28/2018

SECTION: SE 36 **TOWNSHIP:** 26S **RANGE:** 24E

EQUIPMENT DESCRIPTION:

21,000 GALLON FIXED ROOF CRUDE OIL GAUGE STORAGE TANK SERVED BY VAPOR RECOVERY SYSTEM
SHARED WITH S-1737-168

PERMIT UNIT REQUIREMENTS

1. The API gravity of any organic liquid stored or processed in this tank shall be less than 30ø. [District Rule 2201] Federally Enforceable Through Title V Permit
2. VOC fugitive emissions from the components in gas service on tank (if permit includes the vapor control system Insert: and tank vapor collection system) shall not exceed 0.1 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The tank shall be vented to a vapor control system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor control system shall be APCO-approved and maintained in leak-free condition. Vapors shall be discharged to approved control devices having a destruction efficiency of at least 99% by weight. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
4. Permittee shall maintain accurate component count for tank according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors < 10,000 ppmv. Permittee shall update such records when new components are approved and installed. [District Rule 2201] Federally Enforceable Through Title V Permit
5. All piping, valves, and fittings shall be constructed and maintained in a Leak-Free condition. [District Rules 2201 and 4623, 5.6.3] Federally Enforceable Through Title V Permit
6. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated to methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate more than 3 drops per minute. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
7. Any tank gauging or sampling device on a tank vented to the vapor control system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
8. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
9. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
11. The permittee shall keep accurate records of each organic liquid stored in the tank, including its type and API gravity. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-169-3

EXPIRATION DATE: 02/28/2018

SECTION: E36 **TOWNSHIP:** **RANGE:**

EQUIPMENT DESCRIPTION:

126,000 GALLON FIXED ROOF CRUDE OIL GAUGE STORAGE TANK SERVED BY VAPOR RECOVERY SYSTEM
SHARED WITH S-1737-168

PERMIT UNIT REQUIREMENTS

1. The API gravity of any organic liquid stored or processed in this tank shall be less than 30ø. [District Rule 2201] Federally Enforceable Through Title V Permit
2. VOC fugitive emissions from the components in gas service on tank (if permit includes the vapor control system Insert: and tank vapor collection system) shall not exceed 0.1 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The tank shall be vented to a vapor control system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor control system shall be APCO-approved and maintained in leak-free condition. Vapors shall be discharged to approved control devices having a destruction efficiency of at least 99% by weight. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
4. Permittee shall maintain accurate component count for tank according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors < 10,000 ppmv. Permittee shall update such records when new components are approved and installed. [District Rule 2201] Federally Enforceable Through Title V Permit
5. All piping, valves, and fittings shall be constructed and maintained in a Leak-Free condition. [District Rules 2201 and 4623, 5.6.3] Federally Enforceable Through Title V Permit
6. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated to methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate more than 3 drops per minute. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
7. Any tank gauging or sampling device on a tank vented to the vapor control system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
8. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
9. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
11. The permittee shall keep accurate records of each organic liquid stored in the tank, including its type and API gravity. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-168-17

EXPIRATION DATE: 02/28/2018

SECTION: SE36 **TOWNSHIP:** 26S **RANGE:** 24E

EQUIPMENT DESCRIPTION:

126,000 GALLON FIXED ROOF CRUDE OIL GAUGE STORAGE TANK, 3-PHASE SEPARATOR, TWO HEATER TREATERS (EACH WITH BURNER(S) RATED AT 5 MMBTU/HR OR LESS), TWO 2-PHASE SEPARATORS SERVED BY VAPOR RECOVERY SYSTEM SHARED WITH TANKS S-1737-169, '-170, '-171 AND '-193. VAPOR RECOVERY SYSTEM CONSISTS OF COMPRESSOR AND ASSOCIATED PIPING DISCHARGING TO FLARE S-1737-180-0 AND/OR SALES GAS LINE

PERMIT UNIT REQUIREMENTS

1. Gases from the tanks, heater treaters, and all separators shall be flared or routed to a sales pipeline. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The API gravity of any organic liquid stored or processed in this tank shall be less than 30ø. [District Rules 2201 and 4409] Federally Enforceable Through Title V Permit
3. Fugitive VOC emissions from all components associated with this tank shall not exceed 0.14 lb/day as calculated using CAPCOA California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities, Table IV-2c, Oil and Gas Production Screening Value Ranges Emission Factors (Feb 1999). [District Rule 2201] Federally Enforceable Through Title V Permit
4. The storage tank shall be fully enclosed and shall be maintained in a leak-free condition. The storage tank shall be connected to an APCO-approved vapor recovery system consisting of a closed system that collects all VOCs from the storage tank(s) and a VOC control device. The vapor recovery system shall be maintained in leak-free condition. Collected vapor shall be directed to a gas pipeline distribution system or to an approved control devices having a destruction efficiency of at least 99% by weight as determined by the test method specified in Section 6.4.6 of District Rule 4623. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
5. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
6. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
7. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
8. Fugitive VOC emissions from all components associated with the vapor recovery system (shared with S-1737-169, '-170, '-171 and '-193) including vapor collection piping, vapor compressor, heater treaters, flare gas line, separator vessels and scrubbers shall not exceed 0.98 lb/day as calculated using CAPCOA California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities, Table IV-2c, Oil and Gas Production Screening Value Ranges Emission Factors (Feb 1999). [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. Permittee shall maintain accurate fugitive component count and resultant emissions calculated using CAPCOA California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities, Table IV-2c, Oil and Gas Production Screening Value Ranges Emission Factors (Feb 1999). These records shall be retained on-site for a period of at least five years, and shall be made available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Heater treaters shall only be fired on PUC-quality natural gas or LPG. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The permittee shall tune the unit (two heaters) at least twice per calendar year, (from four to eight months apart) using a qualified technician in accordance with the procedure described in Rule 4304. If the unit does not operate throughout a continuous six-month period within a calendar year, only one tune-up is required for a calendar year. No tune-up is required if the unit is not operated during that calendar year; and this unit may be test fired to verify availability of the unit for its intended use, but once the test firing is complete the unit shall be shutdown. [District Rule 4307] Federally Enforceable Through Title V Permit
12. The permittee shall keep accurate records of each organic liquid stored in the tank, including its type and API gravity. [District Rules 1070, 2201 and 4409] Federally Enforceable Through Title V Permit
13. On and after July 1, 2015, the heater treaters in this unit shall comply with the applicable emission requirements of Section 5.1, Table 1 in District Rule 4307. [District Rule 4307] Federally Enforceable Through Title V Permit
14. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

DRAFT

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-167-6

EXPIRATION DATE: 02/28/2018

SECTION: NE03 **TOWNSHIP:** 28S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

14.6 MMBTU/HR PRODUCED GAS FLARE WITH COANDA EFFECT TIP AND PILOT AUTHORIZED TO BE USED AT VARIOUS UNSPECIFIED LOCATIONS WITHIN THE LIGHT OIL CENTRAL STATIONARY SOURCE

PERMIT UNIT REQUIREMENTS

1. Unit shall not be located within 1000 feet of any K-12 school. [CH&SC 42301.6]
2. Flare shall not be used within 500 feet of any business or residence. [District Rule 4102]
3. This flare is approved for use in well testing, tank and well vent control, and equipment shutdown, emergencies and other situation requiring a safety flare. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Permittee shall notify the District Compliance Division of each location at which the unit is located in excess of 24 hours. Such notification shall be made no later than 48 hours after starting operation at the location. [District Rule 1070]
5. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
6. Flare shall operate in a smokeless manner (no greater than 5% opacity) except for three minutes in any one hour. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Flare shall be equipped with volumetric flow rate indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Gas flow rate to flare (not including pilot gas) shall not exceed 350,000 cubic feet per day. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Emission rates from this unit shall not exceed any of the following limits: NO_x (as NO₂) - 0.068 lb/MMBtu; VOC (as methane) - 0.063 lb/MMBtu; CO - 0.37 lb/MMBtu or PM₁₀ - 0.008 lb/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Gas sulfur content shall not exceed 1.0 gr/100 scf. [District Rules 2201 and 4801] Federally Enforceable Through Title V Permit
11. Gas shall be tested quarterly for sulfur content. Upon transfer of location or change in the method of operation of the flare (excluding emergencies), gas shall be tested weekly for sulfur content. If compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks then the fuel testing frequency shall be quarterly. If a quarterly fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The sulfur content of the gas being flared shall be determined using ASTM D1072, D3031, D4084, D3246, or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

13. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2201] Federally Enforceable Through Title V Permit
14. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by: ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2201] Federally Enforceable Through Title V Permit
15. A trained observer, as defined in EPA Method 22, shall check visible emissions at least once every two weeks for a period of 15 minutes. If visible emissions are detected at any time during this period, the observation period shall be extended to two hours. A record containing the results of these observations shall be maintained, which also includes company name, process unit, observer's name and affiliation, date, estimated wind speed and direction, sky condition, and the observer's location relative to the source and sun. [District Rules 2080 and 4101] Federally Enforceable Through Title V Permit
16. The flame shall be present at all times when combustible gases are vented through the flare. [District Rule 4311, 5.2] Federally Enforceable Through Title V Permit
17. The outlet shall be equipped with an automatic ignition system, or, shall operate with a pilot flame present at all times when combustible gases are vented through the flare, except during purge periods for automatic-ignition equipped flares. [District Rule 4311, 5.3] Federally Enforceable Through Title V Permit
18. Permittee shall obtain an ATC to modify any permit unit which authorizes this flare as a control device prior to this flare operating as a control device for that permit unit. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Except for flares equipped with a flow-sensing ignition system, a heat sensing device such as a thermocouple, ultraviolet beam sensor, infrared sensor, or an equivalent device, capable of continuously detecting at least one pilot flame or the flare flame is present, shall be installed and operated. [District Rule 4311, 5.4] Federally Enforceable Through Title V Permit
20. Flares that use flow-sensing automatic ignition systems and which do not use a continuous flame pilot shall use purge gas for purging. [District Rule 4311, 5.5] Federally Enforceable Through Title V Permit
21. The flare shall be inspected every two weeks while in operation for visible emissions. If visible emissions are observed, corrective action shall be taken. If visible emissions continue, an EPA method 9 test shall be conducted within 72 hours. [District Rule 2201] Federally Enforceable Through Title V Permit
22. The flare shall be operated according to the manufacturer's specifications, a copy of which shall be maintained on site. [District Rule 2080] Federally Enforceable Through Title V Permit
23. Permittee shall maintain accurate daily records of volume, type, higher heating value, and sulfur content and of gas flared [District Rule 2201 & 1070] Federally Enforceable Through Title V Permit
24. Permittee shall maintain accurate records of location and duration of operation at each stationary source. [District Rule 2201 & 4409] Federally Enforceable Through Title V Permit
25. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 2201 & 4409] Federally Enforceable Through Title V Permit
26. Permittee shall maintain records of daily amount of total gas flared. Records shall be kept for a minimum of 5 years and shall be made readily available for District inspection upon request. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

DRAFT

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-162-3

EXPIRATION DATE: 02/28/2018

SECTION: NW03 **TOWNSHIP:** 28S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

42,000 GALLON (1,000 BBL) FIXED ROOF OIL SHIPPING TANK SERVED BY SHARED VAPOR CONTROL SYSTEM LISTED ON S-1737-157

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor loss prevention system capable of collecting all VOC emissions and preventing their emissions to the atmosphere at an efficiency of at least 95% by weight. [District Rule 4623] Federally Enforceable Through Title V Permit
2. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Fugitive VOC emissions shall be less than 0.5 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. All piping, valves, and fittings shall be constructed and maintained in a Leak-Free condition. [District Rules 2201 and 4623, 5.6.3] Federally Enforceable Through Title V Permit
6. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated to methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
7. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2201] Federally Enforceable Through Title V Permit
8. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information.
[District Rule 2201] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
11. Formerly S-1132-87-0
12. Formerly S-4241-30-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-161-3

EXPIRATION DATE: 02/28/2018

SECTION: NW03 **TOWNSHIP:** 28S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

42,000 GALLON (1,000 BBL) FIXED ROOF OIL SHIPPING TANK SERVED BY SHARED VAPOR CONTROL SYSTEM LISTED ON S-1737-157

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor loss prevention system capable of collecting all VOC emissions and preventing their emissions to the atmosphere at an efficiency of at least 95% by weight. [District Rule 4623] Federally Enforceable Through Title V Permit
2. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Fugitive VOC emissions shall be less than 0.5 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. All piping, valves, and fittings shall be constructed and maintained in a Leak-Free condition. [District Rules 2201 and 4623, 5.6.3] Federally Enforceable Through Title V Permit
6. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated to methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
7. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2201] Federally Enforceable Through Title V Permit
8. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information. [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
11. Formerly S-1132-86-0
12. Formerly S-4241-29-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-160-4

EXPIRATION DATE: 02/28/2018

SECTION: NW03 **TOWNSHIP:** 28S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

2.0 MMBTU/HR VAPOR RECOVERY GAS FIRED PRODUCTION HEATER

PERMIT UNIT REQUIREMENTS

1. {1829} The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. While dormant, the fuel line shall be physically disconnected from the unit. [District Rule 2080] Federally Enforceable Through Title V Permit
3. Permittee shall submit written notification to the District upon designating the unit as dormant or active. [District Rule 2080] Federally Enforceable Through Title V Permit
4. While dormant, normal source testing shall not be required. [District Rule 2080] Federally Enforceable Through Title V Permit
5. Upon recommencing operation of this unit, normal source testing shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
6. Any source testing required by this permit shall be performed within 60 days of recommencing operation of this unit, regardless of whether the unit remains active or is again designated as dormant. [District Rule 2080] Federally Enforceable Through Title V Permit
7. Records of all dates and times that this unit is designated as dormant or active, and copies of all corresponding notices to the District, shall be maintained, retained for a period of at least five years, and made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
8. Gas rate to the production heater shall not exceed 40,000 scf per day. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Sulfur content of gas burned in flare or heater shall not exceed 0.3 gr/100 scf as sulfur. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Burner shall be equipped with gas flow meter. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Emission rates for the heater shall not exceed any of the following: PM-10: 0.012 lb/MMBtu, NOx (as NO2): 0.10 lb/MMBtu, VOC: 0.0058 lb/MMBtu, or CO: 0.021 lb/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The permittee shall tune the unit at least twice per calendar year, (from four to eight months apart) using a qualified technician in accordance with the procedure described in Rule 4304. If the unit does not operate throughout a continuous six-month period within a calendar year, only one tune-up is required for a calendar year. No tune-up is required if the unit is not operated during that calendar year; and this unit may be test fired to verify availability of the unit for its intended use, but once the test firing is complete the unit shall be shutdown. [District Rule 4307, 5.2.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

13. The operator shall keep accurate daily records of the amount of gas burned in the production heater. [District Rule 1070 & 4307] Federally Enforceable Through Title V Permit
14. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
15. On and after July 1, 2015, this unit shall comply with the applicable emission requirements of Section 5.1, Table 1 in District Rule 4307. [District Rule 4307, 5.2.3] Federally Enforceable Through Title V Permit
16. Formerly S-1132-85-1
17. Formerly S-4241-28-0

These terms and conditions are part of the Facility-wide Permit to Operate.

ATTACHMENT B

Previous Title V Operating Permit

San Joaquin Valley Air Pollution Control District

FACILITY: S-1737-0-4

EXPIRATION DATE: 02/28/2018

FACILITY-WIDE REQUIREMENTS

1. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
2. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)] Federally Enforceable Through Title V Permit
3. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0] Federally Enforceable Through Title V Permit
4. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (12/20/07). [District Rule 2010, 3.0 and 4.0; and 2020] Federally Enforceable Through Title V Permit
5. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.8.1 and 9.13.1] Federally Enforceable Through Title V Permit
6. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031] Federally Enforceable Through Title V Permit
7. Every application for a permit required under Rule 2010 (12/17/92) shall be filed in a manner and form prescribed by the District. [District Rule 2040] Federally Enforceable Through Title V Permit
8. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.4.1] Federally Enforceable Through Title V Permit
9. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate. Any amendments to these Facility-wide Requirements that affect specific Permit Units may constitute modification of those Permit Units.

Facility Name: CALIFORNIA RESOURCES PRODUCTION CORP

Location: LIGHT OIL CENTRAL, KERN COUNTY, CA

S-1737-0-4 : Oct 5 2018 11:53AM - OROZCOA

10. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.5.1] Federally Enforceable Through Title V Permit
11. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520 (6/21/01). [District Rules 2520, 9.5.2 and 1100, 7.0] Federally Enforceable Through Title V Permit
12. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit. [District Rule 2520, 9.7] Federally Enforceable Through Title V Permit
13. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.8.2] Federally Enforceable Through Title V Permit
14. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.8.3] Federally Enforceable Through Title V Permit
15. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.8.4] Federally Enforceable Through Title V Permit
16. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.8.5] Federally Enforceable Through Title V Permit
17. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.9] Federally Enforceable Through Title V Permit
18. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.13.2.1] Federally Enforceable Through Title V Permit
19. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.13.2.2] Federally Enforceable Through Title V Permit
20. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.13.2.3] Federally Enforceable Through Title V Permit
21. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.13.2.4] Federally Enforceable Through Title V Permit
22. No air contaminants shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (02/17/05). If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and County Rules 401 (in all eight counties in the San Joaquin Valley)] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

23. No person shall manufacture, blend, repackage, supply, sell, solicit or apply any architectural coating with a VOC content in excess of the corresponding limit specified in Table of Standards 1 effective until 12/30/10 or Table of Standards 2 effective on and after 1/1/11 of District Rule 4601 (12/17/09) for use or sale within the District. [District Rule 4601, 5.1] Federally Enforceable Through Title V Permit
24. All VOC-containing materials subject to Rule 4601 (12/17/09) shall be stored in closed containers when not in use. [District Rule 4601, 5.4] Federally Enforceable Through Title V Permit
25. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.3 (12/17/09). [District Rule 4601, 6.1 and 6.3] Federally Enforceable Through Title V Permit
26. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.13.1 and 10.0] Federally Enforceable Through Title V Permit
27. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F] Federally Enforceable Through Title V Permit
28. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart B. [40 CFR Part 82, Subpart B] Federally Enforceable Through Title V Permit
29. Disturbances of soil related to any construction, demolition, excavation, extraction, or other earthmoving activities shall comply with the requirements for fugitive dust control in District Rule 8021 unless specifically exempted under Section 4.0 of Rule 8021 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8021] Federally Enforceable Through Title V Permit
30. Outdoor handling, storage and transport of any bulk material which emits dust shall comply with the requirements of District Rule 8031, unless specifically exempted under Section 4.0 of Rule 8031 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8031] Federally Enforceable Through Title V Permit
31. An owner/operator shall prevent or cleanup any carryout or trackout in accordance with the requirements of District Rule 8041 Section 5.0, unless specifically exempted under Section 4.0 of Rule 8041 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8041] Federally Enforceable Through Title V Permit
32. Whenever open areas are disturbed, or vehicles are used in open areas, the facility shall comply with the requirements of Section 5.0 of District Rule 8051, unless specifically exempted under Section 4.0 of Rule 8051 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8051] Federally Enforceable Through Title V Permit
33. Any paved road or unpaved road shall comply with the requirements of District Rule 8061 unless specifically exempted under Section 4.0 of Rule 8061 (8/19/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8061] Federally Enforceable Through Title V Permit
34. Any unpaved vehicle/equipment area that anticipates more than 50 Average annual daily Trips (AADT) shall comply with the requirements of Section 5.1.1 of District Rule 8071. Any unpaved vehicle/equipment area that anticipates more than 150 vehicle trips per day (VDT) shall comply with the requirements of Section 5.1.2 of District Rule 8071. On each day that 25 or more VDT with 3 or more axles will occur on an unpaved vehicle/equipment traffic area, the owner/operator shall comply with the requirements of Section 5.1.3 of District Rule 8071. On each day when a special event will result in 1,000 or more vehicles that will travel/park on an unpaved area, the owner/operator shall comply with the requirements of Section 5.1.4 of District Rule 8071. All sources shall comply with the requirements of Section 5.0 of District Rule 8071 unless specifically exempted under Section 4.0 of Rule 8071 (9/16/2004) or Rule 8011 (8/19/2004). [District Rules 8011 and 8071] Federally Enforceable Through Title V Permit
35. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

36. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.16] Federally Enforceable Through Title V Permit
37. The permittee shall submit an application for Title V permit renewal to the District at least six months, but not greater than 18 months, prior to the permit expiration date. [District Rule 2520, 5.2] Federally Enforceable Through Title V Permit
38. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permits shall apply. [District Rule 2520, 9.1.1] Federally Enforceable Through Title V Permit
39. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), Rule 111 (Kern, Tulare, Kings), and Rule 202 (Fresno, Kern, Tulare, Kings, Madera, Stanislaus, Merced, San Joaquin). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
40. Compliance with permit conditions in the Title V permit shall be deemed in compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (2/17/05); 4601 (12/17/09); 8021 (8/19/2004); 8031 (8/19/2004); 8041 (8/19/2004); 8051 (8/19/2004); 8061 (8/19/2004); and 8071 (9/16/2004). A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
41. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report begin January 1 of every year, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520] Federally Enforceable Through Title V Permit
42. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
43. Operator shall maintain accurate monthly records of Gas-to-oil ratio (GOR) and API gravity of liquids produced showing that facility exclusively processes, stores, or transfers black oil (as defined in 40 CFR 63.761). [40 CFR 63.760(e)] Federally Enforceable Through Title V Permit
44. The permittee shall not use any components that leak in excess of the applicable leak standards as specified in this permit. Components that have been found leaking in excess of the applicable leak standards of this rule may be used provided such leaking components have been identified with a tag for repair, are repaired, or are awaiting re-inspection after being repaired, within the applicable time period specified in this permit. [District Rule 4409, 5.1.1] Federally Enforceable Through Title V Permit
45. For valves, threaded connections, flanges, pipes, pumps, compressors, and other components subject to the requirements of Rule 4409, but not specified in this permit; a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 1,000 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 2,000 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4409, 5.1.1] Federally Enforceable Through Title V Permit
46. For pressure relief devices (PRDs); a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 200 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 400 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4409, 5.1.1] Federally Enforceable Through Title V Permit
47. For polished rod stuffing boxes (PRSBs); a major gas leak is a detection of > 10,000 ppmv as methane; a minor gas leak is a detection of 1,000 to 10,000 ppmv as methane when the component is in liquid service; a minor gas leak is a detection of 1,000 to 10,000 ppmv as methane when the component is in gas/vapor service. [District Rule 4409, 5.1.1] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

48. Each hatch shall be closed at all times except during sampling or adding of process material through the hatch, or during attended repair, replacement, or maintenance operations, provided such activities are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4409, 5.1.2] Federally Enforceable Through Title V Permit
49. Minor gas leaks from PRSBs detected during any District inspection shall not be counted toward determination of compliance with this rule provided the permittee repairs, replaces, or removes leaking PRSBs from VOC service as soon as practicable but not later than seven calendar days. [District Rule 4409, 5.1.3.1.2] Federally Enforceable Through Title V Permit
50. Leaks detected during quarterly operator inspections shall not be counted towards determination of compliance with the provisions of Rule 4409 provided the leaking components are repaired as soon as practicable but not later than the time frame specified in this permit. Leaks detected during quarterly operator inspections that are not repaired, replaced, or removed from operation as soon as practicable but not later than the time frame specified in this rule shall be counted toward determination of compliance with the provisions of Rule 4409. [District Rule 4409, 5.1.3.2.1 and 5.1.3.2.2] Federally Enforceable Through Title V Permit
51. Leaking components at this facility detected during annual operator inspections, as required by Rule 4409 for a specific component type, that exceed the leak standards specified in this permit, shall constitute a violation of this rule. This violation is regardless of whether or not the leaking components are repaired, replaced, or removed from operation within the allowable repair time frame specified in this permit. [District Rule 4409, 5.1.3.2.3] Federally Enforceable Through Title V Permit
52. An open-ended line, or a valve located at the end of the line, that is not sealed with either a blind flange, a plug, a cap, or a second closed valve that is not closed at all times, except during attended operations requiring process fluid flow through the open-ended line is a leak. Attended operations include draining or degassing operations, connection of temporary process equipment, sampling of process streams, emergency venting, and other normal operational needs, provided such operations are done as expeditiously as possible and with minimal spillage of material and VOC emissions to the atmosphere. [District Rule 4409, 5.1.4.1] Federally Enforceable Through Title V Permit
53. A leak from a component is when there is a major liquid leak from the component. A major liquid leak from a component is when a visible mist or a continuous flow of liquid, that is not seal lubricant, leaks from the component. [District Rule 4409, 5.1.4.2] Federally Enforceable Through Title V Permit
54. A leak from a component is when gas emissions greater than 50,000 ppmv, as methane, leaks from the component. [District Rule 4409, 5.1.4.3] Federally Enforceable Through Title V Permit
55. A minor liquid leak from a component is when more than three drops of liquid per minute, that is not seal lubricant and is not a major liquid leak, leaks from the component. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit
56. When 200 or fewer valves are inspected, a leak from a valve is when more than one valve has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 valves are inspected, a leak from a valve is when more than 0.5 % (rounded up to the nearest whole number) of the valves have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit
57. When 200 or fewer threaded connections are inspected, a leak from a threaded connection is when more than one threaded connection has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 threaded connections are inspected, a leak from a threaded connection is when more than 0.5 % (rounded up to the nearest whole number) of the threaded connections have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit
58. When 200 or fewer flanges are inspected, a leak from a flange is when more than one flange has a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 flanges are inspected, a leak from a flange is when more than 0.5 % (rounded up to the nearest whole number) of the flanges have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

59. When 200 or fewer pumps are inspected, a leak from a pump is when more than two pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. When greater than 200 pumps are inspected, a leak from a pump is when more than 1.0 % (rounded up to the nearest whole number) of the pumps have a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit
60. When compressors, PRDs, or other components not specified in this permit are inspected, a leak from these components is when more than one component has a minor liquid leak, a minor gas leak, or a gas leak greater than 10,000 ppmv and less than or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit
61. When 200 or fewer PRSBs are inspected, a leak is when more than four have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 PRSBs are inspected, a leak is when more than 2.0 % (rounded up to the nearest whole number) of the PRSBs have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit
62. When 200 or fewer wells at light crude oil or gas production facilities are inspected, a leak from a pipe is when more than two or more pipes have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. When greater than 200 wells at light crude oil or gas production facilities are inspected, a leak from a pipe is when more than 1.0 % (rounded up to the nearest whole number) of the pipes have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit
63. When pipes at natural gas processing facilities are inspected, a leak from a pipe is when more than two have a minor liquid leak, a minor gas leak, or a gas leak > 10,000 ppmv and < or equal to 50,000 ppmv. [District Rule 4409, 5.1.4.4] Federally Enforceable Through Title V Permit
64. For manned facilities all accessible operating pumps, compressors, and PRDs, in service, shall be audio-visually inspected for leaks at least once every 24 hours except when operators do not report to the facility during a 24 hour period. [District Rule 4409, 5.2.1] Federally Enforceable Through Title V Permit
65. For unmanned facilities all accessible operating pumps, compressors, and PRDs, in service, shall be audio-visually inspected for leaks at least once per calendar week. [District Rule 4409, 5.2.2] Federally Enforceable Through Title V Permit
66. All accessible operating pumps, compressors, and PRDs, in service, that are found to be leaking by audio-visual inspection shall be attempted to be repaired immediately. The leaking component shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4409, 5.2.3] Federally Enforceable Through Title V Permit
67. Except for inaccessible components, unsafe-to-monitor components, or pipes, all components, in service, shall be tested for leaks at least once every calendar quarter. [District Rule 4409, 5.2.4] Federally Enforceable Through Title V Permit
68. All new, replaced, or repaired fittings, flanges, and threaded connections shall be tested for leaks immediately after being placed into service. [District Rule 4409, 5.2.5] Federally Enforceable Through Title V Permit
69. All inaccessible components shall be tested for leaks at least once every 12 months. [District Rule 4409, 5.2.6] Federally Enforceable Through Title V Permit
70. All unsafe-to-monitor components shall be tested for leaks during each turnaround. [District Rule 4409, 5.2.7] Federally Enforceable Through Title V Permit
71. All pipes shall be visually inspected for leaks at least once every 12 months. [District Rule 4409, 5.2.8] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

72. All pipes, in service, that are found to be leaking by visual inspection shall be attempted to be repaired immediately. The leaking pipe shall then be tested within 24 hours and, if found leaking again, shall be repaired as soon as practicable but not later than the timeframe specified in this permit. [District Rule 4409, 5.2.8.1] Federally Enforceable Through Title V Permit
73. The annual pipe inspection required by either the Department of Oil, Gas, and Geothermal Resources (DOGGR) pursuant to California Code of Regulation Title 14, Division 2, Subchapter 2, Section 1774 (Oilfield Facilities and Equipment Maintenance), or by the Spill Prevention Control and Countermeasure Plan (SPCC) pursuant to 40 Code of Federal Regulation Part 112 (Oil Prevention and Response: Non- Transportation-Related Onshore and Offshore Facilities) can be used as the annual pipe inspection required by District Rule 4409. [District Rule 4409, 5.2.8.2] Federally Enforceable Through Title V Permit
74. Except for pumps, compressors, and PRDs, the permittee may apply for written approval from the District to change the inspection frequency of accessible components from quarterly to annually for a specific component type provided the following two qualifying requirements are met. During the previous five consecutive quarterly inspections, for the specific component type, there shall be no more leaks than as allowed by this permit. The permittee also shall not have received a Notice of Violation (NOV) from the District during the previous 12 months for violating any provisions of District Rule 4409 for the specific component type. If these two qualifying requirements have not been met, then the inspection frequency shall revert back to quarterly. The written request shall include pertinent documentation to demonstrate that the operator has successfully met the two qualifying requirements. [District Rule 4409, 5.2.9 and 5.2.10] Federally Enforceable Through Title V Permit
75. The permittee shall notify the District in writing within five calendar days after changing the inspection frequency for a specific component type. The written notification shall include the reason(s) and date of change to a quarterly inspection frequency. [District Rule 4409, 5.2.11] Federally Enforceable Through Title V Permit
76. A PRD that releases to the atmosphere shall be inspected by the permittee for leaks as soon as practicable but not later than 24 hours after the time of the release. The permittee shall reinspect the PRD for leaks not earlier than 24 hours after the initial inspection but not later than 15 calendar days after the date of the initial release. If the PRD is found by the permittee to be leaking during either inspection, the PRD leak shall be treated as if the leak was found during the required quarterly operator inspections. [District Rule 4409, 5.2.12] Federally Enforceable Through Title V Permit
77. Except for PRDs, a component shall be inspected for leaks not later than 15 calendar days after repairing the leak or replacing the component. [District Rule 4409, 5.2.13] Federally Enforceable Through Title V Permit
78. District inspections shall not be counted as an operator inspection required by District Rule 4409. Any attempt by an operator to count such District inspections as part of the operator's mandatory inspections is considered a willful circumvention of the rule and is a violation of this rule. [District Rule 4409, 5.2.14] Federally Enforceable Through Title V Permit
79. The operator, upon detection of a leaking component, shall affix to that component a weatherproof, readily visible tag, bearing the date and time when the leak was detected and the date and time of the leak measurement. For gaseous leaks, the tag shall indicate the leak concentration in ppmv. For liquid leaks, the tag shall indicate whether it is a major liquid leak or a minor liquid leak. The tag shall indicate, when applicable, whether the component is an essential component, an unsafe-to-monitor component, or a critical component. The tag shall remain in place until the leaking component is repaired or replaced and reinspected and found to be in compliance with the requirements of this rule. [District Rule 4409, 5.3.1] Federally Enforceable Through Title V Permit
80. The operator shall minimize all component leaks immediately, to the extent possible, but not later than one hour after detection of the leak in order to stop or reduce leakage to the atmosphere. If the leak has been minimized but the leak still exceeds the applicable leak standards specified in this permit, the operator shall do one of the following within the timeframes specified within this permit: 1) repair or replace the leaking component; 2) vent the leaking component to a closed vent system; 3) or remove the leaking component from operation. A closed vent system is a District approved system that is not open to the atmosphere. It is composed of hard-piping, ductwork connections and, if necessary, flow inducing devices that transport gas or vapor from a piece or pieces of equipment to a District approved control device that has a overall VOC collection and destruction or removal efficiency of at least 95%, or that transports gases or vapors back to a process system. [District Rule 4409, 5.3.4 and 5.3.5] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

81. The operator shall repair minor gas leaks within seven days. The operator shall repair major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, within three days. The operator shall repair major gas leaks, which are > 50,000 ppmv, within two days. The operator shall repair minor liquid leaks within three days. The operator shall repair major liquid leaks within two days. The leak rate measured after leak minimization has been performed shall be the leak rate used to determine the applicable repair period. The start of the repair period shall be the time of the initial leak detection. [District Rule 4409, 5.3.4 and 5.3.5] Federally Enforceable Through Title V Permit
82. For each calendar quarter, the operator may extend the repair period for a total number of leaking components, not to exceed 0.05 % of the number of components inspected, by type, rounded upward to the nearest whole number. The repair period for minor gas leaks can be extended by seven additional days. The repair period for major gas leaks, which are > 10,000 ppmv but < or equal to 50,000 ppmv, can be extended by two additional days. [District Rule 4409, 5.3.5] Federally Enforceable Through Title V Permit
83. If a leaking component is an essential component or a critical component and which cannot be shut down immediately for repairs, the operator shall do the following: 1) minimize the leak within one hour after detection of the leak; 2) and if the leak has been minimized, but the leak still exceeds the applicable leak standards of Rule 4409 as specified in this permit, the essential component or critical component shall be repaired or replaced to eliminate the leak during the next process unit turnaround. The repair shall occur no later than one year from the date of the original leak detection. [District Rule 4409, 5.3.6] Federally Enforceable Through Title V Permit
84. For any component that has incurred five repair actions for major gas leaks or major liquid leaks, or a combination of major gas leaks and major liquid leaks within a continuous 12-month period, the operator shall do one of the following four options. Options 1a through 1f require written notification to the District, option 2 requires written notification to the District and written District approval, options 3 and 4 do not require written notification to the District: 1a) For compressors replace the existing seal with either a dual mechanical seal, an oil film seal, a gas seal, or a face-type seal; 1b) for pumps replace the pump with a seal-less pump or replace the seal with a dual mechanical seal; 1c) for PRDs replace the PRD and install a rupture disc in the line which precedes the PRD such that the PRD is in series with and follows the rupture disc; 1d) for valves replace the valve with a sealed bellows valve, or for seal rings install graphite or Teflon chevron seal rings in a live-loaded packing gland; 1e) for threaded connections weld the connections or replace threaded connections with flanges; 1f) for sampling connections replace the sampling connection with a closed-loop sampling system; 2) Replace the component with Achieved-in-Practice Best Available Control Technology (BACT) equipment; 3) Vent the component to a District approved closed-vent system; 4) Remove the component from operation. For any component that is accessible, is not unsafe-to-monitor, is not an essential component, or is not a critical component, the operator shall comply with these requirements as soon as practicable but not later than twelve months after the date of detection of the fifth major leak within a continuous 12-month period. For any component that is inaccessible, is unsafe-to-monitor, is essential, or is a critical component, the operator shall comply with these requirements as soon as practicable but not later than the next turnaround or not later than two years after the date of detection of the fifth major leak within a continuous 12-month period, whichever comes first. [District Rule 4409, 5.3.7] Federally Enforceable Through Title V Permit
85. All major components and critical components shall be physically identified clearly and visibly for inspection, repair, and recordkeeping purposes. The physical identification shall consist of labels, tags, manufacturer's nameplate identifier, serial number, or model number, or other system approved by the District that enables an operator or the District to locate each individual component. The operator shall replace physical identifications that become missing or unreadable as soon as practicable but not later than 24 hours after discovery. [District Rule 4409, 5.4.1] Federally Enforceable Through Title V Permit
86. The operator shall keep a copy of the District approved Operator Management Plan (OMP) at the facility and make it available to the District, ARB, and EPA upon request. [District Rule 4409, 6.1.2] Federally Enforceable Through Title V Permit
87. By January 30th of each year the operator shall submit to the District for approval, in writing, an annual report indicating any changes to the existing OMP on file at the District. [District Rule 4409, 6.1.4] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

88. The operator shall maintain an inspection log that has been signed and dated by the facility operator responsible for the inspection, certifying the accuracy of the information recorded in the log. The inspection log shall contain, at a minimum, all of the following information: 1) The total number of components inspected, and the total number and percentage of leaking components found by component types; 2) The location, type, name or description of each leaking component and the description of any unit where the leaking component is found; 3) Date of the leak detection and method of the leak detection; 4) For gaseous leaks, record the leak concentration in ppmv, and for liquid leaks record whether the leak is a major liquid leak or a minor liquid leak; 5) The date of repair, replacement, or removal from operation of the leaking component(s); 6) The identification and location of essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes first; 7) The method(s) used to minimize the leak from essential components and critical components found leaking that cannot be repaired until the next process unit turnaround or not later than one year after leak detection, whichever comes earlier; 8) The date of re-inspection and the leak concentration in ppmv after the component is repaired or is replaced; 9) The inspector's name, business mailing address, and business telephone number. [District Rule 4409, 6.2.1] Federally Enforceable Through Title V Permit
89. Records of leaks detected during quarterly or annual operator inspections, and each subsequent repair and re-inspection, shall be submitted to the District, ARB, and EPA upon request. [District Rule 4409, 6.2.2] Federally Enforceable Through Title V Permit
90. Records shall be maintained of each calibration of the portable hydrocarbon detection instrument utilized for inspecting components. The records shall include a copy of the current calibration gas certification from the vendor of the calibration gas cylinder, the date of calibration, the concentration of calibration gas, the instrument reading of calibration gas before adjustment, the instrument reading of calibration gas after adjustment, the calibration gas expiration date, and the calibration gas cylinder pressure at the time of calibration. [District Rule 4409, 6.2.3] Federally Enforceable Through Title V Permit
91. All records required by this permit shall be retained on-site for a minimum of five years and made available for District, ARB, and EPA inspection upon request. [District Rule 4409, 6.2.4] Federally Enforceable Through Title V Permit
92. All measurements of gaseous leak concentrations shall be conducted according to EPA Method 21 using an appropriate portable hydrocarbon detection instrument calibrated with methane. The instrument shall be calibrated in accordance with the procedures specified in EPA Method 21 or the manufacturer's instructions not more than 30 days prior to its use. [District Rule 4409, 6.3.1] Federally Enforceable Through Title V Permit
93. The VOC content by weight percent shall be determined using ASTM D-1945 for gases and South Coast Air Quality Management District (SCAQMD) Method 304-91 for liquids. [District Rule 4409, 6.3.2] Federally Enforceable Through Title V Permit
94. The percent by volume liquid evaporated at 302 °F (150 °C) shall be determined using ASTM D-86. [District Rule 4409, 6.3.3] Federally Enforceable Through Title V Permit
95. The TVP of any organic liquid shall be determined by measuring the Reid Vapor Pressure (RVP) using ASTM D-323, and converting the RVP to TVP at the maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance with the procedures specified in Appendix A of District Rule 4409. [District Rule 4409, 6.3.4] Federally Enforceable Through Title V Permit
96. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM D-287 or ASTM 1298. Sampling for API gravity shall be performed in accordance with ASTM D-4057. [District Rule 4409, 6.3.5] Federally Enforceable Through Title V Permit
97. The control efficiency of any VOC control device, measured and calculated as carbon, shall be determined by EPA Method 25, except when the outlet concentration must be below 50 ppm in order to meet the standard, in which case EPA Method 25a may be used. EPA Method 18 may be used in lieu of EPA Method 25 or EPA Method 25a provided the identity and approximate concentrations of the analytes/compounds in the sample gas stream are known before analysis with the gas chromatograph and the gas chromatograph is calibrated for each of those known analyte/compound to ensure that the VOC concentrations are neither under- or over-reported. [District Rule 4409, 6.3.6] Federally Enforceable Through Title V Permit

FACILITY-WIDE REQUIREMENTS CONTINUE ON NEXT PAGE
These terms and conditions are part of the Facility-wide Permit to Operate.

98. Halogenated exempt compounds shall be analyzed by EPA Method 18 or ARB Method 422. [District Rule 4409, 6.3.7] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-162-2

EXPIRATION DATE: 02/28/2018

SECTION: NW03 **TOWNSHIP:** 28S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

42,000 GALLON (1,000 BBL) FIXED ROOF OIL SHIPPING TANK SERVED BY SHARED VAPOR CONTROL SYSTEM
LISTED ON S-1737-157

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor loss prevention system capable of collecting all VOC emissions and preventing their emissions to the atmosphere at an efficiency of at least 95% by weight. [District Rule 4623] Federally Enforceable Through Title V Permit
2. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Fugitive VOC emissions shall be less than 0.5 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. All piping, valves, and fittings shall be constructed and maintained in a Leak-Free condition. [District Rules 2201 and 4623, 5.6.3] Federally Enforceable Through Title V Permit
6. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated to methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
7. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2201] Federally Enforceable Through Title V Permit
8. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information. [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
11. Formerly S-1132-87-0
12. Formerly S-4241-30-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-161-2

EXPIRATION DATE: 02/28/2018

SECTION: NW03 **TOWNSHIP:** 28S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

42,000 GALLON (1,000 BBL) FIXED ROOF OIL SHIPPING TANK SERVED BY SHARED VAPOR CONTROL SYSTEM LISTED ON S-1737-157

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor loss prevention system capable of collecting all VOC emissions and preventing their emissions to the atmosphere at an efficiency of at least 95% by weight. [District Rule 4623] Federally Enforceable Through Title V Permit
2. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Fugitive VOC emissions shall be less than 0.5 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. All piping, valves, and fittings shall be constructed and maintained in a Leak-Free condition. [District Rules 2201 and 4623, 5.6.3] Federally Enforceable Through Title V Permit
6. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated to methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
7. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2201] Federally Enforceable Through Title V Permit
8. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: CALIFORNIA RESOURCES PRODUCTION CORP

Location: LIGHT OIL CENTRAL, KERN COUNTY, CA

S-1737-161-2 Oct 5 2018 11:53AM -- OROZCOA

9. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information. [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
11. Formerly S-1132-86-0
12. Formerly S-4241-29-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-160-3

EXPIRATION DATE: 02/28/2018

SECTION: NW03 **TOWNSHIP:** 28S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

2.0 MMBTU/HR VAPOR RECOVERY GAS FIRED PRODUCTION HEATER

PERMIT UNIT REQUIREMENTS

1. The facility shall submit an application to modify the Title V permit in accordance with the timeframes and procedures of District Rule 2520. [District Rule 2520] Federally Enforceable Through Title V Permit
2. While dormant, the fuel line shall be physically disconnected from the unit. [District Rule 2080] Federally Enforceable Through Title V Permit
3. Permittee shall submit written notification to the District upon designating the unit as dormant or active. [District Rule 2080] Federally Enforceable Through Title V Permit
4. While dormant, normal source testing shall not be required. [District Rule 2080] Federally Enforceable Through Title V Permit
5. Upon recommencing operation of this unit, normal source testing shall resume. [District Rule 2080] Federally Enforceable Through Title V Permit
6. Any source testing required by this permit shall be performed within 60 days of recommencing operation of this unit, regardless of whether the unit remains active or is again designated as dormant. [District Rule 2080] Federally Enforceable Through Title V Permit
7. Records of all dates and times that this unit is designated as dormant or active, and copies of all corresponding notices to the District, shall be maintained, retained for a period of at least five years, and made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
8. Gas rate to the production heater shall not exceed 40,000 scf per day. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Sulfur content of gas burned in flare or heater shall not exceed 0.3 gr/100 scf as sulfur. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Burner shall be equipped with gas flow meter. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Emission rates for the heater shall not exceed any of the following: PM-10: 0.012 lb/MMBtu, NO_x (as NO₂): 0.10 lb/MMBtu, VOC: 0.0058 lb/MMBtu, or CO: 0.021 lb/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The permittee shall tune the unit at least twice per calendar year, (from four to eight months apart) using a qualified technician in accordance with the procedure described in Rule 4304. If the unit does not operate throughout a continuous six-month period within a calendar year, only one tune-up is required for a calendar year. No tune-up is required if the unit is not operated during that calendar year; and this unit may be test fired to verify availability of the unit for its intended use, but once the test firing is complete the unit shall be shutdown. [District Rule 4307, 5.2.1.1] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

13. The operator shall keep accurate daily records of the amount of gas burned in the production heater. [District Rule 1070 & 4307] Federally Enforceable Through Title V Permit
14. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
15. On and after July 1, 2015, this unit shall comply with the applicable emission requirements of Section 5.1, Table 1 in District Rule 4307. [District Rule 4307, 5.2.3] Federally Enforceable Through Title V Permit
16. Formerly S-1132-85-1
17. Formerly S-4241-28-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-159-2

EXPIRATION DATE: 02/28/2018

SECTION: NW03 **TOWNSHIP:** 28S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

42,000 GALLON (1,000 BBL) FIXED ROOF WASH TANK (T-03) SERVED BY SHARED VAPOR CONTROL SYSTEM LISTED ON S-1737-157

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor loss prevention system capable of collecting all VOC emissions and preventing their emissions to the atmosphere at an efficiency of at least 95% by weight. [District Rule 4623] Federally Enforceable Through Title V Permit
2. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Fugitive VOC emissions shall be less than 0.5 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. All piping, valves, and fittings shall be constructed and maintained in a Leak-Free condition. [District Rules 2201 and 4623, 5.6.3] Federally Enforceable Through Title V Permit
6. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated to methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
7. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2201] Federally Enforceable Through Title V Permit
8. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information. [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
11. Formerly S-1132-84-2
12. Formerly S-4241-27-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-158-2

EXPIRATION DATE: 02/28/2018

SECTION: NW03 **TOWNSHIP:** 28S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

42,000 GALLON (1,000 BBL) SHIPPING TANK (T-02) SERVED BY SHARED VAPOR CONTROL SYSTEM LISTED ON S-1737-157

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor loss prevention system capable of collecting all VOC emissions and preventing their emissions to the atmosphere at an efficiency of at least 95% by weight. [District Rule 4623] Federally Enforceable Through Title V Permit
2. The operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Fugitive VOC emissions shall be less than 0.5 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. All tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623, 5.6.2] Federally Enforceable Through Title V Permit
5. All piping, valves, and fittings shall be constructed and maintained in a Leak-Free condition. [District Rules 2201 and 4623, 5.6.3] Federally Enforceable Through Title V Permit
6. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated to methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
7. All piping, fittings, and valves shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the provisions of this permit. If any of the tank components are found to leak during an annual inspection, the inspection frequency for that component type shall be changed from annual to quarterly. If no tank components are subsequently found to be leaking during five consecutive inspections, the inspection frequency may be changed from quarterly to annual. Components located in inaccessible (over 15 feet above ground when access is required from the ground or over 6 feet away from a platform when access is required from the platform) locations shall be inspected at least annually and components located in unsafe areas shall be inspected and repaired at the next process unit turnaround (the scheduled shutdown of a unit for maintenance and repair work). [District Rule 2201] Federally Enforceable Through Title V Permit
8. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date of leak detection, and method of detection; 3) Date and emission level of recheck after leak is repaired; 4) Identification and location of essential parts of critical process units found leaking that cannot be repaired until the next process unit turnaround; and 5) Method used to minimize the leak from essential parts of critical process units which cannot be repaired until the next process unit turnaround. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: CALIFORNIA RESOURCES PRODUCTION CORP

Location: LIGHT OIL CENTRAL, KERN COUNTY, CA

S-1737-158-2 Oct 5 2018 11:53AM - OROZCOA

9. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information. [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
11. Formerly S-1132-83-0
12. Formerly S-4241-26-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-157-6

EXPIRATION DATE: 02/28/2018

SECTION: NW03 **TOWNSHIP:** 28S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

63,000 GALLON FIXED ROOF WASH TANK (T-01) WITH VAPOR CONTROL SHARED WITH S-1737-158, '-159, '-160, '-161, AND OPTIONAL PORTABLE TANKS S-1737-181, '-182, '-183, AND/OR '-184 VENTING TO GAS SALES LINE, 41.7 MMBTU/HR COANDA TIP FLARE, FLARES S-1737-167 AND '-180 AND/OR 2.0 MMBTU/HR PRODUCTION HEATER (S-1737-160)

PERMIT UNIT REQUIREMENTS

1. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in leak-free condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device that reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
3. VOC fugitive emissions from the components in gas service on tank and tank vapor collection system) shall not exceed 0.5 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
4. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rules 4623] Federally Enforceable Through Title V Permit
5. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Permittee shall maintain accurate component count for tank according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors < 10,000 ppmv. Permittee shall update such records when new components are approved and installed. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Except as otherwise provided in this permit, the operator shall ensure that the vapor recovery system is functional and is operating as designed at all times. [District Rule 2201] Federally Enforceable Through Title V Permit
8. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
9. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 2201 and 4623] Federally Enforceable Through Title V Permit
11. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
12. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
13. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
14. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
15. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
16. Any component found to be leaking on two consecutive annual inspections is in violation of this rule, even if covered under the voluntary inspection and maintenance program. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
17. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rules 4623 and 2080] Federally Enforceable Through Title V Permit
18. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rules 4623 and 2080] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

19. This tank shall be degassed before commencing interior cleaning by 1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less 2) by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia. or 3) by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623] Federally Enforceable Through Title V Permit
20. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623] Federally Enforceable Through Title V Permit
21. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rules 4623] Federally Enforceable Through Title V Permit
22. This tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid having a TVP of 0.5 psia or greater. [District Rule 4623] Federally Enforceable Through Title V Permit
23. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit
24. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit
25. The permittee shall keep accurate records of the dates of inspection and monitoring and the components inspected and monitored. [District Rule 2201] Federally Enforceable Through Title V Permit
26. Gas rate to the production heater shall not exceed 40,000 scf per day. [District Rule 2201] Federally Enforceable Through Title V Permit
27. The 41.7 MMBtu/hr flare shall be equipped with flared gas flow meter. [District Rules 2201 and 4311] Federally Enforceable Through Title V Permit
28. Gas rate to the 41.7 MMBtu/hr flare shall not exceed 4.0 MMscf per day nor 438.0 MMscf per year. [District Rule 2201] Federally Enforceable Through Title V Permit
29. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201] Federally Enforceable Through Title V Permit
30. Emission rates for the 41.7 MMBtu/hr flare shall not exceed any of the following: PM10: 20 lb/MMscf, NOx (as NO2): 68 lb/MMscf, VOC: 33 lb/MMscf, or CO: 38 lb/MMscf. [District Rule 2201] Federally Enforceable Through Title V Permit
31. Sulfur content of gas burned in the 41.7 MMBtu/hr flare or the heater shall not exceed 0.3 gr/100 scf as sulfur. [District Rules 2201 and 4801] Federally Enforceable Through Title V Permit
32. The sulfur content of the gas being incinerated in the 41.7 MMBtu/hr flare shall be determined using ASTM Test Methods D3246, D4084, D4810, double GC for H2S and mercaptans, or other method approved by the APCO. [District Rule 2201] Federally Enforceable Through Title V Permit
33. Permittee shall measure sulfur content of gas incinerated at least once per year. [District Rules 2201 and 4801] Federally Enforceable Through Title V Permit
34. The outlet shall be equipped with an automatic ignition system, or, shall operate with a pilot flame present at all times when combustible gases are vented through the 41.7 MMBtu/hr flare, except during purge periods for automatic-ignition equipped flares. [District Rule 4311, 5.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

35. Except for flares equipped with a flow-sensing ignition system, a heat sensing device such as a thermocouple, ultraviolet beam sensor, infrared sensor, or an equivalent device, capable of continuously detecting at least one pilot flame or the flare flame is present, shall be installed and operated. [District Rule 4311, 5.4] Federally Enforceable Through Title V Permit
36. Flares that use flow-sensing automatic ignition systems and which do not use a continuous flame pilot shall use purge gas for purging. [District Rule 4311, 5.5] Federally Enforceable Through Title V Permit
37. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
38. Permittee shall maintain accurate records of the daily amounts and annual vapor H₂S concentration of the gas burned in the 41.7 MMBtu/hr flare and production heater. [District Rules 2201 and 4311] Federally Enforceable Through Title V Permit
39. The permittee shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2201 and 4623] Federally Enforceable Through Title V Permit
40. Formerly S-1132-82-0
41. Formerly S-4241-25-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-155-2

EXPIRATION DATE: 02/28/2018

SECTION: SW34 **TOWNSHIP:** 28S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

8,820 GALLON (210 BBL) FIXED ROOF PRODUCED WATER STORAGE TANK WITH PRESSURE/VACUUM RELIEF VALVE AND VENT LINE TO OIL SHIPPING TANKS (TULARE 34-1, NORTH SHAFTER FIELD)

PERMIT UNIT REQUIREMENTS

1. Only produced water shall be stored in this tank with no visible oil pad. [District Rule 2201] Federally Enforceable Through Title V Permit
2. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 11 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
3. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in leak-free condition except when the operating pressure exceeds the valve's set pressure. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
5. All records required to be maintained by this permit shall be maintained for a period of at least five years and shall be made readily available for District inspection upon request. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Formerly S-1132-61-0
7. Formerly S-4241-23-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-148-2

EXPIRATION DATE: 02/28/2018

SECTION: 03 **TOWNSHIP:** 28S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

8,820 GALLON SHIPPING TANK (TULARE 3-1 SHIPPING TANK #2)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 11 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Volatile organic compound (VOC) emission rate shall not exceed 1.98 lb/ day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in leak-free condition except when the operating pressure exceeds the valve's set pressure. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
5. TVP shall be calculated using CARB approved correlation from most recent Reid Vapor Pressure (RVP). Testing for RVP shall be conducted annually. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Permittee shall maintain accurate daily records of throughput, true vapor pressure, temperature of liquids stored and VOC emissions, and shall make such records available for District inspection for a period of five years. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
7. Formerly S-1132-28-0
8. Formerly S-4241-12-0

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: CALIFORNIA RESOURCES PRODUCTION CORP

Location: LIGHT OIL CENTRAL, KERN COUNTY, CA

S-1737-148-2 : Oct 5 2018 11:53AM - OROZCOA

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-146-2

EXPIRATION DATE: 02/28/2018

SECTION: NW03 **TOWNSHIP:** 28S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

4.2 MMBTU/HR COANDA EFFECT SMOKELESS FLARE INCINERATING PRODUCED GAS FROM PRIMARY PRODUCTION WELL (TULARE 3-1, NORTH SHAFTER FIELD)

PERMIT UNIT REQUIREMENTS

1. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than 3 minutes in any one hour which is dark or darker than Ringelmann 1/4 or equivalent to 5% opacity. [District NSR Rule] Federally Enforceable Through Title V Permit
2. Flare shall be equipped with a gas flow meter measuring total fuel flow to the flare. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Waste gas flow rate to flare shall not exceed 50 MSCFD. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Emission rates shall not exceed the following: PM10: 0.020 lb/MMBTU, SOx (as SO2): 0.001 lb/MMBTU, NOx (as NO2): 0.068 lb/MMBTU, VOC: 0.088 lb/MMBTU and CO: 0.37 lb/MMBTU. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Sulfur content of gases burned in flare shall not exceed 0.3 gr/100 SCF as H2S. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The sulfur content of the gas being flared shall be determined using ASTM D1072, D3031, D4084, D3246, or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit
7. The gas being flared shall be tested for sulfur content and higher heating value semi-annually. If a semi-annual sulfur content test fails to show compliance, then the compliance testing frequency shall be weekly. If compliance with fuel sulfur content limit has been demonstrated for 8 consecutive weeks, the frequency of testing shall resume to semi-annually. [District Rules 2080 and 4801] Federally Enforceable Through Title V Permit
8. The flame shall be present at all times when combustible gases are vented through the flare. [District Rule 4311, 5.2] Federally Enforceable Through Title V Permit
9. The outlet shall be equipped with an automatic ignition system, or, shall operate with a pilot flame present at all times when combustible gases are vented through the flare, except during purge periods for automatic-ignition equipped flares. [District Rule 4311, 5.3] Federally Enforceable Through Title V Permit
10. Except for flares equipped with a flow-sensing ignition system, a heat sensing device such as a thermocouple, ultraviolet beam sensor, infrared sensor, or an equivalent device, capable of continuously detecting at least one pilot flame or the flare flame is present, shall be installed and operated. [District Rule 4311, 5.4] Federally Enforceable Through Title V Permit
11. Flares that use flow-sensing automatic ignition systems and which do not use a continuous flame pilot shall use purge gas for purging. [District Rule 4311, 5.5] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. The permittee shall keep accurate records of date, time, amount and sulfur content of gas flared. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit
13. Formerly S-1132-26-1
14. Formerly S-4241-10-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-145-2

EXPIRATION DATE: 02/28/2018

SECTION: NW03 **TOWNSHIP:** 28S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

8,820 GALLON FIXED ROOF CRUDE OIL STORAGE TANK WITH PV VENT (WW#3)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 11 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Volatile organic compound (VOC) emission rate shall not exceed 1.98 lb/ day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in leak-free condition except when the operating pressure exceeds the valve's set pressure. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
5. TVP shall be calculated using CARB approved correlation from most recent Reid Vapor Pressure (RVP). Testing for RVP shall be conducted annually. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Permittee shall maintain accurate daily records of throughput, true vapor pressure, temperature of liquids stored and VOC emissions, and shall make such records available for District inspection for a period of five years. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
7. Formerly S-1132-25-1
8. Formerly S-4241-9-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-144-2

EXPIRATION DATE: 02/28/2018

SECTION: 34 **TOWNSHIP:** 27S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

8,820 GALLON SHIPPING TANK (TULARE 34-3 SHIPPING TANK #5)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 11 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Volatile organic compound (VOC) emission rate shall not exceed 1.98 lb/ day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in leak-free condition except when the operating pressure exceeds the valve's set pressure. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
5. TVP shall be calculated using CARB approved correlation from most recent Reid Vapor Pressure (RVP). Testing for RVP shall be conducted annually. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Permittee shall maintain accurate daily records of throughput, true vapor pressure, temperature of liquids stored and VOC emissions, and shall make such records available for District inspection for a period of five years. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
7. Formerly S-1132-24-0
8. Formerly S-4241-8-0

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: CALIFORNIA RESOURCES PRODUCTION CORP

Location: LIGHT OIL CENTRAL, KERN COUNTY, CA

S-1737-144-2 : Oct 5 2018 11:53AM -- OROZCOA

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-143-2

EXPIRATION DATE: 02/28/2018

SECTION: 34 **TOWNSHIP:** 27S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

8,820 GALLON SHIPPING TANK (TULARE 34-3 SHIPPING TANK #4)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 11 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Volatile organic compound (VOC) emission rate shall not exceed 1.98 lb/ day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in leak-free condition except when the operating pressure exceeds the valve's set pressure. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
5. TVP shall be calculated using CARB approved correlation from most recent Reid Vapor Pressure (RVP). Testing for RVP shall be conducted annually. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Permittee shall maintain accurate daily records of throughput, true vapor pressure, temperature of liquids stored and VOC emissions, and shall make such records available for District inspection for a period of five years. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
7. Formerly S-1132-23-0
8. Formerly S-4241-7-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-142-2

EXPIRATION DATE: 02/28/2018

SECTION: NW03 **TOWNSHIP:** 28S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

8,820 GALLON FIXED ROOF CRUDE OIL STORAGE TANK WITH PV VENT (TANK ID WW#2)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 11 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Volatile organic compound (VOC) emission rate shall not exceed 1.99 lb/ day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in leak-free condition except when the operating pressure exceeds the valve's set pressure. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
5. TVP shall be calculated using CARB approved correlation from most recent Reid Vapor Pressure (RVP). Testing for RVP shall be conducted annually. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Permittee shall maintain accurate daily records of throughput, true vapor pressure, temperature of liquids stored and VOC emissions, and shall make such records available for District inspection for a period of five years. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
7. Formerly S-1132-22-1
8. Formerly S-4241-6-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-141-2

EXPIRATION DATE: 02/28/2018

SECTION: NW34 **TOWNSHIP:** 27S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

8,820 GALLON FIXED ROOF PETROLEUM SHIPPING TANK WITH PV VENT (ID: TULARE 34-2 SHIPPING TANK #2)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 11 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Volatile organic compound (VOC) emission rate shall not exceed 1.99 lb/ day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in leak-free condition except when the operating pressure exceeds the valve's set pressure. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Permittee shall maintain accurate daily records of throughput, true vapor pressure, temperature of liquids stored and VOC emissions, and shall make such records available for District inspection for a period of five years. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
6. Formerly S-1132-21-0
7. Formerly S-4241-5-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-140-2

EXPIRATION DATE: 02/28/2018

SECTION: NW34 **TOWNSHIP:** 27S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

8,820 GALLON FIXED ROOF PETROLEUM SHIPPING TANK WITH PV VENT (ID: TULARE 34-2 SHIPPING TANK #1)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 11 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Volatile organic compound (VOC) emission rate shall not exceed 1.99 lb/ day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in leak-free condition except when the operating pressure exceeds the valve's set pressure. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Permittee shall maintain accurate daily records of throughput, true vapor pressure, temperature of liquids stored and VOC emissions, and shall make such records available for District inspection for a period of five years. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
6. Formerly S-1132-20-0
7. Formerly S-4241-4-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-139-2

EXPIRATION DATE: 02/28/2018

SECTION: SE34 **TOWNSHIP:** 27S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

8,820 GALLON FIXED ROOF PETROLEUM SHIPPING TANK WITH PV VENT (ID: TULARE 34-1 SHIPPING TANK #3)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 11 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Volatile organic compound (VOC) emission rate shall not exceed 1.99 lb/ day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in leak-free condition except when the operating pressure exceeds the valve's set pressure. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Permittee shall maintain accurate daily records of throughput, true vapor pressure, temperature of liquids stored and VOC emissions, and shall make such records available for District inspection for a period of five years. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
6. Formerly S-1132-18-0
7. Formerly S-4241-3-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-138-2

EXPIRATION DATE: 02/28/2018

SECTION: SE34 **TOWNSHIP:** 27S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

8,820 GALLON FIXED ROOF PETROLEUM SHIPPING TANK WITH PV VENT (ID: TULARE 34-1 SHIPPING TANK #2)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 11 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Volatile organic compound (VOC) emission rate shall not exceed 1.99 lb/ day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in leak-free condition except when the operating pressure exceeds the valve's set pressure. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Permittee shall maintain accurate daily records of throughput, true vapor pressure, temperature of liquids stored and VOC emissions, and shall make such records available for District inspection for a period of five years. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
6. Formerly S-1132-17-0
7. Formerly S-4241-2-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-137-2

EXPIRATION DATE: 02/28/2018

SECTION: SE34 **TOWNSHIP:** T27 **RANGE:** R25

EQUIPMENT DESCRIPTION:

8,820 GALLON FIXED ROOF PETROLEUM SHIPPING TANK WITH PV VENT (ID: TULARE 34-1 SHIPPING TANK #1)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 11 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Volatile organic compound (VOC) emission rate shall not exceed 1.99 lb/ day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. This tank shall be equipped with a pressure-vacuum (PV) relief valve set to within 10% of the maximum allowable working pressure of the tank, permanently labeled with the operating pressure settings, properly maintained in good operating order in accordance with the manufacturer's instructions, and shall remain in leak-free condition except when the operating pressure exceeds the valve's set pressure. [District Rule 4623, 5.2] Federally Enforceable Through Title V Permit
4. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Permittee shall maintain accurate daily records of throughput, true vapor pressure, temperature of liquids stored and VOC emissions, and shall make such records available for District inspection for a period of five years. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
6. Formerly S-1132-16-0
7. Formerly S-4241-1-0

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-120-5

EXPIRATION DATE: 02/28/2018

SECTION: 34 **TOWNSHIP:** 11N **RANGE:** 19W

EQUIPMENT DESCRIPTION:

42,000 GALLON FIXED ROOF PETROLEUM STORAGE TANK (TEJON)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct True Vapor Pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. In lieu of testing each uncontrolled fixed roof tank, an operator may conduct a TVP testing of a representative tank provided the following requirements are met. The selection of representative, uncontrolled fixed roof tanks is submitted in writing to the APCO, and written approval is granted by the APCO prior to conducting the test. One uncontrolled fixed roof tank represents some or all of the tanks in a tank battery. For crude oil production facilities, the representative uncontrolled fixed roof tank shall be the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. The stored organic liquid in each of the represented tanks is the same and came from the same source. The TVP and storage temperature of the stored organic liquid of the representative tank to be tested are the same or higher than those of the tanks it is to represent. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. If the tank stores crude oil or petroleum distillates, the operator shall also conduct an API gravity testing. [District Rule 4623, 6.2.1.2] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit
6. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit
7. For other organic liquids, the true vapor pressure (TVP) shall be measured using Reid vapor pressure ASTM Method D323, and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance of the oil and gas section of "California Air Resources Boards (ARB) Technical Guidance Document to the Criteria and Guidelines Regulations for AB 2588", dated August 1989. As an alternative to using ASTM D 323, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: CALIFORNIA RESOURCES PRODUCTION CORP

Location: LIGHT OIL CENTRAL, KERN COUNTY, CA

S-1737-120-5 Oct 5 2018 11:53AM - OROZCOA

8. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
9. This tank shall be subject to the requirements of Rule 4623 if the tank loses its exemption under section 4.0 on the date the exemption status is lost. [Rule 4623, 7.2] Federally Enforceable Through Title V Permit
10. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
11. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
12. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-115-6

EXPIRATION DATE: 02/28/2018

SECTION: 34 **TOWNSHIP:** 11N **RANGE:** 19W

EQUIPMENT DESCRIPTION:

31,500 GALLON FIXED ROOF PETROLEUM STORAGE TANK (TEJON)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct True Vapor Pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. In lieu of testing each uncontrolled fixed roof tank, an operator may conduct a TVP testing of a representative tank provided the following requirements are met. The selection of representative, uncontrolled fixed roof tanks is submitted in writing to the APCO, and written approval is granted by the APCO prior to conducting the test. One uncontrolled fixed roof tank represents some or all of the tanks in a tank battery. For crude oil production facilities, the representative uncontrolled fixed roof tank shall be the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. The stored organic liquid in each of the represented tanks is the same and came from the same source. The TVP and storage temperature of the stored organic liquid of the representative tank to be tested are the same or higher than those of the tanks it is to represent. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. If the tank stores crude oil or petroleum distillates, the operator shall also conduct an API gravity testing. [District Rule 4623, 6.2.1.2] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit
6. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit
7. For other organic liquids, the true vapor pressure (TVP) shall be measured using Reid vapor pressure ASTM Method D323, and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance of the oil and gas section of "California Air Resources Boards (ARB) Technical Guidance Document to the Criteria and Guidelines Regulations for AB 2588", dated August 1989. As an alternative to using ASTM D 323, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

8. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
9. This tank shall be subject to the requirements of Rule 4623 if the tank loses its exemption under section 4.0 on the date the exemption status is lost. [Rule 4623, 7.2] Federally Enforceable Through Title V Permit
10. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
11. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
12. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-113-6

EXPIRATION DATE: 02/28/2018

SECTION: 34 **TOWNSHIP:** 11N **RANGE:** 19W

EQUIPMENT DESCRIPTION:

42,000 GALLON FIXED ROOF PETROLEUM STORAGE TANK #1171 (TEJON)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct True Vapor Pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. In lieu of testing each uncontrolled fixed roof tank, an operator may conduct a TVP testing of a representative tank provided the following requirements are met. The selection of representative, uncontrolled fixed roof tanks is submitted in writing to the APCO, and written approval is granted by the APCO prior to conducting the test. One uncontrolled fixed roof tank represents some or all of the tanks in a tank battery. For crude oil production facilities, the representative uncontrolled fixed roof tank shall be the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. The stored organic liquid in each of the represented tanks is the same and came from the same source. The TVP and storage temperature of the stored organic liquid of the representative tank to be tested are the same or higher than those of the tanks it is to represent. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. If the tank stores crude oil or petroleum distillates, the operator shall also conduct an API gravity testing. [District Rule 4623, 6.2.1.2] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit
6. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit
7. For other organic liquids, the true vapor pressure (TVP) shall be measured using Reid vapor pressure ASTM Method D323, and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance of the oil and gas section of "California Air Resources Boards (ARB) Technical Guidance Document to the Criteria and Guidelines Regulations for AB 2588", dated August 1989. As an alternative to using ASTM D 323, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

8. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
9. This tank shall be subject to the requirements of Rule 4623 if the tank loses its exemption under section 4.0 on the date the exemption status is lost. [Rule 4623, 7.2] Federally Enforceable Through Title V Permit
10. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
11. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
12. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-112-6

EXPIRATION DATE: 02/28/2018

SECTION: 34 **TOWNSHIP:** 11N **RANGE:** 19W

EQUIPMENT DESCRIPTION:

42,000 GALLON FIXED ROOF PETROLEUM STORAGE TANK #1172

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct True Vapor Pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. In lieu of testing each uncontrolled fixed roof tank, an operator may conduct a TVP testing of a representative tank provided the following requirements are met. The selection of representative, uncontrolled fixed roof tanks is submitted in writing to the APCO, and written approval is granted by the APCO prior to conducting the test. One uncontrolled fixed roof tank represents some or all of the tanks in a tank battery. For crude oil production facilities, the representative uncontrolled fixed roof tank shall be the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. The stored organic liquid in each of the represented tanks is the same and came from the same source. The TVP and storage temperature of the stored organic liquid of the representative tank to be tested are the same or higher than those of the tanks it is to represent. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. If the tank stores crude oil or petroleum distillates, the operator shall also conduct an API gravity testing. [District Rule 4623, 6.2.1.2] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method)". Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit
6. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit
7. For other organic liquids, the true vapor pressure (TVP) shall be measured using Reid vapor pressure ASTM Method D323, and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance of the oil and gas section of "California Air Resources Boards (ARB) Technical Guidance Document to the Criteria and Guidelines Regulations for AB 2588", dated August 1989. As an alternative to using ASTM D 323, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

8. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
9. This tank shall be subject to the requirements of Rule 4623 if the tank loses its exemption under section 4.0 on the date the exemption status is lost. [Rule 4623, 7.2] Federally Enforceable Through Title V Permit
10. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
11. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
12. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-111-5

EXPIRATION DATE: 02/28/2018

SECTION: 34 **TOWNSHIP:** 11N **RANGE:** 19W

EQUIPMENT DESCRIPTION:

42,000 GALLON FIXED ROOF PETROLEUM STORAGE TANK #12176 (TEJON)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct True Vapor Pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. In lieu of testing each uncontrolled fixed roof tank, an operator may conduct a TVP testing of a representative tank provided the following requirements are met. The selection of representative, uncontrolled fixed roof tanks is submitted in writing to the APCO, and written approval is granted by the APCO prior to conducting the test. One uncontrolled fixed roof tank represents some or all of the tanks in a tank battery. For crude oil production facilities, the representative uncontrolled fixed roof tank shall be the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. The stored organic liquid in each of the represented tanks is the same and came from the same source. The TVP and storage temperature of the stored organic liquid of the representative tank to be tested are the same or higher than those of the tanks it is to represent. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. If the tank stores crude oil or petroleum distillates, the operator shall also conduct an API gravity testing. [District Rule 4623, 6.2.1.2] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method)". Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit
6. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit
7. For other organic liquids, the true vapor pressure (TVP) shall be measured using Reid vapor pressure ASTM Method D323, and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance of the oil and gas section of "California Air Resources Boards (ARB) Technical Guidance Document to the Criteria and Guidelines Regulations for AB 2588", dated August 1989. As an alternative to using ASTM D 323, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

8. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
9. This tank shall be subject to the requirements of Rule 4623 if the tank loses its exemption under section 4.0 on the date the exemption status is lost. [Rule 4623, 7.2] Federally Enforceable Through Title V Permit
10. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
11. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
12. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-110-5

EXPIRATION DATE: 02/28/2018

SECTION: 34 **TOWNSHIP:** 11N **RANGE:** 19W

EQUIPMENT DESCRIPTION:

42,000 GALLON FIXED ROOF PETROLEUM STORAGE TANK #12177 (TEJON)

PERMIT UNIT REQUIREMENTS

1. This tank shall only store, place, or hold organic liquid with a true vapor pressure (TVP) of less than 0.5 psia under all storage conditions. [District Rule 4623] Federally Enforceable Through Title V Permit
2. Permittee shall conduct True Vapor Pressure (TVP) testing of the organic liquid stored in this tank at least once every 24 months during summer (July - September), and/or whenever there is a change in the source or type of organic liquid stored in this tank in order to maintain exemption from the rule. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
3. In lieu of testing each uncontrolled fixed roof tank, an operator may conduct a TVP testing of a representative tank provided the following requirements are met. The selection of representative, uncontrolled fixed roof tanks is submitted in writing to the APCO, and written approval is granted by the APCO prior to conducting the test. One uncontrolled fixed roof tank represents some or all of the tanks in a tank battery. For crude oil production facilities, the representative uncontrolled fixed roof tank shall be the first line tank (or tanks) in a tank battery that is first receiving the produced fluids (mixture of oil, water, and gases) from the crude oil production wells. The stored organic liquid in each of the represented tanks is the same and came from the same source. The TVP and storage temperature of the stored organic liquid of the representative tank to be tested are the same or higher than those of the tanks it is to represent. [District Rule 4623, 6.2.2] Federally Enforceable Through Title V Permit
4. The TVP testing shall be conducted at actual storage temperature of the organic liquid in the tank. If the tank stores crude oil or petroleum distillates, the operator shall also conduct an API gravity testing. [District Rule 4623, 6.2.1.2] Federally Enforceable Through Title V Permit
5. The API gravity of crude oil or petroleum distillate shall be determined by using ASTM Method D 287 e1 "Standard Test Method for API Gravity of Crude Petroleum and Petroleum Products (Hydrometer Method). Sampling for API gravity shall be performed in accordance with ASTM Method D 4057 "Standard Practices for Manual Sampling of Petroleum and Petroleum Products." [District Rule 4623, 6.4.2] Federally Enforceable Through Title V Permit
6. For crude oil with an API gravity of 26 degrees or less, the TVP shall be determined using the latest version of the Lawrence Berkeley National Laboratory "test Method for Vapor pressure of Reactive Organic Compounds in Heavy Crude Oil Using Gas Chromatograph", as approved by ARB and EPA. [District Rule 4623, 6.4.4] Federally Enforceable Through Title V Permit
7. For other organic liquids, the true vapor pressure (TVP) shall be measured using Reid vapor pressure ASTM Method D323, and converting the RVP to TVP at the tank's maximum organic liquid storage temperature. The conversion of RVP to TVP shall be done in accordance of the oil and gas section of "California Air Resources Boards (ARB) Technical Guidance Document to the Criteria and Guidelines Regulations for AB 2588", dated August 1989. As an alternative to using ASTM D 323, the TVP of crude oil with an API gravity range of greater than 26 degrees up to 30 degrees may be determined by using other equivalent test methods approved by APCO, ARB and EPA. [District Rule 4623, 6.4.3] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: CALIFORNIA RESOURCES PRODUCTION CORP

Location: LIGHT OIL CENTRAL, KERN COUNTY, CA

S-1737-110-5 Oct 5 2018 11:53AM - OROZCOA

8. Permittee shall submit the records of TVP and API gravity testing to the APCO within 45 days after the date of testing. The records shall include the tank identification number, Permit to Operate number, type of stored organic liquid, TVP and API gravity of the organic liquid, test methods used, and a copy of the test results. [District Rule 4623] Federally Enforceable Through Title V Permit
9. This tank shall be subject to the requirements of Rule 4623 if the tank loses its exemption under section 4.0 on the date the exemption status is lost. [Rule 4623, 7.2] Federally Enforceable Through Title V Permit
10. As used in this permit, the term "source or type" shall mean liquids with similar characteristics. The operator shall maintain records of API gravity of petroleum liquids stored in this unit to determine which are from common source. [District Rule 2520, 9.3.2] Federally Enforceable Through Title V Permit
11. This unit has a storage capacity less than 420,000 gallons and is used for petroleum or condensate stored, processed and/or treated at a drilling and production facility prior to custody transfer. Therefore, the requirements of 40CFR 60 Subpart K, Ka and Kb do not apply to this source. A permit shield is granted from these requirements. [District Rule 2520, 13.2] Federally Enforceable Through Title V Permit
12. The operator of a fixed roof tank shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2520, 9.4.2] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

PERMIT-EXEMPT EQUIPMENT REGISTRATION (PEER)

PEER NO: S-1737-2-0

EXPIRATION DATE: 03/24/2020

LEGAL OWNER OR OPERATOR: CALIFORNIA RESOURCES PRODUCTION CORP

MAILING ADDRESS: 11109 RIVER RUN BLVD
BAKERSFIELD, CA 93311

FACILITY LOCATION: LIGHT OIL CENTRAL
KERN COUNTY, CA

EQUIPMENT DESCRIPTION:

4.7 MMBTU/HR MAXON MODEL XPO2PB NATURAL GAS-FIRED HEATER TREATER WITH A MAXON LOW NOX BURNER

CONDITIONS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201]
3. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101]
4. This unit shall be fired exclusively on Public Utilities Commission (PUC) quality natural gas with a fuel sulfur content of no more than one (1) grain of total sulfur per one hundred (100) standard cubic feet of fuel. [District Rules 2020, 4307, and 4801]
5. The unit shall not exceed any of the following emission limits: 30 ppmvd-NOx @ 3% O2 or 0.036 lb-NOx/MMBtu, or 400 ppmvd-CO @ 3% O2. [District Rule 4307]
6. The owner/operator shall monitor, at least once a month, the operational characteristics recommended by the manufacturer and approved by the APCO. [District Rule 4307]
7. The owner/operator shall have unit tuned at least twice each calendar year, from four to eight months apart, in which it operates, by a technician that is qualified, to the satisfaction of the APCO, in accordance with the procedure described in Rule 4304 (Equipment Tuning Procedure for Boilers, Steam Generators, and Process Heaters). [District Rule 4307]
8. If the unit does not operate throughout a continuous six-month period within a calendar year, only one tune-up is required for that calendar year. No tune-up is required for any unit that is not operated during that calendar year; this unit may be test fired to verify availability of the unit for its intended use, but once the test firing is completed the unit shall be shutdown. [District Rule 4307]

CONDITIONS CONTINUE ON NEXT PAGE

This PEER remains valid through the expiration date listed above, subject to payment of the annual registration fees and compliance with the PEER conditions and all applicable local, state, and federal regulations. This PEER is valid only within the San Joaquin Valley Air Pollution Control District. Any equipment or operation change may require a PEER application be filed with the District.

Samir Sheikh

Executive Director / APCO

S-1737-2-0 : 10/05/2018 - OROZCOA : Joint Inspection NOT Required

Arnaud Marjollet

Director of Permit Services

9. In lieu of tuning the unit twice each calendar year, the owner/operator shall monitor the emissions with a portable NOx analyzer at least twice each calendar year and adjust the unit's operating parameters accordingly to assure compliance with the emission limits of this rule. [District Rule 4307]
10. Source testing to measure NOx and CO emissions from this unit shall be conducted no later than 60 days after issuance of this PEER or installation, whichever is later. [District Rule 4307]
11. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081]
12. NOx emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rule 4307]
13. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rule 4307]
14. Stack gas oxygen (O2) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rule 4307]
15. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 4307]
16. The owner/operator shall maintain records to verify that the required monitoring of the operational characteristics, and tune-ups or portable NOx analyzing has been performed. [District Rule 4307]
17. Tune-up records shall include: 1) date of tune-up, 2) name of technician performing tune-up, and 3) reason that they are qualified. [District Rule 4307]
18. Portable analyzer records shall include: 1) date of emissions analyzing, 2) results of emissions analyzing, 3) name of technician performing analyzing, 4) make and model of analyzer, 5) date of last calibration of the analyzer, and 6) a description of any adjustments made to the unit's operating parameters for the purposes of assuring compliance. [District Rule 4307]
19. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rules 4307]

PERMIT-EXEMPT EQUIPMENT REGISTRATION (PEER)

PEER NO: S-1737-1-0

EXPIRATION DATE: 03/24/2020

LEGAL OWNER OR OPERATOR: CALIFORNIA RESOURCES PRODUCTION CORP

MAILING ADDRESS: 11109 RIVER RUN BLVD
BAKERSFIELD, CA 93311

FACILITY LOCATION: LIGHT OIL CENTRAL
KERN COUNTY, CA

EQUIPMENT DESCRIPTION:

4.5 MMBTU/HR MAXON MODEL XPO4PB4 NATURAL GAS-FIRED HEATER TREATER WITH A MAXON LOW NOX BURNER

CONDITIONS

1. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102]
2. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201]
3. No air contaminant shall be discharged into the atmosphere for a period or periods aggregating more than three minutes in any one hour which is as dark as, or darker than, Ringelmann 1 or 20% opacity. [District Rule 4101]
4. This unit shall be fired exclusively on Public Utilities Commission (PUC) quality natural gas with a fuel sulfur content of no more than one (1) grain of total sulfur per one hundred (100) standard cubic feet of fuel. [District Rules 2020, 4307, and 4801]
5. The unit shall not exceed any of the following emission limits: 30 ppmvd-NOx @ 3% O2 or 0.036 lb-NOx/MMBtu, or 400 ppmvd-CO @ 3% O2. [District Rule 4307]
6. The owner/operator shall monitor, at least once a month, the operational characteristics recommended by the manufacturer and approved by the APCO. [District Rule 4307]
7. The owner/operator shall have unit tuned at least twice each calendar year, from four to eight months apart, in which it operates, by a technician that is qualified, to the satisfaction of the APCO, in accordance with the procedure described in Rule 4304 (Equipment Tuning Procedure for Boilers, Steam Generators, and Process Heaters). [District Rule 4307]
8. If the unit does not operate throughout a continuous six-month period within a calendar year, only one tune-up is required for that calendar year. No tune-up is required for any unit that is not operated during that calendar year; this unit may be test fired to verify availability of the unit for its intended use, but once the test firing is completed the unit shall be shutdown. [District Rule 4307]

CONDITIONS CONTINUE ON NEXT PAGE

This PEER remains valid through the expiration date listed above, subject to payment of the annual registration fees and compliance with the PEER conditions and all applicable local, state, and federal regulations. This PEER is valid only within the San Joaquin Valley Air Pollution Control District. Any equipment or operation change may require a PEER application be filed with the District.

Samir Sheikh

Executive Director / APCO

S-1737-1-0 10/05/2018 -- OROZCOA Joint Inspection NOT Required

Arnaud Marjollet

Director of Permit Services

9. In lieu of tuning the unit twice each calendar year, the owner/operator shall monitor the emissions with a portable NOx analyzer at least twice each calendar year and adjust the unit's operating parameters accordingly to assure compliance with the emission limits of this rule. [District Rule 4307]
10. Source testing to measure NOx and CO emissions from this unit shall be conducted no later than 60 days after issuance of this PEER or installation, whichever is later. [District Rule 4307]
11. Source testing shall be conducted using the methods and procedures approved by the District. The District must be notified at least 30 days prior to any compliance source test, and a source test plan must be submitted for approval at least 15 days prior to testing. [District Rule 1081]
12. NOx emissions for source test purposes shall be determined using EPA Method 7E or ARB Method 100 on a ppmv basis, or EPA Method 19 on a heat input basis. [District Rule 4307]
13. CO emissions for source test purposes shall be determined using EPA Method 10 or ARB Method 100. [District Rule 4307]
14. Stack gas oxygen (O2) shall be determined using EPA Method 3 or 3A or ARB Method 100. [District Rule 4307]
15. The results of each source test shall be submitted to the District within 60 days thereafter. [District Rule 4307]
16. The owner/operator shall maintain records to verify that the required monitoring of the operational characteristics, and tune-ups or portable NOx analyzing has been performed. [District Rule 4307]
17. Tune-up records shall include: 1) date of tune-up, 2) name of technician performing tune-up, and 3) reason that they are qualified. [District Rule 4307]
18. Portable analyzer records shall include: 1) date of emissions analyzing, 2) results of emissions analyzing, 3) name of technician performing analyzing, 4) make and model of analyzer, 5) date of last calibration of the analyzer, and 6) a description of any adjustments made to the unit's operating parameters for the purposes of assuring compliance. [District Rule 4307]
19. All records shall be maintained and retained on-site for a period of at least 5 years and shall be made available for District inspection upon request. [District Rules 4307]

Permit to Operate

FACILITY: S-1737

EXPIRATION DATE: 02/28/2018

LEGAL OWNER OR OPERATOR:
MAILING ADDRESS:

CALIFORNIA RESOURCES PRODUCTION CORP
11109 RIVER RUN BLVD
BAKERSFIELD, CA 93311

FACILITY LOCATION:

LIGHT OIL CENTRAL
KERN COUNTY, CA

FACILITY DESCRIPTION:

CRUDE OIL AND NATURAL GAS PRODUCTION

The Facility's Permit to Operate may include Facility-wide Requirements as well as requirements that apply to specific permit units.

This Permit to Operate remains valid through the permit expiration date listed above, subject to payment of annual permit fees and compliance with permit conditions and all applicable local, state, and federal regulations. This permit is valid only at the location specified above, and becomes void upon any transfer of ownership or location. Any modification of the equipment or operation, as defined in District Rule 2201, will require prior District approval. This permit shall be posted as prescribed in District Rule 2010.

Samir Sheikh

Executive Director / APCO

Arnaud Marjollet

Director of Permit Services

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-200-1

EXPIRATION DATE: 02/28/2018

SECTION: SW 23 **TOWNSHIP:** 27S **RANGE:** 24E

EQUIPMENT DESCRIPTION:

500 BBL FIXED ROOF CRUDE OIL TANK VENTED TO VAPOR CONTROL SYSTEM LISTED ON TANK S-1737-172

PERMIT UNIT REQUIREMENTS

1. The tank and all piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rules 2201 and 4623]
2. All tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623]
3. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated to methane in accordance with the procedures specified in EPA Test Method 21. A gas leak is a violation of Rule 2201. [District Rule 2201] Federally Enforceable Through Title V Permit
4. VOC fugitive emissions from the components in gas service on the tank up to the vapor control system trunk line shall not exceed 0.2 lb/day. [District Rule 2201]
5. Permittee shall maintain accurate component count for tank according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors < 10,000 ppmv. Permittee shall update such records when new components are approved and installed. [District Rule 2201]
6. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rules 2201 and 4623]
7. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rule 4623]
8. This tank shall be degassed before commencing interior cleaning by one of the following methods (1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less; or (2) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia; or (3) displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623]

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623]
10. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 4623]
11. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rule 4623]
12. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rule 4623]
13. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 4623]
14. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623 shall constitute a violation of this rule. [District Rule 4623]
15. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rule 4623]
16. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 2201]
17. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 2201 and 4623]
18. Operator shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 1070]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-193-1

EXPIRATION DATE: 02/28/2018

SECTION: SW 36 **TOWNSHIP:** 26S **RANGE:** 24E

EQUIPMENT DESCRIPTION:

3,000 BBL FIXED ROOF CRUDE OIL TANK VENTED TO VAPOR CONTROL SYSTEM LISTED ON TANK S-1737-168

PERMIT UNIT REQUIREMENTS

1. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
2. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
3. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
4. VOC fugitive emissions from the components in gas/light oil service on tank and from tank to vapor control, system trunk line shall not exceed 0.1 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall maintain accurate component count for tank according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors < 10,000 ppmv. Permittee shall update such records when new components are approved and installed. [District Rule 2201] Federally Enforceable Through Title V Permit
6. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
7. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
8. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 2201 and 4623] Federally Enforceable Through Title V Permit
9. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: CALIFORNIA RESOURCES PRODUCTION CORP

Location: LIGHT OIL CENTRAL, KERN COUNTY, CA

S-1737-193-1 Oct 5 2018 11:53AM - OROZCOA

10. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
11. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
12. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
13. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rules 2201 and 4623]
14. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rules 4623 and 2080] Federally Enforceable Through Title V Permit
15. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rules 4623 and 2080] Federally Enforceable Through Title V Permit
16. This tank shall be degassed before commencing interior cleaning by 1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less 2) by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia. or 3) by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623] Federally Enforceable Through Title V Permit
17. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623] Federally Enforceable Through Title V Permit
18. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rules 4623] Federally Enforceable Through Title V Permit
19. This tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid having a TVP of 0.5 psia or greater. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

20. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit
21. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit
22. The permittee shall keep accurate records of the dates of inspection and monitoring and the components inspected and monitored. [District Rule 2201] Federally Enforceable Through Title V Permit
23. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
24. The permittee shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2201 and 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-186-0

EXPIRATION DATE: 02/28/2018

SECTION: SE 36 **TOWNSHIP:** 26S **RANGE:** 24E

EQUIPMENT DESCRIPTION:

500 BBL CRUDE OIL STORAGE TANK CONNECTED TO THE VAPOR CONTROL SYSTEM LISTED ON PERMIT S-1737-168

PERMIT UNIT REQUIREMENTS

1. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
2. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
3. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
4. VOC fugitive emissions from the components in gas/light oil service on tank and from tank to vapor control, system trunk line shall not exceed 0.3 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall maintain accurate component count for tank according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors < 10,000 ppmv. Permittee shall update such records when new components are approved and installed. [District Rule 2201] Federally Enforceable Through Title V Permit
6. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
7. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
8. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 2201 and 4623] Federally Enforceable Through Title V Permit
9. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: CALIFORNIA RESOURCES PRODUCTION CORP

Location: LIGHT OIL CENTRAL, KERN COUNTY, CA

S-1737-186-0 Oct 5 2018 11:53AM - OROZCOA

10. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
11. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
12. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
13. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rules 2201 and 4623]
14. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rules 4623 and 2080] Federally Enforceable Through Title V Permit
15. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rules 4623 and 2080] Federally Enforceable Through Title V Permit
16. This tank shall be degassed before commencing interior cleaning by 1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less 2) by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia. or 3) by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623] Federally Enforceable Through Title V Permit
17. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623] Federally Enforceable Through Title V Permit
18. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rules 4623] Federally Enforceable Through Title V Permit
19. This tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid having a TVP of 0.5 psia or greater. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

20. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit
21. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit
22. The permittee shall keep accurate records of the dates of inspection and monitoring and the components inspected and monitored. [District Rule 2201] Federally Enforceable Through Title V Permit
23. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
24. The permittee shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2201 and 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-185-0

EXPIRATION DATE: 02/28/2018

SECTION: SE 36 **TOWNSHIP:** 26S **RANGE:** 24E

EQUIPMENT DESCRIPTION:

500 BBL CRUDE OIL STORAGE TANK CONNECTED TO THE VAPOR CONTROL SYSTEM LISTED ON PERMIT S-1737-168

PERMIT UNIT REQUIREMENTS

1. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
2. A leak-free condition is defined as a condition without a gas leak. A gas leak is defined as a reading in excess of 10,000 ppmv, above background, as measured by a portable hydrocarbon detection instrument in accordance with the procedures specified in EPA Test Method 21. A reading in excess of 10,000 ppmv above background is a violation of this permit and Rule 4623 and shall be reported as a deviation. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
3. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
4. VOC fugitive emissions from the components in gas/light oil service on tank and from tank to vapor control, system trunk line shall not exceed 0.3 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Permittee shall maintain accurate component count for tank according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors < 10,000 ppmv. Permittee shall update such records when new components are approved and installed. [District Rule 2201] Federally Enforceable Through Title V Permit
6. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
7. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
8. Operator shall visually inspect tank shell, hatches, seals, seams, cable seals, valves, flanges, connectors, and any other piping components directly affixed to the tank and within five feet of the tank at least once per year for liquid leaks, and with a portable hydrocarbon detection instrument conducted in accordance with EPA Method 21 for gas leaks. Operator shall also visually or ultrasonically inspect as appropriate, the external shells and roofs of uninsulated tanks for structural integrity annually. [District Rule 2201 and 4623] Federally Enforceable Through Title V Permit
9. Upon detection of a liquid leak, defined as a leak rate of greater than or equal to 30 drops per minute, operator shall repair the leak within 8 hours. For leaks with a liquid leak rate of between 3 and 30 drops per minute, the leaking component shall be repaired within 24 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Upon detection of a gas leak, defined as a VOC concentration of greater than 10,000 ppmv measured in accordance with EPA Method 21, operator shall take one of the following actions: 1) eliminate the leak within 8 hours after detection; or 2) if the leak cannot be eliminated, then minimize the leak to the lowest possible level within 8 hours after detection by using best maintenance practices, and eliminate the leak within 48 hours after minimization. In no event shall the total time to minimize and eliminate a leak exceed 56 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
11. Components found to be leaking either liquids or gases shall be immediately affixed with a tag showing the component to be leaking. Operator shall maintain records of the liquid or gas leak detection readings, date/time the leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
12. Leaking components that have been discovered by the operator that have been immediately tagged and repaired within the timeframes specified in District Rule 4623, Table 3 shall not constitute a violation of this rule. Leaking components as defined by District Rule 4623 discovered by District staff that were not previously identified and/or tagged by the operator, and/or any leaks that were not repaired within the timeframes specified in District Rule 4623, Table 3 shall constitute a violation of this rule. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
13. If a component type for a given tank is found to leak during an annual inspection, operator shall conduct quarterly inspections of that component type on the tank or tank system for four consecutive quarters. If no components are found to leak after four consecutive quarters, the operator may revert to annual inspections. [District Rules 2201 and 4623]
14. Permittee shall notify the APCO in writing at least three (3) days prior to performing tank degassing and interior tank cleaning activities. Written notification shall include the following: 1) the Permit to Operate number and physical location of the tank being degassed, 2) the date and time that tank degassing and cleaning activities will begin, 3) the degassing method, as allowed in this permit, to be used, 4) the method to be used to clean the tank, including any solvents to be used, and 5) the method to be used to dispose of any removed sludge, including methods that will be used to control emissions from the receiving vessel and emissions during transport. [District Rules 4623 and 2080] Federally Enforceable Through Title V Permit
15. This permit authorizes tank cleaning that is not the result of breakdowns or poor maintenance as a routine maintenance activity. [District Rules 4623 and 2080] Federally Enforceable Through Title V Permit
16. This tank shall be degassed before commencing interior cleaning by 1) exhausting VOCs contained in the tank vapor space to an APCO-approved vapor recovery system until the organic vapor concentration is 5,000 ppmv or less, or is 10 percent or less of the lower explosion limit (LEL), whichever is less 2) by filling the tank with a suitable liquid until 90 percent or more of the maximum operating level of the tank is filled. Suitable liquids are organic liquids having a TVP of less than 0.5 psia, water, clean produced water, or produced water derived from crude oil having a TVP less than 0.5 psia. or 3) by displacing VOCs contained in the tank vapor space to an APCO-approved vapor recovery system by filling the tank with a suitable gas. Degassing shall continue until the operator has achieved a vapor displacement equivalent to at least 2.3 times the tank capacity. Suitable gases are air, nitrogen, carbon dioxide, or natural gas containing less than 10 percent VOC by weight. [District Rule 4623] Federally Enforceable Through Title V Permit
17. During tank degassing, the operator shall discharge or displace organic vapors contained in the tank vapor space to an APCO-approved vapor recovery system. [District Rule 4623] Federally Enforceable Through Title V Permit
18. To facilitate connection to an external APCO-approved recovery system, a suitable tank fitting, such as a manway, may be temporarily removed for a period of time not to exceed 1 hour. [District Rules 4623] Federally Enforceable Through Title V Permit
19. This tank shall be in compliance with the applicable requirements of District Rule 4623 at all times during draining, degassing, and refilling the tank with an organic liquid having a TVP of 0.5 psia or greater. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

20. While performing tank cleaning activities, operators may only use the following cleaning agents: diesel, solvents with an initial boiling point of greater than 302 degrees F, solvents with a vapor pressure of less than 0.5 psia, or solvents with 50 grams of VOC per liter or less. [District Rule 4623] Federally Enforceable Through Title V Permit
21. Steam cleaning shall only be allowed at locations where wastewater treatment facilities are limited, or during the months of December through March. [District Rule 4623] Federally Enforceable Through Title V Permit
22. The permittee shall keep accurate records of the dates of inspection and monitoring and the components inspected and monitored. [District Rule 2201] Federally Enforceable Through Title V Permit
23. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
24. The permittee shall maintain all records of required monitoring data and support information for inspection at any time for a period of five years. [District Rule 2201 and 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-180-2

EXPIRATION DATE: 02/28/2018

EQUIPMENT DESCRIPTION:

49 MMBTU/HR FLARE APPROVED FOR USE IN WELL TESTING, TANK AND WELL VENT CONTROL, EQUIPMENT SHUTDOWN, EMERGENCIES AND OTHER SITUATIONS REQUIRING A SAFETY FLARE AT VARIOUS UNSPECIFIED LOCATIONS

PERMIT UNIT REQUIREMENTS

1. Flare shall not be located within 1000 feet of any K-12 school. [CH&SC 42301.6]
2. The flare must not operate within 100 meter from the facility boundary. [District Rule 4102]
3. Permittee shall notify the District Compliance Division of each location at which the flare is located in excess of 24 hours. Such notification shall be made no later than 48 hours after starting operation at the location. [District Rule 1070] Federally Enforceable Through Title V Permit
4. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
5. Flare shall operate in a smokeless manner (0% opacity) except for three minutes in any one hour. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Flare gas inlet line shall be equipped with operational volumetric totalizing flowrate indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Gas flowrate to flare (not including pilot gas) shall not exceed 1.4 MMscf per day nor 255.5 MMscf/yr of gas. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Emission rates from this unit shall not exceed any of the following limits: NO_x (as NO₂) - 0.068 lb/Mscf; VOC (as methane) - 0.063 lb/Mscf; CO - 0.37 lb/Mscf or PM₁₀ - 0.008 lb/Mscf. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Gas sulfur content shall not exceed 0.25 gr/100 scf. [District Rules 2201 and 4801] Federally Enforceable Through Title V Permit
10. Gas shall be tested quarterly for sulfur content. Upon transfer of location or change in the method of operation of the flare (excluding emergencies), gas shall be tested weekly for sulfur content. If compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks then the fuel testing frequency shall be quarterly. If a quarterly fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The sulfur content of the gas being flared shall be determined using ASTM D1072, D3031, D4084, D3246, or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit
12. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by: ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: CALIFORNIA RESOURCES PRODUCTION CORP

Location: LIGHT OIL CENTRAL, KERN COUNTY, CA

S-1737-180-2 : Oct 5 2018 11:53AM - OROZCOA

13. A trained observer, as defined in EPA Method 22, shall check visible emissions at least once every two weeks for a period of 15 minutes. If visible emissions are detected at any time during this period, the observation period shall be extended to two hours. A record containing the results of these observations shall be maintained, which also includes company name, process unit, observer's name and affiliation, date, estimated wind speed and direction, sky condition, and the observer's location relative to the source and sun. [District Rules 2080 and 4101] Federally Enforceable Through Title V Permit
14. The outlet shall be equipped with an automatic ignition system, or, shall operate with a pilot flame present at all times when combustible gases are vented through the flare, except during purge periods for automatic-ignition equipped flares. [District Rule 4311] Federally Enforceable Through Title V Permit
15. Permittee shall obtain an ATC to modify any permit unit which authorizes this flare as a control device prior to this flare operating as a control device for that permit unit. [District Rule 2201] Federally Enforceable Through Title V Permit
16. Except for flares equipped with a flow-sensing ignition system, a heat sensing device such as a thermocouple, ultraviolet beam sensor, infrared sensor, or an equivalent device, capable of continuously detecting at least one pilot flame or the flare flame is present, shall be installed and operated. [District Rule 4311] Federally Enforceable Through Title V Permit
17. Flares that use flow-sensing automatic ignition systems and which do not use a continuous flame pilot shall use purge gas for purging. [District Rule 4311] Federally Enforceable Through Title V Permit
18. Open flares (air-assisted, steam assisted or non-assisted) in which the flare gas pressure is less than 5 psig shall be operated in such a manner that meets the provisions of 40 CFR 60.18. [District Rule 4311] Federally Enforceable Through Title V Permit
19. The flare shall be inspected every two weeks while in operation for visible emissions. If visible emissions are observed, corrective action shall be taken. If visible emissions continue, an EPA method 9 test shall be conducted within 72 hours. [District Rule 2201] Federally Enforceable Through Title V Permit
20. The flare shall be operated according to the manufacturer's specifications, a copy of which shall be maintained on site. [District Rule 2080] Federally Enforceable Through Title V Permit
21. Permittee shall maintain accurate daily records of volume, type, higher heating value, and sulfur content of gas flared [District Rule 2201 & 1070] Federally Enforceable Through Title V Permit
22. Permittee shall maintain accurate records of location and duration of operation at each stationary source. [District Rule 2201, 4311 & 4409] Federally Enforceable Through Title V Permit
23. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 2201, 4311 & 4409] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-178-1

EXPIRATION DATE: 02/28/2018

SECTION: SW23 **TOWNSHIP:** 27S **RANGE:** 23E

EQUIPMENT DESCRIPTION:

25 FOOT TALL MACTRONIC AIR-ASSISTED PROCESS GAS FLARE SERVING VAPOR CONTROL SYSTEM LISTED ON S-1737-172, WITH 2 INCH DIAMETER FLARE GAS LINE, 6 INCH DIAMETER FLARE STACK, ELECTRONIC IGNITOR, AND FLAME ARRESTOR SERVED BY 20 BBL GAS-LIQUID SEPARATOR; 3 EACH, 3 BBL KNOCKOUT VESSELS; AND AN H2S SCAVENGER

PERMIT UNIT REQUIREMENTS

1. Gas shall be processed in the H2S scrubber as needed to meet 50 ppmv sulfur (as H2S) content limit. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Flare air-assist blower shall be maintained and operated for smokeless combustion, i.e. no visible emissions in excess of 5% opacity or 1/4 Ringelmann. [District Rule 2201] Federally Enforceable Through Title V Permit
3. Flare shall be equipped with waste gas volume flow meter. [District Rule 2201] Federally Enforceable Through Title V Permit
4. This permit does not authorize the utilization of any IC engine, or other combustion device requiring a separate permit, for powering the air assist to the flare. [District Rule 2201] Federally Enforceable Through Title V Permit
5. Flare shall operate in a smokeless manner (no greater than 5% opacity) except for three minutes in any one hour. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Operator shall immediately utilize air assist if flare exhibits smoke greater than 0% opacity. [District Rule 2201 and 4101] Federally Enforceable Through Title V Permit
7. Total sulfur (as H2S) concentration of gas incinerated in flare shall not exceed 50 ppmv. [District Rules 2201 and 4801] Federally Enforceable Through Title V Permit
8. The amount of gas combusted shall not exceed 100,000 scf/day. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Emissions from the flare shall not exceed any of the following (based on total gas combusted): NOx (as NO2): 0.068 lb/MMBtu; PM10: 0.008 lb/MMBtu; CO: 0.37 lb/MMBtu; or VOC: 0.063 lb/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Fugitive VOC emissions rate, calculated using CAPCOA California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities Table IV-2c less than or equal to 10,000 ppmv (Feb 1999), from the total number of tank components, including vapor control system components from the tank to the vapor control system trunk line shall not exceed 1.1 pounds per day. [District Rule 2201] Federally Enforceable Through Title V Permit
11. Permittee shall comply with all applicable requirements of Rule 4311. [District Rule 4311] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

12. All piping, valves and fittings shall be constructed and maintained in a gas-tight condition. Gas-tight shall be defined as emitting no more than 10,000 ppmv of methane measured at the potential source with an instrument calibrated with methane in accordance with EPA Method 21. Emissions in excess of this limit shall be considered a leak. [District Rule 2201] Federally Enforceable Through Title V Permit
13. Permittee shall measure sulfur content of gas incinerated in flare at least once every year. Such data shall be submitted to the District within 60 days of sample collection. [District Rules 2201 and 4801] Federally Enforceable Through Title V Permit
14. Permittee shall determine sulfur content of gas flared using ASTM method D3246 or double GC for H₂S and mercaptans. [District Rule 2201] Federally Enforceable Through Title V Permit
15. Permittee shall keep accurate records of daily, quarterly, and annual quantity of gas combusted, and such records shall be retained for a period of five years and made readily available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-177-1

EXPIRATION DATE: 02/28/2018

SECTION: SW 23 **TOWNSHIP:** 27S **RANGE:** 23E

EQUIPMENT DESCRIPTION:

0.5 MMBTU/HR FIELD GAS-FIRED HEATER (SEMITROPIC TANK BATTERY)

PERMIT UNIT REQUIREMENTS

1. Particulate matter emissions shall not exceed 0.1 grain/dscf at operating conditions, nor 0.1 grain/dscf calculated to 12% CO₂, nor 10 lb/hr. [District Rule 4201 and District Rule 4301, 5.1 and 5.2.3] Federally Enforceable Through Title V Permit
2. Emissions of sulfur compounds from this unit shall not exceed 200 lb per hour, calculated as SO₂. [District Rules 4301, 5.2.1] Federally Enforceable Through Title V Permit
3. Emissions of nitrogen oxides from this unit shall not exceed 140 lb per hour, calculated as NO₂. [District Rule 4301, 5.2.1] Federally Enforceable Through Title V Permit
4. Sulfur compound emissions shall not exceed 0.2% by volume, 2000 ppmv, on a dry basis averaged over 15 consecutive minutes. [District Rule 4801]

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-176-1

EXPIRATION DATE: 02/28/2018

SECTION: SW 23 **TOWNSHIP:** 27S **RANGE:** 23E

EQUIPMENT DESCRIPTION:

4200 GALLON FIXED ROOF SLOP TANK VENTED TO VAPOR CONTROL SYSTEM LISTED ON S-1737-172
(SEMITROPIC TANK BATTERY)

PERMIT UNIT REQUIREMENTS

1. Combined VOC emissions rate from the components associated with the tank in gas, light liquid and light crude oil service shall not exceed 0.1 pounds per day. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Any tank gauging or sampling device on this tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
3. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Leak-free shall be a condition without a gas leak or a liquid leak. Gas Leak shall be defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the EPA Method 21. Liquid leak is shall be defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Permittee shall maintain a log indicating component type, number of components, appropriate emission factors from CAPCOA 's document "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities" Table IV-2c (Feb 1999) - Screening Range Emissions Factors, and resultant emissions to demonstrate on-going compliance with the daily emission limit. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Hatch, tank seals and seams, cable seals, piping components directly affixed to the tank including but not limited to valves, flanges, connectors etc. shall be inspected and monitored at least once every quarter by the operator using portable hydrocarbon detection instrument in accordance with EPA Method 21. If a component type found to leak during the quarterly inspection, then conduct monthly inspections of that component type for two consecutive months. If a component type is found to have no leak after two consecutive months, then revert to quarterly inspections. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall keep records of the dates on which components are inspected and monitored, and number of components inspected corresponding to each component type. For leaking components, the operator shall immediately affix a tag and maintain records of liquid leak and gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
8. All records shall be retained for a minimum of five years, and shall be made available for District inspection upon request. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-175-1

EXPIRATION DATE: 02/28/2018

SECTION: SW 23 **TOWNSHIP:** 27S **RANGE:** 23E

EQUIPMENT DESCRIPTION:

21,000 GALLON FIXED ROOF SKIM TANK VENTED TO VAPOR CONTROL SYSTEM LISTED ON S-1737-172
(SEMITROPIC TANK BATTERY)

PERMIT UNIT REQUIREMENTS

1. Combined VOC emissions rate from the components associated with the tank in gas, light liquid and light crude oil service shall not exceed 0.2 pounds per day. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Any tank gauging or sampling device on this tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
3. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Leak-free shall be a condition without a gas leak or a liquid leak. Gas Leak shall be defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the EPA Method 21. Liquid leak is shall be defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Permittee shall maintain a log indicating component type, number of components, appropriate emission factors from CAPCOA 's document "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities" Table IV-2c (Feb 1999) - Screening Range Emissions Factors, and resultant emissions to demonstrate on-going compliance with the daily emission limit. [District Rule 2201] Federally Enforceable Through Title V Permit
6. The operator shall keep records of the dates on which components are inspected and monitored, and number of components inspected corresponding to each component type. For leaking components, the operator shall immediately affix a tag and maintain records of liquid leak and gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Hatch, tank seals and seams, cable seals, piping components directly affixed to the tank including but not limited to valves, flanges, connectors etc. shall be inspected and monitored at least once every quarter by the operator using portable hydrocarbon detection instrument in accordance with EPA Method 21. If a component type found to leak during the quarterly inspection, then conduct monthly inspections of that component type for two consecutive months. If a component type is found to have no leak after two consecutive months, then revert to quarterly inspections. [District Rule 2201] Federally Enforceable Through Title V Permit
8. All records shall be retained for a minimum of five years, and shall be made available for District inspection upon request. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-174-1

EXPIRATION DATE: 02/28/2018

SECTION: SW 23 **TOWNSHIP:** 27S **RANGE:** 23E

EQUIPMENT DESCRIPTION:

21,000 GALLON FIXED ROOF STOCK TANK VENTED TO VAPOR CONTROL SYSTEM LISTED ON S-1737-172
(SEMITROPIC TANK BATTERY)

PERMIT UNIT REQUIREMENTS

1. Combined VOC emissions rate from the components associated with the tank in gas, light liquid and light crude oil service shall not exceed 0.2 pounds per day. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Any tank gauging or sampling device on this tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
3. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Leak-free shall be a condition without a gas leak or a liquid leak. Gas Leak shall be defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the EPA Method 21. Liquid leak is shall be defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Permittee shall maintain a log indicating component type, number of components, appropriate emission factors from CAPCOA 's document "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities" Table IV-2c (Feb 1999) - Screening Range Emissions Factors, and resultant emissions to demonstrate on-going compliance with the daily emission limit. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Hatch, tank seals and seams, cable seals, piping components directly affixed to the tank including but not limited to valves, flanges, connectors etc. shall be inspected and monitored at least once every quarter by the operator using portable hydrocarbon detection instrument in accordance with EPA Method 21. If a component type found to leak during the quarterly inspection, then conduct monthly inspections of that component type for two consecutive months. If a component type is found to have no leak after two consecutive months, then revert to quarterly inspections. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall keep records of the dates on which components are inspected and monitored, and number of components inspected corresponding to each component type. For leaking components, the operator shall immediately affix a tag and maintain records of liquid leak and gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
8. All records shall be retained for a minimum of five years, and shall be made available for District inspection upon request. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-173-1

EXPIRATION DATE: 02/28/2018

SECTION: SW 23 **TOWNSHIP:** 27S **RANGE:** 23E

EQUIPMENT DESCRIPTION:

21,000 GALLON FIXED ROOF STOCK TANK VENTED TO VAPOR CONTROL SYSTEM LISTED ON S-1737-172
(SEMITROPIC TANK BATTERY)

PERMIT UNIT REQUIREMENTS

1. Combined VOC emissions rate from the components associated with the tank in gas, light liquid and light crude oil service shall not exceed 0.2 pounds per day. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Any tank gauging or sampling device on this tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
3. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Leak-free shall be a condition without a gas leak or a liquid leak. Gas Leak shall be defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the EPA Method 21. Liquid leak is shall be defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
5. Permittee shall maintain a log indicating component type, number of components, appropriate emission factors from CAPCOA 's document "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities" Table IV-2c (Feb 1999) - Screening Range Emissions Factors, and resultant emissions to demonstrate on-going compliance with the daily emission limit. [District Rule 2201] Federally Enforceable Through Title V Permit
6. Hatch, tank seals and seams, cable seals, piping components directly affixed to the tank including but not limited to valves, flanges, connectors etc. shall be inspected and monitored at least once every quarter by the operator using portable hydrocarbon detection instrument in accordance with EPA Method 21. If a component type found to leak during the quarterly inspection, then conduct monthly inspections of that component type for two consecutive months. If a component type is found to have no leak after two consecutive months, then revert to quarterly inspections. [District Rule 2201] Federally Enforceable Through Title V Permit
7. The operator shall keep records of the dates on which components are inspected and monitored, and number of components inspected corresponding to each component type. For leaking components, the operator shall immediately affix a tag and maintain records of liquid leak and gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
8. All records shall be retained for a minimum of five years, and shall be made available for District inspection upon request. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-172-8

EXPIRATION DATE: 02/28/2018

SECTION: SW 23 **TOWNSHIP:** 27S **RANGE:** 23E

EQUIPMENT DESCRIPTION:

12,600 GALLON CRUDE OIL WASH TANK WITH VAPOR CONTROL SYSTEM INCLUDING COMPRESSOR, SERVED BY FLARE AND HYDROGEN SULFIDE SCAVENGER SYSTEM LISTED ON S-1737-178, SHARED WITH S-1737-173, -174, -175, -176, AND -200 (SEMITROPIC TANK BATTERY)

PERMIT UNIT REQUIREMENTS

1. Combined VOC emissions rate from the components associated with the tank and the vapor recovery system in gas, light liquid and light crude oil service shall not exceed 0.4 pounds per day. [District Rule 2201] Federally Enforceable Through Title V Permit
2. Vapor recovery system shall be maintained in leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
3. The tank shall be equipped with a vapor recovery system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor recovery system shall be APCO-approved and maintained in gas-tight condition. The VOC control device shall be either of the following: a vapor return or condensation system that connects to a gas pipeline distribution system, or an approved VOC destruction device that reduces the inlet VOC emissions by at least 95% by weight as determined by the test method specified in Section 6.4.6. [District Rule 4623] Federally Enforceable Through Title V Permit
4. Any tank gauging or sampling device on this tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rule 4623] Federally Enforceable Through Title V Permit
5. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rule 4623] Federally Enforceable Through Title V Permit
6. Leak-free shall be a condition without a gas leak or a liquid leak. Gas Leak shall be defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the EPA Method 21. Liquid leak is shall be defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rule 4623] Federally Enforceable Through Title V Permit
7. Permittee shall maintain a log indicating component type, number of components, appropriate emission factors from CAPCOA 's document "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities" Table IV-2c (Feb 1999) - Screening Range Emissions Factors, and resultant emissions to demonstrate on-going compliance with the daily emission limit. [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: CALIFORNIA RESOURCES PRODUCTION CORP

Location: LIGHT OIL CENTRAL, KERN COUNTY, CA

S-1737-172-8 Oct 5 2018 11:53AM -- OROZCOA

8. Hatch, tank seals and seams, cable seals, piping components directly affixed to the tank, components for vapor recovery system including but not limited to valves, flanges, connectors etc. shall be inspected and monitored at least once every quarter by the operator using portable hydrocarbon detection instrument in accordance with EPA Method 21. If a component type found to leak during the quarterly inspection, then conduct monthly inspections of that component type for two consecutive months. If a component type is found to have no leak after two consecutive months, then revert to quarterly inspections. [District Rule 2201] Federally Enforceable Through Title V Permit
9. The operator shall keep records of the dates on which components are inspected and monitored, and number of components inspected corresponding to each component type. For leaking components, the operator shall immediately affix a tag and maintain records of liquid leak and gas leak detection readings, date/time leak was discovered, and date/time the component was repaired to a leak-free condition. [District Rule 2201] Federally Enforceable Through Title V Permit
10. All records shall be retained for a minimum of five years, and shall be made available for District inspection upon request. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-171-2

EXPIRATION DATE: 02/28/2018

SECTION: SE 36 **TOWNSHIP:** 26S **RANGE:** 24E

EQUIPMENT DESCRIPTION:

21,000 GALLON FIXED ROOF CRUDE OIL GAUGE STORAGE TANK SERVED BY VAPOR RECOVERY SYSTEM
SHARED WITH S-1737-168

PERMIT UNIT REQUIREMENTS

1. The API gravity of any organic liquid stored or processed in this tank shall be less than 30ø. [District Rule 2201] Federally Enforceable Through Title V Permit
2. VOC fugitive emissions from the components in gas service on tank (if permit includes the vapor control system Insert: and tank vapor collection system) shall not exceed 0.1 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The tank shall be vented to a vapor control system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor control system shall be APCO-approved and maintained in leak-free condition. Vapors shall be discharged to approved control devices having a destruction efficiency of at least 99% by weight. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
4. Permittee shall maintain accurate component count for tank according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors < 10,000 ppmv. Permittee shall update such records when new components are approved and installed. [District Rule 2201] Federally Enforceable Through Title V Permit
5. All piping, valves, and fittings shall be constructed and maintained in a Leak-Free condition. [District Rules 2201 and 4623, 5.6.3] Federally Enforceable Through Title V Permit
6. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated to methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate more than 3 drops per minute. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
7. Any tank gauging or sampling device on a tank vented to the vapor control system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
8. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
9. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

Facility Name: CALIFORNIA RESOURCES PRODUCTION CORP

Location: LIGHT OIL CENTRAL, KERN COUNTY, CA

S-1737-171-2 : Oct 5 2018 11:53AM -- OROZCOA

10. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
11. The permittee shall keep accurate records of each organic liquid stored in the tank, including its type and API gravity. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-170-2

EXPIRATION DATE: 02/28/2018

SECTION: SE 36 **TOWNSHIP:** 26S **RANGE:** 24E

EQUIPMENT DESCRIPTION:

21,000 GALLON FIXED ROOF CRUDE OIL GAUGE STORAGE TANK SERVED BY VAPOR RECOVERY SYSTEM
SHARED WITH S-1737-168

PERMIT UNIT REQUIREMENTS

1. The API gravity of any organic liquid stored or processed in this tank shall be less than 30ø. [District Rule 2201] Federally Enforceable Through Title V Permit
2. VOC fugitive emissions from the components in gas service on tank (if permit includes the vapor control system Insert: and tank vapor collection system) shall not exceed 0.1 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The tank shall be vented to a vapor control system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor control system shall be APCO-approved and maintained in leak-free condition. Vapors shall be discharged to approved control devices having a destruction efficiency of at least 99% by weight. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
4. Permittee shall maintain accurate component count for tank according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors < 10,000 ppmv. Permittee shall update such records when new components are approved and installed. [District Rule 2201] Federally Enforceable Through Title V Permit
5. All piping, valves, and fittings shall be constructed and maintained in a Leak-Free condition. [District Rules 2201 and 4623, 5.6.3] Federally Enforceable Through Title V Permit
6. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated to methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate more than 3 drops per minute. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
7. Any tank gauging or sampling device on a tank vented to the vapor control system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
8. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
9. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
11. The permittee shall keep accurate records of each organic liquid stored in the tank, including its type and API gravity. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-169-2

EXPIRATION DATE: 02/28/2018

SECTION: E36 **TOWNSHIP:** **RANGE:**

EQUIPMENT DESCRIPTION:

126,000 GALLON FIXED ROOF CRUDE OIL GAUGE STORAGE TANK SERVED BY VAPOR RECOVERY SYSTEM
SHARED WITH S-1737-168

PERMIT UNIT REQUIREMENTS

1. The API gravity of any organic liquid stored or processed in this tank shall be less than 30ø. [District Rule 2201] Federally Enforceable Through Title V Permit
2. VOC fugitive emissions from the components in gas service on tank (if permit includes the vapor control system Insert: and tank vapor collection system) shall not exceed 0.1 lb/day. [District Rule 2201] Federally Enforceable Through Title V Permit
3. The tank shall be vented to a vapor control system consisting of a closed vent system that collects all VOCs from the storage tank, and a VOC control device. The vapor control system shall be APCO-approved and maintained in leak-free condition. Vapors shall be discharged to approved control devices having a destruction efficiency of at least 99% by weight. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
4. Permittee shall maintain accurate component count for tank according to CAPCOA's "California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities," Table IV-2c (Feb 1999), Screening Value Range emission factors < 10,000 ppmv. Permittee shall update such records when new components are approved and installed. [District Rule 2201] Federally Enforceable Through Title V Permit
5. All piping, valves, and fittings shall be constructed and maintained in a Leak-Free condition. [District Rules 2201 and 4623, 5.6.3] Federally Enforceable Through Title V Permit
6. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated to methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate more than 3 drops per minute. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
7. Any tank gauging or sampling device on a tank vented to the vapor control system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
8. All piping, fittings, and valves on this tank shall be inspected annually by the facility operator in accordance with EPA Method 21, with the instrument calibrated with methane, to ensure compliance with the leaking provisions of this permit. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
9. Any component found to be leaking on two consecutive annual inspections is in violation of the District Rule 4623, even if it is under the voluntary inspection and maintenance program. [District Rule 4623] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

10. Operator shall maintain an inspection log containing the following 1) Type of component leaking; 2) Date and time of leak detection, and method of detection; 3) Date and time of leak repair, and emission level of recheck after leak is repaired; 4) Method used to minimize the leak to lowest possible level within 8 hours after detection. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
11. The permittee shall keep accurate records of each organic liquid stored in the tank, including its type and API gravity. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit
12. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rule 1070] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-168-11

EXPIRATION DATE: 02/28/2018

SECTION: SE36 **TOWNSHIP:** 26S **RANGE:** 24E

EQUIPMENT DESCRIPTION:

126,000 GALLON FIXED ROOF CRUDE OIL GAUGE STORAGE TANK, 3-PHASE SEPARATOR, TWO HEATER TREATERS (EACH WITH BURNER(S) RATED AT 5 MMBTU/HR OR LESS), TWO 2-PHASE SEPARATORS SERVED BY VAPOR RECOVERY SYSTEM SHARED WITH TANKS S-1737-169, '-170, '-171 AND '-193. VAPOR RECOVERY SYSTEM CONSISTS OF COMPRESSOR AND ASSOCIATED PIPING DISCHARGING TO FLARE S-1737-180-0 AND/OR SALES GAS LINE

PERMIT UNIT REQUIREMENTS

1. Gases from the tanks, heater treaters, and all separators shall be flared or routed to a sales pipeline. [District Rule 2201] Federally Enforceable Through Title V Permit
2. The API gravity of any organic liquid stored or processed in this tank shall be less than 30ø. [District Rules 2201 and 4409] Federally Enforceable Through Title V Permit
3. Fugitive VOC emissions from all components associated with this tank shall not exceed 0.14 lb/day as calculated using CAPCOA California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities, Table IV-2c, Oil and Gas Production Screening Value Ranges Emission Factors (Feb 1999). [District Rule 2201] Federally Enforceable Through Title V Permit
4. The storage tank shall be fully enclosed and shall be maintained in a leak-free condition. The storage tank shall be connected to an APCO-approved vapor recovery system consisting of a closed system that collects all VOCs from the storage tank(s) and a VOC control device. The vapor recovery system shall be maintained in leak-free condition. Collected vapor shall be directed to a gas pipeline distribution system or to an approved control devices having a destruction efficiency of at least 99% by weight as determined by the test method specified in Section 6.4.6 of District Rule 4623. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
5. All piping, valves, and fittings shall be constructed and maintained in a leak-free condition. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
6. A leak-free condition is defined as a condition without a gas leak or a liquid leak. A gas leak is defined as a reading in excess of 10,000 parts per million by volume (ppmv), as methane, above background on a portable hydrocarbon detection instrument that is calibrated with methane in accordance with the procedures specified in EPA Test Method 21. A liquid leak is defined as the dripping of organic liquid at a rate of more than 3 drops per minute. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
7. Any tank gauging or sampling device on a tank vented to the vapor recovery system shall be equipped with a leak-free cover which shall be closed at all times except during gauging or sampling. [District Rules 2201 and 4623] Federally Enforceable Through Title V Permit
8. Fugitive VOC emissions from all components associated with the vapor recovery system (shared with S-1737-169, '-170, '-171 and '-193) including vapor collection piping, vapor compressor, heater treaters, flare gas line, separator vessels and scrubbers shall not exceed 0.98 lb/day as calculated using CAPCOA California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities, Table IV-2c, Oil and Gas Production Screening Value Ranges Emission Factors (Feb 1999). [District Rule 2201] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

9. Permittee shall maintain accurate fugitive component count and resultant emissions calculated using CAPCOA California Implementation Guidelines for Estimating Mass Emissions of Fugitive Hydrocarbon Leaks at Petroleum Facilities, Table IV-2c, Oil and Gas Production Screening Value Ranges Emission Factors (Feb 1999). These records shall be retained on-site for a period of at least five years, and shall be made available for District inspection upon request. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Heater treaters shall only be fired on PUC-quality natural gas or LPG. [District Rule 2201] Federally Enforceable Through Title V Permit
11. The permittee shall tune the unit (two heaters) at least twice per calendar year, (from four to eight months apart) using a qualified technician in accordance with the procedure described in Rule 4304. If the unit does not operate throughout a continuous six-month period within a calendar year, only one tune-up is required for a calendar year. No tune-up is required if the unit is not operated during that calendar year; and this unit may be test fired to verify availability of the unit for its intended use, but once the test firing is complete the unit shall be shutdown. [District Rule 4307] Federally Enforceable Through Title V Permit
12. The permittee shall keep accurate records of each organic liquid stored in the tank, including its type and API gravity. [District Rules 1070, 2201 and 4409] Federally Enforceable Through Title V Permit
13. On and after July 1, 2015, the heater treaters in this unit shall comply with the applicable emission requirements of Section 5.1, Table 1 in District Rule 4307. [District Rule 4307] Federally Enforceable Through Title V Permit
14. All records shall be retained for a period of at least 5 years and shall be made available for District inspection upon request. [District Rules 1070 and 4623] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

San Joaquin Valley Air Pollution Control District

PERMIT UNIT: S-1737-167-5

EXPIRATION DATE: 02/28/2018

SECTION: NE03 **TOWNSHIP:** 28S **RANGE:** 25E

EQUIPMENT DESCRIPTION:

14.6 MMBTU/HR PRODUCED GAS FLARE WITH COANDA EFFECT TIP AND PILOT AUTHORIZED TO BE USED AT VARIOUS UNSPECIFIED LOCATIONS WITHIN THE LIGHT OIL CENTRAL STATIONARY SOURCE

PERMIT UNIT REQUIREMENTS

1. Unit shall not be located within 1000 feet of any K-12 school. [CH&SC 42301.6]
2. Flare shall not be used within 500 feet of any business or residence. [District Rule 4102]
3. This flare is approved for use in well testing, tank and well vent control, and equipment shutdown, emergencies and other situation requiring a safety flare. [District Rule 2201] Federally Enforceable Through Title V Permit
4. Permittee shall notify the District Compliance Division of each location at which the unit is located in excess of 24 hours. Such notification shall be made no later than 48 hours after starting operation at the location. [District Rule 1070]
5. Particulate matter emissions shall not exceed 0.1 grains/dscf in concentration. [District Rule 4201, 3.1] Federally Enforceable Through Title V Permit
6. Flare shall operate in a smokeless manner (no greater than 5% opacity) except for three minutes in any one hour. [District Rule 2201] Federally Enforceable Through Title V Permit
7. Flare shall be equipped with volumetric flow rate indicator. [District Rule 2201] Federally Enforceable Through Title V Permit
8. Gas flow rate to flare (not including pilot gas) shall not exceed 350,000 cubic feet per day. [District Rule 2201] Federally Enforceable Through Title V Permit
9. Emission rates from this unit shall not exceed any of the following limits: NO_x (as NO₂) - 0.068 lb/MMBtu; VOC (as methane) - 0.063 lb/MMBtu; CO - 0.37 lb/MMBtu or PM₁₀ - 0.008 lb/MMBtu. [District Rule 2201] Federally Enforceable Through Title V Permit
10. Gas sulfur content shall not exceed 1.0 gr/100 scf. [District Rules 2201 and 4801] Federally Enforceable Through Title V Permit
11. Gas shall be tested quarterly for sulfur content. Upon transfer of location or change in the method of operation of the flare (excluding emergencies), gas shall be tested weekly for sulfur content. If compliance with the fuel sulfur content limit has been demonstrated for 8 consecutive weeks then the fuel testing frequency shall be quarterly. If a quarterly fuel content source test fails to show compliance, weekly testing shall resume. [District Rule 2201] Federally Enforceable Through Title V Permit
12. The sulfur content of the gas being flared shall be determined using ASTM D1072, D3031, D4084, D3246, or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 1081] Federally Enforceable Through Title V Permit

PERMIT UNIT REQUIREMENTS CONTINUE ON NEXT PAGE

These terms and conditions are part of the Facility-wide Permit to Operate.

13. If the unit is fired on noncertified gaseous fuel and compliance with SOx emission limits is achieved through fuel sulfur content limitations, then the sulfur content of the gaseous fuel being fired in the unit shall be determined using ASTM D 1072, D 3031, D 4084, D 3246 or grab sample analysis by GC-FPD/TCD performed in the laboratory. [District Rule 2201] Federally Enforceable Through Title V Permit
14. If fuel analysis is used to demonstrate compliance with conditions of this permit, the fuel higher heating value for each fuel shall be certified by a third party fuel supplier or determined by: ASTM D 1826 or D 1945 in conjunction with ASTM D 3588 for gaseous fuels. [District Rule 2201] Federally Enforceable Through Title V Permit
15. A trained observer, as defined in EPA Method 22, shall check visible emissions at least once every two weeks for a period of 15 minutes. If visible emissions are detected at any time during this period, the observation period shall be extended to two hours. A record containing the results of these observations shall be maintained, which also includes company name, process unit, observer's name and affiliation, date, estimated wind speed and direction, sky condition, and the observer's location relative to the source and sun. [District Rules 2080 and 4101] Federally Enforceable Through Title V Permit
16. The flame shall be present at all times when combustible gases are vented through the flare. [District Rule 4311, 5.2] Federally Enforceable Through Title V Permit
17. The outlet shall be equipped with an automatic ignition system, or, shall operate with a pilot flame present at all times when combustible gases are vented through the flare, except during purge periods for automatic-ignition equipped flares. [District Rule 4311, 5.3] Federally Enforceable Through Title V Permit
18. Permittee shall obtain an ATC to modify any permit unit which authorizes this flare as a control device prior to this flare operating as a control device for that permit unit. [District Rule 2201] Federally Enforceable Through Title V Permit
19. Except for flares equipped with a flow-sensing ignition system, a heat sensing device such as a thermocouple, ultraviolet beam sensor, infrared sensor, or an equivalent device, capable of continuously detecting at least one pilot flame or the flare flame is present, shall be installed and operated. [District Rule 4311, 5.4] Federally Enforceable Through Title V Permit
20. Flares that use flow-sensing automatic ignition systems and which do not use a continuous flame pilot shall use purge gas for purging. [District Rule 4311, 5.5] Federally Enforceable Through Title V Permit
21. The flare shall be inspected every two weeks while in operation for visible emissions. If visible emissions are observed, corrective action shall be taken. If visible emissions continue, an EPA method 9 test shall be conducted within 72 hours. [District Rule 2201] Federally Enforceable Through Title V Permit
22. The flare shall be operated according to the manufacturer's specifications, a copy of which shall be maintained on site. [District Rule 2080] Federally Enforceable Through Title V Permit
23. Permittee shall maintain accurate daily records of volume, type, higher heating value, and sulfur content and of gas flared [District Rule 2201 & 1070] Federally Enforceable Through Title V Permit
24. Permittee shall maintain accurate records of location and duration of operation at each stationary source. [District Rule 2201 & 4409] Federally Enforceable Through Title V Permit
25. All records shall be maintained and retained on-site for a minimum of five (5) years, and shall be made available for District inspection upon request. [District Rule 2201 & 4409] Federally Enforceable Through Title V Permit
26. Permittee shall maintain records of daily amount of total gas flared. Records shall be kept for a minimum of 5 years and shall be made readily available for District inspection upon request. [District Rules 1070 and 2201] Federally Enforceable Through Title V Permit

These terms and conditions are part of the Facility-wide Permit to Operate.

ATTACHMENT C

Detailed Summary List of Facility Permits

Detailed Facility Report
For Facility=1737 and excluding Deleted Permits
Sorted by Facility Name and Permit Number10/5/18
1:35 pm

CALIFORNIA RESOURCES PRODUCTION CORP		FAC #	S 1737	TYPE:	TitleV	EXPIRE ON:
LIGHT OIL CENTRAL		STATUS:	A	TOXIC ID:	50283	AREA:
KERN COUNTY, CA		TELEPHONE:				INSP. DATE:

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-1737-110-5	42000 gallons	3020-05 C	1	157.00	157.00	A	42,000 GALLON FIXED ROOF PETROLEUM STORAGE TANK #12177 (TEJON)
S-1737-111-5	42000 gallons	3020-05 C	1	157.00	157.00	A	42,000 GALLON FIXED ROOF PETROLEUM STORAGE TANK #12176 (TEJON)
S-1737-112-6	42000 gallons	3020-05 C	1	157.00	157.00	A	42,000 GALLON FIXED ROOF PETROLEUM STORAGE TANK #1172
S-1737-113-6	42000 gallons	3020-05 C	1	157.00	157.00	A	42,000 GALLON FIXED ROOF PETROLEUM STORAGE TANK #1171 (TEJON)
S-1737-115-6	31500 gallons	3020-05 C	1	157.00	157.00	A	31,500 GALLON FIXED ROOF PETROLEUM STORAGE TANK (TEJON)
S-1737-120-5	42000 gallons	3020-05 C	1	157.00	157.00	A	42,000 GALLON FIXED ROOF PETROLEUM STORAGE TANK (TEJON)
S-1737-137-2	8820 gallons	3020-05 B	1	108.00	108.00	A	8,820 GALLON FIXED ROOF PETROLEUM SHIPPING TANK WITH PV VENT (ID: TULARE 34-1 SHIPPING TANK #1)
S-1737-138-2	8820 gallons	3020-05 B	1	108.00	108.00	A	8,820 GALLON FIXED ROOF PETROLEUM SHIPPING TANK WITH PV VENT (ID: TULARE 34-1 SHIPPING TANK #2)
S-1737-139-2	8820 gallons	3020-05 B	1	108.00	108.00	A	8,820 GALLON FIXED ROOF PETROLEUM SHIPPING TANK WITH PV VENT (ID: TULARE 34-1 SHIPPING TANK #3)
S-1737-140-2	8820 gallons	3020-05 B	1	108.00	108.00	A	8,820 GALLON FIXED ROOF PETROLEUM SHIPPING TANK WITH PV VENT (ID: TULARE 34-2 SHIPPING TANK #1)
S-1737-141-2	8820 gallons	3020-05 B	1	108.00	108.00	A	8,820 GALLON FIXED ROOF PETROLEUM SHIPPING TANK WITH PV VENT (ID: TULARE 34-2 SHIPPING TANK #2)
S-1737-142-2	8820 gallons	3020-05 B	1	108.00	108.00	A	8,820 GALLON FIXED ROOF CRUDE OIL STORAGE TANK WITH PV VENT (TANK ID WW#2)
S-1737-143-2	8820 gallons	3020-05 B	1	108.00	108.00	A	8,820 GALLON SHIPPING TANK (TULARE 34-3 SHIPPING TANK #4)
S-1737-144-2	8820 gallons	3020-05 B	1	108.00	108.00	A	8,820 GALLON SHIPPING TANK (TULARE 34-3 SHIPPING TANK #5)
S-1737-145-2	8820 gallons	3020-05 B	1	108.00	108.00	A	8,820 GALLON FIXED ROOF CRUDE OIL STORAGE TANK WITH PV VENT (WW#3)
S-1737-146-2	4.2 MMbtu/hr	3020-02 F	1	698.00	698.00	A	4.2 MMBTU/HR COANDA EFFECT SMOKELESS FLARE INCINERATING PRODUCED GAS FROM PRIMARY PRODUCTION WELL (TULARE 3-1, NORTH SHAFTER FIELD)
S-1737-148-2	8820 gallons	3020-05 B	1	108.00	108.00	A	8,820 GALLON SHIPPING TANK (TULARE 3-1 SHIPPING TANK #2)
S-1737-155-2	8820 gallons	3020-05 B	1	108.00	108.00	A	8,820 GALLON (210 BBL) FIXED ROOF PRODUCED WATER STORAGE TANK WITH PRESSURE/VACUUM RELIEF VALVE AND VENT LINE TO OIL SHIPPING TANKS (TULARE 34-1, NORTH SHAFTER FIELD)

Detailed Facility Report

For Facility=1737 and excluding Deleted Permits

Sorted by Facility Name and Permit Number

10/5/18
1:35 pm

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-1737-157-6	41.7 MMBtu/hr	3020-02 H	1	1,183.00	1,183.00	A	63,000 GALLON FIXED ROOF WASH TANK (T-01) WITH VAPOR CONTROL SHARED WITH S-1737-158, '-159, '-160, '-161, AND OPTIONAL PORTABLE TANKS S-1737-181, '-182, '-183, AND/OR '-184 VENTING TO GAS SALES LINE, 41.7 MMBTU/HR COANDA TIP FLARE, FLARES S-1737-167 AND '-180 AND/OR 2.0 MMBTU/HR PRODUCTION HEATER (S-1737-160)
S-1737-158-2	42000 gallons	3020-05 C	1	157.00	157.00	A	42,000 GALLON (1,000 BBL) SHIPPING TANK (T-02) SERVED BY SHARED VAPOR CONTROL SYSTEM LISTED ON S-1737-157
S-1737-159-2	42000 gallons	3020-05 C	1	157.00	157.00	A	42,000 GALLON (1,000 BBL) FIXED ROOF WASH TANK (T-03) SERVED BY SHARED VAPOR CONTROL SYSTEM LISTED ON S-1737-157
S-1737-160-3	2.0 MMBtu/hr	3020-02 E	1	473.00	473.00	A	2.0 MMBTU/HR VAPOR RECOVERY GAS FIRED PRODUCTION HEATER
S-1737-161-2	42000 gallons	3020-05 C	1	157.00	157.00	A	42,000 GALLON (1,000 BBL) FIXED ROOF OIL SHIPPING TANK SERVED BY SHARED VAPOR CONTROL SYSTEM LISTED ON S-1737-157
S-1737-162-2	42000 gallons	3020-05 C	1	157.00	157.00	A	42,000 GALLON (1,000 BBL) FIXED ROOF OIL SHIPPING TANK SERVED BY SHARED VAPOR CONTROL SYSTEM LISTED ON S-1737-157
S-1737-167-5	14.6 MMBtu/hr	3020-02 G	1	936.00	936.00	A	14.6 MMBTU/HR PRODUCED GAS FLARE WITH COANDA EFFECT TIP AND PILOT AUTHORIZED TO BE USED AT VARIOUS UNSPECIFIED LOCATIONS WITHIN THE LIGHT OIL CENTRAL STATIONARY SOURCE
S-1737-168-11	126000 gallons	3020-05 E	1	283.00	283.00	A	126,000 GALLON FIXED ROOF CRUDE OIL GAUGE STORAGE TANK, 3-PHASE SEPARATOR, TWO HEATER TREATERS (EACH WITH BURNER(S) RATED AT 5 MMBTU/HR OR LESS), TWO 2-PHASE SEPARATORS SERVED BY VAPOR RECOVERY SYSTEM SHARED WITH TANKS S-1737-169, '-170, '-171 AND '-193. VAPOR RECOVERY SYSTEM CONSISTS OF COMPRESSOR AND ASSOCIATED PIPING DISCHARGING TO FLARE S-1737-180-0 AND/OR SALES GAS LINE
S-1737-169-2	126000 gallons	3020-05 E	1	283.00	283.00	A	126,000 GALLON FIXED ROOF CRUDE OIL GAUGE STORAGE TANK SERVED BY VAPOR RECOVERY SYSTEM SHARED WITH S-1737-168
S-1737-170-2	21000 gallons	3020-05 C	1	157.00	157.00	A	21,000 GALLON FIXED ROOF CRUDE OIL GAUGE STORAGE TANK SERVED BY VAPOR RECOVERY SYSTEM SHARED WITH S-1737-168
S-1737-171-2	21000 gallons	3020-05 C	1	157.00	157.00	A	21,000 GALLON FIXED ROOF CRUDE OIL GAUGE STORAGE TANK SERVED BY VAPOR RECOVERY SYSTEM SHARED WITH S-1737-168
S-1737-172-8	12600 gallons	3020-05 B	1	108.00	108.00	A	12,600 GALLON CRUDE OIL WASH TANK WITH VAPOR CONTROL SYSTEM INCLUDING COMPRESSOR, SERVED BY FLARE AND HYDROGEN SULFIDE SCAVENGER SYSTEM LISTED ON S-1737-178, SHARED WITH S-1737-173, '-174, '-175, '-176, AND '-200 (SEMITROPIC TANK BATTERY)
S-1737-173-1	21000 gallons	3020-05 C	1	157.00	157.00	A	21,000 GALLON FIXED ROOF STOCK TANK VENTED TO VAPOR CONTROL SYSTEM LISTED ON S-1737-172 (SEMITROPIC TANK BATTERY)
S-1737-174-1	21000 gallons	3020-05 C	1	157.00	157.00	A	21,000 GALLON FIXED ROOF STOCK TANK VENTED TO VAPOR CONTROL SYSTEM LISTED ON S-1737-172 (SEMITROPIC TANK BATTERY)

Detailed Facility Report

For Facility=1737 and excluding Deleted Permits

Sorted by Facility Name and Permit Number

PERMIT NUMBER	FEE DESCRIPTION	FEE RULE	QTY	FEE AMOUNT	FEE TOTAL	PERMIT STATUS	EQUIPMENT DESCRIPTION
S-1737-175-1	21000 gallons	3020-05 C	1	157.00	157.00	A	21,000 GALLON FIXED ROOF SKIM TANK VENTED TO VAPOR CONTROL SYSTEM LISTED ON S-1737-172 (SEMITROPIC TANK BATTERY)
S-1737-176-1	4200 gallons	3020-05 A	1	87.00	87.00	A	4200 GALLON FIXED ROOF SLOP TANK VENTED TO VAPOR CONTROL SYSTEM LISTED ON S-1737-172 (SEMITROPIC TANK BATTERY)
S-1737-177-1	0.5 MMBtu/hr	3020-02 C	1	228.00	228.00	A	0.5 MMBTU/HR FIELD GAS-FIRED HEATER (SEMITROPIC TANK BATTERY)
S-1737-178-1	5 MMBtu/hr	3020-02 G	1	936.00	936.00	A	25 FOOT TALL MACTRONIC AIR-ASSISTED PROCESS GAS FLARE SERVING VAPOR CONTROL SYSTEM LISTED ON S-1737-172, WITH 2 INCH DIAMETER FLARE GAS LINE, 6 INCH DIAMETER FLARE STACK, ELECTRONIC IGNITOR, AND FLAME ARRESTOR SERVED BY 20 BBL GAS-LIQUID SEPARATOR; 3 EACH, 3 BBL KNOCKOUT VESSELS; AND AN H2S SCAVENGER
S-1737-180-2	49 MMBtu	3020-02 H	1	1,183.00	1,183.00	A	49 MMBTU/HR FLARE APPROVED FOR USE IN WELL TESTING, TANK AND WELL VENT CONTROL, EQUIPMENT SHUTDOWN, EMERGENCIES AND OTHER SITUATIONS REQUIRING A SAFETY FLARE AT VARIOUS UNSPECIFIED LOCATIONS
S-1737-185-0	21,000 gallons	3020-05 C	1	157.00	157.00	A	500 BBL CRUDE OIL STORAGE TANK CONNECTED TO THE VAPOR CONTROL SYSTEM LISTED ON PERMIT S-1737-168
S-1737-186-0	21,000 gallons	3020-05 C	1	157.00	157.00	A	500 BBL CRUDE OIL STORAGE TANK CONNECTED TO THE VAPOR CONTROL SYSTEM LISTED ON PERMIT S-1737-168
S-1737-193-1	3000 BBL	3020-05 E	1	283.00	283.00	A	3,000 BBL FIXED ROOF CRUDE OIL TANK VENTED TO VAPOR CONTROL SYSTEM LISTED ON TANK S-1737-168
S-1737-200-1	21,000 gallons	3020-05 C	1	157.00	157.00	A	500 BBL FIXED ROOF CRUDE OIL TANK VENTED TO VAPOR CONTROL SYSTEM LISTED ON TANK S-1737-172

Number of Facilities Reported: 1